MarkLogic Server

Connector For SharePoint®
Administrator's Guide

Release 1.1
January, 2011

Last Revised: 1.1-2, January, 2013

Copyright © 2013 MarkLogic Corporation. All rights reserved.

Table of Contents

Connector For SharePoint® Administrator's Guide

1.0 Overview and Requirements 4
- 1.1 Overview of the MarkLogic Connector for SharePoint 4
  - 1.1.1 Library Mirroring 4
  - 1.1.2 Workflow Actions 5
  - 1.1.3 Create Applications Using the Content in MarkLogic Server 5
  - 1.1.4 Use SharePoint Library Services to Maintain MarkLogic Server Content 5
- 1.2 System Requirements 5

2.0 Installing the MarkLogic Connector for SharePoint 6
- 2.1 MarkLogic Connector for SharePoint Installation Package 6
- 2.2 Installing the Connector in SharePoint 6
- 2.3 Installing the mlcadm.exe Utility 7
- 2.4 Installing and Configuring MarkLogic Server to Use the Connector 7
- 2.5 Configuring the MarkLogic Connector for SharePoint 9
  - 2.5.1 Configuring the MarkLogic Connector for Windows SharePoint Services 3.0 9
  - 2.5.2 Configuring the MarkLogic Connector for SharePoint Foundation 2010 11
- 2.6 Uninstalling the MarkLogic Connector for SharePoint from Microsoft SharePoint 12
  - 2.6.1 Uninstalling the MarkLogic Connector for Windows SharePoint Services 3.0 13
  - 2.6.2 Uninstalling the MarkLogic Connector for SharePoint Foundation 2010 14

3.0 mlcadm Command Line Utility 15
- 3.1 About the mlcadm Utility 15
- 3.2 mlcadm Command Line Usage 15
- 3.3 Sample mlcadm Commands 16
  - 3.3.1 Test the Connection 16
  - 3.3.2 Check the Status of the Connection 16
  - 3.3.3 Upload a Document From SharePoint to MarkLogic Server 16

4.0 Workflows and SharePoint 17
- 4.1 SharePoint Workflow Developer's Kit 17
- 4.2 Using Activities With Microsoft Visual Studio 17
- 4.3 Running SharePoint Workflows Without Installing the Connector 18

5.0 Troubleshooting the MarkLogic Connector for SharePoint 19

5.1 Error Log for the MarkLogic Connector for SharePoint 19
5.2 Logging Activity on the SharePoint Server 19
5.3 MarkLogic Server Trace Events for the MarkLogic Connector for SharePoint ...19
5.4 Increasing the Execution Timeout of an ASP.NET Request 20
5.5 Folders Restored from Recycle Bin 20

6.0 Technical Support 21

Combined Product Notices 22
COPYRIGHT 22
TRADEMARK NOTICE 34

1.0 Overview and Requirements

This chapter introduces the MarkLogic Connector for SharePoint® and lists the product requirements and supported platforms. It includes the following sections:

- Overview of the MarkLogic Connector for SharePoint
- System Requirements

1.1 Overview of the MarkLogic Connector for SharePoint

The MarkLogic Connector for SharePoint allows you to integrate Microsoft SharePoint with MarkLogic Server. You can use the MarkLogic Connector for SharePoint for the following:

- Library Mirroring
- Workflow Actions
- Create Applications Using the Content in MarkLogic Server
- Use SharePoint Library Services to Maintain MarkLogic Server Content

1.1.1 Library Mirroring

With library mirroring, you can transparently mirror content from SharePoint document libraries to a MarkLogic Server instance. The MarkLogic Connector for SharePoint listens for changes to major versions of documents and automatically propagates those changes to MarkLogic Server. With library mirroring, you can set it up initially and then, with no further intervention, your SharePoint library is mirrored to MarkLogic Server and any changes that occur in that library are automatically reflected in MarkLogic Server.

You can mirror an entire library or individual documents. If you mirror a library, all of the documents in the library, including all subdirectories and all documents in the subdirectories, are mirrored. If you mirror individual documents, then those documents are mirrored. Any SharePoint event that changes the document state or contents on a mirrored document will be forwarded to MarkLogic Server to determine if the document state or content should be updated in the MarkLogic Server database.

1.1.2 Workflow Actions

The MarkLogic Connector for SharePoint supports three workflow actions: copy, delete, and invoke. As part of a SharePoint workflow, you can copy a document to MarkLogic Server or delete a document from MarkLogic Server. For example, you can create a workflow with an approval process, and as a result of that approval process, the document can be uploaded to MarkLogic Server. The invoke action allows you to invoke an XQuery module on MarkLogic Server, allowing for completely custom behavior in your application.

1.1.3 Create Applications Using the Content in MarkLogic Server

Once the content is in MarkLogic Server, you can create applications that use the content using all of the powerful search and XQuery features of MarkLogic Server. Once the content is in MarkLogic Server, it is no different than any other content, so you can use it any way you choose.

1.1.4 Use SharePoint Library Services to Maintain MarkLogic Server Content

A common use of SharePoint and MarkLogic Server is to use the various SharePoint library services to manage content that ultimately is loaded into MarkLogic Server. The library services include check-in/check-out, versioning, and workflow.

1.2 System Requirements

The MarkLogic Connector for SharePoint has the following system requirements:

- For the MarkLogic Connector for SharePoint, Microsoft Windows SharePoint Services 2007 (version 3.0) or Windows SharePoint Foundation 2010, running under a Microsoft Windows platform supported by MarkLogic.
- For the instance of MarkLogic Server with which the MarkLogic Connector for SharePoint communicates, version 4.0-1 or later, on any supported platform, of MarkLogic Server. See the *Release Notes* and the *Installation Guide* in the MarkLogic Server documentation for details on the requirements for MarkLogic Server.

Additionally, administrative privileges for both SharePoint and MarkLogic Server are required.

2.0 Installing the MarkLogic Connector for SharePoint

This chapter describes how to install the MarkLogic Connector for SharePoint. The MarkLogic Connector for SharePoint installation procedure involves installing the connector in SharePoint and installing some XQuery modules in an instance of MarkLogic Server. The following sections are included:

- MarkLogic Connector for SharePoint Installation Package
- Installing the Connector in SharePoint
- Installing the mlcadm.exe Utility
- Installing and Configuring MarkLogic Server to Use the Connector
- Configuring the MarkLogic Connector for SharePoint
- Uninstalling the MarkLogic Connector for SharePoint from Microsoft SharePoint

2.1 MarkLogic Connector for SharePoint Installation Package

You can download the latest MarkLogic Connector for SharePoint installation package from developer.marklogic.com. The installation package is a zip file containing the following:

- XQuery files (in the `Modules` directory) to be installed on each instance of MarkLogic Server to which the MarkLogic Connector for SharePoint will communicate.
- MarkLogic Connector for SharePoint feature solution package (`.wsp` file in the `SharePoint` directory).
- SharePoint Developer's Kit assembly files (`.dll` files in the `SharePoint` directory).
- MarkLogic Connector for SharePoint command-line utility (`mlcadm.exe` file in the `SharePoint` directory).
- Sample SharePoint Workflows.

There are two main parts to the installation process: installing the MarkLogic Connector for SharePoint and copying the MarkLogic Server XQuery files to each instance of MarkLogic Server to which the connector will communicate. For information about system requirements, see "System Requirements" on page 5.

2.2 Installing the Connector in SharePoint

On the machine in which SharePoint is installed, perform the following steps. You need administrative privileges to SharePoint to perform these steps.

1. Unpack the `MarkLogicConnector.wsp` file from the `SharePoint` directory of MarkLogic Connector for SharePoint zip file and store it in a known disk location.

2. Verify you have SharePointSite Collection Administrator privilege. Without this you will not see the MarkLogic Connector menu when you are done. You can set the Site Collection Administrator in several places in SharePoint, including the following:

   - In the Central Administration tool > Application Management tab > Site Collection Administrators page.
   - In the top-level site in the Site Settings (Site Actions > Site Settings > Advanced permissions).

   For details, see your SharePoint documentation.

3. If a previous version of the MarkLogic Connector for SharePoint is installed in SharePoint, uninstall it as described in "Uninstalling the MarkLogic Connector for SharePoint from Microsoft SharePoint" on page 12.

4. Add the solution to SharePoint server. Open a command window as administrator (right click on Command Prompt and select Run as administrator). Assuming you have the SharePoint administration tool (`stsadm.exe`) on your search path, you can add the solution to SharePoint with the following command:

   ```
   C:\> stsadm -o addsolution -filename <path>\MarkLogicConnector.wsp
   ```

   where <*path*> is the path to the `MarkLogicConnector.wsp` file. The `stsadm` utility will respond with "operation completed successfully" after a successful installation.

2.3 Installing the mlcadm.exe Utility

The release includes a command-line MarkLogic Connector for SharePoint utility called `mlcadm.exe`, distributed in the `SharePoint` folder of the zip installation package. This utility is optional. If you plan on using it, copy the `mlcadm.exe` file to a directory on your search path. For details about using this utility, see "mlcadm Command Line Utility" on page 15.

2.4 Installing and Configuring MarkLogic Server to Use the Connector

Perform the following steps to install the XQuery files used by the MarkLogic Connector for SharePoint on MarkLogic Server. These steps should be repeated for each node in your MarkLogic Server cluster that communicates with the MarkLogic Connector for SharePoint. In order to install the XQuery modules on the machine in which MarkLogic Server is installed, you will need permissions to write to the directory in which MarkLogic Server is installed.

1. Make sure MarkLogic Server is installed. For details on installing MarkLogic Server, see the *Installation Guide* in the MarkLogic Server product documentation.

2. Install the MarkLogic Connector for SharePoint in your Microsoft SharePoint environment, as described in "Installing the Connector in SharePoint" on page 6.

3. Copy the SharePoint installation package to the machine(s) in which MarkLogic Server is installed and unzip it.

4. In your MarkLogic Server installation(s), create a directory named `SharePoint` under *`marklogic-dir`*`/Modules/MarkLogic`, where *marklogic-dir* is the directory in which MarkLogic Server is installed. For example, on Linux systems, enter commands similar to the following:

```
% cd /opt/MarkLogic/Modules/MarkLogic
% mkdir SharePoint
```

5. In your MarkLogic Server installation(s), copy the XQuery files from the MarkLogic Connector for SharePoint installation zip package into the `Modules/MarkLogic/SharePoint` directory in the MarkLogic Server installation directory. For example, on Linux systems, enter commands similar to the following (assuming the installation package is unzipped into the `/tmp` directory):

```
% cd /tmp/SharePointConnector-1.1-1/Modules
% cp *.xqy /opt/MarkLogic/Modules/MarkLogic/SharePoint
```

   The MarkLogic Connector for SharePoint XQuery modules should now be under the *`marklogic-dir`*`/Modules/MarkLogic/SharePoint` directory.

6. In the Admin Interface in your MarkLogic Server installation, create an XDBC Server. Requests from the MarkLogic Connector for SharePoint will use this XDBC Server, and will mirror SharePoint documents in the database specified in the XDBC Server configuration. The XDBC Server must have a root corresponding to the directory in which you copied the XQuery modules. If you copied them as described above, then the XDBC Server root must be `Modules/MarkLogic/SharePoint`. Set authentication to `basic`.
7. Note the hostname, port number for this XDBC Server, and the login credentials for MarkLogic Server, which you will need to access this XDBC Server from the MarkLogic Connector for SharePoint, as described in Configuring the MarkLogic Connector for SharePoint, Step 3.

   Note: If you have a cluster of several MarkLogic Server instances, you only need to create the XDBC Server in one of them (because it will be available to every node in the group in which it is created).

You can now connect to this XDBC Server from the MarkLogic Connector for SharePoint.

2.5 Configuring the MarkLogic Connector for SharePoint

Once you have installed the connector components in Microsoft SharePoint and in MarkLogic Server, you must configure the MarkLogic Connector for SharePoint to point to your MarkLogic Server XDBC Server.

MarkLogic Connector for SharePoint operates with Windows SharePoint Services 3.0 and SharePoint Foundation 2010. The configuration procedure is slightly different for each version. The following sections describe the configuration procedure for both versions of SharePoint:

- Configuring the MarkLogic Connector for Windows SharePoint Services 3.0
- Configuring the MarkLogic Connector for SharePoint Foundation 2010

2.5.1 Configuring the MarkLogic Connector for Windows SharePoint Services 3.0

To configure Windows SharePoint Services 3.0, perform the following steps.

1. Deploy the MarkLogic Connector for SharePoint solution from the SharePoint 3.0 Central Administration tool as follows:
   - Launch the SharePoint Central Administration tool (for example, Start Menu > All Programs > Administrative Tools > SharePoint 3.0 Central Administration).
   - Click the Operations tab.
   - Click Solution management in the Global Configuration section.
   - You should see `marklogicconnector.wsp` in the name column. Click this name.
   - On the Solution Properties page click Deploy Solution.
   - On the Deploy Solution page set Deploy When? to Now. Click OK to deploy the solution.

   The page should revert to the Solution Management page with the `marklogicconnector.wsp` Status set to Deployed.

2. Activate the feature as follows:
   - Log in to the SharePoint Team Site. Typically, this is running on port 80 of the machine in which SharePoint is running (for example, http://team-sp-machine:80/).
   - Click the Site Actions menu and select Site Settings.
   - On the Site Settings page, click Site features (under the Site Administration column).
   - On the Site Features page, click the Activate button for Mark Logic Connector.

   The status of the Mark Logic Connector will change to Active.

3. Configure the MarkLogic connection as follows:
    - In the SharePoint Team Site, click the Site Actions menu and select MarkLogic Connector Settings. [2010: MarkLogic Server Settings]
    - Enter the hostname and port number of the MarkLogic Server XDBC App Server you created in “Installing and Configuring MarkLogic Server to Use the Connector” on page 7, as well as the username and password credentials for MarkLogic Server. The database field is optional.
    - Click the Configure button. You will see a message similar to the following when the configuration is correct:

```
Status: Server xcc://user:pass@host:123/sharepoint has been configured.
Version: 1.1-1
```

4. Test the connection information by clicking the Test Connection button. If the test succeeds then the MarkLogic Connector for SharePoint is communicating successfully with MarkLogic Server. If it fails, go back and repeat the previous steps.
5. Configure document mirroring as follows:
    - The document libraries in your site will be shown as a tree view with checkboxes. Check the libraries which should be mirrored to MarkLogic server. All documents and folders in the library will be mirrored.
    - Click the Push to Server button.
    - Use the Refresh button to refresh the display.
    - If you want to remove the mirrored documents, use the Reset Server button to remove all mirrored documents from this SharePoint site.

The MarkLogic Connector for SharePoint is now ready, and any SharePoint documents or document libraries that you have set up for mirroring are automatically mirrored in MarkLogic Server.

Note: If you mirror a directory containing many documents, enable document mirroring for your document library after saving your docs to the document library to SharePoint. This is to improve the performance of load times. If you attempt to save a large number of docs to a document library with mirroring already enabled, the load will be slow.

2.5.2 Configuring the MarkLogic Connector for SharePoint Foundation 2010

To configure SharePoint Foundation 2010, perform the following steps.

1. Deploy the MarkLogic Connector for SharePoint solution from the SharePoint 2010 Central Administration tool as follows:
   - Launch the SharePoint Central Administration tool (for example, Start Menu > All Programs > Microsoft Sharepoint 2010 Products > SharePoint 2010 Central Administration).
   - Click System Settings in the left-hand menu.
   - In the Farm Management section, click Manage farm solutions.
   - You should see `marklogicconnector.wsp` in the name column. Click this name.
   - On the Solution Properties page click Deploy Solution.
   - On the Deploy Solution page set Deploy When? to Now. Click OK to deploy the solution.

   The page should revert to the Solution Management page with the `marklogicconnector.wsp` Status set to Deployed.

2. Activate the feature as follows:
   - Log in to the SharePoint Team Site. Typically, this is running on port 80 of the machine in which SharePoint is running (for example, http://team-sp-machine:80/).
   - Click the Site Actions menu in the upper left of the page and select Site Settings.
   - On the Site Settings page, under Site Actions, click Manage site features.
   - On the Site Features page, click the Activate button for Mark Logic Connector.

   The status of the Mark Logic Connector will change to Active.

3. Configure the MarkLogic connection as follows:
   - In the SharePoint Team Site, click the Site Actions menu and select MarkLogic Server Settings.
   - Enter the hostname and port number of the MarkLogic Server XDBC App Server you created in “Installing and Configuring MarkLogic Server to Use the Connector” on page 7, as well as the username and password credentials for MarkLogic Server. The database field is optional.
   - Click the Configure button. You will see a message similar to the following when the configuration is correct:

```
Status: Server xcc://user:pass@host:123/sharepoint has been configured.
Version: 1.1-1
```

4. Test the connection information by clicking the Test Connection button. If the test succeeds then the MarkLogic Connector for SharePoint is communicating successfully with MarkLogic Server. If it fails, go back and repeat the previous steps.

5. Configure document mirroring as follows:

    - The document libraries in your site will be shown as a tree view with checkboxes. Check the libraries which should be mirrored to MarkLogic server. All documents and folders in the library will be mirrored.
    - Click the Push to Server button.
    - Use the Refresh button to refresh the display.
    - If you want to remove the mirrored documents, use the Reset Server button to remove all mirrored documents from this SharePoint site.

The MarkLogic Connector for SharePoint is now ready, and any SharePoint documents or document libraries that you have set up for mirroring are automatically mirrored in MarkLogic Server.

Note: If you mirror a directory containing many documents, enable document mirroring for your document library after saving your docs to the document library to SharePoint. This is to improve the performance of load times. If you attempt to save a large number of docs to a document library with mirroring already enabled, the load will be slow.

2.6 Uninstalling the MarkLogic Connector for SharePoint from Microsoft SharePoint

MarkLogic Connector for SharePoint operates with Windows SharePoint Services 3.0 and SharePoint Foundation 2010. The uninstall procedure is slightly different for each version. The following sections describe the uninstall procedure for both versions of SharePoint:

- Uninstalling the MarkLogic Connector for Windows SharePoint Services 3.0
- Uninstalling the MarkLogic Connector for SharePoint Foundation 2010

2.6.1 Uninstalling the MarkLogic Connector for Windows SharePoint Services 3.0

Perform the following steps to uninstall the MarkLogic Connector for SharePoint from your Microsoft SharePoint Services 3.0 installation. You need administrative privileges to SharePoint to perform these steps.

1. Deactivate the feature as follows:
   - Log in to the SharePoint Team Site. Typically, this is running on port 80 of the machine in which SharePoint is running (for example, http://team-sp-machine:80/).
   - Click the Site Actions menu and select Site Settings.
   - On the Site Settings page, click Site features (under the Site Administration column).
   - On the Site Features page, click the Deactivate button for Mark Logic Connector.

   The Active status box next to Mark Logic Connector will disappear.
2. Launch the SharePoint 3.0 Central Administration tool. Typically, you can do this from the Start Menu > All Programs > Administrative Tools > SharePoint 3.0 Central Administration. If you know the machine name and port number, you can also access the Central Administration panel from any browser that has access to your network.
3. Click the Operations tab.
4. Click on Solution Management in the Global Configuration section.
5. Retract and remove the `MarkLogicConnector` solution by clicking the `marklogicconnector.wsp` link.
6. On the Solutions Properties page, click Retract Solution.
7. On the Retract Solution Page, click OK. The page will return to the Solution Management page.
8. Refresh the Solution Management page until `marklogicconnector.wsp` shows a status of Not Deployed.
9. Click the link again and click Remove Solution.

The solution is now uninstalled from SharePoint.

2.6.2 Uninstalling the MarkLogic Connector for SharePoint Foundation 2010

Perform the following steps to uninstall the MarkLogic Connector for SharePoint from your SharePoint Foundation 2010 installation. You need administrative privileges to SharePoint to perform these steps.

1. Deactivate the feature as follows:
   - Log in to the SharePoint Team Site. Typically, this is running on port 80 of the machine in which SharePoint is running (for example, http://team-sp-machine:80/).
   - Click the Site Actions menu in the upper left of the page and select Site Settings.
   - On the Site Settings page, under Site Actions, click Manage site features.
   - On the Site Features page, click the Deactivate button for Mark Logic Connector.

   The Active status box next to Mark Logic Connector will disappear.
2. Launch the SharePoint Central Administration tool (for example, Start Menu > All Programs > Microsoft Sharepoint 2010 Products > SharePoint 2010 Central Administration).
3. Click System Settings in the left-hand menu.
4. In the Farm Management section, click Manage farm solutions.
5. You should see `marklogicconnector.wsp` in the name column. Click this name.
6. On the Solutions Properties page, click Retract Solution.
7. On the Retract Solution Page, click OK. The page will return to the Solution Management page.
8. Refresh the Solution Management page until `marklogicconnector.wsp` shows a status of Not Deployed.
9. Click the link again and click Remove Solution.

The solution is now uninstalled from SharePoint.

3.0 mlcadm Command Line Utility

This chapter describes the commands you can use in the `mlcadm` utility. The following sections are included:

- About the mlcadm Utility
- mlcadm Command Line Usage
- Sample mlcadm Commands

3.1 About the mlcadm Utility

The `mlcadmin` utility is a command-line program that can perform most of the functions of the connector running in SharePoint. The tool requires that the user have SharePoint administrative privileges.

3.2 mlcadm Command Line Usage

When the command references the log, it is referring the `MLConnector.log` file which will be written in the directory in which the command was run.

The `mlcadm.exe` file must be in the search path for the current user. The following is the usage of `mlcadm`, which you can also get by running the command with no arguments or by running `mlcadm usage`:

```
C:\SharePointConnector> mlcadm
Copyright (c) 2009 Mark Logic Corporation. All rights reserved.
Usage: mlcadm command connectString [ siteURL [ docURL [ mlURI ] ] ]

Connect string is of the form: xcc://user:password@host:port[/database]
mode is optional and takes the values: 'mirror', 'copy', and 'dont-copy'

MarkLogic server status commands:
test            Test the connection
status          Send STATUS request to server
getsites        Get web sites
getlists        Get site lists; requires siteURL
getfolders      Get folders under prefix; requires siteURL prefix
getdocs         Get documents under prefix; requires siteURL prefix
getdocprops     Get document properties; requires siteURL and docURL
geturis         Get URI list; requires siteURL and optional docURL

MarkLogic server document commands:
copyfolder      Mirror all documents contained in folder;
                requires siteURL and docUrl
getmetadata     Get metadata; requires siteURL and docURL
putmetadata     Put metadata; requires siteURL and docURL
upload          Upload a document;
                requires siteURL and docURL and optional mode
delete          Delete a document; requires siteURL and docURL
reset           Delete all files and folders on MarkLogic
```

3.3 Sample mlcadm Commands

The section shows some sample `mlcadm` commands, and includes the following samples:

- Test the Connection
- Check the Status of the Connection
- Upload a Document From SharePoint to MarkLogic Server

3.3.1 Test the Connection

The following command tests the connection between the MarkLogic Connector for SharePoint and MarkLogic Server:

```
C:\> mlcadm test xcc://sharepoint-user:password@my-host:1234
Copyright (c) 2008 Mark Logic Corporation. All rights reserved.
SUCCESS: ML-Version-Edition-Platform: 4.0-2-Enterprise-winnt Server:
         sharepoint
Time: 2008-11-07-08:00 13:55:14-08:00
```

3.3.2 Check the Status of the Connection

The following command checks the status of the connection between the MarkLogic Connector for SharePoint and MarkLogic Server, and returns information about the version of the MarkLogic Connector for SharePoint, the version of MarkLogic Server, and other information:

```
C:\> mlcadm status xcc://sharepoint-user:password@my-host:1234
Copyright (c) 2008 Mark Logic Corporation. All rights reserved.
SUCCESS: OK: nvp
SPC-version=1.1-1
ML-version=4.0-2
ML-edition=Enterprise
ML-platform=winnt
ML-server=sharepoint
ML-time=2008-11-07-08:00/13:52:21-08:00
sites=0
```

3.3.3 Upload a Document From SharePoint to MarkLogic Server

The following command uploads a document from SharePoint to MarkLogic Server:

```
c:\>upload xcc://sharepoint-user:password@my-host:1234 \
http://sharepoint-host:19459 \
"Version Test/my Document.docx" \
mirror
SUCCESS: GET_METADATA SEND_CONTENT: Document not found; send content
SUCCESS: UPLOAD 224441 bytes in 0.4218642
SUCCESS: PUT_METADATA OK: Metadata added to document
```

4.0 Workflows and SharePoint

This chapter describes some of the things you can do with workflows, and includes the following section:

- SharePoint Workflow Developer's Kit
- Using Activities With Microsoft Visual Studio
- Running SharePoint Workflows Without Installing the Connector

4.1 SharePoint Workflow Developer's Kit

The SharePoint Workflow Developer's Kit provides connector functionality in a workflow activity library. This allows you to develop workflows in Microsoft Visual Studio. The developer's kit consists of the following assemblies:

- `MarkLogicActivityLibrary.dll` - This file contains activities that can be embedded into workflows
- `MarkLogicConnector.dll` - This file contains the Mark Logic Connector API used by the activities

These files are distributed in the MarkLogic Connector for SharePoint zip file in the `SharePoint` directory.

The following activities are included in the activity library:

- `MarkLogicCopy` — This activity copies a document from SharePoint to MarkLogic Server.
- `MarkLogicDelete` — This activity deletes a SharePoint document from MarkLogic Server.
- `MarkLogicInvoke` — This activity invokes an XQuery module on MarkLogic Server.

4.2 Using Activities With Microsoft Visual Studio

To use the Mark Logic activities in workflow development, you must first load them into the Toolbox in Microsoft Visual Studio. You can drag them onto the design surface and connect their properties into the workflow.

To load Mark Logic activities into the Toolbox, perform the following steps in Microsoft Visual Studio:

1. Start in the context of a workflow project, then select the design view of the workflow to activate the toolbox.
2. In the Toolbox panel, right click and select the Choose Items menu.
3. In the Choose Toolbox Items dialog, select the Activities tab.

4. Click the Browse button, and in the Open dialog box navigate to the directory containing the `MarkLogicActivityLibrary.dll` file. Select this file, and click OK for the Choose Toolbox Items dialog.

The activities `MarkLogicCopy`, `MarkLogicDelete`, and `MarkLogicInvoke` appear in the Toolbox panel. You can drag them onto the workflow design surface. After you drag an activity onto the design surface, it must be connected into the workflow via its properties. There are several categories of properties in the activities. Depending on the activity function, consider the following:

- SharePoint Document Information — The Mark Logic activities are designed to be used in the context of a SharePoint workflow. The `copy` and `delete` activities require the `WebUrl` and `ItemUrl` of the document to be manipulated. These values are available via using the `SPWorkflowActivationProperties` variable.
- Connector Data — All activities optionally allow the workflow author to specify Mark Logic server connection information. If this information is omitted it is assumed to come from the configuration of an installed Mark Logic Connector feature. Note that this allows a workflow to be constructed without the Connector feature installed.
- MarkLogic Invoke — The invoke activity requires the `ModuleName` of the module name of the module to be invoked. The module variable bindings are provided in the `VariableBindings` variable which contains a URL query-string specifying name and string value bindings. (A helper function is provided to convert a C# `Dictionary<string, string>` variable into a URL query string.) The response from the module is passed into the `ModuleResponse` variable.
- Diagnostics — All activities optionally allow the workflow author to specify a log directory. In the case that the Mark Logic Connector feature is installed, the log directory variable is ignored, and the log directory specified in the Connector configuration is used.

4.3 Running SharePoint Workflows Without Installing the Connector

When you run workflow using the Mark Logic activities on a SharePoint site that does not have the Mark Logic Connector installed, you must manually add the connector and activity assemblies to the GAC. You can do this with the following `gacutil` command as follows:

```
C:\> cd <installation directory>\SharePoint
C:\> gacutil -if MarkLogicActivityLibrary.dll
C:\> gacutil -if MarkLogicConnector.dll
C:\> gacutil -if MarklogicXcc.dll
C:\> gacutil -if xcccore.dll
C:\> gacutil -if IKVM.GNU.Classpath.dll
C:\> gacutil -if IKVM.Runtime.dll
C:\> IISRESET
```

Note that retracting the connector feature will remove these assemblies from the GAC.

5.0 Troubleshooting the MarkLogic Connector for SharePoint

This chapter describes the log files and trace event you can use to troubleshoot the MarkLogic Connector for SharePoint. The following sections are included:

- Error Log for the MarkLogic Connector for SharePoint
- Logging Activity on the SharePoint Server
- MarkLogic Server Trace Events for the MarkLogic Connector for SharePoint
- Increasing the Execution Timeout of an ASP.NET Request
- Folders Restored from Recycle Bin

5.1 Error Log for the MarkLogic Connector for SharePoint

There is an error log for the MarkLogic Connector for SharePoint that logs errors in the connector at various levels. The name of the file is `MLConnector.log`, and it is located in the directory where the MarkLogic Connector for SharePoint feature is installed, which is typically the following directory:

```
c:\Program Files\Common Files\Microsoft Shared\web server extension\
        12\TEMPLATE\FEATURE\MarkLogicConnector
```

5.2 Logging Activity on the SharePoint Server

To log activity at the SharePoint server, log into SharePoint as an administrator and click Site Actions -> Mark Logic Server Settings menu. Configure logging by setting the log directory and the log priority threshold.

The default priority threshold is Notice. To see debugging information, set the threshold to Debug. To change the log configuration, make changes to the log directory or priority threshold and then click Configure.

5.3 MarkLogic Server Trace Events for the MarkLogic Connector for SharePoint

The following MarkLogic Server trace event allows you to log SharePoint-related activity on MarkLogic Server:

```
SPC requests
```

To enable this trace event in MarkLogic Server, use the MarkLogic Server Admin Interface Diagnostics page (Group > *group-name* > Diagnostics). On the Diagnostics page in the Admin Interface, enter the `SPC requests` event and enable trace events, then click OK.

When the trace event is activated, various messages will be logged to the MarkLogic Server `ErrorLog.txt` file. For more details about the MarkLogic Server log file, see the *Administrator's Guide*.

5.4 Increasing the Execution Timeout of an ASP.NET Request

If mirroring documents (for example, when you click on "Push To Server" button) times out, you might see the following error in the MarkLogic Connector for SharePoint error log:

```
MLConnector:DocUpload: Thread was being aborted
```

To avoid this error, you can increase execution timeout of MarkLogic connector ASP.NET execution request. To increase the timeout, change the `httpRunTime executionTimeout` setting in the `web.config` file. The timeout is specified in millseconds and defaults to 24 hours (86400000 milliseconds). The file is located in the directory where the MarkLogic Connector for SharePoint feature is installed, which is typically the following directory:

```
c:\Program Files\Common Files\Microsoft Shared\web server extension\
        12\TEMPLATE\LAYOUTS\MarkLogicConnector
```

5.5 Folders Restored from Recycle Bin

There is a bug in SharePoint such that when a folder is restored from the Recycle Bin, no SharePoint event is generated. This causes documents and folders in the restored folder to not be mirrored to Mark Logic server.

To workaround this issue, when a mirrored folder is restored from the Recycle Bin, the administrator must manually push the containing document library to Mark Logic server.

6.0 Technical Support

MarkLogic provides technical support according to the terms detailed in your Software License Agreement or End User License Agreement. For evaluation licenses, MarkLogic may provide support on an “as possible” basis.

For customers with a support contract, we invite you to visit our support website at http://support.marklogic.com to access information on known and fixed issues.

For complete product documentation, the latest product release downloads, and other useful information for developers, visit our developer site at http://developer.marklogic.com.

If you have questions or comments, you may contact MarkLogic Technical Support at the following email address:

support@marklogic.com

If reporting a query evaluation problem, please be sure to include the sample XQuery code.

Combined Product Notices

MarkLogic Server 6.0 and supporting products.
Last updated: August 19, 2013

COPYRIGHT

Copyright © 2013 MarkLogic Corporation. All rights reserved.
This technology is protected by U.S. Patent No. 7,127,469B2, U.S. Patent No. 7,171,404B2, U.S. Patent No. 7,756,858 B2, and U.S. Patent No 7,962,474 B2.

The MarkLogic software is protected by United States and international copyright laws, and incorporates certain third party libraries and components which are subject to the attributions, terms, conditions and disclaimers set forth below.

1. Contains SAP BusinessObjects Text Analysis XI from SAP AG. Copyright © 1996-2011. All rights reserved.

2. Highslide Software from Highslide Software Torstein Honsi. All Highslide Software is protected by local and international copyright laws. All rights reserved.

3. Icons developed by Yusuke Kamiyamane. Copyright © 2011 Yusuke Kamiyamane. All rights reserved. Icons are licensed subject to http://creativecommons.org/licenses/by/3.0/legalcode.

4. Antenna House OfficeHTML Copyright © 2000-2008 Antenna House, Inc. All rights reserved.

5. Argus Copyright ©1999-2008 Iceni Technology Ltd. All rights reserved.

6. Rosette Linguistics Platform 6.5.2/6.5.3 from Basis Technology Corporation, Copyright © 2004-2008 Basis Technology Corporation. All rights reserved.

7. ISYS Search. Copyright © 2011 ISYS™ Search Software, Inc. All rights reserved.

8. Software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/) Copyright © 1995-1998 Eric Young (eay@cryptsoft.com). All rights reserved. Copyright © 1998-2011 The OpenSSL Project. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3. All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)" 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact openssl-core@openssl.org. 5. Products derived from this

software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project. 6. Redistributions of any form whatsoever must retain the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/)" THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. This product includes cryptographic software written by Eric Young (eay@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com). Additional terms may apply to the foregoing software as further set forth at http://www.openssl.org/source/license.html

9. ICU v. 4.2.1 available from http://site.icu-project.org// Copyright © 1995-2011 International Business Machines Corporation and others. All rights reserved. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

10. Tidy available at http://www.w3.org/People/Raggett/tidy/. Copyright © 1998-2008 World Wide Web Consortium (Massachusetts Institute of Technology, European Research Consortium for Informatics and Mathematics, Keio University). All Rights Reserved.

11. 'zlib' general purpose compression library v. 1.2.3. Copyright © 1995-2010 Jean-loup Gailly and Mark Adler. http://www.zlib.net/zlib_license.html

12. RSA Data Security, Inc. MD5 Message-Digest Algorithm, copyright © 1991-2, RSA Data Security, Inc. Created 1991. All rights reserved. License to copy and use this software is granted provided that it is identified as the "RSA Data Security, Inc. MD5 Message-Digest Algorithm" in all material mentioning or referencing this software or this function. License is also granted to make and use derivative works provided that such works are identified as "derived from the RSA Data Security, Inc. MD5 Message-Digest Algorithm" in all material mentioning or referencing the derived work. RSA Data Security, Inc. makes no representations concerning either the merchantability of this software or the suitability of this software for any particular purpose. It is provided "as is" without express or implied warranty of any kind. These notices must be retained in any copies of any part of this documentation and/or software.

13. TRE software, available at http://laurikari.net/tre/. Copyright © 2001-2009 Ville Laurikari <vl@iki.fi>. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: (1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. (2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

14. Eigen Library, version 2.0.10, available at http://eigen.tuxfamily.org/index.php?title=Main_Page. Eigen Library is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version. Eigen Library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details. You should have received a copy of the GNU Lesser General Public License along with Eigen Library. If not, see: http://www.gnu.org/copyleft/lesser.html

15. FunctX XQuery Library v.1.0 available at http://www.xqueryfunctions.com/xq/, Copyright © Datypic (Priscilla Walmsley). You can redistribute such library and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version. This library is distributed in the

hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License as available at http://www.gnu.org/licenses/lgpl-2.1.html#SEC4 for more details.

16. DeployJava.js v. 1.8, Copyright © 2006, 2011, Oracle and/or its affiliates. All rights reserved. ORACLE PROPRIETARY/CONFIDENTIAL. Use of the foregoing library is subject to the following license terms. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of Oracle nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

17. YUI libraries v.2.8 available at http://developer.yahoo.com/yui/. Copyright © 2011 Yahoo! Inc. All rights reserved. Use of the foregoing libraries is subject to the following license terms. Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of Yahoo! Inc. nor the names of YUI's contributors may be used to endorse or promote products derived from this software without specific prior written permission of Yahoo! Inc. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Additional notices related to components included in the foregoing library are also available at the following URL: http://yuilibrary.com/license/

18. XSLTForms libraries available at http://sourceforge.net/projects/xsltforms/ . You can redistribute such libraries and/or modify them under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version. These libraries are distributed in the hope that they will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License as available at http://www.gnu.org/licenses/lgpl-2.1.html#SEC4 for more details.

19. jQuery v.1.7 libraries available at http://jquery.com/ and jQuery UI v.1.8.2 libraries available at http://jqueryui.com/. Copyright © 2011 John Resig. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OFMERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE ANDNONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BELIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTIONOF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTIONWITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

20. JSON v. 2 libraries available at http://www.json.org/json2.js. Copyright © 2002 JSON.org. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. The Software shall be used for Good, not Evil. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

21. CodeMirror libraries available at http://codemirror.net/. Copyright © 2011 by Marijn Haverbeke marijnh@gmail.com. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

22. History.js available https://github.com/balupton/History.js/ Copyright © 2011, Benjamin Arthur Lupton. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of Benjamin Arthur Lupton nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

23. Sample content provided for use with the software is copyrighted by the respective authors as contributed by each of them to Wikipedia pursuant to the Creative Commons Attribution-ShareAlike License found at http://creativecommons.org/licenses/by-sa/3.0/.

24. Visual Studio Tools for Office 3.0 (Microsoft VSTO 3.0) licensed under Microsoft Public License Microsoft Public License (Ms-PL) found at http://msdn.microsoft.com/en-us/library/ff647676.aspx.

25. The MarkLogic Connector for Hadoop contains Apache Jakarta Commons Modeler. Copyright 2001-2007 The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"). You may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

26. jemalloc http://www.canonware.com/jemalloc/index.html, released under the terms of the following BSD-derived licenses: Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1. Redistributions of source code must retain the above copyright notice(s), this list of conditions and the following disclaimer. 2. Redistributions in binary form must reproduce the above copyright notice(s), this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER(S) ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Portions of the software are copyright (C) 2002-2013 Jason Evans, and portions copyright (C) 2009-2013 Facebook, Inc. and copyright (C) 2007-2012 Mozilla Foundation. Neither the name of Facebook, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. All rights reserved.

27. Gziphelper; version: 1.0, Feb, 2003, authored by Gao Dasheng, is distributed subject to the following terms: This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software. Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions: (1.) the origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required; (2) altered source versions must be plainly marked as such, and must not be misrepresented as being the original software; (3) this notice may not be removed or altered from any source distribution.

28. Some features of MarkLogic allow you to develop and use Google Maps. Review Google Map's privacy policy at http://www.google.com/policies/privacy/, legal notices at http://maps.google.com/help/legalnotices_maps.html, and terms of use at http://maps.google.com/help/terms_maps.html.

29. commons-codec, HttpComponents, commons-logging, and Google Maps Utility are used under the Licensed under the Apache License, Version 2.0 (the "License"). You may not use these files except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

30. Mapstraction. Copyright (c) 2012, Mapstraction. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

31. logback-classic and logback-core are provided in object code form only under the Eclipse Public License - v 1.0 available at http://www.eclipse.org/legal/epl-v10.html. Copyright (C) 1999-2012, QOS.ch. All rights reserved. Source code for the Program is available http://logback.qos.ch/.

32. Simple Logging Facade for Java (SLF4J). Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

33. cURL v. 7.22.0 available at http://curl.haxx.se/. Copyright © 1996 - 2011, Daniel Stenberg, <daniel@haxx.se>. All rights reserved. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE. Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

34. heatmap.js distributed subject to the "THE BEER-WARE LICENSE" (Revision 42): <phk@FreeBSD.ORG> wrote this file. As long as you retain this notice you can do whatever you want with this stuff. If we meet some day, and you think this stuff is worth it, you can buy me a beer in return Poul-Henning Kamp.

35. Except for components that are otherwise subject to other open source licenses, the MarkLogic ODBC Driver is released under the GNU Lesser General Public License as published by the Free Software Foundation, version 2.1 of the License.

36. Solr-commons-csv-3.5.0 Copyright 2005-2006 The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

37. Avro v. 1.7.1. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

38. Guava v. 11.0.2. Copyright © Google. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

39. Hadoop-auth v. 2.0.0. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

40. hadoop-hdfs v. 2.0. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

41. commons-lang v. 2.4, 2.5. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

42. commons-configuration v. 2.0. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

43. jackson-core-asl v. 1.8.8. Copyright © FasterXML. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

44. jackson-mapper-asl v. 1.8.8. Copyright © FasterXML. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

45. log4j v. 1.2.16. Copyright © The Apache Software Foundation. Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0. Unless required by applicable law or agreed to in writing, this file is distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

46. protobuf-java v. 2.4.0a. Copyright © Google. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of Google nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

47. xpp3 v. 1.1.3.3. Copyright © 2002 Extreme! Lab, Indiana University. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. The end-user documentation included with the redistribution, if any, must include the following acknowledgment: "This product includes software developed by the Indiana University Extreme! Lab(http://www.extreme.indiana.edu/)." Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear. The names "Indiana Univeristy" and "Indiana Univeristy Extreme! Lab" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact http://www.extreme.indiana.edu/. Products derived from this software may not use "Indiana Univeristy" name nor may "Indiana Univeristy" appear in their name, without prior written permission of the Indiana University. THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS, COPYRIGHT HOLDERS OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IFADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

48. xstream v. 1.4.2. Copyright © 2003-2006, Joe Walnes. Copyright © 2006-2009, 2011 XStream Committers. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of XStream nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR

BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

TRADEMARK NOTICE

The MarkLogic name and logo are registered trademarks of MarkLogic Corporation in the United States and/or other countries. Excel and PowerPoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Any other names or logos included in the Software, this notice or the documentation are property of the respective trademark owners.