MarkLogic Server

Search Developer's Guide

MarkLogic 8
February, 2015

Last Revised: 8.0-7, August, 2017

Table of Contents

Search Developer's Guide

1.0 Developing Search Applications in MarkLogic Server 20
1.1 Overview of Search Features in MarkLogic Server 20
1.1.1 High Performance Full Text Search 20
1.1.2 APIs for Multiple Programming Languages 21
1.1.3 Support for Multiple Query Styles 22
1.1.4 Support for Multiple Query Types 24
1.1.5 Full XPath Search Support in XQuery 25
1.1.6 Lexicon and Range Index-Based APIs 25
1.1.7 Stemming, Wildcard, Spelling, and Much More Functionality 26
1.1.8 Alerting API and Built-Ins 26
1.2 Where to Find Search Information 27

2.0 Search API: Understanding and Using 28
2.1 Understanding the Search API 28
2.1.1 Making the Search API Available to Your Application 29
2.1.2 Simple search:search Example and Response Output 29
2.1.3 Automatic Query Text Parsing and Grammar 30
2.1.4 Constrained Searches and Faceted Navigation 32
2.1.5 Built-In Snippetting 34
2.1.6 Search Term Completion 34
2.1.7 Search Customization Via Options and Extensions 34
2.1.8 Speed and Accuracy 35
2.2 Controlling a Search With Query Options 35
2.3 Search Term Completion Using search:suggest 36
2.3.1 default-suggestion-source Option 36
2.3.2 Choose Suggestions With the suggestion-source Option 37
2.3.3 Use Multiple Query Text Inputs to search:suggest 38
2.3.4 Make Suggestions Based on Cursor Position 39
2.3.5 search:suggest Examples 39
2.4 Creating a Custom Constraint 40
2.4.1 Implementing the parse Function 40
2.4.2 Implementing the start-facet Function 43
2.4.3 Implementing the finish-facet Function 44
2.4.4 Example: Creating a Simple Custom Constraint 45
2.4.5 Example: Creating a Custom Constraint for Structured Queries 46
2.4.6 Example: Creating a Custom Constraint Geospatial Facet 48
2.5 Search Grammar 51
2.6 Returning Lexicon Values With search:values 52

2.6.1 Specifying the Input Lexicons 52
2.6.2 Constraining and Filtering Your Results 53
2.6.3 Example: Using a Query to Constrain Results 54
2.6.4 Example: Filtering with Starting Value, Limit, and Page Length 56
2.6.5 Example: Finding Value Co-Occurrences 58
2.6.6 Additional Interfaces 58
2.7 JSON Support in the Search API 58
2.8 More Search API Examples 60
2.8.1 Buckets Example 60
2.8.2 Computed Buckets Example 62
2.8.3 Sort Order Example 64

3.0 Searching Using String Queries 65
3.1 String Query Overview 65
3.2 The Default String Query Grammar 66
3.2.1 Query Components and Operators 66
3.2.2 Operator Precedence 69
3.2.3 Using Relational Operators on Constraints 70
3.2.4 String Query Examples 70
3.3 Modifying and Extending the String Query Grammar 71
3.3.1 starter 73
3.3.2 joiner 75
3.3.3 quotation 76
3.3.4 implicit 76

4.0 Searching Using Structured Queries 78
4.1 Structured Query Overview 78
4.2 Structured Query Concepts 79
4.2.1 Major Query Categories 80
4.2.2 Understanding the Difference Between Term and Word Queries 81
4.2.3 Understanding Containment 81
4.2.4 Text Match Semantics 83
4.2.5 Structured Query Sub-Query Taxonomy 84
4.3 Constructing a Structured Query 85
4.4 Syntax Summary 86
4.5 Examples of Structured Queries 87
4.5.1 Example: Simple Structured Search 87
4.5.2 Example: Structured Search With Constraint References as Text 88
4.5.3 Example: Structured Search With Constraint References 89
4.6 Syntax Reference 90
4.6.1 query 93
4.6.2 term-query 95
4.6.3 and-query 97
4.6.4 or-query 98
4.6.5 and-not-query 100

4.6.6 not-query 102
4.6.7 not-in-query 103
4.6.8 near-query 105
4.6.9 boost-query 107
4.6.10 properties-fragment-query 109
4.6.11 directory-query 112
4.6.12 collection-query 114
4.6.13 container-query 115
4.6.14 document-query 117
4.6.15 document-fragment-query 118
4.6.16 locks-fragment-query 120
4.6.17 range-query 121
4.6.18 value-query 125
4.6.19 word-query 128
4.6.20 geo-elem-query 132
4.6.21 geo-elem-pair-query 136
4.6.22 geo-attr-pair-query 140
4.6.23 geo-path-query 144
4.6.24 geo-json-property-query 148
4.6.25 geo-json-property-pair-query 151
4.6.26 range-constraint-query 155
4.6.27 value-constraint-query 158
4.6.28 word-constraint-query 161
4.6.29 collection-constraint-query 163
4.6.30 container-constraint-query 165
4.6.31 element-constraint-query 168
4.6.32 properties-constraint-query 170
4.6.33 custom-constraint-query 171
4.6.34 geospatial-constraint-query 174
4.6.35 lsqt-query 177
4.6.36 period-compare-query 179
4.6.37 period-range-query 181
4.6.38 operator-state 183

5.0 Searching Using Query By Example 186
5.1 QBE Overview 186
5.1.1 Search Criteria Based on Document Structure 188
5.1.2 Logical Operators 192
5.1.3 Comparison Operators 193
5.1.4 Query by Value or Word 194
5.1.5 Search Result Customization 195
5.1.6 Options for Controlling Search Behavior 195
5.2 Example 195
5.2.1 XML Example 196
5.2.2 JSON Example 197
5.3 Understanding QBE Sub-Query Types 199

5.3.1 Value Query 200
5.3.2 Word Query 201
5.3.3 Range Query 202
5.3.4 Composed Query 204
5.3.5 Container Query 205
5.4 Search Criteria Quick Reference 208
5.4.1 XML Search Criteria Quick Reference 208
5.4.2 JSON Search Criteria Quick Reference 210
5.4.3 Searching Entire Documents 213
5.5 QBE Structural Reference 215
5.5.1 Top Level Structure 216
5.5.2 Query Components 217
5.5.3 Response Components 219
5.5.4 XML-Specific Considerations 220
5.5.5 JSON-Specific Considerations 222
5.6 How Indexing Affects Your Query 226
5.7 Adding Options to a QBE 227
5.7.1 Specifying Options in XML 227
5.7.2 Specifying Options in JSON 227
5.7.3 Option List 228
5.7.4 Using Persistent Query Options 230
5.8 Customizing Search Results 232
5.8.1 When to Include a Response in Your Query 232
5.8.2 Using the snippet Formatter 233
5.8.3 Using the extract Formatter 235
5.8.4 Example: Search Customization 236
5.9 Scoping a Search by Document Type 237
5.10 Converting a QBE to a Combined Query 238
5.11 Validating a QBE 238

6.0 Composing cts:query Expressions 240
6.1 Understanding cts:query 240
6.1.1 cts:query Hierarchy 241
6.1.2 Use to Narrow the Search 243
6.1.3 Understanding cts:element-query 243
6.1.4 Understanding cts:element-word-query 243
6.1.5 Understanding Field Word and Value Query Constructors 244
6.1.6 Understanding the Range Query Constructors 244
6.1.7 Understanding the Reverse Query Constructor 244
6.1.8 Understanding the Geospatial Query Constructors 245
6.1.9 Specifying the Language in a cts:query 245
6.2 Creating a Query From Search Text With cts:parse 245
6.2.1 String Query Overview 246
6.2.2 Grammar Components and Operators 247
6.2.3 Binding a Tag to a Reference, Field, or Query Generator 253
6.2.4 Customizing Naked Term Handling With Bindings 264

6.2.5 Query Text Parsing Examples 265
6.3 Combining multiple cts:query Expressions 268
6.3.1 Using cts:and-query and cts:or-query 268
6.3.2 Proximity Queries using cts:near-query 269
6.3.3 Using Bounded cts:query Expressions 269
6.3.4 Matching Nothing and Matching Everything 270
6.4 Joining Documents and Properties with cts:properties-query or cts:document-fragment-query 270
6.5 Registering cts:query Expressions to Speed Search Performance 271
6.5.1 Registered Query APIs 271
6.5.2 Must Be Used Unfiltered 272
6.5.3 Registration Does Not Survive System Restart 272
6.5.4 Storing Registered Query IDs 273
6.5.5 Registered Queries and Relevance Calculations 273
6.5.6 Example: Registering and Using a cts:query Expression 273
6.6 Adding Relevance Information to cts:query Expressions: 273
6.7 XML Serializations of cts:query Constructors 274
6.7.1 Serializing a cts:query to XML 274
6.7.2 Add Arbitrary Annotations With cts:annotation 274
6.7.3 Function to Construct a cts:query From XML 275
6.8 Example: Creating a cts:query Parser 275

7.0 Creating JavaScript Search Applications 278
7.1 JSearch Introduction 278
7.1.1 JSearch Feature Summary 279
7.1.2 Top Level Function Summary 279
7.1.3 Query Design Pattern 280
7.1.4 How JSearch Relates to Other MarkLogic Search APIs 283
7.1.5 Running the Examples in This Chapter 283
7.2 Scoping Operations by Collection 284
7.3 Searching Documents 284
7.3.1 Document Search Basics 285
7.3.2 Example: Basic Document Search 287
7.4 Creating a cts.query 289
7.4.1 Using byExample to Create a Query 290
7.4.2 Using Query Text to Create a cts.query 294
7.4.3 Using cts.query Constructors 296
7.5 Including Facets in Search Results 296
7.5.1 Introduction to Facets 297
7.5.2 Basic Steps for Generating Facets 298
7.5.3 Example: Generating Facets From JSON Properties 300
7.5.4 Creating a Facet Definition 301
7.5.5 Understanding the Output of Facets 303
7.5.6 Sorting Facet Values with OrderBy 306
7.5.7 Retrieving Facets and Content in a Single Operation 307
7.5.8 Multi-Facet Interactions Using othersWhere 310

7.5.9 Example: Multi-Facet Interactions Using othersWhere 311
7.6 Controlling the Ordering of Results 316
7.6.1 Sorting Document Search Results 316
7.6.2 Sorting Values or Tuples Query Results 318
7.6.3 Sorting Word Lexicon Query Results 318
7.6.4 Sorting Facet Values 319
7.7 Returning a Result Subset 319
7.8 Including Snippets of Matching Content in Search Results 320
7.8.1 Enabling Snippet Generation 321
7.8.2 Configuring the Built-In Snippet Generator 322
7.8.3 Returning Snippets and Documents Together 323
7.8.4 Generating Custom Snippets 324
7.8.5 Standalone Snippet Generation 324
7.9 Extracting Portions of Each Matched Document 325
7.9.1 Extraction Overview 325
7.9.2 How selected Affects Extraction 327
7.9.3 Combining Extraction With Snippeting 329
7.10 Using Options to Control a Query 330
7.11 Transforming Results with Map and Reduce 331
7.11.1 Map and Reduce Overview 331
7.11.2 Configuring the Built-In Mapper 332
7.11.3 Using a Custom Mapper 333
7.11.4 Configuring the Built-In Reducer 334
7.11.5 Using a Custom Reducer 335
7.11.6 Example: Using a Custom Mapper for Content Transformation 336
7.11.7 Example: Custom Reducer For Document Search 338
7.11.8 Example: Custom Reducer For Values Query 340
7.12 Querying Lexicons and Range Indexes 341
7.12.1 Querying the Values in a Lexicon or Index 341
7.12.2 Finding Value Co-Occurrences in Lexicons and Indexes 344
7.12.3 Querying Values in a Word Lexicon 346
7.12.4 Computing Aggregates Over Range Indexes 349
7.12.5 Constructing Lexicon and Range Index References 353
7.13 Grouping Values and Facets Into Buckets 354
7.13.1 Bucketing Overview 354
7.13.2 Example: Generating Buckets With makeBuckets 356
7.13.3 Example: Grouping Using Custom Buckets 359
7.14 Preparing to Run the Examples 362
7.14.1 Configuring the Database 362
7.14.2 Loading the Sample Documents 366

8.0 Search Customization Using Query Options 368
8.1 Introduction 368
8.2 Getting the Default Query Options 369
8.3 Checking Query Options for Errors 369
8.4 Constraint Options 369

8.4.1 Value Constraint Example 376
8.4.2 Word Constraint Examples 376
8.4.3 Collection Constraint Example 377
8.4.4 Bucketed Range Constraint Example 378
8.4.5 Exact Match (Unbucketed) Range Constraint Example 380
8.4.6 Geospatial Constraint Example 380
8.5 Operator Options 382
8.6 Return Options 385
8.7 Searchable Expression Option 385
8.8 Fragment Scope Option 386
8.9 Modifying Your Snippet Results 387
8.9.1 Specifying transform-results Options 387
8.9.2 Specifying Your Own Code in transform-results 389
8.10 Extracting a Portion of Matching Documents 390
8.11 Customizing Search Results with a Decorator 394
8.11.1 Understanding Search Result Decorators 394
8.11.2 Writing a Custom Search Result Decorator 395
8.11.3 Installing a Custom Search Result Decorator 396
8.11.4 Using a Custom Search Result Decorator 396
8.12 Other Search Options 397
8.13 Query Options Examples 397
8.13.1 Example: Values and Tuples Query Options 398
8.13.2 Example: Field Constraint Query Options 401
8.13.3 Example: Collection Constraint Query Options 401
8.13.4 Example: Path Range Index Constraint Query Options 402
8.13.5 Example: Element Attribute Range Constraint Query Options 404
8.13.6 Example: Geospatial Constraint Query Options 406

9.0 Relevance Scores: Understanding and Customizing 408
9.1 Understanding How Scores and Relevance are Calculated 408
9.1.1 log(tf)*idf Calculation 409
9.1.2 log(tf) Calculation 409
9.1.3 Simple Term Match Calculation 410
9.1.4 Random Score Calculation 410
9.1.5 Term Frequency Normalization 410
9.2 How Fragmentation and Index Options Influence Scores 411
9.3 Using Weights to Influence Scores 411
9.4 Proximity Boosting With the distance-weight Option 412
9.4.1 Example of Simple Proximity Boosting 412
9.4.2 Using Proximity Boosting With cts:and-query Semantics 413
9.4.3 Using cts:near-query to Achieve Proximity Boosting 414
9.5 Boosting Relevance Score With a Secondary Query 415
9.6 Including a Range or Geospatial Query in Scoring 416
9.6.1 How a Range Query Contributes to Score 417
9.6.2 Use Cases for Range Query Score Contributions 417
9.6.3 Enabling Range Query Score Contribution 417

9.6.4 Understanding Slope Factor 419
9.6.5 Performance Considerations 421
9.6.6 Range Query Scoring Examples 422
9.7 Interaction of Score and Quality 426
9.8 Using cts:score, cts:confidence, and cts:fitness 426
9.9 Relevance Order in cts:search Versus Document Order in XPath 427
9.10 Exploring Relevance Score Computation 428
9.11 Sample cts:search Expressions 430
9.11.1 Magnify the Score Boost for Documents With Quality 430
9.11.2 Increase the Score for some Terms, Decrease for Others 430

10.0 Browsing With Lexicons 431
10.1 About Lexicons 431
10.2 Creating Lexicons 432
10.3 Word Lexicons 433
10.3.1 Word Lexicon for the Entire Database 433
10.3.2 Element/Element-Attribute Word Lexicons 434
10.3.3 JSON Property Word Lexicons 434
10.3.4 Field Word Lexicons 435
10.4 Element/Element-Attribute/Path Value Lexicons 435
10.5 Field Value Lexicons 436
10.6 Value Co-Occurrences Lexicons 437
10.7 Geospatial Lexicons 439
10.8 Range Lexicons 440
10.9 URI and Collection Lexicons 440
10.10 Performing Lexicon-Based Queries 441
10.10.1Lexicon APIs 441
10.10.2Constraining Lexicon Searches to a cts:query Expression 442
10.10.3Using the Match Lexicon APIs 443
10.10.4Determining the Number of Fragments Containing a Lexicon Term 443

11.0 Using Range Queries in cts:query Expressions 445
11.1 Overview of Range Queries 445
11.1.1 Uses for Range Queries 445
11.1.2 Requirements for Using Range Queries 446
11.1.3 Performance and Coding Advantages of Range Queries 446
11.2 Range Query cts:query Constructors 447
11.3 Examples of Range Queries 447

12.0 Using Aggregate Functions 449
12.1 Introduction to Aggregate Functions 449
12.2 Using Builtin Aggregate Functions 449
12.3 Using Aggregate User-Defined Functions 451

13.0 Highlighting Search Term Matches 454
13.1 Overview of cts:highlight 454
13.1.1 All Matching Terms, Including Stemmed, and Capitalized 454
13.2 General Search and Replace Function 455
13.3 Built-In Variables For cts:highlight 455
13.3.1 Using the $cts:text Variable to Access the Matched Text 456
13.3.2 Using the $cts:node Variable to Access the Context of the Match 456
13.3.3 Using the $cts:queries Variable to Feed Logic Based on the Query 457
13.3.4 Using $cts:start to Capture the String-Length Position 458
13.3.5 Using $cts:action to Stop Highlighting 458
13.4 Using cts:highlight to Create Snippets 458
13.5 cts:walk Versus cts:highlight 459
13.6 Common Usage Notes 459
13.6.1 Input Must Be a Single Node 460
13.6.2 Using xdmp:set Side Effects With cts:highlight 460
13.6.3 No Highlighting with cts:similar-query or cts:element-attribute-*-query 461

14.0 Geospatial Search Applications 462
14.1 Overview of Geospatial Data in MarkLogic Server 462
14.1.1 Terminology 462
14.1.2 Coordinate System 463
14.1.3 Types of Geospatial Queries 464
14.1.4 XQuery Primitive Types And Constructors for Geospatial Queries 464
14.1.5 Well-Known Text (WKT) and Well-Known Binary (WKB) Support ...465
14.2 Understanding Geospatial Coordinates and Regions 466
14.2.1 Understanding the Basics of Coordinates and Points 466
14.2.2 Understanding Geospatial Boxes 467
14.2.3 Understanding Geospatial Polygons: Polygons, Complex Polygons, and Linestrings 468
14.2.4 Understanding Geospatial Circles 470
14.3 Geospatial Indexes 470
14.3.1 Different Kinds of Geospatial Indexes 471
14.3.2 Geospatial Index Positions 474
14.3.3 Geospatial Lexicons 474
14.4 Performing a GeoSpatial Query 475
14.4.1 Basic Procedure for Performing a Geospatial Query 475
14.4.2 Geospatial Query Constructors 476
14.4.3 Geospatial Format Conversion Functions 476
14.4.4 Example: Simple XQuery Geospatial Search 477
14.5 Summary of Other Geospatial Operations 479
14.6 Converting To and From Common Geospatial Representations 480
14.6.1 Conversion Overview 480
14.6.2 WKT and WKB Conversions in XQuery 482
14.6.3 WKT and WKB Conversions in JavaScript 483

14.6.4 Mapping of WKT and WKB Types to MarkLogic Types 485
14.7 Constructing Geospatial Point and Region Values 486
14.8 Geospatial Query Support in Other APIs 487

15.0 Marking Up Documents With Entity Enrichment 489
15.1 Overview of Entity Enrichment 489
15.2 Entity Enrichment Pipelines 489
15.2.1 Sample Pipelines Using Third-Party Technologies 490
15.2.2 Custom Entity Enrichment Pipelines 490

16.0 Creating Alerting Applications 491
16.1 Overview of Alerting Applications in MarkLogic Server 491
16.2 cts:reverse-query Constructor 492
16.3 XML Serialization of cts:query Constructors 492
16.4 Security Considerations of Alerting Applications 493
16.4.1 Alert Users, Alert Administrators, and Controlling Access 493
16.4.2 Predefined Roles for Alerting Applications 493
16.5 Indexes for Reverse Queries 494
16.6 Alerting API 495
16.6.1 Alerting API Concepts 495
16.6.2 Using the Alerting API 497
16.6.3 Using CPF With an Alerting Application 499
16.7 Alerting Sample Application 501

17.0 Using fn:count vs. xdmp:estimate 502
17.1 fn:count is Accurate, xdmp:estimate is Fast 502
17.2 The xdmp:estimate Built-In Function 502
17.3 Using cts:remainder to Estimate the Size of a Search 503
17.4 When to Use xdmp:estimate 503
17.4.1 When Estimates Are Good Enough 505
17.4.2 When XPaths Meet The Right Criteria 505
17.4.3 When Empirical Tests Demonstrate Correctness 506

18.0 Understanding and Using Stemmed Searches 507
18.1 Stemming in MarkLogic Server 507
18.2 Enabling Stemming 508
18.3 Stemmed Searches Versus Word Searches 509
18.4 Using cts:highlight or cts:contains to Find if a Word Matches a Query 510
18.5 Interaction With Wildcard Searches 510

19.0 Custom Dictionaries for Tokenizing and Stemming 511
19.1 Custom Dictionaries in MarkLogic Server 511
19.2 Dictionary and Entry Schemas 512
19.3 Custom Dictionary Functions 513

19.3.1 Get All Licensed Languages 513
19.3.2 Get A Custom Dictionary 514
19.3.3 Add/Write A Custom Dictionary 514
19.3.4 Delete A Custom Dictionary 514
19.4 Usage Examples 514

20.0 Extracting Metadata and Text From Binary Documents 517
20.1 Metadata and Text Extraction Overview 517
20.2 Usage Examples 517
20.2.1 Microsoft Word 517
20.2.2 File Archives 519
20.2.3 PowerPoint 521
20.3 Supported Binary Formats 522
20.3.1 **Archives 522**
20.3.2 **Databases 523**
20.3.3 Email and Messaging 523
20.3.4 Multimedia 523
20.3.5 Other 523
20.3.6 ....Presentation 523
20.3.7 Raster Image 524
20.3.8 Spreadsheet 524
20.3.9 Text and Markup 524
20.3.10Vector Image 524
20.3.11Word Processing and General Office 525

21.0 Understanding and Using Wildcard Searches 526
21.1 Wildcards in MarkLogic Server 526
21.1.1 Wildcard Characters 526
21.1.2 Rules for Wildcard Searches 526
21.2 Enabling Wildcard Searches 527
21.2.1 Specifying Wildcards in Queries 528
21.2.2 Recommended Wildcard Index Settings 528
21.2.3 Understanding the Wildcard Indexes 529
21.3 Interaction with Other Search Features 530
21.3.1 Wildcarding and Stemming 530
21.3.2 Wildcarding and Punctuation Sensitivity 531

22.0 Collections 536
22.1 The collection() Function 536
22.2 Collections Versus Directories 537
22.3 Defining Collections 538
22.3.1 Implicitly Defining Unprotected Collections 538
22.3.2 Explicitly Defining Protected Collections 539
22.4 Collection Membership 540
22.5 Collections and Security 540

22.5.1 Unprotected Collections 541
22.5.2 Protected Collections 542
22.6 Performance Characteristics 542
22.6.1 Number of Collections to Which a Document Belongs 543
22.6.2 Adding/Removing Existing Documents To/From Collections 543

23.0 Using the Thesaurus Functions 544
23.1 The Thesaurus Module 544
23.2 Function Reference 544
23.3 Thesaurus Schema 545
23.4 Capitalization 545
23.5 Managing Thesaurus Documents 545
23.5.1 Loading Thesaurus Documents in XQuery 546
23.5.2 Loading Thesaurus Documents in JavaScript 546
23.5.3 Lowercasing Terms When Inserting a Thesaurus Document 547
23.5.4 Loading the XML Version of the WordNet Thesaurus 547
23.5.5 Updating a Thesaurus Document 548
23.5.6 Security Considerations With Thesaurus Documents 549
23.5.7 Example Queries Using Thesaurus Management Functions 549
23.6 Expanding Searches Using a Thesaurus in XQuery 555
23.7 Expanding Searches Using a Thesaurus in JavaScript 556

24.0 Using the Spelling Correction Functions 557
24.1 Overview of Spelling Correction 557
24.2 Function Reference 557
24.2.1 The Spelling Built-In Functions 558
24.2.2 The Spelling Dictionary Management Module Functions 558
24.3 Dictionary Documents 559
24.3.1 XML Dictionary Document 559
24.3.2 JSON Dictionary Document 559
24.4 Capitalization 560
24.5 Managing Dictionary Documents 560
24.5.1 Loading Dictionary Documents in XQuery 561
24.5.2 Loading Dictionary Documents in JavaScript 561
24.5.3 Loading one of the Sample XML Dictionaries 561
24.5.4 Updating a Dictionary Document 562
24.5.5 Security Considerations With Dictionary Documents 564
24.6 Testing if a Word is Spelled Correctly 564
24.7 Getting Spelling Suggestions for Incorrectly Spelled Words 565

25.0 Distinctive Terms and cts:similar-query 566
25.1 Understanding cts:similar-query 566
25.2 Finding the Distinctive Terms of a Set of Nodes 566
25.3 Understanding the cts:distinctive-terms Output 567
25.4 Example Design Pattern: Making a Tag Cloud 568

26.0 Training the Classifier 570
26.1 Understanding How Training and Classification Works 570
26.1.1 Training and Classification 570
26.1.2 XML SVM Classifier 570
26.1.3 Hyper-Planes and Thresholds for Classes 571
26.1.4 Training Content for the Classifier 575
26.2 Classifier API 575
26.2.1 XQuery Built-In Functions 575
26.2.2 Data Can Reside Anywhere or Be Constructed 576
26.2.3 API is Extremely Tunable 576
26.2.4 Supports Versus Weights Classifiers 576
26.2.5 Kernels (Mapping Functions) 577
26.2.6 Find Thresholds That Balance Precision and Recall 577
26.3 Leveraging XML With the Classifier 577
26.4 Creating a Training Set 577
26.4.1 Importance of the Training Set 578
26.4.2 Defining Labels for the Training Set 578
26.5 Methodology For Determining Thresholds For Each Class 579
26.6 Example: Training and Running the Classifier 580
26.6.1 Shakespeare's Plays: The Training Set 581
26.6.2 Comedy, Tragedy, History: The Classes 581
26.6.3 Partition the Training Content Set 581
26.6.4 Create Labels on the First Half of the Training Content 582
26.6.5 Run cts:train on the First Half of the Training Content 582
26.6.6 Run cts:classify on the Second Half of the Content Set 583
26.6.7 Use cts:thresholds to Compute the Thresholds on the Second Half 584
26.6.8 Evaluating Your Results, Make Changes, and Run Another Iteration 584
26.6.9 Run the Classifier on Other Content 585

27.0 Results Clustering Using cts:cluster 586
27.1 Understanding cts:cluster 586
27.2 Options to cts:cluster 587
27.2.1 Clustering (cts:cluster) Options 587
27.2.2 Indexing (db:) Options 588
27.3 Understanding the cts:cluster Output 588
27.4 Example that Creates an HTML Report of the Cluster 590

28.0 Language Support in MarkLogic Server 594
28.1 Overview of Language Support in MarkLogic Server 594
28.2 Tokenization and Stemming 595
28.2.1 Language-Specific Tokenization 595
28.2.2 Stemmed Searches in Different Languages 597
28.3 Language Aspects of Loading and Updating Documents 598
28.3.1 Tokenization and Stemming 598
28.3.2 xml:lang Attribute 598

28.3.3 Language-Related Notes About Loading and Updating Documents 599
28.4 Querying Documents By Languages 600
28.4.1 Tokenization, Stemming, and the xml:lang Attribute 600
28.4.2 Language-Aware Searches 600
28.4.3 Unstemmed Searches 601
28.4.4 Unknown Languages 602
28.5 Supported Languages 603
28.6 Generic Language Support 604

29.0 Custom Tokenization 605
29.1 Introduction to Custom Tokenizer Overrides 605
29.2 How Character Classification Affects Tokenization 606
29.3 Using xdmp:describe to Explore Tokenization 607
29.4 Performance Impact of Using Tokenizer Overrides 607
29.5 Defining a Custom Tokenizer Override 608
29.6 Examples of Custom Tokenizer Overrides 608
29.6.1 Example: Configuring a Field with Tokenizer Overrides 608
29.6.2 Example: Improving Accuracy of Wildcard-Enabled Searches 610
29.6.3 Example: Data Normalization 612
29.6.4 Example: Searching Within a Word 612
29.6.5 Example: Using the Symbol Classification 614

30.0 Encodings and Collations 616
30.1 Character Encoding 616
30.2 Collations 617
30.2.1 Overview of Collations 617
30.2.2 Two Common Collation URIs 618
30.2.3 Collation URI Syntax 618
30.2.4 Backward Compatibility with 3.1 Range Indexes and Lexicons 622
30.2.5 UCA Root Collation 622
30.2.6 How Collation Defaults are Determined 622
30.2.7 Specifying Collations 624
30.3 Collations and Character Sets By Language 624

31.0 Data Visualization Widgets 629
31.1 Overview of Visualization Widgets 630
31.2 Working with the Visualization Widgets 633
31.2.1 Building The Oscars Example Application 633
31.2.2 General Operation of Widgets 635
31.2.3 Working with the Line Chart Widget 636
31.2.4 Working with the Bar and Column Chart Widgets 637
31.2.5 Working with the Pie Chart Widget 639
31.2.6 Working with the Map Widget 640
31.3 Overview of the Widget Architecture 643
31.3.1 Widgets 643

31.3.2 Controller 644
31.3.3 Identification 644
31.3.4 Interaction within a Widget 644
31.3.5 Shadow Queries 645
31.4 Adding Visualization Widgets to an HTML Page 646
31.4.1 Common JavaScript And CSS In The <head> Element 646
31.4.2 Common Code In The <body> Element 647
31.4.3 Initialize the Display 648
31.5 Example: Adding Widgets to Applications 649
31.6 Visualization Widget Limitations 656
31.7 Set Up A Proxy 656
31.8 Widget API Reference 657
31.8.1 ML.controller Methods 657
31.8.2 ML.createWidget (Null Widget) Method 659
31.8.3 General Widget Methods 660
31.8.4 ML.chartWidget Method 661
31.8.5 ML.mapWidget Method 662
31.8.6 Widget Events 664
31.8.7 Widget Query Structure 665
31.8.8 Widget Query Update Structure 665
31.8.9 Search Results Format 665
31.8.10Facet Structure 666
31.8.11Internal Widget Events 667

32.0 Appendix: Query Options Reference 668
32.1 How to Use This Reference 669
32.2 Options Summary 669
32.3 additional-query 672
32.3.1 Syntax Summary 672
32.3.2 Component Description 673
32.3.3 Examples 673
32.3.4 See Also 673
32.4 concurrency-level 673
32.5 constraint 674
32.5.1 Syntax Summary 675
32.5.2 Component Description 676
32.5.3 Examples 677
32.5.4 See Also 677
32.5.5 range 677
32.5.6 value 683
32.5.7 word 687
32.5.8 collection 691
32.5.9 container 694
32.5.10element-query 696
32.5.11properties 698
32.5.12geo-attr-pair 699

32.5.13geo-elem 704
32.5.14geo-elem-pair 707
32.5.15geo-json-property 710
32.5.16geo-json-property-pair 714
32.5.17geo-path 717
32.5.18custom 721
32.5.19heatmap 724
32.5.20bucket 727
32.5.21computed-bucket 731
32.5.22path-index 735
32.6 debug 737
32.7 default-suggestion-source 737
32.7.1 Syntax Summary 738
32.7.2 Component Description 739
32.7.3 Examples 740
32.7.4 See Also 741
32.8 extract-document-data 742
32.8.1 Syntax Summary 743
32.8.2 Component Description 744
32.8.3 Examples 745
32.8.4 See Also 745
32.9 forest 745
32.10 fragment-scope 746
32.11 grammar 747
32.11.1Syntax Summary 747
32.11.2Component Description 748
32.11.3Examples 749
32.11.4See Also 750
32.11.5starter 750
32.11.6joiner 752
32.12 operator 755
32.12.1Syntax Summary 756
32.12.2Component Description 756
32.12.3Examples 758
32.12.4See Also 759
32.13 page-length 759
32.14 quality-weight 760
32.15 result-decorator 760
32.15.1Syntax Summary 761
32.15.2Component Description 761
32.15.3Examples 762
32.16 return-aggregates 762
32.17 return-constraints 763
32.18 return-facets 763
32.19 return-frequencies 764
32.20 return-metrics 764

32.21 return-plan 764
32.22 return-qtext 765
32.23 return-query 765
32.24 return-results 766
32.25 return-similar 766
32.26 return-values 767
32.27 search-option 767
32.28 searchable-expression 768
32.28.1Syntax Summary 769
32.28.2Component Description 769
32.28.3Examples 770
32.28.4See Also 770
32.29 sort-order 770
32.29.1Syntax Summary 771
32.29.2Component Description 772
32.29.3Examples 773
32.30 suggestion-source 774
32.30.1Syntax Summary 774
32.30.2Component Description 775
32.30.3Examples 776
32.30.4See Also 777
32.31 term 777
32.31.1Syntax Summary 778
32.31.2Component Description 779
32.31.3Examples 780
32.32 transform-results 782
32.32.1Syntax Summary 783
32.32.2Component Description 784
32.32.3Examples 785
32.32.4See Also 786
32.33 tuples 787
32.33.1Syntax Summary 787
32.33.2Component Description 788
32.33.3Examples 790
32.33.4See Also 790
32.34 values 791
32.34.1Syntax Summary 792
32.34.2Component Description 792
32.34.3Examples 794
32.34.4See Also 795
32.35 Term Options 796
32.36 Facet Options 796
32.37 Range Options 797
32.38 Geospatial Options 798
32.39 Suggestion Options 799
32.40 Values Options 799

33.0 Technical Support 801

34.0 Copyright 802
34.0 NOTICE 802

1.0 Developing Search Applications in MarkLogic Server

This chapter provides an overview of developing search applications in MarkLogic Server, and includes the following sections:

- Overview of Search Features in MarkLogic Server
- Where to Find Search Information

1.1 Overview of Search Features in MarkLogic Server

MarkLogic Server includes rich full-text search features. All of the search features are implemented as extension functions available in XQuery, and most of them are also available through the REST and Java interfaces. This section provides a brief overview some of the main search features in MarkLogic Server and includes the following parts:


- High Performance Full Text Search
- APIs for Multiple Programming Languages
- Support for Multiple Query Styles
- Support for Multiple Query Types
- Full XPath Search Support in XQuery
- Lexicon and Range Index-Based APIs
- Stemming, Wildcard, Spelling, and Much More Functionality
- Alerting API and Built-Ins

1.1.1 High Performance Full Text Search

MarkLogic Server is designed to scale to extremely large databases (100s of terabytes or more). All search functionality operates directly against the database, no matter what the database size. As part of loading a document, full-text indexes are created making arbitrary searches fast. Searches automatically use the indexes. Features such as the `xdmp:estimate` XQuery function and the `unfiltered` search option allow you to return results directly out of the MarkLogic indexes.

1.1.2 APIs for Multiple Programming Languages

MarkLogic Server provides search features through a set of layered APIs that support multiple programming languages. The following diagram illustrates the layering of the MarkLogic search APIs. These APIs are extensible and work in a large number of applications.



Note: Some tiers do not expose all the features of adjacent tiers.

The core text search foundation in MarkLogic Server is the cts API, a set of built-in XQuery functions in the `cts` namespace that perform full-text search. These capabilities are also exposed through Server-Side Javascript functions with a "cts." prefix.

The APIs above the cts foundation provide a higher level of abstraction that enables rapid development of search applications using XQuery, Java, or any programming language with support for making HTTP requests. For example, the XQuery Search API leverages cts functions such as `cts:search`, `cts:word-query`, and `cts:element-value-query`.

The Search API, `jsearch` API, and the Client APIs are sufficient for most applications. Use the cts built-ins for advanced application features, such as using reverse queries to create alerting applications and creating content classifiers. These higher level APIs offer benefits such as the following:

- Abstraction of queries from the constraints and indexes that support them.
- Built in support for search result snippeting, highlighting, and performance analysis.
- An extensible simple string query grammar.
- Easy-to-use syntax for query composition.
- Built in best practices that optimize performance.

You can use more than one of these APIs in an application. For example, a Java application can include an XQuery or Server-Side JavaScript extension to perform custom search result transformations on the server. Similarly, an XQuery application can call both `search:*` and `cts:*` functions.


1.1.3 Support for Multiple Query Styles

Each of the APIs described in "APIs for Multiple Programming Languages" on page 21 supports one or more input query styles for searching content and metadata, from simple string queries (`cat OR dog`) to XML or JSON representations of complex queries. Search results are returned in either raw or report form. The supported query styles and result format vary by API.

For example, the primary search function for the CTS API, `cts:search`, accepts input in the form of a `cts:query`, which is a composable query style that enables you to perform fine-grained searches. The `cts:search` function returns raw results as a sequence of matching nodes.

The Search, REST, Node.js and Java APIs accept more abstract query styles such as string and structured queries, and return results either in report form, as an XML `search:response` (or equivalent JSON structure) or matching documents. The customizable `search:response` can include details such as snippets with highlighting of matching terms and query metrics. The REST and Java APIs can also return the results report as JSON.

The following diagram summarizes the query styles and results formats each API provides for searching content and metadata:



The following table provides a brief description of each query style. The level of complexity of query construction increases as you read down the table.

Query Style	Supporting APIs	Description
String Query	all	Construct queries as text strings using a simple grammar of terms, phrases, and operators such as as AND and ">". String queries are easily composable by end users typing into a search text box. The `cts` and `jsearch` APIs use a slightly different grammar than the higher level APIs. For details, see "Creating a Query From Search Text With cts:parse" on page 245 and "Searching Using String Queries" on page 65.
Query By Example	• REST • Java • Node.js • jsearch	Construct queries in XML or JSON using syntax that resembles your document structure. Conceptually, Query By Example enables developers to quickly search for "documents that look like this". For details, see "Searching Using Query By Example" on page 186.
Structured Query	• Search • REST • Java • Node.js	Construct queries in JSON or XML using an Abstract Syntax Tree (AST) representation, while still taking advantage of Search API based abstractions and options. Useful for tweaking or adding to a query originally expressed as a string query. For details, see "Searching Using Structured Queries" on page 78.
Combined Query	• REST • Java • Node.js	Search using XML or JSON structures that bundle a string and/or structured query with query options. This enables searching without pre-defining query options as is otherwise required by the REST and Java APIs. For details, see Specifying Dynamic Query Options with Combined Query in *REST Application Developer's Guide* or Apply Dynamic Query Options to Document Searches in *Java Application Developer's Guide*
`cts:query`	• Search • jsearch • cts	Construct queries in XML from low level `cts:query` elements such as `cts:and-query` and `cts:not-query`. This representation is tree structured like Structured Query, but more complicated to work with. For details, see "Composing cts:query Expressions" on page 240. You can also compose cts:queries in Server-Side JavaScript using the `cts.*` constructors such as `cts.andQuery`.

1.1.4 Support for Multiple Query Types

A query encapsulates your search criteria. When you search for documents matching a query, your criteria fall into one or more of the query types described in this section, no matter what query style you use (string, structured, QBE, etc.).

The following query types are basic search building blocks that describe the content you want to match.

- Range: Match values that satisfy a relational expression. You can express conditions such as “less than 5” or “not equal to true”. A range query must be backed by a range index.
- Value: Match an entire literal value, such as a string or number, in a specific JSON property or XML element. By default, value queries use exact match semantics. For example, a search for “mark” will not match “Mark Twain”.
- Word: Match a word or phrase in a specific JSON property, XML element, or XML attribute. In contrast to a value query, a word query will match a subset of a text value and does not not use exact match semantics by default. For example, a search for “mark” will match “Mark Twain” in a specific context.
- Term: Match a word or phrase anywhere it appears. In contrast to a value query, a term query will match a subset of a text value and does not use exact match semantics by default. For example, a search for “mark” will match “Mark Twain” anywhere it appears in a document.

Additional query types enable you to build up complex queries by combining the basic content queries with each other and with criteria that add additional constraints. The additional query types fall into the following categories.

- Logical Composers: Express logical relationships between criteria. You can build up compound logical expressions such as “*x* AND (*y* OR *z*)”.
- Document Selectors: Select documents based on collection, directory, or URI. For example, you can express criteria such as “*x* only when it occurs in documents in collection *y*”.
- Location Qualifiers: Further limit results based on where the match appears. For example, “*x* only when contained in JSON property *z*”, or “*x* only when it occurs within *n* words of *y*”, or “*x* only when it occurs in a document property”.

The CTS API includes query constructors for all the above query types, such as `cts:*-range-query`, `cts:*-value-query`, `cts:*-word-query`, `cts:and-query`, `cts:collection-query`, and `cts:near-query`. For details, see “Composing cts:query Expressions” on page 240.

With no additional configuration, string queries support term queries and logical composers. For example, the query string “cat AND dog” is implicitly two term queries, joined by an “and” logical composer. However, you can easily extend the expressive power of a string query using constraint bindings to enable additional query types. For example, if you use a range constraint binding to tie the identifier “cost” to a specific indexed JSON property, you enable string queries of the form “cost GT 10”. For details, see “Searching Using String Queries” on page 65.

In a QBE, content matches are value queries by default. For example, a QBE search criteria of the form `{'my-key': 'desired-value'}` is implicitly a value query for the JSON property `'my-key'` whose value is exactly `'desired-value'`. However, the QBE syntax includes special property names that enable you to construct other types of query. For example, use `$word` to create a word query instead of a value query: `{'my-key': {'$word': 'desired-value'}}`. For details, see “Searching Using Query By Example” on page 186.

Structured query includes components that encompass all the query types, such as value-query, range-query, term-query, and-query, and directory-query. Some of the Client APIs include a structured query builder interface to assist you with structured query composition. For details, see “Searching Using Structured Queries” on page 78.

1.1.5 Full XPath Search Support in XQuery

MarkLogic Server implements the XQuery language, which includes XPath 2.0. XPath expressions are searches which can search XML across the entire database. For example, consider the following XPath expression:

```
/my-node/my-child[fn:contains(., "hello")]
```

This expression searches across the entire database returning `my-child` nodes that match the expression. XPath expressions take full advantage of the indexes in the database and are designed to be fast.

MarkLogic Server extends XPath so that you can also use it to address JSON content. For details, see Traversing JSON Documents Using XPath in the *Application Developer's Guide*.

1.1.6 Lexicon and Range Index-Based APIs

MarkLogic Server enables you to define range indexes which index XML structures such as elements, element attributes; XPath expressions; and JSON properties. You can also define range indexes over geospatial values. Each of these range indexes has lexicon APIs associated with them. The lexicon APIs enable you to return values directly from the indexes. Lexicons are very useful in constructing facets and in finding fast counts of XML element, XML attribute, and JSON property values. The Search API and Node.js, Java, and REST Client APIs makes extensive use of the lexicon features. For details about lexicons, see “Browsing With Lexicons” on page 431.

1.1.7 Stemming, Wildcard, Spelling, and Much More Functionality

MarkLogic Server search supports a wide range of full-text features. These features include stemming, wildcarded searches, diacritic-sensitive/insensitive searches, case-sensitive/insensitive searches, spelling correction functions, thesaurus functions, geospatial searches, advanced language and collation support, and much more. These features are all designed to build off of each other and work together in an extensible and flexible way.

1.1.8 Alerting API and Built-Ins

You can create applications that notify users when new content is available that matches a predefined query. There is an API to help build these applications as well as a built-in `cts:query` constructor (`cts:reverse-query`) and indexing support to build large and scalable alerting applications. For details on alerting applications, see "Creating Alerting Applications" on page 491.

1.2 Where to Find Search Information

The *MarkLogic XQuery and XSLT Function Reference* contains the XQuery function signatures and descriptions, as well as many code examples. This *Search Developer's Guide* contains descriptions and technical details about the search features in MarkLogic Server, including:

- "Search API: Understanding and Using" on page 28
- "Composing cts:query Expressions" on page 240
- "Relevance Scores: Understanding and Customizing" on page 408
- "Browsing With Lexicons" on page 431
- "Using Range Queries in cts:query Expressions" on page 445
- "Highlighting Search Term Matches" on page 454
- "Geospatial Search Applications" on page 462
- "Marking Up Documents With Entity Enrichment" on page 489
- "Creating Alerting Applications" on page 491
- "Using fn:count vs. xdmp:estimate" on page 502
- "Understanding and Using Stemmed Searches" on page 507
- "Understanding and Using Wildcard Searches" on page 526
- "Collections" on page 536
- "Using the Thesaurus Functions" on page 544
- "Using the Spelling Correction Functions" on page 557
- "Language Support in MarkLogic Server" on page 594
- "Encodings and Collations" on page 616

For other information about developing applications in MarkLogic Server, see the *Application Developer's Guide*. For information about XQuery in MarkLogic Server, see the *XQuery and XSLT Reference Guide*.

2.0 Search API: Understanding and Using

This chapter describes the Search API, which is an XQuery API designed to make it easy to create search applications that contain facets, search results, and snippets. This chapter includes the following sections:

- Understanding the Search API
- Controlling a Search With Query Options
- Search Term Completion Using search:suggest
- Creating a Custom Constraint
- Search Grammar
- Returning Lexicon Values With search:values
- JSON Support in the Search API
- More Search API Examples

This chapter provides background, design patterns, and examples of using the Search API. For the function signatures and descriptions, see the Search documentation under XQuery Library Modules in the *MarkLogic XQuery and XSLT Function Reference*.

2.1 Understanding the Search API

The Search API is an XQuery library that combines searching, search parsing, search grammar, faceting, snippeting, search term completion, and other search application features into a single API. You can interact with the Search API through XQuery, REST, Node.js, and Java, using a variety of query styles, as described in "Support for Multiple Query Styles" on page 22.

The Search API makes it easy to create search applications without needing to understand many of the details of the underlying `cts:search` and `cts:query` APIs. The Search API is designed for large-scale, production applications.

This section provides an overview and describes some of the features of the Search API, and contains the following topics:

- Making the Search API Available to Your Application
- Simple search:search Example and Response Output
- Automatic Query Text Parsing and Grammar
- Constrained Searches and Faceted Navigation
- Built-In Snippetting
- Search Term Completion

- Search Customization Via Options and Extensions
- Speed and Accuracy

2.1.1 Making the Search API Available to Your Application

The Search API is implemented as an XQuery library module. You can use it directly from XQuery. You can also access most of the Search API features through the REST, Node.js, and Java Client APIs; for details, see *REST Application Developer's Guide*, *Node.js Application Developer's Guide*, or *Java Application Developer's Guide*. Server-Side JavaScript applications can access similar features through the JSearch library; for details, see "Creating JavaScript Search Applications" on page 278.

To use the Search API from XQuery, import the Search API library module into your XQuery module with the following prolog statement:

```
import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";
```

The Search API uses the namespace prefix `search:`, which is not predefined in the server. The Search API has the following core functions to perform searches and provide search results, snippets, and query-completion suggestions: `search:search`, `search:snippet`, and `search:suggest`. There are also other functions to perform these activities at finer granularities and to provide convenience tools.

For the Search API function signatures and details about each individual function, see the *MarkLogic XQuery and XSLT Function Reference* for the Search API.

2.1.2 Simple search:search Example and Response Output

The `search:search` function takes search terms, parses them into an appropriate `cts:query`, and returns a response with snippets and URIs for matching nodes in the database. You can get started with the Search API with a very simple query:

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

search:search("hello world")
=>
<search:response total="1" start="1" page-length="10" xmlns=""
  xmlns:search="http://marklogic.com/appservices/search">
  <search:result index="1" uri="/hello.xml"
    path="doc(&amp;quot;/hello.xml&amp;quot;)" score="136"
    confidence="0.67393" fitness="0.67393">
    <search:snippet>
```

```
        <search:match path="doc(&quot;/hello.xml&quot;)/hello">This is
          where you say "<search:highlight>Hello</search:highlight>
          <search:highlight>World</search:highlight>".
        </search:match>
      </search:snippet>
    </search:result>
    <search:qtext>hello world</search:qtext>
    <search:metrics>
      <search:query-resolution-time>PT0.328S
        </search:query-resolution-time>
      <search:total-time>PT0.352S</search:total-time>
    </search:metrics>
  </search:response>
```

The output is a `search:response` element, and it contains everything needed to build a search results page. It includes an estimate of the total number of documents that match the search, the URI and XPath for each result, pagination of the search results, a snippet of the result content, the original query text submitted, and metrics on the response time. You can customize the data returned in each `search:result` using the `result-decorator` query option.

To try the Search API on your own content, run a simple search like the above example against a database of your own content, and then examine the search results.

The `search:search` function is highly customizable, but by default it includes sensible settings that will provide good results for many applications. With the results of `search:search`, it is easy to build useful results pages that are as simple or as complex as you like.

2.1.3 Automatic Query Text Parsing and Grammar

In a typical search application, a user enters query text into a search box in a browser. This text is a *string query*. The Search API automatically parses a string query into a `cts:query` for efficient and powerful searches. You can use string queries in XQuery, Java, Node.js, and REST, through interfaces such as the following:

- XQuery: The `search:search, search:parse`, and `search:resolve` functions
- Java: The `com.marklogic.client.query.QueryManager` class
- Node.js: The `DatabaseClient.documents.query` and `queryBuilder.parsedFrom` functions.
- REST: The `/search` service

The default string query grammar is similar to the Google grammar. The default grammar supports simple terms and double-quoted phrases, logical and relational operators (`AND`, `OR`, `LT`, `GT`), grouping with parentheses (`( )`), negation with a minus sign (`-`), and user-configured constraints with a colon (`:`).

The following is a summary of the default grammar. For details, see “The Default String Query Grammar” on page 66.

- Terms can be free standing:

```
cat
```

- AND and OR operators, with AND having higher precedence.
- Parentheses can override default precedence:

```
(cat OR dog) AND horse
```

- Multiple terms are combined as an AND:

```
cat dog
```

- Phrases are surrounded by double-quotes:

```
"cat and dog"
```

- Terms are excluded through a leading minus:

```
cat -dog
```

- Colon operators indicate configured constraint or operator searches (for details, see "Constraint Options" on page 369 and "Operator Options" on page 382):

```
tag:value
```

- Constraint and operator searches may operate over phrases:

```
tag:"a phrase value"
```

- A query text can comprise any number of these types of searches in any order.
- The default precedence for a search order provides preference to explicitly ordered (with parenthesis, for example) then for implicitly ordered. Therefore, multi-term queries using the explicit AND operator do not parse as equivalent to the same string using the implicit AND because there is a difference in the way that precedence is applied. For example, `A OR B AND C` parses to the equivalent of `A OR (B AND C)`, while `A OR B C` parses to the equivalent of `(A OR B) and C`.

String query parsing takes into account constraints and operators specified in an options node at search runtime. Additionally, you can change, extend, and modify the default search parsing grammar in the options node. Most applications will not need to modify the search grammar, as the default grammar is quite robust and full-featured. For details on modifying the default grammar, see "Modifying and Extending the String Query Grammar" on page 71. For details on the options node for the Search API, see "Controlling a Search With Query Options" on page 35.


2.1.4 Constrained Searches and Faceted Navigation

The Search API makes it easy to constrain your searches to a subset of the content. For example, you can create a search that only returns results for documents with titles that include the word `hello`, or you can create a search that constrains the results to a particular decade. The default string query grammar makes it easy to express these kinds of searches in a simple query text string. For example, you create a constraint through query options such that the following string query represents a search that constrains matches to a particular decade:

```
decade:2000s
```

These types of searches are useful in creating facets, which allow a user to drill down by narrowing the search criteria. Facets also typically have counts of the number of results that match. The Search, REST, Node.js, and Java Client APIs return these counts to use in facets.

The following is an example of a facet in an end-user application:



Users can click on any of the links to narrow the results of the search by decade. For example, the query generated by clicking the top link contains the string `decade:2000s`, and constrains the search to that decade.

The facet also includes counts for each constraint value. The number to the right of the link represents the number of search results returned if you constrain it to that decade.

The Search API returns XML in its response that contains all of the information to create a facet like the above example. The REST and Java Client APIs can return this information as XML or JSON; the Node.js Client API returns this information as JSON.

The facets returned by a search include the counts and values needed to generate the user interface. For example, the following XML, returned from the Search API, was used to create the above facet:

```
<search:response total="2370" start="1" page-length="10" xmlns=""
   xmlns:search="http://marklogic.com/appservices/search">
  <search:facet name="decade">
    <search:facet-value name="2000s" count="240">
     2000s</search:facet-value>
    <search:facet-value name="1990s" count="300">
     1990s</search:facet-value>
    <search:facet-value name="1980s" count="300">
     1980s</search:facet-value>
    <search:facet-value name="1970s" count="300">
     1970s</search:facet-value>
    <search:facet-value name="1960s" count="299">
     1960s</search:facet-value>
    <search:facet-value name="1950s" count="300">
     1950s</search:facet-value>
    <search:facet-value name="1940s" count="324">
     1940s</search:facet-value>
    <search:facet-value name="1930s" count="245">
     1930s</search:facet-value>
    <search:facet-value name="1920s" count="61">
     1920s</search:facet-value>
  </search:facet>
</search:response>
```

The counts and values in the response are also filtered by any other active query in the search, so they represent the counts for that particular search.

You can generate facets from range, collection, geospatial, and custom constraints. To generate facets from a constraint and include them in your search results, set the `facet` XML attribute or JSON property to true on a constraint definition in your search options. For example:

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="subject">
    <collection prefix="/my-collections/" facet="true" />
  </constraint>
</options>
```

For more details, see “Appendix: Query Options Reference” on page 668.

There are many kinds of constraints and facets you can build with the Search, REST, and Java APIs. For more details about constraints, see “Constraint Options” on page 369.

2.1.5 Built-In Snippetting

A search results page typically shows portions of matching documents with the search matches highlighted, perhaps with some text showing the context of the search matches. These search result pieces are known as *snippets*. For example, a search for `MarkLogic Server` might produce the following snippet:

```
MarkLogic Server is an XML Server that provides the agility you need
to build and ... Use MarkLogic Server's geospatial capability to
create new dynamic ...
```

The Search API and the Node.js, Java, and REST Client APIs include snippets in the `search:response` output, making it easy to create search results pages that show the matches in the context of the document. Providing the best snippet for a given content set is often very application specific, however. Therefore, the Search API allows you to customize the snippets, either using the built-in snippetting algorithm or by adding your own snippetting code. For details on ways to customize the snippetting behavior for your searches, see "Modifying Your Snippet Results" on page 387.

2.1.6 Search Term Completion

Search applications often offer suggestions for search terms as the user types into the search box. The suggestions are based on terms that are in the database, and are typically used to make the user interface more interactive and to quickly suggest search terms that are appropriate to the application. The `search:suggest` function in the Search API is designed to supply the terms to a search-completion user interface. For more details on how to use search term completion, see "Search Term Completion Using search:suggest" on page 36.

2.1.7 Search Customization Via Options and Extensions

The Search, REST and Java APIs make it easy to customize your searches. A wide range of customizations are available directly through the query options that you pass into the search. There are a large number of options controlling nearly every aspect of the search you are performing.

For cases where the built-in options do not do what you need, there is an XQuery extension mechanism. The mechanism includes hooks which allow you to call out to your own XQuery code. The hooks allow you to specify the location and name of the function containing your own implementation of a function to replace the implementation of that function in the Search API. The Search API uses function values to pass your custom function as a parameter, replacing the default Search API functionality. For details on function values, see Function Values in the *Application Developer's Guide*.

The basic pattern to specify your extension function using the attributes `apply`, `ns`, and `at` as attributes on various elements in the `search:options` node. These correspond to the localname of your implemented function, the namespace of the function, and the location of the function library module in which the code exists, respectively. For example, consider the following:

```
<transform-results apply="my-snippet" ns="my-namespace"
     at="/my-module.xqy" />
```

In this example, the `transform-results` option specifies to use the `my-snippet` function in the library module `my-module` under your App Server root instead of the default snippeting function that the Search API uses. For additional details about working with `transform-results`, see "Modifying Your Snippet Results" on page 387.

Any search option that has an `apply` attribute can use this extension pattern to point to your own implementation for the functionality of that option, including `transform-results`, several `grammar` options, `custom` constraints, and so on.

2.1.8 Speed and Accuracy

The Search API, and the Client APIs (Node.js, Java, REST) that build upon it, are designed to be fast. When creating any search application, you make trade-offs between speed and guaranteed accuracy. The values of various options in the Search API control things like filtered versus unfiltered search, diacritic and case-sensitivity, and other options. These options affect the accuracy of search estimates in MarkLogic Server. The default values of these query options are designed to be sensible for most application. All applications are different, however, and MarkLogic gives you the tools to control what makes sense for your specific application.

Range constraints use lexicons to get fast accurate unique values and counts. Keep in mind, however, that certain operations might not produce accurate counts in all cases. For example, when you pass a `cts:query` into a lexicon API (which the Search API does in some cases), it filters the lexicon calls based on the index resolution of the `cts:query`, not on the filtered search values, and the index resolution is not guaranteed to be accurate for all queries. For details on how search index resolution works, see Fast Pagination and Unfiltered Searches in *Query Performance and Tuning Guide*.

Other factors such as fragmentation and what you search for (`searchable-expression` in the Search API options) can also contribute to whether the index resolution for a search is correct, as can various options to lexicons. The default values for these various options make the trade-offs that are sensible for many search applications. For example, the value of the `total` attribute in the `search:response` output is the result of a `cts:remainder`, which will always be fast but is not guaranteed to be accurate for all searches. For details, see "Using fn:count vs. xdmp:estimate" on page 502.

2.2 Controlling a Search With Query Options

Most search operations in the XQuery Search API and the Client APIs make use of optional query options. Query options enable you to specify the behavior and results format for a search. Default query options are pre-defined. You can override the defaults by supplying custom query options. For example, the XQuery function `search:search` accepts a `search:options` XML node as input.

The REST and Java Client APIs supports query options expressed in either JSON or XML. The Node.js Client API abstracts the representation from your application, but in most cases, this API uses the JSON representation.

For more details, see "Search Customization Using Query Options" on page 368 and "Appendix: Query Options Reference" on page 668.

2.3 Search Term Completion Using search:suggest

The `search:suggest` function returns suggestions that match a wildcarded string, and it is used in query-completion applications. For an example of an application that uses `search:suggest`, see the Oscars sample application that you can generate with Application Builder, as described in Building the Oscars Sample Application in the *Application Builder Developer's Guide*.

A typical way to use the `search:suggest` function in an application is to have a Javascript event listen for changes in the text box, and then upon those changes it asynchronously submits a `search:suggest` call to MarkLogic Server. The result is that, after every letter is typed in, new suggestions appear in the user interface. The remainder of this sections describes the following details of the search:suggest function:

- default-suggestion-source Option
- Choose Suggestions With the suggestion-source Option
- Use Multiple Query Text Inputs to search:suggest
- Make Suggestions Based on Cursor Position
- search:suggest Examples

For information on using this feature with the Client APIs, see the following:

- REST: Generating Search Term Completion Suggestions in the *REST Application Developer's Guide*.
- Java: Generating Search Term Completion Suggestions in the *Java Application Developer's Guide*.
- Node.js: Generating Search Term Completion Suggestions in the *Node.js Application Developer's Guide*.

2.3.1 default-suggestion-source Option

To use `search:suggest`, it is best to specify a `default-suggestion-source`. The Search API uses the `default-suggestion-source` to look for search term suggestions. If no `default-suggestion-source` is specified, then any call to `search:suggest` returns only suggestions for constraints and operators, or if there are none, then it returns the empty sequence.

The `search:suggest` function suggests constraint and operator names if they match the query text string, and in the case of range index-based constraints, it will suggest matching constraint values. For details on the syntax of the `default-suggestion-source` option, see the `search:search` options documentation in the *MarkLogic XQuery and XSLT Function Reference*.

For best performance, especially on large databases, use with a `default-suggestion-source` with a `range` or `collection` instead of one with a `word` lexicon.

The following `default-suggestion-source` example uses the string range index on the attribute named `my-attribute` as a source for suggesting terms. Range suggestion sources tend to perform the best, especially for large databases. The range index must exist or an exception is thrown at search runtime.

```
<default-suggestion-source>
  <range type="xs:string">
    <element ns="my-namespace" name="my-localname"/>
    <attribute ns="" name="my-attribute"/>
   </range>
</default-suggestion-source>
```

The following example specifies using a field lexicon to look for search term suggestions. Fields can work well for suggestion sources, especially if the field is a relatively small subset of the whole database. A field word lexicon for the specified field must exist or an exception is thrown at search runtime.

```
<default-suggestion-source>
    <word collation="http://marklogic.com/collation/">
        <field name="my-field"/>
    </word>
</default-suggestion-source>
```

For more details, see “default-suggestion-source” on page 737.

2.3.2 Choose Suggestions With the suggestion-source Option

For some applications, you want to have a very specific list from which to choose suggestions for a particular constraint. For example, you might have a constraint named name that has millions of unique values, but perhaps you only want to make suggestions for a specific 500 of them. In such cases, you can specify the `suggestion-source` option to override the suggestions that `search:suggest` returns for query text matching values in that constraint.

You specify the constraint to override in the in the `name` attribute of the `suggestion-source` element. For example, the following options specify to use the values from the `short-list-name` element instead of from the `name` element when make suggestions for the `name` constraint.

```
<constraint name="name">
   <range collation="http://marklogic.com/collation"
          type="xs:string" facet="true">
```

```
      <element ns="my-namespace" name="fullname"/>
    </range>
  </constraint>
  <suggestion-source ref="name">
      <range collation="http://marklogic.com/collation"
           type="xs:string" facet="true">
       <element ns="my-namespace" name="short-list-name"/>
    </range>
  </suggestion-source>
```

For cases where you have a named constraint to use for searching and facets, but might want to use a slightly (or completely) different source for type-ahead suggestions without needing to re-parse your search terms, use the `suggestion-source` option.

If you want a particular constraint to not return suggestion, add an empty `suggestion-source` for that constraint:


```
<suggestion-source ref="socialsecuritynumber" />
```

For more details, see "suggestion-source" on page 774.

2.3.3 Use Multiple Query Text Inputs to search:suggest

You can specify one or more query text parameters to `search:suggest`. When you specify a sequence of more than one query text for `search:search`, the first item (or the one corresponding to the `$focus` parameter) specifies the text to match against the suggestion source. Each of the other items in the sequence is parsed as a `cts:query`, and that query is used to constrain the search suggestions from the text-matching query text. Note that this is different from the other Search API functions, which combine multiple query texts with a `cts:and-query`.

Consider a user interface that looks as follows:



The search text box on top is where the user types text. The lower check box might be another control that the user can use to specify the decade. The `decade:1980s` text shown might be the query text that is the result of that user interface control (possibly from a facet, for example). You can then construct a `search:suggest` call from this user interface that uses the `decade:1980s` text as a constraint to the terms matching `comp` (from the specified suggestion source). The following is a `search:suggest` call that can be generated from this example:

```
search:suggest(("comp", "decade:1980s"), $options)
```

This ends up returning suggestions that match `comp*` on fragments that match `search:parse("decade:1980s")`. For example, it might return a sequence including the words `competent`, `component`, and `computer`.

2.3.4 Make Suggestions Based on Cursor Position

The `search:suggest` function makes search suggestions based on the position of the cursor (which you specify with the `$cursor-position` parameter. The idea is that when the user changes the cursor position, you should suggest terms based on where the user is currently entering text.

2.3.5 search:suggest Examples

The following are some example `search:suggest` queries with sample output.

Assume a constraint named filesize for the following example:

```
search:suggest("fi", $options)

(: Returns the "filesize" constraint name first, followed
   by words from the default source of word suggestions:

  ("filesize:", "field", "file", "fitness", "five",)  :)
```

The following example shows how search:suggest works with bucketed `range` constraints:

```
(: Assume $options contains the following:
  <constraint name="date">
   <range type="xs:dateTime">
      <bucket name="today">
      <bucket name="yesterday">
      <bucket name="thismonth">
      <bucket name="thisyear">
...

:)
search:suggest("date:", $options)
(: bucket names from the "date" range constraint are
   used to create suggestions

("date:thismonth", "date:thisyear", "date:today", "date:yesterday") :)
```

2.4 Creating a Custom Constraint

By default, the Search API supports many, but not all, types of constraints. If you need to create a constraint for which there is not one pre-defined in the Search API, there is a mechanism to extend the Search API to use your own constraint type. This type of constraint, called a `custom` constraint, requires you to write XQuery functions to implement your own custom parsing and to generate your own custom facets. You specify your function implementations in the options XML as follows:

```
<constraint name="my-custom">
    <custom facet="true"> <!-- or false -->
       <parse apply="parse" ns="..." at="..." />
       <start-facet apply="start" ns="..." at="..." />
       <finish-facet apply="finish" ns="..." at="..." />
    </custom>
</constraint>
```

The three functions you need to implement are `parse`, `start-facet`, and `finish-facet`. The `apply` attribute specifies the localname of the function, the `ns` attribute specifies the namespace, and the `at` attribute specifies the location of the module containing the function. This section describes how to create a custom constraint and includes some example code for creating a custom geospatial constraint. This section includes the following parts:

- Implementing the parse Function
- Implementing the start-facet Function
- Implementing the finish-facet Function
- Example: Creating a Simple Custom Constraint
- Example: Creating a Custom Constraint for Structured Queries
- Example: Creating a Custom Constraint Geospatial Facet

2.4.1 Implementing the parse Function

The purpose of the `parse` function is to parse the custom constraint and generate the correct `cts:query` from the query text.

This section covers the following topics:

- Choosing a Parser Interface
- Implementing a String Query parse Function
- Implementing a Structured Query parse Function
- Implementing a Multi-Format parse Function

2.4.1.1 Choosing a Parser Interface

The signature of your constraint parsing function varies depending on the type of query input (string query or structured query) and the API through which you make your queries.

If your constraint can be used in queries initiated from XQuery, such as by calling `cts:search` or `search:search`, choose one of the following solutions:

- If the input is always a string query, see "Implementing a String Query parse Function" on page 41.
- If the input is always a structure query, see "Implementing a Structured Query parse Function" on page 42.
- If the input can be either a string or structured query, see "Implementing a Multi-Format parse Function" on page 42.

If your constraint is only used in queries initiated through the REST, Java, or Node.js Client API and never through XQuery, you can use the structured query parse interface to service both string and structured queries; your query is converted internally as needed. The selections described above for XQuery are also usable with the REST, Node.js and Java Client APIs.

2.4.1.2 Implementing a String Query parse Function

For parsing your custom constraint in a string query, the custom function you implement must have a signature compatible with the following signature:

```
declare function example:parse-string(
  $constraint-qtext as xs:string,
  $right as schema-element(cts:query))
as schema-element(cts:query)
```

You can use any namespace and localname for the function, but the number and order of the parameters must be compatible and the return type must be compatible.

The `$constraint-qtext` parameter is the constraint name and joiner part of the query text *for the portion of the query pertaining to this constraint*. For example, if the constraint name is `geo` and the joiner is the default joiner, then the value of `$constraint-qtext` will be `geo:`. The `$constraint-qtext` value is used in the `qtextconst` attribute, which is needed by `search:unparse` to re-create the query text from the annotated `cts:query`.

The `$right` parameter contains the value of the constraint parsed as a `cts:query`. In other words, it is the text to the right of what is passed into `$constraint-qtext` in the query text, and then that text is parsed by the Search API as a `cts:query`, and returned to the parse function as the XML representation of a `cts:query`. The value of `$right` is what the parse function uses for generating its custom `cts:query`. For details on how `cts:query` constructors work, see "Composing cts:query Expressions" on page 240.

The `parse` function you implement takes the `cts:query` from the `$right` parameter, parses it as you see fit, and then returns a `cts:query` XML element. For example, if the value of `$right` is as follows:

```
<cts:word-query>
  <cts:text>1@2@3@4</cts:text>
</cts:word-query>
```

Your code must process the `cts:text` element to construct the cts:query you need. For example, you can tokenize on the `@` character of the `cts:text` element, then use each value to construct a part of the query. As part of constructing the `cts:query`, you can optionally add `cts:annotation` elements and annotation attributes to the `cts:query` you generate. These annotations allow the Search API to unparse the `cts:query` back into its original form. If you do not add the proper annotations, then `search:unparse` might not return the original query text. For a sample function that does something similar, see "Example: Creating a Custom Constraint Geospatial Facet" on page 48.

2.4.1.3 Implementing a Structured Query parse Function

To use a custom constraint in a structured query, your custom parse function must have a signature compatible with the following:

```
declare function example:parse-structured(
  $query-elem as element(),
  $options as element(search:options))
as schema-element(cts:query)
```

You can use any namespace and localname for the function, but the number and order of the parameters must be compatible and the return type must be compatible. For a full example, see "Example: Creating a Custom Constraint for Structured Queries" on page 46.

The `$query-elem` parameter is `custom-constraint-query` structured query that references your constraint. For details, see "custom-constraint-query" on page 171.

2.4.1.4 Implementing a Multi-Format parse Function

You can create a single parse function capable of handling either a string query or a structured query as input by generalizing the parse function interface to accomodate both and using the XQuery `instance of` operator to determine the query type.

The following parse function skeleton generalizes the input query as an `item()` and the second parameter, which can be either a `cts:query` or `search:options`, to `element()`, and then uses `instance of` to detect the actual input query type:

```
declare function example:combo-parser(
  $query as item(),
  $right-or-option as element())
as schema-element(cts:query)
```

```
{
  if ($query instance of element(search:query))
  then ... (: handle as structured query :)
  else if ($query instance of xs:string)
  then ... (: handle as string query :)
  else ... (: error :)
};
```

Once you determine the input query type, coerce the second parameter to the correct type and parse your query as you would in the appropriate string or structured query parse function, as described in "Implementing a String Query parse Function" on page 41 and "Implementing a Structured Query parse Function" on page 42.

2.4.2 Implementing the start-facet Function

The sole purpose of the `start-facet` function is to make a lexicon API call that returns the values and counts that are used in constructing a facet. For details on lexicons, see "Browsing With Lexicons" on page 431. The custom function you implement must have a signature compatible with the following signature:

```
declare function my-namespace:start-facet(
  $constraint as element(search:constraint),
  $query as cts:query?,
  $facet-options as xs:string*,
  $quality-weight as xs:double?,
  $forests as xs:unsignedLong*)
as item()*
```

You can use any namespace and localname for the function, but the number and order of the parameters must be compatible and the return type must be compatible.

Each of the parameters is passed into the function by the Search API. The `$query` parameter includes any custom query your `parse` function implements, combined with any other query that the Search API generates (which depends on other options passed into the original search such as `additional-query`). All other parameters are specified in the `search:options` XML node passed into the Search API call. You can choose to use them or not, as is needed to perform your custom action.

When implementing a lexicon call in the `start-facet` function, you must add the `"concurrent"` option to the `$facet-options` parameter and use the combined sequence as input to the `$options` parameter of the lexicon API. The `"concurrent"` option takes advantage of concurrency, and can greatly speed performance, especially for applications with many facets. For a sample function, see "Example: Creating a Custom Constraint Geospatial Facet" on page 48.

Note: The `start-facet` function is optional, but is the recommended way to create a custom facet that uses any of the MarkLogic Server lexicon functions. If you do not use the `start-facet` function, then the `finish-facet` function must do all of the work to construct the facet (including constructing the values for the facet). For

details on the lexicon functions, see the *MarkLogic XQuery and XSLT Function Reference* and "Browsing With Lexicons" on page 431.

2.4.3 Implementing the finish-facet Function

The `finish-facet` function takes input from the `start-facet` function (if it is used) and constructs the `facet` element. This function must have a signature compatible with the following signature:

```
declare function my-namespace:finish-facet(
  $start as item()*,
  $constraint as element(search:constraint),
  $query as cts:query?,
  $facet-options as xs:string*,
  $quality-weight as xs:double?,
  $forests as xs:unsignedLong*)
as element(search:facet)
```

You can use any namespace and localname for the function, but the number and order of the parameters must be compatible and the return type must be compatible.

The parameters are passed into the function by the Search API. The `$query` parameter includes any custom query your `parse` function implemented, combined with any other query that the Search API generates (which depends on other options passed in to the original search such as `additional-query`). All of the remaining parameters are specified in the `search:options` XML passed into the Search API call. You can choose to use them or not, as is needed to perform your custom action. For a sample function, see "Example: Creating a Custom Constraint Geospatial Facet" on page 48.

If you do not use a `start-facet` function, then the empty sequence is passed in for the `$start` parameter. If you are not using a `start-facet` function, then the `finish-facet` function is responsible for constructing the values and counts used in the facet, as well as creating the facet XML.

2.4.4 Example: Creating a Simple Custom Constraint

The following is a library module that implements a very simple custom constraint for use with string queries. This constraint adds a `cts:directory-query` for the values specified in the constraint. This constraint has no facets, so it does not need the `start-facet` and `finish-facet` functions. This code does very minimal parsing; your actual code might parse the `$right` query more carefully.

```
xquery version "1.0-ml";
module namespace my="my-namespace";

declare variable $prefix := "/mydocs/" ;

declare function part(
  $constraint-qtext as xs:string,
  $right as schema-element(cts:query))
as schema-element(cts:query)
{
let $query :=
<root>{
  let $s := fn:string($right//cts:text/text())
  let $dir :=
    if ( $s eq "book")
    then fn:concat($prefix, "book-dir/")
    else if ( $s eq "api")
    then ( fn:concat($prefix, "api-dir1/"),
           fn:concat($prefix, "api-dir2/") )
    (: if it does not match, just constrain on the prefix :)
    else $prefix
  return
  (: make these an or-query so you can look through several dirs :)
    cts:or-query((
    for $x in $dir
    return
      cts:directory-query($x, "infinity")
    ))
    }
</root>/*
return
(: add qtextconst attribute so that search:unparse will work -
   required for some search library functions :)
element { fn:node-name($query) }
  { attribute qtextconst {
      fn:concat($constraint-qtext, fn:string($right//cts:text)) },
    $query/@*,
    $query/node()}
} ;
```

If you put this module in a file named `my-module.xqy` your App Server root, you can run this constraint with the following options node:

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="part">
    <custom facet="false">
      <parse apply="part" ns="my-namespace" at="/my-module.xqy"/>
    </custom>
  </constraint>
</options>
```

The following query text results in constraining this search to the `/mydocs/book-dir/` directory:

```
part:book
```

2.4.5 Example: Creating a Custom Constraint for Structured Queries

The following is a library module that implements a very simple custom constraint to be used with structured queries. This constraint adds a `cts:directory-query` for the values specified in the constraint. This constraint has no facets, so it does not need the `start-facet` and `finish-facet` functions.

```
xquery version "1.0-ml";

module namespace my = "my-namespace";
import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

declare variable $prefix := "/mydocs/" ;

declare function part(
  $query-elem as element(),
  $options as element(search:options)
) as schema-element(cts:query)
{
let $query :=
<root>{
  let $s := $query-elem/search:text/text()
  let $dir :=
    if ( $s eq "book")
    then fn:concat($prefix, "book-dir/")
    else if ( $s eq "api")
    then ( fn:concat($prefix, "api-dir1/"),
           fn:concat($prefix, "api-dir2/") )
    (: if it does not match, just constrain on the prefix :)
    else $prefix
  return
  (: make these an or-query so you can look through several dirs :)
    cts:or-query((
    for $x in $dir
    return
```

```
      cts:directory-query($x, "infinity")
    ))
    }
</root>/*
return
(: add qtextconst attribute so that search:unparse will work -
   required for some search library functions :)
element { fn:node-name($query) }
  { attribute qtextconst {
      fn:concat(
        $query-elem/search:constraint-name, ":",
        $query-elem/search:text/text()) },
    $query/@*,
    $query/node()}
} ;
```

If you put this module in a file named `my-module.xqy` your App Server root, you can run this constraint with the following options node:

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="part">
    <custom facet="false">
      <parse apply="part" ns="my-namespace" at="/my-module.xqy"/>
    </custom>
  </constraint>
</options>
```

The following structured query constrains the search to the `/mydocs/book-dir/` directory:

```
<query xmlns="http://marklogic.com/appservices/search">
  <custom-constraint-query>
    <constraint-name>part</constraint-name>
    <text>book</text>
  </custom-constraint-query>
</query>
```

You can use the `return-query` query option to see the `directory-query` generated by the custom constraint. For example, if you add the following to your options node:

```
<return-query>true</return-query>
```

Then the search response will include a query similar to the following:

```
<search:response ...>
  <search:query>
    <cts:or-query xmlns:cts="http://marklogic.com/cts">
      <cts:directory-query depth="infinity">
        <cts:uri>/mydocs/book-dir/</cts:uri>
      </cts:directory-query>
    </cts:or-query>
  </search:query>
```

```
  ...
</search:response>
```

2.4.6 Example: Creating a Custom Constraint Geospatial Facet

The following is a library module that implements a geospatial facet that uses a custom constraint. It tokenizes the constraint value on the `@` character to produce input to the geospatial lexicon function. This is a simplified example, meant to demonstrate the design pattern, not meant for production, as it does not do any error checking to make it more robust at handling user input.

Note: While you could use the code in this example, it is meant as an example of the design patterns you use to create custom constraints. If you want to use a geospatial constraint, use the built-in geospatial contraint types (`geo-attr-pair`, `geo-elem-pair`, and `geo-elem`) as described in "Constraint Options" on page 369.

```
xquery version "1.0-ml";
module namespace geoexample = "my-geoexample";
(:
  Sample custom constraint for this example :

  <constraint name="geo">
     <custom>
       <parse apply="parse" ns="my-geoexample"
              at="/geoexample.xqy"/>
       <start-facet apply="start-facet" ns="my-geoexample"
                    at="/geoexample.xqy"/>
       <finish-facet apply="finish-facet" ns="my-geoexample"
                    at="/geoexample.xqy"/>
        <annotation>
            <regions>
               <region label="A">[0, -180, 30, -90]</region>
               <region label="B">[0, -90, 30, 0]</region>
               <region label="C">[30, -180, 45, -90]</region>
               <region label="D">[30, -90, 45, 0]</region>
               <region label="E">[45, -180, 60, -90]</region>
               <region label="F">[45, -90, 60, 0]</region>
               <region label="G">[45, 90, 60, 180]</region>
               <region label="H">[60, -180, 90, -90]</region>
               <region label="I">[60, -90, 90, 0]</region>
               <region label="J">[60, 90, 90, 180]</region>
            </regions>
        </annotation>
     </custom>
  </constraint>

  This example assumes the presence of an element-pair
  geospatial index, on data structured as follows (note lat/lon
  children of quake):

    <quake>
     <area>0</area>
     <perimeter>0</perimeter>
```

```
      <quakesx020>2</quakesx020>
      <quakesx0201>26024</quakesx0201>
      <catalog_sr>PDE</catalog_sr>
      <year>1994</year>
      <month>6</month>
      <day>11</day>
      <origin_tim>164453.48</origin_tim>
      <lat>61.61</lat>
      <lon>168.28</lon>
      <depth>9</depth>
      <magnitude>4.3</magnitude>
      <mag_scale>mb</mag_scale>
      <mag_source/>
      <dt>1994-06-11T16:44:53.48Z</dt>
    </quake>
:)

declare namespace search = "http://marklogic.com/appservices/search";
(:
   The Search API calls the parse function during the parsing of the
   query text.  It accepts the parsed-so-far query text for this
   constraint, parses that query, and outputs a serialized cts:query
   for the custom part.  The Search API passes the parameters to this
   function based on the custom constraint in the search:options and
   the query text passed into search:search.
:)
declare function geoexample:parse(
  $qtext as xs:string,
  $right as schema-element(cts:query) )
as schema-element(cts:query)
{
    let $point := fn:tokenize(fn:string($right//cts:text), "@")
    let $s := $point[1]
    let $w := $point[2]
    let $n := $point[3]
    let $e := $point[4]
    return
        element cts:element-pair-geospatial-query {
            attribute qtextconst {
                fn:concat($qtext, fn:string($right//cts:text)) },
            element cts:annotation {
               "this is a custom constraint for geo" },
            element cts:element { "quake" },
            element cts:latitude {"lat"},
            element cts:longitude {"lon"},
            element cts:region {
                attribute xsi:type { "cts:box" },
                fn:concat("[", fn:string-join(($s, $w, $n, $e),
                                  ", "), "]")
            },
            element cts:option { "coordinate-system=wgs84" }
        }
};
```

```
(:
  The start-facet function starts the concurrent lexicon evaluation.
:)
declare function geoexample:start-facet(
  $constraint as element(search:constraint),
  $query as cts:query?,
  $facet-options as xs:string*,
  $quality-weight as xs:double?,
  $forests as xs:unsignedLong*)
as item()*
{
  let $latitude-bounds  := (0, 30, 45, 60, 90)
  let $longitude-bounds := (-180, -90, 0, 90, 180)
  return
  cts:element-pair-geospatial-boxes(
        xs:QName("quake"), xs:QName("lat"), xs:QName("lon"),
$latitude-bounds,
        $longitude-bounds, ($facet-options, "concurrent", "gridded"),
        $query, $quality-weight, $forests)
};

(:
  The finish-facet function constructs the facet, based on the
  values from $start returned by the start-facet function.
:)
declare function geoexample:finish-facet(
  $start as item()*,
  $constraint as element(search:constraint),
  $query as cts:query?,
  $facet-options as xs:string*,
  $quality-weight as xs:double?,
  $forests as xs:unsignedLong*)
as element(search:facet)
{
(: Uses the annotation from the constraint to extract the regions :)
  let $labels :=
$constraint/search:custom/search:annotation/search:regions
  return
  element search:facet {
    attribute name {$constraint/@name},
    for $range in $start
    return
    element search:facet-value{
        attribute name {
              $labels/search:region[. eq fn:string($range)]/@label },
        attribute count {cts:frequency($range)}, fn:string($range) }
  }
};
```

To run a custom constraint that references the above custom code, put the above module in the App Server root in a file names `geoexample.xqy` and run the following:

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="geo">
     <custom>
       <parse apply="parse" ns="my-geoexample"
              at="/geoexample.xqy"/>
       <start-facet apply="start-facet" ns="my-geoexample"
                    at="/geoexample.xqy"/>
       <finish-facet apply="finish-facet" ns="my-geoexample"
                    at="/geoexample.xqy"/>
        <annotation>
            <regions>
               <region label="A">[0, -180, 30, -90]</region>
               <region label="B">[0, -90, 30, 0]</region>
               <region label="C">[30, -180, 45, -90]</region>
               <region label="D">[30, -90, 45, 0]</region>
               <region label="E">[45, -180, 60, -90]</region>
               <region label="F">[45, -90, 60, 0]</region>
               <region label="G">[45, 90, 60, 180]</region>
               <region label="H">[60, -180, 90, -90]</region>
               <region label="I">[60, -90, 90, 0]</region>
               <region label="J">[60, 90, 90, 180]</region>
            </regions>
        </annotation>
      </custom>
   </constraint>
</options>
return
search:search("geo:1@2@3@4", $options)
```

2.5 Search Grammar

The XQuery Search API and the REST, Node.js, and Java Client APIs use a built-in grammar to generate a search query from simple query text, which is typically text entered by an end-user in a simple HTML form. The default grammar provides a robust ability to generate complex queries. The following are some examples of queries that use the default grammar:

- `(cat OR dog) NEAR vet`

  at least one of the terms `cat` or `dog` within 10 terms (the default distance for `cts:near-query`) of the word `vet`

- `dog NEAR/30 vet`
  the word `dog` within 30 terms of the word `vet`
- `cat -dog`

the word `cat` where there is no word `dog`.

Customization of the string query grammar is available using the `grammar` query option.

For details, see "Searching Using String Queries" on page 65

2.6 Returning Lexicon Values With search:values

A lexicon is a list of unique words or values, either throughout an entire database (words only) or over a named element, attribute, or field (words or values). The `search:values` Search API function returns values from lexicons. You can optionally constrain the values with a structured query, choose a subset of the matching values, calculate aggregates based on the lexicon values, and find co-occurrences of values in multiple lexicons.

For general information about lexicons, see "Browsing With Lexicons" on page 431. This section covers the following related topics specific to the Search API.

- Specifying the Input Lexicons
- Constraining and Filtering Your Results
- Example: Using a Query to Constrain Results
- Example: Filtering with Starting Value, Limit, and Page Length
- Example: Finding Value Co-Occurrences
- Additional Interfaces

2.6.1 Specifying the Input Lexicons

The most basic `search:values` call has the following form:

```
search:values($spec-name, $options)
```

Where `$spec-name` is the name of a `values` or `tuples` specification defined in the `search:options` passed as the second parameter. Use a `values` specification to work with the values in a single lexicon. Use a `tuples` specification to work with co-occurrences of values in multiple lexicons.

Before you can query the values or words in an element, attribute, or field, you define a corresponding range index or a word lexicon using the Admin Interface or Admin API. Before you can query the URI or collection lexicons, you must enable them using the Admin Interface or Admin API. For details, see "Creating Lexicons" on page 432.

The following example returns all values of the `<first-name/>` element, assuming the existence of an element range index over the element.

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <values name="names">
    <range type="xs:string">
      <element ns="" name="first-name" />
    </range>
  </values>
</options>
return
search:values("names", $options)

<values-response name="names" type="xs:string"
    xmlns="http://marklogic.com/appservices/search"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <distinct-value frequency="1">George</distinct-value>
  <distinct-value frequency="1">Fred</distinct-value>
  ...
</values-response>
```

For more examples of values and tuples specifications, see the API reference for `search:values`.

The `search:values` function accepts additional parameters you can use to constrain and filter your results; for details, see “Constraining and Filtering Your Results” on page 53. You can also apply a pre-defined or user-defined aggregate function to values or tuples by defining an aggregate in the search options; for details, see “Using Aggregate Functions” on page 449.

2.6.2 Constraining and Filtering Your Results

The `search:values` function has the following interface. Only the `$spec-name` and `$options` parameters are required.

```
search:values($spec-name, $options, $query,
              $limit, $start, $page-start, $page-length)
```

Use the `$query`, `$limit`, `$start`, `$page-start`, and `$page-length` parameters to filter the results returned by `search:values`, as described in the following table:

Parameter	Description
`$query`	Limit results to values in document that match the provided query. Default: None; return values from all documents.
`$limit`	The maximum number of values to retrieve from the lexicon. Default: No limit; return all values in the lexicon, or all values in the subset selected by `$query`.
`$start`	The first value to return. If this value is not in the lexicon, then values are returned beginning with the next logical value. Default: The first value in the lexicon, or the first value in the subset selected by `$query`.
`$page-start` `$page-length`	Define a subset of the results to return to your application. Default: Return all values selected by `$query`, `$limit`, and `$start`.

The `$query`, `$limit`, and `$start` parameters limit the values selected from the lexicon. The `$page-start` and `$page-length` parameters retrieve a subset of the selected values and can be used to "page through" the selected values in successive invocations.

You cannot use $page-start and $page-length to retrieve values outside the subset selected by `$limit` and/or `$start`. For example, if `$page-start` + `$page-length` exceeds `$limit`, then only (`$limit` - `$page-start` + 1) values are returned.

Most of the filtering parameters can be used independent of one another. That is, you can specify a limit without a query or a start value without a limit. However, if you specify `$page-start`, then you must also specify `$page-length`.

2.6.3 Example: Using a Query to Constrain Results

Imagine a set of documents describing animals. Each document includes an animal name and kind. For example, each document is of the following form:

```
<animal>
  <name>aardvark</name>
  <kind>mammal</kind>
</animal>
```

If an element or field range index is defined on `/animal/name`, then the following query returns a result for all the animal names in the database:

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <values name="animals">
    <range type="xs:string">
      <field name="animal-name" />
    </range>
  </values>
</options>
return
search:values("animals", $options)

<values-response name="animals" type="xs:string"
    xmlns="http://marklogic.com/appservices/search"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <distinct-value frequency="1">aardvark</distinct-value>
  <distinct-value frequency="1">badger</distinct-value>
  <distinct-value frequency="1">camel</distinct-value>
  <distinct-value frequency="1">duck</distinct-value>
  <distinct-value frequency="1">emu</distinct-value>
  ...
  <distinct-value frequency="1">zebra</distinct-value>
</values-response>
```

The following example adds a query that limits the results to values in documents that match the query “mammal OR marsupial”, eliminating `duck`, `emu` and other “bird” values from the result set. This example uses a structured query derived from a string query by calling `search:parse`, but you can use any structured query.

```
search:values("animals", $options,
    search:parse("mammal OR marsupial", (), "search:query")
)

<values-response name="animals" type="xs:string"
    xmlns="http://marklogic.com/appservices/search"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <distinct-value frequency="1">aardvark</distinct-value>
  <distinct-value frequency="1">badger</distinct-value>
  <distinct-value frequency="1">camel</distinct-value>
  <distinct-value frequency="1">fox</distinct-value>
  <distinct-value frequency="1">hare</distinct-value>
  ...
  <distinct-value frequency="1">zebra</distinct-value>
</values-response>
```

If you include other filtering parameters, such as `$limit`, they are applied after the query. For example, adding a limit of 4 returns the value set [`aardvark badger camel fox`] from the above results.

```
search:values("animals", $options,
    search:parse("mammal OR marsupial", (), "search:query"), 4)
)
```

2.6.4 Example: Filtering with Starting Value, Limit, and Page Length

Assume your lexicon contains a string value for each lower-case letter in the alphabet so that the following query returns results for the values `a,b,c...,z`:

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <values name="alphabet">
    <range type="xs:string">
      <field name="letter" />
    </range>
  </values>
</options>
return
search:values("alphabet", $options)
```

The following query supplies a limit of 10, a start value of "c", a page start of 4, and page length of 3 to the above query:

```
search:values("alphabet", $options, (), 10, "c", 4, 3)
  (: $limit       = 10 :)
  (: $start       = "c" :)
  (: $page-start  = 4 :)
  (: $page-length = 3 :)
```

The `$limit` and `$start` parameter values result in a subset of 10 values, beginning with "c", that are retrieved from the lexicon. The example below uses square brackets (`[ ]`) to delimit the selected subset.

```
a b [ c d e f g h i j k l ] m n ... x y z
```

Then, `$page-start` and `$page-length` parameter values define the final “page” of values returned by `search:values`. Since "f" is the 4th value in subset defined by `$limit` and `$start`, the final result subset contains the value f..h. The example below uses curly braces ({ }) to delimit the selected page of values:

```
a b [ c d e { f g h } i j k l ] m n ... x y z
```

Note that `$page-start` and `$page-length` can never yield a result set that extends past the last value in the subset of values defined by `$limit`. Thus, in the example above, no value beyond "l" can be returned without varying `$start` or `$limit`.

The table below illustrates the values returned when applying various combinations of the `$start`, `$limit`, `$page-start`, and `$page-length` parameters and how `search:values` arrives at the final results. As above, square brackets (`[ ]`) delimit the values selected by `$limit` and/or `$start`, and curly braces (`{ }`) delimit the values selected by `$page-start` and `$page-length`.

Filtering Parameters	Returned Values	How the Results Are Derived
`$limit: 5`	`a b c d e`	`[ a b c d e ] f g ... x y z`
`$start: "c"`	`c d e ... z`	`a b [ c d e f g ... x y z]`
`$limit: 5` `$start: "c"`	`c d e f g`	`a b [ c d e f g ] ... x y z`
`$page-start: 1` `$page-length: 3`	`a b c`	`{ a b c } d e f g ... x y z`
`$page-start: 4` `$page-length: 3`	`d e f`	`a b c { d e f } g ... x y z`

`$limit: 5`
`$start: "c"`
`$page-start: 2`
`$page-length: 3`
	`d e f`	`a b [ c { d e f } g ] h ... x y z`

`$limit: 5`
`$page-start:4`
`$page-length: 3`
	`d e`	`[ a b c { d e } ] f g ... x y z`

If a query parameter is included, the above filtering is applied to the results after applying the query.

2.6.5 Example: Finding Value Co-Occurrences

The following shows how to return co-occurrences (tuples) from the URI lexicon and an element, constraint on a query for `hello AND goodbye`, pulling data exclusively out of the range index:

```
xquery version "1.0-ml";
import module namespace search =
     "http://marklogic.com/appservices/search"
     at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <tuples name="hello">
    <uri/>
    <range type="xs:string"
      collation="http://marklogic.com/collation/">
      <element ns="" name="hello"/>
    </range>
  </tuples>
</options>
return
$values := search:values("hello", $options,
  search:parse("hello goodbye", (), "search:query"))
```

2.6.6 Additional Interfaces

You can also query lexicons using the following interfaces:

- The `cts:values` XQuery function. For details, see “Browsing With Lexicons” on page 431.
- The REST Client API methods `GET:/v1/values/{name}` and `POST:/v1/values/{name}`. For details, see Querying the Values in a Lexicon or Range Index and Finding Value Co-Occurrences in Lexicons in the *REST Application Developer’s Guide*.
- The Java Client API `ValuesDefinition` interface. For details, see the Javadoc and Search On Tuples (Tuples Query / Values Query) in the *Java Application Developer’s Guide*.
- The Node.js Client API DatabaseClient.values interface. For details, see Querying Lexicons and Range Indexes in the *Node.js Application Developer’s Guide*.

2.7 JSON Support in the Search API

The options node in the Search API allows you to specify JSON property names when you have loaded JSON documents into the database and the values you are searching for are associated with JSON properties. The following options node shows some sample `json-property` specifications:

```
<!-- Example of enhanced options structures supporting JSON -->
```

```
<options xmlns="http://marklogic.com/appservices/search">
<!-- range constraint -->
    <constraint name="foo">
        <range type="xs:int">
            <json-property>foo</json-property>
        </range>
    </constraint>

<!-- range values -->
    <values name="foo-values">
        <range type="xs:int">
            <json-property>foo</json-property>
        </range>
    </values>

<!-- range tuples -->
    <tuples name="foo-tuples">
        <range type="xs:int">
            <json-property>foo</json-property>
        </range>
        <range type="xs:string">
            <json-property>bar</json-property>
        </range>
    </tuples>

<!-- default term with word -->
    <term apply="term">
        <default>
            <word>
                <json-property>bar</json-property>
            </word>
        </default>
        <empty apply="all-results"/>
    </term>

    <constraint name="bar">
        <word>
            <json-property>bar</json-property>
        </word>
    </constraint>

    <constraint name="baz">
        <value>
            <json-property>baz</json-property>
        </value>
    </constraint>

    <operator name="sort">
        <state name="score">
            <sort-order direction="ascending">
               <score/>
            </sort-order>
        </state>
         <state name="foo">
```

```
            <sort-order type="xs:int" direction="ascending">
               <json-property>asc</json-property>
            </sort-order>
        </state>
    </operator>
    <sort-order type="xs:int" direction="descending">
        <json-property>desc</json-property>
    </sort-order>

    <transform-results apply="snippet">
        <preferred-matches>
            <element ns="f" name="foo"/>
            <json-property>chicken</json-property>
        </preferred-matches>
    </transform-results>

    <extract-metadata>
        <qname elem-ns="n" elem-name="p"/>
        <json-property>name</json-property>
        <json-property>title</json-property>
        <json-property>affiliation</json-property>
    </extract-metadata>
    <debug>true</debug>
    <return-similar>false</return-similar>
</options>
```

2.8 More Search API Examples

This section shows the following examples that use the Search API:

- Buckets Example
- Computed Buckets Example
- Sort Order Example

2.8.1 Buckets Example

The following example from the Oscars sample application shows how to create a search that defines several decades as buckets, and those buckets are used to generate facets and as a constraint in the search grammar. Buckets are a type of range constraint, which are described in “Constraint Options” on page 369.

Each bucket defines boundary conditions that determines what values fit into the bucket (`@ge`, `@lt`, etc.). Each bucket has a unique name (`@name`) that identifies the bucket search terms. For example, “`decade:1940s`” matches values that fit into the bucket with the name “1990s”.

A bucket can also have a label as the element text data. The label has no functional use in a search, but it is returned in the facet data and can be used by the application for display purposes.

This example defines a constraint that uses a range index of type `xs:gYear` on a Wikipedia `nominee/@year` attribute.

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<search:options>
  <search:constraint name="decade">
    <search:range type="xs:gYear" facet="true">
      <search:bucket ge="2000" name="2000s">Noughts</search:bucket>
      <search:bucket lt="2000" ge="1990"
        name="1990s">Nineties</search:bucket>
      <search:bucket lt="1990" ge="1980"
        name="1980s">Eighties</search:bucket>
      <search:bucket lt="1980" ge="1970"
         name="1970s">Seventies</search:bucket>
      <search:bucket lt="1970" ge="1960"
         name="1960s">Sixties</search:bucket>
      <search:bucket lt="1960" ge="1950"
         name="1950s">Fifties</search:bucket>
      <search:bucket lt="1950" ge="1940"
         name="1940s">Forties</search:bucket>
      <search:bucket lt="1940" ge="1930"
         name="1930s">Thirties</search:bucket>
      <search:bucket lt="1930" ge="1920"
         name="1920s">Twenties</search:bucket>
      <search:facet-option>limit=10</search:facet-option>
      <search:attribute ns="" name="year"/>
      <search:element ns="http://marklogic.com/wikipedia"
         name="nominee"/>
    </search:range>
  </search:constraint>
</search:options>
return
search:search("james stewart decade:1940s", $options)
```

The following is a partial response from this query:

```
<search:response total="2" start="1" page-length="10" xmlns=""
   xmlns:search="http://marklogic.com/appservices/search">
  <search:result index="1" uri="/oscars/843224828394260114.xml"
    path="doc(&quot;/oscars/843224828394260114.xml&quot;)" score="200"
    confidence="0.670319" fitness="1">
    <search:snippet>
      <search:match path=
        "doc(&quot;/oscars/843224828394260114.xml&quot;)/*:nominee
        /*:name"><search:highlight>James</search:highlight>
        <search:highlight>Stewart</search:highlight></search:match>
.......
    </search:snippet>
    <search:snippet>.......</search:snippet>
.......
  </search:result>
  <search:facet name="decade">
    <search:facet-value name="1940s"
count="2">Forties</search:facet-value>
  </search:facet>
  <search:qtext>james stewart decade:1940s</search:qtext>
  <search:metrics>
    <search:query-resolution-time>
     PT0.152S</search:query-resolution-time>
    <search:facet-resolution-time>
     PT0.009S</search:facet-resolution-time>
    <search:snippet-resolution-time>
     PT0.073S</search:snippet-resolution-time>
    <search:total-time>PT0.234S</search:total-time>
  </search:metrics>
</search:response>
```

2.8.2 Computed Buckets Example

The `computed-bucket` range constraint operates over `xs:date` and `xs:dateTime` range indexes. The constraint specifies boundaries for the buckets that are computed at runtime based on computations made at the current time. The `anchor` attribute on the `computed-bucket` element has the following values:

`<computed-bucket anchor="value">`	Description
`anchor="now"`	The current time.
`anchor="start-of-day"`	The time of the start of the current day.
`anchor="start-of-month"`	The time of the start of the current month.
`anchor="start-of-year"`	The time of the start of the current year.

These values can also be used in `ge-anchor` and `le-anchor` attributes of the `computed-bucket` element.

The following search specifies a computed bucket and finds all of the documents that were updated today (this example assumes the maintain last-modified property is set on the database configuration):

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

search:search('modified:today',
<options xmlns="http://marklogic.com/appservices/search">
  <searchable-expression>xdmp:document-properties()
  </searchable-expression>
  <constraint name="modified">
    <range type="xs:dateTime">
      <element ns="http://marklogic.com/xdmp/property"
               name="last-modified"/>
      <computed-bucket name="today" ge="P0D" lt="P1D"
       anchor="start-of-day">Today</computed-bucket>
      <computed-bucket name="yesterday" ge="-P1D" lt="P0D"
       anchor="start-of-day">yesterday</computed-bucket>
      <computed-bucket name="30-days" ge="-P30D" lt="P0D"
       anchor="start-of-day">Last 30 days</computed-bucket>
      <computed-bucket name="60-days" ge="-P60D" lt="P0D"
       anchor="start-of-day">Last 60 Days</computed-bucket>
      <computed-bucket name="year" ge="-P1Y" lt="P1D"
       anchor="now">Last Year</computed-bucket>
    </range>
  </constraint>
</options>)
```

The `anchor` attributes have a value of `start-of-day`, so the duration values specified in the `ge` and `lt` attributes are applied at the start of the current day. Note that this is not the same as the "previous 24 hours," as the `start-of-day` value uses 12 o'clock midnight as the start of the day. The notion of time relative to days, months, and years, as opposed to relative to the exact current time, is the difference between relative buckets (`computed-bucket`) and absolute buckets (`bucket`). For an example that uses absolute buckets, see "Buckets Example" on page 60.

2.8.3 Sort Order Example

The following search specifies a custom sort order.

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<search:options>
  <search:operator name="sort">
    <search:state name="relevance">
      <search:sort-order>
        <search:score/>
      </search:sort-order>
    </search:state>
    <search:state name="year">
      <search:sort-order direction="descending" type="xs:gYear"
            collation="">
        <search:attribute ns="" name="year"/>
        <search:element ns="http://marklogic.com/wikipedia"
          name="nominee"/>
      </search:sort-order>
      <search:sort-order>
        <search:score/>
      </search:sort-order>
    </search:state>
  </search:operator>
</search:options>
return
search:search("lange sort:year", $options)
```

This search specifies to sort by year. The options specification allows you to specify `year` or `relevance`, and without specifying, sorts by score (which is the same as `relevance` in this example).

3.0 Searching Using String Queries

This chapter describes how to perform searches using simple string queries with Search API. This chapter includes the following sections:

- String Query Overview
- The Default String Query Grammar
- Modifying and Extending the String Query Grammar

This chapter provides background, design patterns, and examples of using string queries. For the function signatures and descriptions, see the Search documentation under XQuery Library Modules in the *MarkLogic XQuery and XSLT Function Reference*.

3.1 String Query Overview

A *string query* is a plain text search string composed of terms, phrases, and operators that can be easily composed by end users typing into an application search box. For example, "cat AND dog" is a string query for finding documents that contain both the term "cat" and the term "dog".

The syntax of a string query is determined by a configurable grammar. A powerful default grammar is pre-defined. You can modify or extend the grammar through the `grammar` search option. For details, see "The Default String Query Grammar" on page 66 and "Modifying and Extending the String Query Grammar" on page 71.

The default grammar provides a robust ability to generate complex queries. The following are some examples of queries that use the default grammar:

- `(cat OR dog) NEAR vet`

  at least one of the terms `cat` or `dog` within 10 terms (the default distance for `cts:near-query`) of the word `vet`

- `dog NEAR/30 vet`

  the word `dog` within 30 terms of the word `vet`

- `cat -dog`

the word `cat` where there is no word `dog`.

You can use string queries to search contents and metadata with the following MarkLogic Server APIs:

- XQuery Search API. For details, see `search:search` and `search:parse`.
- Java API. For details, see Searching in the *Java Application Developer's Guide*.

- REST API. For details, see Using and Configuring Query Features in the *REST Application Developer's Guide*.

3.2 The Default String Query Grammar

The Search API has a built-in default grammar for interpreting string querys such as "cat AND dog". The default grammar enables you to write applications that perform complex queries against a database based on simple search strings. You can also modify the default grammar or define a custom grammar; for details, see "Modifying and Extending the String Query Grammar" on page 71.

- Query Components and Operators
- Operator Precedence
- Using Relational Operators on Constraints
- String Query Examples

3.2.1 Query Components and Operators

Use the following components and operators to form string queries with the default search grammar:

Query	Example	Description
any terms	`dog` `dog cat`	Match one or more terms, as with a `cts:and-query`. Adjacent terms and phrases are implicitly joined with `AND`. For example, `dog cat` is the same as `dog AND cat`.

`" "`	`"dog tail"`
	`"dog tail" "cat whisker"`
	`dog "cat whisker"`
		Terms in double quotes are treated as a phrase. Adjacent terms and phrases are implicitly joined with `AND`. For example, `dog "cat whisker"` matches documents containing both the term `dog` and the phrase `cat whisker`.

( )	`(cat OR dog) zebra`	Parentheses indicate grouping. The example matches documents containing at least one of the terms `cat` or `dog`, and also contain the term `zebra`.

Query	Example	Description

-query	`-dog`
	`-(dog OR cat)`
	`cat -dog`
		A NOT operation, as with a `cts:not-query`. For example, `cat -dog` matches documents that contain the term `cat` but that do not contain the term `dog`.

query1 `AND` *query2*	`dog AND cat` `(cat OR dog) AND zebra`	Match two query expressions, as with a `cts:and-query`. For example, `dog AND cat` matches documents containing both the term `dog` and the term `cat`. `AND` is the default way to combine terms and phrases, so the previous example is equivalent to `dog cat`.
query1 `OR` *query2*	`dog OR cat`	Match either of two queries, as with a `cts:or-query`. The example matches documents containing at least one of either of terms `cat` or `dog`.
query1 `NOT_IN` *query2*	`dog NOT_IN "dog house"`	Match one query when the match does not overlap with another, as with `cts:not-in-query`. The example matches occurrences of `dog` when it is not in the phrase `dog house`.
query1 `NEAR` *query2*	`dog NEAR cat` `(cat food) NEAR mouse`	Find documents containing matches to the queries on either side of the `NEAR` operator when the matches occur within 10 terms of each other, as with a `cts:near-query`. For example, `dog NEAR cat` matches documents containing `dog` within 10 terms of `cat`.
query1 `NEAR/`*`N`* *query2*	`dog NEAR/2 cat`	Find documents containing matches to the queries on either side of the NEAR operator when the matches occur within *`N`* terms of each other, as with a `cts:near-query`. The example matches documents where the term `dog` occurs within 2 terms of the term `cat`.

Query	Example	Description

constraint`:`*value*	`color:red`
	`decade:1980s`
	`birthday:1999-12-31`
		Find documents that match the named constraint with given value, as with a `cts:element-range-query` or other range query. For details, see "Using Relational Operators on Constraints" on page 70.

operator`:`*state*	`sort:relevance` `sort:date`	Apply a runtime configuration operator such as sort order, defined by an `operator` XML element or JSON property in the search options. For details, see "Operator Options" on page 382.
constraint `LT` *value*	`color LT red` `birthday LT 1999-12-31`	Find documents that match the named range constraint with a value less than *value*. For details, see "Using Relational Operators on Constraints" on page 70.
constraint `LE` *value*	`color LE red` `birthday LE 1999-12-31`	Find documents that match the named range constraint with a value less than or equal to *value*. For details, see "Using Relational Operators on Constraints" on page 70.
constraint `GT` *value*	`color GT red` `birthday GT 1999-12-31`	Find documents that match the named range constraint with a value greater than *value*. For details, see "Using Relational Operators on Constraints" on page 70.
constraint `GE` *value*	`color GE red` `birthday GE 1999-12-31`	Find documents that match the named range constraint with a value greater than or equal to *value*. For details, see "Using Relational Operators on Constraints" on page 70.

Query	Example	Description
constraint NE *value*	`color NE red` `birthday NE 1999-12-31`	Find documents that match the named range constraint with a value that is not equal to *value*. For details, see "Using Relational Operators on Constraints" on page 70.
query1 BOOST *query2*	`george BOOST washington`	Find documents that match *query1*. Boost the relevance score of documents that also match *query2*. The example returns all matches for the term "george", with matches in documents that also contain "washington" having a higher relevance score. For more details, see `cts:boost-query`.

3.2.2 Operator Precedence

The precedence of operators in the default grammar, from highest to lowest, is shown in the following table. Each row in the table represents a precedence level. Where multiple operators have the same precedence, evaluation occurs from left to right. Query sub-expressions using operators higher in the table are evaluated before sub-expressions using operators lower in the table.

Operator
:, LT, LE, GT, GE, NE
-
NOT_IN
BOOST
( ), NEAR, NEAR/*N*
AND
OR

For example, AND has higher precedence than OR, so the following queries:

```
A AND B OR C
A OR B AND C
```

Evaluate as if written as follows:

```
(A AND B) OR C
A OR (B AND C)
```

3.2.3 Using Relational Operators on Constraints

The relational query operators :, `LT`, `LE`, `GT`, `GE`, and `NE` accept a constraint name on the left hand side and a value on the right hand side. That is, queries using these operators are of the following form:

```
constraint op value
```

These relational operators match fragments that meet the named constraint with a value that matches the relationship defined by the operator (equals, less than, greater than, etc.). For example, if your query options define an element word constraint named `color`, then `color:red` matches documents that contain elements meeting the `color` constraint with a value of `red`. For details and more examples, see "Constraint Options" on page 369.

The constraint name must be the name of a `<constraint/>` XML element or `"constraint"` JSON object defined by the query options governing the search. The constraint can be a word, value, range, or geospatial constraint. There must be a range index associated with the constraint.

If the constraint is unbucketed, the value on the right hand side of the operator must be convertible to the type of the constraint. For example, if the range index behind the constraint has type `xs:date`, then the value to match must represent an `xs:date`.

If the constraint is bucketed, then the value must be the name of a bucket defined by the constraint. For example, if searching using the `decade` bucketed constraint defined in "Bucketed Range Constraint Example" on page 378, then the value on the right hand side must be a bucket name such as `1920s` or `2000s`, such as `decade:1920s`.

3.2.4 String Query Examples

The default grammar provides a robust ability to generate complex queries. The following are some examples of queries that use the default grammar:

- `(cat OR dog) NEAR vet`

  at least one of the terms `cat` or `dog` within 10 terms (the default distance for `cts:near-query`) of the word `vet`

- `dog NEAR/30 vet`

  the word `dog` within 30 terms of the word `vet`

- `cat -dog`

the word `cat` where there is no word `dog`

3.3 Modifying and Extending the String Query Grammar

You can customize the grammar used for constructing string queries by specifying a custom `grammar` XML element or JSON object in the query options used with a search. A grammar is defined by the following components:

- `starter`
- `joiner`
- `quotation`
- `implicit`

A `grammar` must contain at least one `starter`, `joiner`, or `implicit` element. If a `grammar` element is present in your query options, but it is empty, the search is parsed according to the `term-option` settings.

The following is the default string query `grammar` that implements the syntax and semantics described in "The Default String Query Grammar" on page 66. You can retrieve the default grammar by retrieving the default query options; for details, see "Getting the Default Query Options" on page 369.

```
<grammar xmlns="http://marklogic.com/appservices/search">
  <quotation>"</quotation>
  <implicit>
    <cts:and-query strength="20" xmlns:cts="http://marklogic.com/cts"/>
  </implicit>
  <starter strength="30" apply="grouping" delimiter=")">(</starter>
  <starter strength="40" apply="prefix" element="cts:not-query">-</starter>
  <joiner strength="10" apply="infix" element="cts:or-query"
     tokenize="word">OR</joiner>
  <joiner strength="20" apply="infix" element="cts:and-query"
     tokenize="word">AND</joiner>
  <joiner strength="30" apply="infix" element="cts:near-query"
     tokenize="word">NEAR</joiner>
  <joiner strength="30" apply="near2" consume="2"
     element="cts:near-query">NEAR/</joiner>
  <joiner strength="32" apply="boost" element="cts:boost-query"
     tokenize="word">BOOST</joiner>
  <joiner strength="35" apply="not-in" element="cts:not-in-query"
     tokenize="word">NOT_IN</joiner>
  <joiner strength="50" apply="constraint">:</joiner>
  <joiner strength="50" apply="constraint" compare="LT"
     tokenize="word">LT</joiner>
  <joiner strength="50" apply="constraint" compare="LE"
     tokenize="word">LE</joiner>
  <joiner strength="50" apply="constraint" compare="GT"
     tokenize="word">GT</joiner>
  <joiner strength="50" apply="constraint" compare="GE"
     tokenize="word">GE</joiner>
  <joiner strength="50" apply="constraint" compare="NE"
     tokenize="word">NE</joiner>
</grammar>
```

The following table describes the concepts used in the search grammar:

Concept	Description
`implicit`	The *implicit* grammar element specifies the `cts:query` to use by default to join two search terms together. By default, the Search API uses a `cts:and-query`, but you can change it to any cts:query with the `implicit` grammar option.
`starter`	A *starter* is a string that appears before a term to denote special parsing for the term, for example, the minus sign (`-`) for negation. Additionally, when used with the `delimiter` attribute, a starter specifies starting and ending strings that separate terms for grouping things together, and allows the grammar to set an order of precedence for terms when parsing a string.

`joiner`	A *joiner* is a string that combines two terms together. For example, AND and OR function as joiners in these queries using the default grammar:
	
	`cat AND dog`
	`cat OR dog`
	
	The default grammar also uses joiners for the string that separates a constraint or operator from its value, as described in “Constraint Options” on page 369 and “Operator Options” on page 382. If `joiner/@tokenize` is set to `"word"` attribute is present, then the terms and the joiner must be whitespace-separated; otherwise the parser looks for the joiner string anywhere in the query text.

`quotation`	The `quotation` string specifies the string to use to indicate the start and end of a phrase. For example, in the default grammar, the following is parsed as a phrase (instead of a sequence of terms combined with an `AND`): `"this is a phrase"`
strength	The *strength* attribute provides the parser with information on which tokens are processed first. Higher strength tokens or groups are processed before lower strength tokens or groups.

The `starter` elements define how to parse portions of the grammar. The `apply` attributes specify the functions to which the `starter` and the `delimiter` apply.

The `joiner` elements define how to parse various operators, constraints, and other operations and specifies the functions that define the joiner’s behavior. For example, if you wanted to change the `OR` joiner above, which joins tokens with a `cts:or-query`, to use the pipe character (`|`) instead, you would substitute the following `joiner` element for the one above:

```
<search:joiner strength="10" apply="infix" element="cts:or-query"
     tokenize="word">|</search:joiner>
```

Setting `@tokenize` to `word` specifies that a token must have whitespace immediately before and after it in order to be recognized. Without that attribute, if `OR` was the joiner, then a search for `CORN` would result in a search for `C OR N` (`cts:or-query(("C"), ("N"))`). With joiners used in constraints (for example, the colon character `:`), you probably do not want that, so the `tokenize` attribute is omitted, thus allowing searches like `decade:1990s` to parse as a constraint.

You can add a joiner string to specify the composable `cts:query` elements that take a sequence of queries (`cts:or-query`, `cts:and-query`, or `cts:near-query`) by specifying the element in the `element` attribute on an `apply="infix"` joiner. For example, the following `search:joiner` element specifies a joiner for `cts:near-query`, which would combine the surrounding terms with a `cts:near-query` (and would use the default distance of 10) using the joiner string `CLOSETO`:

```
<search:joiner strength="10" apply="infix" element="cts:near-query"
       tokenize="word">CLOSETO</search:joiner>
```

Using the above joiner specification, the following query text `bicycle CLOSETO shop` would return matches that have `bicycle` and `shop` within 10 words of each other.

By default, the search grammar is very powerful, and implements a grammar similar to the Google grammar. With the customization, you can make it even more powerful and customize it to your specific needs. To add custom parsing, you must implement a function and use the `apply`, `ns`, `at` design pattern (described in "Search Customization Via Options and Extensions" on page 34) and construct a `search:grammar` options node to point to the function(s) you implemented.

3.3.1 starter

A `starter` defines a unary prefix operator or a pair of grouping symbols. For example, the default grammar defines the minus sign (-) as a starter for negation and parentheses (()) as a grouping starter.

A `grammar` query option can contain 0 or more starter elements, but must contain at least one `starter` or `joiner`.

Do the following to define a unary starter operator in your grammar:

1. Identify the XQuery parsing function using the `apply`, `at`, and `ns`, as described in "Search Customization Via Options and Extensions" on page 34.

2. Put the operator token in the XML `<starter/>` text node or the JSON `label` sub-object.

3. Set `strength` to reflect the evaluation precedence this operator should have relative to other operators in the same grammar.

4. Set `element` to the QName of the `cts:query` element returned by the parsing function. For example, the negation operator defined by the default grammar produces a `cts:not-query` element.

5. Optionally, set `options` to a space separated list of search options to pass to the parsing function.

For example, the default grammar defines a unary "-" operator as follows:

XML	JSON
`<starter strength="40" apply="prefix" element="cts:not-query">-</starter>`	`"starter": [ { "strength": 40, "apply": "prefix", "element": "cts:not-query", "label": "-" } ]`

Do the following to define a grouping symbol in your grammar:

1. Identify the XQuery parsing function using the `apply`, `at`, and `ns`, as described in "Search Customization Via Options and Extensions" on page 34.

2. Put the grouping start token in the XML `<starter/>` text node or the JSON `label` sub-object.

3. Set `delimiter` to the grouping end token.

4. Set `strength` to reflect the evaluation precedence this operator should have relative to other operators in the same grammar.

5. Set `element` to the QName of the `cts:query` element returned by the parsing function. For example, the negation operator defined by the default grammar produces a `cts:not-query` element.

6. Optionally, set `options` to a space separated list of search options to pass to the parsing function.

For example, the default grammar defines "( )" as grouping tokens as follows:

XML	JSON
`<starter strength="30" apply="grouping" delimiter=")">(</starter>`	`"starter": [ { "strength": 30, "apply": "grouping", "delimiter": ")", "label": "(" } ]`

3.3.2 joiner

A joiner defines a binary operator that "joins" two string query expressions. Examples of joiners in the default grammar include `AND`, `OR`, `LT`, and colon (:).

A `grammar` query option can contain 0 or more joiners, but must contain at least one `starter` or `joiner`.

Do the following to define a joiner:

1. Identify the XQuery parsing function using the `apply`, `at`, and `ns`, as described in "Search Customization Via Options and Extensions" on page 34.

2. Put the operator token or symbol in the XML `<joiner/>` text node or the JSON `label` sub-object.

3. Set `strength` to reflect the evaluation precedence this operator should have relative to other operators in the same grammar.

4. Set `element` to the QName of the `cts:query` element returned by the parsing function. For example, the `AND` operator defined by the default grammar produces a `cts:and-query` element.

5. Optionally, set `options` to a space separated list of search options to pass to the parsing function.

To define a prefix operator, put the operator token in the XML `<starter/>` text node or the JSON `label` sub-object. For example, the default grammar defines a unary "-" operator as follows:

XML	JSON

<starter strength="40" apply="prefix"
element="cts:not-query">-</starter>
	"starter": [
	{
	"strength": 40,
	"apply": "prefix",
	"element": "cts:not-query",
	"label": "-"
	}
	]

3.3.3 quotation

The `quotation` grammar element defines symbol used to demarcate phrases. The default grammar uses double quotes ("):

```
<quotation>"</quotation>
```

A grammar can contain at most one `quotation` definition.

In XML, place the symbol in the text node of the `<quotation/>` element. In JSON, place the symbol in the string value associated with the `quotation` key. For example, to use percent (%) instead of double quotes for phrases, include the following in your grammar:

XML	JSON
<quotation>%</quotation>	"quotation": "%"

3.3.4 implicit

The `implicit` grammar element specifies how to handle adjacent terms that are are not separated by an explicit joiner operator. For example, how to interpret a string query such as “cat dog”. A `grammar` query option can contain at most one implicit rule.

Do the following to define an implicit operation:

1. Select a query type from the `cts:query` hierarchy defined in “cts:query Hierarchy” on page 241.

2. If you are building XML query options, add a child element of the appropriate type to the `<implicit/>` element. You can build this using the `cts:query` constructors. For example, you can construct an empty `cts:and-query` by evaluating “`cts:and-query((), ())`”.

3. If you are building JSON query options, set the value associated with the `implicit` key to the serialized representation of the `cts:query` element type selected in Step 1.

For example, the default grammar includes an `implicit` rule that specifies `cts:and-query` as the implicit operation, so “cat dog” is equivalent to “cat AND dog”:

XML	JSON

`<implicit>`
`  <cts:and-query`
`  xmlns:cts="http://marklogic.com/cts"/>`
`</implicit>`
	`"implicit":`
	`  "<cts:and-query`
	`xmlns='http://marklogic.com/cts`
	`'/>"`

4.0 Searching Using Structured Queries

This chapter describes how to perform searches using structured queries expressed in XML or JSON. The annotated `cts:query` that is generated by default from `search:parse` or `search:search` works well for cases where you do not need to perform extensive modification to the query. If you want to generate your own query, or if you want to parse your query using different rules from the Search API grammar rules, there is an alternate query style called structured query.

This chapter includes the following topics:

- Structured Query Overview
- Structured Query Concepts
- Constructing a Structured Query
- Syntax Summary
- Examples of Structured Queries
- Syntax Reference

4.1 Structured Query Overview

A *structured query* is an Abstract Syntax Tree representation of a search expression, expressed in XML or JSON. For example, the following is a structured query in XML that is equivalent to the string query “cat AND dog”.

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:and-query>
    <search:term-query>
      <search:text>cat</search:text>
    </search:term-query>
    <search:term-query>
      <search:text>dog</search:text>
    </search:term-query>
  </search:and-query>
</search:query>
```

Any time you want to intercept a query and either augment or manipulate it in some way, consider using a structured query. The following use cases are good candidates for structured queries:

- Queries that do not work well in a string query. For example, constraints such as a geospatial constraint of a complex polygon are designed to be machine generated.
- Search strings that include complex sets of rules, or a set of rules that do not map well to the string query grammar.
- Combining a pre-parsed structured query with a user-generated or dynamically constructed string query.

- Converting a non-MarkLogic query representation such as an in-house query format into a form consumable by MarkLogic Server.
- String queries that require application-specific validation.

You can generate a structured query using the XQuery function `search:parse` or by writing your own code that returns a structured query. You can use structured queries to search contents and metadata with the following MarkLogic Server APIs:

- XQuery Search API. For details, see `search:search` and `search:resolve`.
- Java API. For details, see Searching in the *Java Application Developer's Guide*.
- REST API. For details, see Using and Configuring Query Features in the *REST Application Developer's Guide*.

4.2 Structured Query Concepts

The concepts covered in this section should help you understand the purpose and scope of the various structured query building blocks. For detailed information about a particular sub-query, see "Syntax Reference" on page 90.

The following topics are covered:

- Major Query Categories
- Understanding the Difference Between Term and Word Queries
- Understanding Containment
- Text Match Semantics
- Structured Query Sub-Query Taxonomy

4.2.1 Major Query Categories

A query encapsulates your search criteria. You can combine search criteria into complex search expressions using many different types of query combinations. The many sub-query components of structured query fall into one of the categories described in this section.

The query categories in the following table are "leaf" queries that never contain other queries. These type of query are the basic search building blocks that describe what content you want to match.

Query Type	Description
value	Match an entire value in a specific place, such as a phrase or number in a JSON property or XML element. Value queries on JSON property values must use properly typed criteria; if you do not specify a type, string is assumed. For example, to match the value of a property with "number" type, you must explicitly set the criteria value type to "number" in your query. For details, see "value-query" on page 125.
word	Match a word or phrase in a specific place, such as in a specific JSON property, XML element or attribute, or field. A word query will match a subset of a text value. A word query only matches text, so it will never match JSON property values that have number, boolean, or null type. For details, see "word-query" on page 128.
term	Match a word or phrase anywhere it appears in a document or container. A term query will match a subset of a text value and does not use exact match semantics by default. For details, see "term-query" on page 95.
range	Match values that satisfy a relational expression applied to a typed value. You can express conditions such as "less than 5" or "not equal to true". A range query must either be backed by a range index or used in a filtered search operation. For details, see "range-query" on page 121.

Additional sub-queries enable you to combine the basic content queries with each other and with additional criteria and constraints. The additional query types fall into the following general categories.

- Logical Composers: Express logical relationships between criteria. You can build up compound logical expressions such as "*x* AND (*y* OR *z*)".
- Document Selectors: Select documents based on collection, directory, or URI. For example, you can express criteria such as "*x* only when it matches in documents in collection *y*".

- Location Qualifiers: Further limit a criteria based on where the match appears. For example, "*x* only when contained in JSON property *z*", or "*x* only when it matches within *n* words of *y*", or "*x* only when it matches in a document property".

4.2.2 Understanding the Difference Between Term and Word Queries

Term queries and word queries differ primarily in how they handle containment. A term query finds matches anywhere within its context container, while a word query matches only immediate children. For example, suppose your JSON or XML document has the following structure:

JSON	XML

`{ "a": {`
`  "b": "value",`
`  "c": { "d": "value" }`
`} }`
	`<a>`
	`  <b>value</b>`
	`  <c>`
	`  <d>value</d>`
	`  </c>`
	`</a>`

A term query for "value" in "a" finds 2 matches: The occurrence in "b", and the one in "d". However, a word query for "value" in "a" finds no matches because "value" does not occur as an immediate child of "a".

To locate occurrences of "value" using a word query, you must constrain the word query to the scope of "b" or "d". For example, the following sub-queries match "value" in "b" in the JSON and XML documents, respectively:

JSON	XML

`"word-query": {`
`  "json-property": "b",`
`  "text": "value"`
`}`
	`<search:word-query>`
	`  <search:element name="b">`
	`  <search:text>value</search:text>`
	`</search:word-query>`

4.2.3 Understanding Containment

Many sub-query types constrain matches to the context of a particular container. A *container* is a JSON property, XML element, or XML element attribute.

A query such as a word or value query that includes the name of a container only matches occurrences within that container. However, the container can appear at any level within the enclosing document or container. That is, it does not have to be an immediate child.

For example, the following word queries only matches occurrences of "value" when appears in the value of a JSON property or XML element named "a". (The examples use `json-property` in the JSON version and `element` in the XML version, but you can use these specifiers independent of query format.)

JSON	XML

`"word-query": {`
`  "json-property": "b",`
`  "text": "value"`
`}`
	`<search:word-query>`
	`  <search:element name="b">`
	`  <search:text>value</search:text>`
	`</search:word-query>`

However, in the absence of other restrictions, the container named "b" can occur anywhere. For example, the following documents each contain two matches because there are 2 JSON properties (or XML elements) containing "value".

JSON	XML

`{"a": {`
`  "b": "value",`
`  "c": { "b": "value" }`
`} }`
	`<a>`
	`  <b>value</b>`
	`  <c>`
	`  <b>value</b>`
	`  </c>`
	`</a>`

You can wrap a query in a container-query to further limit the scope of the matches. For example, the following sub-queries only match "value" in "b" when "b" occurs inside "c":

JSON	XML

`"container-query": {`
`  "json-property": "c",`
`  "word-query": {`
`  "json-property": "b",`
`  "text": "value"`
`  }`
`}`
	`<search:container-query>`
	`  <search:element name="c" />`
	`  <search:word-query>`
	`  <search:element name="b">`
	`  <search:text>value</search:text>`
	`  </search:word-query>`
	`</search:container-query>`

You can limit the scope of matches in other ways, such as collection, database directory, or property fragment scope. For details, see "Location Qualifiers" on page 85 and "Document Selectors" on page 85.

4.2.4 Text Match Semantics

Whether a value, term, or word query on text content is case-sensitive, diacritic-sensitive, whitespace-sensitive, or punctuation-sensitive depends on the query options in scope during the search. Whether stemming and wildcarding are active similar depends on options and database configuration.

The defaults for text matches are as follows:

- Case: If the criteria text is all lower-case, then the match is case-insenstive. If the criteria contains any upper-case letters, then the match is case sensitive.
- Diacritics: If the criteria text contains no diacritics, then the match is diacritic-insenstive. If the criteria contains any diacritics, then the match is diacritic-sensitive.
- Whitespace: Whitespace insenstive. (Whitespace is still used to tokenize words.)
- Punctuation: If the criteria text contains no punctuation, then the match is punctuation-insenstive. If the criteria contains any punctuation, then the match is punctuation sensitive.
- Stemming: Depends on the database configuration. Stemmed search is disabled on a database by default.
- Wildcarding: Depends on the database configuration and the criteria text. Wildcard searches are disabled on a database by default. If any wildcard search is enabled and the criteria text contains wildcard characters ('?' or '*'), then wildcarding is applied.

For example, a word query for "purple" matches both "purple elephants" and "Purple Elephants", but a word query for "Purple" only matches "Purple Elephants".

Similarly, a word query for "purple elephants" matches both "purple elephants" and "purple, elephants", but a word query for "purple,elephants" will only match "purple, elephants".

You can override some of these behaviors with query options and database configuration. For example, if wildcard searches are not enabled on the database, then a word query for "thom*" will not match "Thomas". Similarly, you can set term options local to a particular word-query or value-query, or more widely through the `term-options` query option.

For more details, see "Term Options" on page 796 and Understanding the Text Index Settings in the *Administrator's Guide*.

4.2.5 Structured Query Sub-Query Taxonomy

Structured query explicitly exposes all the query types described in "Major Query Categories" on page 80. This section is a quick reference for locating the kind of sub-query you need, based on this categorization.

You can use most kinds of sub-query in combination with each other to build up complex queries. For details, see "Syntax Reference" on page 90.

- Basic Content Queries
- Logical Expression Composers
- Location Qualifiers
- Document Selectors

4.2.5.1 Basic Content Queries

Basic content queries express search criteria about your content, such as "JSON property A contains value B" or "any document containing the phrase 'dog'". These queries function as "leaves" in the structure of a complex, compound query because they do not contain sub-queries.

- term-query
- word-query
- value-query
- range-query
- geo-elem-query
- geo-elem-pair-query
- geo-attr-pair-query
- geo-json-property-query
- geo-json-property-pair-query
- geo-path-query

4.2.5.2 Logical Expression Composers

Logical composers are queries that join one or more sub-queries into a logical expression. For example, "documents which match both query1 and query2" or "documents which match either query1 or query2 or query3".

- and-query
- and-not-query

- boost-query
- not-query
- not-in-query
- or-query

4.2.5.3 Location Qualifiers

Location qualifiers limit results based on where subquery matches occur, such as only in content, only in metadata, or only when contained by a specified JSON property or XML element. For example, “matches for this sub-query that occur in metadata” or “matches for this sub-query that are contained in JSON Property P”.

- document-fragment-query
- locks-fragment-query
- near-query
- properties-fragment-query
- container-query

4.2.5.4 Document Selectors

Document selectors are queries that match a group of documents by database attributes such as collection membership, directory, or URI, rather than by contents. For example, “all documents in collections A and B” or “all documents in directory D”.

- collection-query
- directory-query
- document-query

4.3 Constructing a Structured Query

You can construct a structured query in multiple ways:

- Manually, using the syntax described in “Syntax Reference” on page 90.
- In XQuery, by calling the XQuery function `search:parse` and supplying `"search:query"` as the 3rd parameter to see the XML representation.
- In Java, using the class `com.marklogic.client.query.StructuredQueryBuilder`. or `com.marklogic.client.pojo.PojoQueryBuilder`, or an equivalent interface.

The XQuery Search API only accepts structured queries in XML. The REST and Java APIs accept XML and JSON representations.

For XML, you can use the `search:parse` technique with Query Console to explore how a string query or serialized `cts:query` maps to a structured query, and then modify it according to your needs. For example:

```
xquery version "1.0-ml";
import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

return search:parse("cat AND dog", (), "search:query")
```

If you run the above query in Query Console and display the results as XML, you get the XML representation of "cat AND dog" when parsed with the default search options in effect:

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:and-query>
    <search:term-query>
      <search:text>cat</search:text>
    </search:term-query>
    <search:term-query>
      <search:text>dog</search:text>
    </search:term-query>
  </search:and-query>
</search:query>
```

4.4 Syntax Summary

This section gives a brief summary of structure of a structured query. For details, see "Syntax Reference" on page 90

A structured query is a `search:query` XML element with children representing `cts:query` composers, `cts:query` scoping constructors, and abstractions for Search API components such as constraints and operators. When using the XQuery Search API, you must use the XML representation. In REST and Java, you can choose between the XML or JSON representations.

Like `cts:query` constructors in XQuery, structured queries are composable to make a complex search query. A structured query expressed as XML must have a `<search:query>` wrapper node. For example:

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:and-query>...</search:and-query>
</search:query>
```

Similarly, the JSON representation of a structured query has a `query` wrapper object. Within this wrapper, the sub-queries are enclosed in a `queries` array. The queries wrapper is used wherever multiple sub-queries can occur. For example:

```
{
  "query": {
```

```
      "queries": [
        { "and-query": ... }
      ]
    }
  }
```

You can compose complex queries consisting of and-queries, or-queries, and so on, and they can contain any number of term-queries with terms to search for. You can constrain queries to an element, attribute, JSON property, or field; use range-queries; and so on. For background on how `cts:query` expressions work in MarkLogic Server, see "Composing cts:query Expressions" on page 240.

The REST API and the Java API support XML and JSON representations of structured queries. The REST and Java APIs internally use the JSON conversion features in MarkLogic to convert between JSON and XML. For details on this conversion, see Working With JSON in the *Application Developer's Guide*.

4.5 Examples of Structured Queries

This section includes the following examples of Structured Search, with an XML example as well as the corresponding JSON example for each:

- Example: Simple Structured Search
- Example: Structured Search With Constraint References as Text
- Example: Structured Search With Constraint References

For additional examples, see "Syntax Reference" on page 90.

4.5.1 Example: Simple Structured Search

The following is a structured query XML node equivalent to a string query for the phrase `"imagine a complex search"`:

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:term-query>
    <search:text>imagine a complex search</search:text>
  </search:term-query>
</search:query>
```

The following is the JSON representation of the same query (for use in the REST API or the Java API):

```
{
  "query": {
    "queries": [{
      "term-query": {
        "text": [ "imagine a complex search" ]
      }
    }]
}}
```

With XQuery, you can generate the XML structured query from a string query using `search:parse`, and perform a search with the structured query using `search:resolve`, as shown in the following code:

```
xquery version "1.0-ml";
import module namespace search =
     "http://marklogic.com/appservices/search"
     at "/MarkLogic/appservices/search/search.xqy";

let $complex-search :=
  search:parse('"imagine a complex search"',
      (), "search:query")
return
search:resolve($complex-search)

=> a search:response element
```

The REST API and Java API include interfaces for searching directly with structured queries. For details, see Searching With Structured Queries in *REST Application Developer's Guide* and Search Documents Using Structured Query Definition in *Java Application Developer's Guide*.

4.5.2 Example: Structured Search With Constraint References as Text

The following is a slightly more complicated Structured Search query. It has an and-query to combine terms, and has references to a constraint defined in a search options node, as it would be if parsed using the default query grammar (for example, `decade:1940s` represents the `decade` constraint with the value `1940s`).

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:and-query>
    <search:term-query>
      <search:text>hepburn</search:text>
    </search:term-query>
    <search:term-query>
      <search:text>decade:1940s</search:text>
    </search:term-query>
  </search:and-query>
</search:query>
```

The following is the corresponding JSON representation:

```
{
  "query": {
    "queries": [{
      "and-query": {
        "queries": [
          { "term-query": { "text": [ "hepburn" ] } },
          { "term-query": { "text": [ "decade:1940s" ] } }
        ]
      }
    }]
}}
```

4.5.3 Example: Structured Search With Constraint References

The following example demonstrates a query that includes an explicit reference to a constraint defined in query options.

Assume the query options include a decade bucketed constraint definition, and one of the buckets is named 1940s:

```
<!-- for complete options, see "Buckets Example" on page 60 -->
<search:constraint name="decade">
    <search:range type="xs:gYear" facet="true">
      ...more buckets...
      <search:bucket lt="1950" ge="1940"
         name="1940s">1940s</search:bucket>
      <search:bucket lt="1940" ge="1930"
         name="1930s">1930s</search:bucket>
      ...more buckets...
      <search:facet-option>limit=10</search:facet-option>
      <search:attribute ns="" name="year"/>
      <search:element ns="http://marklogic.com/wikipedia"
         name="nominee"/>
    </search:range>
  </search:constraint>
</search:options>
```

When evaluated with the above options, the string query `"hepburn AND decade:1940s"` expresses a range constraint (`decade:1940s`) that limits matches to those that meet the criteria for the `1940s` bucket of the `decade` constraint. The following is the equivalent structured query, expressed in XML:

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:and-query>
    <search:term-query>
      <search:text>hepburn</search:text>
    </search:term-query>
    <search:range-constraint-query>
      <search:constraint-name>decade</search:constraint-name>
      <search:value>1940s</search:value>
    </search:range-constraint-query>
  </search:and-query>
</search:query>
```

The following is the corresponding JSON representation:

```
{
  "query": {
    "queries": [{
      "and-query": {
        "queries": [
          { "term-query": { "text": [ "hepburn" ] } },
          {
            "range-constraint-query": {
              "value": [ "1940s" ],
              "constraint-name": "decade"
            }
          }
        ]
      }
    }]
}}
```

4.6 Syntax Reference

This section provides detailed syntax information on structured queries. There is a subsection for each top level element in a structured query. Each section includes detailed syntax, an explanation of the child elements, and an example. Begin with the top level `query` wrapper.

- query
- term-query
- and-query
- or-query
- and-not-query

- not-query
- not-in-query
- near-query
- boost-query
- properties-fragment-query
- directory-query
- collection-query
- container-query
- document-query
- document-fragment-query
- locks-fragment-query
- range-query
- value-query
- word-query
- geo-elem-query
- geo-elem-pair-query
- geo-attr-pair-query
- geo-path-query
- geo-json-property-query
- geo-json-property-pair-query
- range-constraint-query
- value-constraint-query
- word-constraint-query
- collection-constraint-query
- container-constraint-query
- element-constraint-query
- properties-constraint-query
- custom-constraint-query
- geospatial-constraint-query
- lsqt-query
- period-compare-query

- period-range-query
- operator-state

4.6.1 query

A `query` is the top level wrapper around a structured query definition. It can contain one or more subquery children. See the subsections on each child for details.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <!-- word or phrase query -->`
`  <term-query />`
`  <!-- cts:query composers -->`
`  <and-query />`
`  <or-query />`
`  <and-not-query />`
`  <not-query />`
`  <not-in-query />`
`  <near-query />`
`  <boost-query />`
`  <!-- cts:query scoping ctors -->`
`  <properties-fragment-query />`
`  <directory-query />`
`  <collection-query />`
`  <container-query />`
`  <document-query />`
`  <document-fragment-query />`
`  <locks-fragment-query />`
`  <range-query />`
`  <value-query />`
`  <word-query />`
`  <geo-elem-query />`
`  <geo-elem-pair-query />`
`  <geo-attr-pair-query />`
`  <geo-path-query />`
`  <geo-json-property-query />`
`  <geo-json-property-pair-query />`
`  <lsqt-query />`
`  <period-compare-query />`
`  <period-range-query />`
`  <!-- Search API abstractions -->`
`  <range-constraint-query />`
`  <value-constraint-query />`
`  <word-constraint-query />`
`  <collection-constraint-query />`
`  <container-constraint-query />`
`  <element-constraint-query />`
`  <properties-constraint-query />`
`  <custom-constraint-query />`
`  <geospatial-constraint-query />`
`  <operator-state />`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [`
	`  term-query,`
	
	`  and-query,`
	`  or-query,`
	`  and-not-query,`
	`  not-query,`
	`  not-in-query,`
	`  near-query,`
	`  boost-query,`
	
	`  properties-fragment-query,`
	`  directory-query,`
	`  collection-query,`
	`  container-query,`
	`  document-query,`
	`  document-fragment-query,`
	`  locks-fragment-query,`
	`  range-query,`
	`  value-query,`
	`  word-query,`
	`  geo-elem-query,`
	`  geo-elem-pair-query,`
	`  geo-attr-pair-query,`
	`  geo-path-query,`
	`  geo-json-property-query,`
	`  geo-json-property-pair-query,`
	`  lsqt-query,`
	`  period-compare-query,`
	`  period-range-query,`
	
	`  range-constraint-query,`
	`  value-constraint-query,`
	`  word-constraint-query,`
	`  collection-constraint-query,`
	`  container-constraint-query,`
	`  element-constraint-query,`
	`  properties-constraint-query,`
	`  custom-constraint-query,`
	`  geospatial-constraint-query,`
	`  operator-state`
	`  ]`
	`  }`
	`}`

4.6.2 term-query

A query that matches one or more search terms or phrases. By default, a `term-query` is equivalent to `cts:word-query`. However, if you use the `term` query option to customize query term handling, this equivalence may not hold. For example, if your search includes a `term` option that specifies a field word constraint, then a `term-query` might be handled as a `cts:field-word-query`. For details, see "term" on page 777.

- Syntax Summary
- Component Description
- Examples

4.6.2.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<term-query>`
`  <text>`*term*`-or-phrase</text>`
`  <weight>`*value*`</weight>`
`  <term-option>`*option*`</term-option>`
`</term-query>`
	`"term-query": {`
	`  "text": [ "`*term-or-phrase*`" ]`
	`  "weight": "`*value*`",`
	`  "term-option": [ `*option*` ]`
	`}`

4.6.2.2 Component Description

Element or JSON Property Name	Req'd?	Description
`text`	Y	The term or phrase to search for. The query can contain multiple `text` children. When there are multiple terms, the query matches if any of the terms match.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.
`term-option`	N	Term options to apply to the query. You can specify multiple term options. If the option has a value, the value of `term-option` is *`option=value`*. For example: `<term-option>min-occurs=1</term-option>` in XML, or `"term-option": ["min-occurs=1"]` in JSON. For details, see the `cts` query corresponding to the query constraint type: `cts:word-query`, `cts:element-word-query`, `cts:element-attribute-word-query`, `cts:field-word-query`, or `cts:json-property-word-query`; and "Term Options" on page 796.

4.6.2.3 Examples

The following example searches for documents containing either of the terms “dog” or “cat”.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <term-query>`
`  <text>dog</text>`
`  <text>cat</text>`
`  </term-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "term-query": {`
	`  "text": [ "dog", "cat" ]`
	`  }`
	`  }]`
	`}}`

4.6.3 and-query

Find the intersection of matches specified by one or more sub-queries. For details, see `cts:and-query`.

- Syntax Summary
- Component Description
- Examples

4.6.3.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<and-query>`
`  anyQueryType`
`  <ordered>bool</ordered>`
`</and-query>`
	`"and-query": {`
	`  "queries": [`
	`  anyQueryType,`
	`  "ordered": boolean`
	`  ]`
	`}`

4.6.3.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	N	One or more sub-queries.
ordered	N	Whether or not the sub-query matches must occur in the order of the sub-queries. For example, if the sub-queries are "cat" and "dog", an ordered query will only match fragments where both "cat" and "dog" occur, and where "cat" comes before "dog" in the fragment. Default: false.

4.6.3.3 Examples

The following example searches for documents containing both of the terms "dog" and "cat", with "dog" occurring before "cat".

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <and-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  <term-query>`
`  <text>cat</text>`
`  </term-query>`
`  <ordered>true</ordered>`
`  </and-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "and-query": {`
	`  "queries": [`
	`  {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  },`
	`  {`
	`  "term-query": {`
	`  "text": [ "cat" ]`
	`  }`
	`  },`
	`  { "ordered": "true" }`
	`  ]`
	`  }`
	`  }]`
	`}}`

4.6.4 or-query

Find the union of matches specified by one or more sub-queries. For details, see `cts:or-query`.

- Syntax Summary
- Component Description
- Examples

4.6.4.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<or-query>`
`  anyQueryType`
`</or-query>`
	`"or-query": {`
	`  "queries": [ anyQueryType ]`
	`}`

4.6.4.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	N	One or more sub-queries.

4.6.4.3 Examples

The following example matches documents containing either the phrase “dog bone” or the term “cat”.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <or-query>`
`  <term-query>`
`  <text>dog bone</text>`
`  </term-query>`
`  <term-query>`
`  <text>cat</text>`
`  </term-query>`
`  </or-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "or-query": {`
	`  "queries": [`
	`  {`
	`  "term-query": {`
	`  "text": ["dog bone"]`
	`  }`
	`  },`
	`  {`
	`  "term-query": {`
	`  "text": [ "cat" ]`
	`  }`
	`  }`
	`  ]}`
	`  }]`
	`}}`

4.6.5 and-not-query

Find the set difference of the matches specified by two sub-queries. That is, return results that match the positive query, but which do not match the negative query. For details, see `cts:and-not-query`.

- Syntax Summary
- Component Description
- Examples

4.6.5.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<and-not-query>`
`  <positive-query>`
`  anyQueryType`
`  </positive-query>`
`  <negative-query>`
`  anyQueryType`
`  </negative-query>`
`</and-not-query>`
	`"and-not-query": {`
	`  "positive-query": { anyQueryType },`
	`  "negative-query" : { anyQueryType }`
	`}`

4.6.5.2 Component Description

Element or JSON Property Name	Req'd?	Description
`positive-query`	Y	A query specifying the results filtered in. All results will match this query.
`negative-query`	Y	A query specifying the results filtered out. None of the results will match this query.

4.6.5.3 Examples

The following example matches occurrences of dog, but only where “cat” does not occur in the same fragment.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <and-not-query>`
`  <positive-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  </positive-query>`
`  <negative-query>`
`  <term-query>`
`  <text>cat</text>`
`  </term-query>`
`  </negative-query>`
`  </and-not-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "and-not-query": {`
	`  "positive-query": {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }},`
	`  "negative-query": {`
	`  "term-query": {`
	`  "text": [ "cat" ]`
	`  }}`
	`  }`
	`  }]`
	`}}`

4.6.6 not-query

A query that filters out any results that match its sub-query. For details, see `cts:not-query`.

- Syntax Summary
- Component Description
- Examples

4.6.6.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<not-query>`
`  anyQueryType`
`</not-query>`
	`"not-query": {`
	`  anyQueryType`
	`}`

4.6.6.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	Y	A negative query, specifying the search results to filter out.

4.6.6.3 Examples

The following only matches documents that do not include the term "dog".

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<query>`
`  <not-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  </not-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "not-query": {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  }`
	`  }]`
	`}}`

4.6.7 not-in-query

A query that returns results matching a positive query only when those matches do not overlap positionally with matches to a negative query. For details, see `cts:not-in-query`.

- Syntax Summary
- Component Description
- Examples

4.6.7.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<not-in-query>`
`  <positive-query>`
`  *anyQueryType*`
`  </positive-query>`
`  <negative-query>`
`  *anyQueryType*`
`  </negative-query>`
`</not-in-query>`
	`"not-in-query": {`
	`  "positive-query": { *anyQueryType* },`
	`  "negative-query" : { *anyQueryType* }`
	`}`

4.6.7.2 Component Description

Element or JSON Property Name	Req'd?	Description
`positive-query`	Y	A positive query, specifying the search results to filter in.
`negative-query`	Y	A negative query, specifying the search results to filter out.

4.6.7.3 Examples

The example below matches fragments that contain at least one occurrence of "dog" outside of the phrase "man bites dog".

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <not-in-query>`
`  <positive-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  </positive-query>`
`  <negative-query>`
`  <term-query>`
`  <text>man bites dog</text>`
`  </term-query>`
`  </negative-query>`
`  </not-in-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "not-in-query": {`
	`  "positive-query": {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }},`
	`  "negative-query": {`
	`  "term-query": {`
	`  "text": [`
	`  "man bites dog"`
	`  ]`
	`  }}`
	`  }`
	`  }]`
	`}}`

4.6.8 near-query

A query that returns results matching all of the specified queries where the matches occur within a specified distance of each other. For details, see `cts:near-query`.

- Syntax Summary
- Component Description
- Examples

4.6.8.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<near-query>`
`  anyQueryType`
`  <distance>double</distance>`
`  <distance-weight>`
`  double`
`  </distance-weight>`
`  <ordered>boolean</ordered>`
`</near-query>`
	`"near-query": {`
	`  "queries": [`
	`  anyQueryType,`
	`  "distance": "number",`
	`  "distance-weight": "number",`
	`  "ordered" : boolean`
	`  ]`
	`}`

4.6.8.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	Y	One or more queries that must match within the specified proxmity to each other.
`distance`	N	A distance, in number of words, between any two matching queries. Default: 10
`distance-weight`	N	A weight attributed to the distance for this query. Higher weights add to the importance of distance (as opposed to term matches) when the relevance order is calculated. Default: 1.0.
`ordered`	N	Whether or not the sub-query matches must occur in the order of the sub-queries. For example, if the sub-queries are "cat" and "dog", an ordered query will only match fragments where both "cat" and "dog" occur within the required distance and "cat" comes before "dog" in the fragment. Default: false.

4.6.8.3 Examples

The following example matches occurrences of "dog" occuring within in two terms of "cat".

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <near-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  <term-query>`
`  <text>cat</text>`
`  </term-query>`
`  <distance>2</distance>`
`  </near-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "near-query": {`
	`  "queries": [`
	`  {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  },`
	`  {`
	`  "term-query": {`
	`  "text": [ "cat" ]`
	`  }`
	`  },`
	`  { "distance": "2" }`
	`  ]`
	`  }`
	`  }]`
	`}}`

4.6.9 boost-query

Find all matches to a query. Boost the search relevance score of results that also match the boosting query. For details, see `cts:boost-query` and "Boosting Relevance Score With a Secondary Query" on page 415.

- Syntax Summary
- Component Description
- Examples

4.6.9.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<boost-query>`
`  <matching-query>`
`  *anyQueryType*`
`  </matching-query>`
`  <boosting-query>`
`  anyQueryType`
`  </boosting-query>`
`</and-query>`
	`"boost-query": {`
	`  "matching-query": { *anyQueryType* },`
	`  "boosting-query" : { *anyQueryType* }`
	`}`

4.6.9.2 Component Description

Element or JSON Property Name	Req'd?	Description
`matching-query`	N	The query to match. All search results matching this query are returned (modulo limitations imposed by search options). This element can occur multiple times; multiple occurrences are AND'd together. If there are no occurrences, the boosting query implicitly matches all documents.
`boosting-query`	N	The query to use for relevance score boosting. Those results which match both `matching-query` and `boosting-query` have their relevance scores modified proportional to the weight of `boosting-query`. The `boosting-query` is not evaluated if there are no matches to `matching-query`. This element can occur multiple times; multiple occurrences are AND'd together. If there are no occurrences, the boosting query implicitly matches all documents.

4.6.9.3 Examples

The following example searches for documents containing the term “dog”. Documents that also contain the term “cat” will return a search:result with a relevance score boosted proportional to the weight 10.0, giving them higher scores than documents that do not contain “cat”.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <boost-query>`
`  <matching-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  </matching-query>`
`  <boosting-query>`
`  <term-query>`
`  <text>cat</text>`
`  <weight>10.0</weight>`
`  </term-query>`
`  </boosting-query>`
`  </boost-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "boost-query": {`
	`  "matching-query": {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }},`
	`  "boosting-query": {`
	`  "term-query": {`
	`  "text": [ "cat" ],`
	`  "weight": "10.0"`
	`  }}`
	`  }`
	`  }]`
	`}}`

4.6.10 properties-fragment-query

A query that matches all documents where the sub-query matches against document properties. For details, see `cts:properties-fragment-query`.

- Syntax Summary
- Component Description
- Examples

4.6.10.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<properties-fragment-query>`
`  anyQueryType`
`</properties-fragment-query>`
	`"properties-fragment-query": {`
	`  anyQueryType`
	`}`

4.6.10.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	Y	A sub-query to run against document properties.

4.6.10.3 Examples

The following example matches all documents modified since 2012-12-31, assuming you define an element range index on the "last-modified" property and your query includes options defining the "modified" constraint.

Format	Query

XML	<options xmlns="http://marklogic.com/appservices/search">
	  <constraint name="modified">
	  <range type="xs:string">
	  <element
	  ns="http://marklogic.com/xdmp/property"
	  name="last-modified"/>
	  <fragment-scope>properties</fragment-scope>
	  </range>
	  </constraint>
	</options>
	
	<query xmlns="http://marklogic.com/appservices/search">
	  <properties-fragment-query>
	  <range-constraint-query>
	  <constraint-name>modified</constraint-name>
	  <value>2012-12-31</value>
	  <range-operator>GT</range-operator>
	  </range-constraint-query>
	  </properties-fragment-query>
	</query>

Format	Query

JSON	{
	  "options": {
	  "constraint": [
	  {
	  "name": "modified",
	  "range": {
	  "type": "xs:string",
	  "element": {
	  "ns": "http://marklogic.com/xdmp/property",
	  "name": "last-modified"
	  },
	  "fragment-scope": "properties"
	  }]
	}}
	
	{
	  "query": {
	  "queries": [{
	  "properties-fragment-query": {
	  "range-constraint-query": {
	  "value": ["2012-12-31"],
	  "constraint-name": "modified",
	  "range-operator": "GT"
	  }
	  }
	  }]
	}}

4.6.11 directory-query

A query matching documents in the directories with the given URIs. For details, see `cts:directory-query`.

- Syntax Summary
- Component Description
- Examples

4.6.11.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<directory-query>`
`  <uri>`*`directory-uri`*`</uri>`
`  <infinite>`*`boolean`*`</infinite>`
`</directory-query>`
	`"directory-query": {`
	`  "uri": [ `*`directory-uris`*` ],`
	`  "infinite": `*`boolean`*
	`}`

4.6.11.2 Component Description

Element or JSON Property Name	Req'd?	Description
`uri`	Y	One or more directory URIs. A directory URI must end with a forward slash ("/").
`infinite`	N	Whether or not to recurse through all child directories. Default: true.

4.6.11.3 Examples

The following example matches documents in the database directories `/documents/` or `/images/`, but does not look for matches in any sub-directories.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <directory-query>`
`  <uri>/documents/</uri>`
`  <uri>/images/</uri>`
`  <infinite>false</infinite>`
`  </directory-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "directory-query": {`
	`  "uri": [`
	`  "/documents/",`
	`  "/images/"`
	`  ],`
	`  "infinite": false`
	`  }`
	`  }]`
	`}}`

4.6.12 collection-query

A query matching documents in any of the collections with the given URIs. For details, see `cts:collection-query`.

- Syntax Summary
- Component Description
- Examples

4.6.12.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<collection-query>`
`  <uri>`*`collection-uri`*`</uri>`
`</collection-query>`
	`"collection-query": {`
	`  uri": [ `*`collection-uris`*` ]`
	`}`

4.6.12.2 Component Description

Element or JSON Property Name	Req'd?	Description
`uri`	Y	One or more collection URIs. A document matches if it is in any one of the collections specified by `uri`.

4.6.12.3 Examples

The following example matches documents in the `reports` collection or the `analysis` collection.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <collection-query>`
`  <uri>reports</uri>`
`  <uri>analysis</uri>`
`  </collection-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "collection-query": {`
	`  "uri": ["reports","analysis"]`
	`  }`
	`  }]`
	`}}`

4.6.13 container-query

A query matching documents containing a specified XML element or JSON property whose contents match a specified sub-query.

- Syntax Summary
- Component Description
- Examples

4.6.13.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<container-query>`
`  <element name=`*`string`* `ns=`*`string`* `/>`
`  <json-property>`*`name`*`</json-property>`
`  <fragment-scope>`*`scope`*`</fragment-scope>`
`  `*`anyQueryType`*
`</container-query>`
	`"container-query": {`
	`  "element": {`
	`  "name": `*`elem-name`*`,`
	`  "ns": `*`namespace`*
	`  },`
	`  "json-property": `*`prop-name`*`,`
	`  "fragment-scope": `*`scope`*`,`
	`  `*`anyQueryType`*
	`}`

4.6.13.2 Component Description

Element or JSON Property Name	Req'd?	Description
`element`	Y	An XML element descriptor, identified by `name` and namespace (`ns`). Both `name` and `ns` are required. If you include `element`, you should not include a `json-property`. If you specify multiple elements, the query matches documents that satisfy any one of the element constraints.
`json-property`	Y	A JSON property name. If you include `json-property`, you should not include an `element`. If you specify multiple properties, the query matches documents that satisfy any one of the property constraints.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the fragment-scope query option.
`anyQueryType`	Y	A sub-query to run against the contents of matching containers (XML elements or JSON properties).

Your query must include exactly one of `element` or `json-property`.

4.6.13.3 Examples

The following XML example matches all documents containing a `<pets/>` element with descendants whose contents match the term “dog”. The JSON example matches all documents containing the property named “pets” with descendants whose contents match the term “dog”.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <container-query>`
`  <element name="pet" ns="" />`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "container-query": {`
	`  "json-property": "pet",`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  }`
	`  }]`
	`}}`

4.6.14 document-query

A query matching documents with the given URIs.. For details, see `cts:document-query`.

- Syntax Summary
- Component Description
- Examples

4.6.14.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<document-query>`
`  <uri>`*`document-uri`*`</uri>`
`</document-query>`
	`"document-query": {`
	`  "uri": [ `*`document-uris`*` ]`
	`}`

4.6.14.2 Component Description

Element or JSON Property Name	Req'd?	Description
`uri`	Y	One or more document URIs.

4.6.14.3 Examples

The following example matches either the document with URI `/documents/reports.xml` or the document with URI `/documents/analysis.xml`.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <document-query>`
`  <uri>/documents/reports.xml</uri>`
`  <uri>/documents/analysis.xml</uri>`
`  </document-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "document-query": {`
	`  "uri": [`
	`  "/documents/reports.xml",`
	`  "/documents/analysis.xml"`
	`  ]`
	`  }`
	`  }]`
	`}}`

4.6.15 document-fragment-query

A query that matches all documents where a sub-query matches any document fragment. For details, see `cts:document-fragment-query`.

- Syntax Summary
- Component Description
- Examples

4.6.15.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<document-fragment-query>`
`  anyQueryType`
`</document-fragment-query>`
	`"document-fragment-query": {`
	`  anyQueryType`
	`}`

4.6.15.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	Y	The query to be matched against any document fragment.

4.6.15.3 Examples

The following example matches any documents that include fragments that contain the term `dog`.

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<query>`
`  <document-fragment-query>`
`  <term-query>`
`  <text>dog</text>`
`  </term-query>`
`  </document-fragment-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "document-fragment-query": {`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  }`
	`  }]`
	`}}`

4.6.16 locks-fragment-query

A query that matches all documents where a sub-query matches a `document-locks` fragment. For details, see `cts:locks-fragment-query`.

- Syntax Summary
- Component Description
- Examples

4.6.16.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<locks-fragment-query>`
`  anyQueryType`
`</locks-fragment-query>`
	`"locks-fragment-query": {`
	`  anyQueryType`
	`}`

4.6.16.2 Component Description

Element or JSON Property Name	Req'd?	Description
anyQueryType	Y	The query to be matched against any document fragment.

4.6.16.3 Examples

The following example matches documents with document locks fragments that include the term `write` in `lock:lock-type` element. This example assumes the existence of an element range index on `lock:lock-type` and query options that include a constraint on that element with the name `lock-type`.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <locks-fragment-query>`
`  <container-constraint-query>`
`  <constraint-name>`
`  lock-type`
`  </constraint-name>`
`  <term-query>`
`  <text>write</text>`
`  </term-query>`
`  </container-constraint-query>`
`  </locks-fragment-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "locks-fragment-query": {`
	`  "container-constraint-query": {`
	`  "constraint-name": "lock-type",`
	`  "term-query": {`
	`  "text": [ "write" ]`
	`  }`
	`  }}`
	`  }]`
	`}}`

4.6.17 range-query

A query that applies a range constraint and compares the results to the specified value. For details, see “Constraint Options” on page 369 and the XQuery functions `cts:element-range-query`, `cts:element-attribute-range-query`, `cts:field-range-query`, and `cts:path-range-query`.

A `range-query` is equivalent to string query expressions of the form `constraint:value` or `constraint LE value`. The constraint is defined in the query and must be backed by a range index.

- Syntax Summary
- Component Description
- Examples

4.6.17.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<range-query type=`*`index-type`* ` collation=`*`uri`*`>`
`  <element name=`*`elem-name`* ` ns=`*`namespace`* ` />`
`  <attribute name=`*`attr-name`* ` ns=`*`namespace`* ` />`
`  <json-property>`*`name`*`</json-property>`
`  <field name=`*`field-name`* ` collation=`*`uri`* ` />`
`  <path-index>`*`path-expr`*`</path-index>`
`  <fragment-scope>`*`scope`*`</fragment-scope>`
`  <value>`*`value`*`</value>`
`  <range-operator>`*`operator`*`</operator>`
`  <range-option>`*`option`*`</range-option>`
`</range-query>`
	`"range-query": {`
	`  "type": `*`index-type`*`,`
	`  "collation": `*`index-collation-uri`*`,`
	`  "element": {`
	`  "name": `*`elem-name`*`,`
	`  "ns": `*`namespace`*
	`  },`
	`  "attribute": {`
	`  "name": `*`attr-name`*`,`
	`  "ns": `*`namespace`*
	`  },`
	`  "json-property": `*`prop-name`*`,`
	`  "field": {`
	`  "name": `*`field-name`*`,`
	`  "collation": `*`uri`*
	`  },`
	`  "path-index": {`
	`  "text": `*`path-expr`*`,`
	`  "namespaces": {`
	`  `*`prefix`*`: `*`namespace-uri`*
	`  }`
	`  },`
	`  "fragment-scope": `*`scope`*`,`
	`  "value": `*`value-as-string`*`,`
	`  "range-operator": `*`operator`*`,`
	`  "range-option": `*`option`*
	`}`

4.6.17.2 Component Description

You must specify an `element`, `json-property`, `field`, or `path-index`, or an `element` and an `attribute` to define the range constraint to apply to the query. These components are mutually exclusive: Except for `element` and `attribute`, a query must include exactly one.

Element or JSON Property Name	Req'd?	Description
`element`	N	An XML element descriptor, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required. If you include `element`, you should not include a `json-property`, `field`, or `path-index`.
`attribute`	N	An XML attribute descriptor, identifying the attribute by `name` and namespace (`ns`). Both `name` and `ns` are required.
`json-property`	N	A JSON property name. If you include `json-property`, you should not include an `element`, `field`, or `path-index`.
`field`	N	A field descriptor, identified by the field `name` (required) and optional `collation`. The database configuration must include a definition for this field. If you include `field`, you should not include an `element`, `json-property`, or `path-index`.
`path-index`	N	A path range expression. If the path expression includes namespace prefixes, you must define the namespace bindings on the `path-index`. If you include `path-index`, you should not include an `element`, `json-property`, or `field`. The database configuration must include a matching path range index. The path expression and namespace URIs must match the index configuration; namespace prefixes do not have to match. The path expression is limited to the subset of XPath that can be used to define a path range index. For details, see Understanding Path Range Indexes in *Administrator's Guide*.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.

Element or JSON Property Name	Req'd?	Description
`value`	N	The value against which to match XML elements, XML element attributes, JSON properties, or fields that match the constraint identified by `constraint-name`. This element can occur 0 or more times.
`range-operator`	N	One of `LT`, `LE`, `GT`, `GE`, `EQ`, `NE`. Default: `EQ`. The relationship that must be satisfied between constraint matches and `value`.
`range-option`	N	One or more range query options. Allowed values depend on the type of range query (element, path, field, etc.). For details, see Including a Range or Geospatial Query in Scoring in *Search Developer's Guide*. For a list of options, see "Range Options" on page 797.
`type`	N	The type of the range index. Required when you have multiple indexes over the same item with different datatypes.
`collation`	N	A collation URI to use if the index type is string.

4.6.17.3 Examples

The following example matches documents containing a `<body-color/>` element with a value of `black`, assuming an element range index exists on `<body-color/>`.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <range-query type="xs:string">`
`  <element ns="" name="body-color"/>`
`  <value>black</value>`
`  </range-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "range-query": {`
	`  "type": "xs:string",`
	`  "element": {`
	`  "ns": "",`
	`  "name": "body-color"`
	`  },`
	`  "value": [ "black" ]`
	`  }`
	`  }]`
	`}}`

4.6.18 value-query

A query that matches fragments where the value of an XML element, XML attribute, JSON property, or field matches value in the `text` XML element or JSON property of the query.

When searching JSON documents, the criteria value in the query `text` element or JSON property must be properly typed by setting the `type` element or property in the query. If you do not set `type` in the query, "string" is assumed, which will never match a number, boolean, or null value in a JSON document.

The match semantics depend on the `text` value, the database configuration, and the options in effect. For details, see "Text Match Semantics" on page 83 or `cts:element-value-query`, `cts:element-attribute-value-query`, `cts:json-property-value-query`, or `cts:field-value-query`.

- Syntax Summary
- Component Description
- Examples

4.6.18.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<value-query type=node-type>`
`  <element name=elem-name ns=namespace />`
`  <attribute name=attr-name ns=namespace />`
`  <json-property>name</json-property>`
`  <field name=field-name collation=uri />`
`  <fragment-scope>scope</fragment-scope>`
`  <text>name</text>`
`  <term-option>option/term-option>`
`  <weight>value</weight>`
`</value-query>`
	`"value-query": {`
	`  "type": node-type,`
	`  "element": {`
	`  "name": elem-name,`
	`  "ns": namespace`
	`  },`
	`  "attribute": {`
	`  "name": attr-name,`
	`  "ns": namespace`
	`  },`
	`  "json-property": name,`
	`  "field": {`
	`  "name": field-name,`
	`  "collation": uri`
	`  },`
	`  "fragment-scope": scope,`
	`  "text": [ name ],`
	`  "term-option": [ option ],`
	`  "weight": number`
	`}`

4.6.18.2 Component Description

You must specify an `element`, `json-property`, `field`, or an `element` and an `attribute` to define the range constraint to apply to the query. These components are mutually exclusive: Except for `element` and `attribute`, a query must include exactly one.

Element, Attribute, or JSON Property Name	Req'd?	Description
`type`	N	A JSON node type, one of `string` (default), `boolean`, `null`, `number`. Only meaningful for JSON content. Use `type` to constrain the matches to values in this node type. Non-JSON documents never contain boolean, null or number nodes.
`element`	N	An XML element descriptor, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required. If you include `element`, you should not include a `json-property`.
`attribute`	N	An XML attribute descriptor, identifying the attribute by `name` and namespace (`ns`). Both `name` and `ns` are required.
`json-property`	N	A JSON property name. If you include `json-property`, you should not include an `element`.
`field`	N	A field descriptor, identified by the field `name` (required) and optional `collation`. The database configuration must include a definition for this field.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`text`	N	The value that must match in an XML element, XML element attribute, JSON property, or field value. Multiple values can be specified. If there is no `type` specifier, the values are treated as strings for matching purposes. The interpretation of the value is determined by the `type` setting in the query.

Element, Attribute, or JSON Property Name	Req'd?	Description
`term-option`	N	Term options to apply to the query when matching text. You can specify multiple term options. If the option has a value, the value of term-option is option=value. For example: `<term-option>min-occurs=1</term-option>`. For details, see the `cts` query corresponding to the query constraint type: `cts:element-value-query`, `cts:element-attribute-value-query`, `cts:json-property-value-query`, or `cts:field-value-query`; and "Term Options" on page 796.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.

4.6.18.3 Examples

The following example matches documents where the field defined with the name "`myFieldName`" has the value "`Jane Doe`". The example assumes the field "`myFieldName`" is defined in the database configuration and that field searches are enabled for the database.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <value-query>`
`  <field name="myFieldName" />`
`  <text>Jane Doe</text>`
`  </value-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "value-query": {`
	`  "field": {`
	`  "name": "myFieldName",`
	`  },`
	`  "text": [ "Jane Doe" ],`
	`  }`
	`  }]`
	`}}`

The following example matches documents where the JSON property "num" contains the number value 42. Since `type` is set to "number", the query matches a document such as `{ "num": 42 }`, but it will not match a document such as `{ "num": "42" }`. If you did not set type, then the type would be string and the query would match a document such as `{ "num": "42" }` but would not match a document such as `{ "num": "42" }`.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <value-query>`
`  <json-property>num</json-property>`
`  <text>42</text>`
`  <type>number</type>`
`  </value-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "value-query": {`
	`  "json-property": "num",`
	`  "type": "number",`
	`  "text": [ "42" ],`
	`  }`
	`  }]`
	`}}`

Note that in the JSON version of the query, the value of `text` can be either a string ("42") or a number (42). The interpretation of the value depends on the `type` setting in the query.

4.6.19 word-query

A query that matches fragments containing the specified terms or phrases in the XML element or attribute, JSON property, or field identified by the constraint defined in the query. This is similar to a string query of the form `constraint:value`, where the constraint is an element, element attribute, JSON property, or field constraint. For details, see the cts word query function that corresponds to your constraint type, such as `cts:element-word-query` or `cts:field-word-query`.

- Syntax Summary
- Component Description
- Examples

4.6.19.1 Syntax Summary

<table>
<tr><th>XML</th><th>JSON</th></tr>
<tr><td>All elements are in the namespace
http://marklogic.com/appservices/search.

<word-query>
  <element name=<i>elem-name</i> ns=<i>namespace</i> />
  <attribute name=<i>attr-name</i> ns=<i>namespace</i>
/>
  <json-property><i>name</i></json-property>
  <field name=<i>field-name</i> collation=<i>uri</i> />
  <fragment-scope><i>scope</i></fragment-scope>
  <text><i>name</i></text>
  <term-option><i>option</i>/term-option>
  <weight><i>value</i></weight>
</word-query></td><td>"word-query": {
  "element": {
  "name": <i>elem-name</i>,
  "ns": <i>namespace</i>
  },
  "attribute": {
  "name": <i>attr-name</i>,
  "ns": <i>namespace</i>
  },
  "json-property": <i>prop-name</i>,
  "field": {
  "name": <i>field-name</i>,
  "collation": <i>uri</i>
  },
  "fragment-scope": <i>scope</i>,
  "text": [<i>name</i>],
  "term-option": [<i>option</i>],
  "weight": <i>number</i>
}</td></tr>
</table>

4.6.19.2 Component Description

You must specify at least one `element`, `json-property`, `field`, or an `element` and an `attribute` to define the range constraint to apply to the query. These components are mutually exclusive: Except for `element` and `attribute` pairs, a `word-query` must include exactly one type of constraint specifier.

Element or JSON Property Name	Req'd?	Description
`element`	N	An XML element descriptor, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required. You can specify multiple elements, in which case the query matches if a match is found in any of the elements. If you include `element`, you should not include a `json-property` or `field`.
`attribute`	N	An XML attribute descriptor, identifying the attribute by `name` and namespace (`ns`). Both `name` and `ns` are required. You can specify multiple attributes, in which case the query matches if a match is found in any of the attributes. You cannot use this component in conjunction with `json-property` or `field`.
`json-property`	N	A JSON property name. You can specify multiple properties, in which case the query matches if a match is found in any of the properties. If you include `json-property`, you should not include an `element`, `attribute`, or `field`.
`field`	N	A field descriptor, identified by the field `name` (required) and optional `collation`. The database configuration must include a definition for the field. You can specify multiple fields, in which case the query matches if a match is found in any of the fields. If you include `field`, you should not include an `element`, `attribute`, or `json-property`.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`text`	N	Terms or phrases that must occur in documents matching the constraint defined by this query. Multiple values can be specified; if any one matches, the document matches the query.

Element or JSON Property Name	Req'd?	Description
`term-option`	N	Term options to apply to the query. You can specify multiple term options. If the option has a value, the value of term-option is option=value. For example: `<term-option>min-occurs=1</term-option>`. For details, see the `cts` query corresponding to the query constraint type, such as: `cts:element-word-query`, `cts:element-attribute-word-query`, `cts:json-property-word-query`, or `cts:field-word-query`; and "Term Options" on page 796.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.

4.6.19.3 Examples

The following example matches documents containing a `<body-color/>` element that contains the word `black`.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<query>`
`  <word-query>`
`  <element name="body-color" ns="" />`
`  <text>black</text>`
`  </word-query>`
`</query>`
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "word-query": {`
	`  "element": {`
	`  "name": "body-color",`
	`  "ns": ""`
	`  },`
	`  "text": [ "black" ],`
	`  }`
	`  }]`
	`}}`

4.6.20 geo-elem-query

A query that returns documents that match the geospatial element constraint defined in the query. For details, see `cts:element-geospatial-query`, `cts:element-child-geospatial-query`, or "Geospatial Search Applications" on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.20.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geo-elem-query>` `  <parent name=`*elem-name* `ns=`*uri* `/>` `  <element name=`*elem-name* `ns=`*uri* `/>` `  <geo-option>`*option*`</geo-option>` `  <fragment-scope>`*scope*`</fragement-scope>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `</geo-elem-query>`	`"geo-elem-query": {` `  "parent": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "element": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "geo-option": [ `*option*` ],` `  "fragment-scope": `*scope*`,` `  "point": [` `  {` `  "latitude": `*number*`,` `  "longitude": `*number* `  }` `  ],` `  "box": [` `  {` `  "south": `*number*`,` `  "west": `*number*`,` `  "north": `*number*`,` `  "east": `*number* `  }` `  ],` `  "circle": [` `  {` `  "radius": `*number*`,` `  *point* ` }` `],` ` "polygon": [`*point*`]` `}`

4.6.20.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element pair containing geospatial data are described by `parent`, `lat`, and `lon`. For details, see "Geospatial Search Applications" on page 462

Element or JSON Property Name	Req'd?	Description
`parent`	N	Optional. The parent element of the element containing geospatial data, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required.
`element`	Y	The element containing geospatial data, identified by `name` and namespace (`ns`). Both `name` and `ns` are required.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:element-geospatial-query` or `cts:element-child-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.20.3 Examples

The following example matches points contained in either of two polygons. The constraint defined in the query by `parent` and `element` defines how to construct the points to match against the regions defined in the query.

Format	Query

XML	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <geo-elem-query>`
	`  <parent ns="ns1" name="elem1"/>`
	`  <element ns="ns1" name="elem2"/>`
	`  <polygon>`
	`  <point> <latitude>1</latitude> <longitude>2</longitude> </point>`
	`  <point> <latitude>3</latitude> <longitude>4</longitude> </point>`
	`  <point> <latitude>5</latitude> <longitude>6</longitude> </point>`
	`  <point> <latitude>7</latitude> <longitude>8</longitude> </point>`
	`  </polygon>`
	`  <polygon>`
	`  <point> <latitude>2</latitude> <longitude>6</longitude> </point>`
	`  <point> <latitude>3</latitude> <longitude>7</longitude> </point>`
	`  <point> <latitude>4</latitude> <longitude>8</longitude> </point>`
	`  <point> <latitude>5</latitude> <longitude>9</longitude> </point>`
	`  </polygon>`
	`  </geo-elem-query>`
	`</query>`

Format	Query

JSON	<pre>{
	  "query": {
	    "queries": [{
	      "geo-elem-query": {
	        "parent": { "ns": "ns1", "name": "elem1" },
	        "element": { "ns": "ns1", "name": "elem2" },
	        "polygon": [
	          {
	            "point": [
	              { "latitude": 1, "longitude": 2 },
	              { "latitude": 3, "longitude": 4 },
	              { "latitude": 5, "longitude": 6 },
	              { "latitude": 7, "longitude": 8 }
	            ]
	          },
	          {
	            "point": [
	              { "latitude": 2, "longitude": 6 },
	              { "latitude": 3, "longitude": 7 },
	              { "latitude": 4, "longitude": 8 },
	              { "latitude": 5, "longitude": 9 }
	            ]
	          }
	        ]
	      }
	    }]
	}}</pre>

4.6.21 geo-elem-pair-query

A query that returns documents that match the geospatial XML element constraint defined in the query. For details, see `cts:element-pair-geospatial-query` and "Geospatial Search Applications" on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.21.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geo-elem-pair-query>` `  <parent name=`*elem-name* `ns=`*uri* `/>` `  <lat name=`*elem-name* `ns=`*uri* `/>` `  <lon name=`*elem-name* `ns=`*uri* `/>` `  <geo-option>`*option*`</geo-option>` `  <fragment-scope>`*scope*`</fragement-scope>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `</geo-elem-pair-query>`	`"geo-elem-pair-query": {` `  "parent": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "lat": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "lon": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "geo-option": [ `*option*` ],` `  "fragment-scope": `*scope*`,` `  "point": [` `  {` `  "latitude": `*number*`,` `  "longitude": `*number* `  }` `  ],` `  "box": [` `  {` `  "south": `*number*`,` `  "west": `*number*`,` `  "north": `*number*`,` `  "east": `*number* `  }` `  ],` `  "circle": [` `  {` `  "radius": `*number*`,` `  *point* ` }` `],` ` "polygon": [`*point*`]` `}`

4.6.21.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element pair containing geospatial data are described by `parent`, `lat`, and `lon`.

Element or JSON Property Name	Req'd?	Description
`parent`	N	The element containing geospatial data, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required.
`lat`	Y	The XML element containing latitude data, identified by `name` and namespace (`ns`). Both `name` and `ns` are required.
`lon`	Y	The XML element containing longitude data, identified by `name` and namespace (`ns`). Both `name` and `ns` are required.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:element-pair-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.21.3 Examples

The following example matches points contained in either of two polygons. The constraint defined in the query by `parent`, `lat`, and `lon` defines how to construct the points to match against the regions defined in the query.

Format	Query
XML	<query xmlns="http://marklogic.com/appservices/search"> <geo-elem-pair-query> <parent ns="ns1" name="elem2"/> <lat ns="ns2" name="attr2"/> <lon ns="ns3" name="attr3"/> <polygon> <point> <latitude>1</latitude> <longitude>2</longitude> </point> <point> <latitude>3</latitude> <longitude>4</longitude> </point> <point> <latitude>5</latitude> <longitude>6</longitude> </point> <point> <latitude>7</latitude> <longitude>8</longitude> </point> </polygon> <polygon> <point> <latitude>2</latitude> <longitude>6</longitude> </point> <point> <latitude>3</latitude> <longitude>7</longitude> </point> <point> <latitude>4</latitude> <longitude>8</longitude> </point> <point> <latitude>5</latitude> <longitude>9</longitude> </point> </polygon> </geo-elem-pair-query> </query>

Format	Query

JSON	{"query": {
	"queries": [{
	"geo-elem-pair-query": {
	"parent": { "ns": "ns1", "name": "elem2" },
	"lat": { "ns": "ns2", "name": "attr2" },
	"lon": { "ns": "ns3", "name": "attr3" }
	"polygon": [
	{
	"point": [
	{ "latitude": 1, "longitude": 2 },
	{ "latitude": 3, "longitude": 4 },
	{ "latitude": 5, "longitude": 6 },
	{ "latitude": 7, "longitude": 8 }
	]
	},
	{
	"point": [
	{ "latitude": 2, "longitude": 6 },
	{ "latitude": 3, "longitude": 7 },
	{ "latitude": 4, "longitude": 8 },
	{ "latitude": 5, "longitude": 9 }
	]
	}
	]
	}
	}]
	}}

4.6.22 geo-attr-pair-query

A query that returns documents that match the geospatial element constraint defined in the query. For details, see `cts:element-attribute-pair-geospatial-query` or “Geospatial Search Applications” on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.22.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geo-attr-pair-query>` `  <parent name=`*elem-name* `ns=`*uri* `/>` `  <lat name=`*attr-name* `ns=`*uri* `/>` `  <lon name=`*attr-name* `ns=`*uri* `/>` `  <geo-option>`*option*`</geo-option>` `  <fragment-scope>`*scope*`</fragement-scope>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `</geo-attr-pair-query>`	`"geo-attr-pair-query": {` `  "parent": {` `  "name": `*elem-name* `  "ns": `*uri* `  },` `  "lat": {` `  "name": `*attr-name* `  "ns": `*uri* `  },` `  "lon": {` `  "name": `*attr-name* `  "ns": `*uri* `  },` `  "geo-option": [ `*option*` ],` `  "fragment-scope": `*scope*`,` `  "point": [` `  {` `  "latitude": `*number*`,` `  "longitude": `*number* `  }` `  ],` `  "box": [` `  {` `  "south": `*number*`,` `  "west": `*number*`,` `  "north": `*number*`,` `  "east": `*number* `  }` `  ],` `  "circle": [` `  {` `  "radius": `*number*`,` `  *point* ` }` `],` ` "polygon": [`*point*`]` `}`

4.6.22.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element pair containing geospatial data are described by `parent`, `lat`, and `lon`. For details, see "Geospatial Search Applications" on page 462

Element or JSON Property Name	Req'd?	Description
`parent`	Y	The element containing the `lat` and `lon` attributes that hold geospatial data, identified by element `name` and namespace (`ns`). Both `name` and `ns` are required.
`lat`	Y	The name of the attribute that contains latitude data, identified by `name` and namespace (`ns`). Both `name` and `ns` are required.
`lon`	Y	The name of the attribute that contains longitude data, identified by `name` and namespace (`ns`). Both `name` and `ns` are required.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:element-attribute-pair-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.22.3 Examples

The following example matches points contained in either of two polygons. The constraint defined in the query by `parent`, `lat`, and `lon` defines how to construct the points to match against the regions defined in the query.

Format	Query
XML	<query xmlns="http://marklogic.com/appservices/search"> <geo-attr-pair-query> <parent ns="ns1" name="elem"/> <lat ns="ns1" name="attr1"/> <lon ns="ns1" name="attr2" /> <polygon> <point> <latitude>1</latitude> <longitude>2</longitude> </point> <point> <latitude>3</latitude> <longitude>4</longitude> </point> <point> <latitude>5</latitude> <longitude>6</longitude> </point> <point> <latitude>7</latitude> <longitude>8</longitude> </point> </polygon> <polygon> <point> <latitude>2</latitude> <longitude>6</longitude> </point> <point> <latitude>3</latitude> <longitude>7</longitude> </point> <point> <latitude>4</latitude> <longitude>8</longitude> </point> <point> <latitude>5</latitude> <longitude>9</longitude> </point> </polygon> </geo-attr-pair-query> </query>

Format	Query

JSON	<pre>{
	  "query": {
	    "queries": [{
	      "geo-elem-query": {
	        "parent": { "ns": "ns1", "name": "elem1" },
	        "element": { "ns": "ns1", "name": "elem2" },
	        "polygon": [
	          {
	            "point": [
	              { "latitude": 1, "longitude": 2 },
	              { "latitude": 3, "longitude": 4 },
	              { "latitude": 5, "longitude": 6 },
	              { "latitude": 7, "longitude": 8 }
	            ]
	          },
	          {
	            "point": [
	              { "latitude": 2, "longitude": 6 },
	              { "latitude": 3, "longitude": 7 },
	              { "latitude": 4, "longitude": 8 },
	              { "latitude": 5, "longitude": 9 }
	            ]
	          }
	        ]
	      }
	    }]
	}}</pre>

4.6.23 geo-path-query

A query that returns documents that match the geospatial constraint defined in the query only when it occurs in an XML element, XML attribute, or JSON property that matches a specified XPath expression. For details, see `cts:path-geospatial-query` or “Geospatial Search Applications” on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.23.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-path-query>`
`  <path-index>`*`path-expr`*`</path-index>`
`  <geo-option>`*`option`*`</geo-option>`
`  <fragment-scope>`*`scope`*`</fragement-scope>`
`  <point>`
`  <latitude>`*`float`*`</latitude>`
`  <longitude>`*`float`*`</longitude>`
`  </point>`
`  <box>`
`  <south>`*`float`*`</south>`
`  <west>`*`float`*`</west>`
`  <north>`*`float`*`</north>`
`  <east>`*`float`*`</east>`
`  </box>`
`  <circle>`
`  <radius>`*`float`*`</radius>`
`  <point/>`
`  </circle>`
`  <polygon>`
`  <point/>`
`  </polygon>`
`</geo-path-query>`
	`"geo-path-query": {`
	`  "path-index": {`
	`  "text": `*`path-expr`*`,`
	`  "namespaces": [{`
	`  `*`prefix`*`: `*`namespace-uri`*
	`  }]`
	`  },`
	`  "geo-option": [ `*`option`*` ],`
	`  "fragment-scope": `*`scope`*`,`
	`  "point": [`
	`  {`
	`  "latitude": `*`number`*`,`
	`  "longitude": `*`number`*
	`  }`
	`  ],`
	`  "box": [`
	`  {`
	`  "south": `*`number`*`,`
	`  "west": `*`number`*`,`
	`  "north": `*`number`*`,`
	`  "east": `*`number`*
	`  }`
	`  ],`
	`  "circle": [`
	`  {`
	`  "radius": `*`number`*`,`
	`  `*`point`*
	`  }`
	`  ],`
	`  "polygon": [ `*`point`*` ]`
	`}`

4.6.23.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element or attribute containing geospatial data are described by `path-index`. For details, see “Geospatial Search Applications” on page 462

Element or JSON Property Name	Req'd?	Description
`path-index`	Y	A path range expression matching an element or attribute whose contents represent a point contained within the given geographic region(s). If the path expression includes namespace prefixes, you must define the namespace bindings on the `path-index`. The database configuration must include a matching path range index. The path expression and namespace URIs must match the index configuration; namespace prefixes do not have to match. The path expression is limited to the subset of XPath that can be used to define a path range index. For details, see Understanding Path Range Indexes in *Administrator's Guide*.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:element-attribute-pair-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.23.3 Examples

The following example matches points contained in either of two polygons. The constraint defined in the query by `path-index` defines how to construct the points to match against the regions defined in the query.

Format	Query
XML	<query xmlns="http://marklogic.com/appservices/search"> <geo-path-query> <path-index xmlns:ns1="/my/ns">/ns:a/ns:b</path-index> <polygon> <point> <latitude>1</latitude> <longitude>2</longitude> </point> <point> <latitude>3</latitude> <longitude>4</longitude> </point> <point> <latitude>5</latitude> <longitude>6</longitude> </point> <point> <latitude>7</latitude> <longitude>8</longitude> </point> </polygon> <polygon> <point> <latitude>2</latitude> <longitude>6</longitude> </point> <point> <latitude>3</latitude> <longitude>7</longitude> </point> <point> <latitude>4</latitude> <longitude>8</longitude> </point> <point> <latitude>5</latitude> <longitude>9</longitude> </point> </polygon> </geo-path-query> </query>

JSON	{"query":{
	  "geo-path-query":{
	  "path-index": {
	  "text": "/ns1:a/ns2:b",
	  "namespaces": [{"ns1": "/my/ns1"}, {"ns2": "my/ns2"}]
	  },
	  "polygon": [
	  {"point": [
	  { "latitude": 1, "longitude": 2 },
	  { "latitude": 3, "longitude": 4 },
	  { "latitude": 5, "longitude": 6 },
	  { "latitude": 7, "longitude": 8 }
	  ] },
	  {"point": [
	  { "latitude": 2, "longitude": 6 },
	  { "latitude": 3, "longitude": 7 },
	  { "latitude": 4, "longitude": 8 },
	  { "latitude": 5, "longitude": 9 }
	  ] }
	  ]
	  }
	}}

4.6.24 geo-json-property-query

A query that returns documents that match the geospatial constraint defined in the query only when it occurs a specified JSON property. For details, see `cts:json-property-geospatial-query`, `cts:json-property-child-geospatial-query`, or "Geospatial Search Applications" on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.24.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geo-json-property-query>` `  <parent-property>`*name*`</parent-property>` `  <json-property>`*name*`</json-property>` `  <geo-option>`*option*`</geo-option>` `  <fragment-scope>`*scope*`</fragement-scope>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `</geo-json-property-query>`	`"geo-json-property-query": {` `  "parent-property":` *name*`,` `  "json-property":` *name*`,` `  "geo-option": [` *option* `],` `  "fragment-scope":` *scope*`,` `  "point": [` `  {` `  "latitude":` *number*`,` `  "longitude":` *number* `  }` `  ],` `  "box": [` `  {` `  "south":` *number*`,` `  "west":` *number*`,` `  "north":` *number*`,` `  "east":` *number* `  }` `  ],` `  "circle": [` `  {` `  "radius":` *number*`,` `  *point* ` }` `],` ` "polygon": [` *point* `]` `}`

4.6.24.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element pair containing geospatial data are described by `parent`, `lat`, and `lon`. For details, see "Geospatial Search Applications" on page 462

Element or JSON Property Name	Req'd?	Description
`parent-property`	N	Optional. The parent property of the property containing geospatial data, identified by name.
`json-property`	Y	The name of the property containing geospatial data.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:json-property-geospatial-query` or `cts:json-property-child-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.24.3 Examples

The following example matches points contained in either of two polygons. The JSON property defined in the query by `parent-property` and `json-property` defines how to construct the points to match against the regions defined in the query.

Format	Query

XML	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <geo-json-property-query>`
	`  <parent-property>myParent</parent>`
	`  <json-property>loc</json-property>`
	`  <polygon>`
	`  <point> <latitude>1</latitude> <longitude>2</longitude> </point>`
	`  <point> <latitude>3</latitude> <longitude>4</longitude> </point>`
	`  <point> <latitude>5</latitude> <longitude>6</longitude> </point>`
	`  <point> <latitude>7</latitude> <longitude>8</longitude> </point>`
	`  </polygon>`
	`  <polygon>`
	`  <point> <latitude>2</latitude> <longitude>6</longitude> </point>`
	`  <point> <latitude>3</latitude> <longitude>7</longitude> </point>`
	`  <point> <latitude>4</latitude> <longitude>8</longitude> </point>`
	`  <point> <latitude>5</latitude> <longitude>9</longitude> </point>`
	`  </polygon>`
	`  </geo-json-property-query>`
	`</query>`

Format	Query

JSON	<pre>{
	  "query": {
	    "queries": [{
	      "geo-json-property-query": {
	        "parent-property": "myParent",
	        "json-property": "loc",
	        "polygon": [
	          {
	            "point": [
	              { "latitude": 1, "longitude": 2 },
	              { "latitude": 3, "longitude": 4 },
	              { "latitude": 5, "longitude": 6 },
	              { "latitude": 7, "longitude": 8 }
	            ]
	          },
	          {
	            "point": [
	              { "latitude": 2, "longitude": 6 },
	              { "latitude": 3, "longitude": 7 },
	              { "latitude": 4, "longitude": 8 },
	              { "latitude": 5, "longitude": 9 }
	            ]
	          }
	        ]
	      }
	    }]
	}}</pre>

4.6.25 geo-json-property-pair-query

A query that returns documents that match the geospatial constraint defined in the query only when it occurs a JSON property that matches a specified XPath expression. For details, see `cts:json-property-pair-geospatial-query` or “Geospatial Search Applications” on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.25.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geo-json-property-pair-query>` `  <parent-property>`*name*`</parent-property>` `  <lat-property>`*name*`</lat-property>` `  <lon-property>`*name*`</lon-property>` `  <geo-option>`*option*`</geo-option>` `  <fragment-scope>`*scope*`</fragement-scope>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `</geo-json-property-pair-query>`	`"geo-json-property-pair-query": {` `  "parent-property":` *name*`,` `  "lat-property":` *name*`,` `  "lon-property":` *name*`,` `  "geo-option": [` *option* `],` `  "fragment-scope":` *scope*`,` `  "point": [` `  {` `  "latitude":` *number*`,` `  "longitude":` *number* `  }` `  ],` `  "box": [` `  {` `  "south":` *number*`,` `  "west":` *number*`,` `  "north":` *number*`,` `  "east":` *number* `  }` `  ],` `  "circle": [` `  {` `  "radius":` *number*`,` `  *point* ` }` `],` ` "polygon": [` *point* `]` `}`

4.6.25.2 Component Description

A geospatial query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects. The element pair containing geospatial data are described by `parent`, `lat-property`, and `lon-property`. For details, see "Geospatial Search Applications" on page 462

Element or JSON Property Name	Req'd?	Description
`parent-property`	Y	The name of JSON property containing `lat-property` and `lon-property`.
`lat-property`	Y	The name of the JSON property that contains latitude data.
`lon-property`	Y	The name of the JSON property that contains longitude data.
`fragment-scope`	N	Constrain matches to the specified fragment scope. Allowed values: `documents` (default) or `properties`. For more details, see the `fragment-scope` query option.
`geo-option`	N	Geospatial options to apply to the query. You can specify multiple options. If an option has a value, the value of `geo-option` is of the form *`option=value`*. For example: `<geo-option>units=miles</geo-option>`. For details, see `cts:json-property-pair-geospatial-query`.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.25.3 Examples

The following example matches points contained in either of two polygons. The constraint defined in the query by `parent`, `lat`, and `lon` defines how to construct the points to match against the regions defined in the query.

Format	Query
XML	<query xmlns="http://marklogic.com/appservices/search"> <geo-json-property-pair-query> <parent-property>myParent</parent> <lat-property>loc</lat-property> <lon-property>lon</lon-property> <polygon> <point> <latitude>1</latitude> <longitude>2</longitude> </point> <point> <latitude>3</latitude> <longitude>4</longitude> </point> <point> <latitude>5</latitude> <longitude>6</longitude> </point> <point> <latitude>7</latitude> <longitude>8</longitude> </point> </polygon> <polygon> <point> <latitude>2</latitude> <longitude>6</longitude> </point> <point> <latitude>3</latitude> <longitude>7</longitude> </point> <point> <latitude>4</latitude> <longitude>8</longitude> </point> <point> <latitude>5</latitude> <longitude>9</longitude> </point> </polygon> </geo-json-property-pair-query> </query>

Format	Query

JSON	<pre>{
	  "query": {
	    "queries": [{
	      "geo-json-property-pair-query": {
	        "parent-property": "myParent",
	        "lat-property": "lat",
	        "lon-property": "lon",
	        "polygon": [
	          {
	            "point": [
	              { "latitude": 1, "longitude": 2 },
	              { "latitude": 3, "longitude": 4 },
	              { "latitude": 5, "longitude": 6 },
	              { "latitude": 7, "longitude": 8 }
	            ]
	          },
	          {
	            "point": [
	              { "latitude": 2, "longitude": 6 },
	              { "latitude": 3, "longitude": 7 },
	              { "latitude": 4, "longitude": 8 },
	              { "latitude": 5, "longitude": 9 }
	            ]
	          }
	        ]
	      }
	    }]
	}}</pre>

4.6.26 range-constraint-query

A query that applies a pre-defined range constraint and compares the results to the specified value. For details, see “Constraint Options” on page 369 and the XQuery functions `cts:element-range-query`, `cts:element-attribute-range-query`, `cts:field-range-query`, and `cts:path-range-query`.

A `range-constraint-query` is equivalent to string query expressions of the form `constraint:value` or `constraint LE value`. The named constraint must be backed by a range index.

- Syntax Summary
- Component Description
- Examples

4.6.26.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<range-constraint-query>`
`  <constraint-name>`*`name`*`</constraint-name>`
`  <value>`*`value-to-match`*`</value>`
`  <range-operator>`*`operator`*`</range-operator>`
`  <range-option>`*`option`*`</range-option>`
`</range-constraint-query>`
	`"range-constraint-query": {`
	`  "constraint-name": "`*`name`*`",`
	`  "value": [ `*`value-to-match`*` ],`
	`  "range-operator": "`*`operator`*`",`
	`  "range-option": [ `*`option`*` ]`
	`}`

4.6.26.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a constraint defined in the global or query-specific query options.
`value`	Y	The value against which to match XML elements, XML element attributes, JSON properties, or fields that match the constraint identified by `constraint-name`. This element can occur 0 or more times.
`range-operator`	N	One of `LT`, `LE`, `GT`, `GE`, `EQ`, `NE`. Default: `EQ`. The match relationship that must be satisfied between `constraint-name matches` and `value`.
`range-option`	N	One or more range query options. Allowed values depend on the type of range query (element, path, field, etc.). For details, see Including a Range or Geospatial Query in Scoring in *Search Developer's Guide*. For a list of options, see "Range Options" on page 797.

4.6.26.3 Examples

The following example matches documents containing a `<body-color/>` element with a value of `black`, assuming an element range index exists on `<body-color/>`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="color">`
	`  <range type="xs:string">`
	`  <element ns="" name="body-color"/>`
	`  </range>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <range-constraint-query>`
	`  <constraint-name>color</constraint-name>`
	`  <value>black</value>`
	`  </range-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [`
	`  {`
	`  "name": "color",`
	`  "range": {`
	`  "type": "xs:string",`
	`  "element": {`
	`  "ns": "",`
	`  "name": "body-color"`
	`  }`
	`  }}]}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "range-constraint-query": {`
	`  "constraint-name": "color",`
	`  "value": [ "black" ]`
	`  }`
	`  }]`
	`}}`

4.6.27 value-constraint-query

A query that matches fragments where the value of the content of an XML element, XML attribute, JSON property, or field exactly matches the `text, number, boolean, or null` value in the query. The match semantics depend on the value, the database configuration, and the options in effect. The element, attribute, property, or field is identified by a value constraint defined in query options. This is similar to a string query term of the form `constraint:value`. For details, see `cts:element-value-query`, `cts:element-attribute-value-query`, `cts:field-value-query`, `cts:json-property-value-query`.

- Syntax Summary
- Component Description
- Examples

4.6.27.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<value-constraint-query>`
`  <constraint-name>`*`name`*`</constraint-name>`
`  <text>`*`value-to-match`*`</text>`
`  <weight>`*`value`*`</weight>`
`</value-constraint-query>`
	`"value-constraint-query": {`
	`  "constraint-name": "`*`name`*`",`
	`  "text": [ `*`string`*` ],`
	`  "weight": `*`number`*
	`}`

4.6.27.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a values constraint defined in the global or query-specific query options.
`text`	N	A value to match. Multiple values can be specified. If there is no `text`, `number`, `boolean`, or `null` component, all values matching the constraint are returned.
`number`	N	A numeric value to match. Applicable to only to JSON documents. Multiple values can be specified. If there is no `text`, `number`, `boolean`, or `null` component, all values matching the constraint are returned.
`boolean`	N	A boolean value to match. Applicable to only to JSON documents. Multiple values can be specified. If there is no `text`, `number`, `boolean`, or `null` component, all values matching the constraint are returned.
`null`	N	Match a null value. Applicable to only to JSON documents. Multiple values can be specified. If there is no `text`, `number`, `boolean`, or `null` component, all values matching the constraint are returned.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.

4.6.27.3 Examples

The following example matches documents where the field defined with the name "`myFieldName`" has the value "`Jane Doe`". The example assumes the field "`myFieldName`" is defined in the database configuration and that field searches are enabled for the database.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="full-name">`
	`  <value>`
	`  <field name="myFieldName"/>`
	`  </value>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <value-constraint-query>`
	`  <constraint-name>full-name</constraint-name>`
	`  <text>Jane Doe</text>`
	`  </value-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [`
	`  {`
	`  "name": "full-name",`
	`  "value": {`
	`  "field": {`
	`  "name": "myFieldName"`
	`  }}}]}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "value-constraint-query": {`
	`  "text": [ "Jane Doe" ],`
	`  "constraint-name": "full-name"`
	`  }`
	`  }]`
	`}}`

4.6.28 word-constraint-query

A query that matches fragments containing the specified terms or phrases in the XML element or attribute, JSON property, or field identified by a specified constraint. This is similar to a string query of the form `constraint:value`, where the constraint is a word constraint. For details, see `cts:word-query`.

- Syntax Summary
- Component Description
- Examples

4.6.28.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<word-constraint-query>`
`  <constraint-name>`*name*`</constraint-name>`
`  <text>`*text-to-match*`</text>`
`  <weight>`*value*`</weight>`
`</word-constraint-query>`
	`"word-constraint-query": {`
	`  "constraint-name": "`*name*`",`
	`  "text": [ `*string*` ],`
	`  "weight": `*number*
	`}`

4.6.28.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a word constraint defined in the global or query-specific query options. If you include multiple constraint names, the query matches if any of the constraints are met.
`text`	N	Terms or phrases that must occur in documents matching the constraint defined by `constraint-name`. Multiple values can be specified; if any one matches, the document matches the query.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.

4.6.28.3 Examples

The following example matches documents containing a `<body-color/>` element that contains the word `black`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="color">`
	`  <word>`
	`  <element name="body-color"/>`
	`  </word>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <word-constraint-query>`
	`  <constraint-name>color</constraint-name>`
	`  <text>black</text>`
	`  </word-constraint-query>`
	`</query>`

JSON	`{`
	`  "query": {`
	`  "queries": [{`
	`  "word-constraint-query": {`
	`  "text": [ "black" ],`
	`  "constraint-name": "color"`
	`  }`
	`  }]`
	`}}`

4.6.29 collection-constraint-query

A query that applies a pre-defined constraint and compares the results to the specified value. For details, see `cts:collection-query`.

- Syntax Summary
- Component Description
- Examples

4.6.29.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<collection-constraint-query>`
`  <constraint-name>`*name*`</constraint-name>`
`  <uri>`*collection-uri*`</value>`
`</collection-constraint-query>`
	`"collection-constraint-query": {`
	`  "constraint-name": "`*name*`",`
	`  "uri": [ `*collection-uri*` ]`
	`}`

4.6.29.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a collection constraint defined in the global or query-specific query options.
`uri`	N	One or more collection URIs to match against.

4.6.29.3 Examples

The following example matches documents in the collection `reports` or the collection `analysis`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="biz">`
	`  <collection prefix="my-coll-prefix"/>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <collection-constraint-query>`
	`  <constraint-name>biz</constraint-name>`
	`  <uri>reports</uri>`
	`  <uri>analysis</uri>`
	`  </collection-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [{`
	`  "name": "biz",`
	`  "collection": {`
	`  "prefix": "my-coll-prefix"`
	`  }`
	`  }]`
	`}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "collection-constraint-query": {`
	`  "uri": [ "reports", "analysis" ],`
	`  "constraint-name": "biz"`
	`  }`
	`  }]`
	`}}`

4.6.30 container-constraint-query

A query that matches XML elements or JSON properties meeting a specified constraint, with contained elements, attributes or properties that match a specified sub-query(s). The matching container and all of its descendants are considered by the sub-queries. For details, see `cts:element-query`.

- Syntax Summary
- Component Description

- Examples

4.6.30.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<container-constraint-query>`
`  <constraint-name>`*`name`*`</constraint-name>`
`  `*`anyQueryType`*
`</element-constraint-query>`
	`"container-constraint-query": {`
	`  "constraint-name": "`*`name`*`",`
	`  `*`anyQueryType`*
	`}`

4.6.30.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a constraint defined in the global or query-specific query options. If you specify multiple constraints, the query matches documents that satisfy any one of the constraints.
`anyQueryType`	Y	A query to run against containers matching the constraint identified by `constraint-name`.

4.6.30.3 Examples

The following example matches occurrences of a `<body-color/>` element that contains the term `black`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="body-color">`
	`  <container>`
	`  <element name="color" ns="" />`
	`  </container>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <container-constraint-query>`
	`  <constraint-name>body-color</constraint-name>`
	`  <term-query>`
	`  <text>black</text>`
	`  </term-query>`
	`  </container-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [{`
	`  "name": "body-color",`
	`  "container": {`
	`  "element": {`
	`  "name": "color",`
	`  "ns": ""`
	`  }`
	`  }`
	`  }]`
	`}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "container-constraint-query": {`
	`  "constraint-name": "body-color",`
	`  "term-query": {`
	`  "text": [ "black" ]`
	
	`  }`
	`  }]`
	`}}`

4.6.31 element-constraint-query

A query that matches elements meeting a specified element constraint, with sub-elements and/or attribute that match a specified sub-query(s). The matching element and all of its descendants are considered by the sub-queries. For details, see `cts:element-query`.

> **Note:** Use of this query type is deprecated. Use container-constraint-query instead.

- Syntax Summary
- Component Description
- Examples

4.6.31.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<element-constraint-query>`
`  <constraint-name>`*`name`*`</constraint-name>`
`  `*`anyQueryType`*
`</element-constraint-query>`
	`"element-constraint-query": {`
	`  "constraint-name": "`*`name`*`",`
	`  `*`anyQueryType`*
	`}`

4.6.31.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a container constraint defined in the global or query-specific query options. If you specify multiple constraints, the query matches documents that satisfy any one of the constraints.
`anyQueryType`	Y	A query to run against elements matching the constraint identified by `constraint-name`.

4.6.31.3 Examples

The following example matches occurrences of a `<body-color/>` element that contains the term `black`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="body-color">`
	`  <element-query name="color" ns="" />`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <element-constraint-query>`
	`  <constraint-name>body-color</constraint-name>`
	`  <term-query>`
	`  <text>black</text>`
	`  </term-query>`
	`  </element-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [{`
	`  "name": "body-color",`
	`  "element": {`
	`  "name": "color",`
	`  "ns": ""`
	`  }`
	`  }]`
	`}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "element-constraint-query": {`
	`  "constraint-name": "body-color",`
	`  "term-query": {`
	`  "text": [ "black" ]`
	
	`  }`
	`  }]`
	`}}`

4.6.32 properties-constraint-query

A query that matches documents with properties that match the specified property constraint, where the matching properties also match the specified query. For details, see `cts:properties-fragment-query`.

- Syntax Summary
- Component Description
- Examples

4.6.32.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<properties-constraint-query>`
`  <constraint-name>`*`name`*`</constraint-name>`
`  `*`anyQueryType`*
`</properties-constraint-query>`
	`"properties-constraint-query": {`
	`  "constraint-name": "`*`name`*`",`
	`  `*`anyQueryType`*
	`}`

4.6.32.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a properties constraint defined in the global or query-specific query options.
`anyQueryType`	Y	A query to run against properties matching the constraint identified by `constraint-name`.

4.6.32.3 Examples

The following example matches documents that have properties fragments containing the term `dog`.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="prop-only">`
	`  <properties />`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <properties-constraint-query>`
	`  <constraint-name>prop-only</constraint-name>`
	`  <term-query>`
	`  <text>dog</text>`
	`  </term-query>`
	`  </properties-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [{`
	`  "name": "prop-only",`
	`  "properties": null`
	`  }]`
	`}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "properties-constraint-query": {`
	`  "constraint-name": "prop-only",`
	`  "term-query": {`
	`  "text": [ "dog" ]`
	`  }`
	`  }`
	`  }]`
	`}}`

4.6.33 custom-constraint-query

A query constructed by a custom XQuery extension function, using the supplied criteria. For details, see “Creating a Custom Constraint” on page 40.

- Syntax Summary

- Component Description
- Examples

4.6.33.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<custom-constraint-query>`
`  <constraint-name>`*name*`</constraint-name>`
`  <text>term</text>`
`</custom-constraint-query>`
	`"custom-constraint-query": {`
	`  "constraint-name": "`*name*`",`
	`  "text": [ `*term*` ]`
	`}`

4.6.33.2 Component Description

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a custom constraint defined in the global or query-specific query options.
`text`	N	A query to run against fragments matching the constraint identified by `constraint-name`.

4.6.33.3 Examples

The following example is equivalent to the string query "`part:book`" where `part` is the name of a custom constraint defined in the query options.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="part">`
	`  <custom facet="false">`
	`  <parse apply="part" ns="my-namespace" at="/my-module.xqy"/>`
	`  </custom>`
	`  </constraint>`
	`</options>`
	
	`<query xmlns="http://marklogic.com/appservices/search">`
	`  <custom-constraint-query>`
	`  <constraint-name>part</constraint-name>`
	`  <text>book</text>`
	`  </custom-constraint-query>`
	`</query>`

JSON	`{`
	`  "options": {`
	`  "constraint": [{`
	`  "name": "part",`
	`  "custom": {`
	`  "facet": false,`
	`  "parse": {`
	`  "apply": "part",`
	`  "ns": "my-namespace",`
	`  "at": "/my-module.xqy"`
	`  }`
	`  }`
	`  }]`
	`}}`
	
	`{`
	`  "query": {`
	`  "queries": [{`
	`  "custom-constraint-query": {`
	`  "text": [ "book" ],`
	`  "constraint-name": "part"`
	`  }`
	`  }]`
	`}}`

4.6.34 geospatial-constraint-query

A query that returns documents that match the specified geospatial constraint and the matching fragments also match the geospatial queries. For details, see "Geospatial Search Applications" on page 462.

- Syntax Summary
- Component Description
- Examples

4.6.34.1 Syntax Summary

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<geospatial-constraint-query>` `  <constraint-name>`*name*`</constraint-name>` `  <point>` `  <latitude>`*float*`</latitude>` `  <longitude>`*float*`</longitude>` `  </point>` `  <box>` `  <south>`*float*`</south>` `  <west>`*float*`</west>` `  <north>`*float*`</north>` `  <east>`*float*`</east>` `  </box>` `  <circle>` `  <radius>`*float*`</radius>` `  <point/>` `  </circle>` `  <polygon>` `  <point/>` `  </polygon>` `  <text>term</text>` `</geospatial-constraint-query>`	`"geospatial-constraint-query": {` `  "constraint-name": "`*name*`",` `  "point": [` `  {` `  "latitude": `*number*`,` `  "longitude": `*number* `  }` `  ],` `  "box": [` `  {` `  "south": `*number*`,` `  "west": `*number*`,` `  "north": `*number*`,` `  "east": `*number* `  }` `  ],` `  "circle": [` `  {` `  "radius": `*number*`,` `  *point* ` }` `],` ` "polygon": [`*point*`]` `}`

4.6.34.2 Component Description

A geospatial constraint query contains one or more points or regions, described by `point`, `box`, `circle`, and `polygon` XML child elements or JSON sub-objects.

Element or JSON Property Name	Req'd?	Description
`constraint-name`	Y	The name of a custom constraint defined in the global or query-specific query options.
`point`	N	Zero or more geographic points, each defined by a `latitude` and a `longitude`. The query can contain 0 or more points.
`box`	N	Zero or more rectangular regions, each defined by 4 points: `north`, `south`, `east`, and `west`.
`circle`	N	Zero or more circles, each defined by `radius` and a center `point`.
`polygon`	N	Zero or more polygons, each series of `point`'s.

4.6.34.3 Examples

The following example matches points contained in either of two polygons. The `my-geo-elem-pair` constraint in the query options defines how to construct the points.

Format	Query
XML	<options xmlns="http://marklogic.com/appservices/search"> <constraint name="my-geo-elem-pair"> <geo-elem-pair> <parent ns="ns1" name="elem2"/> <lat ns="ns2" name="attr2"/> <lon ns="ns3" name="attr3"/> </geo-elem-pair> </constraint> </options> <query xmlns="http://marklogic.com/appservices/search"> <geospatial-constraint-query> <constraint-name>name</constraint-name> <polygon> <point> <latitude>1</latitude> <longitude>2</longitude> </point> <point> <latitude>3</latitude> <longitude>4</longitude> </point> <point> <latitude>5</latitude> <longitude>6</longitude> </point> <point> <latitude>7</latitude> <longitude>8</longitude> </point> </polygon> <polygon> <point> <latitude>2</latitude> <longitude>6</longitude> </point> <point> <latitude>3</latitude> <longitude>7</longitude> </point> <point> <latitude>4</latitude> <longitude>8</longitude> </point> <point> <latitude>5</latitude> <longitude>9</longitude> </point> </polygon> </geospatial-constraint-query> </query>

Format	Query

JSON	<pre>{
	  "options": {
	    "constraint": [{
	      "name": "my-geo-elem-pair",
	      "geo-elem-pair": {
	        "parent": { "ns": "ns1", "name": "elem2" },
	        "lat": { "ns": "ns2", "name": "attr2" },
	        "lon": { "ns": "ns3", "name": "attr3" }
	      }
	    }]
	}}
	
	{
	  "query": {
	    "queries": [{
	      "geospatial-constraint-query": {
	        "constraint-name": "name",
	        "polygon": [
	          {
	            "point": [
	              { "latitude": 1, "longitude": 2 },
	              { "latitude": 3, "longitude": 4 },
	              { "latitude": 5, "longitude": 6 },
	              { "latitude": 7, "longitude": 8 }
	            ]
	          },
	          {
	            "point": [
	              { "latitude": 2, "longitude": 6 },
	              { "latitude": 3, "longitude": 7 },
	              { "latitude": 4, "longitude": 8 },
	              { "latitude": 5, "longitude": 9 }
	            ]
	          }
	        ]
	      }
	    }]
	}}</pre>

4.6.35 lsqt-query

A query that returns documents before Last Stable Query Time (LSQT) or before a given timestamp that is before LSQT. For details, see `cts:lsqt-query` or Searching Temporal Documents in the *Temporal Developer's Guide*.

- Syntax Summary
- Component Description
- Examples

4.6.35.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<lsqt-query>`
`  <temporal-collection>`*`name`*`</temporal-collection>`
`  <timestamp>`*`dateTime`*`</timestamp>`
`  <weight>`*`value`*`</weight>`
`  <temporal-option>`*`option`*`</temporal-option>`
`</lsqt-query>`
	`"lsqt-query": {`
	`  "temporal-collection":` *`name`*`,`
	`  "timestamp":` *`string`*`,`
	`  "weight":` *`number`*`,`
	`  "temporal-option": [` *`string`* `]`
	`}`

4.6.35.2 Component Description

Element or JSON Property Name	Req'd?	Description
`temporal-collection`	Y	The name of a temporal collection.
`timestamp`	N	Return only temporal documents with a system start time less than or equal to this value. Timestamps greater than LSQT are rejected. Default: LSQT for the named temporal collection.
`weight`	N	A weight for this query. Default: 1.0. Higher weights move search results up in the relevance order. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64, inclusive). Weights greater than 64 have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.
`temporal-option`	N	Temporal options to apply to the query. You can specify multiple options. If the option has a value, the value of `temporal-option` is `option=value`. For example: `<temporal-option>score-function=linear</temporal-option>`. For available options, see `cts:lsqt-query`.

4.6.35.3 Examples

The following example returns documents in the temporal collection “myTemporalCollection” before LSQT.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	
	`</options>`
	
	`<query xmlns:search="http://marklogic.com/appservices/search">`
	`  <lsqt-query>`
	`  <temporal-collection>myTemporalCollection</temporal-collection>`
	`  <temporal-option>cached-incremental</temporal-option>`
	`  </lsqt-query>`
	`</query>`

JSON	`{"query": {`
	`  "queries": [{`
	`  "lsqt-query": {`
	`  "temporal-collection": "myTemporalCollection",`
	`  "temporal-option": [ "cached-incremental" ]`
	`  }`
	`  }]`
	`}}`

4.6.36 period-compare-query

A query that matches documents for which the specified relationship holds between two temporal axes. For details, see `cts:period-compare-query` or Searching Temporal Documents in the *Temporal Developer’s Guide*.

- Syntax Summary
- Component Description
- Examples

4.6.36.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<period-compare-query>`
`  <axis1>axis-`*`name`*`</axis1>`
`  <temporal-operator>`
`  `*`operator`*
`  </temporal-operator>`
`  <axis2>axis-`*`name`*`</axis2>`
`  <temporal-option>`*`option`*`</temporal-option>`
`</period-compare-query>`
	`"period-compare-query": {`
	`  "axis1": `*`name`*`,`
	`  "temporal-operator": `*`string`*`,`
	`  "axis2": `*`name`*`,`
	`  "temporal-option": [ `*`string`*` ]`
	`}`

4.6.36.2 Component Description

Element or JSON Property Name	Req'd?	Description
`axis1`	Y	The name of the first temporal axis.
`temporal-operator`	Y	The comparison operation to apply to the two axes. For a list of operator names, see `cts:period-compare-query` and Period Comparison Operators in the *Temporal Developer's Guide*.
`axis2`	Y	The name of the second temporal axis.
`temporal-option`	N	Temporal options to apply to the query. You can specify multiple options. If the option has a value, the value of `temporal-option` is `option=value`. For example: `<temporal-option>score-function=linear</temporal-option>`. For available options, see `cts:lsqt-query`.

4.6.36.3 Examples

The following example matches documents that were in the database when the time period defined by the axis named "valid" is within the time period defined by the axis "system".

Format	Query

XML	`<query xmlns:search="http://marklogic.com/appservices/search">`
	`  <period-compare-query>`
	`  <axis1>system</axis1>`
	`  <temporal-operator>iso_contains</temporal-operator>`
	`  <axis2>valid</axis2>`
	`  </period-compare-query>`
	`</query>`

JSON	`{"query": {`
	`  "queries": [{`
	`  "period-compare-query": {`
	`  "axis1": "system",`
	`  "temporal-operator": "iso_contains",`
	`  "axis2": "valid"`
	`  }`
	`  }]`
	`}}`

4.6.37 period-range-query

- Syntax Summary
- Component Description
- Examples

4.6.37.1 Syntax Summary

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<period-range-query>`
`  <axis>axis-`*`name`*`</axis>`
`  <temporal-operator>`
`  `*`operator`*
`  </temporal-operator>`
`  <period>`
`  <period-start>dateTime</period-start>`
`  <period-end>period-end</period-end>`
`  </period>`
`  <temporal-option>`*`option`*`</temporal-option>`
`</period-range-query>`
	`"period-range-query": {`
	`  "axis": [ `*`name`*` ],`
	`  "temporal-operator": `*`string`*`,`
	`  "period": [`
	`  {`
	`  "period-start": `*`string`*`,`
	`  "period-end": `*`string`*
	`  }`
	`  ],`
	`  "temporal-option": [ `*`string`*` ]`
	`}`

4.6.37.2 Component Description

Element or JSON Property Name	Req'd?	Description
`axis`	Y	The name of a temporal axis. You can specify multiple axis names.
`temporal-operator`	Y	The comparison operation to apply to the axis and period. For a list of operator names, see `cts:period-range-query` and Period Comparison Operators in the *Temporal Developer's Guide*.
`period`	Y	One or more periods to match. When multiple periods are specified, the query matches if any value matches.
`temporal-option`	N	Temporal options to apply to the query. You can specify multiple options. If the option has a value, the value of `temporal-option` is `option=value`. For example: `<temporal-option>score-function=linear</temporal-option>`. For available options, see `cts:lsqt-query`.

4.6.37.3 Examples

The following example matches temporal documents a valid end time before. 14:00.

Format	Query

XML	`<query xmlns:search="http://marklogic.com/appservices/search">`
	`  <period-range-query>`
	`  <axis>valid</axis>`
	`  <temporal-operator>aln_before</temporal-operator>`
	`  <period>`
	`  <period-start>2014-04-03T14:00:00</period-start>`
	`  <period-end>9999-12-31T11:59:59Z</period-end>`
	`  </period>`
	`  </period-range-query>`
	`</query>`

Format	Query

JSON	{"query": {
	  "queries": [{
	  "period-range-query": {
	  "axis": ["valid"],
	  "temporal-operator": "aln_before",
	  "period": [
	  {
	  "period-start": "2014-04-03T14:00:00",
	  "period-end": "9999-12-31T11:59:59Z"
	  }
	  ]
	  }
	  }]
	}}

4.6.38 operator-state

This component of a structured query sets the state of a custom runtime configuration operator defined by your string query grammar. For details, see “Operator Options” on page 382.

- Syntax Summary
- Component Description
- Examples

4.6.38.1 Syntax Summary

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<operator-state>`
`  <operator-name>`*name*`</operator-name>`
`  <state-name>`*state*`</state-name>`
`</operator-state>`
	"operator-state": {
	  "operator-name": "*name*",
	  "state-name": "*state*"
	}

4.6.38.2 Component Description

Element or JSON Property Name	Req'd?	Description
`operator-state`	Y	The name of a custom runtime configuration operator defined by the `<operator/>` query option.
`state-name`	Y	The name of a state recognized by this operator.

4.6.38.3 Examples

The following example illustrates use of a custom `sort` operator defined in the query options. The example structured query is equivalent to the string query "`sort:date`". For details, see "Operator Options" on page 382.

Format	Query

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <operator name="sort">`
	`  <state name="relevance">`
	`  <sort-order>`
	`  <score/>`
	`  </sort-order>`
	`  </state>`
	`  <state name="date">`
	`  <sort-order direction="descending" type="xs:dateTime">`
	`  <element ns="my-ns" name="date"/>`
	`  </sort-order>`
	`  <sort-order>`
	`  <score/>`
	`  </sort-order>`
	`  </state>`
	` </operator>`
	`</options>`
	
	`<query xmlns:search="http://marklogic.com/appservices/search">`
	`  <operator-state>`
	`  <operator-name>sort</operator-name>`
	`  <state-name>date</state-name>`
	`  </operator-state>`
	`</query>`

Format	Query

JSON	<pre>{
	  "options": {
	    "operator": [{
	      "name": "sort",
	      "state": [
	        {
	          "name": "relevance",
	          "sort-order": [{ "score": null }]
	        },
	        {
	          "name": "date",
	          "sort-order": [
	            {
	              "direction": "descending",
	              "type": "xs:dateTime",
	              "element": { "ns": "my-ns", "name": "date" }
	            },
	            { "score": null }
	          ]
	      }]
	    }]
	}}
	
	{
	  "query": {
	    "queries": [{
	      "operator-state": {
	        "operator-name": "sort",
	        "state-name": "date"
	      }
	    }]
	}}</pre>

5.0 Searching Using Query By Example

This chapter describes how to perform searches using Query By Example (QBE). A QBE is a query whose structure closely models the structure of the documents you want to match. You can use a QBE to search XML and JSON documents with the REST, Node.js and Java APIs.

This chapter includes the following sections:

- QBE Overview
- Example
- Understanding QBE Sub-Query Types
- Search Criteria Quick Reference
- QBE Structural Reference
- How Indexing Affects Your Query
- Adding Options to a QBE
- Customizing Search Results
- Scoping a Search by Document Type
- Converting a QBE to a Combined Query
- Validating a QBE

For details on supporting APIs, see *Java Application Developer's Guide* and *REST Application Developer's Guide*.

5.1 QBE Overview

The simple, intuitive syntax of a Query By Example (QBE) enables rapid prototyping of queries for "documents that look like this" because search criteria in a QBE resemble the structure of documents in your database. In its simplest form, a QBE models one or more XML elements, XML element attributes, or JSON properties in your documents.

For example, if your documents include an `author` XML element or JSON property, you can use the following QBE to find documents with an `author` value of "Mark Twain".

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Mark Twain</author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": { "author": "Mark Twain" }`
	`}`

A QBE always contains a `query` component in which you define search criteria. A QBE can include an optional `response` component for customizing search results, and flags and options that control search behaviors. For details, see "QBE Structural Reference" on page 215.

QBE exposes many powerful features of the Search API, including the following:

- Search Criteria Based on Document Structure
- Logical Operators. Create complex composed queries using AND, OR, NOT and NEAR operators.
- Comparison Operators. Create range queries that test the value of XML elements, XML attributes, and JSON properties using comparison operators such as less than, greather than, and not equal.
- Query by Value or Word. Choose to match values exactly or as subset of the contained content.
- Search Result Customization. Control what to include in the results and snippets returned by your search.
- Options for Controlling Search Behavior. Use options and flags to control query behaviors such as case sensitivity, weights, and number of occurrences.

You can prototype queries using QBE without creating any database indexes, though doing so has implications for performance. For details, see "How Indexing Affects Your Query" on page 226.

This chapter covers the syntax and semantics of QBE. You can use a QBE to search XML and JSON documents with the the following MarkLogic APIs:

API	More Information
Node.js Client API	Searching with Query By Example in the *Node.js Application Developer's Guide*.
Java Client API	Prototype a Query Using Query By Example in the *Java Application Developer's Guide*
REST Client API	Using Query By Example to Prototype a Query in the in *REST Application Developer's Guide*.

If you need access to more advanced search features, APIs are available for converting a QBE to a combined query, giving you a foundation on which to build. For details, refer to Client API documentation.

5.1.1 Search Criteria Based on Document Structure

A QBE uses search criteria expressed as XML elements, XML element attributes, or JSON properties that closely resemble portions of documents in the database.

For example, if the database contains documents of the following form:

Format	Example Document

XML	`<book>`
	`  <title>Tom Sawyer</title>`
	`  <author>Mark Twain</author>`
	`  <edition format="paperback"/>`
	`</book>`

JSON	`"book": {`
	`  "title": "Tom Sawyer",`
	`  "author" : "Mark Twain",`
	`  "edition": [`
	`  { "format": "paperback" }`
	`  ]`
	`} }`

Then you can construct a QBE to find all paperback books by a given author by creating criteria that model the `author`, edition `format`. The following QBE finds all paperback books by Mark Twain.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Mark Twain</author>`
	`  <edition format="paperback"/>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "author": "Mark Twain",`
	`  "edition": {`
	`  "format": "paperback"`
	`  }`
	`} }`

By default, the literal values in criteria must exactly match document contents. That is, the above query matches if the `author` value is “Mark Twain”, but it will not match documents where the author is “M. Twain” or “mark twain”. You can change this behavior using word queries and options. For details, see “Understanding QBE Sub-Query Types” on page 199 and “Adding Options to a QBE” on page 227.

You can construct criteria that express value, word, and range queries. For example, you can construct a QBE that satisfies all of the following criteria. The Example Criteria column shows an XML and a JSON criteria that expresses each requirement.

Requirement	Query Type	Example Criteria

the author includes “twain”	word	`<author><q:word>twain</q:word></author>`
		
		`"author": {"$word": "shakespeare"}`

there is a paperback edition	value	`<edition format="paperback"/>`
		
		`"edition": {"format": "paperback"}`

the price of the paperback edition is less than 9.00	range	`<edition>`
		`  <price><q:lt>9.00</q:lt></price>`
		`</edition>`
		
		`"edition": {"price": {"$lt": 9.00} }`

When you combine the above criteria into a single query, you get the following QBE. Notice that the child elements of `query` are implicitly AND’d together.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author><q:word>twain</q:word></author>`
	`  <edition format="paperback">`
	`  <price><q:lt>9.00</q:lt></price>`
	`  </edition>`
	`  <q:filtered>true</q:filtered>`
	`  </q:query>`
	`</q:qbe>`

Format	Example

JSON	{
	  "$query": {
	  "author": {
	  "$word": "twain"
	  },
	  "edition": {
	  "format": "paperback",
	  "price": { "$lt": 9.00 }
	  },
	  "$filtered": true
	  }
	}

The above examples demonstrate searching for direct containment, such as "the author is Mark Twain." You can also search for matches anywhere within a containing XML element or JSON property. For example, suppose a `book` contains `author` and `editor` names, broken down into `first-name` and `last-name`:

Format	Example Document
XML	<book> <author> <first-name>Mark</first-name> <last-name>Twain</last-name> </author> <editor> <first-name>Mark</first-name> <last-name>Matthews</last-name> </editor> </book>

JSON	"book": {
	  "author" : {
	  "first-name": "Mark",
	  "last-name": "Twain"
	  },
	"editor" : {
	  "first-name": "Mark",
	  "last-name": "Matthews"
	  }
	} }

You can search for “any occurences of Mark as a first name contained by a book” using criteria such as the following:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <book><first-name>Mark</last-name></book>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "book": { "first-name": "Mark" }`
	`} }`

Such criteria represent container queries. For details, see “Container Query” on page 205.

5.1.2 Logical Operators

You can use logical “operators” to create powerful composed queries. The QBE grammar supports `and`, `or`, `not`, and `near` composers. The following example matches documents that contain “twain” or “shakespeare” in the `author` XML element or JSON property.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <q:or>`
	`  <author><q:word>twain</q:word></author>`
	`  <author><q:word>shakespeare</q:word></author>`
	`  </q:or>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query" : {`
	`  "$or": [`
	`  { "author": {"$word": "twain" } },`
	`  { "author": {"$word": "shakespeare" } }`
	`  ]`
	`  }`
	`}`

Sub-queries that are immediate children of query represent an implicit `and` query.

For details, see “Composed Query” on page 204.

5.1.3 Comparison Operators

The QBE grammar supports the following comparison operators for constructing range queries on XML element, XML attribute, and JSON property values: `lt`, `le`, `eq`, `ne`, `ge`, `gt`. For example, the following query matches all documents where the price is greater than or equal to 10.00 and less than or equal to 20.00.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <price><q:ge>10.00</q:ge></price>`
	`  <price><q:le>20.00</q:le></price>`
	`  <q:filtered>true</q:filtered>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{ "$query": {`
	`  "$and": [`
	`  {"price" : { "$ge": 10.00 } },`
	`  {"price" : { "$le": 20.00 } } ],`
	`  "$filtered": true`
	`}}`

The `filtered` flag is included in the above query because you must either use filtered search or back the range queries on “price” with a range index. For details, see “How Indexing Affects Your Query” on page 226.

For details, see “Range Query” on page 202.

5.1.4 Query by Value or Word

When you construct a criteria on a literal value, it is an implicit value query that matches an exact value. For example, the following criteria matches only when author is “Mark Twain”. It will not match “mark twain”or “M. Twain”:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Mark Twain</author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": { "author": "Mark Twain" }`
	`}`

When this is not the desired behavior, you can use a word query and/or options to modify the default behavior. A word query differs from a value query in two ways: It relaxes the default exact match semantics of a value query, and it matches a subset of the value in a document.

For example, the following query matches if the `author` contains “twain”, with any capitalization, so it matches values that are not matched by the original query, such as “Mark Twain”, “M. Twain” and “mark twain”.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author><q:word>twain</q:word></author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": { "author": { "$word": "twain" } }`
	`}`

For details, see “Value Query” on page 200 and “Word Query” on page 201.

5.1.5 Search Result Customization

You can include a `response` XML element or JSON property to customize the contents of returned search results. The default search results include a highlighted snippet of matching XML elements or JSON properties. Use the `response` section of a QBE to disable snippeting, extract additional elements, or return an entire document.

For details, see "Customizing Search Results" on page 232.

5.1.6 Options for Controlling Search Behavior

The QBE grammar includes several flags and options to control your search. Flags usually have a global effect on your search, such as how to score search results. Options affect a portion of your query, such as whether or not perform an exact match against a particular XML element or JSON property value.

The following example uses the `exact` option to disable exact matches on value queries.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author><q:value exact="false">mark twain</q:value></author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": {`
	`  "author": {`
	`  "$exact": false,`
	`  "$value" : "mark twain"`
	`  }`
	`  }`
	`}`

For more details, see "Adding Options to a QBE" on page 227.

5.2 Example

This section includes an example that uses most of the query features of a QBE.

- XML Example
- JSON Example

5.2.1 XML Example

This example assumes the database contains documents with the following structure:

```
<book>
  <title>Tom Sawyer</title>
  <author>Mark Twain</author>
  <edition format="paperback">
    <publisher>Clipper</publisher>
    <pub-date>2011-08-01</pub-date>
    <price>9.99</price>
    <isbn>1613800917</isbn>
  </edition>
</book>
```

The following query uses most of the features of QBE and matches the above document. The sub-queries that are immediate children of query are implicitly AND'd together, so all these conditions must be met by matching documents.

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <title>
      <q:value exact="false">Tom Sawyer</q:value>
    </title>
    <q:near distance="2">
      <author><q:word>mark</q:word></author>
      <author><q:word>twain</q:word></author>
    </q:near>
    <edition format="paperback">
      <q:or>
        <publisher>Clipper</publisher>
        <publisher>Daw</publisher>
      </q:or>
    </edition>
    <q:and>
      <price><q:lt>10.00</q:lt></price>
      <price><q:ge>8.00</q:ge></price>
    </q:and>
    <q:filtered>true</q:filtered>
  </q:query>
</q:qbe>
```

The following table explains the requirement expressed by each component of the query. Each of the subquery types used in this example is explored in more detail in "Understanding QBE Sub-Query Types" on page 199.

Requirement	Example Criteria

The title is "Tom Sawyer". Exact match is disabled, so the match is not sensitive to whitespace, punctuation, or diacritics. The match is case sensitive because the value ("Tom Sawyer") is mixed case.	`<title>`
	`  <q:value exact="false">Tom Sawyer</q:value>`
	`</title>`

The author contains the word "mark" and the word "twain" within 2 words of each other.	`<q:near distance="2">`
	`  <author><q:word>mark</q:word></author>`
	`  <author><q:word>twain</q:word></author>`
	`</q:near>`

The edition format is "paperback" and the publisher is "Clipper" or "Daw". All the atomic values in this sub-query use exact value match semantics.	`<edition format="paperback">`
	`  <q:or>`
	`  <publisher>Clipper</publisher>`
	`  <publisher>Daw</publisher>`
	`  </q:or>`
	`</edition>`

The price is less than 10.00 and greather than or equal to 8.00.	`<q:and>`
	`  <price><q:lt>10.00</q:lt></price>`
	`  <price><q:ge>8.00</q:ge></price>`
	`</q:and>`

Use unfiltered search. This flag can be omitted if there is a range index on `price`. For details, see "How Indexing Affects Your Query" on page 226.	`<q:filtered>true</q:filtered>`

5.2.2 JSON Example

This example assumes the database contains documents with the following structure:

```
{"book": {
  "title": "Tom Sawyer",
  "author" : "Mark Twain",
  "edition": [
    { "format": "paperback",
      "publisher": "Clipper",
      "pub-date": "2011-08-01",
      "price" : 9.99,
```

```
      "isbn": "1613800917",
    }
  ]
} }
```

The following query uses most of the features of QBE and matches the above document. The sub-queries that are immediate children of query are implicitly AND'd together, so all these conditions must be met by matching documents.

```
{"$query": {
    "title": {
      "$value": "Tom Sawyer",
      "$exact": false
    },
    "$near": [
      { "author": { "$word": "mark" } },
      { "author": { "$word": "twain" } }
    ], "$distance": 2,
    "edition": {
      "format": "paperback",
      "$or" : [
        { "publisher": "Clipper" },
        { "publisher": "Daw" }
      ]
    },
    "$and": [
      {"price": { "$lt": 10.00 }},
      {"price": { "$ge": 8.00 }}
    ],
    "$filtered": true
} }
```

The following table explains the requirement expressed by each component of the query. Each of the subquery types used in this example is explored in more detail in “Understanding QBE Sub-Query Types” on page 199.

Requirement	Example Criteria

The title is “Tom Sawyer”. Exact match is disabled, so the match is not sensitive to whitespace, punctuation, or diacritics. The match is case sensitive because the value (“Tom Sawyer”) is mixed case.	`"title": {`
	`  "$value": "Tom Sawyer",`
	`  "$exact": false`
	`}`

The author contains the word “mark” and the word “twain” within 2 words of each other.	`"$near": [`
	`  { "author": { "$word": "mark" } },`
	`  { "author": { "$word": "twain" } }`
	`],`
	`"$distance": 2`

The edition format is “paperback” and the publisher is “Clipper” or “daw”. All the atomic values in this sub-query use exact value match semantics.	`"edition": {`
	`  "format": "paperback",`
	`  "$or" : [`
	`  { "publisher": "Clipper" },`
	`  { "publisher": "Daw" }`
	`  ]`
	`}`

The price is less than 10.00 and greater than or equal to 8.00.	`"$and": [`
	`  {"price": { "$lt": 10.00 }},`
	`  {"price": { "$ge": 8.00 }}`
	`]`

Use unfiltered search. This flag can be omitted if there is range index on `price`. For details, see “How Indexing Affects Your Query” on page 226.	`"$filtered": true`

5.3 Understanding QBE Sub-Query Types

The `query` portion of a QBE is composed of sub-queries. While QBE enables you to express a sub-query using syntax that closely models your documents, you should understand the query types represented by this modeling. You can express the following query types in a QBE:

- Value Query
- Word Query
- Range Query

- Composed Query
- Container Query

5.3.1 Value Query

A value query matches an entire literal value, such as a string, date, or number.

By default, an XML element or JSON property criteria represents a value query with exact match semantics:

- The value in the criteria is matched with case, diacritic, punctuation, and whitespace sensitivity enabled.
- Stemming and wildcarding are not enabled.
- The specified value must be an immediate child of the containing XML element or JSON property.
- The value in the query will not match if it is a subset of the value in a document.

For example, the following criteria only matches documents where the `author` XML element or JSON property contains exactly and only the text "Twain". It will not match author values such as "Mark Twain" or "twain".

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Twain</author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": { "author": "Twain" }`
	`}`

You can override some of the exact match semantics with options. For example, you can disable case-sensitive matches. For details, see "Adding Options to a QBE" on page 227.

A value query can be explicit or implicit. The example above is an implicit value query. You can make an explicit value query using the `value` QBE keyword. This is useful when you want to add options to a value query. The following example is an explicit value query that uses the `case-sensitive` option.

Format	Example
XML	<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample"> <q:query> <author> <q:value case-sensitive="false">Twain<q:value> </author> </q:query> </q:qbe>

JSON	{ "$query": {
	  "author": {
	  "$value": "Twain",
	  "$case-sensitive": false
	  }
	} }

5.3.2 Word Query

A word query matches a word or phrase appearing anywhere in a text value. A word query will match a subset of a text value. By default, word queries do not use exact match semantics.

- The value in the criteria is matched with case, diacritic, punctuation, and whitespace sensitivity disabled.
- Stemmed matches are included.
- Wildcard matching is performed if wildcarding is enabled for the database.
- The specified word or phrase can occur in the value of the immediately containing XML element or JSON property, or in the value of child components.

You can use options to override some of the match semantics. For details, see “Adding Options to a QBE” on page 227.

Word queries occurring within another container, such as an XML element or JSON property that describes content in your document, match occurrences within the container. Word queries that are not in a container, such as word queries that are immediate children of the top level QBE `query` wrapper, match occurrences anywhere in a document. For details, see “Container Query” on page 205 and “Searching Entire Documents” on page 213.

The following example QBE matches if the `author` contains “twain” with any capitalization, so it matches values such as “Mark Twain”, “M. Twain” and “mark twain”.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author><q:word>twain</q:word></author>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": { "author": { "$word": "twain" } }`
	`}`

In JSON, the value in a word query can be either a string or an array of strings. An array of values is treated as an AND-related list of word queries. For example, the following query matches documents where `author` contains word matches for “mark” and “twain”. The matched values need not be array item values.

```
{
  "$query": { "author": { "$word": [ "mark", "twain" ] } }
}
```

5.3.3 Range Query

A range query matches values that satisfy a relational expression applied to a string, number, date, time, or dateTime value, such as “less than 5” or “not equal to 10”. This section includes the following topics:

- JSON Property Value Range Query
- XML Element Value Range Query
- XML Element Attribute Value Range Query
- Type Conversion in Range Expressions

Note: You must either back a range query by a range index or use the `filtered` flag. For details see “How Indexing Affects Your Query” on page 226.

5.3.3.1 JSON Property Value Range Query

To construct a range query for a JSON property value, construct a JSON property with the operator name prefixed with “$” as the name and the boundary value as the value:

```
{ "$operator" : boundary-value }
```

The following example criteria tests for `format` not equal to “paperback”:

```
"format": {"$ne": "paperback" }
```

You cannot construct a range query that is constrained to match an array item.

5.3.3.2 XML Element Value Range Query

To construct a range query on an XML element value, use the following syntax, where `q` is the namespace prefix for `http://marklogic.com/appservices/querybyexample`:

```
<container>
  <q:operator>boundary-value</q:operator>
</container>
```

The following example criteria tests for publication date greather than 2010-01-01:

```
<pub-date>
  <q:gt>2010-01-01</q:gt>
</pub-date>
```

5.3.3.3 XML Element Attribute Value Range Query

To construct a range query on an XML element attribute value, prefix the operator name with “$” and put the comparison expression in the string value of the attribute on the containing element criteria:

```
<container attr="$operator value" />
```

The following example criteria tests that `@format` of `edition` does not equal “paperback”:

```
<edition format="$ne paperback" />
```

5.3.3.4 Type Conversion in Range Expressions

By default, values in range queries are treated as `xs:boolean`, `xs:double`, `xs:dateTime`, `xs:date`, or `xs:time` if castable as such, and as strings otherwise.

You can use the `xsi:type` (XML) or `$datatype` (JSON) option to force a particular type conversion; for details, see “Adding Options to a QBE” on page 227.

5.3.4 Composed Query

A composed query is one composed of sub-queries joined by a logical "operator" such `and`, `or`, `not`, or `near`. The following example matches documents where the value of `author` is "Mark Twain" or "Robert Frost".

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <q:or>`
	`  <author>Mark Twain</author>`
	`  <author>Robert Frost</author>`
	`  </q:or>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "$or": [`
	`  "author": "Mark Twain",`
	`  "author": "Robert Frost"`
	`  ]`
	`} }`

The `near` operator models a `cts:near-query` and accepts an optional `distance` XML attribute or JSON property to specify a maximum acceptable distance in words between matches for the operands queries. For example, the following near query specifies a maximum distance of 2 words. The default distance is 10.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <q:near distance="2">`
	`  <author><q:word>mark</q:word></author>`
	`  <author><q:word>twain</q:word></author>`
	`  </q:near>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "$near": [`
	`  { "author": { "$word": "mark" } },`
	`  { "author": { "$word": "twain" } }`
	`  ],`
	`  "$distance": 2`
	`} }`

5.3.5 Container Query

A container query matches when sub-query conditions are met within the scope of a specific XML element or JSON property. In a container query, the relationship between the named container and XML element or JSON property names used in the sub-queries is "contained by" not merely "child of".

A container query is implicitly defined when you use search criteria that model your document and that contain a composed query or structural sub-queries (XML element, XML attribute, or JSON property).

For example, an XML criteria such as the following defines defines a container query on `edition` because it contains an implicit value query on another element, `price`.

```
<edition><price>8.99</price></edition>
```

By contrast, the following criteria is a value query, not a container query, on `author`:

```
<author>twain</author>
```

Similarly, the following JSON criteria is a container query on `edition` because it contains an implicit value query on another property, `price`.

```
"edition":{"price": 8.99}
```

By contrast, a criteria such as the following is a value query, not a container query, on `author`.

```
"author":"twain"
```

The examples below demonstrate how a container query for `price` contained by `book` matches at multiple levels.

Query	Example Matching Documents

`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
`  <q:query>`
`  <book><price>8.99</price></book>`
`  </q:query>`
`</q:qbe>`
	`<book>`
	`  <price>8.99</price>`
	`</book>`

	`<book>`
	`  <edition>`
	`  <price>8.99</price>`
	`  </edition>`
	`</book>`

`{"$query": {`
`  "book":{"price": 8.99}`
`} }`
	`{ "book": {`
	`  "price": 8.99`
	`} }`

	`{ "book": {`
	`  "edition": {"price": 8.99 }`
	`} }`

	`{ "book": {`
	`  "edition": [ {"price": 8.99} ]`
	`} }`

A query on an XML element attribute is a container query in that the element "contains" the attribute. However, only attributes on the containing element can match. The following criteria matches `@format` only when it appears as an attribute of `edition`. It does not match occurrences of `@format` on child elements of `edition`.

```
<edition format="paperback"/>
```

The following table contains XML examples of container queries.

Description	Container Query

The element `price` is contained by the element `edition` and has a value of exactly 8.99.
 	
`price` need not be an immediate child of edition.
	`<edition>`
	`  <price>8.99</price>`
	`</edition>`

The attribute `format` is contained by the element `edition` and has the exact value "paperback".	`<edition format="paperback"/>`

The element `price` is contained by the element `edition` and has the exact value 8.99, or the element `publisher` is contained by the element `edition` and has the exact value "Fawcett".	`<edition>`
	`  <q:or>`
	`  <price>8.99</price>`
	`  <publisher>Fawcett</publisher>`
	`  </q:or>`
	`</edition>`

The following table contains JSON examples of container queries.

Description	Container Query
The JSON property `price` is contained in a property named `edition` and has the exact value 8.99. `price` need not be an immediate child of edition.	`"edition": {"price": 8.99 }`

The JSON property `price` is contained in a property named `edition` and has the exact value 8.99, or the property named `publisher` is contained in JSON property named `edition` and has the exact value "Fawcett".	`"edition": {`
	`  "$or": [`
	`  "price": 8.99,`
	`  "publisher": "Fawcett"`
	`  ]`
	`}`

5.4 Search Criteria Quick Reference

This section provides templates for constructing composed queries and frequently used criteria that model your documents.

- XML Search Criteria Quick Reference
- JSON Search Criteria Quick Reference
- Searching Entire Documents

5.4.1 XML Search Criteria Quick Reference

The table below provides a quick reference for constructing QBE search criteria and composed queries in XML. Use these examples as templates for your own criteria. For more details, see "QBE Structural Reference" on page 215.

The examples below assume that the namespace prefix q is bound to `http://marklogic.com/appservices/querybyexample`.

Criteria Description	Example

element *e* has value *v*	`<e>v</e>`
	
	`<e><q:value>v</q:value></e>`

the value of attribute *a* of element *e* is *v*	`<e a="v"/>`
	
	`<e a="$value v"/>`

element *e* contains word *w* anywhere in the substructure of the element content	`<e><q:word>w</q:word></e>`
the value of attribute a of element *e* includes the word *w*	`<e a="$word w"/>`
element *e* has a value greater than 5	`<e><q:gt>5</q:gt></e>`
the value of attribute a of element *e* is greater than 5	`<e a="$gt 5"/>`
element *e* exists	`<e><q:exists/></e>`
attribute *a* of element *e* exists	*not supported*

Criteria Description	Example

element *e1* contains element *e2* with value v; *e2* can occur anywhere in the substructure of the element content	`<e1>`
	`  <e2>v</e2>`
	`</e1>`

element *e1* contains a descendant element *e2*, and *e2* contains word w anywhere in the substructure of the element content	`<e1>`
	`  <e2><q:word>w</q:word></e2>`
	`</e1>`

element *e1* contains a descendant element *e2*, that has an attribute *a* with value *v*	`<e1>`
	`  <e2 a="v"/>`
	`</e1>`

element *e1* contains a descendant element *e2* that has an attribute a with word *w* in its value	`<e1>`
	`  <e2 a="$word w"/>`
	`</e1>`

a descendant of element *e* has attribute *a*	*not supported*

element *e* has value *v1* or *v2*	`<q:or>`
	`  <e>v1</e>`
	`  <e>v2</e>`
	`</q:or>`

element *e* contains word *w1* or *w2* anywhere in the substructure of the element content	`<q:or>`
	`  <e><q:word>w1</q:word></e>`
	`  <e><q:word>w2</q:word></e>`
	`</q:or>`

element *e1* contains a descendant element *e2*, and *e2* has value *v1* or *v2*	`<e1>`
	`  <q:or>`
	`  <e2>v1</e2>`
	`  <e2>v2</e2>`
	`  </q:or>`
	`</e1>`

the value of attribute *a* of element *e* has is *v1* or *v2*	`<q:or>`
	`  <e a="v1"/>`
	`  <e a="v2"/>`
	`</q:or>`

the value of attribute *a* of element *e* includes word *w1* or *w2*	`<q:or>`
	`  <e a="$word w1"/>`
	`  <e a="$word w2"/>`
	`</q:or>`

the value of attribute *a* of element *e2* that is a descendant of element *e1* is *v1* or *v2*	`<e1>`
	`  <q:or>`
	`  <e2 a="v1"/>`
	`  <e2 a="v2"/>`
	`  </q:or>`
	`</e1>`

5.4.2 JSON Search Criteria Quick Reference

The table below provides a quick reference for constructing QBE search criteria and composed queries in JSON. Where the example property name begins with *c*, the criteria represents a container query. For more details, see "QBE Structural Reference" on page 215.

This list of example critieria is not exhaustive. Additional forms are supported. For example, not all variants of explicit and implicit value queries are shown for a given criteria.

Criteria Description	Example

Property *k* with value *v*	`{ "k": "v"}`
	
	`{ "k": {"$value": "v"}}`

Array item with value *v*	`["v"]`
	
	`{"$value": ["v"]}`

Property *k* containing word *w* anywhere in the substructure of the property value	`{"k":{"$word":"w"}}`
Array item with a value that includes word *w*	`{"$word":["w"]}`
Property *k* with a value greater than 5	`{"k":{"$gt":5}}`
Array item with a value greater than 5	*not supported*
Property *k* exists	`{"k":{"$exists":{}}}`
Array item exists	*not supported*

A property named *c* containing a property named *k* with value *v*, where `k` can be anywhere in the substructure of *c*'s value	`{"c": {"k":"v"} }`
	
	`{"c": {`
	`  "k": {"$value": "v"}`
	`} }`

A property named *c* containing a property named *k* with a value that includes word *w*, where *k* can be anywhere in the substructure of *c*'s value	`{"c":{`
	`  "k":{"$word":"w"}`
	`}}`

A property named *c* containing an array item with value *v* anywhere within the substucture of *c*'s value.	`{"c": ["v"] }`
	
	`{"c":{`
	`  "k":{"$value": ["v"]}`
	`}}`

Criteria Description	Example
A property named *c* containing an array item that includes word *w*. The matching array item can be anywhere within the substructure of *c*'s value.	`{"c": {"$word": ["w"]} }`

A property named *k* with value *v1* or value *v2*	`{"$or":[`
	`  {"k":"v1"},`
	`  {"k":"v2"}`
	`]}`
	
	`{"$or":[`
	`  {"k": {"$value": "v1"}},`
	`  {"k": {"$value": "v2"}}`
	`]}`
	
	`{"k": {"$or": [`
	`  {"$value": "v1"},`
	`  {"$value": "v2"}`
	`]}}`

A property named *k* that includes word *w1* or *w2* in its value.	`{"$or":[`
	`  {"k":{"$word":"w1"}},`
	`  {"k":{"$word":"w2"}}`
	`]}`
	
	`{"k": {"$or": [`
	`  {"$word": "v1"},`
	`  {"$word": "v2"}`
	`]}}`

A property named *c* that contains a property named *k* with value *v1* or *v2* anywhere within the substructure of *c*'s value	`{"c":{"$or":[`
	`  {"k":"v1"},`
	`  {"k":"v2"}`
	`]}}`

A property named *c* that contains a property named *k* with value *v1* and a property named *k* with value *v2* anywhere within the substructure of *c*'s value. Matching documents will contain at least two occurrences of a property named *k*.	`{"c":{"$and":[`
	`  {"k":"v1"},`
	`  {"k":"v2"}`
	`]}}`
	
	`{"c":{"$and":[`
	`  {"k": {"$value": "v1"}},`
	`  {"k": {"$value": "v2"}}`
	`]}}`

Criteria Description	Example

A property named *k1* with value *v1* and a property named *k2* with value *v2*. *k1* and *k2* can be in different objects.	`{`
	`  "k1":"v1",`
	`  "k2":"v2"`
	`}`
	
	`{"$and":[`
	`  {"k1":"v1"},`
	`  {"k2":"v2"}`
	`]}`
	
	`{`
	`  "k1": {"$value": "v1"},`
	`  "k2": {"$value": "v2"}`
	`}`
	
	`{"$and":[`
	`  {"k1": {"$value": "v1"}},`
	`  {"k2": {"$value": "v2"}}`
	`]}`

An array item with value *v1* or an array item with value *v2*	`{"$or": ["v1", "v2"] }`
	
	`{"$or": [`
	`  {"$value": ["v1"]},`
	`  {"$value": ["v2"]}`
	`] }`

An array item with value *v1* and an array item with value *v2*	`["v1", "v2"]`
	
	`{"$value": ["v1", "v2"]}`
	
	`{"$and": ["v1", "v2"] }`
	
	`{"$and": [`
	`  {"$value": ["v1"]},`
	`  {"$value": ["v2"]}`
	`] }`

Criteria Description	Example

An array item with a value that includes word *w1* or an array item with a value that includes word *w2*	`{"$or":[`
	`  {"$word": ["w1"]},`
	`  {"$word": ["w2"]}`
	`]}`

An array item with a value that includes word *w1* and an array item with a value that includes word *w2*, possibly in different arrays	`{"$word": [ "w1", "w2" ]}`
	
	`{"$and": [`
	`  {"$word": ["w1"]},`
	`  {"$word": ["w2"]}`
	`] }`

A property named *c* that contains an array item with value *v1* and an array item with value *v2* anywhere in the substructure of *c*'s value.	`{"c":[ "v1", "v2" ]}`
	
	`{"c":{"$value":[ "v1", "v2" ]}}`
	
	`{"c":{"$and":[ "v1", "v2" ]}}`
	
	`{"$and":[`
	`  {"c":["v1"]},`
	`  {"c":["v2"]}`
	`]}`
	
	`{"$and":[`
	`  {"c": {"$value": ["v1"]}},`
	`  {"c": {"$value": ["v2"]}}`
	`]}`

A property named *c* that contains an array item with value *v1* or an array item with value *v2* anywhere in the substructure of *c*'s value	`{"c":{"$or":[ "v1", "v2" ]}}`
	
	`{"$or":[`
	`  {"c":["v1"]},`
	`  {"c":["v2"]}`
	`]}`
	
	`{"$or":[`
	`  {"c": {"$value": ["v1"]}},`
	`  {"c": {"$value": ["v2"]}}`
	`]}`

5.4.3 Searching Entire Documents

This section describes how to construct a query that matches words or phrases anywhere in a document, rather than constraining the match to occurrences in a particular XML element, XML attribute, or JSON property.

A word query has document scope if it is not contained in an XML element or JSON property criteria. For example, a word query that is an immediate child of the top level query element, or one that is a child at any depth of a hierarchy of composed queries (`and`, `or`, `not`, `near`). This also applies to the implicit `and` query that joins the immediate children of `query`.

For example, the following query matches all documents containing the phrase "moonlight sonata":

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <q:word>moonlight sonata</q:word>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "$word": "moonlight sonata"`
	`} }`

The following example matches all documents containing either the phrase "moonlight sonata" or the word "sunlight".

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <q:or>`
	`  <q:word>moonlight sonata</q:word>`
	`  <q:word>sunlight</q:word>`
	`  </q:or>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{"$query": {`
	`  "$or": [`
	`  {"$word": "moonlight sonata"},`
	`  {"$word": "sunlight"}`
	`  ]`
	`} }`

An AND relationship between words and phrases can be either explicit or implicit. The following example queries match all documents contains both the phrase “moonlight sonata” and the word “sunlight”:

Format	Example
XML	<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample"> <q:query> <q:word>moonlight sonata</q:word> <q:word>sunlight</q:word> </q:query> </q:qbe> <q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample"> <q:query> <q:and> <q:word>moonlight sonata</q:word> <q:word>sunlight</q:word> </q:and> </q:query> </q:qbe>

JSON	{"$query": [
	  {"$word": "moonlight"},
	  {"$word": "sunlight"}
	] }
	
	{"$query": {
	  "$and": [
	  {"$word": "moonlight"},
	  {"$word": "sunlight"}
	  ]
	} }

5.5 QBE Structural Reference

This section describes the syntax and semantics of a QBE. The following topics are covered:

- Top Level Structure
- Query Components
- Response Components
- XML-Specific Considerations
- JSON-Specific Considerations

5.5.1 Top Level Structure

At the top level, a QBE must contain a `query` and can optionally contain a `response` and/or a `format` flag. A QBE has the following top level parts:

- `query`: Define matching document requirements in the `query`.
- `response`: Customize your search results in the `response`; if there is no `response`, the default search response is returned.
- `format`: Use the `format` flag to override the interpretation of bare names as JSON property names or XML element names in no namespace, based on the query format. For details, see "Scoping a Search by Document Type" on page 237.
- `validate`: Use the validate flag to enable query validation before evaluating the search. The default is no validation, which can result in surprising search results if your QBE contains errors. However, validation has a performance cost, so it is best used only for debugging during development.

The following table outlines the top level of a QBE:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  *search parameters*`
	`  </q:query>`
	`  <q:response>`
	`  *search result customizations*`
	`  </q:response>`
	`  <q:format>*xml-or-json*</q:format>`
	`  <q:validate>*true-or-false*</q:validate>`
	`</q:qbe>`

JSON	`{`
	`  "$query": {`
	`  *search parameters*`
	`  },`
	`  "$response": {`
	`  *search result customizations*`
	`  },`
	`  "$format": *xml-or-json*,`
	`  "$validate": *boolean*`
	`}`

A `query` contains one or more XML elements or JSON properties defining element or property criteria or composed queries. Use criteria to model document structure. Use a composed query to logically join sub-queries using operators such as `and`, `or`, `not`, and `near`.

In XML, a QBE has a `qbe` wrapper element. Element and attribute names pre-defined by the QBE grammar, such as `qbe`, `query`, and `word`, are in the namespace `http://marklogic.com/appservices/querybyexample`. All other element and attributes names represent element and attribute names in your documents. For details, see "Managing Namespaces" on page 220

In JSON, all property names pre-defined by the QBE grammar have a "$" prefix, such as `$query` or `$word`. Any property name without a "$" prefix represents a property in your documents. For details, see "Property Naming Convention" on page 222.

You will not usually need to set the `format` flag. You only need to set the `format` flag to use a JSON QBE to match XML documents, or vice versa. For details, see "Scoping a Search by Document Type" on page 237.

5.5.2 Query Components

The table below describes the components of the `query` portion of a QBE. Additional format-specific details are covered in "XML-Specific Considerations" on page 220 and "JSON-Specific Considerations" on page 222.

Component Type	XML localname	JSON Property Name	Description
query	`query`	`$query`	Defines the search criteria. Required.
criteria	*`your element name`*	*`your property name`*	Defines search criteria to apply within the scope of an XML element or JSON property in your documents. The name corresponds to an element or property in the content to be matched by the query. If the criteria wraps a composed query or another criteria, then it represents a container query. Otherwise, it represents a value, word, or range query.

composed query	`and`
	
	`or`
	
	`not`
	
	`near`
		`$and`
		
		`$or`
		
		`$not`
		
		`$near`
			Defines a composed query that joins sub-queries using logical "operators".
			
			The `near` operator accepts an optional `distance` XML attribute or JSON property:
			• `<q:near distance="5">...</q:near>`
			• `{ "$near": "$distance":5, [..] }`

Component Type	XML localname	JSON Property Name	Description

range query	`lt, le`
	`gt, ge`
	`eq, ne`
		`$lt, $le`
		`$gt, $ge`
		`$eq, $ne`
			Defines a relational "expressions" on a value in an XML element, XML attribute, or JSON property.

modifier	`value`
	`word`
	`exists`
		`$value`
		`$word`
		`$exists`
			A modifier on a value that defines how to match that value: with a value query (the default with no modifier), with a word query, or with an existence test.

flag	`filtered` `score`	`$filtered` `$score`	Flags are modifiers of search behavior. Use the boolean `filtered` flag to control whether the search is filtered or unfiltered (default). For more details, see "How Indexing Affects Your Query" on page 226. Use the score flag to override the search result scoring function. Allowed values: `logtf`, `logtfidf`, `random`, `simple`, `zero`. Default: `logtfidf`. For details, see "Relevance Scores: Understanding and Customizing" on page 408.
options			Use options to fine tune your search criteria and results. For details, see "Adding Options to a QBE" on page 227.

The following table summarizes where each component type can be used. Options are covered in "Adding Options to a QBE" on page 227.

Component Type	Contains	Contained By
query	One or more criteria, composed queries, and the `filtered` or `score` flags	`qbe` (XML) root object (JSON)
criteria	• Nothing (empty); or • One value; or • One word, (explicit) value, or range query; or • One or more criteria or composed queries	`query`, composed query, criteria
composed query (`and`, `or`, etc.)	One or more criteria, composed queries, or word queries. Word queries are only permitted when the composed query is an immediate child of `query`.	`query`, composed query, or criteria
range query (`lt`, `gt`, etc.)	a value	criteria
word or value query	a value (string, number, date, time, dateTime)	`word`: `query`, criteria, or composed query `value`: criteria; composed query contained by a criteria
`exists`		criteria
flag		`query`

5.5.3 Response Components

You can use the `response` portion of a QBE to customize the format of your search results. The following table describes the components of a `response`. A `response` is optional, and can only occur at the top level of a QBE, as a sibling of `query`.

A response can contain the following formatter components:

XML localname	JSON Property Name	Description
`snippet`	`$snippet`	A `snippet` element controls what is returned for search matches. You can specify elements to prefer if they have a match and/or set a policy (`default`, `document`, `none`) for what to show.
`extract`	`$extract`	An `extract` element supplements a `snippet` by listing XML elements or JSON properties to extract from matching documents, whether or not a match occurs in the listed elements or property.

For details, see "Customizing Search Results" on page 232.

5.5.4 XML-Specific Considerations

This section covers structural and semantic details you should know when constructing a QBE in XML.

- Managing Namespaces
- Querying Attributes

5.5.4.1 Managing Namespaces

Use the namespace `http://marklogic.com/appservices/querybyexample` for all pre-defined element names in the QBE grammar, such as `qbe`, `query`, and `word`. This namespace distinguishes the structural parts of the query from criteria elements that model your documents. You define this namespace at the top level of your QBE. For example:

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
   ...
</q:qbe>
```

Define namespaces required by your element criteria on the criteria or any enclosing element container. You cannot bind the same namespace prefix to different namespaces within a QBE.

The following example demonstrates declaring user-defined namespaces on the root `qbe` element, on a containing element, and on an element criteria.

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample"
       xmlns:ns1="http://marklogic.com/example1">
```

```
  <q:query xmlns:ns2="http://marklogic.com/example2">
    <ns1:author xmlns="http://marklogic.com/example">
      Mark Twain
    </ns1:author>
    <ns2:edition format="paperback"/>
    <title xmlns="http://marklogic.com/example3">Tom Sawyer</title>
  </q:query>
</q:qbe>
```

5.5.4.2 Querying Attributes

To query an element attribute, create an element criteria that contains the attribute. The following example represents a value query for the attribute `edition/@format` with a value of "paperback".

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <edition format="paperback"/>
  </q:query>
</q:qbe>
```

The value of the attribute can be an implicit value query, as in the example above, or an explicit value, word, or range query. To create a word, range, or explicit value query on an attribute, use the following template for the attribute value, where *keyword* is a modifier (`word` or `value`) or comparator (`lt`, `gt`, etc.).

```
$keyword value
```

For example, the following QBE represents a range query on the attribute `edition/@price`.

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <edition price="$lt 9.00"/>
  </q:query>
</q:qbe>
```

You cannot use the `exists` modifier in an attribute value.

Multiple attributes on an element criteria are AND'd together. For example, the following QBE uses a range query on `edition/@price` and a word query on `edition/@format` paperback to find all paperback editions with a price less than 9.00.

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <edition price="$lt 9.00" format="$word paperback" />
    <q:filtered>true</q:filtered>
  </q:query>
</q:qbe>
```

You cannot use range, word, or value query options such as `exact`, `min-occurs`, or `score-function` on attribute criteria. If you need this level of control over an attribute query, use a structured query instead of QBE. For details, see "Searching Using Structured Queries" on page 78.

5.5.5 JSON-Specific Considerations

This section covers structural and semantic details you should know when constructing a QBE in JSON. The following topics are covered:

- Property Naming Convention
- Matching Array Items
- Searching Array and Object Containers
- Constructing a QBE with the Node.js QueryBuilder

5.5.5.1 Property Naming Convention

In JSON, all pre-defined JSON property names in the QBE grammar have a "`$`" prefix to distinguish them from names that occur in your documents. For example, the property name for the `query` part of a JSON QBE is `$query`.

If your documents include property names that start with "$", the names in your content can conflict with the pre-defined property names. In such a case, you must use a structured query instead of QBE. For details, see "Searching Using Structured Queries" on page 78.

For a list of pre-defined property names, see "Query Components" on page 217 and "Response Components" on page 219.

5.5.5.2 Matching Array Items

QBE does not distinguish between values contained in an array and values not contained in an array. For example, the following query:

```
{ "$query": {"k": ["v"]} }
```

Matches both of the following documents:

```
{ "k": "v" }
```

```
{ "k": ["v"] }
```

Also, the query is exactly equivalent to the following query that does not use array syntax:

```
{ "$query": {"k": "v"} }
```

Consequently, you cannot use QBE to match a property whose value is exactly and only a specified array value.

When you use array syntax and include multiple values, an AND relationship is implied between the values. For example, the following two queries are equivalent:

```
{"$query":
  {"k": ["v1", "v2"]}
}

{"$query": {
  "$and": [
    {"k": "v1"},
    {"k": "v2"}
  ]
}}
```

Both queries will match all of the following documents:

```
{ "k": ["v1", "v2"] }

{ "k": ["v1", "v2", "v3"] }

{ "c": [{"k": "v1"}, {"k": "v2"}] }

{"c": {"k": "v1", "c2": {"k": "v2"}}
```

5.5.5.3 Searching Array and Object Containers

The type of query represented by a criteria property that names a JSON property in your content depends on the type of value in the property. If the value is an object or a composed query, then it represents a container query. Otherwise, it is a value, word, or range query. You should understand how container queries apply to searching JSON documents..

A criteria property expresses “Match a JSON property named *k* whose value meets these conditions” if the value is a literal value, or a word, value, or range query. Such a criteria is not a container query. The table below illustrates these forms.

Criteria Template	Example Criteria	Description
name : *value*	{ "price" : 8.99 }	Match a property named "price" whose value is 8.99

name : {
  word-or-value : *value*
}
	{ "title" : {
	  "$word" : "sawyer"
	} }
		Match a property named "title" whose value includes "sawyer"

name : {
  relational-op : *value*
}
	{ "price" : {
	  "$lt" : 9
	} }
		Match a property named "price" whose value is less than 9

A criteria property in which the value is an object or a composed query is a container query. Such a query says "Match a property named *c* that contains a value meeting these conditions *anywhere in its substructure*." The table below illustrtates these forms.

Criteria Template	Example Criteria	Description
name : *object*	{"edition": {"price" : 8.99 } }	Match a JSON property named "price" whose value is 8.99 and that is contained somewhere within a property named "edition". The value can occur as an array item.

name : {
logical-op : [
sub-query+
]
}
	{"edition" : {
	"$or": [
	{"format": "paperback"},
	{"format": "hardback"}
	]
	} }
		Match a JSON property named "format" that is contained somewhere within a property named "edition" and whose value is "paperback" or "hardback". The values can occur as array items.

Since a container query always matches its sub-queries anywhere within the container substructure, you cannot construct a JSON QBE that matches "a container with property name *k* whose value is exactly and only this object".

The table below provides example documents matched by a value query and several kinds of container query. The matched document examples are not exhaustive. Each query is annotated with a textual description of what the criteria asserts about matching documents. For more examples, see "JSON Search Criteria Quick Reference" on page 210.

QBE	Matches
{"$query": { "k": "v" } } Property *k* has value "*v*"	{ "k": "v" } { "k": ["v"] }

QBE	Matches
{"$query": {"k": ["v1", "v2"]} } Property *k* has value "*v1*" and value "v2".	{ "k": ["v1", "v2"] } { "c": [{"k": "v1"}, {"k": "v2"}] } {"c": {"k": "v1", "c2": {"k": "v2"}}

{"$query":
  {"c": {"k": "v"}}
}
 	
Property *c* contains a property *k* that has value "*v*", where *k* can occur anywhere in *c*'s substructure.
	{ "c" : {"k" : "v" } }
	
	{ "c" :
	  {"c2": {"k": "v" }}
	}

5.5.5.4 Constructing a QBE with the Node.js QueryBuilder

This topic describes how to use the information in this chapter in conjunction with the Node.js Client API.

The Node.js Client API enables you to construct a QBE using the `QueryBuilder.byExample` function. The parameters of `byExample` correspond to the criteria within the `$query` portion of a raw QBE, expressed as a JavaScript object. For example, the table below shows a QBE example from elsewhere in this chapter and the equivalent `QueryBuilder.byExample` call.

Raw QBE	QueryBuilder.byExample

{"$query": {
  "author": {"$word": "twain"},
  "$filtered": true
}}
	qb.byExample({
	  author: {$word: 'twain'},
	  $filtered: true
	})

You can also supply the entire `$query` portion of a QBE to `byExample` as a JavaScript object. For example:

```
qb.byExample(
  { $query: {
    author: {$word: 'twain'},
    $filtered: true
  }
)
```

However, you cannot specify `$response` portions of a raw QBE through `QueryBuilder.byExample`. Response customization is still available through `QueryBuilder.extract` and `QueryBuilder.snippet`.

For details, see Querying Documents and Metadata in the *Node.js Application Developer's Guide*.

5.6 How Indexing Affects Your Query

You do not have to define any indexes to use QBE. This allows you to get started with QBE quickly. However, indexes can significantly improve the performance of your search.

Unless your database is small or your query produces only a small set of pre-filtering results, you should define an index over any XML element, XML attribute, or JSON property used in a range query. To configure an index, see Range Indexes and Lexicons in *Administrator's Guide*.

If your QBE includes a range query, you must either have an index configured on the XML element, XML attribute, or JSON property used in the range query, or you must use the `filtered` flag to force a filtered search.

A filtered search uses available indexes, if any, but then checks whether or not each candidate meets the query requirements. This makes a filtered search accurate, but much slower than an unfiltered search. An unfiltered search relies solely on indexes to identify matches, which is much faster, but can result in false positives. For details, see Fast Pagination and Unfiltered Searches in *Query Performance and Tuning Guide*.

In the absence of a backing index, a range query cannot be used with unfiltered search. To enable filtered search, set the `filtered` flag to true in the `query` portion of your QBE, as shown in the following example:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author><q:word>twain</q:word></author>`
	`  **<q:filtered>true</q:filtered>**`
	`  </q:query>`
	`</q:qbe>`

JSON	`{`
	`  "$query": {`
	`  "author": {"$word": "twain"},`
	`  **"$filtered": true**`
	`  }`
	`}`

5.7 Adding Options to a QBE

Options give you fine grained control over a QBE. Most options are associated with a value, word, or range query.

- Specifying Options in XML
- Specifying Options in JSON
- Option List
- Using Persistent Query Options

5.7.1 Specifying Options in XML

In an XML QBE, an option is an attributes of the predefined QBE element it modifies, such `<q:lt/>`, `<q:word/>` or `<q:value>`. The following query demonstrates use of the `exact` option on a value query.

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <author><q:value exact="false">mark twain</q:value></author>
  </q:query>
</q:qbe>
```

You cannot apply options to queries on attributes because the range, word, or value query is embedded in the attribute value. For example, you cannot add a `case-sensitive` option to the following attribute word query:

```
<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">
  <q:query>
    <edition @format="$word paperback"/></edition>
  </q:query>
</q:qbe>
```

If you need such control over an element attribute query, you should use a structured or combined query.

5.7.2 Specifying Options in JSON

In a JSON QBE, an option is a sibling of the QBE object it modifies, such as a value, word, or range query. Option names always have a “$” prefix.

The following example query uses the `exact` option to modify a value query by including it as a JSON property at the same level as the `$value` object:

```
{
  "$query": {
    "author": {
      "$exact": false,
```

```
            "$value": "mark twain"
          }
        }
      }
```

5.7.3 Option List

The following table describes the options available for use in a QBE. The MarkLogic Server Search API supports additional options through other query formats, such as string or structured query, and through the use of persistent query options. For details, see "Search Customization Using Query Options" on page 368.

Option Attribute or Property Name	Description
`case-sensitive`	Whether or not to perform a case-sensitive match. Default: false if the text to match is all lower case, true otherwise. Value type: boolean. Usable with: word or value query. For details, see `cts:word-query` or `cts:value-query`.
`diacritic-sensitive`	Whether or not to perform a diacritic-sensitive match. Default: Depends on context: false if the text to match contains no diacritics, true otherwise. Value type: boolean. Usable with: word or value query. For details, see `cts:word-query` or `cts:value-query`.
`punctation-sensitive`	Whether or not to perform a punctuation-sensitive match. Default: depends on context: false if the text to match contains no punctuation, true otherwise. Value type: boolean. Usable with: word or value query. For details, see `cts:word-query` or `cts:value-query`.
`whitespace-sensitive`	Whether or not to perform a whitespace-sensitive match. Default: false. Value type: boolean. Usable with: word or value query. For details, see `cts:word-query` or `cts:value-query`.
`stemmed`	Whether or not to use stemming. Default: Depends on context and database configuration; for details, see `cts:word-query`. Value type: boolean. Usable with: word or value query. For details, see `cts:word-query` or `cts:value-query`.

Option Attribute or Property Name	Description
`exact`	Whether to perform an exact match or use the builtin context-sensitive default behaviors for the `*-sensitive` options. When true, `exact` is shorthand for case-sensitive, diacritic sensitive, punctuation-sensitive, whitespace-sensitive, unstemmed, and unwildcarded. Default: true for value and range query, false for word query. Value type: boolean. Usable with: word or value query.
`score-function`	Use the selected scoring function. Allowed values: `linear`, `reciprocal`. Usable with: range query. For details, see "Including a Range or Geospatial Query in Scoring" on page 416.
`slope-factor`	Apply the given number as a scaling factor to the slope of the scoring function. Default: 1.0. Value type: double. Usable with: range query. For details, see "Including a Range or Geospatial Query in Scoring" on page 416.
`min-occurs`	The minimum number of occurrences required. If there are fewer occurrences, the fragment does not match. Default: 1. Value type: integer. Usable with: range, word, or value query. For details, see `cts:word-query`.
`max-occurs`	The maximum number of occurrences required. If there are more occurrences, the fragment does not match. Default: Unbounded. Value type: integer. Usable with: range, word, or value query. For details, see `cts:word-query`.
`lang`	The language under which to interpret the content. The option value is case-insensitive. Allowed values: An ISO 639 language code. Default: The default language configured for the database. Usable with: `query`; range, word, or value query. In XML it can also appear on the `qbe` element. In JSON, it can appear as a top level property.
`weight`	A weight for this query. Higher weights move search results up in the relevance order. Allowed values: less than or equal to 64 and greater tha or equal to -16 (between -16 and 64). Default: 1.0. Usable with: a word or value query, or a range query that is backed by a range index. For details, see `cts:word-query`, `cts:value-query`, or `cts:element-range-query`.

Option Attribute or Property Name	Description
`constraint`	The name of a range, values, or word constraint specified for the same XML element or JSON property in persisted query options associated with the search. Usable with: range, word, or value query. For details, see "Using Persistent Query Options" on page 230.
`@xsi:type (XML)` `$datatype (JSON)`	The `xsi:type` to which to cast the value supplied in a range query. Default: Values are treated as `xs:boolean`, `xs:double`, `xs:date`, `xs:dateTime`, or `xs:time` if castable as such, and as string otherwise. Usable with: range query.

5.7.4 Using Persistent Query Options

The REST and Java APIs enable you to install persistent query options on your REST instance and apply them to subsequent searches. You can also use persistent query options with the Node.js Client API, but the API has no facility for creating and maintaining the persistent options.

Using persistent query options with a QBE allows you to use options not supported directly by the QBE grammar. Using persistent options with a QBE also allows you to define global options to apply throughout your query, such as making all word queries case-sensitive instead of specifying the `case-sensitive` option on each word query in your QBE.

Query options applied through through the `constraint` option override options specified inline on a QBE.

You can apply persistent query options to a QBE using the `constraint` option. To use this option:

1. Install named, persistent query options following the directions appropriate for the API you are using.

2. Specify the name of a constraint defined in the persistent options from Step 1 as the value of a `constraint` option on a word, value, or range query in your QBE. See the example, below.

3. When you execute a search with your QBE, associate the persistent query options from Step 1 with your search in the manner prescribed by the client API (REST, Java, or Node.js).

For details on defining, installing and using persistent query options, see Configuring Query Options in *REST Application Developer's Guide* or Query Options in *Java Application Developer's Guide*.

The pre-defined constraint named by the `constraint` option should match the type of query to which it is applied. That is, name a range constraint for a range query, a value constraint for a value query, and a word constraint for a word query.

The following example pre-defines a word constraint called "w-t" that gives weight 2.0 to matches in a `title` XML element or JSON property, and then applies it to a QBE that contains a word query on `title`. This enables word queries on `title` a default weight that can be overridden by omitting the `constraint` option.

If the folloiwng persistent query options are installed specified as a parameter to the search performed with the QBE:

XML Options	JSON Options

`<search:options`
`  xmlns:search="http://marklogic.com/appservices/search">`
`  <search:constraint name="w-t">`
`  <search:word>`
`  <search:element name="title" ns=""/>`
`  <search:weight>2.0</search:weight>`
`  </search:word>`
`  </search:constraint>`
`</search:options>`
	`{"options": {`
	`  "constraint": [ {`
	`  "name": "w-t",`
	`  "word": {`
	`  "json-property": "title",`
	`  "weight": 2`
	`  }`
	`  } ]`
	`} }`

Then the following QBE applies the "w-t" option to a word query on `title` to give weight 2.0 to matches in a `title` element.

XML	JSON

`<q:qbe`
`  xmlns:q="http://marklogic.com/appservices/querybyexample">`
`  <q:query>`
`  <title>`
`  <q:word **constraint="w-t"**>sawyer</q:word>`
`  </title>`
`  </q:query>`
`</q:qbe>`
	`{ "$query": {`
	`  "title": {`
	`  "$word": "sawyer",`
	`  **"$constraint": "w-t"**`
	`  }`
	`} }`

5.8 Customizing Search Results

You can include a `response` XML element or JSON property to customize the contents of returned search results. You can modify or supplement the default search results using the `snippet` and `extract` formatters in the `response` section of a QBE.

This section covers the following topics:

- When to Include a Response in Your Query
- Using the snippet Formatter
- Using the extract Formatter

5.8.1 When to Include a Response in Your Query

Add an optional `response` section to a QBE to do one or more of the following:

- Return matching documents instead of snippets. (`snippet`)
- Return only information about the document and the match, such as database URI, document format, and relevance score. (`snippet`)
- Specify XML elements or JSON properties to prefer when constructing snippets. (`snippet`)
- Specify XML elements or JSON properties to extract from matching documents, whether or not the match occurs within those elements or properties. (`extract`)

Advanced customization is available using result decorators, transforms, and persistent query options. For details, see Customizing Search Results in *REST Application Developer's Guide* or Transforming Search Results in *Java Application Developer's Guide*.

5.8.2 Using the snippet Formatter

Use `snippet` to control what, if anything, is included in the snippet portion of a search match and to identify preferred XML elements or JSON properties to include a snippet. The default snippet is a small text excerpt with the matching text tagged for highlighting. The following table contains an excerpt of the snippet section of a search response generated with the default policy.

Format	Default Snippet Example

XML	`<search:response ...>`
	`  <search:result ...>`
	`  **<search:snippet>**`
	`  **<search:match**`
	`  **path="fn:doc("/books/sawyer.xml")/book">**`
	`  **<search:highlight>Mark Twain</search:highlight>**`
	`  **</search:match>**`
	`  **</search:snippet>**`
	`  </search:result>`
	`  ...`
	`</searchresponse>`

JSON	`{`
	`  ...`
	`  "results": [ {`
	`  ...`
	`  "matches": [ {`
	`  "path": "fn:doc(\"/books/sawyer.json\")/*:json/*:book/*:author",`
	`  **"match-text": [ { "highlight": "Mark Twain" } ]**`
	`  } ]`
	`  } ],`
	`  ...`
	`}`

The snippet formatter has the following form:

XML	JSON

`<q:response>`
`  <q:snippet>`
`  <q:*policy*/>`
`  *preferred-element*`
`  </q:snippet>`
`</q:response>`
	`{ "$response": {`
	`  "$snippet": {`
	`  *policy*: {},`
	`  *preferred-property*: {}`
	`  },`
	`} }`

The *policy*, *preferred-element*, and *preferred-property* are optional.

The snippeting policy controls whether or not snippets are included in the output and whether to include a small text excerpt (default) or the entire document when snippets are enabled. Use one of the following element or property names for policy.

XML	JSON	Description
`default`	`$default`	Include a small excerpt of the text around the matching terms, with the matched text tagged for highlighting.
`document`	`$document`	Return the entire document.
`none`	`$none`	Do not include any snippets.

The following example disables snippet generation by setting the snippet policy to `none`. In JSON, specify an empty object value for the policy property.

XML	JSON

`<q:response>`
`  <q:snippet>`
`  <q:none/>`
`  </q:snippet>`
`</q:response>`
	`{ "$response": {`
	`  "$snippet": {`
	`  "$none": {}`
	`  }`
	`} }`

You can also specify one or more XML element or JSON property names to be preferred when generating snippets. For example, if you specify a preference for the `title` element or property, and both `title` and `author` contain a match, the snippet is generated from the match in `title`. In JSON, specify the preferred property with an empty object value.

XML	JSON

`<q:response>`
`  <q:snippet>`
`  <title/>`
`  </q:snippet>`
`</q:response>`
	`{ "$response": {`
	`  "$snippet": {`
	`  "title": {}`
	`  }`
	`} }`

5.8.3 Using the extract Formatter

Use the `extract` formatter to specify additional XML elements or JSON properties to include in the search output. If snippets are included, the extracted components supplement any snippet in a match, rather than replacing it.

XML	JSON

`<q:response>`
`  <q:extract>`
`  <your-element/>`
`  </q:extract>`
`</q:response>`
	`{ "$response": {`
	`  "$extract": {`
	`  "your-property-name": {}`
	`  }`
	`} }`

For example, the following response says to extract the `title` and `author` from a matching document. The `title` and `author` need not contain the matching terms or values.

XML	JSON

`<q:response>`
`  <q:extract>`
`  <title/>`
`  <author/>`
`  </q:extract>`
`</q:response>`
	`{ "$response": {`
	`  "$extract": {`
	`  "title": {},`
	`  "author": {}`
	`  }`
	`} }`

Extracted elements or properties go into the `metadata` section of the enclosing match. For an example, see “Example: Search Customization” on page 236.

5.8.4 Example: Search Customization

The following QBE modifies the search results to exclude snippets and to extract the `title` XML element or JSON property into the search result `metadata` section.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Mark Twain</author>`
	`  </q:query>`
	`  <q:response>`
	`  <q:extract><title/></q:extract>`
	`  <q:snippet><q:none/></q:snippet>`
	`  </q:response>`
	`</q:qbe>`

JSON	`{`
	`  "$query": {`
	`  "author": "Mark Twain"`
	`  },`
	`  "$response": {`
	`  "$snippet": { "$none": {} },`
	`  "$extract": { "title": {} }`
	`  }`
	`}`

The following table shows the default output and the modified output produced by the above query.

Format	Default Output	Customized Output
XML	<search:response **snippet-format="snippet"** total="1" start="1" page-length="10" ...> <search:result index="1" uri="/books/sawyer.xml" ...> **<search:snippet>** **<search:match ...>** **<search:highlight>** **Mark Twain** **</search:highlight>** **</search:match>** **</search:snippet>** </search:result> ... </search:response>	<search:response **snippet-format="empty-snippet"** total="1" start="1" page-length="10" ..> <search:result index="1" uri="/books/sawyer.xml" ...> **<search:snippet/>** **<search:metadata>** **<title>Tom Sawyer</title>** **</search:metadata>** </search:result> ... </search:response>

JSON	{
	"snippet-format": "snippet",
	"total": 1,
	"start": 1,
	"page-length": 10,
	"results": [{
	"index": 1,
	"uri": "/books/sawyer.json",
	"matches": [{
	"path": ...,
	"match-text": [{
	"highlight": "Mark Twain"
	}]
	}]
	}],
	...
	}
		{
		"snippet-format":
		"empty-snippet",
		"total": 1,
		"start": 1,
		"page-length": 10,
		"results": [{
		"index": 1,
		"uri": "/books/sawyer.json",
		...,
		"matches": [],
		"metadata": [{
		"title": "Tom Sawyer"
		}]
		}],
		...
		}

5.9 Scoping a Search by Document Type

This section describes how the treatment of bare names in a QBE affects the type of documents matched by the query.

A bare name in a JSON QBE is a JSON property name that does not include a "$" prefix. A bare name in an XML QBE is an element name in no namespace.

By default, the interpretation of bare names matches your query format. That is, bare names in a JSON QBE represent JSON property names in content, and bare names in an XML QBE represent element names in content that are in no namespace. The net effect is that an XML QBE only matches XML documents, and a JSON QBE only matches JSON documents by default.

Use the `format` option to override the default behavior, as shown in the following example:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  **<q:format>json</q:format>**`
	`  <q:query>...</q:query>`
	`</q:qbe>`

JSON	`{`
	`  **"$format": "xml"**,`
	`  "$query": {...}`
	`}`

5.10 Converting a QBE to a Combined Query

The primary use case for QBE is rapid prototyping of queries during development. For best performance and access to the full set of Search API capabilities, you should eventually convert your QBE to a combined query. A combined query is a lower level representation that combines a structured query and query options.

The REST and Java APIs include an interface for generating a combined query from a QBE. For details, see the following:

- Convert a QBE to a Combined Query in *Java Application Developer's Guide*
- Generating a Combined Query from a QBE in *REST Application Developer's Guide*
- "Searching Using Structured Queries" on page 78

5.11 Validating a QBE

You can set the `validate` flag to true to perform query validation before evaluating a QBE. When validation is enabled, if you submit a QBE that contains errors, MarkLogic reports the errors and does not perform the search. If your query does not contain errors, the search proceeds as usual.

Performing query validation on every search can be expensive, so you should not enable validation in production. It is best used for debugging during development.

The following example is a QBE with validation enabled:

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <author>Mark Twain</author>`
	`  </q:query>`
	`  <q:validate>true</q:validate>`
	`</q:qbe>`

JSON	`{`
	`  "$query": {`
	`  "author": "Mark Twain"`
	`  },`
	`  "$validate": true`
	`}`

6.0 Composing cts:query Expressions

Searches in MarkLogic Server use expressions that have a `cts:query` type. This chapter describes how to create various types of `cts:query` expressions and how you can register some complex expressions to improve performance of future queries that use the registered `cts:query` expressions.

MarkLogic Server includes many Built-In XQuery functions to compose `cts:query` expressions. The signatures and descriptions of the various APIs are described in the *MarkLogic XQuery and XSLT Function Reference*.

This chapter includes the following sections:

- Understanding cts:query
- Creating a Query From Search Text With cts:parse
- Combining multiple cts:query Expressions
- Joining Documents and Properties with cts:properties-query or cts:document-fragment-query
- Registering cts:query Expressions to Speed Search Performance
- Adding Relevance Information to cts:query Expressions:
- XML Serializations of cts:query Constructors
- Example: Creating a cts:query Parser

6.1 Understanding cts:query

The second parameter for `cts:search` takes a parameter of `cts:query` type. The contents of the `cts:query` expression determines the conditions in which a search will return a document or node. This section describes `cts:query` and includes the following parts:


- cts:query Hierarchy
- Use to Narrow the Search
- Understanding cts:element-query
- Understanding cts:element-word-query
- Understanding Field Word and Value Query Constructors
- Understanding the Range Query Constructors
- Understanding the Reverse Query Constructor
- Understanding the Geospatial Query Constructors
- Specifying the Language in a cts:query

6.1.1 cts:query Hierarchy

The `cts:query` type forms a hierarchy, allowing you to construct complex `cts:query` expressions by combining multiple expressions together. The hierarchy includes composable and non-composable `cts:query` constructors.

A *composable* constructor is one that is used to combine multiple `cts:query` constructors together. A *leaf-level* constructor is one that cannot be used to combine with other `cts:query` constructors (although it can be combined using a composable constructor).

The following diagram shows the leaf-level `cts:query` constructors, which are not composable, and the composable `cts:query` constructors, which you can use to combine both leaf-level and other composable `cts:query` constructors. The diagram shows most of the available constructors, but not necessarily all of them.



Equivalent constructors exist for Server-Side JavaScript. For example, the JavaScript built-in `cts.andQuery` is equivalent to the XQuery built-in `cts:and-query` in the diagram above.

The remainder of this chapter goes into more detail on combining constructors.

6.1.2 Use to Narrow the Search

The core search `cts:query` API is `cts:word-query`. The `cts:word-query` function returns true for words or phrases that match its `$text` parameter, thus narrowing the search to fragments containing terms that match the query. If needed, you can use other `cts:query` APIs to combine a `cts:word-query` expression into a more complex expression. Similarly, you can use the other leaf-level cts:query constructors to narrow the results of a search.

6.1.3 Understanding cts:element-query

The `cts:element-query` function searches through a specified element and all of its children. It is used to narrow the field of search to the specified element hierarchy, exploiting the XML structure in the data. Also, it is composable with other `cts:element-query` functions, allowing you to specify complex hierarchical conditions in the `cts:query` expressions.

For example, the following search against a Shakespeare database returns the title of any play that has SCENE elements that have SPEECH elements containing both the words “room” and “castle”:

```
for $x in cts:search(fn:doc(),
   cts:element-query(xs:QName("SCENE"),
       cts:element-query(xs:QName("SPEECH"),
           cts:and-query(("room", "castle")) ) ) )
return
($x//TITLE)[1]
```

This query returns the first `TITLE` element of the play. The `TITLE` element is used for both play and scene titles, and the first one in a play is the title of the play.

When you use `cts:element-query` and you have both the `word positions` and `element word positions` indexes enabled in the Admin Interface, it will speed the performance of many queries that have multiple term queries (for example, `"the long sly fox"`) by eliminating some false positive results.

6.1.4 Understanding cts:element-word-query

While `cts:element-query` searches through an element and all of its children, `cts:element-word-query` searches only the immediate text node children of the specified element. For example, consider the following XML structure:

```
<root>
  <a>hello
    <b>goodbye</b>
  <a>
</root>
```

The following query returns `false`, because `"goodbye"` is not an immediate text node of the element named `a`:

```
cts:element-word-query(xs:QName("a"), "goodbye")
```

6.1.5 Understanding Field Word and Value Query Constructors

The `cts:field-word-query` and `cts:field-value-query` constructors search in fields for either words or values. A field value is defined as all of the text within a field, with a single space between text that comes from different elements. For example, consider the following XML structure:

```
<name>
  <first>Raymond</first>
  <middle>Clevie</middle>
  <last>Carver</last>
</name>
```

If you want to normalize names in the form `firstname lastname`, then you can create a field on this structure. The field might include the element `name` and exclude the element `middle`. The value of this instance of the field would then be `Raymond Carver`, with a space between the text from the two different element values from `first` and `last`. If your document contained other `name` elements with the same structure, their values would be derived similarly. If the field is named `my-field`, then a `cts:field-value-query("my-field", "Raymond Carver")` returns true for documents containing this XML. Similarly, a `cts:field-word-query("my-field", "Raymond Carver")` returns true.

For more information about fields, see Fields Database Settings in the *Administrator's Guide*. For information on lexicons on fields, see "Field Value Lexicons" on page 436.

6.1.6 Understanding the Range Query Constructors

The `cts:element-range-query`, `cts:element-atribute-range-query`, `cts:path-range-query`, and `cts:field-range-query` constructors allow you to specify constraints on a value in a `cts:query` expression. The range query constructors require a range index on the specified element or attribute. For details on range queries, see "Using Range Queries in cts:query Expressions" on page 445.

6.1.7 Understanding the Reverse Query Constructor

The `cts:reverse-query` constructor allows you to match queries stored in a database to nodes that would match those queries. Reverse queries are used as the basis for alert applications. For details, see "Creating Alerting Applications" on page 491.

6.1.8 Understanding the Geospatial Query Constructors

The geospatial query constructors are used to constrain `cts:query` expressions on geospatial data. Geospatial searches are used with documents that have been marked up with latitude and longitude data, and can be used to answer queries like "show me all of the documents that mention places within 100 miles of New York City." For details on gesospatial searches, see "Geospatial Search Applications" on page 462.

6.1.9 Specifying the Language in a cts:query

All leaf-level `cts:query` constructors are language-aware; you can either explicitly specify a language value as an option, or it will default to the database default language. The language option specifies the language in which the query is tokenized and, for stemmed searches, the language of the content to be searched.

To specify the language option in a `cts:query`, use the `lang=`*`language_code`*, where *language_code* is the two or three character ISO 639-1 or ISO 639-2 language code (http://www.loc.gov/standards/iso639-2/php/code_list.php). For example, the following query:

```
let $x :=
<root>
 <el xml:lang="en">hello</el>
 <el xml:lang="fr">hello</el>
</root>
return
$x//el[cts:contains(.,
         cts:word-query("hello", ("stemmed", "lang=fr")))]
```

returns only the French-language node:

```
<el xml:lang="fr">hello</el>
```

Depending on the language of the `cts:query` and on the language of the content, a string will tokenize differently, which will affect the search results. For details on how languages and the `xml:lang` attribute affect tokenization and searches, see "Language Support in MarkLogic Server" on page 594.

6.2 Creating a Query From Search Text With cts:parse

This section describes how to create a cts:query from a simple search string using the `cts:parse`. XQuery function or the `cts.parse` Server-Side JavaScript function. The following topics are covered:

- String Query Overview
- Grammar Components and Operators
- Binding a Tag to a Reference, Field, or Query Generator

- Customizing Naked Term Handling With Bindings

6.2.1 String Query Overview

A *string query* is a plain text search string ("query text") composed of terms, phrases, and operators that can be easily composed by end users typing into an application search box. For example, "cat AND dog" is a string query for finding documents that contain both the term "cat" and the term "dog".

You can use the `cts:parse` XQuery built-in function or the `cts.parse` Server-Side JavaScript built-in function to convert such a string query into a cts:query (XQuery) or cts.query (JavaScript). Use the resulting query in any interface that accepts a cts query, such as the `cts:search` XQuery function, the `cts.search` JavaScript function, and several JSearch API interfaces.

The following example uses `cts:parse` to match documents that contain the term "cat" and the term "dog".

Language	Example
XQuery	`cts:search(cts:parse("cat AND dog"))`

JavaScript	`// with cts.search`
	`cts.search(cts.parse('cat AND dog'))`
	
	`// with JSearch`
	`var jsearch = require('/MarkLogic/jsearch.sjs');`
	`jsearch.documents()`
	`  .where(cts.parse('cat AND dog'))`
	`  .result()`

The string query grammar supported by `cts:parse` enables users to compose complex queries. Adjacents terms, phrases and sub-expressions are implicitly AND'd together.

The following are some examples of queries that work with `cts:parse` "out of the box":

- `(cat OR dog) NEAR vet`

  at least one of the terms `cat` or `dog` within 10 terms (the default distance for `cts:near-query`) of the word `vet`

- `dog NEAR/30 vet`

  the word `dog` within 30 terms of the word `vet`

- `cat -dog`

  the word `cat` where there is no word `dog`

You can also bind a tag name to an index reference, lexicon reference, or field name. When such a tag name appears in a query string, it parses to a word, value, or range query that is scoped to the bound entity.

For example, binding the tag "color" to a `cts:reference` to a JSON property named `bodyColor` enables users to create query text like the following:

- `color:red`

  Match documents where the value of the `bodyColor` contains the word "red"

- `color NE blue`

  Match documents where the value of `bodyColor` is not "blue"

Without the binding, the above examples are just word queries that include the term "color". For example, without a binding, "color NE blue" becomes a query for documents containing the words "color", "NE", and "blue".

You can also bind a tag name to a reference to a function that generates a query, giving you more control over the interpretation. For example, you can use a query generator function to scope a query to documents in a particular collection or directory.

For details, see "Binding a Tag to a Reference, Field, or Query Generator" on page 253.

6.2.2 Grammar Components and Operators

This section describes the components and operators you can use in query text passed to cts.parse. Some operators are only available in search terms that involve tags bound to query generators using the parse binding feature.

- Basic Components and Operators
- Operators Usable With Bound Tags
- Including Options and Weights in Query Text
- Query Text Parsing Examples

6.2.2.1 Basic Components and Operators

The table below describes the basic components and operators recognized by the `cts:parse` XQuery function and the `cts.parse` JavaScript function. If you define bindings, then additional operators become available for query expressions using a bound tag. For details, see "Operators Usable With Bound Tags" on page 250.

Note that an empty query string (`cts:parse("")`) generates an empty `cts:and-query` that matches everything.

Query	Example	Description

any adjacent terms	`dog`
	`dog tail`
	`"dog tail" cat mouse`
	`dog (cat OR mouse)`
		Match one or more terms or query expressions, as with a `cts:and-query`. Adjacent terms and query expressions are implicitly joined with `AND`. For example, `dog tail` is the same as `dog AND tail`.

"*phrase*"	`"dog tail"`
	`"dog tail" "cat whisker"`
	`dog "cat whisker"`
		Terms in double quotes are treated as a phrase. Adjacent terms and phrases are implicitly joined with `AND`. For example, `dog "cat whisker"` matches documents containing both the term `dog` and the phrase `cat whisker`.

( )	`(cat OR dog) zebra`	Parentheses indicate grouping. The example matches documents containing at least one of the terms `cat` or `dog` as well as the term `zebra`.

-query	`-dog`
	`-(dog OR cat)`
	`cat -dog`
		A NOT operation, as with a `cts:not-query`. For example, `cat -dog` matches documents that contain the term `cat` but that do not contain the term `dog`.

query1 `AND` *query2*	`dog AND cat` `(cat OR dog) AND zebra`	Match two query expressions, as with a `cts:and-query`. For example, `dog AND cat` matches documents containing both the term `dog` and the term `cat`. `AND` is the default way to combine terms and phrases, so the previous example is equivalent to `dog cat`.

Query	Example	Description
query1 `OR` *query2*	`dog OR cat`	Match either of two queries, as with a `cts:or-query`. The example matches documents containing at least one of either of terms `cat` or `dog`.
query1 `NOT_IN` *query2*	`dog NOT_IN "dog house"`	Match one query when the match does not overlap with another, as with `cts:not-in-query`. The example matches occurrences of `dog` when it is not in the phrase `dog house`.
query1 `NEAR` *query2*	`dog NEAR cat` `(cat food) NEAR mouse`	Find documents containing matches to the queries on either side of the `NEAR` operator when the matches occur within 10 terms of each other, as with a `cts:near-query`. For example, `dog NEAR cat` matches documents containing `dog` within 10 terms of `cat`.
query1 `NEAR/`*`N`* *query2*	`dog NEAR/2 cat`	Find documents containing matches to the queries on either side of the NEAR operator when the matches occur within *N* terms of each other, as with a `cts:near-query`. The example matches documents where the term `dog` occurs within 2 terms of the term `cat`.
query1 `BOOST` *query2*	`george BOOST washington`	Find documents that match *query1*. Boost the relevance score of documents that also match *query2*. The example returns all matches for the term “george”, with matches in documents that also contain “washington” having a higher relevance score. For more details, see `cts:boost-query`.
query [*opt*,*opt*,...]	`cat[min-occurs=5]`	Pass options or a weight to the cts query generated for *query*. For details, see “Including Options and Weights in Query Text” on page 252

6.2.2.2 Operators Usable With Bound Tags

When you bind a tag to an index, lexicon, field, or query generator, then you can use the tag name in the ways shown in the following table. If you use these operators in a context in which the left operand is not a tag name, then the "operator" is simply interpreted as another query term. That is, "unbound LT value" is a `cts:and-query` of word queries on the words "unbound", "LT", and "value".

For more information on defining a binding, see "Binding a Tag to a Reference, Field, or Query Generator" on page 253.

The sub-expressions enabled by these operators can be used in combination with the grammar features described in "Basic Components and Operators" on page 248. You can also associate options with sub-expressions that use tags; for details, see "Including Options and Weights in Query Text" on page 252.

If you bind a tag to a geospatial index reference, the value you compare to the tag can be geospatial point or region. Not all the operators listed below are sensible in a geospatial context. For details, see "Binding to a Geospatial Index Reference" on page 258.

Query	Example	Description

tag`:`*value*	`color:red`
	`decade:1980s`
	`birthday:1999-12-31`
		Matches documents where *value* satisfies a word query against the reference bound to *tag*. For example, as with a `cts:element-word-query`.

tag`:(`*valueList*`)`	`color:(red blue)` `decade:(1980s 1990s)`	Matches documents where at least one value in *valueList* satisfies a word query against the reference bound to *tag*. For example, as with a `cts:element-word-query`.

tag `=` *value*	`color = red`
	`decade = 1980s`
	`birthday = 1999-12-31`
		Matches documents where *value* satisfies a value query against the reference bound to *tag.* For example, as with a `cts:element-value-query`.

tag `=` (*valueList*)	`color = (red blue)` `decade = (1980s 1990s)`	Matches documents where at least one value in *valueList* satisfies a value query against the reference bound to *tag*. For example, as with a `cts:element-value-query`.

Query	Example	Description

tag `EQ` *value*	`color EQ red`
	
	`decade EQ 1980s`
	`birthday EQ 1999-12-31`
		Matches documents where *value* satisfies a range query with the "=" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.

tag EQ (*valueList*)	`color EQ (red blue)` `decade EQ (1980s 1990s)`	Matches documents where at least one value in *valueList* satisfies a range query with the "=" operator against the reference bound to *tag*. For example, as with a `cts:element-word-query`.
tag `NE` *value*	`color NE red` `birthday NE 1999-12-31`	Matches documents where *value* satisfies a range query with the "!=" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.
tag `LT` *value*	`color LT red` `birthday LT 1999-12-31`	Matches documents where *value* satisfies a range query with the "<" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.
tag `LE` *value*	`color LE red` `birthday LE 1999-12-31`	Matches documents where *value* satisfies a range query with the "<=" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.
tag `GT` *value*	`color GT red` `birthday GT 1999-12-31`	Matches documents where *value* satisfies a range query with the ">" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.

Query	Example	Description
tag `GE` *value*	`color GE red` `birthday GE 1999-12-31`	Matches documents where *value* satisfies a range query with the ">=" operator against the reference bound to *tag*. For example, as with a `cts:element-range-query`.
query [*opt*,*opt*,...]	`color:(red,blue)[unstemmed]`	Pass options or a weight to the cts query generated for *query*. For details, see "Including Options and Weights in Query Text" on page 252

6.2.2.3 Including Options and Weights in Query Text

Your query text can include query options or a weight that is passed through to the query generated by cts:parse. This is an advanced feature that you would not typically expose directly to end users. To use this feature, put the options or weight in brackets after query term:

```
query[option1, ..., optionN]
```

To specify a weight, use "weight=*N*". See the examples below.

The following table provides some examples of passing options and weights in query text.

Query Text	Generated Query
`cat`	`cts:word-query("cat", ("lang=en"), 1)`
`cat[case-sensitive]`	`cts:word-query(` `  "cat", ("case-sensitive","lang=en"), 1)`
`chat[stemmed,lang=fr]`	`cts:word-query("chat", ("stemmed","lang=fr"), 1)`

`cat AND dog`	`cts:and-query(`
	`  (cts:word-query("cat", ("lang=en"), 1),`
	`  cts:word-query("dog", ("lang=en"), 1)`
	`  ),("unordered"))`

`cat[min-occurs=3] AND`
`  dog[weight=2]`
	`cts:and-query(`
	`  (cts:word-query("cat",`
	`  ("lang=en","min-occurs=3"), 1),`
	`  cts:word-query("dog", ("lang=en"), 2)`
	`  ),("unordered"))`

6.2.3 Binding a Tag to a Reference, Field, or Query Generator

This topic describes how to define parse bindings that enable the use of specially scoped relational and comparison operators in query text passed to the `cts:parse` XQuery function or `cts.parse` Server-Side JavaScript function. You can create bindings to XML elements, XML element attributes, JSON properties, fields, and paths, as well as to custom parsing functions.

The following topics are covered:

- Binding Overview
- Binding to a cts:reference
- Binding to a Field by Simple Name
- Binding to a Geospatial Index Reference
- Binding to an XQuery Query Generator Function
- Binding to a JavaScript Query Generator Function

6.2.3.1 Binding Overview

The `cts:parse` XQuery function and the `cts.parse` JavaScript function accept an optional 2nd parameter that is a set of bindings between a tag and a content reference, field name, or a query generator function. When you use the tag in query text, `cts:parse` (`cts.parse`) uses the binding to generate a query based on the bound reference, field, or function.

In XQuery, bindings are represented by a map with the tag names as the keys. In JavaScript, the bindings are represented by a JavaScript object with the tag names as the object property names. For example, the following code snippet binds the tag “by” to an XML element/JSON property named “author”:

Language	Example

XQuery	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "by", cts:element-reference(xs:QName("author"))`

JavaScript	`var bindings =` `  { by: cts.jsonPropertyReference('author') };`

Given the above binding, you can use "by" in query text to represent the value of the "author" element or property. For example, the following query text parses to a `cts:element-word-query` (or `cts.jsonPropertyWordQuery`) for the phrase "mark twain" in the "author" XML element or JSON property.

```
by:"mark twain"
```

Note: The example above uses an element reference in XQuery and a JSON property reference in JavaScript, but your choice of query language does not limit you to a particular reference type. For example, you can create a binding with `cts:json-property-reference` in XQuery and with `cts.elementReference` in JavaScript.

You can examine the serialized output from `cts:parse` in Query Console to observe the results of using a bound tag in query text. For example, passing the above query text and bindings to `cts:parse` yields the results shown below:

Language	Example

XQuery	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "by", cts:element-reference(xs:QName("author")))`
	`return cts:parse('by:"mark twain"', $bindings)`
	
	`(: emits`
	`: cts:element-word-query(fn:QName("","author"), "mark twain")`
	`:)`

JavaScript	`var bindings =`
	`  { by: cts.jsonPropertyReference('author') };`
	`cts.parse('by:"mark twain"', bindings)`
	
	`// emits`
	`// cts.jsonPropertyWordQuery("author", "mark twain")`

You get this result because the ":" operator signifies comparison as per a word query, and the binding dictates the word query is scoped to a specific JSON property. Thus, the combination of the operator and the bound reference determines the generated query. For details, see "Binding to a cts:reference" on page 255.

The ":", "=", and "EQ" operators also accept a grouping of values, which is handled like an OR. For example, the following query matches documents where the "author" JSON property contains either the word "twain" or the word "frost":

```
by:(twain frost)
```

If you define a binding with an empty string as the tag, the binding applies to unqualified terms like "cat". For details, see "Customizing Naked Term Handling With Bindings" on page 264.

Binding to a simple string is similar, but the bound entity in that case is a field. For details, see "Binding to a Field by Simple Name" on page 257.

For a complete mapping of reference type and operator to query type, refer to the reference documentation for `cts:parse` in the *MarkLogic XQuery and XSLT Function Reference* or `cts.parse` in the *MarkLogic Server-Side JavaScript Function Reference*.

If the default query mapping does not satisfy the requirements of your application, you can bind a tag to a query generator function instead. Binding a tag to a function that generates a cts query gives you more control over the interpretation of a query sub-expression and enables using the following operators in query text: ":", "=", "LT", "LE", "GT", "GE", "EQ", "NE".

The bound function is expected to generate a cts:query (or cts.query) from the operator and operands. For example, you could cause the query text 'by:"mark twain"' to match "mark twain" in the `author` property only when the phrase occurs in documents in a specific collection. For details, see "Binding to an XQuery Query Generator Function" on page 261 or "Binding to a JavaScript Query Generator Function" on page 262.

> **Note:** Function binding is designed to enable you to override the default query selection when a tag is bound to a reference or simple string. It is not a general purpose grammar extender. For example, you cannot define a new operators or change the number of operands expected by an operator.

6.2.3.2 Binding to a cts:reference

You can bind a tag to a cts:reference by using any cts:reference constructor. This enables you to bind a tag to an XML element or element attribute, JSON property, field, or path. Query expressions using the tag can parse to a word query, value query, or range query, depending on the operator context.

For example, the following code binds the tag “cost” to an XML element or JSON property named “price”, then uses the “cost” tag in the query expression “cost LT 15”. The use of the tag with the “LT” operator causes the expression to parse to a range query, so the database configuration should include a range index on “price” with type “float”.

Language	Example

XQuery	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "cost", cts:element-reference(xs:QName("price")))`
	`return cts:parse('cost LT 15', $bindings)`
	
	`(: cts:element-range-query(`
	`  fn:QName("","price"), "<", xs:float("15"), (), 1)`
	`:)`

JavaScript	`var bindings =`
	`  { by: cts.jsonPropertyReference('price') };`
	`cts.parse('cost LT 15', bindings)`
	
	`// cts.jsonPropertyRangeQuery(`
	`//  "price", "<", xs.float("15"), [], 1)`

If you use the binding in a different operator context, the parser generates a different kind of query. For example, the “:” operator generates a word query in most cases, so the query text “cost:15” parses to a `cts:element-word-query` or `cts.jsonPropertyWordQuery`, similar to the following:

```
cts:element-word-query(fn:QName("","price"), "15", ("lang=en"), 1)

cts.jsonPropertyWordQuery("price", "15", ["lang=en"], 1)
```

If you bind a tag to a geospatial index reference, the “:” operator generates a geospatial query. For details, see “Binding to a Geospatial Index Reference” on page 258.

For a complete list of the types of query generated by each operator, refer to `cts:parse` in the *MarkLogic XQuery and XSLT Function Reference* or `cts.parse` in the *MarkLogic Server-Side JavaScript Function Reference*.

By default, the parser checks for the existence of a backing index or lexicon for each cts reference when it processes your bindings. Though it is usually beneficial to have a backing index for a binding, you can suppress the index check if you want to defer index creation or know you will never use the binding in a search context that actually requires an index. For example, range queries always require an index, but a word query does not necessarily require one. If you use an unchecked binding to create a query that requires an index, you will still get an error when you use the query in a search.

To suppress the parse time index check, add the "unchecked" and "type" options when creating the reference. The "type" option is required because the parser can no longer derive this information from the index definition. The following example illustrates the parse time check vs. the search time check:

Language	Example

XQuery	`(: parse time XDMP-ELEMRIDXNOTFOUND if no range index exists:)`
	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "cost", cts:element-reference(xs:QName("price")))`
	`return cts:parse('cost LT 15', $bindings);`
	
	`(: search time XDMP-ELEMRIDXNOTFOUND :)`
	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings, "cost", cts:element-reference(xs:QName("price"),`
	`  **("type=float","unchecked")**))`
	`return cts:search(cts:parse('cost LT 15', $bindings))`

JavaScript	`// parse time XDMP-ELEMRIDXNOTFOUND if no range index exists`
	`cts.parse('cost LT 15', {p: cts.jsonPropertyReference('price')})`
	
	`// Suppress the parse time index check`
	`var query = cts.parse('cost LT 15',`
	`  {cost: cts.jsonPropertyReference(`
	`  'price',**['type=float','unchecked']**)})`
	`// But will still get search time error if no range index found`
	`cts.search(query)  // XDMP-ELEMRIDXNOTFOUND`

6.2.3.3 Binding to a Field by Simple Name

You can bind to a field by name or by cts:reference. This section describes how to bind to field by name. To use a reference constructor, instead, see "Binding to a cts:reference" on page 255.

When you bind a tag to a simple string, the string is interpreted as the name of a field. The database configuration should include a corresponding field definition.

For example, the following binds the tag “name” to a field named “person”:

Language	Example

XQuery	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "name", "person")`
	`return cts:parse('name:"jane doe"', $bindings)`
	
	`(: cts:field-word-query("name", "jane doe", ("lang=en"), 1) :)`

JavaScript	`var bindings = { name: 'person' };`
	`cts.parse('name:"jane doe"', bindings)`
	
	`// cts.fieldWordQuery("name", "jane doe", ["lang=en"], 1)`

When you use the bound tag, it will parse to a `cts:field-word-query`, `cts:field-value-query`, or `cts:field-range-query`, depending on the operator context. If you use the tag name in a context that parses to a range query, you will get an error if the database configuration does not include a corresponding field range index.

To learn more about fields, see Fields Database Settings in the *Administrator's Guide*.

For a complete list of the kinds of query generated by the supported (cts:reference, operator) pairs, refer to cts:parse in the *MarkLogic XQuery and XSLT Function Reference* or cts.parse in the *MarkLogic Server-Side JavaScript Function Reference*.

6.2.3.4 Binding to a Geospatial Index Reference

If you bind a tag (or naked terms) to a cts:reference to a geospatial index, you can construct query terms that represents a geospatial query. For example you can match documents that include a point that is contained within a region defined in the query text, or documents containing a point equal to a point defined in the query text. You can define a point, circle, box, or polygon in the query text.

For example, if you bind the tag “loc” to a geospatial index on an XML element or JSON property, then the following query text matches documents where the indexed element or property contains a point within a circle defined by a radius and a center point, using the syntax “*@radius lon,lat*”:

```
loc:"@5 37.5,-122.4"
```

The following code demonstrates how to define the binding and parse the above query text. In this example, the tag “loc” is bound to a geospatial index on an XML element or JSON property named “incidents”. The resulting query matches documents containing points in the “incidents” element or property contained within the circle with center (37.5,-122.4) and a radius of 5 miles.

Language	Example

XQuery	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put(`
	`  $bindings,`
	`  "loc", cts:geospatial-element-reference(xs:QName("incidents")))`
	`return cts:parse('loc:"@5 37.5,-122.4"', $bindings)`
	
	`(: cts:element-geospatial-query(`
	`:  fn:QName("","incidents"),`
	`:  cts:circle("@5 37.5,-122.4"),`
	`:  ("coordinate-system=wgs84"), 1)`
	`:)`

JavaScript	`cts.parse('loc:"@5 37.5,-122.4"',`
	`  { loc: cts.geospatialJsonPropertyReference('incidents') })`
	
	`// cts.jsonPropertyGeospatialQuery(`
	`//  "incidents",`
	`//  cts.circle("@5 37.5,-122.4"),`
	`//  ["coordinate-system=wgs84"], 1)`

Geospatial search terms can use either the MarkLogic representation of a point or region, or WKT. The following examples of query text represent the same underlying cts query for finding points contained within a polygon. The first uses the MarkLogic serialization of a cts:polygon, and the second uses the WKT representation of the same polygon.

```
"0,0 0,10 10,10 10,0 0,0"

"POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))"
```

For more details about using WKT in MarkLogic, see “Converting To and From Common Geospatial Representations” on page 480.

The following table summarizes the MarkLogic syntax for defining points and regions in query text. This syntax is the serialization of `cts:point`, `cts:circle`, `cts:box`, and `cts:polygon` in XQuery; and of `cts.point`, `cts.circle`, `cts.box`, and `cts.polygon` in JavaScript. For details, see the corresponding region constructors and "Constructing Geospatial Point and Region Values" on page 486.

Geospatial Entity	Pattern	Example
point	`lat,lon`	*tag*:"37.5, -122.4"
circle	`@radius lat,lon`	*tag*:"@5 37.5,-122.4"
box	`[sbound, wbound, nbound, ebound]`	*tag*:"[45, -122, 78, 30]"
polygon	`lat1,lon1 lat2,lon2 ...latN,lonN`	*tag*:"100,0 101,0 101,1 100,1 100,0"

When you use a tag bound to a geospatial index with the ":" operator, the parse function produces a geospatial query. The type of query depends on the type of geospatial reference in the tag binding.

The following list shows the relationship between the reference type and geospatial query in XQuery:

- `cts:geospatial-attribute-pair-reference` generates `cts:element-attribute-pair-geospatial-query`
- `cts:geospatial-element-child-reference` generates `cts:element-child-geospatial-query`
- `cts:geospatial-element-pair-reference` generates `cts:element-pair-geospatial-query`
- `cts:geospatial-json-property-child-reference` generates `cts:json-property-child-geospatial-query`
- `cts:geospatial-json-property-pair-reference` generates `cts:json-property-pair-geospatial-query`
- `cts:geospatial-json-property-reference` generates `cts:json-property-geospatial-query`
- `cts:geospatial-path-reference` generates `cts:path-geospatial-query`

The following list shows the relationship between the reference type and geospatial query in Server-Side JavaScript:

- `cts.geospatialAttributePairReference` generates `cts.elementAttributePairGeospatialQuery`

- `cts.geospatialElementChildReference` generates `cts.elementChildGeospatialQuery`
- `cts.geospatialElementPairReference` generates `cts.elementPairGeospatialQuery`
- `cts.geospatialJsonPropertyChildReference` generates `cts.jsonPropertyChildGeospatialQuery`
- `cts.geospatialJsonPropertyPairReference` generates `cts.jsonPropertyPairGeospatialQuery`
- `cts.geospatialJsonPropertyReference` generates `cts.jsonPropertyGeospatialQuery`
- `cts.geospatialPathReference` generates `cts.pathGeospatialQuery`

For more information on searching geospatial data, see "Geospatial Search Applications" on page 462.

6.2.3.5 Binding to an XQuery Query Generator Function

A query generator function should implement the following interface:

```
function (
  $operator as xs:string,
  $values as xs:string*,
  $options as xs:string*
) as cts:query?
```

If your function does not return a value, the query sub-expression is interpreted as text.

The following example adds a `cts:collection-query` to the search, corresponding to each term in the query text that is qualified by the tag name "cat" (as in "category"). If an unsupported category name is supplied, an error is thrown. If the operator is not ":" or "EQ", no value is returned.

```
xquery version "1.0-ml";

(: The query generator :)
declare function local:scope-to-coll(
  $operator as xs:string,
  $values as xs:string*,
  $options as xs:string*)
as cts:query?
{
  if ($operator = (":", "EQ")) then
    let $known := ("classics", "fiction", "poetry")
    return cts:collection-query(
      for $c in ($values)
      return
        if ($c = $known)
        then $c
        else fn:error(
          xs:QName("ERROR"),
          fn:concat("Unrecognized category: ", $c))
```

```
    )
  else ()       (: unsupported operator :)
};

(: how to use it :)
let $bindings := map:map()
let $_ := map:put($bindings, "cat", local:scope-to-coll#3)
return cts:parse('cat EQ classics california', $bindings)
(: matchs docs in the "classics" collection that contain califorina :)
```

This query generator function produces the following results:

Query Text	Result

`cat:classics`
 	
`cat EQ classics`
	`cts:collection-query("classics")`

`cat:unrecognized`	`None - function reports an error`

`cat LT anything`	`(: interpreted as text :)`
	`cts:and-query((`
	`  (cts:word-query("cat", ("lang=en"), 1),`
	`  cts:word-query("LT", ("lang=en"), 1),`
	`  cts:word-query("anything", ("lang=en"), 1)`
	`  ),("unordered"))`

6.2.3.6 Binding to a JavaScript Query Generator Function

A query generator function should implement the following interface:

```
function (operator, values, options)
```

Where `operator` is a string containing the operator token, and `values` and `options` are either a single value or a (possibly empty) `ValueIterator`.

Your function can return a cts.query, return nothing, or throw an error by calling `fn.error`. If you return nothing, the sub-expression is interpreted as text.

The following example adds a `cts.collectionQuery` to the search, corresponding to each term in the query text that is qualified by the tag name “cat” (as in “category”). If an unsupported category name is supplied, an error is thrown. If the operator is not “:” or “EQ”, no value is returned.

```
function scopeToColl(operator, category, options) {
  if (operator === ':' || operator === 'EQ') {
    // normalize input, which can be one val or an iterator
    var categories =
        (category instanceof ValueIterator)
```

```
          ? category.toArray() : [category];
      var known = ['classics', 'fiction', 'poetry']
      var collections = [];
      categories.forEach(function (c) {
        if (known.indexOf(c) != -1) {
          collections.push(c);
        } else {
          fn.error('ERROR', 'Unrecognized category: ' + c);
        }
      });
      return cts.collectionQuery(collections);
    }
    // else, unsupported operator, so return nothing
  };

  var bindings = { cat: scopeToColl };
  cts.parse('cat:(classics poetry) california', bindings)
```

This query generator function produces the following results:

Query Text	Result

`cat:classics`
 	
`cat EQ classics`
	`cts.collectionQuery('classics')`

`cat:unrecognized`	`None - function reports an error`

`cat LT anything`	`// Function returns nothing, phrase interpreted as text`
	`// by cts.parse`
	`cts.andQuery(`
	`  [cts.wordQuery("cat", ["lang=en"], 1),`
	`   cts.wordQuery("LT", ["lang=en"], 1),`
	`   cts.wordQuery("anything", ["lang=en"], 1)],`
	`  ["unordered"])`

The values in the second parameter may be strings or numbers. If a term in the query text can be represented as a number, then your function receives it as a number. Otherwise, the term is a string.

The following table illustrates the how several variations on query text are interpreted and passed as input to your query generator:

Query Text	Function Parameter Values

`tag LT value`	`operator: 'LT'`
	`values: value`
	`options: an empty ValueIterator`

`tag = (val1 val2)`	`operator: '='`
	`values: ValueIterator over val1 and val2`
	`options: an empty ValueIterator`

`tag:42`	`operator: ':'`
	`values: 42 as a number`
	`options: an empty ValueIterator`

`tag:true`	`operator: ':'`
	`values: 'true' (string, not boolean)`
	`options: an empty ValueIterator`

`tag:value[opt]`	`operator: ':'`
	`values: value`
	`options: 'opt'`

`tag LT value[opt1,opt2=42]`	`operator: 'NE'`
	`values: value`
	`options: a ValueIterator over 'opt1' and 'opt2=42'`

6.2.4 Customizing Naked Term Handling With Bindings

You can use bindings to control the interpretation of terms in query text that are not qualified by a tag (naked terms). For example, in query text such as “cat AND dog”, “cat” and “dog” are naked terms. The default interpretation of this query text is a query that matches the terms “cat” and “dog” anywhere they appear, similar to the following

```
cts:and-query((cts:word-query('cat'), cts:word-query('dog')))
```

If you create a binding with the empty string as the tag, you can customize the handling of terms that have no tag qualifier in the same way you can customize the interpretation of a defined tag. For example, you can configure the parser to scope the terms “cat” and “dog” to a particular XML element or JSON property.

You can bind naked terms to a content reference, field name, or a query generator function, just as when using a tag.

The following examples constrain naked terms to occurrences in an XML element/JSON property named “title”.

Language	Example

XQuery	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ := map:put($bindings, "",`
	`  cts:element-reference(xs:QName("title")))`
	`return cts:parse('cat AND dog', $bindings)`
	
	`(:`
	`  cts:and-query((`
	`  cts:element-word-query(fn:QName("","title"),"cat",("lang=en"),1),`
	`  cts:element-word-query(fn:QName("","title"),"dog",("lang=en"), 1)),`
	`  ("unordered"))`
	`:)`

JavaScript	`cts.parse(`
	`  'cat AND dog',`
	`  {'': cts.jsonPropertyReference('title')}`
	`)`
	
	`// cts.andQuery([`
	`//  cts.jsonPropertyWordQuery("title", "cat", ["lang=en"], 1),`
	`//  cts.jsonPropertyWordQuery("title", "dog", ["lang=en"], 1)`
	`//  ],`
	`//  ["unordered"])`

For more details on using bindings, see “Binding a Tag to a Reference, Field, or Query Generator” on page 253.

6.2.5 Query Text Parsing Examples

This section illustrates the output from the `cts:parse` XQuery function or `cts.parse` JavaScript function various inputs. For examples of queries that include option values, see “Including Options and Weights in Query Text” on page 252.

You can use a query similar to the following in Query Console to explore the parser output on your own. The bindings are only needed for the examples that use the “color” or “loc” tag. To parse some of the query text that uses the bound tags, you need to define an element range index on the “body-color” XML element or “bodyColor” JSON property, and a geospatial element ranage index on an XML element or JSON property named “incidents”.

Query Language	Query Template

XML	`xquery version "1.0-ml";`
	`let $bindings := map:map()`
	`let $_ :=`
	`  map:put($bindings,`
	`  "color", cts:element-reference(xs:QName("body-color")))`
	`return cts:parse(`***`queryText`***`, $bindings)`

JavaScript	`cts.parse(`***`queryText`***`,` `  { color: cts.jsonPropertyReference('bodyColor') })`

The following table contains examples of input query text and the result returned by the parser.

Query Text	cts:parse Output (XQuery)	cts.parse Output (JavaScript)
`cat`	`cts:word-query(` `  "cat", ("lang=en"), 1)`	`cts.wordQuery(` `  "cat", ["lang=en"], 1)`

`cat dog`
 	
`cat AND dog`
	`cts:and-query((`
	`  cts:word-query(`
	`  "cat", ("lang=en"), 1),`
	`  cts:word-query(`
	`  "dog", ("lang=en"), 1)`
	`  ), ("unordered"))`
		`cts.andQuery([`
		`  cts.wordQuery(`
		`  "cat", ["lang=en"], 1),`
		`  cts.wordQuery(`
		`  "dog", ["lang=en"], 1)`
		`  ], ["unordered"])`

`cat dog OR mouse`	`cts:or-query((`
	`  cts:and-query((`
	`  cts:word-query(`
	`  "cat",("lang=en"),1),`
	`  cts:word-query(`
	`  "dog",("lang=en"), 1)`
	`  ), ("unordered")),`
	`  cts:word-query(`
	`  "mouse",("lang=en"),1)`
	`  ), ())`
		`cts.orQuery([`
		`  cts.andQuery([`
		`  cts.wordQuery(`
		`  "cat",["lang=en"],1),`
		`  cts.wordQuery(`
		`  "dog", ["lang=en"],1)`
		`  ], ["unordered"]),`
		`  cts.wordQuery(`
		`  "mouse", ["lang=en"],1)`
		`  ], [])`

Query Text	cts:parse Output (XQuery)	cts.parse Output (JavaScript)
`cat (dog OR mouse)`	`cts:and-query(( cts:word-query( "cat", ("lang=en"), 1), cts:or-query(( cts:word-query( "dog",("lang=en"),1), cts:word-query( "mouse",("lang=en"), 1) ), ()) ), ("unordered"))`	`cts.andQuery([ cts.wordQuery( "cat", ["lang=en"], 1), cts.orQuery([ cts.wordQuery( "dog",["lang=en"],1), cts.wordQuery( "mouse",["lang=en"],1) ], []) ], ["unordered"])`
`cat -dog`	`cts:and-query(( cts:word-query( "cat", ("lang=en"), 1), cts:not-query( cts:word-query( "dog", ("lang=en"), 1), 1) ), ("unordered"))`	`cts.andQuery([ cts.wordQuery( "cat", ["lang=en"], 1), cts.notQuery( cts.wordQuery( "dog", ["lang=en"],1), 1) ], ["unordered"])`
`color:red`	`cts:element-word-query( fn:QName("","body-color"), "red", ("lang=en"), 1)`	`cts.jsonPropertyWordQuery( "bodyColor", "red", ["lang=en"], 1)`
`color = red`	`cts:element-value-query( fn:QName("","body-color"), "red", ("lang=en"), 1)`	`cts.jsonPropertyValueQuery( "bodyColor", "red", ["lang=en"], 1)`
`color EQ red`	`cts:element-range-query( fn:QName("","body-color"), "=", "red", ("collation=..."), 1)`	`cts.jsonPropertyRangeQuery( "bodyColor", "=", "red", ["collation=..."], 1)`
`color:(red blue)`	`cts:element-word-query( fn:QName("","body-color"), ("red", "blue"), ("lang=en"), 1)` Matches if body-color contains either red or blue.	`cts.jsonPropertyWordQuery( "color", ["red", "blue"], ["lang=en"], 1)` Matches if bodyColor contains either red or blue.

Query Text	cts:parse Output (XQuery)	cts.parse Output (JavaScript)
`loc:"100.0,1.0"`	`cts:element-geospatial-query( fn:QName("","incidents"), cts:point("100,1"), ("coordinate-system=wgs84"), 1)`	`cts.jsonPropertyGeospatialQuery( "incidents", cts.point("100,1"), ["coordinate-system=wgs84"], 1)`
`loc:"[10,20,30,40]"`	`cts:element-geospatial-query( fn:QName("","incidents"), cts:box("[10, 20, 30, 40]"), ("coordinate-system=wgs84", 1)`	`cts.jsonPropertyGeospatialQuery( "incidents", cts.box("[10,20,30,40]"), ["coordinate-system=wgs84", 1)`

6.3 Combining multiple cts:query Expressions

Because `cts:query` expressions are composable, you can combine multiple expressions to form a single expression. There is no limit to how complex you can make a `cts:query` expressions. Any API that has a return type of `cts:*` (for example, `cts:query`, `cts:and-query`, and so on) can be composed with another `cts:query` expression to form another expression. This section has the following parts:

- Using cts:and-query and cts:or-query
- Proximity Queries using cts:near-query
- Using Bounded cts:query Expressions
- Matching Nothing and Matching Everything

6.3.1 Using cts:and-query and cts:or-query

You can construct arbitrarily complex boolean logic by combining `cts:and-query` and `cts:or-query` constructors in a single `cts:query` expression.

For example, the following search with a relatively simple nested `cts:query` expression will return all fragments that contain either the word `alfa` or the word `maserati`, and also contain either the word `saab` or the word `volvo`.

```
cts:search(fn:doc(),
  cts:and-query( ( cts:or-query(("alfa", "maserati")),
                   cts:or-query(("saab", "volvo") )
  ) )
)
```

Additionally, you can use `cts:and-not-query` and `cts:not-query` to add negation to your boolean logic.

6.3.2 Proximity Queries using cts:near-query

You can add tests for proximity to a `cts:query` expression using `cts:near-query`. Proximity queries use the `word positions` index in the database and, if you are using `cts:element-query`, the `element word positions` index. Proximity queries will still work without these indexes, but the indexes will speed performance of queries that use `cts:near-query`.

Proximity queries return `true` if the query matches occur within the specified distance from each other. For more details, see the *MarkLogic XQuery and XSLT Function Reference* for `cts:near-query`.

6.3.3 Using Bounded cts:query Expressions

The following `cts:query` constructors allow you to bound a `cts:query` expression to one or more documents, a directory, or one or more collections.

- `cts:document-query`
- `cts:directory-query`
- `cts:collection-query`

These bounding constructors allow you to narrow a set of search results as part of the second parameter to `cts:search`. Bounding the query in the `cts:query` expression is much more efficient than filtering results in a `where` clause, and is often more convenient than modifying the XPath in the first `cts:search` parameter. To combine a bounded `cts:query` constructor with another constructor, use a `cts:and-query` or a `cts:or-query` constructor.

For example, the following constrains a search to a particular directory, returning the URI of the document(s) that match the `cts:query`.

```
for $x in cts:search(fn:doc(),
   cts:and-query((
     cts:directory-query("/shakespeare/plays/", "infinity"),
         "all's well that"))
)
return xdmp:node-uri($x)
```

This query returns the URI of all documents under the specified directory that satisfy the query `"all's well that"`.

> **Note:** In this query, the query `"all's well that"` is equivalent to a `cts:word-query("all's well that")`.

6.3.4 Matching Nothing and Matching Everything

An empty `cts:word-query` will always match no fragments, and an empty `cts:and-query` will always match all fragments. Therefore the following are true:

```
cts:search(fn:doc(), cts:word-query("") )
=> returns the empty sequence

cts:search(fn:doc(), "" )
=> returns the empty sequence

cts:search(fn:doc(), cts:and-query( () ) )
=> returns every fragment in the database
```

You can also use cts:true-query and cts:false-query to match everything or nothing. For example:

```
cts:search(fn:doc(), cts:false-query())
==> returns the empty sequence

cts:search(fn:doc(), cts:true-query())
==> returns every fragment in the database
```

One use for an empty `cts:word-query` is when you have a search box that an end user enters terms to search for. If the user enters nothing and hits the submit button, then the corresponding cts:search will return no hits.

An empty `cts:and-query` or a `cts-true-query` that matches everything is sometimes useful when you need a `cts:query` to match everything.

6.4 Joining Documents and Properties with cts:properties-query or cts:document-fragment-query

You can use a `cts:properties-query` to match content in properties document. If you are searching over a document, then a `cts:properties-query` will search in the properties document at the URI of the document. The `cts:properties-query` joins the properties document with its corresponding document. The `cts:properties-query` takes a `cts:query` as a parameter, and that query is used to match against the properties document. A `cts:properties-query` is composable, so you can combine it with other `cts:query` constructors to create arbitrarily complex queries.

Using a `cts:properties-query` in a `cts:search`, you can easily create a query that returns results that join content in a document with content in the corresponding properties document. For example, consider a document that represents a chapter in a book, and the document has properties containing the publisher of the book. you can then write a search that returns documents that match a cts:query where the document has a specific publisher, as in the following example:

```
cts:search(collection(), cts:and-query((
  cts:properties-query(
```

```
      cts:element-value-query(xs:QName("publisher"), "My Press") ),
    cts:word-query("a small good thing") )) )
```

This query returns all documents with the phrase `a small good thing` and that have a value of `My Press` in the `publisher` element in their corresponding properties document.

Similarly, you can use `cts:document-fragment-query` to join documents against properties when searching over properties.

6.5 Registering cts:query Expressions to Speed Search Performance

If you use the same complex `cts:query` expressions repeatedly, and if you are using them as an *unfiltered* `cts:query` constructor, you can register the `cts:query` expressions for later use. Registering a `cts:query` expression stores a pre-evaluated version of the expression, making it faster for subsequent queries to use the same expression. Unfiltered constructors return results directly from the indexes and return all candidate fragments for a search, but do not perform post-filtering to validate that each fragment perfectly meets the search criteria. For details on unfiltered searches, see "Using Unfiltered Searches for Fast Pagination" in the *Query Performance and Tuning Guide*.

This section describes registered queries and provides some examples of how to use them. It includes the following topics:

- Registered Query APIs
- Must Be Used Unfiltered
- Registration Does Not Survive System Restart
- Storing Registered Query IDs
- Registered Queries and Relevance Calculations
- Example: Registering and Using a cts:query Expression

6.5.1 Registered Query APIs

To register and reuse unfiltered searches for `cts:query` expressions, use the following XQuery APIs:

- `cts:register`
- `cts:registered-query`
- `cts:deregister`

For the syntax of these functions, see the *MarkLogic XQuery and XSLT Function Reference*.

6.5.2 Must Be Used Unfiltered

You can only use registered queries on unfiltered constructors; using a registered query as a filtered constructor throws the `XDMP-REGFLT` exception. To specify an unfiltered constructor, use the `"unfiltered"` option to `cts:registered-query`. For details about unfiltered searches, see "Using Unfiltered Searches for Fast Pagination" in the *Query Performance and Tuning Guide*.

6.5.3 Registration Does Not Survive System Restart

Registered queries are only stored in the memory cache, and if the cache grows too big, some registered queries might be aged out of the cache. Also, if MarkLogic Server stops or restarts, any queries that were registered are lost and must be re-registered.

If you attempt to call `cts:registered-query` in a `cts:search` and the query is not currently registered, it throws an `XDMP-UNREGISTERED` exception. Because registered queries are not guaranteed to be registered every time they are used, it is good practice to use a `try/catch` around calls to `cts:registered-query`, and re-register the query in the `catch` if the it throws an `XDMP-UNREGISTERED` exception.

For example, the following sample code shows a `cts:registered-query` call used with a try/catch expression in XQuery:

```
(: wrap the registered query in a try/catch :)
try{
xdmp:estimate(cts:search(fn:doc(),
  cts:registered-query(995175721241192518, "unfiltered")))
}
catch ($e)
{
let $registered := 'cts:register(
cts:word-query("hello*world", "wildcarded"))'
return
if ( fn:contains($e/*:code/text(), "XDMP-UNREGISTERED") )
then ( "retry this query with the following registered query ID: ",
       xdmp:eval($registered) )
else ( $e )
}
```

This code is somewhat simplified: it catches the `XDMP-UNREGISTERED` exception and simply reports what the new registered query ID is. In an application that uses registered queries, you probably would want to re-run the query with the new registered ID. Also, this example performs the `try/catch` in XQuery. If you are using XCC to issue queries against MarkLogic Server, you can instead perform the `try/catch` in the middleware Java or .NET layer.

6.5.4 Storing Registered Query IDs

When you register a `cts:query` expression, the `cts:register` function returns an integer, which is the ID for the registered query. After the `cts:register` call returns, there is no way to query the system to find the registered query IDs. Therefore, you might need to store the IDs somewhere. You can either store them in the middleware layer (if you are using XCC to issue queries against MarkLogic Server) or you can store them in a document in MarkLogic Server.

The registered query ID is generated based on a hash of the actual query, so registering the same query multiple times results in the same ID. The registered query ID is valid for all queries against the database across the entire cluster.

6.5.5 Registered Queries and Relevance Calculations

Searches that use registered queries will generate results having different scores from the equivalent searches using a non-registered queries. This is because registered queries are treated as a single term in the relevance calculation. For details on relevance calculations, see "Relevance Scores: Understanding and Customizing" on page 408.

6.5.6 Example: Registering and Using a cts:query Expression

To run a registered query, you first register the query and then run the registered query, specifying it by ID. This section describes some example steps for registering a query and then running the registered query.

1. First register the `cts:query` expression you want to run, as in the following example:

```
cts:register(cts:word-query("hello*world", "wildcarded"))
```

2. The first step returns an integer. Keep track of the integer value (for example, store it in a document).

3. Use the integer value to run a search with the registered query (with the `"unfiltered"` option) as follows:

```
cts:search(fn:doc(),
          cts:registered-query(987654321012345678, "unfiltered") )
```

6.6 Adding Relevance Information to cts:query Expressions:

The leaf-level `cts:query` APIs (`cts:word-query`, `cts:element-word-query`, and so on) have a weight parameter, which allows you to add a multiplication factor to the scores produced by matches from a query. You can use this to increase or decrease the weight factor for a particular query. For details about score, weight, and relevance calculations, see "Relevance Scores: Understanding and Customizing" on page 408.

6.7 XML Serializations of cts:query Constructors

You can create an XML serialization of a `cts:query`. The XML serialization is used by alerting applications that use a `cts:reverse-query` constructor and is also useful to perform various programmatic tasks to a `cts:query`. Alerting applications (see "Creating Alerting Applications" on page 491) find queries that would match nodes, and then perform some action for the query matches. This section describes the serialized XML and includes the following parts:

- Serializing a cts:query to XML
- Function to Construct a cts:query From XML

6.7.1 Serializing a cts:query to XML

A serialized `cts:query` has XML that conforms to the `<marklogic-dir>/Config/cts.xsd` schema, which is in the `http://marklogic.com/cts` namespace, which is bound to the `cts` prefix. You can either construct the XML directly or, if you use any `cts:query` expression within the context of an element, MarkLogic Server will automatically serialize that `cts:query` to XML. Consider the following example:

```
<some-element>{cts:word-query("hello world")}</some-element>
```

When you run the above expression, it serializes to the following XML:

```
<some-element>
  <cts:word-query xmlns:cts="http://marklogic.com/cts">
    <cts:text xml:lang="en">hello world</cts:text>
  </cts:word-query>
</some-element>
```

If you are using an alerting application, you might choose to store this XML in the database so you can match searches that include `cts:reverse-query` constructors. For details on alerts, see "Creating Alerting Applications" on page 491.

6.7.2 Add Arbitrary Annotations With cts:annotation

You can annotate your `cts:query` XML with `cts:annotation` elements. A `cts:annotation` element can be a child of any element in the `cts:query` XML, and it can consist of any valid XML content (for example, a single text node, a single element, multiple elements, complex elements, and so on). MarkLogic Server ignores these annotations when processing the query XML, but such annotations are often useful to the application. For example, you can store information about where the query came from, information about parts of the query to use or not in certain parts of the application, and so on. The following is some sample XML with `cts:annotation` elements:

```
<cts:and-query xmlns:cts="http://marklogic.com/cts">
  <cts:directory-query>
    <cts:annotation>private</cts:annotation>
    <cts:uri>/myprivate-dir/</cts:uri>
  </cts:directory-query>
  <cts:and-query>
    <cts:word-query><cts:text>hello</cts:text></cts:word-query>
    <cts:word-query><cts:text>world</cts:text></cts:word-query>
  </cts:and-query>
  <cts:annotation>
    <useful>something useful to the application here</useful>
  </cts:annotation>
</cts:and-query>
```

For another example that uses `cts:annotation` to store the original query string in a function that generates a `cts:query` from a string, see the last part of the example in "XML Serializations of cts:query Constructors" on page 274.

6.7.3 Function to Construct a cts:query From XML

You can turn an XML serialization of a cts:query back into an un-serialized cts:query with the `cts:query` function. For example, you can turn a serialized `cts:query` back into a `cts:query` as follows:

```
cts:query(
  <cts:word-query xmlns:cts="http://marklogic.com/cts">
    <cts:text>word</cts:text>
  </cts:word-query>
)
(: returns: cts:word-query("word", ("lang=en"), 1) :)
```

6.8 Example: Creating a cts:query Parser

The following sample code shows a simple query string parser that parses double-quote marks to be a phrase, and considers anything else that is separated by one or more spaces to be a single term. If needed, you can use the same design pattern to add other logic to do more complex parsing (for example, OR processing or NOT processing).

```
xquery version "1.0-ml";
declare function local:get-query-tokens($input as xs:string?)
  as element() {
(: This parses double-quotes to be exact matches. :)
<tokens>{
let $newInput := fn:string-join(
(: check if there is more than one double-quotation mark.  If there is,
   tokenize on the double-quotation mark ("), then change the spaces
   in the even tokens to the string "!+!".  This will then allow later
   tokenization on spaces, so you can preserve quoted phrases as phrase
   searches (after re-replacing the "!+!" strings with spaces).  :)
    if ( fn:count(fn:tokenize($input, '"')) > 2 )
```

```
    then ( for $i at $count in fn:tokenize($input, '"')
           return
             if ($count mod 2 = 0)
             then fn:replace($i, "\s+", "!+!")
             else $i )
    else ( $input ) , " ")
let $tokenInput := fn:tokenize($newInput, "\s+")

return (
for $x in $tokenInput
where $x ne ""
return
<token>{fn:replace($x, "!\+!", " ")}</token>)
}</tokens>
} ;

let $input := 'this is a "really big" test'
return
local:get-query-tokens($input)
```

This returns the following:

```
<tokens>
  <token>this</token>
  <token>is</token>
  <token>a</token>
  <token>really big</token>
  <token>test</token>
</tokens>
```

Now you can derive a `cts:query` expression from the tokenized XML produced above, which composes all of the terms with a `cts:and-query`, as follows (assuming the `local:get-query-tokens` function above is available to this function):

```
xquery version "1.0-ml";
declare function local:get-query($input as xs:string)
{
let $tokens := local:get-query-tokens($input)
return
 cts:and-query( (cts:and-query(
        for $token in $tokens//token
        return
        cts:word-query($token/text()) ) ))
} ;

let $input := 'this is a "really big" test'
return
local:get-query($input)
```

This returns the following (spacing and line breaks added for readability):

```
cts:and-query(
  cts:and-query((
    cts:word-query("this", (), 1),
    cts:word-query("is", (), 1),
    cts:word-query("a", (), 1),
    cts:word-query("really big", (), 1),
    cts:word-query("test", (), 1)
    ), ()) ,
  () )
```

You can now take the generated `cts:query` expression and add it to a `cts:search`.

Similarly, you can generate a serialized `cts:query` as follows (assuming the `local:get-query-tokens` function is available):

```
xquery version "1.0-ml";
declare function local:get-query-xml($input as xs:string)
{
let $tokens := local:get-query-tokens($input)
return
 element cts:and-query {
       element cts:and-query {
           for $token in $tokens//token
           return
           element cts:word-query { $token/text() } },
           element cts:annotation {$input} }
} ;

let $input := 'this is a "really big" test'
return
local:get-query-xml($input)
```

This returns the folllowing XML serialization:

```
<cts:and-query xmlns:cts="http://marklogic.com/cts">
  <cts:and-query>
    <cts:word-query>this</cts:word-query>
    <cts:word-query>is</cts:word-query>
    <cts:word-query>a</cts:word-query>
    <cts:word-query>really big</cts:word-query>
    <cts:word-query>test</cts:word-query>
  </cts:and-query>
  <cts:annotation>this is a "really big" test</cts:annotation>
</cts:and-query>
```

7.0 Creating JavaScript Search Applications

This chapter describes how to add search operations and lexicon analysis to your Server-Side JavaScript modules and extensions using the JSearch library module. This chapter includes the following sections:

- JSearch Introduction
- Searching Documents
- Scoping Operations by Collection
- Creating a cts.query
- Including Facets in Search Results
- Controlling the Ordering of Results
- Returning a Result Subset
- Including Snippets of Matching Content in Search Results
- Extracting Portions of Each Matched Document
- Using Options to Control a Query
- Transforming Results with Map and Reduce
- Querying Lexicons and Range Indexes
- Grouping Values and Facets Into Buckets
- Preparing to Run the Examples

This chapter provides background, design patterns, and examples of the JSearch library module. For the function signatures and descriptions, see the JSearch documentation under JavaScript Library Modules in the *MarkLogic Server-Side JavaScript Function Reference*.

You can also use the Node.js Client API to integrate search operations and lexicon analysis into your client-side code. For details, see the *Node.js Application Developer's Guide*.

7.1 JSearch Introduction

This section provides a high level overview of the features and design patterns of the JSearch library. This section covers the following topics:

- JSearch Feature Summary
- Top Level Function Summary
- Query Design Pattern
- How JSearch Relates to Other MarkLogic Search APIs

- Running the Examples in This Chapter

7.1.1 JSearch Feature Summary

You can use the JSearch library to perform most of the query operations available through the cts built-in functions and the Search API, including the following:

- Search document contents and document properties using Query By Example (QBE), query text parsable by `cts:parse`, and cts queries.
    - Include documents, snippets, and/or facets in your search results.
    - Apply content transformations to search results.
    - Return results in configurable slices.
- Generate facets for an arbitrary set of documents in the database.
- Query lexicons and range indexes.
    - Find lexicon and range index values and tuples (value co-occurrences).
    - Compute aggregates over lexicon and range index values and tuples.

7.1.2 Top Level Function Summary

The following table provides an overview of the key top level JSearch methods. All these methods are effectively query builders. You can chain additional methods to them to refine and produce results. For details, see “Query Design Pattern” on page 280.

The API also includes helper functions, not listed here, for constructing complex inputs such as lexicon references, facet definitions, and heatmap definitions.

For a complete list of functions, see `jsearch` in the *MarkLogic Server-Side JavaScript Function Reference*.

JSearch Method	Description
`collections`	Creates a `jsearch` object that implicitly scopes all operations to one or more collections. For details, see “Scoping Operations by Collection” on page 284.
`documents`	Search documents and document properties. You can tailor the results to include data such as matching documents, document projections, and snippets, as well as search metadata such as relevance score. For details, see “Document Search Basics” on page 285.

JSearch Method	Description
`values`	Query the values in a lexicon or range index, optionally computing one or more aggregates over the values. For details, see "Querying the Values in a Lexicon or Index" on page 341.
`tuples`	Find n-way value co-occurrences in lexicons and range indexes, optionally computing one or more aggregates over the tuples. For details, see "Finding Value Co-Occurrences in Lexicons and Indexes" on page 344.
`words`	Query the values in a word lexicon. For details, see "Querying Values in a Word Lexicon" on page 346.
`facets`	Generate facets from a value lexicon. The results can optionally include documents as well as facets. For details, see "Including Facets in Search Results" on page 296.
`documentSelect`	Generate snippets, sparse document projections, and/or a set of similar documents from an arbitrary set of documents, such as the result of calling `cts.search` or `fn.doc`.

7.1.3 Query Design Pattern

The top level JSearch operations, such as document search, lexicon value queries, and lexicon tuple queries use a pipeline pattern for defining the query and customizing results. The pipeline mirrors steps MarkLogic performs when evaluating a query. The pipeline stages vary by operation, but can include steps such as query criteria definition, result ordering, and result transformations.

Building and evaluating a query consists of the following steps:

1. Select the resource you want to work with, such as documents, lexicon values, or tuples.

2. Add the pipeline stages that define your query and desired result set, such as query criteria, sort order, and transformations. All pipeline stages are optional.

3. Optionally, specify advanced options, such as a quality weight. The available options depend on the resource selected in Step 1.

4. Perform the operation and get results.

If you omit all the pipeline stages in Step 2, then you retrieve the default slice from all selected resources. For example, all the documents in the database or all values or tuples in the selected lexicon(s).

Consider the case of a document search. The following example (1) selects documents as the resource; (2) defines the query and customizes the result using the `where`, `orderBy`, `slice`, and `map` pipeline stages; (3) specifies the `returnQueryPlan` option using the `withOptions` method; and then (4) evaluates the assembled query and gets results.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()                       // 1. resource selection
  .where(cts.parse('title:california',    // 2. query defn pipeline
          {title: cts.jsonPropertyReference('title')}))
  .orderBy('price')                       //     .
  .slice(0,5)                             //     .
  .map({snippet: true})                   //     .
  .withOptions({returnQueryPlan: true})   // 3. additional options
  .result()                               // 4. query evaluation
```

The query definition pipeline in this example uses the following stages:

Stage	Description
`where(...)`	Define the query criteria: Match documents with “california” in the `title` JSON property (or XML element).
`orderBy('price')`	Define the ordering of results: Order the results by the values in the `price` property.
`slice(0,5)`	Define a result subset: Limit the results to the first 5 matches.
`map({snippet: true})`	Define a mapping operation to apply to each result: Use the built-in mapper to generate snippets.

For comparsion, below is a JSearch values query. Observe that it follows the same pattern. In this case, the selected resource is the values in a range index on the `price` JSON property or XML element.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')                   // 1. resource selection
  .where(cts.parse('by:"mark twain"',     // 2. query defn pipeline
           {by: cts.jsonPropertyReference('author')}))
  .orderBy('item','descending')           //     .
  .slice(0,20)                            //     .
  .withOptions({qualityWeight: 2})        // 3. additional options
  .result()                               // 4. query evaluation
```

The query definition pipeline in this values query example uses the following stages:

Stage	Description
`where(...)`	Define the query criteria: Limit the results to the values in documents where the `author` property or element value is "mark twain".

`orderBy(`
`  'item',`
`  'descending')`
	Define the ordering of results: Return the values in descending item order.

`slice(0,20)`	Define a result subset: Return the first 20 values.

The query definition pipeline is realized through a call chain, as shown in the examples. All pipeline stages are optional, but the order is fixed. The table below summarizes the pipeline stages available for querying each resource type. The stage names are also JSearch method names. Note that two pipelines are available for values and tuples queries: one for retrieving values or tuples from lexicons and another for computing aggregates over the values or tuples.

Selected Resource	Query Definition Pipeline
Documents	`where > orderBy > filter > slice > (map or reduce)`

Values	`where > (match or groupInto) > orderBy > slice > (map or reduce)`
	
	`where > aggregate`

Tuples	`where > orderBy > slice > (map or reduce)`
	
	`where > aggregate`

Results can be returned as values (typically, an array) or as an iterator. The default is values. For example, the default output from a document search has the following form:

```
{ results: [resultItems], estimate: totalEstimatedMatches }
```

However, if you request an iterator by passing `'iterator'` to the result method, then you get the following:

```
{ results: iteratorOverResultItems, estimate: totalEstimatedMatches }
```

When you request iterable results by calling `results('iterator')` on the various JSearch APIs, you receive a `ValueIterator` in some contexts and a `Generator` in others. For more information on these constructs, see ValueIterator in the *JavaScript Reference Guide* and the definition of Generator in the JavaScript standard:

http://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Generator

7.1.4 How JSearch Relates to Other MarkLogic Search APIs

The JSearch library module is primarily designed for JavaScript developers writing MarkLogic applications that initiate document searches and lexicon queries on the server. The same capabilities are available through other server-side interfaces, such as the `cts` built-in functions and the Search API, but JSearch offers the following advantages for a JavaScript developer:

- All input and output is in the form of JavaScript objects.
- A fluent call chain pattern that is natural for JavaScript.
- Powerful convenience methods for operations such as snippet generation and faceting.

In addition, the design patterns, query styles, and configuration options are similar to those used by the Node.js Client API. Thus, developers creating multi-tier JavaScript applications will find it easy to move between client (or middle) and server tiers when using JSearch. To learn more about the Node.js Client API, see the *Node.js Application Developer's Guide*.

You can use the JSearch API in conjunction with the `cts` built-in functions, in many contexts. For example:

- You can use the `cts` query constructors to create input queries usable with a JSearch-based document search. For details, see "Using cts.query Constructors" on page 296.
- You can construct index references for a JSearch values query using the `cts.reference` constructors.
- You can use the `jsearch.documentSelect` method to generate snippets or sparse document projections from the results returned by `cts.search`.
- Many JSearch operations enable you to pass advanced options to the underlying cts layer through the `withOptions` method. For details, see "Using Options to Control a Query" on page 330.

7.1.5 Running the Examples in This Chapter

All the examples in this chapter can be run using Query Console. To configure the sample database and load the sample documents, see the instructions in "Preparing to Run the Examples" on page 362.

For more information about Query Console, see the *Query Console User Guide* or the Query Console help.

7.2 Scoping Operations by Collection

If your application primarily works with documents in one or more collections, you can use the `collections` method to create a top level `jsearch` object that implicitly limits operations by collection.

For example, suppose your application is operating on documents in a collection with the URI "classics". Including a `cts.collectionQuery('classics')` in all your query operations can be inconvenient. Instead, use the `collections` method to create a scoped search object through which you can perform all JSearch operations, as shown below:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var classics = jsearch.collections('classics');

// implicitly limit results to matches in the 'classics' collection
classics.documents()
  .where(cts.parse('california'))
  .result()
```

You can use the resulting object everywhere you can use the object returned by the `require` that brings the JSearch library into scope.

You can scope to one or many collections. When you specify multiple collections, the implicit collection query matches documents in any of the collections. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');

// Work with documents in either the "novels" or "poems" collection
var books = jsearch.collections(['novels','poems']);
```

The collection scope is ignored on operations for which it makes no sense, such as when constructing a lexicon reference using a helper function like `jsearch.elementLexicon`. On operations where scope matters, such as `documents`, `values`, and `words`, the implicit `cts.collectionQuery` is added to a top-level `cts.andQuery` on every `where` clause.

For more details, see `jsearch.collections`.

7.3 Searching Documents

To perform a document search, use the `jsearch.documents` method and the design pattern described in "Query Design Pattern" on page 280.

- Document Search Basics
- Example: Basic Document Search

7.3.1 Document Search Basics

This section outlines how to perform a document search. The search features touched on here are discussed in more detail in the remainder of this chapter.

Bring the JSearch library module functions into scope by including a `require` statement similar to the following in your code. (You can use any variable name.)

```
var jsearch = require('/MarkLogic/jsearch.sjs');
```

A document search begins by selecting documents as the resource you want to work with by calling the top level `documents` method. You can invoke this method either on the object created by the require statement, or on a collection-scoped instantiation.

```
// Work with all documents
jsearch.documents().where(cts.parse('cat')).result() ...

// Work with documents in collections 'coll1' and 'coll2'
var myColls = jsearch.collections([coll1,coll2]);
myColls.documents().where(cts.parse('cat')).result() ...
```

To learn more about working with collections, see “Scoping Operations by Collection” on page 284

Build and execute your search following the pattern described in “Query Design Pattern” on page 280. The following table maps the applicable JSearch methods to the steps in the design pattern. Note that all the pipeline stages in Step 2 are optional, but you must use them in the order shown. For an example, see “Example: Basic Document Search” on page 287.

Pattern Step		Method(s)	Notes
1	Select resource	`documents`	Required. Select documents as the resource to work with. For details, see `jsearch.documents` in the *MarkLogic Server-Side JavaScript Function Reference*.

Pattern Step		Method(s)	Notes
2	Add a query definition and result set pipeline	`where`	Optional. Define your query. Accepts one or more cts.query objects as input. If you pass in more than one `cts.query` object, the queries are implicitly AND'd together. You can create a cts.query from a QBE, query text, cts.query constructors, or any other technique that creates a `cts.query`. For details, see "Creating a cts.query" on page 289 and `DocumentsSearch.where` in the *MarkLogic Server-Side JavaScript Function Reference*.
		`orderBy`	Optional. Specify sort keys and/or sorting direction. For details, see "Controlling the Ordering of Results" on page 316 and `DocumentsSearch.orderBy` in the *MarkLogic Server-Side JavaScript Function Reference*.
		`filter`	Optional. Specify whether or not to filter the search. By default, the search is unfiltered. Filtered search is always accurate, but can take longer. For details, see `DocumentsSearch.filter` and Fast Pagination and Unfiltered Searches in the *Query Performance and Tuning Guide*.
		`slice`	Optional. Select a subset of documents from the result set. The default slice is the first 10 documents. Retrieving results incrementally is best practice for most applications.For details, see "Returning a Result Subset" on page 319 and `DocumentsSearch.slice` in the *MarkLogic Server-Side JavaScript Function Reference*.
		`map | reduce`	Optional. Configure snippeting, extraction of specific pieces of matched documents, or custom transformations. You cannot use `map` and `reduce` together. For details, see "Transforming Results with Map and Reduce" on page 331, `DocumentsSearch.map`, and `DocumentsSearch.reduce`.

Pattern Step		Method(s)	Notes
3	Add advanced options	`withOptions`	Optional. Specify additional, advanced search options that customize the search behavior. For details, see "Using Options to Control a Query" on page 330 and `DocumentsSearch.withOptions` in the *MarkLogic Server-Side JavaScript Function Reference*.
4	Evaluate the query and get results	`result`	Required. Execute the search and receive your results, optionally specifying whether to receive the results as a value or an iterator. The default is a value (typically an array).

7.3.2 Example: Basic Document Search

The following is the most minimal JSearch document search, but it has the broadest scope in that it returns the default slice of all documents in the database.

```
jsearch.documents().result()
```

More typically, your search will include at least a `where` "clause" that defines the desired set of results. The `where` method accepts one or more cts.query objects as input and defines your search criteria. For example, the following query matches documents where the `author` property has the value "Mark Twain":

```
jsearch.documents()
  .where(jsearch.byExample({author: 'Mark Twain'}))
  .result()
```

You can customize the results by adding `orderBy`, `slice`, `map`, and `reduce` stages to the operation. For example, you can suppress the search metadata, include snippets instead of (or in addition to) the full documents, extract just a portion of each matching document, or apply a custom content transformation. These and other features are covered elsewhere in this chapter.

The following example matches documents that contain an `author` JSON property with the value "Mark Twain", `price` property with a value less than10, and that are in the `/books/` directory. Notice that the search criteria are expressed in several ways; for details, see "Creating a cts.query" on page 289. The search results contain at most the first 3 matching documents (`slice`), ordered by the value of the `title` property (`orderBy`).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where([
    jsearch.byExample({author: 'Mark Twain'}),
    cts.parse('price LT 10',
              {price: cts.jsonPropertyReference('price')}),
```

```
      cts.directoryQuery('/books/')])
  .orderBy('title')
  .slice(0,3)
  .result()
```

This query produces output similar to the following when run against the documents and database configuration described in “Preparing to Run the Examples” on page 362.

```
{ "results": [
    { "index": 0,
      "uri": "/books/twain3.json",
      "score": 16384,
      "confidence": 0.43934014439583,
      "fitness": 0.69645345211029,
      "document": {
        "title": "Adventures of Huckleberry Finn",
        "author": "Mark Twain",
        "edition": {
          "format": "paperback",
          "price": 8
        },
        "synopsis": "The adventures of Huck, a boy ..."
      }
    },
    { "index": 1,
      "uri": "/books/twain1.json",
      "score": 16384,
      "confidence": 0.43934014439583,
      "fitness": 0.69645345211029,
      "document": {
        "title": "Adventures of Tom Sawyer",
        "author": "Mark Twain",
        "edition": {
          "format": "paperback",
          "price": 9
        },
        "synopsis": "Tales of mischief and adventure ..."
      }
    }
  ],
  "estimate": 2
}
```

By default, the results include search metadata (`uri`, `score`, `confidence`, `fitness`, etc.) and the full content of each matched document.

You can also choose whether to work with the results embedded in the return value as a value or an iterator. For example, by default the results are returned in an array:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var response =
  jsearch.documents()
```

```
    .where(jsearch.byExample({author: 'Mark Twain'}))
    .result();                          // or .result('value')
response.results.forEach(function (result) {
  // work with the result object
});
```

By passing "iterator" as the input to the result method, you can work with the results through an iterator instead:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var response =
  jsearch.documents()
    .where(jsearch.byExample({author: 'Mark Twain'}))
    .result('iterator');
for (var result of response.results) {
  // work with the result object
}
```

For more details, see the following topics:

- "Creating a cts.query" on page 289
- "Controlling the Ordering of Results" on page 316
- "Returning a Result Subset" on page 319
- "Including Snippets of Matching Content in Search Results" on page 320
- "Including Facets in Search Results" on page 296
- "Transforming Results with Map and Reduce" on page 331
- `DocumentsSearch` in the *MarkLogic Server-Side JavaScript Function Reference*

7.4 Creating a cts.query

This section describes the most common ways of creating a cts.query for defining query criteria. Most JSearch operations include a `where` clause that accepts one or more cts.query objects as input. For example, the `documents`, `values`, and `tuples` methods all return an object with a `where` method for defining query criteria.

This section covers the following topics:

- Using byExample to Create a Query
- Using Query Text to Create a cts.query
- Using cts.query Constructors

7.4.1 Using byExample to Create a Query

The `jsearch.byExample` method enables you to build queries by modeling the structure of the content you want to match. It enables you to express your search in terms of "documents that look like this".

This section covers the following topics:

- Introduction to byExample
- Example: Building a Query With byExample
- Differences Between byExample and QBE

7.4.1.1 Introduction to byExample

Use `jsearch.byExample` to create a `cts.query` from Query By Example (QBE) style search criteria that closely model the structure of the documents you want to match. For example, the following call produces a `cts.query` that matches JSON documents with an 'author' property with the value:

```
jsearch.byExample({author: 'Mark Twain'})
```

Search criteria like the one above are implicitly value queries with exact match semantics in QBE, so the query constructed with `byExample` above is equivalent to the following `cts.query` constructor call:

```
// equivalent cts.query constructor call:
cts.jsonPropertyValueQuery(
  'author', 'Mark Twain',
  ['case-sensitive','diacritic-sensitive',
   'punctuation-sensitive','whitespace-sensitive',
   'unstemmed','unwildcarded','lang=en'],
  1)
```

QBE provides much of the expressive power of `cts.query` constructors. For example, you can use QBE keywords in your criteria to construct value, word, and range queries, as well as compose compound queries with logical "operators. For a more complete example see "Example: Building a Query With byExample" on page 292. For details, see "Searching Using Query By Example" on page 186.

Note: The JSearch `byExample` method does not use the `$response` portion of a QBE. This and other QBE features, such as result customization, are provided through other JSearch interfaces. For details, see "Differences Between byExample and QBE" on page 293.

The input to `jsearch.byExample` can be a JavaScript object, XML node, or JSON node. In all cases, the object or node can express either a complete QBE, as described in "Searching Using Query By Example" on page 186, or just the contents of the query portion of a QBE (the search criteria). For convenience, you can also pass in a document that encapsulates an XML or JSON node that meets the preceding requirements. You must use the complete QBE form of input if you need to specify the `format` or `validate` QBE flags.

For example, all the following are valid inputs to `jsearch.byExample`:

Input	Example
JavaScript Object	`// Criteria only` `{author: 'Mark Twain'}`
	`// Fully formed QBE` `{ $query: {author: 'Mark Twain'}, $validate: true}`

JSON node	`// Criteria only`
	`xdmp.unquote(`
	`  '{"author": "Mark Twain"}'`
	`).next().value.root`

	`// Fully formed QBE`
	`xdmp.unquote(`
	`  '{"$query": {"author": "Mark Twain"}, "$validate": true}}'`
	`).next().value.root`

XML node	`// Criteria only`
	`xdmp.unquote(`
	`  '<my:author xmlns:my="http://marklogic.com/example">' +`
	`  'Mark Twain</my:author>'`
	`).next().value.root`

	`// Fully formed QBE`
	`xdmp.unquote(`
	`  '<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">' +`
	`  '<q:query>' +`
	`  '<my:author xmlns:my="http://marklogic.com/example">' +`
	`  'Mark Twain</my:author>'+`
	`  '</q:query>' +`
	`  '<q:validate>true</q:validate>' +`
	`  '</q:qbe>'`
	`).next().value.root`

Document node	`// (xdmp.unquote returns a ValueIterator over document nodes)`
	`xdmp.unquote(`
	`  '{"$query": {"author": "Mark Twain"}, "$validate": true}}'`
	`).next().value`

By default, a query expressed as JavaScript object or JSON node will match JSON documents and a query expressed as an XML node will match XML documents. You can use the `format` QBE flag to override this behavior; for details, see "Scoping a Search by Document Type" on page 237.

You must use the XML node (or a corresponding document node wrapper) form to search XML documents that use namespaces as there is no way to define namespaces in the JavaScript/JSON QBE format.

7.4.1.2 Example: Building a Query With byExample

This example assumes the database contains documents with the following structure:

```
{ "title": "Tom Sawyer",
  "author" : "Mark Twain",
  "edition": {
    "format": "paperback",
    "price" : 9.99
  }
}
```

To add similar data to your database, see "Preparing to Run the Examples" on page 362.

The following query uses most of the expressive power of QBE and matches the above document. The top level properties in the query object passed to `byExample` are implicitly AND'd together, so all these conditions must be met by matching documents. Since the query includes range queries on a "price" property, the database configuration must include an element range index with localname "price" and type float.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({
    "title": {
      "$value": "adventures of tom sawyer",
      "$exact": false
    },
    "$near": [
      { "author": { "$word": "mark" } },
      { "author": { "$word": "twain" } }
    ], "$distance": 2,
    "edition": {
      "$or" : [
        { "format": "paperback" },
        { "format": "hardback" }
      ]
    },
    "$and": [
      {"price": { "$lt": 10.00 }},
      {"price": { "$ge": 8.00 }}
    ]
```

```
  }))
.result()
```

If you run this query using the documents created by “Preparing to Run the Examples” on page 362, the above query should match one document.

The following table explains the requirements expressed by each component of the query. Each of the subquery types used in this example is explored in more detail in “Understanding QBE Sub-Query Types” on page 199.

Requirement	Example Criteria

The title is “adventures of tom sawyer”. Exact match is disabled, so the match is not sensitive to case, whitespace, punctuation, or diacritics.	`"title": {`
	`  "$value": "adventures of tom sawyer",`
	`  "$exact": false`
	`}`

The author contains the word “mark” and the word “twain” within 2 words of each other.	`"$near": [`
	`  { "author": { "$word": "mark" } },`
	`  { "author": { "$word": "twain" } }`
	`],`
	`"$distance": 2`

The edition format is “paperback” or “hardback”. All the atomic values in this sub-query use exact value match semantics.	`"edition": {`
	`  "$or" : [`
	`  { "format": "paperback" },`
	`  { "format": "hardback" }`
	`  ]`
	`}`

The price is less than 10.00 and greater than or equal to 8.00.	`"$and": [`
	`  {"price": { "$lt": 10.00 }},`
	`  {"price": { "$ge": 8.00 }}`
	`]`

If you examine the output from `byExample`, you can see that the generated cts.query is complicated and much more difficult to express than the QBE syntax.

For more details, see “Searching Using Query By Example” on page 186.

7.4.1.3 Differences Between byExample and QBE

The `byExample` method of JSearch does not use all parts of a QBE. A full QBE encapsulates search criteria, results refinement, and other options. However, JSearch supports some QBE features through other interfaces like `filter` and `map`. If you pass a full QBE to `byExample`, only the `$query`, `$format`, and `$validate` properties are used. Similarly, if you use an XML QBE, only the `query`, `format`, and `validate` elements are used.

When reviewing the QBE documentation or converting QBE queries from client-side code, keep the following differences and restrictions in mind:

- Use the JSearch `filter` method instead of the QBE `$filtered` flag to enable filtered search.
- Your database configuration must include a range index definition for any range queries. There is no equivalent to using `$filtered` to avoid or defer index creation.
- Use the JSearch `withOptions` method instead of the QBE `$score` flag to select a scoring algorithm.
- You cannot use the QBE options `$constraint` or `$datatype` in your queries.
- Use the JSearch `map` method instead of the QBE `$response` property to customize results.

The following table contains a QBE on the left that uses several features affected by the differences listed above, including `$filtered`, `$score`, and `$response`. The JSearch example on the right illustrates how to achieve the same result by combining `byExample` with other JSearch features.

Standalone QBE	Equivalent JSearch byExample

{"$query": {
"author": "Mark Twain"
"$filtered": true,
"$score": "logtf"
},
"$response": {
"$snippet": { "$none": {} },
"$extract": { "title": {} }
}
}
	var jsearch = require('/MarkLogic/jsearch.sjs');
	jsearch.documents()
	.where(jsearch.byExample({author: 'Mark Twain'}))
	.filter()
	.map({snippet:false,
	extract: {paths: ['/title']}
	})
	.result()

7.4.2 Using Query Text to Create a cts.query

Use `cts.parse` to create a `cts.query` from query text such as “cat AND dog” that a user might enter in a search text box. The `cts.parse` grammar is similar to the Search API default string query grammar. For grammar details, see “Creating a Query From Search Text With cts:parse” on page 245.

For example, the following code matches documents that contain the word “steinbeck” and the word “california”, anywhere.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.parse('steinbeck AND california'))
  .result()
```

You can use the `cts.parse` grammar to generate complex queries. The following table illustrates some simple query text strings with their equivalent `cts.query` constructor calls.

Query Text	Equivalent cts.query	Explanation
`(tom or huck) NEAR becky`	`cts.nearQuery( [ cts.orQuery([ cts.wordQuery("tom"), cts.wordQuery("huck")]), cts.wordQuery("becky") ])`	at least one of the terms `tom` or `huck` within 10 terms (the default distance for `cts.near-query`) of the term `becky`
`tom NEAR/30 huck`	`cts.nearQuery([ cts.wordQuery("tom"), cts.wordQuery("huck")], 30)`	the term `tom` within 30 terms of the term `huck`
`huck -tom`	`cts.andQuery([ cts.wordQuery("huck"), cts.notQuery( cts.wordQuery("tom")) ])`	the term `huck` where there is no occurrence of `tom`

You can also bind a keyword to a query-generating function that the parser uses to generate a sub-query when the keyword appears in a query expression. This feature is similar to using pre-defined constraint names in Search API string queries. You can use a built-in function, such as `cts.jsonPropertyReference`, or supply a custom function that returns a `cts.query`.

For example, you can use a binding to cause the query text "by:twain" to generate a query that matches the word "twain" only when it appears in the value of the `author` JSON property. (In the `cts.parse` grammar, the colon (":") operator signifies a word query by default.)

```
var jsearch = require('/MarkLogic/jsearch.sjs');

// bind 'by' to the JSON property 'author'
var queryBinding = {
  by: cts.jsonPropertyReference('author')
};

// Perform a search using the bound name in a word query expression
jsearch.documents()
  .where(cts.parse('by:twain', queryBinding))
  .result();
```

You can also define a custom binding function rather than using a pre-defined function such as `cts.jsonPropertyReference`. For more details and examples, see "Creating a Query From Search Text With cts:parse" on page 245.

7.4.3 Using cts.query Constructors

You can build a `cts.query` by calling one or more `cts.query` constructor built-in functions such as `cts.andQuery` or `cts.jsonPropertyQuery`. The constructors enable you to compose complex and powerful queries.

For example, the following code uses a `cts.query` constructor built-in function to create a word query that matches documents containing the phrase "mark twain" in the value of the "author" JSON property.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(
    cts.jsonPropertyWordQuery('author', 'mark twain'))
  .result();
```

Query constructor built-in functions can be either leaf constructors, such as the one in the above example, or composable constructors. A leaf constructor does not accept cts.query's as input, while a composable constructor does. You can use composable constructors to build up powerful, complex queries.

For example, the following call creates a query that matches documents in the database directory `/books` that contain the phrase "huck" or the phrase "tom" in the "title" property and either have a "format" property with the value "paperback" or a "price" property with a value that is less than 10.

```
cts.andQuery([
  cts.directoryQuery('/books/', 'infinity'),
  cts.jsonPropertyWordQuery('title', ['huck','tom']),
  cts.orQuery([
    cts.jsonPropertyValueQuery('format', 'paperback'),
    cts.jsonPropertyRangeQuery('price', '<', 10)])
])
```

You can pass options to most cts.query constructor built-ins for fine-grained control of each portion of your search. For example, you can specify whether or not a particular word query should be case and diacritic insensitive. For details on available options, see the API reference documentation for each constructor.

For more details on constructing cts.query objects, see "Composing cts:query Expressions" on page 240.

7.5 Including Facets in Search Results

Search facets provide a summary of the values of a given characteristic across a set of search results. For example, you could query an inventory of appliances and facet on the manufacturer names. Facets can also include counts. The JSearch `facets` method enables you to generate search result facets quickly and easily.

This section includes the following topics:


- Introduction to Facets
- Basic Steps for Generating Facets
- Example: Generating Facets From JSON Properties
- Creating a Facet Definition
- Understanding the Output of Facets
- Sorting Facet Values with OrderBy
- Retrieving Facets and Content in a Single Operation
- Multi-Facet Interactions Using othersWhere
- Example: Multi-Facet Interactions Using othersWhere

7.5.1 Introduction to Facets

Search facets can enable your application users to narrow a search by "drilling down" with search criteria presented by the application.

For example, suppose you have an application that enables users to search bibliographic data on books. If the user searches for American authors, the application displays the search results, plus filtering controls that enable the user to narrow the results by author and/or media format. The filtering controls may include both a list of values, such as author names, and the number of items matching each selection.

The following diagram depicts such an interaction. Search results are not shown; only the filtering controls are included due to space constraints. The greyed out items are just representative of how an application might choose to display unselected facet values.



The filtering categories “Author” and “Media Format” represent facets. The author names and formats are values from the author and format facets, respectively. The numbers after each value represent the number of items containing that value.

MarkLogic generates facet values and counts from range indexes and lexicons. Therefore, your database configuration must include a lexicon or index for any content feature you want to use as a facet source, such as a JSON property or XML element.

Use the JSearch `facet` method to identify an index from which to source facet data; for details, see “Creating a Facet Definition” on page 301. Use the Jsearch `facets` method to generate facets from such definitions. Only facet data is returned by default, but you can optionally request matching documents as well; for details, see “Retrieving Facets and Content in a Single Operation” on page 307.

The remainder of this section describes how to generate and customize facets in more detail.

7.5.2 Basic Steps for Generating Facets

The primary interfaces for generating facets are the JSearch `facets` and `facet` methods. Use the `facet` method to create a facet definition, then pass your facet definitions to the `facets` method to create a facet generation operation. As with other JSearch operations, facets are not generated until you call the `result` method.

The following procedure outlines the steps for building a faceting operation. For a complete example, see "Example: Generating Facets From JSON Properties" on page 300.

1. Define one or more facets using the `jsearch.facet` method. For each, provide a label and an index, lexicon, or JSON property reference that identifies the facet source. The label becomes the property name for the facet data in the results.

   For example, the following call defines a facet labeled "Author" derived from a range index on the JSON property named "author". The database must include a range index on "author".

   ```
   jsearch.facet('Author', 'author')
   ```

   A facet definition can include additional configuration. For details, see "Creating a Facet Definition" on page 301.

2. Pass your facet definitions to the `jsearch.facets` method. For example:

   ```
   jsearch.facets([
       jsearch.facet('Author', 'author'),
       jsearch.facet('MediaFormat', 'format')])
   ```

3. Optionally, add a `documents` "clause" to return document search results and contents along with the facets. By default, only the facet data is returned. For example:

   ```
   jsearch.facets([
       jsearch.facet('Author', 'author'),
       jsearch.facet('MediaFormat', 'format')],
       jsearch.documents())
   ```

4. Optionally, use `FacetsSearch.where` to select the documents over which to facet. You can pass one or more `cts.query` objects, just as for a document search. For example:

   ```
   jsearch.facets([
       jsearch.facet('Author', 'author'),
       jsearch.facet('MediaFormat', 'format')])
     .where(jsearch.byExample({price: {$lt: 15}}))
   ```

5. Optionally, use the `FacetsSearch.withOptions` method to specify advanced options. For example:

   ```
   jsearch.facets([
       jsearch.facet('Author', 'author'),
       jsearch.facet('MediaFormat', 'format')])
     .where(jsearch.byExample({price: {$lt: 15}}))
     .withOptions({maxThreads: 15})
   ```

6. Generate facets (and documents, if requested in Step 3) by calling the `result` method. For example:

```
jsearch.facets([
    jsearch.facet('Author', 'author'),
    jsearch.facet('MediaFormat', 'format')])
  .where(jsearch.byExample({price: {$lt: 15}}))
  .result()
```

For a complete example, see "Example: Generating Facets From JSON Properties" on page 300.

For more details, see the following topics in the *MarkLogic Server-Side JavaScript Function Reference*:

- `jsearch.facet` and `FacetDefinition`
- `jsearch.facets` and `FacetsSearch`

7.5.3 Example: Generating Facets From JSON Properties

This example is a simple demonstration of generating facets. The example uses the sample documents and database configuration described in "Preparing to Run the Examples" on page 362.

The example generates facets for documents that contain a "price" property with value less than 15 (`jsearch.byExample({price: {$lt: 15}})`). Since the search criteria is a range query, the database configuration must include a range index on "price".

Facets are generated for the matched documents from two content features:

- The "author" JSON property values. The database configuration must include a range index on this property.
- The "format" JSON property values. The database configuration must include a range index on this property.

If your database is configured according to the instructions in "Preparing to Run the Examples" on page 362, then it already includes the indexes needed to run this example.

The following query builds up and then evaluates a facet request. Facets are not generated until the `result` method is evaluated.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author'),
    jsearch.facet('MediaFormat', 'format')])
  .where(jsearch.byExample({price: {$lt: 15}}))
  .result()
```

Running this query in Query Console produces the following output:

```
{"facets":{
  "Author": {
    "Mark Twain": 2,
    "John Steinbeck": 1
  },
  "MediaFormat": {
    "paperback": 3
}}}
```

Notice that the "facets" property of the results contains a child property corresponding to each facet definition created by `jsearch.facet`. In this case, the documents that met the "price < 15" criteria include two documents with an "author" value of "Mark Twain" and one document with an author value of "John Steinbeck". Similarly, based on the "format" property, a total of 3 paperbacks meet the price criteria.

If you add a documents query, you can retrieve facets and matched documents together. For details, see "Retrieving Facets and Content in a Single Operation" on page 307.

7.5.4 Creating a Facet Definition

The `facets` method accepts one or more facet definitions as input. Use the top level JSearch `facet` method to create each facet definitions.

The simplest form of facet definition just associates a facet name with a reference to a JSON property, XML element, field or other index or lexicon. For example, the following facet definition associates the name "Author" with a JSON property named "author".

```
jsearch.facet('Author', 'author')
```

However, you can further customize the facet using a pipeline pattern similar to the one described in “Query Design Pattern” on page 280. The table below describes the pipeline stages availble for building a facet definition.All pipeline stages are optional, can appear at most once, and must be used in the order shown. Most stages behave as they do when used with a values query; for details, see `ValuesSearch` in the *MarkLogic Server-Side JavaScript Function Reference*.

Method	Stage Description
`othersWhere`	Control how facets interact with each other and with any queries that are part of the facets call, such as a documents query. For details, see “Multi-Facet Interactions Using othersWhere” on page 310 and `FacetDefinition.othersWhere` in the *MarkLogic Server-Side JavaScript Function Reference*.
`thisWhere`	Control how facets interact with each other and with any queries that are part of the facets call, such as a documents query. For details, see “Multi-Facet Interactions Using othersWhere” on page 310 and `FacetDefinition.thisWhere` in the *MarkLogic Server-Side JavaScript Function Reference*.
`groupInto`	Group facet values into buckets based on a range of values. For example you can facet on price and group facet values into price range buckets such as “Less than $10” and “$10 or more”, rather than simply retrieving a set of individual prices and counts. For details, see “Grouping Values and Facets Into Buckets” on page 354 and `FacetDefinition.groupInto` in the *MarkLogic Server-Side JavaScript Function Reference*.
`orderBy`	Control whether the results from this facet are ordered by frequency or value and whether they’re listed in ascending or descending order. For details, see “Sorting Values or Tuples Query Results” on page 318 and `FacetDefinition.orderBy` in the *MarkLogic Server-Side JavaScript Function Reference*.
`slice`	Define a subset of the results to return. Slicing enables you to “page” through a large set of results. For details, see “Returning a Result Subset” on page 319 and `FacetDefinition.slice` in the *MarkLogic Server-Side JavaScript Function Reference*.


Method	Stage Description
`map | reduce`	Use `map` or `reduce` to apply transformations to the results. You can only use `map` or `reduce`, never both together. For details, see "Transforming Results with Map and Reduce" on page 331, `FacetDefinition.map`, and `FacetDefinition.reduce`.
`withOptions`	Specify advanced faceting options, such as an option accepted by `cts.values` or a quality weight. A facet definition accepts the same options configuration as a values query. For details, see `FacetDefinition.withOptions` in the *MarkLogic Server-Side JavaScript Function Reference*.

7.5.5 Understanding the Output of Facets

By default, only facet data is returned from a facets request, and the data for each facet is an object containing *`facetValue:count`* properties. That is, the default output has the following form:

```
{"facets": {
  "facetName1": {
    "facetValue1": count,
    ...
    "facetValueN": count,
  },
  "facetNameN": { ... },
}}
```

The facet names come from the facet definition. The facet values and counts come from the index or lexicon referenced in the facet definition. The following diagram shows the relationship between a facet definition and the facet data generated from it:



For example, the following output was produced by a facets request that included two facet definitions, name "Author" and "MediaFormat". For details on the input facet definitions, see "Example: Generating Facets From JSON Properties" on page 300.

```
{"facets":{
  "Author": {
```

```
    "Mark Twain": 2,
    "John Steinbeck": 1
  },
  "MediaFormat": {
    "paperback": 3
}}}
```

The built-in reducer generates the per facet objects, with counts. If you do not require counts, you can use the `map` method to bypass the reducer and configure the built-in mapper to omit the counts. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    jsearch.facet('Author', 'author').map({frequency: 'none'})
  .where(cts.directoryQuery('/books/'))
  .result()
```

Running this query on a database configured according to the instructions in “Preparing to Run the Examples” on page 362 produces the following output:

```
{"facets": {
  "Author": ["Mark Twain", "Robert Frost", "John Steinbeck"]
}}
```

If you include a `documents` call in your `facets` operation, then the output includes both facet data and the results of the document search. The output has the following form:

```
{ "facets": {
    property for each facet
  },
  "documents": [
    descriptor for each matched document
  ]
}
```

The documents array items are search result descriptors exactly as returned by a document search. They can include the document contents and search match snippets. For an example, see “Example: Generating Facets From JSON Properties” on page 300.

You can pass 'iterator' to your `result` call to return a `ValueIterator` as the value of each facet instead of an object. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var results =
  jsearch.facets(jsearch.facet('Author', 'author'))
    .where(cts.directoryQuery('/books/'))
    .result('iterator')
var authors = [];
for (var author of results.facets.Author) {
  authors.push(author)
}
```

```
authors

==> [{"Mark Twain":4, "Robert Frost":1, "John Steinbeck":3}]
```

In this case, the returned iterator contains only a single item: The object containing the *value:count* properties for the facet that is produced by the built-in reducer. However, if you use a mapper or a custom reducer, you can have more items to iterate over.

For example, the following call chain configures the built-in mapper to return only the facet values, without counts, so returning an iterator results in a `ValueIterator` over each facet value (author name, here):

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var results =
jsearch.facets(
    jsearch.facet('Author', 'author').map({frequency: 'none'})
  .where(cts.directoryQuery('/books/'))
  .result('iterator')
var authors = [];
for (var author of results.facets.Author) {
  authors.push(author)
}
authors

==> ["Mark Twain", "Robert Frost", "John Steinbeck"]
```

If you use `groupInto` to group the values for a facet into "buckets" representing value ranges, then the value of the facet is either an object or iterator over the bucket descriptors. For example, suppose you generate facets on a 'price' property and get the following values:

```
{"facets":{
  "Price": "8":1, "9":1, "10":1, "16":1, "18":2, "20":1, "30":1}
}}
```

You could add a `groupInto` specification to group the facet values into 3 price range buckets instead, as shown in the following query:

```
jsearch.facets(
  jsearch.facet('Price','price')
    .groupInto([
      jsearch.bucketName('under $10'), 10,
      jsearch.bucketName('$10 to $19.99'), 20,
      jsearch.bucketName('over $20')
    ]))
  .where(cts.directoryQuery('/books/'))
  .result();
```

Now, the generated facets are similar to the following:

```
{"facets": {
  "Price": {
```

```
      "under $10": {
        "value": {
          "minimum": 8,
          "maximum": 9,
          "upperBound": 10
        },
        "frequency": 2
      },
      "$10 to $19.99": {
        "value": {
          "minimum": 10,
          "maximum": 18,
          "lowerBound": 10,
          "upperBound": 20
        },
        "frequency": 4
      },
      "over $20": {
        "value": {
          "minimum": 20,
          "maximum": 30,
          "lowerBound": 20
        },
        "frequency": 2
      }
    }
} }
```

For details, see "Grouping Values and Facets Into Buckets" on page 354.

7.5.6 Sorting Facet Values with OrderBy

As mentioned in "Introduction to Facets" on page 297, facet results include a count (or frequency) by default. You can use `FacetDefinition.orderBy` to sort the results for a given facet by this frequency. Including an explicit sort order in your facet definition changes the structure of the results.

For example, the following query, which does not use `orderBy`, produces a set of facet values on "author", in the form of a JSON object. This is the default behavior. Since the facet is an object with *`facetValue`*:*`count`* properties, the facet values are effectively unordered.

```
const jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author')])
  .where(jsearch.byExample({price: {$lt: 50}}))
  .result();

// Produces the following output:
// {"facets":{
//   "Author":{
//     "John Steinbeck":3,
//     "Mark Twain":4,
```

```
//     "Robert Frost":1}
// }}
```

If you add an `orderBy` clause to the facet definition, then the value of the facet is an array of arrays, where each inner array is of the form `[ item_value, count ]`. The array items are ordered by the frequency. For example:

```
const jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author').orderBy('frequency') ])
  .where(jsearch.byExample({price: {$lt: 50}}))
  .result();

// Produces the following output:
// {"facets":{
//   "Author":[
//     ["Mark Twain", 4],
//     ["John Steinbeck", 3],
//     ["Robert Frost", 1]
//   ]
// }}
```

You can also sort by item (the value of "author" in our example), and choose whether to list the facet values in ascending or descending order. For example, if you use the `orderBy` clause `orderBy('item', descending)`, the you get the following output:

```
{"facets":{
  "Author":[
    ["Robert Frost", 1],
    ["Mark Twain", 4],
    ["John Steinbeck", 3]
  ]
}}
```

If the default structure does not meet the needs of your application, you can modify the output using a custom mapper. For more details, see "Transforming Results with Map and Reduce" on page 331.

7.5.7 Retrieving Facets and Content in a Single Operation

By default, the result of facet generation does not include content from the documents from which the facets are derived. Add snippets, complete documents, or document projections to the results by including a `documents` query in your `facets` call.

For example, the following query returns both facets and snippets for documents that contain a "price" property with a value less than 15:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author'),
```

```
    jsearch.facet('MediaFormat', 'format')],
    jsearch.documents())
  .where(jsearch.byExample({price: {$lt: 15}}))
  .result()
```

Running this query against the database created by "Preparing to Run the Examples" on page 362 produces the following output. Notice the output includes facets on author and format, plus the document search results containing snippets (in the "properties" property).

```
{ "facets": {
    "Author": {
      "Mark Twain": 2,
      "John Steinbeck": 1
    },
    "MediaFormat": { "paperback": 3 }
  },
  "documents": [
    { "uri": "/books/twain1.json",
      "path": "fn:doc(\"/books/twain1.json\")",
      "index": 0,
      "matches": [ {
        "path":
          "fn:doc(\"/books/twain1.json\")/edition/number-node(\"price\")",
        "matchText": [ { "highlight": "9" } ]
      } ]
    },
    ...additional documents...
  ],
  "estimate": 3
}
```

The `matches` property of each `documents` item contains the snippets. For example, if the above facets results are saved in a variable named "results", then you can access the snippets for a given document through `results.documents[n].matches`.

To include the complete documents in your facet results instead of just snippets, configure the built-in mapper on the documents query to extract "all". For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author'),
    jsearch.facet('MediaFormat', 'format')],
    jsearch.documents().map({extract:{select:'all'}})
  .where(jsearch.byExample({price: {$lt: 15}}))
  .result()
```

In this case, you access the document contents through the extracted property of each document. For example, `results.documents[n].extracted`. The `extracted` property value is an array because you can potentially project multiple subsets of content out of the matched document using the map and reduce features. For details, see "Extracting Portions of Each Matched Document" on page 325.

The documents query can include `where`, `orderBy`, `filter`, `slice`, `map`/`reduce`, and `withOptions` qualifiers, just as with a standalone document search. For details, see "Document Search Basics" on page 285.

The document search combines the queries in the `where` qualifier of the `facets` query, the `where` qualifier of the documents query, and any `othersWhere` queries on facet definitions into a single AND query.

For example, the following `facets` query includes uses all three query sources.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author'),
    jsearch.facet('MediaFormat','format')
      .othersWhere(jsearch.byExample({format: 'paperback'}))],
    jsearch.documents()
      .where(jsearch.byExample({author: 'Mark Twain'})))
  .where(jsearch.byExample({price: {$lt: 20}}))
  .result()
```

This query has the following effect on the returned results:

- Only generate facets from documents where "price < 20". From this part of the query: `jsearch.facets(...).where(jsearch.byExample({price: {$lt: 20}})).`
- For facets other than `format`, only return facet values for documents where "format is paperback". From this part of the query: `jsearch.facet('MediaFormat','format').othersWhere(jsearch.byExample({format: 'paperback'}))`
- Only return documents where "author is Mark Twain". From this part of the query: `jsearch.documents().where(jsearch.byExample({author: 'Mark Twain'}))`

Thus, the query only returns matches where all the following conditions are met: "price < 20" and "format is paperback" and "author is Mark Twain".

You can use the `returnQueryPlan` option to explore this relationship. For example, adding a `withOptions` call to the documents query as shown below returns the following information in the results:

```
...
jsearch.documents()
  .where(jsearch.byExample({author: 'Mark Twain'}))
  .withOptions({returnQueryPlan: true})
...

==> results.queryPlan includes the following information
    (reformatted for readability)

Search query contributed 3 constraints:
  cts.andQuery([
```

```
    cts.jsonPropertyRangeQuery("price", "<", xs.float("20"), [], 1),
    cts.jsonPropertyValueQuery("format", "paperback",
      ["case-sensitive","diacritic-sensitive","punctuation-sensitive",
       "whitespace-sensitive","unstemmed","unwildcarded","lang=en"], 1),
    cts.jsonPropertyValueQuery("author", "Mark Twain",
      ["case-sensitive","diacritic-sensitive","punctuation-sensitive",
       "whitespace-sensitive","unstemmed","unwildcarded","lang=en"], 1)
  ], [])
```

7.5.8 Multi-Facet Interactions Using othersWhere

Use the `FacetDefinition.othersWhere` method to efficiently vary facet values across user interactions and deliver a more intuitive faceted navigation user experience.

Imagine an application that enables users to filter a search using facet-based filtering controls. Each time a user interacts with the filtering controls, the application makes a request to MarkLogic to retrieve new search results and facet values that reflect the current search criteria.

A naive implementation might apply the selection criteria across all facets and document results. However, this causes values to "drop out" of the filtering choices, making it more difficult for users to be aware of other choice or change the filters.

The application could generate the values for each facet and for the matching documents independently, but this is inefficient because it requires multiple requests to MarkLogic. A better approach is to use the `othersWhere` method to apply criteria asymmetrically to the facets and collectively to the document search portion.

The following example uses `othersWhere` to generate facet values for two selection criteria, an author value of "Mark Twain" and a format value of "paperback":

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    [jsearch.facet('Author', 'author')
       .othersWhere(jsearch.byExample({author: 'Mark Twain'})),
     jsearch.facet('MediaFormat', 'format')
       .othersWhere(jsearch.byExample({format: 'paperback'}))],
    jsearch.documents())
  .where(cts.directoryQuery('/books/'))
  .result()
```

When each facet applies `othersWhere` to selection criteria based on itself, you get multi-facet interactions. For example, the above query returns the following results. Thanks to the use of `othersWhere` on each facet definition, the author facet values are unaffected by the "Mark Twain" selection and the format facet values are unaffected by "paperback" selection. The document search is affected by both.

```
{"facets":{
   "Author":{"John Steinbeck":1, "Mark Twain":2, "Robert Frost":1},
   "MediaFormat":{"hardback":2, "paperback":2}},
```

```
 "documents":[ ...snippets for docs matching both criteria... ]
}
```

If you pass the criteria in through the `where` method instead, some facet values "drop out", making it more difficult for users to see the available selections or to change selections. For example, the following query puts the author and format criteria in the `where` call, resulting in the facet values shown:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    [jsearch.facet('Author', 'author'),
     jsearch.facet('MediaFormat', 'format')],
    jsearch.documents())
  .where([cts.directoryQuery('/books/'),
          jsearch.byExample({author: 'Mark Twain'}),
          jsearch.byExample({format: 'paperback'})])
  .result()

==>
{"facets":{
    "Author":{"Mark Twain":2},
    "MediaFormat":{"paperback":2}},
 "documents":[ ...snippets for docs matching both criteria... ]
```

The differences in these two approaches are explored in more detail in "Example: Multi-Facet Interactions Using othersWhere" on page 311.

The JSearch API also includes a `FacetDefinition.thisWhere` modifier which has the opposite effect of `othersWhere`: The selection criteria is applied only to the subject facet, not to any other facets or to the document search. For details, see `FacetDefinition.thisWhere` in the *MarkLogic Server-Side JavaScript Function Reference*.

7.5.9 Example: Multi-Facet Interactions Using othersWhere

This example explores the use of `othersWhere` to enable search selection criteria to affect related facets asymmetrically, as described in "Multi-Facet Interactions Using othersWhere" on page 310.

This example assumes the database configuration and content described in "Preparing to Run the Examples" on page 362.

Suppose you have an application that enables users to search for books, and the application displays facets on author and format (hardback, paperback, etc.) that can be used to narrow a search.

The following diagram contrasts two possible approaches to implementing such a faceted navigation control. The middle column represents a faceted navigation control when the user's selection criteria are applied symmetrically to all factes through the `where` method. The rightmost column represents the same control when the user's criteria are applied asymmetrically using `othersWhere`. Notice that, in the rightmost column, the user can always see and select alternative criteria.


Facet criteria	Selections apply to ALL facets (where())	Selections apply to OTHER facets (othersWhere())
No selection criteria	**Author** ☐ Mark Twain (4) ☐ Robert Frost (1) ☐ John Steinbeck (3) **Media Format** ☐ audiobook (1) ☐ hardback (3) ☐ paperback (4)	**Author** ☐ Mark Twain (4) ☐ Robert Frost (1) ☐ John Steinbeck (3) **Media Format** ☐ audiobook (1) ☐ hardback (3) ☐ paperback (4)
author: Mark Twain	**Author** ■ Mark Twain (4) **Media Format** ☐ hardback (2) ☐ paperback (2)	**Author** ■ Mark Twain (4) ☐ Robert Frost (1) ☐ John Steinbeck (3) **Media Format** ☐ hardback (2) ☐ paperback (2)
format: paperback	**Author** ☐ Mark Twain (2) ☐ Robert Frost (1) ☐ John Steinbeck (1) **Media Format** ■ paperback (4)	**Author** ☐ Mark Twain (2) ☐ Robert Frost (1) ☐ John Steinbeck (1) **Media Format** ☐ audiobook (1) ☐ hardback (3) ■ paperback (4)
author: Mark Twain AND format: paperback	**Author** ■ Mark Twain (2) **Media Format** ■ paperback (2)	**Author** ■ Mark Twain (2) ☐ Robert Frost (1) ☐ John Steinbeck (1) **Media Format** ☐ hardback (2) ■ paperback (2)

The remainder of this example walks through the code that backs the results in both columns.

Before the user selects any criteria, the baseline facets are generated with the following request. Facet values are generated for the "author" and "format" JSON properties. The documents in the "/books/" directory seed the initial search results that the user can drill down on. (Matched documents are not shown.)

```
// baseline - no selection criteria
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets([
    jsearch.facet('Author', 'author'),
    jsearch.facet('MediaFormat', 'format')
  ], jsearch.documents())
  .where(cts.directoryQuery('/books/'))
  .result()
```

Consider the case where the user then selects an author, and the application applies the selection criteria unconditionally, resulting in the following filtering control changes:




The user can no longer readily see the other available authors. These results were generated by the following query, where the `cts.directoryQuery` query represents the baseline search, and the `jsearch.byExample` query represents the user selection. Passing the author query to the `where` method applies it to all facets and the document search.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    [jsearch.facet('Author', 'author'),
     jsearch.facet('MediaFormat', 'format')],
    jsearch.documents())
  .where([cts.directoryQuery('/books/'),
          jsearch.byExample({author: 'Mark Twain'})])
  .result()
```

By moving the author query to an `othersWhere` modifier on the `author` facet, you can apply the selection to other facets, such as `format`, and to the document search, but leave the author facet unaffected by the selection criteria. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    [jsearch.facet('Author', 'author')
       .othersWhere(jsearch.byExample({author: 'Mark Twain'})),
     jsearch.facet('MediaFormat', 'format')],
    jsearch.documents())
  .where(cts.directoryQuery('/books/'))
  .result()
```


Using using `othersWhere` instead of `where` to pass the criteria results in the following display. The user can clearly see the alternative author choices and the number of items that match each other. Yet, the user can still see how his author selection affects the available media formats and the matching documents. The diagram below illustrates how the application might display the returned facet values. Snippets are returned for all documents with "Mark Twain" as the author.



If the user chooses to further filter on the "paperback" media format, you can use `othersWhere` on the `format` facet to apply this criteria to the `author` facet values and the document search, but leave all the `format` facets values available. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
    [jsearch.facet('Author', 'author')
       .othersWhere(jsearch.byExample({author: 'Mark Twain'})),
     jsearch.facet('MediaFormat', 'format')
       .othersWhere(jsearch.byExample({format: 'paperback'}))],
    jsearch.documents())
  .where(cts.directoryQuery('/books/'))
  .result()
```

The above query results in the following display. The user can easily see and select a different author or format. The matched documents are not shown, but they consist of documents that match both the author and format selections.



7.6 Controlling the Ordering of Results

Use the `orderBy` method to control the order in which your query results are returned. You can apply an `orderBy` "clause" to a document search, word lexicon query, values query, or tuples query.

Though you can use `orderBy` with all these query types, the specifics vary. For example, you can only specify content-based sort keys in a document search, and you can only choose between item order and frequency order on a values or tuples query.

This section covers the following topics.

- Sorting Document Search Results
- Sorting Values or Tuples Query Results
- Sorting Word Lexicon Query Results
- Sorting Facet Values

7.6.1 Sorting Document Search Results

By default, search results are returned in relevance order, with most relevant results displayed first. That is, the sort key is the relevance score and the sort order is descending.

You can use the `DocumentsSearch.orderBy` method to change the sort key and ordering (ascending/descending). You can sort the results by features of your content, such as the value of a specified JSON property, and by attributes of the match, such as fitness, confidence, or document order. You must configure a range index for each JSON property, XML element, XML attribute, field, or path on which you sort.

For example, the following code sorts results by value of the JSON property named "title". A range index for the "title" property must exist.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({'author': { '$word': 'twain' }}))
  .orderBy('title')
  .result();
```

The use of a simple name in the `orderBy` call implies a `cts.jsonPropertyReference`. You can also explicitly construct a `cts.reference` by calling an index reference constructor such as `cts.jsonPropertyReference`, `cts.elementReference`, `cts.fieldReference`, or `cts.pathReference`. For example, the following call specifies ordering on the JSON property "price":

```
orderBy(cts.jsonPropertyReference('price'))
```

To sort results based on search metadata such as confidence, fitness, and quality, use the `cts.order` constructors. For example, the following `orderBy` specifies sorting by confidence rather than relevance score:

```
orderBy(cts.confidenceOrder())
```

You can also use the `cts.order` constructors to control whether results are sorted in ascending or descending order with respect to a sort key. For example, the following call sorts by the JSON property "price", in ascending order:

```
orderBy(
  cts.indexOrder(cts.jsonPropertyReference('price'), 'ascending'))
```

You can specify more than one sort key. When there are multiple keys, they're applied in the order they appear in the array passed to `orderBy`. For example, the following call says to first order results by the "price" JSON property values, and then by the "title" values.

```
orderBy(['price', 'title'])
```

For details, see `DocumentsSearch.orderBy` in the *MarkLogic Server-Side JavaScript Function Reference* and Sorting Searches Using Range Indexes in the *Query Performance and Tuning Guide*.

7.6.2 Sorting Values or Tuples Query Results

By default, values and tuples query results are returned in ascending item order. You can use the `ValuesSearch.orderBy` and `TuplesSearch.orderBy` methods to specify whether to order the results by value (item order) or frequency, and whether to use ascending or descending order.

For example, the following query returns all the values of the `price` JSON property, in ascending order of the values:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price').result()

==> [8, 9, 10, 16, 18, 20, 30]
```

The following code modifies the query to return the results in frequency order. By default, frequency order returns results in descending order (most to least frequent). In this case, the database contained multiple documents with price 18, and only a single document containing each of the other price points, so the 18 value sorted to the front of the result array, and the remaining values that share the same frequency appear in document order.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price').orderBy('frequency').result()

==> [18, 8, 9, 10, 16, 20, 30]
```

To order the results by ascending frequency value, pass 'ascending' as the second parameter of `orderBy`. For example:

```
orderBy('frequency', 'ascending')
```

You can also include the frequency values in the results using the map or reduce methods. For details, see “Querying the Values in a Lexicon or Index” on page 341.

7.6.3 Sorting Word Lexicon Query Results

When you query a word lexicon using the `jsearch.words` resource selector method, results are returned in ascending order. Use the `WordsSearch.orderBy` method to control whether the results are returned in ascending or descending order.

For example, the following query returns the first 10 results in the default (ascending) order:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.words('title').result()

==>
["Adventures", "and", "Collected",
 "East", "Eden", "Finn", "Grapes",
 "Huckleberry", "Men", "Mice"]
```

You can use `orderBy` to change the order of results. For example, the following call returns the 10 results when the words in `title` are sorted in descending order:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.words('title').orderBy('descending').result()

==>
["Wrath", "Works", "Tom", "The",
 "Sawyer", "Of", "of", "Mice",
 "Men", "Huckleberry"]
```

Note that this example assumes the database configuration includes a word lexicon on the "title" JSON property. For more details on querying word lexicons, see "Querying Values in a Word Lexicon" on page 346.

7.6.4 Sorting Facet Values

When you generate facets with frequencies using `jsearch.facets`, the values of each facet are expressed as a JSON object, so they are effectively unordered. You can use `FacetDefinition.orderBy` to control the sort order and change the output to a structure that can be meaningfully ordered (an array of arrays).

For more details, see "Sorting Facet Values with OrderBy" on page 306.

7.7 Returning a Result Subset

You can use the `slice` method to return a subset of the results from a top level documents, values, tuples, or words query, or when generating facets.

A slice specification works like `Array.slice` and has the following form:

```
slice(firstPosToReturn, lastPosToReturn + 1)
```

The positions use a 0-based index. That is, the first item is position 0 in the result list. Thus, the following returns the first 3 documents in the "classics" collection:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var classics = jsearch.collections('classics');

classics.documents()
  .slice(0,3)
  .result()
```

You cannot request items past the end of result set, so it is possible get fewer than the requested number of items back. When the search results are exhausted, the `results` property of the return value is `null`, just as for a search which matches nothing. For example:

```
{ results: null, estimate: 4 }
```

Applying `slice` iteratively to the same query enables you to return successive "pages" of results. For example, the following code iterates over search results in blocks of three results at a time:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var sliceStep = 3;      // max results per batch
var sliceStart = 0;
var sliceEnd = sliceStep;
var response = {};
do {
  response = jsearch.documents().slice(sliceStart, sliceEnd).result();
  if (response.results != null) {
    // do something with the results
    sliceStart += response.results.length;
    sliceEnd += sliceStep;
  }
} while (response.results != null);
```

You can set the slice end position to zero to suppress returning results when you're only interested in query metadata, such as the estimate or when using `returnQueryPlan:true`. For example, the following returns the estimate without results:

```
var jsearch = require('/MarkLogic/jsearch.sjs');

jsearch.documents()
  .where(cts.jsonPropertyValueQuery('author', 'Mark Twain'))
  .slice(0,0)
  .result()

==>

{ results: null, estimate: 4 }
```

For details, see the following methods:

- `DocumentsSearch.slice`
- `FacetDefinition.slice`
- `ValuesSearch.slice`
- `TuplesSearch.slice`
- `WordsSearch.slice`

7.8 Including Snippets of Matching Content in Search Results

When you perform a document search using `jsearch.documents`, the result is an array or `ValueIterator` over descriptors of each match. Each descriptor includes the contents of the matching document by default. You can use snippeting to a include portion of the content around the match in each result, instead of (or in addition to) the complete document.

This section covers the following topics:

- Enabling Snippet Generation
- Configuring the Built-In Snippet Generator
- Returning Snippets and Documents Together
- Generating Custom Snippets
- Standalone Snippet Generation

7.8.1 Enabling Snippet Generation

You can include snippets in a document query by adding a `map` clause to your query that sets the built-in mapper configuration property `snippet` to `true` or setting `snippet` to a configuration object, as described in "Configuring the Built-In Snippet Generator" on page 322. (Snippets are generated by default when you include any document query in `jsearch.facets` operation.)

For example, the following query matches occurrences of the word "california" and returns the default snippets instead of the matching document:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({synopsis: {$word: 'california'}}))
  .map({snippet: true})
  .result()

==>
{"results":[
  {"score":28672,
   "fitness":0.681636929512024,
   "uri":"/books/steinbeck1.json",
   "path":"fn:doc(\"/books/steinbeck1.json\")",
   "confidence":0.529645204544067,
   "index":0,
   "matches":[{
     "path":"fn:doc(\"/books/steinbeck1.json\")/text(\"synopsis\")",
     "matchText":[
       "...from their homestead and forced to the promised land of ",
       {"highlight":"California"}, "."
     ]
   }]
  },
  { ... }, ...
  ],
  "estimate":3
}
```

If this was a default search (no snippets), there would be a "document" property instead of the "matches" property, as shown in "Example: Basic Document Search" on page 287.

For more details, see `DocumentsSearch.map`.

7.8.2 Configuring the Built-In Snippet Generator

You can configure the built-in snippet generator by setting the built-in mapper `snippet` property to a configuration object instead of a simple boolean vaue.

You can set the following snippet configuration properties:

Property	Description
`maxMatches`	The maximum number of nodes containing a highlighted term to include in the snippet. Default: 4.
`perMatchTokens`	The maximum number of tokens (typically words) per matching node that surround the highlighted term(s) in the snippet. Default: 30.
`maxSnippetChars`	The maximum total snippet size, in characters. Default: 200.
`preferredMatches`	The snippet alogorithm looks for matches first in the specified XML element or JSON property nodes in each snippet. If no matches are found in the preferred elements or properties, the algorithm falls back to default content. XML element names can be namespace qualified; use the `namespaces` property (sibling of `snippet`) to define your prefixes.
`query`	Generate snippets based on matches to the specified query. Required when snippeting with `documentSelect`, optional when snippeting with `documents`. This is only useful for `documents().map()` when the snippet query needs to be different from the document retrieval query (e.g. the query in the `where` clause).

For example, the following configuration only returns snippets for matches occurring in the `synopsis` property and surrounds the highlighted matching text by at most 5 tokens.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.wordQuery('california'))
  .map({snippet: {
    preferredMatches: ['synopsis'],
    perMatchTokens: 5
  }})
  .result()
```

Thus, if the word query for occurrences of "california" matched text in both the `title` and `synopsis` for some documents, only the matches in `synopsis` are returned. Also, the snippet match text is shorter, as shown below.

```
// match text in snippet with default perMatchTokens
"matchText":[
  "...an unlikely pair of drifters who move from
   job to job as farm laborers in ",
  {"highlight":"California"},
  ", until it all goes horribly awry."
]

// match text in snippet with perMatchTokens set to 5
"matchText":[
  "...farm laborers in ",
  {"highlight":"California"},
  ", until it..."
]
```

When snippeting over XML documents and using `preferredMatches`, use a QName rather than a simple string to specify namespace-qualified elements. For example:

```
{snippet: {
  preferredMatches: [fn.QName('/my/namespace','synopsis')]
}}
```

For more details, see `DocumentsSearch.map`.

7.8.3 Returning Snippets and Documents Together

To return snippets and complete documents or document projections together, set `snippet` to `true` and configure the `extract` property of the built-in mapper to select the desired document contents. For details about `extract`, see "Extracting Portions of Each Matched Document" on page 325.

The following example returns the entire matching document in an `extracted` property and the snippets in the `matches` property of the results:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({synopsis: {$word: 'California'}}))
  .map({snippet: true, extract: {selected: 'all'}})
  .result()

==>
{"results":[
  {"score":28672,
   "fitness":0.681636929512024,
   "uri":"/books/steinbeck1.json",
   "path":"fn:doc(\"/books/steinbeck1.json\")",
   "extracted":[{
     "title":"The Grapes of Wrath",
```

```
      "author":"John Steinbeck",
      "edition":{"format":"paperback", "price":9.99},
      "synopsis":"Chronicles the 1930s Dust Bowl migration of one
         Oklahoma farm family, from their homestead and forced to
         the promised land of California."
    }]
    "confidence":0.529645204544067,
    "index":0,
    "matches":[{
      "path":"fn:doc(\"/books/steinbeck1.json\")/text(\"synopsis\")",
      "matchText":[
        "...from their homestead and forced to the promised land of ",
        {"highlight":"California"}, "."
      ]
    }]
  },
  { ... }, ...
  ],
  "estimate":3
}
```

For more details, see `DocumentsSearch.map`.

7.8.4 Generating Custom Snippets

If the snippets and projections generated by the built-in mapper do not meet the needs of your application, you can use a custom mapper to generate customized results. For details, see “Transforming Results with Map and Reduce” on page 331.

7.8.5 Standalone Snippet Generation

You can use the `jsearch.documentSelect` method to generate snippets from an arbitrary set of documents, such as the output from `cts.search` or `fn.doc`. The output is a `ValueIterator` over the results.

If the input is the result of a search that matches text, then the results include search result metadata such as score, along with your snippets. Search metadata is not included if the input is an arbitrary set of documents or the result of a search that doesn't match text, such as a collection or directory query.

You must include a query in the snippet configuration when using `documentSelect` so the snippeter has search matches against which to generate snippets. You can also include the other properties described in “Configuring the Built-In Snippet Generator” on page 322.

The following example uses `documentSelect` to generate snippets from the result of calling `cts.search` (instead of `jsearch.documents()`).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var myQuery =
```

```
    cts.andQuery([
      cts.directoryQuery('/books/'),
      cts.jsonPropertyWordQuery('synopsis', 'california')])
jsearch.documentSelect(
  cts.search(myQuery),
  {snippet: {query: myQuery}})
```

7.9 Extracting Portions of Each Matched Document

You can use the built-in mapper of document search to return selected portions of each document that matches a search. You can use the extraction feature with `jsearch.documents` and `jsearch.documentSelect`.

This section includes the following topics:

- Extraction Overview
- How selected Affects Extraction
- Combining Extraction With Snippeting

7.9.1 Extraction Overview

By default, a document search returns the complete document for each search match. You can use `extract` feature of the built-in `documents` mapper to extract only selected parts of each matching document instead. Such a subset of the content in a document is sometimes called a *sparse document projection*. This feature is similar to the query option `extract-document-data`. available to the XQuery Search API and the Client APIs.

You use XPath expressions to identify the portions of the document to include or exclude. XPath is a standard expression language for addressing XML content. MarkLogic has extended XPath so you can also use it to address JSON. For details, see Traversing JSON Documents Using XPath in the *Application Developer's Guide* and XPath Quick Reference in the *XQuery and XSLT Reference Guide*.

To generate sparse projections, configure the `extract` property of the built-in mapper of a document search. The property has the following form:

```
extract: {
  paths: xPathExpr | [xPathExprs],
  selected: 'include' | 'include-with-ancestors' | 'exclude' | 'all'
}
```

Specify one or more XPath expressions in the `paths` value; use an array for specifying multiple expressions. The `selected` property controls how the content selected by the paths affects the document projection. The `selected` property is optional and defaults to `'include'` if not present; for details, see "How selected Affects Extraction" on page 327.

For example, the following code extracts just the `title` and `author` properties of documents containing the word "California" in the `synopsis` property.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({synopsis: {$word: 'California'}}))
  .map({extract: {paths: ['/title', '/author']}})
  .result()
```

The table below displays the default output of the query (without a mapper) on the left and the result of using the example extraction on the right. Notice that the `document` property that contains the complete document contents has been replaced with an `extracted` property that contains just the requested subset of content.

Default Output	With Extract

{ "results": [
  { "index": 0,
  "uri": "/books/steinbeck1.json",
  "score": 34816,
  "confidence": 0.54882669448852,
  "fitness": 0.6809344291687,
  "document": {
  "title": "The Grapes of Wrath",
  "author": "John Steinbeck",
  "edition": {
  "format": "paperback",
  "price": 10
  },
  "synopsis": "Chronicles the 1930s Dust Bowl migration of one Oklahoma farm family, from their homestead and forced to the promised land of California."
  }
  }, ...*additonal results*...],
  "estimate": 3
}
	{ "results": [
	  { "index": 0
	  "uri": "/books/steinbeck1.json",
	  "score": 18432,
	  "confidence": 0.4903561770916,
	  "fitness": 0.71398365497589,
	  "path": "fn:doc(\"/books/steinb...",
	  "extracted": [
	  { "title": "The Grapes of Wrath" },
	  { "author": "John Steinbeck" }
	  ],
	  }, ...*additional results*...],
	  "esitmate": 3
	}

When extracting XML content that uses namespaces, you can use namespace prefixes in your extract paths. Define the prefix bindings in the namespaces property of the mapper configuration object. For example, the following configuration binds the prefix "my" to the namespace URI "/my/namespace", and then uses the "my" prefix in an extract path.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documentSelect(fn.doc('/books/some.xml'),
  {
```

```
    namespaces: {my: '/my/namespace'},
    extract: {paths: ['/my:book/my:title']}
  })
```

Since the extraction feature is a capability of the built-in mapper for a document search, you cannot use it when using a custom mapper. If you want to return document subsets when using a custom mapper, you must construct the projections yourself.

For more details on using and configuring mappers, see "Transforming Results with Map and Reduce" on page 331.

7.9.2 How selected Affects Extraction

The `selected` property of the `extract` configuration for `DocumentsSearch.map` determines what to include in the extracted content. By default, the extracted content includes only the content selected by the path expressions. However, you can use the `select` property to configure these alternatives:

- include enclosing objects or elements (ancestors) in addition to the named nodes
- exclude the specified nodes rather than include them
- include all nodes, effectively ignoring the specified paths and including the whole document

For example, the documents loaded by "Preparing to Run the Examples" on page 362 have the following form:

```
{ "title": string,
  "author": string,
  "edition": {
    "format": string,
    "price": number
  },
  "synopsis": string
}
```

The table below illustrates how various `selected` settings affect the extraction of the `title` and `price` properties. The first row (`'include'`) also represents the default behavior when `selected` is not explicitly set.

`extract` Configuration	`extracted` Value

{extract: {
  paths: ['/title','/price'],
  selected: 'include'
}}
	"extracted":[
	  {"title": "The Grapes of Wrath"},
	  {"price": 10}
	]

{extract: {
  paths: ['/title','/price'],
  selected: 'include-with-ancestors'
}}
	"extracted":[{
	  "title": "The Grapes of Wrath",
	  "edition": {"price":10}
	}]

{extract: {
  paths: ['/title','/price'],
  selected: 'exclude'
}}
	"extracted":[{
	  "author": "John Steinbeck",
	  "edition": {"format":"paperback"},
	  "synopsis": ...
	}]

{extract: {
  paths: ['/title','/price'],
  selected: 'all'
}}
	"extracted":[{
	  "title":"The Grapes of Wrath",
	  "author":"John Steinbeck",
	  "edition":{
	  "format":"paperback",
	  "price":10
	  },
	  "synopsis": ...
	}]

If the combination of `paths` and `select` selects no content for a given document, then the results contain an `extractedNone` property instead of an `extracted` property. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({synopsis: {$word: 'California'}}))
  .map({extract: {paths: ['/no/matches'], selected: 'include'}})
  .result()

==>

{"results":[
  { ...,
    "extractedNone":true,
    ...
}]}
```

7.9.3 Combining Extraction With Snippeting

By default, snippets are not generated when you use extraction, but you can configure your search to return both snippets and extracted content by setting `snippet` to true in the mapper configuration. For example, the following search:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(jsearch.byExample({synopsis: {$word: 'California'}}))
  .map({snippet: true, extract: {paths: ['/title', '/author']}})
  .result()
```

Produces output similar to the following, with the document projects in the extracted property and the snippets in the matches property:

```
{ "results": [
  { "score": 18432,
    "fitness": 0.71398365497589,
    "uri": "/books/steinbeck1.json",
    "path": "fn:doc(\"/books/steinbeck1.json\")",
    "extracted": [
      { "title": "The Grapes of Wrath" },
      { "author": "John Steinbeck" }
    ],
    "confidence": 0.4903561770916,
    "index": 0,
    "matches": [{
      "path": "fn:doc(\"/books/steinbeck1.json\")/text(\"synopsis\")",
      "matchText": [
        "...from their homestead and forced to the promised land of ",
        { "highlight": "California" },
        "."
      ]
    }]
  }, ...]
}
```

Similarly, you can include both `snippet` and `extract` specifications in the configuration for `jsearch.documentSelect`. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documentSelect(
  cts.search(cts.jsonPropertyWordQuery('synopsis', 'California')),
  {snippet: {
    query: cts.jsonPropertyWordQuery('synopsis', 'California') }
   extract: {paths: ['/title', '/author'], selected: 'include'}
  }
)
```

For more details on snippeting, see “Including Snippets of Matching Content in Search Results” on page 320.

7.10 Using Options to Control a Query

You can control a document search with options in two ways:

- Specify query-specific options during construction of a query.
- Specify search-wide options using the `DocumentsSearch.withOptions` method.

Other JSearch operations, such as lexicon searches, use a similar convention for passing options to a specific query or applying them to the entire operation.

For example, the following query uses the query-specific `$exact` option of QBE to disable exact match semantics on the value query constructed with `jsearch.byExample`. However, this setting has no effect on the query constructed by `cts.jsonPropertyValueQuery` or on the top level `cts.orQuery`.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.orQuery([
    jsearch.byExample({author: {$value: 'mark twain', $exact: false}}),
    cts.jsonPropertyValueQuery('author', 'john steinbeck')
  ]))
  .result()
```

The available per-query options depend on the type of query. The mechanism for specifying per-query options depends on the construction method you choose. For details, consult the appropriate API reference.

For example, `cts.jsonPropertyValueQuery` accepts a set of options as parameter. through these options you can control attributes such as whether or not to enable stemming:

```
cts.jsonPropertyValueQuery(
  'author', 'mark twain', ['case-insensitive', 'lang=en'])
```

Options that can apply to the entire search are specified using the `withOptions` method. For example, you can use `withOptions` to pass options to the underlying `cts.search` operation of a documents search:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.jsonPropertyValueQuery('author','mark twain'))
  .withOptions({search: ['format-xml','score-logtf']})
  .result()
```

For more details, see the following methods:

- `DocumentsSearch.withOptions`
- `ValuesSearch.withOptions`

- `TuplesSearch.withOptions`
- `WordsSearch.withOptions`
- `FacetsSearch.withOptions`
- `FacetDefinition.withOptions`

Note that, specifically in the case of passing options through to `cts.search`, some commonly used options are surfaced directly through JSearch methods, such as the `DocumentsSearch.filter` method. You should use the JSearch mechanism when this overlap is present.

7.11 Transforming Results with Map and Reduce

The top level JSearch query options such as documents, values, tuples, and words include map and reduce methods you can use to tailor the final results in a variety of ways, such as including snippets in a document search or applying a content transformation.

This section includes the following topics:

- Map and Reduce Overview
- Configuring the Built-In Mapper
- Using a Custom Mapper
- Configuring the Built-In Reducer
- Using a Custom Reducer
- Example: Using a Custom Mapper for Content Transformation
- Example: Custom Reducer For Document Search
- Example: Custom Reducer For Values Query

7.11.1 Map and Reduce Overview

The top level JSearch operations for document search (`documents`) and lexicon queries (`values`, `tuples`, and `words`) include `map` and `reduce` methods for customizing your query results. You can choose to use either `map` or `reduce`, but not both.

A mapper takes in a single value and produces zero results or one result. The mapper is invoked once for each item (search result, value, or tuple) processed by the query operation. The output from the mapper is pushed on to the results array. A mapper is well suited for applying transformations to results.

In broad strokes, a reducer takes in a previous result and a single value and returns either an item to pass to next invocation of the reducer, or a final result. The output from the final invocation becomes the result. Reducers are well suited for computing aggregates over a set of results.

You can supply a custom mapper or reducer by passing a function reference to the `map` or `reduce` method. Some operations also have a built-in mapper and/or reducer that you can invoke by passing a configuration object in to the `map` or `reduce` method. For example, the built-in mapper for document search can be used to generate snippets.

Thus, your `map` or `reduce` call can have one of the following forms:

```
// configure the built-in mapper, if supported
.map({configProperties...})

// use a custom mapper
.map(function (currentItem) {...})

// configure the built-in reducer, if supported
.reduce({configProperties...})

// use a custom reducer
.reduce(function (prevResult, currentItem, index, state) {...})
```

The available configuration properties and behavior of the built-in mapper and reducer depend on the operation you apply map or reduce to. For details, see "Configuring the Built-In Mapper" on page 332.

The following methods support map and reduce operations. For configuration details, see the *MarkLogic Server-Side JavaScript Function Reference*.

- `DocumentsSearch.map` and `DocumentsSearch.reduce`
- `FacetDefinition.map` and `FacetDefinition.reduce`
- `ValuesSearch.map` and `ValuesSearch.reduce`
- `TuplesSearch.map` and `TuplesSearch.reduce`
- `WordsSearch.map` and `WordsSearch.reduce`

7.11.2 Configuring the Built-In Mapper

The capabilities of the built-in mapper vary, depending on the type of query operation (`documents`, `values`, or `tuples`). For example, the built-in mapper for a document search can be configured to generate snippets and document projections, while the built-in mapper on a values query can be configured to include frequency values in the results.

Configure the built-in mapper by passing a configuration object to the `map` method instead of a function reference. For example, the following call chain configures the built-in mapper for document search to return snippets:

```
jsearch.documents().map({snippet:true}).result()
```

The table below outlines the capabilities of the built-in mapper for each JSearch query operation.

Operation	Built-In Mapper Capabilities
`documents`	Generation of snippets, document projections, and/or URIs for similar documents. For details, see "Including Snippets of Matching Content in Search Results" on page 320, "Extracting Portions of Each Matched Document" on page 325, and `DocumentsSearch.map` in the *MarkLogic Server-Side JavaScript Function Reference*.
`values`	Control and generation of frequency data in the results. Optionally, add labels to returned values and frequencies. For details, see `ValuesSearch.map` in the *MarkLogic Server-Side JavaScript Function Reference*.
`tuples`	Control and generation of frequency data in the results. Optionally, adds labels to returned tuples and frequencies. For details, `TuplesSearch.map` in the *MarkLogic Server-Side JavaScript Function Reference*.
`words`	None. The `words` operation only supports a custom mapper.

7.11.3 Using a Custom Mapper

You can supply a custom mapper to the map method of the `documents`, `values`, `tuples`, and `words` queries. To use a custom mapper, pass a function reference to the `map` method in your query call chain:

```
... .map(funcRef)
```

The mapper function must have the following signature and should produce either no result or a single result. If the function returns a value, it is pushed on to the final results array or iterator.

```
function (currentItem)
```

The *`currentItem`* parameter can be a search result, tuple, value, or word, depending on the calling context. For example, the mapper on a document search (the `documents` method) takes a single search result descriptor as input.

Any value returned by your mapper is pushed on to the "results" array.

The following example uses a custom mapper on a document search to add a property named "iWasHere" to each search result. The input in this case is the search result for one document.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.jsonPropertyValueQuery('author','Mark Twain'))
  .map(function (value) {value.iWasHere = true; return value;})
```

```
  .result()

==>
{"results":[
   {"index":0,
    "uri":"/books/twain4.json",
    "score":14336,
    "confidence":0.3745157122612,
    "fitness":0.7490314245224,
    "document":{...},
    "iWasHere":true
   },
   {"index":1, ...},
   ...
  ],
  "estimate":4
}
```

Your mapper is not required to return a value. If you return nothing or explicitly return `undefined`, then the final results will contain no value corresonding to the current input item. For example, the following mapper eliminates every other search result:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .map(function (value) {
    if (value.index % 2 > 0) {
      return value;
    }
  })
  .result().results.length
```

If your database that contains only the documents from "Preparing to Run the Examples" on page 362, then the script should produce the answer 4 when run in Query Console.

For an additional example, see "Example: Using a Custom Mapper for Content Transformation" on page 336.

7.11.4 Configuring the Built-In Reducer

The capabilities of the built-in reducer vary, depending on the type of query operation. Currently, only `values` offers a built-in reducer.

Configure the built-in reducer by passing a configuration object to the `reduce` method instead of a function reference. For example, the following configures the built-in reducer for a values query to return item frequency data along with the values:

```
jsearch.values('price').reduce({frequency: 'item'}).result()
```

The table below outlines the capabilities of the built-in reducer for each JSearch query operation.

Operation	Built-In Reducer Capabilities
`documents`	None. The `documents` operation only supports a custom reducer.
`values`	Control and generation of frequency data in the results. Optionally, adds labels to returned values and frequencies. For details, see `ValuesSearch.reduce` in the *MarkLogic Server-Side JavaScript Function Reference*.
`tuples`	None. The `tuples` operation only supports a custom reducer.
`words`	None. The `words` operation only supports a custom reducer.

7.11.5 Using a Custom Reducer

To use a custom reducer, pass a function reference and optional initial seed value to the `reduce` method of your query call chain:

```
... .reduce(funcRef, seedValue)
```

The reducer function must have the following signature:

```
function (prevResult, currentItem, index, state)
```

If you pass a seed value, it becomes the value of *`prevResult`* on the first invocation of your function. For example, the following reduce call seeds an accumulator object with initial values. On the first call to `myFunc`, *`prevResult`* contains `{count: 0, value: 0, matches: []}`.

```
... .reduce(myFunc, {count: 0, value: 0, matches: []}) ...
```

For example, the following call chain uses a custom mapper with an initial seed value as part of a document search.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.jsonPropertyValueQuery('author','Mark Twain'))
  .reduce(function (prev, match, index, state) {
    // do something
  }, {count: 0, value: 0, matches: []})
  .result()
```

The value returned by the last invocation of your reducer becomes the final result of the query. You can detect or signal the last invocation through `state.isLast`.

The following table describes the inputs to the reducer function:

Parameter	Description
prevResult	The value returned by the previous invocation of your function during this reduction. If a seed value is passed to `reduce`, then the seed is the value of *prevResult* on the first invocation. Otherwise, *prevResult* is null on the first invocation.
currentItem	The current value to act upon. The structure of the value depends on the calling context: • word: The current word. • documents: The search result object. • values: The current value. • tuples: The current n-way co-ocurrence tuple.
index	The zero-based index of the *currentItem* in the set of items being iterated over.
state	An object describing the state of the reduction. It contains an `isLast` property that is true only if this is the last invocation of the reducer for this reduction. You can explicitly set `isLast` to true to force early termination.

Note that the `map` and `reduce` methods are exclusive of one another. If your query uses `reduce`, it cannot use `map`.

For more examples, see the following:

- “Example: Custom Reducer For Document Search” on page 338
- “Example: Custom Reducer For Values Query” on page 340

7.11.6 Example: Using a Custom Mapper for Content Transformation

The following example demonstrates using a custom mapper to transform document content returned by a search. For more details, see “Using a Custom Mapper” on page 333 and `DocumentsSearch.map`.

The following example code uses a custom mapper to redact the value of the JSON property “author” in each document matched by the search.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.jsonPropertyValueQuery('format','paperback'))
```

```
  .slice(0,2)
  .map(function (match) {
    match.document = match.document.toObject();
    match.document.author = 'READACTED';
    return match;
  })
  .result()
```

Each time the mapper is invoked, the "author" property value is changed to "REDACTED" in the document embedded in the search result. Notice the application of `toObject` to the document:

```
match.document = match.document.toObject();
```

This is necessary because `match.document` is initially a read-only document node. Applying `toObject` to the document node creates an in-memory, mutable copy of the contents.

If your database contains the documents created by "Preparing to Run the Examples" on page 362, then running the script produces output similar to the following. The part of each result affected by the mapper is shown in bold. Only two results are returned because of the `slice`(0,2) clause on the search.

```
{ "results": [
    { "index": 0,
      "uri": "/books/frost1.json",
      "score": 14336,
      "confidence": 0.43245348334312,
      "fitness": 0.7490314245224,
      "document": {
        "title": "Collected Works",
        "author": "REDACTED",
        "edition": {
          "format": "paperback",
          "price": 29.99
        },
        "synopsis": "The complete works of the American Poet
                     Robert Frost."
      }
    },
    { "index": 1,
      "uri": "/books/steinbeck1.json",
      "score": 14336,
      "confidence": 0.43245348334312,
      "fitness": 0.7490314245224,
      "document": {
        "title": "The Grapes of Wrath",
        "author": "REDACTED",
        "edition": {
          "format": "paperback",
          "price": 9.99
        },
        "synopsis": "Chronicles the 1930s Dust Bowl migration of
                     one Oklahoma farm family, from their homestead
```

```
                        and forced to the promised land of California."
        }
      }
    ],
    "estimate": 4
}
```

7.11.7 Example: Custom Reducer For Document Search

The following example demonstrates using `DocumentsSearch.reduce` to apply a custom reducer as part of a document search.

The search selects a random sample of 1000 documents by setting the search scoring algorithm to "score-random" in `withOptions`. and the slice size to 1000 with `slice`. Notice that there is no `where` clause, so the search matches all documents in the database.

The following code snippet is the core search that drives the reduction:

```
jsearch.documents()
  .slice(0, 1000)
  .reduce(...)
  .withOptions({search: 'score-random'})
  .result();
```

The reducer iterates over the node names (JSON property names or XML element names) in each document, adding each name to a map, along with a corresponding counter.

```
function nameExtractor(previous, match, index, state) {
  var nameCount = 0;
  for (var name of match.document.xpath('//*/fn:node-name(.)')) {
    nameCount = previous[name];
    previous[name] = (nameCount > 0) ? nameCount + 1 : 1;
  }
  return previous;
  }
```

Each time the reducer is invoked, the `match` parameter contains the search result for a single document. That is, input of the following form. The precise properties in the input object can vary somewhat, depending on the search options.

```
{ index: 0,
  uri: '/my/document/uri',
  score: 14336,
  confidence: 0.3745157122612,
  fitness: 0.7490314245224,
  document: { documentContents }
}
```

The following code puts all of the above together in a complete script. Notice that an empty object ({ }) is passed to reduce as a seed value for the initial value of the `previous` input parameter.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .slice(0, 1000)
  .reduce(function nameExtractor(previous, match, index, state) {
      var nameCount = 0;
      for (var name of match.document.xpath('//*/fn:node-name(.)')) {
        nameCount = previous[name];
        previous[name] = (nameCount > 0) ? nameCount + 1 : 1;
      }
      return previous;
    }, {})
  .withOptions({search: 'score-random'})
  .result();
```

Running this script with the documents created by “Preparing to Run the Examples” on page 362 produces output similar to the following.

```
{"results":{
   "title":8,
   "author":8,
   "edition":8,
   "format":8,
   "price":8,
   "synopsis":8
 },
 "estimate":8}
```

The property names are the JSON property names found in the sample documents. The property values are the number of ocurrences of each name in the sampled documents. The values in this case are all the same because all the sample documents contain exactly the same properties. However, if you run the query on a less homogeneous set of documents you might get results such as the following:

```
{"results":{
    "Placemark":52,
    "name":53,
    "Style":52,
    "ExtendedData":52,
    "SimpleData":208,
    "Polygon":574,
    "coordinates":610,
    "MultiGeometry":24,
  },
  "estimate":58
}
```

If you want to retain the search results along with whatever computation is performed by your reducer, you must accumulate them yourself. For example, the reducer in the following script accumulates the results in an array in the result object:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.documents()
  .where(cts.jsonPropertyValueQuery('author','Mark Twain'))
  .reduce(function (prev, match, index, state) {
    prev.count++;
    prev.value += match.document.edition.price;
    prev.matches.push(match);
    if (state.isLast) {
      return {avgCost: prev.value / prev.count, matches: prev.matches};
    } else {
      return prev;
    }
  }, {count: 0, value: 0, matches: []})
  .result()
```

When run against the sample data from “Preparing to Run the Examples” on page 362, the output is similar to the following:

```
{"results":{
    "avgCost": 13.25,
    "matches": [{"index":0, "uri": ...}, ...more matches...]
  },
  estimate: 4
}
```

7.11.8 Example: Custom Reducer For Values Query

This example demonstrates using `ValuesSearch.reduce` to apply a custom reducer that computes an aggregate value from the results of a values query. The example relies on the sample data from “Preparing to Run the Examples” on page 362.

The query that produces the inputs to the reduction is a values query over the `price` JSON property. The database configuration should include a range index over `price` with scalar type `float`. The scalar type of the index determines the datatype of the value passed into the second parameter of the reducer.

The following code computes an average of the values of the `price` JSON property. Each call to the reducer accumulates the count and sum contributing to the final answer. When `state.isLast` becomes true, the final aggregate value is computed and returned. The reduction is seeded with an initial accumulator value of `{count: 0, sum: 0}`, through the second parameter passed to `reduce`.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')
  .where(cts.directoryQuery('/books/'))
  .reduce(function (accum, value, index, state) {
```

```
    var freq = cts.frequency(value);
    accum.count += freq;
    accum.sum += value * freq;
    return state.isLast ? (accum.sum / accum.count) : accum;
  }, {count: 0, sum: 0})
.result();
```

If you run the query in Query Console using the data from "Preparing to Run the Examples" on page 362, you should see output similar to the following:

```
16.125
```

Notice the use of `cts.frequency` in the example. The reducer is called once for each unique value in the index. If you're doing a reduction that depends on frequency, use `cts.frequency` on the input value to get this information.

Average and sum are only used here as a convenient simple example. In practice, if you needed to compute the average or sum, you would use built-in aggregate functions. For details, see "Computing Aggregates Over Range Indexes" on page 349.

7.12 Querying Lexicons and Range Indexes

- Querying the Values in a Lexicon or Index
- Finding Value Co-Occurrences in Lexicons and Indexes
- Querying Values in a Word Lexicon
- Computing Aggregates Over Range Indexes
- Constructing Lexicon and Range Index References

7.12.1 Querying the Values in a Lexicon or Index

Use `jsearch.values` to begin building a query over the values in a values lexicon or range index, and then use `result` to execute the query and return results. You can also use the `values` method to compute aggregates lexicon and index values; for details, see "Computing Aggregates Over Range Indexes" on page 349.

For example, the following code creates a values query over a range index on the "title" JSON property. The returned values are limited to those found in documents matching a directory query (`where`) and those that match the pattern "*adventure*" (`match`). The results are returned in frequency order (`orderBy`). Only the first 3 results are returned (`slice`).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('title')
  .where(cts.directoryQuery('/books/'))
  .match('*adventure*')
  .orderBy('frequency')
```

```
    .slice(0,3)
    .result()
```

This query produces the following output when run against the sample data from “Preparing to Run the Examples” on page 362.

```
["Adventures of Huckleberry Finn", "Adventures of Tom Sawyer"]
```

Your database configuration must include an index or range index on each JSON property, XML element, XML element attribute, field, or path used in a `values` query.

For general information on lexicon queries, see “Browsing With Lexicons” on page 431.

Build and execute your values query following the pattern described in “Query Design Pattern” on page 280. The following table maps the applicable JSearch methods to the steps in the design pattern. Note that all the pipeline stages in Step 2 are optional, but you must use them in the order shown. For more details, see ValuesSearch in the *MarkLogic Server-Side JavaScript Function Reference*.

Pattern Step		Method(s)	Notes
1	Select resource	`values`	Required. Select index and lexicon values as the resource to work with. Supply one or more lexicon or index references or JSON property names as input to `values`.

Pattern Step		Method(s)	Notes
2	Add a query definition and result set pipeline	`where`	Optional. Constrain the set of results (and frequency computation) to values from documents matching a query, as described in "Constraining Lexicon Searches to a cts:query Expression" on page 442. If you pass in multiple queries, they are implicitly AND'd together. You can create a cts.query from a QBE, query text, cts.query constructors, or any other technique that creates a `cts.query`. For details, see "Creating a cts.query" on page 289.

		`match` | `groupInto`	Optional. You cannot use `match` and `groupInto` together. Use `match` to limit values to those matching a wildcard pattern. For example:
			
			`jsearch.values('title')`
			`  .where(cts.directoryQuery('/books/'))`
			`  .match('*adventure*')`
			
			Use `groupInto` to group values into value range buckets. For details and examples, see "Grouping Values and Facets Into Buckets" on page 354.

		`orderBy`	Optional. Specify the order of results. You can choose whether to order by frequency or item value, and ascending or descending order. For details, see "Controlling the Ordering of Results" on page 316
		`slice`	Optional. Select a subset of values from the result set. The default slice is the first 10 values. For details, see "Returning a Result Subset" on page 319.
		`map` | `reduce`	Optional. Apply a mapper or reducer function to the results. You cannot use `map` and `reduce` together. For details, see "Transforming Results with Map and Reduce" on page 331.
3	Add advanced options	`withOptions`	Optional. Specify additional, advanced options that customize the query behavior. For details, see "Using Options to Control a Query" on page 330 and `ValuesSearch.withOptions`.
4	Evaluate the query and get results	`result`	Required. Execute the query and receive your results, optionally specifying whether to receive the results as a value or an iterator. The default is a value (typically an array).

7.12.2 Finding Value Co-Occurrences in Lexicons and Indexes

Use the `jsearch.tuples` method to find co-occurrences of values in lexicons and range indexes. Use `tuples` to begin building your query, and then use `result` to execute the query and return results. You can also use the `tuples` method to compute aggregates over tuples; for details, see "Computing Aggregates Over Range Indexes" on page 349.

For example, the following code creates a tuples query for 2-way co-occurences of the values in the "author" and "format" JSON properties. Only tuples in documents matching the directory query are considered (`where`). The results are returned in item order (`orderBy`).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.tuples(['author','format'])
  .where(cts.directoryQuery('/books/'))
  .orderBy('item')
  .result()
```

This query produces the following output when applied to the data from "Preparing to Run the Examples" on page 362.

```
[["John Steinbeck", "audiobook"], ["John Steinbeck", "hardback"],
 ["John Steinbeck", "paperback"], ["Mark Twain", "hardback"],
 ["Mark Twain", "paperback"], ["Robert Frost", "paperback"]]
```

Your database configuration must include an index or range index on each JSON property, XML element, XML element attribute, field, or path used in a `tuples` query.

Build and execute your tuples query following the pattern described in "Query Design Pattern" on page 280. The following table maps the applicable JSearch methods to the steps in the design pattern. Note that all the pipeline stages in Step 2 are optional, but you must use them in the order shown. For more details, see TuplesSearch in the *MarkLogic Server-Side JavaScript Function Reference*.

Pattern Step		Method(s)	Notes
1	Select resource	`tuples`	Required. Select index and lexicon value co-occurrences as the resource to work with. Supply one or more lexicon or index references or JSON property names as input to `values`.
2	Add a query definition and result set pipeline	`where`	Optional. Constrain the set of tuples (and frequency computation) to values in documents matching a query, as described in "Constraining Lexicon Searches to a cts:query Expression" on page 442. If you pass in multiple queries, they are implicitly AND'd together. You can create a cts.query from a QBE, query text, cts.query constructors, or any other technique that creates a `cts.query`. For details, see "Creating a cts.query" on page 289.
		`orderBy`	Optional. Specify the order of results. You can choose whether to order by frequency or item value, and ascending or descending order. For details, see "Controlling the Ordering of Results" on page 316
		`slice`	Optional. Select a subset of tuples from the result set. The default slice is the first 10 tuples. For details, see "Returning a Result Subset" on page 319.
		`map	reduce`	Optional. Apply a mapper or reducer function to the results. You cannot use `map` and `reduce` together. For details, see "Transforming Results with Map and Reduce" on page 331.
3	Add advanced options	`withOptions`	Optional. Specify additional, advanced options that customize the query behavior. For details, see "Using Options to Control a Query" on page 330 and `TuplesSearch.withOptions`.
4	Evaluate the query and get results	`result`	Required. Execute the query and receive your results, optionally specifying whether to receive the results as a value or an iterator. The default is a value (typically an array).

7.12.3 Querying Values in a Word Lexicon

Use the `jsearch.words` method to create a word lexicon query, and then use `result` to execute the query and return results.

For example, the following code performs a word lexicon query for all words in the `synopsis` JSON property that begin with 'c' (`match`). Only occurrences in documents where the `author` property contains "steinbeck" (`where`) are returned. At most the first 5 words are returned (`slice`).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.words('synopsis')
  .where(cts.jsonPropertyWordQuery('author', 'steinbeck'))
  .match('c*')
  .slice(0,5)
  .result();
```

When run against the data from "Preparing to Run the Examples" on page 362, this query produces the following output:

```
["Cain", "California", "Chronicles"]
```

Your database configuration must either enable the database-wide word lexicon or include a word lexicon on each JSON property, XML element, XML element attribute, or field used in a `words` query. For details on lexicon configuration, see Range Indexes and Lexicons in the *Administrator's Guide*.

For general information on lexicon queries, see "Browsing With Lexicons" on page 431.

Build and execute your word query following the pattern described in “Query Design Pattern” on page 280. The following table maps the applicable JSearch methods to the steps in the design pattern. Note that all the pipeline stages in Step 2 are optional, but you must use them in the order shown. For more details, see WordsSearch in the *MarkLogic Server-Side JavaScript Function Reference*.

Pattern Step		Method(s)	Notes

1	Select resource	`words`	Required. Select index and word lexicons as the resource to work with. Supply one or more lexicon or index references or JSON property names as input to `values`. For example:
			
			`// query word lexicon on a JSON property`
			`jsearch.words('synopsis'). ...`
			
			`// query the database wide word lexicon`
			`jsearch.words(jsearch.databaseLexicon()).`
			`...`
			
			`// query the word lexicon on an XML element`
			`jsearch.words(`
			`  jsearch.elementLexicon(`
			`  fn.QName(`
			`  'http://marklogic.com/example',`
			`  'myElem')))`

Pattern Step		Method(s)	Notes
2	Add a query definition and result set pipeline	`where`	Optional. Constrain the set of tuples (and frequency computation) to words in documents matching a query, as described in "Constraining Lexicon Searches to a cts:query Expression" on page 442. If you pass in multiple queries, they are implicitly AND'd together. You can create a cts.query from a QBE, query text, cts.query constructors, or any other technique that creates a `cts.query`. For details, see "Creating a cts.query" on page 289.

		`match`	Optional. Limit words to those matching a wildcard pattern. For example, the following match clause selects words beginning with 'c':
			
			`var jsearch =`
			`  require('/MarkLogic/jsearch.sjs');`
			`jsearch.words('synopsis')`
			`  .where(cts.directoryQuery('/books/'))`
			`  .match('c*')`

		`orderBy`	Optional. Specify whether to list the results in ascending or descending order. For details, see "Controlling the Ordering of Results" on page 316
		`slice`	Optional. Select a subset of tuples from the result set. The default slice is the first 10 results. For details, see "Returning a Result Subset" on page 319.
		`map | reduce`	Optional. Apply a mapper or reducer function to the results. You cannot use `map` and `reduce` together. For details, see "Transforming Results with Map and Reduce" on page 331.
3	Add advanced options	`withOptions`	Optional. Specify additional, advanced options that customize the query behavior. For details, see "Using Options to Control a Query" on page 330 and `WordsSearch.withOptions`.
4	Evaluate the query and get results	`result`	Required. Execute the query and receive your results, optionally specifying whether to receive the results as a value or an iterator. The default is a value (typically an array).

7.12.4 Computing Aggregates Over Range Indexes

You can compute aggregate values over range indexes and lexicons using built-in or user-defined aggregate functions using `ValuesSearch.aggregate` or `TuplesSearch.aggregate`. This section covers the following topics:

- Aggregate Function Overview
- Using Built-In Aggregate Functions
- Using Aggregate User-Defined Functions

7.12.4.1 Aggregate Function Overview

An aggregate function performs an operation over values or tuples in lexicons and range indexes. For example, you can use an aggregate function to compute the sum of values in a range index. You can apply an aggregate computation to the results of a values or tuples query using `ValuesSearch.aggregate` or `TuplesSearch.aggregate`.

MarkLogic Server provides built-in aggregate functions for many common analytical functions; for a list of functions, see "Using Built-In Aggregate Functions" on page 351. For a more detailed description of each built-in, see Using Builtin Aggregate Functions in the *Search Developer's Guide*.

You can also implement aggregate user-defined functions (UDFs) in C++ and deploy them as native plugins. Aggregate UDFs must be installed before you can use them. For details, see Implementing an Aggregate User-Defined Function in the *Application Developer's Guide*. You must install the native plugin that implements your UDF according to the instructions in Implementing Native Plugin Libraries in the *Application Developer's Guide*.

> **Note:** You cannot use the JSearch API to apply aggregate UDFs that require additional parameters.

Build and execute your aggregate computation following the pattern described in "Query Design Pattern" on page 280. The following table maps the applicable JSearch methods to the steps in the design pattern. Note that you must use the pipeline stages in Step 2 in the order shown. For more details, see ValuesSearch or TuplesSearch in the *MarkLogic Server-Side JavaScript Function Reference*.

Pattern Step		Method(s)	Notes
1	Select resource	`values | tuples`	Required. Select index and lexicon values or tuples (co-occurrences) as the resource to work with. Supply one or more lexicon or index references or JSON property names as input.
2	Add a query definition and result set pipeline	`where`	Optional. Constrain the values or tuples to values in documents matching a query, as described in "Constraining Lexicon Searches to a cts:query Expression" on page 442. If you pass in multiple queries, they are implicitly AND'd together. You can create a cts.query from a QBE, query text, cts.query constructors, or any other technique that creates a `cts.query`. For details, see "Creating a cts.query" on page 289.
		`aggregate`	Required. Specify one or more built-in or user-defined aggregate functions. You can combine built-in and user-defined aggregates in the same query. For details, see "Using Built-In Aggregate Functions" on page 351 and "Using Aggregate User-Defined Functions" on page 352.
3	Add advanced options	`withOptions`	**Optional. Specify additional, advanced options that customize the query behavior. For details, see "Using Options to Control a Query" on page 330 and `ValuesSearch.withOptions` or `TuplesSearch.withOptions`.**
4	Evaluate the query and get results	`result`	Required. Execute the query and receive your results, optionally specifying whether to receive the results as a value or an iterator. The default is a value (typically an array).

7.12.4.2 Using Built-In Aggregate Functions

To use a builtin aggregate function, pass the name of the function to the `aggregate` method of a values or tuples query. The built-in aggregate functions only support tuples queries on 2-way co-occurrences. That is, you cannot use them on tuples queries involving more than 2 lexicons or indexes.

The following example uses built-in aggregate functions to compute the minimum, maximum, and average of the values in the `price` JSON property and produces the results shown. As with all values queries, the database must include a range index over the target property or XML element.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')
  .aggregate(['min','max','avg'])
  .result();

==> {"min":8, "max":30, "avg":16.125}
```

The following built-in aggregate functions are supported on values queries:

Values Aggregate Name	Description
`avg`	Compute the average of the values in a lexicon or range index. For details, see `cts.avgAggregate`.
`count`	Returns a count of the values in a lexicon or range index. For details, see `cts.countAggregate`.
`max`	Compute the maximum of the values in a lexicon or range index. For details, see `cts.max`.
`min`	Compute the minimum of the values in a lexicon or range index. For details, see `cts.min`.
`stddev`	Compute the frequency-weighted sample standard deviation of the values in a lexicon or range index. For details, see `cts.stddev`.

Values Aggregate Name	Description
`stddev-population`	Compute the frequency-weighted sample standard deviation of the population from the values in a lexicon or range index. For details, see `cts.stddevP`.
`sum`	Compute the sum of the values in a lexicon or range index. For details, see `cts.sumAggregate`.
`variance`	Compute the frequency-weighted sample variance of the values in a lexicon or range index. For details, see `cts.variance`.
`variance-population`	Compute the frequency-weighted variance of population of the values in a lexicon or range index. For details, see `cts.varianceP`.

The following built-in aggregate functions are supported on tuples queries:

Tuples Aggregate Name	Description
`correlation`	Compute the frequency-weighted correlation of 2-way co-occurences. For details, see `cts.correlation`.
`covariance`	Compute the frequency-weighted correlation of 2-way co-occurrences. For details, see `cts.covariance`.
`covariance-population`	Compute the frequency-weighted correlation of the population of 2-way co-occurrences. For details, see `cts.covarianceP`.

7.12.4.3 Using Aggregate User-Defined Functions

An aggregate UDF is identified by the function name and a relative path to the plugin that implements the aggregate, as described in “Using Aggregate User-Defined Functions” on page 451. You must install your UDF plugin on MarkLogic Server before you can use it in a query. For details on creating and installing aggregate UDFs, see User-Defined Functions in the *Application Developer's Guide*.

Once you install your plugin, use `jsearch.udf` to create a reference to your UDF, and pass the reference to the `aggregate` clause of a values or tuples query. For example, the following script uses a native UDF called “count” provided by a plugin installed in the modules database under “native/sampleplugin”:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')
  .aggregate(jsearch.udf('native/sampleplugin', 'count'))
  .result();
```

For more details, see `ValuesSearch.aggregate` and `TuplesSearch.aggregate`.

7.12.5 Constructing Lexicon and Range Index References

This section provides a brief overview of the functions available for constructing the index and lexicon reference you may need for values queries, tuples queries, and facet generation.

Most JSearch interfaces that accept index or lexicon references also accept a simple JSON property name string. In most contexts, this is interpreted as a `cts.jsonPropertyReference` for a string property. If the referenced property (and associated index) have a type other than string, you can create a properly typed index reference as shown in these examples:

```
cts.jsonPropertyReference('price', ['type=float'])
cts.jsonPropertyReference('start', ['type=date'])
```

Similar reference constructors are available for XML element indexes, XML element attribute index, path indexes, field indexes, and geospatial property, element, and path indexes. The following is a small sample of the available constructors:

- `cts.elementReference`
- `cts.field-reference`
- `cts.path-reference`
- `cts.geospatialJsonPropertyReference`

Use the following reference constructors for the database-wide URI and collection lexicons. (These lexicons must be enabled on the database before you can use them.)

- `cts.uriReference`
- `cts.collectionReference`

JSearch also provides the following word lexicon reference constructors for constructing references to word lexicons specifically for use with `jsearch.words`. Using these constructors ensures you only create word lexicons queries on lexicon types that support them.

- `jsearch.databaseLexicon`
- `jsearch.jsonPropertyLexicon`
- `jsearch.elementLexicon`
- `jsearch.elementAttributeLexicon`
- `jsearch.fieldLexicon`

For more details, see the *MarkLogic Server-Side JavaScript Function Reference* and “Browsing With Lexicons” on page 431.

7.13 Grouping Values and Facets Into Buckets

This section covers the following topics related to using the `ValuesSearch.groupInto` and `FacetDefinition.groupInto` to group values by range:

- Bucketing Overview
- Example: Generating Buckets With makeBuckets
- Example: Grouping Using Custom Buckets

7.13.1 Bucketing Overview

You can use the `groupInto` method to group values into ranges when performing a values query or generating facets. Such grouping is sometimes called "bucketed search". The `groupInto` method of `values` and `facets` has the following form:

```
groupInto(bucketDefinition)
```

You can apply `groupInto` to a values query or a facet definition. For example:

```
// using groupInto with a values query
jsearch.values(...).groupInto(bucketDefinition).result()

// using groupInto for facet generation
jsearch.facets(
  jsearch.facet(...).groupInto(bucketDefinition),
  ...more facet definitions...
).result()
```

A bucket definition can be an array of boundary values or an array of alternating bucket names and boundary value pairs. For geospatial buckets, a boundary value can be an object with lat and lon properties (`{lat: latVal, lon: lonVal}`). The JSearch API includes helper functions for creating bucket names (`jsearch.bucketName`), generating a set of buckets from a value range and step (`jsearch.makeBuckets`), and generating buckets corresponding to a geospatial heatmap (`jsearch.makeHeatmap`).

Buckets can be unnamed, use names generated from the boundary values, or use custom names. For example:

```
// Unnamed buckets with boundaries X < 10, 10 <= X < 20, and X > 20
groupInto([10,20])

// The same set of buckets with generated default bucket names
groupInto([
  jsearch.bucketName(),10,
  jsearch.bucketName(),20,
  jsearch.bucketName()])

// The same set of buckets with custom bucket names
```

```
groupInto([
  jsearch.bucketName('under $10'), 10,
  jsearch.bucketName('$10 to $19.99'), 20,
  jsearch.bucketName('over $20')])

// Explictly specify geospatial bucket boundaries
groupInto([
  jsearch.bucketName(),{lat: lat1, lon: lon1,
  jsearch.bucketName(),{lat: lat2, lon: lon2,
  jsearch.bucketName(),{lat: lat3, lon: lon3}])
```

You can create a bucket definition in the following ways:

- Define a set of unnamed buckets by creating an array of boundary values. For example, `[10,20]` defines 3 buckets with boundaries `X < 10`, `10 <= X < 20`, and `X > 20`.
- Define a set of named buckets by creating an array of (*`bucketName`*, *`upperBound`*) pairs. Use the `buckeName` helper function to generate the name of each bucket. You can specify custom bucket names or groupInto generate bucket names from the boundary values.
- Use the `makeBuckets` helper function to create a set of buckets over a range of values (min and max) and a step or number of divisions. For example, create a series of buckets that each correspond to a decade over a 100 year time span.
- Use the `makeHeatMap` helper function to generate buckets from a geospatial lexicon based on a heatmap box with latitude and longitude divisions.

The bounds for bucket for a scalar value or date/time range are determined by an explicit upper bound and the position of the bucket in a set of bucket definitions. For example, in the following custom bucket definition, each line represents one bucket as a name and upper bound.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')
  .groupInto([
    jsearch.bucketName(), 10,
    jsearch.bucketName(), 20,
    jsearch.bucketName()])
  .result()
```

The first bucket has no lower bound because it occurs first. The lower bound of the second bucket is the upper bound of the previous bucket (10), inclusive. The upper bound of the second bucket is 20, exclusive. The last bucket has no upper bound. When plugged into a values or facets query, the results are grouped into the following ranges:

```
x < 10
10 <= x < 20
20 <= x
```

For geospatial data, you can use `makeHeatMap` to sub-divide a region into boxes. For example, the following constraint includes a heat map that corresponds very roughly to the continental United States, and divides the region into a set of 20 boxes (5 latitude divisions and 4 longitude divisions).

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('incidents')
  .groupInto(makeHeatMap({
    north: 49.0,
    east: -67.0,
    south: 24.0,
    west: -125.0,
    lonDivs: 4,
    latDivs: 5
  }))
  .result()
```

When combined with a reducer that returns frequency, you can use the resulting set of boxes and frequencies to illustrate the concentration of points in each box, similar to a grid-based heat map.

You can create more customized geospatial buckets by specifying a series of latitude bounds and longitude bounds that define a grid in an object of the form `{lat:[...], lon:[...]}`. The points defined by the latitude bounds and longitude bounds are divided into box-shaped buckets. The lat and lon values must be ascending order. For example:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('incidents')
  .groupInto({lat: [15, 30, 45, 60, 75], lon: [0, 30, 60, 90, 120]})
  .result()
```

For more details, see `jsearch.makeHeatmap` and `cts:geospatial-boxes`.

7.13.2 Example: Generating Buckets With makeBuckets

The examples in this section demonstrate the following features:

- Using `jsearch.makeBuckets` to generate buckets for a values query.
- Using `jsearch.makeBuckets` to generate bucketed facets.
- Using a custom mapper to decorate your buckets.

The example uses `makeBuckets` to group date information by month, leveraging MarkLogic's built-in support for date, time and duration data..

The example assumes the following conditions exist in the database:

- The database contains documents of the following form describing events. Each document includes a `start` property that represents the start date of the event.

```
{ title: 'San Francisco Ocean Film Festival',
  venue: 'Fort Mason, San Francisco',
  start: '2015-02-27',
  end: '2015-03-01'
}
```

- All the event documents of interest are in a collection with the URI ‘events’.
- The database configuration includes an element range index of type ‘date’ on the `start` proeprty.

The following query groups the values in the lexicon for the year 2015 by month, using `jsearch.makeBuckets` and `ValuesSearch.groupInto`. The results include frequency data in each bucket.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var events = jsearch.collections('events');
events.values(cts.jsonPropertyReference('start', ['type=date']))
  .groupInto( jsearch.makeBuckets({
    min: xs.date('2015-01-01'),
    max: xs.date('2015-12-31'),
    step: xs.yearMonthDuration('P1M')}))
  .map({frequency: 'item', names: ['bucket', 'count']})
  .result()
```

Notice the use of a 1 month duration (‘P1M’) for the step between buckets. You can use many MarkLogic date, dateTime, and duration operations from Server-side JavaScript. For details, see JavaScript Duration and Date Arithmetic and Comparison Methods in the *JavaScript Reference Guide*.

The query generates results similar to the following:

```
[ {
    "bucket": {
      "minimum": "2015-02-27",
      "maximum": "2015-02-27",
      "lowerBound": "2015-02-01",
      "upperBound": "2015-03-01"
    },
    "count": 1
  },
  {
    "bucket": {
      "minimum": "2015-03-07",
      "maximum": "2015-03-14",
      "lowerBound": "2015-03-01",
      "upperBound": "2015-04-01"
    },
```

```
    "count": 2
  },
  ...
]
```

You can use a custom mapper to name each bucket after the month it covers. Note that plugging in a custom mapper also eliminates the frequency data, so you must add it back in explicitly. The following example mapper adds a month name and count property to each bucket:

```
// For mapping month number to user-friendly bucket name
var months = [
  'January', 'February', 'March',
  'April', 'May', 'June',
  'July', 'August', 'September',
  'October', 'November', 'December'
  ];

// Add a name and count field to each bucket. Use month for name.
function supplementBucket(bucket) {
  // get a mutable copy of the input
  var result = bucket.toObject();
  // Compute index into month names. January == month 1 == index 0.
  var monthNum = fn.monthFromDate(xs.date(bucket.lowerBound)) - 1;

  result.name = months[monthNum];
  result.count = cts.frequency(bucket);
  return result;
};

// Generate buckets and counts
var jsearch = require('/MarkLogic/jsearch.sjs');
var events = jsearch.collections('events');
events.values(cts.jsonPropertyReference('start', ['type=date']))
  .groupInto(jsearch.makeBuckets({
    min: xs.date('2015-01-01'),
    max: xs.date('2015-12-31'),
    step: xs.yearMonthDuration('P1M')}))
  .map(supplementBucket)
  .result()
```

The output generated is similar to the following:

```
[ {
    "minimum": "2015-02-27",
    "maximum": "2015-02-27",
    "lowerBound": "2015-02-01",
    "upperBound": "2015-03-01",
    "name": "February",
    "count": 1
  }, {
    "minimum": "2015-03-07",
    "maximum": "2015-03-14",
    "lowerBound": "2015-03-01",
```

```
      "upperBound": "2015-04-01",
      "name": "March",
      "count": 2
    }, ...
]
```

Similarly, you can use the `FacetDefinition.groupInto` and `FacetDefinition.map` when generating facets for a document search with `jsearch.facets`. For example, the following query generates facets based on the same set of buckets:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
var events = jsearch.collections('events');
events.facets(
  events.facet('events', cts.jsonPropertyReference('start', ['type=date']))
    .groupInto(jsearch.makeBuckets({
      min: xs.date('2015-01-01'),
      max: xs.date('2015-12-31'),
      step: xs.yearMonthDuration('P1M')}))
    .map(supplementBucket),
    events.documents()
  ).result()
```

The output from this query is similar to the following:

```
{"facets": {
  "events": [ {
    "minimum": "2015-02-27",
    "maximum": "2015-02-27",
    "lowerBound": "2015-02-01",
    "upperBound": "2015-03-01",
    "name": "February",
    "count": 1
  }, {
    "minimum": "2015-03-07",
    "maximum": "2015-03-14",
    "lowerBound": "2015-03-01",
    "upperBound": "2015-04-01",
    "name": "March",
    "count": 2
  }, ...
  ]},
  "documents": [ ...]
}
```

For more details on faceting, see “Including Facets in Search Results” on page 296.

7.13.3 Example: Grouping Using Custom Buckets

This example demostrates how to use custom buckets for grouping. The example applies the grouping to facet generation, but you can use the same technique with a values query.

The following code defines custom buckets that group the values of the 'price' JSON property into 3 price range buckets.

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.facets(
  jsearch.facet('Price','price')
    .groupInto([
      jsearch.bucketName('under $10'), 10,
      jsearch.bucketName('$10 to $19.99'), 20,
      jsearch.bucketName('over $20')
    ]))
  .where(cts.directoryQuery('/books/'))
  .result();
```

If the lexicon contains the values `[8, 9, 10, 16, 18, 20, 30]`, then the query results in the following output. (Comments were added for clarity and are not part of the actual output.)

```
{"facets": {
  "price": {
    "under $10": {          // bucket label (for display purposes)
      "value": {
        "minimum": 8,       // min value found in bucket range
        "maximum": 9,       // max value found in bucket range
        "upperBound": 10    // bucket upper bound
      },
      "frequency": 2
    },
    "$10 to $19.99": {
      "value": {
        "minimum": 10,
        "maximum": 18,
        "lowerBound": 10,
        "upperBound": 20
      },
      "frequency": 4
    },
    "over $20": {
      "value": {
        "minimum": 20,
        "maximum": 30,
        "lowerBound": 20
      },
      "frequency": 2
    }
  }
} }
```

The results tell you, for example, that the `price` lexicon contains values under 10, with the maximum value in that range being 9 and the minimum being 8. Similarly, the lexicon contains values greater than or equal to 10, but less than 20. The minimum value found in that range is 10 and the maximum value is 18.

If you use the same grouping specification with `ValuesSearch.groupInto`, you get the same information, but it is arranged slightly differently. For example, the following output was produced using the `values` operation with the same `groupInto` clause.

```
[ {
    "minimum": 8,
    "maximum": 9,
    "upperBound": 10,
    "name": "under $10"
  }, {
    "minimum": 10,              // min value found in bucket range
    "maximum": 18,              // max value found in bucket range
    "lowerBound": 10,           // bucket lower bound
    "upperBound": 20,           // bucket upper bound
    "name": "$10 to $19.99"     // bucket label (for display purposes)
  }, {
    "minimum": 20,
    "maximum": 30,
    "lowerBound": 20,
    "name": "over $20"
} ]
```

If you specify an empty bucket name, a default name is generated from the bucket bounds. For example, the following code applies a similar set of buckets to a values query, using generated bucket names:

```
var jsearch = require('/MarkLogic/jsearch.sjs');
jsearch.values('price')
  .where(cts.directoryQuery('/books/'))
  .groupInto([
    jsearch.bucketName(), 10,
    jsearch.bucketName(), 20,
    jsearch.bucketName()
    ])
  .result();
```

This code produces the following output. The bucket min, max, and bounds are the same as before, but the bucket names are the default generated ones:

```
[ {
    "minimum": 8,
    "maximum": 9,
    "upperBound": 10,
    "name": "x < 10"
  }, {
    "minimum": 10,
    "maximum": 19,
    "lowerBound": 10,
    "upperBound": 20,
    "name": "10 <= x < 20"
  }, {
    "minimum": 20,
```

```
    "maximum": 30,
    "lowerBound": 20,
    "name": "20 <= x"
} ]
```

7.14 Preparing to Run the Examples

Use the instructions and scripts in this section to set up your MarkLogic environment to run the examples in this chapter. This includes loading the sample documents and configuring your database to have the required indexes and lexicons.

- Configuring the Database
- Loading the Sample Documents

7.14.1 Configuring the Database

This section guides you through creation of a database configured to run the examples in this chapter. Many examples do not require the indexes, and only the word lexicon query examples require a word lexicon. However, this setup will ensure you have the configuration needed for all the examples.

Running the setup scripts below will do the following. The configuration details are summarized in a table at the end of the section.

- Create a database named jsearch-ex with one forest, named jsearch-ex-1, attached.
- Create element range indexes on the `title`, `author`, `format`, and `price` JSON properties found in the sample documents.
- Create an element word lexicon on the title JSON property found in the sample documents.

The instructions below use Query Console and XQuery to create and configure the database. You do not need to know XQuery to use these instructions. However, if you prefer to do the setup manually using the Admin Interface, see the table at the end of this section for configuration details.

Follow this procedure to create and configure the example database.

1. In your browser, navigate to Query Console and authenticate as a user with Admin privileges. For example, navigate to the following URL is MarkLogic is installed on localhost:

   ```
   http://localhost:8000/qconsole
   ```

2. Use the “+” button to create a new, empty script.

3. Select XQuery in the Query Type dropdown.

4. Paste the following in Query Console as the text of the script just created.

```
xquery version "1.0-ml";

(: Create the database and forest :)
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $config := admin:get-configuration()
let $config :=
  admin:database-create(
    $config, "jsearch-ex",
    xdmp:database("Security"),
    xdmp:database("Schemas"))
let $config :=
  admin:forest-create(
    $config, "jsearch-ex-1",
    xdmp:host(), (), (), ())
return admin:save-configuration($config);

(: Attach the forest to the database :)
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $config := admin:get-configuration()
let $config :=
  admin:database-attach-forest(
    $config, xdmp:database("jsearch-ex"),
    xdmp:forest("jsearch-ex-1"))
return admin:save-configuration($config);
```

5. Click the Run button to execute the script. The database and forest are created.

6. Optionally, confirm creation of the database using the Admin Interface. For example, navigate to the following URL:

```
http://localhost:8001
```

7. In Query Console, click "+" to create another new script. Confirm that the Query Type is still XQuery.

8. Paste the following in Query Console as the text of the script just created. This script will create the indexes and lexicons needed by the examples.

```
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
at "/MarkLogic/admin.xqy";

let $title-index := admin:database-range-element-index(
```

```
    "string", "", "title", "http://marklogic.com/collation/",
fn:false())
let $author-index := admin:database-range-element-index(
    "string", "", "author", "http://marklogic.com/collation/",
fn:false())
let $format-index := admin:database-range-element-index(
    "string", "", "format", "http://marklogic.com/collation/",
fn:false())
let $price-index := admin:database-range-element-index(
    "float", "", "price", "", fn:false())
let $config := admin:get-configuration()
let $config :=
  admin:database-add-range-element-index(
    $config, xdmp:database("jsearch-ex"),
    ($title-index, $author-index, $format-index, $price-index))
return admin:save-configuration($config);

import module namespace admin = "http://marklogic.com/xdmp/admin"
at "/MarkLogic/admin.xqy";

let $title-lexicon := admin:database-element-word-lexicon(
    "", "title", "http://marklogic.com/collation/")
let $config := admin:get-configuration()
let $config :=
  admin:database-add-element-word-lexicon(
    $config, xdmp:database("jsearch-ex"),
    ($title-lexicon))
return admin:save-configuration($config);
```

9. Click the Run button. The range indexes and word lexicon are created.

You should now proceed to “Loading the Sample Documents” on page 366.

If you choose to create the example environment manually with the Admin Interface, use the configuration summary below.

Resource	Configuration	
	Setting	Value
Forest	name	jsearch-ex-1
Database	name	jsearch-ex

Resource	Configuration	
	Setting	Value
`title` element range index	type	`string`
	namespace URI	none
	localname	`title`
	collation	`http://marklogic.com/collation/`
	range value positions	`false`
`author` element range index	type	`string`
	namespace URI	none
	localname	`author`
	collation	`http://marklogic.com/collation/`
	range value positions	`false`
`format` element range index	type	`string`
	namespace URI	none
	localname	`format`
	collation	`http://marklogic.com/collation/`
	range value positions	`false`
`price` element range index	type	`float`
	namespace URI	none
	localname	`price`
	range value positions	`false`
`title` element wod lexicon	namespace URI	none
	localname	`title`
	collation	`http://marklogic.com/collation/`

7.14.2 Loading the Sample Documents

After you create and configure the sample database, follow the instructions in this section to load the sample documents.

1. In your browser, navigate to Query Console and authenticate as a user with write privileges for the `jsearch-ex` database. For example, navigate to the following URL is MarkLogic is installed on localhost:

   ```
   http://localhost:8000/qconsole
   ```

2. Use the "+" button to create a new, empty script.

3. Select `JavaScript` in the Query Type dropdown.

4. Select `jsearch-ex` in the Content Source dropdown.

   You will not see it if you have just finished creating and configuring the database and are still using the same Query Console session. If this happen, reload Query Console in your browser to refresh the Content Source list.

5. Paste the following in Query Console as the text of the script just created.

```
var directory = '/books/';
var books = [
  {uri: 'frost1.json',
   data: { title: 'Collected Works', author: 'Robert Frost',
          edition: {format: 'paperback', price: 30 },
          synopsis: 'The complete works of the American Poet Robert
Frost.'
         }},
  {uri: 'twain1.json',
   data: { title: 'Adventures of Tom Sawyer', author: 'Mark Twain',
          edition: {format: 'paperback', price: 9 },
          synopsis: 'Tales of mischief and adventure along the
Mississippi River with Tom Sawyer, Huck Finn, and Becky Thatcher.'
         }},
  {uri: 'twain2.json',
   data: { title: 'Adventures of Tom Sawyer', author: 'Mark Twain',
          edition: {format: 'hardback', price: 18 },
          synopsis: 'Tales of mischief and adventure along the
Mississippi River with Tom Sawyer, Huck Finn, and Becky Thatcher.'
         }},
  {uri: 'twain3.json',
   data: { title: 'Adventures of Huckleberry Finn', author: 'Mark
Twain',
          edition: {format: 'paperback', price: 8 },
            synopsis: 'The adventures of Huck, a boy of 13, and Jim, an
escaped slave, rafting down the Mississippi River in pre-Civil War
America.'
         }},
```

```
  {uri: 'twain4.json',
   data: { title: 'Adventures of Huckleberry Finn', author: 'Mark
Twain',
           edition: {format: 'hardback', price: 18 },
             synopsis: 'The adventures of Huck, a boy of 13, and Jim, an
escaped slave, rafting down the Mississippi River in pre-Civil War
America.'
         }},
  {uri: 'steinbeck1.json',
   data: { title: 'The Grapes of Wrath', author: 'John Steinbeck',
           edition: {format: 'paperback', price: 10 },
           synopsis: 'Chronicles the 1930s Dust Bowl migration of one
Oklahoma farm family, from their homestead and forced to the promised
land of California.'
  }},
  {uri: 'steinbeck2.json',
   data: { title: 'Of Mice and Men', author: 'John Steinbeck',
           edition: {format: 'hardback', price: 20 },
            synopsis: 'A tale of an unlikely pair of drifters who move
from job to job as farm laborers in California, until it all goes
horribly awry.'
  }},
  {uri: 'steinbeck3.json',
   data: { title: 'East of Eden', author: 'John Steinbeck',
           edition: {format: 'audiobook', price: 16 },
          synopsis: 'Follows the intertwined destinies of two California
families whose generations reenact the fall of Adam and Eve and the
rivalry of Cain and Abel.'
  }}
];

books.forEach( function(book) {
  xdmp.eval(
    'declareUpdate(); xdmp.documentInsert(uri, data,
xdmp.defaultPermissions(), ["classics"]);',
    {uri: directory + book.uri, data: book.data}
  );
});
```

6. Click the Run button to execute script. The sample documents are inserted into the database.

7. Optionally, click the Explore button to examine the database contents. You should see 8 JSON documents with URIs such as “/books/frost1.json”.

The jsearch-ex database is now fully configured to support all the samples in this chapter in Query Console. When running the examples, but sure to set the Content Source to `jsearch-ex` and the Query Type to `JavaScript`.

8.0 Search Customization Using Query Options

When you use the XQuery Search API, REST API, or Java API, you can customize and control your searches using query options. This chapter highlights key query option features. The following topics are covered:

- Introduction
- Getting the Default Query Options
- Checking Query Options for Errors
- Constraint Options
- Operator Options
- Return Options
- Searchable Expression Option
- Fragment Scope Option
- Modifying Your Snippet Results
- Extracting a Portion of Matching Documents
- Customizing Search Results with a Decorator
- Other Search Options
- Query Options Examples

For details on the syntax of each option, see “Appendix: Query Options Reference” on page 668.

8.1 Introduction

Query options enable you to control many aspects of content and values searches, including limiting the scope of a search, customizing the string search grammar, defining sort order, and specifying the contents and format of search results.

MarkLogic Server defines a set of default query options that are applied when you do not include custom query options in a search. You can modify the default query options if you are using the REST or Java API. You can override the default options by defining custom query options and apply them to individual searches.

Query options can be specified in XML for all APIs. The REST and Java APIs also support a JSON representation. XML query options are always expressed as a `search:options` element in the following namespace:

```
http://marklogic.com/appservices/search
```

Most search operations in the XQuery, REST and Java APIs accept optional query options, including the following:

- XQuery: The functions `search:search`, `search:resolve`, `search:values`, and `search:parse`
- REST: The `/search`, `/values`, `/keyvalue` services
- Java: Searches performed using the `com.marklogic.client.query.QueryManager` class.

8.2 Getting the Default Query Options

If you do not include any query options in a search operation that accepts them, the default query options are used. You can retrieve the default query options definition using the XQuery or REST APIs.

To retrieve the default query options using XQuery, call `search:get-default-options`.

To retrieve the default query options using REST, make a GET request to `/config/query/default`. For details, see the REST Client API Reference.

8.3 Checking Query Options for Errors

Query options can be fairly complex. The XQuery, REST and Java APIs include mechanisms for checking your query options for errors.

In XQuery, use the function `search:check-options`. This function validates your options and reports any errors it finds. It returns empty if the options are valid. If it finds errors, they are returned in the form of one or more `search:report` nodes.

The REST API can perform an equivalent check when you persist query options through the `/config/query` service. The Java API performs this check when you call `com.marklogic.client.admin.QueryOptionsManager.writeOptions`.

It is a good idea to only use query option validation in development, as it can slow down queries to check the options on every search. You can also set the `debug` option to true in a `search:options` node to return the output of `search:check-options` as part of your response.

A common MarkLogic XQuery design pattern is to add a `$debug` option to your code that defaults to `false`, and when `true`, runs `search:check-options` or adds the `debug` option your query options. Set the `$debug` variable to true for development and false for production.

8.4 Constraint Options

A *constraint* is a mechanism the Search, REST and Java APIs use to define ways of constraining a search based on a slice of the database. Constraints provide the search operation with information about your database and specify how to query against those details of the database.


Constraints are designed to take advantage of range indexes, other configuration objects (such as word lexicons, collection lexicons, and fields) that exist in the database, and the structures of documents in the database (for example, element values, attribute values, words, and so on). Constraints are primarily used for the following purposes:

- To provide a way to specify the constraint in a string query. For information on search parsing and grammar, see "The Default String Query Grammar" on page 66.
- To return information designed to be used in creating facets in an application. For information on facets, see "Constrained Searches and Faceted Navigation" on page 32.
- To enhance search suggestions made by `search:suggest`. For information on search suggestions, see "Search Term Completion" on page 34.

Each constraint is named. The name must be unique across all operators and constraints in your query options and must not contain whitespace. When you specify a constraint as query text in a string query, you use the name as a constraint in the search grammar followed by the constraint *joiner* symbol defined in string query grammar (a colon character [`:`] by default). The joiner string joins the constraint (or the operator) with its value. For example, the following query text:

```
decade:1980s
```

specifies the constraint named `decade` with a value of `1980s`. The following figure shows each portion of the constraint query text:



For more details about the search grammar, see "Automatic Query Text Parsing and Grammar" on page 30 and "The Default String Query Grammar" on page 66.

The following table lists the types of constraints you can build with query options. For more details, see "constraint" on page 674 in the options reference.

<table>
<tr><th>Constraint</th><th>Description</th><th>cts:query Equivalent for constraint</th><th>Lexicon API Equivalent for Facets</th></tr>
<tr><td rowspan="2">value</td><td>Constrains on an element value or on an attribute value or on a field value.</td><td>cts:element-value-query, cts:element-attribute-value-query, cts:field-value-query</td><td>No facets for value constraints.</td></tr>
<tr><td colspan="3">Example value constraint:

<pre>
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="my-value">
    <value>
      <element ns="my-namespace" name="my-localname"/>
    </value>
  </constraint>
</options>
</pre>
For more details, see "Value Constraint Example" on page 376 and "value" on page 683.</td></tr>
<tr><td rowspan="2">word</td><td>Constrains on a word-query of either element, attribute, or field.</td><td>cts:element-word-query, cts:element-attribute-word-query, cts:field-word-query</td><td>No facets for word constraints.</td></tr>
<tr><td colspan="3">Example word constraint:

<pre>
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="name">
    <word>
      <element ns="http://authors-r-us.com" name="name"/>
    </word>
  </constraint>
</options>
</pre>
For more details, see "Word Constraint Examples" on page 376 and "word" on page 687 in the options reference.</td></tr>
</table>

<table>
<tr><th>Constraint</th><th>Description</th><th>cts:query Equivalent for constraint</th><th>Lexicon API Equivalent for Facets</th></tr>
<tr><td rowspan="2">collection</td><td>Requires the collection lexicon to be enabled in the database.</td><td>cts:collection-query</td><td>cts:collections</td></tr>
<tr><td colspan="3">Example collection constraint:

<pre><options xmlns="http://marklogic.com/appservices/search">
  <constraint name="subject">
    <collection prefix="/my-collections/"/>
  </constraint>
</options></pre>
For more details, see “Collection Constraint Example” on page 377 and “collection” on page 691 in the options reference.</td></tr>
<tr><td>range</td><td>Requires the underlying range index to exist in the database. All range constraints are type aware for the element or attribute values or for the field values, and the constraint can optionally include either bucket or computed-bucket elements. For examples, see “Bucketed Range Constraint Example” on page 378, “Buckets Example” on page 60, “Computed Buckets Example” on page 62. and the search:search options node description in the MarkLogic XQuery and XSLT Function Reference.</td><td>The lexicon APIs, such as cts:element-range-query, cts:element-attribute-range-query, cts:path-range-query, and cts:field-range-query</td><td>cts:element-values, cts:element-attribute-values, cts:values, cts:field-values, cts:element-value-ranges, cts:element-attribute-value-ranges, cts:value-ranges, cts:values cts:field-value-ranges</td></tr>
</table>

<table>
<tr><th>Constraint</th><th>Description</th><th>cts:query Equivalent for constraint</th><th>Lexicon API Equivalent for Facets</th></tr>
<tr><td rowspan="2">container</td><td>Restricts qtext to a particular XML element or JSON property. Requires position indexes enabled on the database for the best performancce.</td><td>cts:element-query</td><td>No facets for container constraints.</td></tr>
<tr><td colspan="3">Example element-query constraint:

<pre>
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="sample-element-constraint">
    <container>
      <element name="title" ns="http://my/namespace" />
    </container>
  </constraint>
</options>
</pre></td></tr>
<tr><td rowspan="2">properties</td><td>Finds matches on the corresponding properties documents.</td><td>cts:properties-query</td><td>No facets for properties constraints.</td></tr>
<tr><td colspan="3">Example properties constraint:

<pre>
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="sample-property-constraint">
    <properties />
  </constraint>
</options>
</pre></td></tr>
</table>

<table>
<tr><th>Constraint</th><th>Description</th><th><code>cts:query</code> Equivalent for constraint</th><th>Lexicon API Equivalent for Facets</th></tr>
<tr><td rowspan="2"><code>geo-attr-pair</code>
<code>geo-elem-pair</code>
<code>geo-elem</code>
<code>geo-path</code>
<code>geo-json-propty</code>
<code>geo-json-property-pair</code></td><td>These geospatial constraints find matches on geospatial data. To use as a facet, the <code><constraint></code> element requires a <code><heatmap></code> child; for details, see “Geospatial Constraint Example” on page 380.</td><td><code>cts:element-attribute-pair-geospatial-query</code>
<code>cts:element-pair-geospatial-query</code>
<code>cts:element-geospatial-query</code>
<code>cts:element-child-geospatial-query</code></td><td><code>cts:element-attribute-pair-geospatial-boxes</code>
<code>cts:element-pair-geospatial-boxes</code>
<code>cts:element-geospatial-boxes</code></td></tr>
<tr><td colspan="3">Example <code>geo-*</code> constraints:

<pre>
<options xmlns="http://marklogic.com/appservices/search">
<constraint name="my-geo-attr-pair">
       <!-- Uses cts:element-attribute-pair-geospatial-query, and
       cts:element-attribute-pair-geospatial-boxes for the
       heatmap facet. -->
  <geo-attr-pair>
    <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"
             latdivs="4" londivs="4"/>
    <facet-option>empties</facet-option>
    <parent ns="ns1" name="elem1"/>
    <lat ns="ns2" name="attr2"/>
    <lon ns="ns3" name="attr3"/>
  </geo-attr-pair>
</constraint>
<constraint name="geo-elem-child">
  <geo-elem>
    <parent ns="" name="g-elem-child-parent" />
    <element ns="" name="g-elem-child-point" />
  </geo-elem>
</constraint>
</options>
</pre></td></tr>
<tr><td><code>custom</code></td><td>Create your own type of constraint by implementing your own functions for parsing and for creating facets. For an example, see “Creating a Custom Constraint” on page 40.</td><td>Depends on what your custom code implements</td><td>Depends on what your custom code implements</td></tr>
</table>

Constraints are designed to be fast. When they have facets, they must generate fast and accurate counts and distinct values. Therefore the constraints that allow facets require a range index on the element or attribute on which they apply, or require a particular lexicon to exist in the database. Other constraints (`value` and `word` constraints) do not require any special indexing, and they cannot be used to create facets.

WhenMarkLogic Server parses a constraint in a query (using `search:parse` or `search:search` for example), it looks for the joiner string and then applies the value to the right of the joiner string, parsing the value as a `cts:query`. If the constraint is not defined in your query options and the value is a single search term, then the joiner string is treated as part of the search term. For example:

```
search:parse('unrecognized-constraint:hello')
=>
<cts:word-query qtextref="cts:text"
       xmlns:cts="http://marklogic.com/cts">
   <cts:text>unrecognized-constraint:hello</cts:text>
</cts:word-query>
```

If the constraint is not defined in your query options and the value is quoted text, then the Search API ignores the constraint and the joiner when parsing the query, but saves the original text as an attribute. For example:

```
search:parse('unrecognized-constraint:"hello world"')
=>
<cts:word-query qtextpre="unrecognized-constraint:&quot;"
     qtextref="cts:text" qtextpost="&quot;"
     xmlns:cts="http://marklogic.com/cts">
   <cts:text>hello world</cts:text>
</cts:word-query>
```

The following examples show constraints of the following types:

- Value Constraint Example
- Word Constraint Examples
- Collection Constraint Example
- Bucketed Range Constraint Example
- Exact Match (Unbucketed) Range Constraint Example
- Geospatial Constraint Example

For an example of a custom constraint, see “Creating a Custom Constraint” on page 40.

8.4.1 Value Constraint Example

The following query options define two value constraints: one for an element and one for an attribute.

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="my-value">
    <value>
      <element ns="my-namespace" name="my-localname"/>
    </value>
  </constraint>
  <constraint name="my-attribute-value">
    <value>
      <attribute ns="" name="my-attribute"/>
      <element ns="my-namespace" name="my-localname"/>
    </value>
  </constraint>
</options>
```

Using these constraints, you can use string queries such as the following to use these constraints:

```
my-value:"This is an element value."
my-attribute-value:123456
```

Both parts of the above queries would match the following document:

```
<my-document xmlns="my-namespace">
  <my-localname>This is an element value.</my-localname>
  <my-localname my-attribute="123456"/>
</my-document>
```

For more details, see “value” on page 683 in the options reference.

8.4.2 Word Constraint Examples

The following query options define two word constraints: One for the `<name/>` element in the namespace `http://authors-r-us.com` and one for the field `my-field`. one for a `cts:element-word-query` and one for a `cts:field-word-query`:

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="name">
    <word>
      <element ns="http://authors-r-us.com" name="name"/>
    </word>
  </constraint>
  <constraint name="description">
    <word>
        <field name="my-field"/>
    </word>
  </constraint>
</options>
```

You can create string and structured queries that use these constraints. For example, the following string query uses the `name` constraint.

```
name:raymond
```

When parsed, it becomes a `cts:element-word-query`:

```
<cts:element-word-query>
  <cts:element xmlns:_1="http://authors-r-us.com">
    _1:name
  </cts:element>
  <cts:text>raymond</cts:text>
</cts:element-word-query>
```

This query matches the following document (because a `cts:word-query("raymond")` would match):

```
<my-document xmlns="http://authors-r-us.com">
  <name>Raymond Carver</name>
</my-document>
```

Similarly, the following string query using the `description` constraint parses into a `cts:field-word-query`:

```
description:author
```

This query matches the above document if the `name` element is included in the definition of the field named `my-field`. For details on fields, see Fields Database Settings in the *Administrator's Guide*.

For more details, see "word" on page 687 in the query options reference.

Word constraints can also be used in structured queries. For example, the following structured query is equivalent to the `name:raymond` string query:

```
<search:query xmlns:search="http://marklogic.com/appservices/search">
  <search:word-constraint-query>
    <search:constraint-name>name</search:constraint-name>
    <search:text>raymond</search:text>
  </search:word-constraint-query>
</search:query>
```

For details, see "Searching Using Structured Queries" on page 78.

8.4.3 Collection Constraint Example

The following query options define a collection constraint, which allows you to constrain your search to documents that are in a specified collection.

Note: You must enable the collection lexicon in the database to use collection constraints. If the collection lexicon is not enabled, an exception is thrown when you use a query with a collection constraint.

If you include a `prefix` attribute in the definition of a collection constraint, then the collection name is derived from the `prefix` concatenated with the constraint value.

One use for a collection constraint is to allow faceted navigation based on collections. For example, if you have collections based on subjects (for example, one called `history`, one called `math`, and so on), then you can use a collection constraint to narrow the search to one of the subjects.

```
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="subject">
    <collection prefix="/my-collections/"/>
  </constraint>
</options>
```

Assuming that all documents in your database have collection URIs that begin with the string `/my-collections/` like the following:

```
/my-collections/math
/my-collections/economics
/my-collections/zoology
```

Then the following query text examples will match documents in the corresponding collections:

```
subject:math
subject:economics
subject:zoology
```

If the database contains no documents in the specified collection, then the search returns no matches. For information on collections, see "Collections" on page 536.

You can also use collection constraints in a structured query, using `collection-constraint-query`. For details, see "Searching Using Structured Queries" on page 78.

8.4.4 Bucketed Range Constraint Example

Range constraints operate on typed element, element attribute, or JSON property values that have a corresponding range index in the database. Without the correct range index, queries using range constraints throw a runtime exception.

Range constraint values can match on either all of the individual values for the element, attribute, or key, or on specified *buckets*, which are named ranges of values. There are two types of buckets, specified with the `bucket` and `computed-bucket` elements in the `range` constraint specification. The `bucket` specification takes absolute ranges, and the `computed-bucket` specification takes ranges that are relative to a given time. For more information about `computed-bucket` range constraints, see "Computed Buckets Example" on page 62.

The following example uses `search:parse` with query options that define a `bucket` range constraint.

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

search:parse('decade:1980s',
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="decade">
    <range type="xs:gYear" facet="true">
      <bucket lt="1930" ge="1920" name="1920s">1920s</bucket>
      <bucket lt="1940" ge="1930" name="1930s">1930s</bucket>
      <bucket lt="1950" ge="1940" name="1940s">1940s</bucket>
      <bucket lt="1960" ge="1950" name="1950s">1950s</bucket>
      <bucket lt="1970" ge="1960" name="1960s">1960s</bucket>
      <bucket lt="1980" ge="1970" name="1970s">1970s</bucket>
      <bucket lt="1990" ge="1980" name="1980s">1980s</bucket>
      <bucket lt="2000" ge="1990" name="1990s">1990s</bucket>
      <bucket ge="2000" name="2000s">2000s</bucket>
      <facet-option>limit=10</facet-option>
      <attribute ns="" name="year"/>
      <element ns="http://marklogic.com/wikipedia" name="nominee"/>
    </range>
  </constraint>
</options>)
```

This query returns the following `cts:query`:

```
<cts:and-query qtextconst="decade:1980s"
    xmlns:cts="http://marklogic.com/cts">
  <cts:element-attribute-range-query qtextconst="decade:1980s"
      operator="&gt;=">
    <cts:element xmlns:_1="http://marklogic.com/wikipedia">
     _1:nominee</cts:element>
    <cts:attribute>year</cts:attribute>
    <cts:value xsi:type="xs:gYear"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    1980</cts:value>
  </cts:element-attribute-range-query>
  <cts:element-attribute-range-query qtextconst="decade:1980s"
    operator="&lt;">
    <cts:element xmlns:_1="http://marklogic.com/wikipedia">
     _1:nominee</cts:element>
    <cts:attribute>year</cts:attribute>
    <cts:value xsi:type="xs:gYear"
     xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
     1990</cts:value>
  </cts:element-attribute-range-query>
</cts:and-query>
```

See the Oscars sample application that you generate from Application Builder for sample data against which you can run this query. For other range constraint examples, see "Buckets Example" on page 60 and "Computed Buckets Example" on page 62, and the following example.

For syntax details, see "bucket" on page 727 of the query options appendix.

8.4.5 Exact Match (Unbucketed) Range Constraint Example

The following example shows an exact match year range constraint against the Oscars sample application. It returns results that match the year 1964. To see the output, use Query Console to run this query against the Oscars database.

```
xquery version "1.0-ml";

import module namespace search =
  "http://marklogic.com/appservices/search"
  at "/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="year">
   <range type="xs:gYear" facet="true">
   <facet-option>limit=10</facet-option>
   <attribute ns="" name="year"/>
   <element ns="http://marklogic.com/wikipedia"
            name="nominee"/>
   </range>
  </constraint>
</options>
return
search:search("year:1964", $options)
```

You can also try out these query options with the Java and REST APIs. For details, see Apply Dynamic Query Options to Document Searches in the *Java Application Developer's Guide* or Specifying Dynamic Query Options with Combined Query in the *REST Application Developer's Guide*.

8.4.6 Geospatial Constraint Example

The following example shows how to use a geospatial constraint to generate geospatial facets in the form of boxes. For details on these options, see "Appendix: Query Options Reference" on page 668.

Suppose the database contains documents of the following form, describing earthquake events:

```
<event xmlns="http://quakeml.org/xmlns/bed/1.2">
  <time>2015-03-24T09:39:15.500Z</time>
  <latitude>36.5305</latitude>
  <longitude>-98.8456</longitude>
  <depth>8.72</depth>
  <mag>3.4</mag>
```

```
  <magType>mb_lg</magType>
  <id>us10001q5d</id>
  <place>33km ENE of Mooreland, Oklahoma</place>
  <type>earthquake</type>
</event>
```

If you define a geospatial element pair range index on the `/event/latitude` and `/event/longitude` elements, then you can use query options to define an associated constraint that can be used to generate geospatial facets by including a `heatmap` element in the constraint definition.

The `heatmap` element defines a region over which to generate facets, along with the number of latitude and longitude divisions to use in sub-divisions the region into boxes. When you perform a search with the constraint in scope, the search response includes a set of `search:box` elements that give you the frequency of matches in each sub-division. You can use this box data for faceting or heatmap generation.

For example, the following constraint includes a heat map that corresponds very roughly to the continental United States, and divides the region into a set of 20 boxes (5 latitude divisions and 4 longitude divisions):

```
<constraint name="qgeo">
  <geo-elem-pair facet="true">
    <parent ns="http://quakeml.org/xmlns/bed/1.2" name="event"/>
    <lat ns="http://quakeml.org/xmlns/bed/1.2" name="latitude"/>
    <lon ns="http://quakeml.org/xmlns/bed/1.2" name="longitude"/>
    <heatmap s="24.0" n="49.0" e="-67.0" w="-125.0"
             latdivs="5" londivs="4" />
    <facet-option>gridded</facet-option>
  </geo-elem-pair>
</constraint>
```

If you also define an element range index on /event/mag, then the following search finds earthquakes with a magnitude (`mag`) greater than 4.0 within the continental US.

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search" at
"/MarkLogic/appservices/search/search.xqy";

let $options :=
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="qgeo">
    <geo-elem-pair facet="true">
      <parent ns="http://quakeml.org/xmlns/bed/1.2" name="event"/>
      <lat ns="http://quakeml.org/xmlns/bed/1.2" name="latitude"/>
      <lon ns="http://quakeml.org/xmlns/bed/1.2" name="longitude"/>
      <heatmap s="24.0" n="49.0" e="-67.0" w="-125.0"
               latdivs="5" londivs="4" />
      <facet-option>gridded</facet-option>
    </geo-elem-pair>
  </constraint>
```

```
  <constraint name="mag">
    <range type="xs:float" facet="false">
      <element ns="http://quakeml.org/xmlns/bed/1.2" name="mag"/>
    </range>
  </constraint>
  <return-facets>true</return-facets>
</options>
return search:search("mag GT 4", $options)
```

The search response includes the following frequency count per geographic region, based on the geo constraint in the options:

```
<search:boxes name="qgeo">
  <search:box count="3" s="-18.9346" w="-178.4936"
              n="-17.8151" e="-174.9279"/>
  <search:box count="2" s="-48.36" w="-87.3529"
              n="7.6115" e="-81.8738"/>
  <search:box count="8" s="-20.7243" w="-73.0949"
              n="6.8852" e="151.9563"/>
  <search:box count="2" s="36.2665" w="70.65"
              n="36.4086" e="140.0085"/>
  <search:box count="3" s="53.6477" w="160.0923"
              n="53.8233" e="161.7353"/>
</search:boxes>
```

By default, the returned boxes are the smallest box within each grid box that encompasses all the matched documents. To return boxes corresponding to the grid divisions instead, add `<facet-option>gridded</facet-option>` to the geo constraint definition. In this example it results in the following boxes:

```
<search:boxes name="qgeo">
  <search:box count="3" s="-90" w="-180" n="24" e="-125"/>
  <search:box count="2" s="-90" w="-96" n="24" e="-81.5"/>
  <search:box count="8" s="-90" w="-81.5" n="24" e="180"/>
  <search:box count="2" s="34" w="-81.5" n="39" e="180"/>
  <search:box count="3" s="44" w="-81.5" n="90" e="180"/>
</search:boxes>
```

For an example of expression a geospatial constraint in JSON, see “geo-attr-pair” on page 699 and “heatmap” on page 724.

8.5 Operator Options

Search operators enable you to define operators in your string query grammar that provide runtime, user-controlled configuration and search choices. A typical search operator might control sorting, thereby allowing the user to specify the sort order directly in a string query or query text. For details, see “operator” on page 755 in the query options appendix.

For example, the following options XML defines an operator named `sort` that enables you to sort by relevance or by date:

```
<options xmlns="http://marklogic.com/appservices/search">
 <search:operator name="sort">
   <search:state name="relevance">
      <search:sort-order>
         <search:score/>
      </search:sort-order>
   </search:state>
   <search:state name="date">
      <search:sort-order direction="descending" type="xs:dateTime">
         <search:element ns="my-ns" name="date"/>
      </search:sort-order>
      <search:sort-order>
         <search:score/>
      </search:sort-order>
   </search:state>
 </search:operator>
</options>
```

This operator definition in the query options allows you to add text like the following to a string query, and MarkLogic Server will parse the string and sort it according to the operator specification.

```
sort:date


sort:relevance
```

Each operator is named, and the name must be unique across all operators and constraints in your query options. When you specify an operator in a string query, you use the name as an operator in the search grammar followed by the `apply="constraint"` *joiner* string (a colon character [`:`] by default). The joiner string joins the operator (or the constraint) with its value. For example, the following query text:

```
sort:date
```

specifies using the operator named `sort` with a value of `date`. You can also include operator settings in structured queries, using the `operator-state` element. For details, see “operator-state” on page 183.

The following figure shows each portion of the operator query text:



For more details about the search grammar, see "Automatic Query Text Parsing and Grammar" on page 30 and "The Default String Query Grammar" on page 66.

The `search:state` element is a child of the `search:operator` element, and the following options XML elements are allowed as a child of `search:state` element:

- `additional-query`
- `debug`
- `forest`
- `page-length`
- `quality-weight`
- `search-option`
- `searchable-expression`
- `sort-order`
- `transform-results`

Operators use the same syntax as constraints, but control other aspects of the search (for example, the sort order) besides which results are returned.

8.6 Return Options

You can specify a number of options that control what is include in a search response, such as the results returned by the XQuery Search API function `search:search`, a GET request to the `/search` service of the REST API, or the Java API method `com.marklogic.client.query.QueryManager.search`. These include the following boolean options:

- `return-aggregates`
- `return-constraints`
- `return-facets`
- `return-frequencies`
- `return-metrics`
- `return-plan`
- `return-qtext`
- `return-query`
- `return-results`
- `return-similar`
- `return-values`

For details on these and other options, see "Appendix: Query Options Reference" on page 668.

Setting one of these options to `true` includes the specified information in the `search:response` returned by a search. Setting to `false` omits the information from the response. For example, the following specifies to return query statistics and facets in the result, but not to return the search hits:

```
<options xmlns="http://marklogic.com/appservices/search">
   <return-metrics>true</return-metrics>
   <return-facets>true</return-facets>
   <return-results>false</return-results>
</options>
```

Only the needed parts of the response are computed, so if you do not return results (as in the above example) or do not return something else, then the work needed to perform that part of the response is not done, and the search runs faster.

For details on each return option, including their default values, see the `search:search` function documentation in *MarkLogic XQuery and XSLT Function Reference*.

8.7 Searchable Expression Option

Use the `searchable-expression` option to specify what expression to search over and what is returned in the search results. The expression corresponds to the first parameter to `cts:search`, and must be a fully searchable expression. For details on fully searchable expressions, see Fully Searchable Paths and cts:search Operations in *Query Performance and Tuning Guide*.

By default, searches apply to the whole database (`fn:collection()`). In most cases, your `searchable-expression` should search over fragment roots, although searching below fragment roots is allowed.

The following example shows a searchable expression that searches over both `CITATION` elements and `html` elements:

```
<searchable-expression xmlns:xh="http://www.w3.org/1999/xhtml">
    /(xh:html | CITATION)
</searchable-expression>
```

If an expression is not fully searchable, it will throw an `XDMP-UNSEARCHABLE` exception at runtime.

For more details, see "searchable-expression" on page 768 in the query options appendix.

8.8 Fragment Scope Option

You can specify a `fragment-scope` option which controls the fragments over which a search or a constraint operates. A `fragment-scope` can be either `documents` or `properties`. By default, the scope is `documents`. A `fragment-scope` of `documents` searches over documents fragments, and a `fragment-scope` of `properties` searches over properties fragments.

There are two types of `fragment-scope` options: a global fragment scope, which applies to the both the search and any constraints in the search, and a local fragment scope, which applies to a given constraint. A global `fragment-scope` is specified as a child of `<options>`, and a local fragment scope is specified as a child of a `<term>` or a contraint kind (for example, a child of `<range>`, `<value>`, or `<word>`). Any local fragment scope will override the global fragment scope.

A local fragment scope of `properties` on a range constraint with a global fragment scope of `documents` allows you to create a facet on data that is in a properties fragment. For example, the following query returns results from documents and a `dateTime` last-modified facet from the `prop:last-modified` system property:

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
     at "/MarkLogic/appservices/search/search.xqy";

search:search("the",
<options xmlns="http://marklogic.com/appservices/search">
<fragment-scope>documents</fragment-scope>
  <constraint name="last-modified">
    <range type="xs:dateTime">
      <element ns="http://marklogic.com/xdmp/property"
               name="last-modified"/>
      <fragment-scope>properties</fragment-scope>
    </range>
  </constraint>
```

```
  <debug>true</debug>
</options>)
```

Setting fragment scope in a `<term>` definition causes term queries to be evaluated in the specified scope. However, the local fragment scope is ignored under the following conditions:

- The `<term>` definition includes an inline word, value, or range constraint or a reference to another constraint. In this case, the fragment scope of the constraint definition applies.
- The `<term>` definition specifies a custom term processing function using `apply`/`ns`/`at`. In this case, the custom function controls scope.

For more details, see "fragment-scope" on page 746 in the query options appendix.

8.9 Modifying Your Snippet Results

The `transform-results` option enables you to specify options for the *snippet* code for your application. A *snippet* is the search result blurb (an abbreviated and highlighted summary) that typically comes up in search results. A snippet is created by taking the matching search result node and running it through transformation code. The transformation typically displays the portion of the result you want in your results page, perhaps highlighting the query matches and showing some text around it, often discarding the rest of the result. This section describes the following ways to control and modify the snippet results from the Search API:

- Specifying transform-results Options
- Specifying Your Own Code in transform-results

8.9.1 Specifying transform-results Options

By default, the Search API has its own code to take search result matches and transform them into snippets used in the search results. By default, the Search API uses the `apply="snippet"` attribute on the `transform-results` option. Snippets tend to be very application specific, and the built-in `apply="snippet"` option has several parameters that you can control with a `transform-results` options node.

The following is the default `transform-results` options node:

```
<transform-results apply="snippet">
    <per-match-tokens>30</per-match-tokens>
    <max-matches>4</max-matches>
    <max-snippet-chars>200</max-snippet-chars>
    <preferred-matches/>
</transform-results>
```

The following table describes the `transform-results` options when `apply="snippet"`, each of which is configurable at search runtime by specifying your own values for the options. For more details, see "transform-results" on page 782 in the query options appendix.

`transform-results` Child Element	Description
`per-match-tokens`	Maximum number of tokens (typically words) per matching node that surround the highlighted term(s) in the snippet.
`max-matches`	The maximum number of nodes containing a highlighted term that will display in the snippet.
`max-snippet-chars`	Limit total snippet size to this many characters.

`preferred-matches`	Specify zero or more XML elements or JSON properties that the snippet algorithm looks in first to find matches. For example, if you want any matches in the `TITLE` element to take preference, specify `TITLE` as a preferred element as in the following sample:
	`<transform-results apply="snippet">`
	`  <preferred-matches>`
	`  <element ns="" name="TITLE"/>`
	`  </preferred-matches>`
	`</transform-results>`
	For JSON properties, use a `json-property` child element or property. For example:
	`<transform-results apply="snippet">`
	`  <preferred-matches>`
	`  <json-property>title</json-property>`
	`  </preferred-matches>`
	`</transform-results>`

There are also three other built-in snippetting options, which are exposed as attributes on the `transform-results` options node:

- `apply="raw"`
- `apply="empty-snippet"`
- `apply="metadata-snippet"`

Note: The `apply` attribute for the `transform-results` element is only applicable to the `search:search` and `search:resolve` functions; `search:snippet` always uses the default snippitting option of `snippet` and ignores anything specified in the `apply` attribute.

The `apply="raw"` snippetting option looks as follows:

```
<transform-results apply="raw" />
```

The `apply="raw"` option returns the whole node (with *no* highlighting) in the `search:response` output. You can then take the node and do your own transformation on it, or just return it as-is, or whatever else makes sense for your application.

The `apply="empty-snippet"` snippetting option is as follows:

```
<transform-results apply="empty-snippet" />
```

The `apply="empty-snippet"` option returns no result node, but does return an empty `search:snippet` element for each `search:result`. The `search:result` wrapper element does have the information (for example, the URI and path to the node) needed to access the node and perform your own transformation on the matching search node(s), so you can write your own code outside of the Search API to process the results.

The `apply="metadata-snippet"` snippeting option is as follows:

```
<transform-results apply="metadata-snippet">
  <preferred-matches>
    <!-- Specify namespace and localname for elements that exist
         in properties documents -->
    <element ns="http://my.namespace" name="my-local-name"/>
  </preferred-matches>
</transform-results>
```

The `apply="metadata-snippet"` option returns the specified preferred elements from the properties documents. If no `<preferred-matches>` element is specified, then the `metadata-snippet` option returns the `prop:last-modified` element for its snippet, and if the `prop:last-modified` element does not exist, it returns an empty snippet.

8.9.2 Specifying Your Own Code in transform-results

If the default snippet code does not meet your application requirements, you can use your own snippet code to use for a given search.

To specify your own snippet code, use the design pattern described in “Search Customization Via Options and Extensions” on page 34. The function you implement must have a signature compatible with the following signature:

```
declare function search:snippet(
   $result as node(),
   $ctsquery as schema-element(cts:query),
   $options as element(search:transform-results)?
) as element(search:snippet)
```

The Search API will pass the function the result node and the `cts:query` XML representation and your custom function can transform it any way you see fit. An options node that specifies a custom transformation looks as follows:

```
<options xmlns="http://marklogic.com/appservices/search">
  <transform-results apply="my-snippet" ns="my-namespace"
      at="/my-snippet.xqy">
  </transform-results>
</options>
```

You must generate an XML `<search:snippet/>` element, even when producing snippets for JSON documents. You can embed JSON in your generated snippet as text. If you include a `format="json"` attribute in your snippet, the REST, Java, and Node.js client APIs will treat the embedded text as JSON and unquote when returning search results as JSON. For example:

```
declare function my:snippeter(
   $result as node(),
   $ctsquery as schema-element(cts:query),
   $options as element(search:transform-results)?
) as element(search:snippet) {
    element search:snippet {
        attribute format { "json" },
        text {'{"MY":"CUSTOM SNIPPET"}'}
    }
};
```

You can optionally pass additional information into your custom snippeting function by adding extra children to the `transform-results` option. The Search API passes the `transform-results` element into your function, and if you want to use any part of the option, you can write code to parse the option and extract whatever you need from it.

8.10 Extracting a Portion of Matching Documents

This sections explains how to use the `extract-document-data` option to project selected XML elements, XML attributes, and JSON properties out of documents matched by a search. For more details, see “extract-document-data” on page 742 in the query options appendix.

By default, a search returns only the `search:response` result summary. When you use `extract-document-data`, you can embed selected portions of each matching document in the search results or return the selected portions as documents instead in a `search:response`.

The projected contents are specified through absolute XPath expressions in `extract-document-data` and a `selected` attribute that specifies how to treat the selected content.

For example, suppose your database includes the following documents:

XML	JSON
URI: /extract/doc1.xml <root> <a>foo <body> <target>content</target> </body> bar </root>	URI: /extract/doc2.json {"root": { "a": "foo", "body": { "target":"content" }, "b": "bar" }}

Then, if you search for "content" both of the above documents match.

```
search:search("content")
```

If you add the following `extract-document-data` option, the search response includes the projected content in each search result, similar to the way sinippets are returned. Each projection contains only the `target` element or property specified by the option.

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

search:search("content",
  <options xmlns="http://marklogic.com/appservices/search">
    <extract-document-data>
      <extract-path>/root/body/target</extract-path>
    </extract-document-data>
    <search-option>filtered</search-option>
  </options>
)

==>

<search:response snippet-format="snippet" total="2" start="1" ...>
  <search:result index="1" uri="/extract/doc1.xml"
       path="fn:doc(&amp;quot;/extract/doc1.xml&amp;quot;)" ...>
    <search:snippet>...</search:snippet>
    <search:extracted context="fn:doc(&amp;quot;/extract/doc1.xml&amp;quot;)">
      <target>content</target>
    </search:extracted>
  </search:result>
  <search:result index="2" uri="/extract/doc2.json"
       path="fn:doc(&amp;quot;/extract/doc2.json&amp;quot;)" ...>
    <search:snippet>...</search:snippet>
```

```
    <search:extracted format="json" kind="object"
        context="fn:doc("/extract/doc2.json")">
      {"target":"content"}
    </search:extracted>
  </search:result>
  ...
</search:response>
```

Using `extract-document-data` with `search:resolve` has a similar effect. However, if you use the option with `search:resolve-nodes`, you get the projected content as sparse documents instead of a `search:response`. For example:

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

search:resolve-nodes(
  search:parse("content"),
  <options xmlns="http://marklogic.com/appservices/search">
    <extract-document-data>
      <extract-path>/root/body/target</extract-path>
    </extract-document-data>
    <search-option>filtered</search-option>
  </options>
)

==>

(
  <?xml version="1.0" encoding="UTF-8"?>
  <search:extracted context="fn:doc(&amp;quot;/extract/doc1.xml&amp;quot;)"
      xmlns:search="http://marklogic.com/appservices/search">
    <target>content</target>
  </search:extracted>,

  {"context":"fn:doc(\"/extract/doc2.json\")",
   "extracted":[{"target":"content"}]}
)
```

You can specify multiple `extract-path` elements. For paths to XML elements and attributes, namespaces in scope on the `search:options` (or `search:search` for a combined query) can be used for namespace prefix bindings on the path expressions.

The path expressions are limited to the subset of XPath that can be used to create a path range index. For details, see Limitations on Index Path Expressions in the *Administrator's Guide*.

Use the `selected` attribute to specify how to use the content selected by `extract-path` in the returned documents. You can set the attribute to `include` (default), `include-with-ancestors`, `exclude`, or `all`. If you choose anything except `include`, the output for each match is a sparse representation of the original document instead of a document with an `extracted` element or JSON property; see the examples in the table below.

The table below demonstrates how `extract-document-data/@selected` affects the content extracted from the two sample documents.

selected	XML	JSON
include	`<target>content</target>`	`{"target":"content"}`

include-with-ancestors	`<root>`
	`  <body>`
	`  <target>content</target>`
	`  </body>`
	`</root>`
		`{"root":{`
		`  "body":{`
		`  "target":"content"`
		`  }`
		`}}`

exclude	`<root>`
	`  <a>foo</a>`
	`  <body/>`
	`  <b>bar</b>`
	`</root>`
		`{"root":{`
		`  "a":"foo",`
		`  "body":{},`
		`  "b":"bar"`
		`}}`

all	`<root>`
	`  <a>foo</a>`
	`  <body>`
	`  <target>content</target>`
	`  </body>`
	`  <b>bar</b>`
	`</root>`
		`{"root":{`
		`  "a":"foo",`
		`  "body":{`
		`  "target":"content"`
		`  },`
		`  "b":"bar"`
		`}}`

When `selected` is `include` or `include-with-ancestors` and no content for a given search result is matched by the `extract-path` expressions, an `extracted-none` placeholder is returned to preserve the presence of the document in the result list. For example:

```
<search:extracted-none
  context="fn:doc("/extract/doc1.xml&")" ... />

{ "context":"fn:doc(\"/extract/doc2.json\")",
  "extracted-none":null}
```

The Node.js Client API supports `extract-document-data` through the `queryBuilder.extract` method. By default, `DatabaseClient.documents.query` is a multi-document read, so it returns the extracted content as individual documents. You can request a search result summary instead, including the extracted content by using `queryBuilder.withOptions({categories: 'none'})`. For details, see Extracting a Portion of Each Matching Document in the *Node.js Application Developer's Guide*.

The Java Client API supports `extract-document-data` via the `QueryManager.search` and `DocumentManager.search` interfaces. For details on embedding extracted content in the search results, see Extracting a Portion of Matching Documents in the *Java Application Developer's Guide*. For details on retrieving extracted content in document form, see Extracting a Portion of Each Matching Document in the *Java Application Developer's Guide*.

When you use `extract-document-data` with the REST Client API `/v1/search` service, whether the extracted content is returned in the search response or as separate documents depends on the Accept header. A multi-document read returns the extracted content as documents. A simple search returns the extracted content in the search response. For details, see Extracting a Portion of Each Matching Document in the *REST Application Developer's Guide*.

8.11 Customizing Search Results with a Decorator

This section describes how to implement a custom search result *decorator* function to add extra information to the search results for your application. The following topics are covered:

- Understanding Search Result Decorators
- Writing a Custom Search Result Decorator
- Installing a Custom Search Result Decorator
- Using a Custom Search Result Decorator

8.11.1 Understanding Search Result Decorators

When you perform a query, MarkLogic Server returns a `<search:response/>` containing a `<search:result>` for each document or fragment that satisfies your query. You can use a search result decorator to add additional information to the each `<search:result/>`, without changing the basic structure or default contents.

For example, the MarkLogic REST API uses an internal result decorator to add `href`, `mimetype`, and `format` attributes to search results. The following output shows the extended information added by the REST API default decorator:

```
<search:response snippet-format="snippet" total="1" ...>
  <search:result ...
    href="/v1/documents?uri=/docs/example.xml"
    mimetype="text/xml" format="xml">
  ...
```

```
  </search:result>
</search:response>
```

Applications using the XQuery Search API can use custom result decorators to similarly add attributes and elements to a `<search:result/>`.

> **Note:** Users of the REST API and Java API should use search result transformations to modify search results, rather than result decorators. It is possible to override the builtin REST API result decorator, but it is not recommended. If you use a custom result decorator in a REST or Java API context, it completely replaces the default decorator that adds `href`, `mimetype`, and `format` data to results. Also, any data added by a decorator is returned as serialized XML, even when the client requests results in JSON.

To create and use a search result decorator, do the following:

1. Write an XQuery function that conforms to the decorator interface.
2. Install your function in the modules database or modules directory associated with your App Server.
3. Instruct MarkLogic Server to use your function by specifying it in a `result-decorator` query option that you supply with your search.

The rest of this section covers these steps in detail.

8.11.2 Writing a Custom Search Result Decorator

To create a custom decorator, implement an XQuery function that conforms to the following interface:

```
declare function your-name($uri as xs:string) as node()*
```

The `$uri` input parameter is the URI of a document containing search matches. The nodes returned by your function become attributes or child nodes of the `search:result` element on whose behalf it is called.

Your result decorator should always produce XML, even when working with JSON documents or producing output for a client expecting JSON search results.

The following example is a custom decorator function that returns the same information as the default REST API decorator (`href`, `mimetype`, and `format`), with the attribute names changed so you can see them in use. The example also adds a `<my-elem/>` element to the search results.

```
xquery version "1.0-ml";

module namespace my-lib = "http://marklogic.com/example/my-lib";
```

```
declare function my-lib:decorator($uri as xs:string) as node()*
{
  let $format   := xdmp:uri-format($uri)
  let $mimetype := xdmp:uri-content-type($uri)
  return (
    attribute my-href { concat("/documents/are/here?uri=", $uri) },

    if (empty($mimetype)) then ()
    else attribute my-mimetype {$mimetype},

    if (empty($format)) then ()
    else attribute my-format { $format }

    element my-elem { "Extra Goodness" }
  )
};
```

To use your function, install it as a module in your App Server, and then specify it in a `result-decorator` query option. For details, see "Installing a Custom Search Result Decorator" on page 396 and "Using a Custom Search Result Decorator" on page 396.

8.11.3 Installing a Custom Search Result Decorator

Install the XQuery library module containing your decorator function in the modules database or under the filesystem root associated with your App Server.

For example, running the following query in Query Console loads an XQuery module into the modules database with the URI `/my.domain/decorator.xqy`, assuming you select the modules database as the Content Source in Query Console:

```
xquery version "1.0-ml";
xdmp:document-load(
  "/space/rest/decorator.xqy",
  <options xmlns="xdmp:document-load">
    <uri>/my.domain/decorator.xqy</uri>
  </options>)
```

If you use the REST API or Java API, install the module in the modules database associated with your REST API instace.

8.11.4 Using a Custom Search Result Decorator

To use a custom search result decorator, specify it in a `result-decorator` query option that is included with your query.

For example, if you install the custom decorator from "Writing a Custom Search Result Decorator" on page 395 as `/my.domain/decorator.xqy`, then you can reference it in query options as follows:

```
<options xmlns="http://marklogic.com/appservices/search">
  <result-decorator apply="decorator"
      ns="http://marklogic.com/example/my-lib"
      at="/my.domain/decorator.xqy"/>
</options>
```

The following example uses the above query options in a search:

```
xquery version "1.0-ml";
import module namespace search =
  "http://marklogic.com/appservices/search"
     at "/MarkLogic/appservices/search/search.xqy";

search:search(
  "cat AND dog",
  <options xmlns="http://marklogic.com/appservices/search">
    <result-decorator apply="decorator"
        ns="http://marklogic.com/example/my-lib"
        at="/my.domain/decorator.xqy" />
  </options>
)
```

The decorator adds the `my-href`, `my-mimetype`, and `my-format` attributes and the `my-elem` element to the search results, similar to the following:

```
<search:response ...>
  <search:result index="1" uri="/docs/example.xml"
       path="fn:doc(&amp;quot;/docs/example.xml&amp;quot;)" ...
       my-href="/documents/are/here?uri=/docs/example.xml"
       my-mimetype="text/xml" my-format="xml">
    <my-elem>Extra Goodness!</my-elem>
    ...
  </search:result>
</search:response>
```

8.12 Other Search Options

There are many other options in the Search API, including `additional-query` (an additional `cts:query` combined as an and-query to the active query in your search), `term-option` (pass any of the `cts:query` options such as `case-sensitive` to your `cts:query`), and others. For a complete list, see "Appendix: Query Options Reference" on page 668.

8.13 Query Options Examples

This section includes the following additional query options examples:

- Example: Values and Tuples Query Options
- Example: Field Constraint Query Options
- Example: Collection Constraint Query Options
- Example: Path Range Index Constraint Query Options
- Example: Element Attribute Range Constraint Query Options
- Example: Geospatial Constraint Query Options

8.13.1 Example: Values and Tuples Query Options

This examples demonstrates how to create and use a values or tuples query option. For more details, see “values” on page 791 and “tuples” on page 787 in the query options appendix.

This example sets up the following configurations:

- A values tuple `/v1/values/pop`, which gets the values from the element range index from `xs:QName("popularity")` (in no namespace), and is typed as an `xs:int`.
- A values tuple /`v1/values/score`, which gets the values from the element range index from a QName with namespace `"http://test.aggr.com"` and localname `"score"`, typed as an `xs:decimal`.
- A tuple `/v1/values/pop-rate-tups`, which combines the range index from from `xs:QName("popularity")` (in no namespace), and typed as an `xs:int`, and the range index from a QName with namespace `"http://test.aggr.com"` and localname `"score"`, typed as an `xs:decimal`.

Format	Options
XML	<search:options xmlns:search="http://marklogic.com/appservices/search"> <search:values name="pop-aggr"> <search:range type="xs:int"> <search:element ns="" name="popularity"/> </search:range> </search:values> <search:values name="score-aggr"> <search:range type="xs:decimal"> <search:element ns="http://test.aggr.com" name="score"/> </search:range> </search:values> <search:tuples name="pop-rate-tups"> <search:range type="xs:int"> <search:element ns="" name="popularity"/> </search:range> <search:range type="xs:int"> <search:element ns="http://test.tups.com" name="rate"/> </search:range> </search:tuples> </search:options>

Format	Options

JSON	<pre>{ "options": {
	    "values": [{
	      "name": "pop-aggr",
	      "range": {
	        "type": "xs:int",
	        "element": {
	           "ns": "",
	           "name": "popularity"
	        }
	      }
	    },
	    {
	      "name": "score-aggr",
	      "range": {
	        "type": "xs:decimal",
	        "element": {
	          "ns": "http://test.aggr.com",
	          "name": "score"
	        }
	      }
	    }],
	    "tuples": [{
	      "name": "pop-rate-tups",
	      "range": [
	         {
	           "type": "xs:int",
	           "element": {
	             "ns": "",
	             "name": "popularity"
	           }
	         },
	         {
	           "type": "xs:int",
	           "element": {
	             "ns": "http://test.tups.com",
	             "name": "rate"
	           }
	         }
	       ]
	    }]
	} }</pre>

8.13.2 Example: Field Constraint Query Options

This example constructs a simple options node that sets up just one constraint, based on the field named `"bbqtext"`. It creates a word constraint, therefore when you search for

```
summary:"hot dog"
```

It constrains the search to documents that have the phrase `"hot dog"` in the field called `"bbqtext"`.

Format	Options

XML	`<search:options`
	`  xmlns:search="http://marklogic.com/appservices/search">`
	`  <search:constraint name="summary">`
	`  <search:word>`
	`  <search:field name="bbqtext"/>`
	`  </search:word>`
	`  </search:constraint>`
	`</search:options>`

JSON	`{ "options": {`
	`  "constraint": [ {`
	`  "name": "summary",`
	`  "word": {`
	`  "field": { "name": "bbqtext" }`
	`  }`
	`  } ]`
	`} }`

For more details, see “constraint” on page 674 in the query options appendix.

8.13.3 Example: Collection Constraint Query Options

The query options in this example do the following:

- Sets flags that modify the search results (`return-metrics` and `return-qtext`).
- Specifies a builtin `transform-results` function that will return raw document search results.
- Defines a collection constraint that uses the collection URIs.

The collection constraint named `"coll"` uses the collection URIs with `"http://test.com"` stripped off.

Format	Options

XML	`<search:options`
	`  xmlns:search="http://marklogic.com/appservices/search">`
	`<search:debug>true</search:debug>`
	`<search:constraint name="coll">`
	`<search:collection prefix="http://test.com"/>`
	`</search:constraint>`
	`<search:return-metrics>false</search:return-metrics>`
	`<search:return-qtext>false</search:return-qtext>`
	`<search:transform-results apply="raw">`
	`<search:preferred-matches/>`
	`</search:transform-results>`
	`</search:options>`

JSON	`{ "options": {`
	`"debug": true,`
	`"constraint": [ {`
	`"name": "coll",`
	`"collection": { "prefix": "http://test.com" }`
	`} ],`
	`"return-metrics": false,`
	`"return-qtext": false,`
	`"transform-results": {`
	`"apply": "raw",`
	`"preferred-matches": ""`
	`}`
	`} }`

For more details, see “collection” on page 691 in the query options appendix.

8.13.4 Example: Path Range Index Constraint Query Options

This example shows how to configure a constraint with a path range index. With this in place, searching for:

```
pindex:low
```

Searches for values less than 5 from the nodes at `/Employee/fn` (in no namespace). It is a string range index, faceted, scoped to documents, with a nice looking unicode label. The facet values are returned with any search.

Format	Options
XML	<search:options xmlns:search="http://marklogic.com/appservices/search"> <search:constraint name="pindex"> <search:range type="xs:string" facet="true" collation="http://marklogic.com/collation/"> <search:path-index>/Employee/fn</search:path-index> <search:fragment-scope>documents</search:fragment-scope> <search:bucket name="low" ge="5">0 to 5</search:bucket> <search:bucket name="medium" lt="10" ge="5" >5 to 10</search:bucket> <search:bucket name="high" lt="15" ge="10" >10 to 15</search:bucket> </search:range> </search:constraint> </search:options>

JSON	{ "options": {
	"constraint": [{
	"name": "pindex",
	"range": {
	"type": "xs:string",
	"facet": true,
	"collation": "http://marklogic.com/collation/",
	"path-index": { "text": "/Employee/fn" },
	"fragment-scope": "documents",
	"bucket": [
	{
	"name": "low",
	"lt": "5",
	"label": "0 to 5"
	},
	{
	"name": "medium",
	"lt": "10",
	"ge": "5",
	"label": "5 to 10"
	},
	{
	"name": "high",
	"lt": "15",
	"ge": "10",
	"label": "10 to 15"
	}
	]
	}
	}]
	} }

8.13.5 Example: Element Attribute Range Constraint Query Options

This example shows an element attribute range index, with computed buckets. When you search, the facets will be filled out depending on the values of `{http://example.com}entry/@date`.

Format	Options
XML	<search:options xmlns:search="http://marklogic.com/appservices/search"> <search:constraint name="date"> <search:range type="xs:dateTime" facet="true"> <search:attribute ns="" name="date"/> <search:element ns="http://example.com" name="entry"/> <search:fragment-scope>documents</search:fragment-scope> <search:computed-bucket name="older" lt="-P1Y" anchor="start-of-year">Older</search:computed-bucket> <search:computed-bucket name="year" lt="P1Y" ge="P0Y" anchor="start-of-year">This Year</search:computed-bucket> <search:computed-bucket name="month" lt="P0M" ge="P1M" anchor="start-of-month">This Month</search:computed-bucket> <search:computed-bucket name="today" lt="P0D" ge="P1D" anchor="start-of-day">Today</search:computed-bucket> <search:computed-bucket name="future" ge="P0D" anchor="now">Future</search:computed-bucket> </search:range> </search:constraint> </search:options>

Format	Options

JSON	{ "options": {
	"constraint": [{
	"name": "date",
	"range": {
	"type": "xs:dateTime",
	"facet": true,
	"attribute": {
	"ns": "",
	"name": "date"
	},
	"element": {
	"ns": "http://example.com",
	"name": "entry"
	},
	"fragment-scope": "documents",
	"computed-bucket": [
	{
	"name": "older",
	"lt": "-P1Y",
	"anchor": "start-of-year",
	"label": "Older"
	},
	{
	"name": "year",
	"lt": "P1Y",
	"ge": "P0Y",
	"anchor": "start-of-year",
	"label": "This Year"
	},
	{
	"name": "month",
	"lt": "P0M",
	"ge": "P1M",
	"anchor": "start-of-month",
	"label": "This Month"
	},
	{
	"name": "today",
	"lt": "P0D",
	"ge": "P1D",
	"anchor": "start-of-day",
	"label": "Today"
	},
	{
	"name": "future",
	"ge": "P0D",
	"anchor": "now",
	"label": "Future"
	}
	]
	}}]}}

8.13.6 Example: Geospatial Constraint Query Options

This example shows geospatial constraint query options. In addition to having a search results configuration setting (`page-length`), this sets up three geospatial constraints and three element constraints.

Format	Options
XML	<search:options xmlns:search="http://marklogic.com/appservices/search"> <search:debug>true</search:debug> <search:return-metrics>false</search:return-metrics> <search:page-length>25</search:page-length> <search:constraint name="geo-elem"> <search:geo-elem> <search:element ns="" name="g-elem-point"/> </search:geo-elem> </search:constraint> <search:constraint name="geo-elem-pair"> <search:geo-elem-pair> <search:lat ns="" name="lat"/> <search:lon ns="" name="long"/> <search:parent ns="" name="g-elem-pair"/> </search:geo-elem-pair> </search:constraint> <search:constraint name="geo-attr-pair"> <search:geo-attr-pair> <search:lat ns="" name="lat"/> <search:lon ns="" name="long"/> <search:parent ns="" name="g-attr-pair"/> </search:geo-attr-pair> </search:constraint> </search:options>

Format	Options

JSON	<pre>{ "options": {
	    "debug": true,
	    "return-metrics": false,
	    "page-length": 25,
	    "constraint": [
	      { "name": "geo-elem",
	        "geo-elem": {
	          "element": {
	            "ns": "",
	            "name": "g-elem-point"
	          }
	        }
	      },
	      { "name": "geo-elem-pair",
	        "geo-elem-pair": {
	          "lat": {
	            "ns": "",
	            "name": "lat"
	          },
	          "lon": {
	            "ns": "",
	            "name": "long"
	          },
	          "parent": {
	            "ns": "",
	            "name": "g-elem-pair"
	          }
	        }
	      },
	      { "name": "geo-attr-pair",
	        "geo-attr-pair": {
	          "lat": {
	            "ns": "",
	            "name": "lat"
	          },
	          "lon": {
	            "ns": "",
	            "name": "long"
	          },
	          "parent": {
	            "ns": "",
	            "name": "g-attr-pair"
	          }
	        }
	      }
	    ]
	} }</pre>

9.0 Relevance Scores: Understanding and Customizing

Search results in MarkLogic Server return in *relevance* order; that is, the result that is most relevant to the `cts:query` expression in the search is the first item in the search return sequence, and the least relevant is the last. There are several tools available to control the relevance score associated with a search result item. This chapter describes the different methods available to calculate relevance, and includes the following sections:

- Understanding How Scores and Relevance are Calculated
- How Fragmentation and Index Options Influence Scores
- Using Weights to Influence Scores
- Proximity Boosting With the distance-weight Option
- Boosting Relevance Score With a Secondary Query
- Including a Range or Geospatial Query in Scoring
- Interaction of Score and Quality
- Using cts:score, cts:confidence, and cts:fitness
- Relevance Order in cts:search Versus Document Order in XPath
- Exploring Relevance Score Computation
- Sample cts:search Expressions

9.1 Understanding How Scores and Relevance are Calculated

When you perform a `cts:search` operation, MarkLogic Server produces a result set that includes items matching the `cts:query` expression and, for each matching item, a *score*. The score is a number that is calculated based on statistical information, including the number of documents in a database, the frequency in which the search terms appear in the database, and the frequency in which the search term appears in the document. The relevance of a returned search item is determined based on its score compared with other scores in the result set, where items with higher scores are deemed to be more relevant to the search. By default, search results are returned in relevance order, so changing the scores can change the order in which search results are returned.

As part of a `cts:search` expression, you can specify the following different methods for calculating the score, each of which uses a different formula in its score calculation:

- log(tf)*idf Calculation
- log(tf) Calculation
- Simple Term Match Calculation
- Random Score Calculation

- Term Frequency Normalization

You can use the `relevance-trace` option with `cts:relevance-info` to explore score calculations in detail. For details, see "Exploring Relevance Score Computation" on page 428.

9.1.1 log(tf)*idf Calculation

The `logtfidf` method of relevance calculation is the default relevance calculation, and it is the option `score-logtfidf` of `cts:search`. The `logtfidf` method takes into account term frequency (how often a term occurs in a single fragment) and document frequency (in how many documents does the term occur) when calculating the score. Most search engines use a relevance formula that is derived by some computation that takes into account term frequency and document frequency.

The `logtfidf` method (the default scoring method) uses the following formula to calculate relevance:

```
log(term frequency) * (inverse document frequency)
```

The `term frequency` is a normalized number representing how many terms are in a document. The term frequency is normalized to take into account the size of the document, so that a word that occurs 10 times in a 100 word document will get a higher score than a word that occurs 100 times in a 1,000 word document.

The `inverse document frequency` is defined as:

```
log(1/df)
```

where `df` (document frequency) is the number of documents in which the term occurs.

For most search-engine style relevance calculations, the `score-logtfidf` method provides the most meaningful relevance scores. Inverse document frequency (IDF) provides a measurement of how "information rich" a document is. For example, a search for "the" or "dog" would probably put more emphasis on the occurences of the term "dog" than of the term "the".

9.1.2 log(tf) Calculation

The option `score-logtf` for `cts:search` computes scores using the `logtf` method, which does not take into account how many documents have the term. The `logtf` method uses the following formula to calculate scores:

```
log(term frequency)
```

where the `term frequency` is a normalized number representing how many terms are in a document. The term frequency is normalized to take into account the size of the document, so that a word that occurs 10 times in a 100 word document will get a higher score than a word that occurs 100 times in a 1,000 word document.

When you use the `logtf` method, scores are based entirely on how many times a document matches the search term, and does not take into account the "information richness" of the search terms.

9.1.3 Simple Term Match Calculation

The option `score-simple` on `cts:search` performs a simple term-match calculation to compute the scores. The `score-simple` method gives a score of 8*weight for each matching term in the `cts:query` expression, and then scales the score up by multiplying by 256. It does not matter how many times a given term matches (that is, the term frequency does not matter); each match contributes 8*weight to the score. For example, the following query (assume the default weight of 1) would give a score of 8*256=2048 for any fragment with one or more matches for "hello", a score of 16*256=4096 for any fragment that also has one or more matches for "goodbye", or a score of zero for fragments that have no matches for either term:

```
cts:or-query(("hello", "goodbye"))
```

Use this option if you want the scores to only reflect whether a document matches terms in the query, and you do not want the score to be relative to frequency or "information-richness" of the term.

9.1.4 Random Score Calculation

The option `score-random` on `cts:search` computes a randomly-generated score for each search match. You can use this to randomly choose fragments matching a query. If you perform the same search multiple times using the `score-random` option, you will get different ordering each time (because the scores are randomly generated at runtime for each search).

9.1.5 Term Frequency Normalization

The scoring methods that take into account term frequency (`score-logtfidf` and `score-logtf`) will, by default, normalize the term frequency (how many search term matches there are for a document) based on the size of the document. The idea of this normalization is to take into account how frequent a term occurs in the document, relative to the other documents in the database. You can think of this is the density of terms in a document, as opposed to simply the frequency of the terms. The term frequency normalization makes a document that has, for example, 10 occurrences of the word `"dog"` in a 10,000,000 word document have a lower relevance than a document that has 10 occurrences of the word `"dog"` in a 100 words document. With the default term frequency normalization of `scaled-log`, the smaller document would have a higher score (and therefore be more relevant to the search), because it has a greater "term density" of the word `"dog"`. For most search applications, this behavior is desirable.

If you would like to change that behavior, you can set the `tf normalization` option on the database configuration to lessen or eliminate the effects of the size of the matching document in the score calculation, which in turn would strengthen the effect of its term frequency (the number of matches in that document). The `unscaled-log` option does no scaling based on document size,

and the `scaled-log` option (the default) does the maximum scaling of the document based on document size. Additionally, there are four intermediate settings, `weakest-scaled-log`, `weakly-scaled-log`, `moderately-scaled-log`, and `strongly-scaled-log`, which have increasing degrees of scaling in between none and the most scaling. If you change this setting in the database and `reindexer enable` is set to `true`, then the database will begin reindexing.

9.2 How Fragmentation and Index Options Influence Scores

Scores are calculated based on index data, and therefore based on unfiltered searches. That has several implications to scores:

- Scores are fragment-based, so term frequency and document frequency are calculated based on term frequency per fragment and fragment frequency respectively.
- Scores are based on unfiltered searches, so they include false-positive results.

Because scores are based on fragments and unfiltered searches, index options will affect scores, and in some case will make the scores more "accurate"; that is, base the scores on searches that return fewer false-positive results. For example, if you have `word positions` enabled in the database configuration, searches for three or more term phrases will have fewer false-positive matches, thereby improving the accuracy of the scores.

For details on unfiltered searches and how you can tell if there are false-positive matches, see "Using Unfiltered Searches for Fast Pagination" in the *Query Performance and Tuning Guide*.

9.3 Using Weights to Influence Scores

Use a weight in a query sub-expression to either boost or lower the sub-expression contribution to the relevance score.

For example, you can specify weights for leaf-level `cts:query` constructors, such as `cts:word-query` and `cts:element-value-query`; for details, see *XQuery and XSLT Reference Guide*. You can also specify weights in the equivalent Search API abstractions, such as the structured query constructs `value-query` and `word-constraint-query`, or when defining a word or value constraint in query options.

The default weight is 1.0. Use the following guidelines for choosing custom weights:

- To boost the score contribution, set the weight higher than 1.0.
- To lower the score contribution, set the weight between 0 and 1.0.
- To contribute nothing to the score, set the weight to 0.
- To make the score contribution negative, set the weight to a negative number.

Scores are normalized, so a weight is not an absolute multiplier on the score. Instead, weights indicate how much terms from a given query sub-expression are weighted in comparison to other sub-expressions in the same expression. A weight of 2.0 doubles the contribution to the score for terms that match that query. Similarly, a weight of 0.5 halves the contribution to the score for terms that match that query. In some cases, the score reaches a maximum, so a weight of 2.0 and a weight of 20,000 can yield the same contribution to the score.

Adding weights is particularly useful if you have several components in a query expression, and you want matches for some parts of the expression to be weighted more heavily than other parts. For an example of this, see "Increase the Score for some Terms, Decrease for Others" on page 430.

9.4 Proximity Boosting With the distance-weight Option

If you have the `word positions` indexing option enabled in your database, you can use the `distance-weight` option to the leaf-level `cts:query` constructors, and then all of the terms passed into that `cts:query` constructors will consider the proximity of the terms to each other for the purposes of scoring. This proximity boosting will make documents with matches close together have higher scores. Because search results are sorted by score, it will have the effect of making documents having the search terms close together have higher relevance ranking. This section provides some examples that use the `distance-weight` option along with explanations of the examples, and includes the following parts:

- Example of Simple Proximity Boosting
- Using Proximity Boosting With cts:and-query Semantics
- Using cts:near-query to Achieve Proximity Boosting

9.4.1 Example of Simple Proximity Boosting

The distance weight is only applied to the matches for `cts:query` constructors in which the `distance-weight` occurs. For example, consider the following `cts:query` constructor:

```
cts:word-query(("cat", "dog")), "distance-weight=3")
```

If one document has an instance of `"cat"` very near `"dog"`, and another document has the same number of `"cat"` and `"dog"` terms, but they are not very near, then the one with the `"cat"` near `"dog"` will have a higher score.

For example, consider the following:

```
xquery version "1.0-ml";
(: make sure word positions are enabled in the database :)
(:
   create 3 documents, then run two searches, one with
   distance-weight and one without, printing out the scores
:)
xdmp:document-insert("/2.xml",
```

```
  <p>The cat is pretty near a dog.</p>) ;

xdmp:document-insert("/1.xml",
  <p>The cat dog is very near.</p>) ;

xdmp:document-insert("/3.xml",
  <p>The cat is not very near the very large dog.</p>) ;

for $x in (cts:search(fn:doc(), cts:word-query(("cat", "dog") ,
                                "distance-weight=3" ) ),
           cts:search(fn:doc(), cts:word-query(("cat", "dog") ) ) )
return
element hit{attribute uri {xdmp:node-uri($x)},
            attribute score {cts:score($x)},
            attribute text{fn:string($x/p)}}
```

This returns the following results:

```
<hit uri="/1.xml" score="146" text="The cat dog is very near."/>
<hit uri="/2.xml" score="140" text="The cat is pretty near a dog."/>
<hit uri="/3.xml" score="135"
     text="The cat is not very near the very large dog."/>
<hit uri="/3.xml" score="72"
     text="The cat is not very near the very large dog."/>
<hit uri="/2.xml" score="72" text="The cat is pretty near a dog."/>
<hit uri="/1.xml" score="72" text="The cat dog is very near."/>
```

Notice that the first three hits use the `distance-weight`, and the ones with the terms closer together have higher scores, and thus rank higher in the search. The last three hits have the same score because they all have the same number of each term in the `cts:query` and there is no proximity taken into account in the scores.

9.4.2 Using Proximity Boosting With cts:and-query Semantics

Because the `distance-weight` option applies to the terms in individual `cts:query` constructors, the terms are combined as an or-query (that is, any term match is a match for the query). Therefore, the example above would also return results for documents that contain `"cat"` and not `"dog"` and vice versa. If you want to have and-query semantics (that is, all terms must match for the query to match) and also have proximity boosting, you will have to construct a `cts:query` that does an and of all of the terms in addition to the `cts:query` with the `distance-weight` option.

For example:

```
xquery version "1.0-ml";
cts:search(fn:doc(), cts:and-query((
                       cts:word-query("cat"),
                       cts:word-query("dog"),
                       cts:word-query(("cat", "dog") ,
                               "distance-weight=3" ) )) )
```

The difference between this query and the previous one is that the previous one would return a document that contained `"cat"` but not `"dog"` (or vice versa), and this one will only return documents containing both `"cat"` and `"dog"`.

If you have a large corpus of documents and you expect to have many matches for your searches, then you might find you do not need to use the `cts:and-query` approach. The reason a large corpus has an effect is because document frequency is taken into account in the relevance calculation, as described in "Understanding How Scores and Relevance are Calculated" on page 408. You might find that the most relevant documents still float to the top of your search even without the `cts:and-query`. What you do will depend on your application requirements, your preferences, and your data.

9.4.3 Using cts:near-query to Achieve Proximity Boosting

Another technique that makes results with closer proximity have higher scores is to use `cts:near-query`. Searches that use the `cts:near-query` constructor will take proximity into account when calculating scores, as long as the `word positions` index option is enabled in the database. Additionally, you can use the `distance-weight` parameter to further boost the effect of proximity on scoring.

Because `cts:near-query` takes a `distance` argument, you have to think about how near you want results to be in order for them to match. With the `distance` parameter to `cts:near-query`, there is a tradeoff between the size of the `distance` and performance. The higher the number for the `distance`, the more work MarkLogic Server does to resolve the query. For many queries, this amount of work might be very small, but for some complex queries it can be noticeable.

To construct a query that uses `cts:near-query` for proximity boosting, pass the `cts:query` for your search as the first parameter to a `cts:near-query`, and optionally add a `distance-weight` parameter to further boost the proximity. The `cts:near-query` matches will always take distance into account, but setting a `distance-weight` will further boost the proximity weight. For example, consider how the following query, which uses the same data as the above examples, produces similar results:

```
xquery version "1.0-ml";
cts:search(fn:doc(),
   cts:near-query(
     cts:and-query((
        cts:word-query("cat"),
        cts:word-query("dog") )),
     1000, (), 3) )
```

This query uses a `distance` of 1,000, therefore documents that have `"cat"` and `"dog"` that are more than 1,000 words apart are not included in its result. The size you use is dependent on your data and the performance characteristics of your searches. If you were more concerned about missing document where the matches are more than 1,000 words away, then you should raise that number; if you are seeing performance issues and want faster performance, and you are OK with missing results that are above the distance threshold (which are probably not relevant anyway), then you

should make the number smaller. For databases with a large amount of documents, keep in mind that not returning the documents with words that are far apart from each other will probably result in very similar search results, especially for the most relevant hits (because the results with the matches far apart have low relevance scores compared to the ones that have matches close together).

9.5 Boosting Relevance Score With a Secondary Query

You can use `cts:boost-query` to modify the relevance score of search results that match a secondary (or "boosting") query. The following example returns results from all documents containing the term "dog", and assigns a higher score to results that also contain the term "cat". The relevance score of matches for the first query are boosted by matches for the second query.

```
cts:search(fn:doc(),
  cts:boost-query(
    cts:word-query("dog"),
    cts:word-query("cat"))
)
```

As discussed in "Understanding How Scores and Relevance are Calculated" on page 408, many factors affect relevance score, so the exact quantitative effect of a boosting query on relevance score varies. However, the effect is always proportional to the weighting of the boosting query.

For example, suppose the database includes two documents, `/example/dogs.xml` and `/example/llamas.xml` that have the following contents:

```
/example/dogs.xml:
  <data>This is my dog. I do not have a cat.</data>
/example/llamas.xml:
  <data>This is my llama. He likes to spit at dogs.</data>
```

Then an unboosted search for the word "dog" returns the following matches:

```
cts:search(fn:doc(), cts:word-query("dog"))

<data>This is my dog. I do not have a cat.</data>
<data>This is my llama. He likes to spit at dogs.</data>
```

Assume these matches have the same relevance score. If you repeat the search as a boost query with default weight, the first match has a score that is roughly double that of the 2nd match. (The actual score values do not matter, only their relative values.)

```
for $n in (cts:search(fn:doc(),
    cts:boost-query(
      cts:word-query("dog"),
      cts:word-query("cat"))))
return fn:concat(fn:document-uri($n), " : ", cts:score($n))
```

```
==>
/example/dogs.xml : 22528
/example/llamas.xml : 11264
```

If you increase the weight on the boosting query to 10.0, the relevance score of the document containing both terms becomes roughly 10x that of the document that only contains `"dog"`.

```
for $n in (cts:search(fn:doc(),
    cts:boost-query(
      cts:word-query("dog"),
      cts:word-query("cat", (), 10.0))))
return cts:score($n)

==>
/example/dogs.xml : 22528
/example/llamas.xml : 2048
```

If the primary (or "matching") query returns no results, the boosting query is not evaluated. A boosting query is ignored in an XPath expression or any other context in which the score is zero or randomized.

The `BOOST` string query operator allows equivalent boosting in string search; for details, see "Query Components and Operators" on page 66. The `boost-query` structured query component also exposes the same functionality as `cts:boost-query`; for details, see "boost-query" on page 107.

9.6 Including a Range or Geospatial Query in Scoring

By default, range queries do not influence relevance score. However, you can enable range and geospatial queries score contribution using the `score-function` and `slope-factor` options. This section covers the following topics:

- How a Range Query Contributes to Score
- Use Cases for Range Query Score Contributions
- Enabling Range Query Score Contribution
- Understanding Slope Factor
- Performance Considerations
- Range Query Scoring Examples

9.6.1 How a Range Query Contributes to Score

By default, a range query makes no contribution to score. If you enable scoring for a given range query, it has the same impact as a word query. The contribution from a range query is just one of many factors influencing the overall score, especially in a complex query. As with any query, you can use weights to change the influence a range query has on score; for details, see "Using Weights to Influence Scores" on page 411.

The difference between a matching value and the reference value does not contribute directly to the score. A function is applied to the delta, with suitable scaling based on datatype, such that the resulting range is comparable to the term frequency (TF) contribution from a word query. You control the scaling using the slope factor of the function; for details, see "Understanding Slope Factor" on page 419.

The type of function (linear or reciprocal) determines whether values closest to or furthest from the reference value contribute more to the score. The reference value is the constraining value in the query. For example, if a range query expresses a constraint such as "> 5", then the reference value is 5. You cannot choose the function, but you can choose the type of function.

If a document contains multiple matching values, the highest contribution is used in the overall score computation.

9.6.2 Use Cases for Range Query Score Contributions

Range query score contributions are useful in cases such as the following:

- Boost the score of newer documents over similar older documents, where "newness" is a function of dateTime or another numeric element value. For example, boost the score of recently published documents.
- Boost the score based on how close some element value is to a reference value. For example, boost scores for documents containing prices closest to an ideal of $20.
- Boost the score based on how far away some element value is from a reference value. For example, boost scores for items with a price furthest below a maximum of $20.
- Boost the score based on geospatial distance. For example, find all hotels within 5 miles, boosting the scores for those closest to my current location.

For examples of how to realize these use cases, see "Range Query Scoring Examples" on page 422.

9.6.3 Enabling Range Query Score Contribution

Add the `score-function` option to a range or geospatial query constructor to enable score contributions. You can also use the `slope-factor` option to scale the contribution; for details, see "Understanding Slope Factor" on page 419.

For example, the following search boosts the score more for documents with high ratings (furthest from the reference value 0). Setting the slope factor to 10 decrease the range of values that make a distinct contribution and increases the difference between the amount of contribution.

```
(: Scoring for positive ratings in range 1 to 100 :)
cts:search(doc(),
  cts:element-range-query(xs:QName("ratings"), ">", 0,
    ("score-function=linear","slope-factor=10")))
```

For examples of constructing a similar query with other MarkLogic Server APIs, see "Range Query Scoring Examples" on page 422.

You can set the value of `score-function` to one of the following function types:

Score Function	Description
`zero`	Default. The score contribution of the range query is zero.
`reciprocal`	Use a reciprocal function to calculate the scoring contribution. Document values nearer to the reference value receive higher scores.
`linear`	Use a linear function to calculate the scoring contribution. Document values further from the reference value receive higher scores.

You can specify a score function and slope factor with the following XQuery query constructors, or the equivalent structured or QBE range query constructs.

- `cts:element-range-query`
- `cts:element-attribute-range-query`
- `cts:field-range-query`
- `cts:path-range-query`
- `cts:element-geospatial-query`
- `cts:element-child-geospatial-query`
- `cts:element-pair-geospatial-query`
- `cts:element-attribute-pair-geospatial-query`
- `cts:path-geospatial-query`
- `cts:triple-range-query`

9.6.4 Understanding Slope Factor

In addition to specifying a score function for a range query, you can use the `slope-factor` option to specify a multiplier on the slope of the scoring function applied to a range query. The slope factor affects how the range of differences between a matching value and the reference value affect the score contribution. You should experiment with your application to determine the best slope factor for a given range query. This section provides details to guide your experimentation.

The *delta* for a given range query match is the difference between the matching value and the reference value in a range query:


```
delta = reference_value - matching_value
```

For example, if a range query expresses "greater than 5" and the matching value is 3, then the delta is 2. This delta is the basis of the score contribution for a given match, though it is not the actual score contribution.

Each possible delta value does not make a different score contribution because contribution is bucketed. The range of delta values is bounded by a min and max delta value, beyond which all deltas make the same contribution. The granularity represents the size of each bucket within that range. All deltas that fall in the same bucket make the same score contribution, so granularity determines the range of deltas that make a distinct score contribution.

The number of buckets does not change as you vary the slope factor, so changing the slope factor affects the min, max, and granularity of the score function.

The figure below shows the relationship between slope, minimum delta, maximum delta, and granularity for a linear score function.



A slope factor greater than 1 results in finer granularity, but a more narrow range of delta values. A slope factor less than 1 gives a coarser granularity, but a greater range of delta values. Doubling the slope factor with a linear function gives you half the range and half the granularity.

The minimum delta, maximum delta, and granularity for a given slope factor depend upon the type of the range index. The table below shows minimum delta, maximum delta, and granularity for each range index type with the default slope factor (1.0). The granularity is not linear for a reciprocal score function.

Range Index Type	Lower Bound	Upper Bound	Granularity
`integer`	1	8192	32
`float`	1.0	8192.0	32.0
`double`	1.0	8192.0	32.0
`decimal`	1.0	8192.0	32.
`string`	1	64	1
`point (wgs84)`	1.0 mile ~0.87 deg	800.0 miles ~11.59 deg	~3.112 miles ~2.7 min
`point (raw)`	1.0	800.0	~3.125
`date`	1 day	8 years	~11.75 days
`time`	1 min	24 hours	~5.5 min
`dateTime`	1 min	8 months	~22.5 hours
`dayTimeDuration`	1 min	24 hours	~5.5 min
`yearMonthDuration`	1 month	100 years	9 months
`gYear`	1 year	800 years	3 years
`gMonth`	1 month	8 years	1 month
`gDay`	1 day	248 days	1 day
`gYearMonth`	1 month	200 years	9 months

For example, the table contains the following information about range queries over `dateTime` with the default slope factor:

```
Min delta: 1 minute
Max delta: 8 months
Granularity: 22.5 hours
```

From this, you can deduce the following for a slope factor of 1.0:

- Any delta smaller than 1 minute makes the same contribution as 1 minute
- Any delta greater than 8 months makes the same contribution as 8 months.
- Deltas within 22.5 hours of each other can make the same contribution. For example, a delta of 5 minutes and a delta of 22 hours make the same contribution because they both fall into the bucket for "1 min. < delta ≤ 22.5 hours".

In a `dateTime` range query where the deltas are on the order of hours, the default slope factor provides a good spread of contributions. However, if you need to distinguish between deltas of a few minutes or seconds, you would increase the slope factor to provide a finer granularity. When you do this, the minimum and maximum delta values get closer together, so the overall range of distinguishable delta values becomes smaller.

Another way to look at slope factor is based on the target minimum or maximum delta. For example, if the default maximum delta for your datatype is 1024 and the range of "interesting" delta values for your range query is only 1 to 100, you probably want to set slope-factor to 10, which lowers the maximum delta to 100 (`1024 div 10`).

9.6.5 Performance Considerations

The performance impact of enabling range query score contributions depends on the nature of your query. The cost is highest for queries that return many matches and queries on strings.

The number of matches affects cost because the scoring calculation is performed for each match. The value type affects the cost because the score calculation is significantly more complex for string values.

Range query score contribution calculations are skipped (and therefore have no negative performance impact) if any of the following conditions apply:

- The `score-function` option is not set or is set to `zero`.
- The range query has a weight of 0.
- The scoring method does not use term frequency. That is, the scoring method is not `score-logtfidf` or `score-logtf`.

9.6.6 Range Query Scoring Examples

This section contains examples that illustrate the use cases outlined in “Use Cases for Range Query Score Contributions” on page 417, plus examples of how to use the feature with additional APIs, such as structured query and QBE.

The following examples are included:

- Example: Most Recently Published
- Example: Closest to a Target Price
- Example: Best Price Below a Maximum
- Example: Closest to a Location
- Example: Use in a Structured Query
- Example: Use in Query By Example

9.6.6.1 Example: Most Recently Published

Boost the score of newer documents over similar older documents, where “newness” is a function of `dateTime` or another numeric element value. The following example boosts the score of recently published documents, where the publication date is stored in a `pubdate` element:

```
cts:element-range-query(
  xs:QName("pubdate"), "<=", current-dateTime(),
  "score-function=reciprocal")
```

The example uses a reciprocal score function so that `pubdate` values closest to “now” contribute the most to the score. That is, the smallest deltas make the biggest contribution.

9.6.6.2 Example: Closest to a Target Price

Boost the score based on how close some element value is to a reference value. The following example boost scores for documents containing prices closest to an ideal of $20, assuming the `price` is an attribute of the `item` element:

```
cts:element-attribute-range-query(
  xs:QName("item"), xs:QName("price"), ">=", 20.0,
  "score-function=reciprocal")
```

The example uses a reciprocal score function so that the smallest deltas between actual and ideal price ($20) make the highest contribution.

9.6.6.3 Example: Best Price Below a Maximum

Boost the score based on how far away some element value is from a reference value. For example, boost scores for items with a price furthest below a maximum of $20:

```
cts:element-attribute-range-query(
  xs:QName("item"), xs:QName("price"), "<=", xs:decimal(20.0),
  ("score-function=linear","slope-factor=51.2"))
```

The example uses a linear function so that the largest deltas between the actual price and the maxiumum price ($20) make the highest contribution.

The slope factor is increased to bring the range of interesting delta values down. As shown in "Understanding Slope Factor" on page 419, the default maximum delta for `xs:decimal` is 1024.0. However, in this example, the interesting deltas are all in the range of 0 to 20.0. To bring the upper bound down to ~20.0, we calculate the slope factor as follows:

```
slope-factor = 1024.0 / 20.0 = 51.2
```

Increasing the slope factor also reduces the granularity, so smaller price differences make different score contributions. With the default slope factor, the granularity is ~3.98, which is very coarse for a delta range of 0-20.0.

9.6.6.4 Example: Closest to a Location

Boost the score based on geospatial distance. For example, find all hotels within 10 miles, boosting the scores for those closest to my current location:

```
cts:and-query(("hotel",
  cts:element-geospatial-query(
    xs:QName("pt"), cts:circle(10, $current-location),
    ("score-function=reciprocal", "slope-factor=10.0"))))
```

The example uses a reciprocal score function so that points closest to the reference location (the smallest deltas) make the greatest score contribution.

The slope factor is increased because the range of interesting delta values is only 0 to 10 ("within 10 miles"). As shown in "Understanding Slope Factor" on page 419, the default maximum delta for a point is 100.0 miles. To bring the maximum delta down to 10.0, slope factor is computed as follows:

```
slope-factor = 100.0 / 10.0 = 10.0
```

9.6.6.5 Example: Use in a Structured Query

The following example is a structured query containing a range query for ratings greater than zero, boosting the score more as the rating increases. Documents with a higher rating receive a higher range query score contribution.

Format	Query

XML	`<search:query xmlns:search="http://marklogic.com/appservices/search"`
	`  <search:range-query type="xs:integer">`
	`  <search:element ns="" name="rating"/>`
	`  <search:range-operator>GT</range-operator>`
	`  <search:value>0</value>`
	`  <search:range-option>score-function=linear</range-option>`
	`  <search:range-option>slope-factor=10</range-option>`
	`  </search:range-query>`
	`</search:query>`

JSON	`{ "query": {`
	`  "queries": [{`
	`  "range-query": {`
	`  "type": "xs:integer",`
	`  "element": {`
	`  "ns": "",`
	`  "name": "rating"`
	`  },`
	`  "range-operator": "GT",`
	`  "value": [ 0 ],`
	`  "range-option": [`
	`  "score-function=linear",`
	`  "slope-factor=10"`
	`  ]`
	`  }`
	`  }]`
	`}}`

For details, see "Searching Using Structured Queries" on page 78 and the following interfaces:

Interface	Interface	More Information
Search API	`search:resolve`	*XQuery and XSLT Reference Guide*
REST API	GET/POST methods of the `/search` service	Querying Documents and Metadata in *REST Application Developer's Guide*
Java API	`RawStructuredQueryDefinition` or `StructuredQueryBuilder` in `com.marklogic.client.query`	Search Documents Using Structured Query Definition in *Java Application Developer's Guide*

9.6.6.6 Example: Use in Query By Example

The following example is a QBE that contains a range query for ratings greater than zero, boosting the score more as the rating increases. Documents with a higher rating receive a higher range query score contribution.

This query is suitable for use with the REST API `/qbe` service or the Java API `RawQueryByExampleDefinition` interface.

Format	Example

XML	`<q:qbe xmlns:q="http://marklogic.com/appservices/querybyexample">`
	`  <q:query>`
	`  <rating>`
	`  <q:gt score-function="linear" slope-factor="10">0</q:gt>`
	`  </rating>`
	`  </q:query>`
	`</q:qbe>`

JSON	`{ "$query": {`
	`  "rating": {`
	`  "$gt": 0,`
	`  "$score-function": "linear",`
	`  "$slope-factor": 10`
	`  }`
	`} }`

For details, see “Searching Using Query By Example” on page 186 and the following interfaces:

Interface	Interface	More Information
Search API	`search:resolve`	*XQuery and XSLT Reference Guide*
REST API	GET/POST methods of the `/qbe` service	Using Query By Example to Prototype a Query in *REST Application Developer’s Guide*
Java API	`RawQueryByExampleDefinition` in `com.marklogic.client.query`	Prototype a Query Using Query By Example in *Java Application Developer’s Guide*

9.7 Interaction of Score and Quality

Each document contains a quality value, and is set either at load time or with `xdmp:document-set-quality`. You can use the optional `$QualityWeight` parameter to `cts:search` to force document quality to have an impact on scores. The scores are then determined by the following formula:

```
Score = Score + (QualityWeight * Quality)
```

The default of `QualityWeight` is 1.0 and the default quality on a document is 0, so by default, documents without any quality set have no quality impact on score. Documents that do have quality set, however, will have impact on the scores by default (because the default `QualityWeight` is 1, effectively boosting the score by the document quality).

If you want quality to have a smaller impact on the score, set the `QualityWeight` between 0 and 1.0. If you want the quality to have no impact on the score, set the `QualityWeight` to 0. If you want the quality to have a larger impact on raising the score, set the `QualityWeight` to a number greater than 1.0. If you want the quality to have a negative effect on scores, set the `QualityWeight` to a negative number or set document quality to a negative number.

> **Note:** If you set document quality to a negative number and if you set `QualityWeight` to a negative number, it will boost the score with a positive number.

9.8 Using cts:score, cts:confidence, and cts:fitness

You can get the score for a result node by calling `cts:score` on that node. The score is a number, where higher numbers indicate higher relevance for that particular result set.

Similarly, you can get the confidence by calling `cts:confidence` on a result node. The confidence is a number (of type `xs:float`) between 0.0 and 1.0. The confidence number does not include any quality settings that might be on the document. Confidence scores are calculated by first bounding the scores between 0 and 1.0, and then taking the square root of the bounded number.

As an alternate to `cts:confidence`, you can get the fitness by calling `cts:fitness` on a result node. The fitness is a number (of type `xs:float`) between 0.0 and 1.0. The fitness number does not include any quality settings that might be on the document, and it does not use document frequency in the calculation. Therefore, `cts:fitness` returns a number indicating how well the returned node satisfies the query issued, which is subtly different from relevance, because it does not take into account other documents in the database.

9.9 Relevance Order in cts:search Versus Document Order in XPath

When understanding the order an expression returns in, there are two main rules to consider:

- `cts:search` expressions always return in relevance order (the most relevant to the least relevant).
- XPath expressions always return in document order.

A subtlety to note about these rules is that if a `cts:search` expression is followed by some XPath steps, it turns the expression into an XPath expression and the results are therefore returned in document order. For example, consider the following query:

```
cts:search(fn:doc(), "my search phrase")
```

This returns a relevance-ordered sequence of document nodes that contain the specified phrase. You can get the scores of each node by using `cts:score`. Things will change if you then add an XPath step to the expression as follows:

```
cts:search(fn:doc(), "my search phrase")//TITLE
```

This will now return a *document-ordered* sequence of `TITLE` elements. Also, in order to compute the answer to this query, MarkLogic Server must first perform the search, and then reorder the search in document order to resolve the XPath expression. If you need to perform this type of query, it is usually more efficient (and often *much* more efficient) to use `cts:contains` in an XPath predicate as follows:

```
fn:doc()[cts:contains(., "my search phrase")]//TITLE
```

Note: In most cases, this form of the query (all XPath expression) will be much more efficient than the previous form (with the XPath step after the `cts:search` expression). There might be some cases, however, where it might be less efficient, especially if the query is highly selective (does not match many fragments).

When you write queries as XPath expressions, MarkLogic Server does not compute scores, so if you need scores, you will need to use a `cts:search` expression. Also, if you need a query like the above examples but need the results in relevance order, then you can put the search in a `FLWOR` expression as follows:

```
for $x in cts:search(fn:doc(), "my search phrase")
return
$x//TITLE
```

This is more efficient than the `cts:search` with an XPath step following it, and returns relevance-ranked and scored results.

9.10 Exploring Relevance Score Computation

You can use the `relevance-trace` search option to explore how the relevance scores are computed for a query. For example, you can use this feature to explore the impact of varying query weight and document quality weight.

> **Note:** Collecting score computation information during a search is costly, so you should only use the `relevance-trace` option when you intend to generate a score computation report from the collected trace.

When you use the `relevance-trace` option on a search, MarkLogic Server collects detailed information about how the relevance score is computed. You can access the information in one of the following ways:

- If you search using `cts:search`, call `cts:relevance-info` on your search results to generate an XML report.
- If you search using the Search API (`search:search` or `search:resolve`), REST API, or Java API, an XML report is automatically returned in the relevance-info section of each serach result. (The REST and Java APIs can also return a JSON report.)

The following example generates a score computation report from the results of cts:search.

```
for $x in cts:search(fn:doc(), "example", "relevance-trace")
return cts:relevance-info($x)
```

The resulting score computation report looks similar to the following:

```
<qry:relevance-info xmlns:qry="http://marklogic.com/cts/query">
  <qry:score
    formula="(256*scoreSum/weightSum)+(256*qualityWeight*documentQuality)"
    computation="(256*208/1)+(256*1*0)">53248</qry:score>
  <qry:confidence formula="sqrt(score/(256*8*maxlogtf*maxidf))"
    computation="sqrt(53248/(256*8*18*log(848)))">0.462837</qry:confidence>
  <qry:fitness formula="sqrt(score/(256*8*maxlogtf*avgidf))"
    computation="sqrt(53248/(256*8*18*(3.13196/1)))">0.679113</qry:fitness>
  <qry:uri>/example.xml</qry:uri>
  <qry:path>fn:doc("/example.xml")</qry:path>
  <qry:term weight="3.25">
    <qry:score formula="8*weight*logtf" computation="26*8">208</qry:score>
    <qry:key>16979648098685758574</qry:key>
    <qry:annotation>word("example")</qry:annotation>
  </qry:term>
</qry:relevance-info>
```

Each `qry:score` element contains a `@formula` describing the computation, and a `@computation` showing the values plugged into the formula. The data in the `score` element is the result of the computation. For example:

```
<qry:score
    formula="(256*scoreSum/weightSum)+(256*qualityWeight*documentQuality)"
    computation="(256*154/2)+(256*1*0)">
  19712
</qry:score>
```

The following example generates a score computation report using the XQuery Search API:

```
xquery version "1.0-ml";
import module namespace search =
    "http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

search:search("example",
  <search:options xmlns="http://marklogic.com/appservices/search">
    <search-option>relevance-trace</search-option>
  </search:options>
)
```

The query generates results similar to the following:

```
<search:response snippet-format="snippet" total="1" start="1" ...>
  <search:result index="1" uri="/example.xml"
      path="fn:doc(&amp;quot;/example.xml&amp;quot;)" score="14336"
      confidence="0.749031" fitness="0.749031">
    <search:snippet>...</search:snippet>
    <qry:relevance-info xmlns:qry="http://marklogic.com/cts/query">
      <qry:score
        formula="(256*scoreSum/weightSum)+(256*qualityWeight*documentQuality)"
        computation="(256*56/1)+(256*1*0)">14336</qry:score>
      <qry:confidence formula="sqrt(score/(256*8*maxlogtf*maxidf))"
        computation="sqrt(14336/(256*8*18*log(2)))">0.749031</qry:confidence>
      <qry:fitness formula="sqrt(score/(256*8*maxlogtf*avgidf))"
        computation="sqrt(14336/(256*8*18*(0.693147/1)))">
        0.749031
       </qry:fitness>
      <qry:uri>/example.xml</qry:uri>
      <qry:path>fn:doc("/example.xml")</qry:path>
      <qry:term weight="0.875">
        <qry:score formula="8*weight*logtf" computation="7*8">56</qry:score>
        <qry:key>16979648098685758574</qry:key>
        <qry:annotation>word("example")</qry:annotation>
      </qry:term>
    </qry:relevance-info>
  </search:result>
  <search:qtext>example</search:qtext>
  ...
</search:response>
```

The REST and Java APIs use the same query options as the above Search API example, and return a report in the same way, inside each `search:result`.

9.11 Sample cts:search Expressions

This section lists several `cts:search` expressions that include weight and/or quality parameters. It includes the following examples:

- Magnify the Score Boost for Documents With Quality
- Increase the Score for some Terms, Decrease for Others

9.11.1 Magnify the Score Boost for Documents With Quality

The following search will make any documents that have a quality set (set either at load time or with `xdmp:document-set-quality`) give much higher scores than documents with no quality set.

```
cts:search(fn:doc(), cts:word-query("my phrase"), (), 3.0)
```

Note: For any documents that have a quality set to a negative number less than -1.0, this search will have the effect of lowering the score drastically for matches on those documents.

9.11.2 Increase the Score for some Terms, Decrease for Others

The following search will boost the scores for documents that satisfy one query while decreasing the scores for documents that satisfy another query.

```
cts:search(fn:doc(), cts:and-query((
  cts:word-query("alfa", (), 2.0), cts:word-query("lada", (), 0.5)
  )) )
```

This search will boost the scores for documents that contain the word `alfa` while lowering the scores for document that contain the word `lada`. For documents that contain both terms, the component of the score from the word `alfa` is boosted while the component of the score from the word `lada` is lowered.

10.0 Browsing With Lexicons

MarkLogic Server allows you to create *lexicons*, which are lists of unique words or values, either throughout an entire database (words only) or within named elements or attributes (words or values). Also, you can define lexicons that allow quick access to the document and collection URIs in the database, and you can create word lexicons on named fields. This chapter describes the lexicons you can create in MarkLogic Server and describes how to use the API to browse through them. This chapter includes the following sections:

- About Lexicons
- Creating Lexicons
- Word Lexicons
- Element/Element-Attribute/Path Value Lexicons
- Field Value Lexicons
- Value Co-Occurrences Lexicons
- Geospatial Lexicons
- Range Lexicons
- URI and Collection Lexicons
- Performing Lexicon-Based Queries

10.1 About Lexicons

A *word lexicon* stores all of the unique, case-sensitive, diacritic-sensitive words, either in a database, in an element defined by a QName, or in an attribute defined by a QName. A *value lexicon* stores all of the unique values for an element or an attribute defined by a QName (that is, the entire and exact contents of the specified element or attribute). A *value co-occurrences lexicon* stores all of the pairs of values that appear in the same fragment. A *geospatial lexicon* returns geospatial values from the geospatial index. A *range lexicon* stores buckets of values that occur within a specified range of values. A *URI lexicon* stores the URIs of the documents in a database, and a *collection lexicon* stores the URIs of all collections in a database.

All lexicons determine their order and uniqueness based on the collation specified (for `xs:string` types), and you can create multiple lexicons on the same object with different collations. For information on collations, see “Collations” on page 617. You can also create value lexicons on non-string values.

All of these types of lexicons have the following characteristics:

- Lexicon terms and values are case-sensitive.
- Lexicon terms and values are unstemmed.
- Lexicon terms and values are diacritic-sensitive.
- Lexicon terms and values do not have any relevance information associated with them.
- Uniqueness in lexicons is based on the specified collation of the lexicon.
- Lexicon terms in word lexicons do not include any punctuation. For example, the term `case-sensitive` in a database will be two terms in the lexicon: `case` and `sensitive`.
- Lexicon values in value lexicons do include punctuation.
- In order to perform lexicon-based queries, the appropriate lexicon must be created. If the lexicon has not been created, the lexicon query will throw an exception.
- Lexicons are used with the Search API to create constraints. Lexicons based on range indexes are used to create value constraints, which are used for facets. For details on the Search API, constraints, and facets, see "Search API: Understanding and Using" on page 28.

Even though the lexicons store terms case-sensitive, unstemmed, and diacritic-sensitive, you can still do case-insensitive and diacritic-insensitive lexicon-based queries by specifying the appropriate option(s). For details on the syntax, see the *MarkLogic XQuery and XSLT Function Reference*.

10.2 Creating Lexicons

You must create the appropriate lexicon before you can run lexicon-based queries. You can create lexicons using the Admin Interface or the Admin API. For detailed information on creating lexicons, see the "Text Indexing" and "Element/Attribute Range Indexes and Lexicons" chapters of the *Administrator's Guide*. You must complete at least one of the following tasks before you can successfully run lexicon-based queries:

- Create/enable the lexicon before you load data into the database, or
- Reindex the database after creating/enabling the lexicon, or
- Reload the data after creating/enabling the lexicon.

The following is a brief summary of how to create each of the various types of lexicons:

- To create a word lexicon for the entire database, enable the `word lexicon` setting on the Admin Interface Database Configuration page (Databases > *db_name*) and specify a collation for the lexicon (for example, `http://marklogic.com/collation/` for the UCA Root Collation).

- To create an element word lexicon, specify the element namespace URI, localname, and collation on the Admin Interface Element Word Lexicon Configuration page (Databases > *db_name* > Element Word Lexicons).
- To create an element attribute word lexicon, specify the element and attribute namespace URIs, localnames, and collation on the Admin Interface Element Attribute Word Lexicon Configuration page (Databases > *db_name* > Attribute Word Lexicons).
- To create an element value lexicon, specify the element namespace URI and localname, the collation (for `xs:string`), and the type (for example, `xs:string`) on the Admin Interface Range Element Index Configuration page (Databases > *db_name* > Element Indexes).
- To create an element attribute value lexicon, specify the element and attribute namespace URIs and localnames, the collation (for `xs:string`), and the type (for example, `xs:string`) on the Admin Interface Range Element-Attribute Index Configuration page (Databases > *db_name* > Attribute Indexes).
- To create a field value lexicon, first create a field in the Admin Interface (Databases > *db_name* > Fields). Then create the field value lexicon by specifying the type (for example, `xs:string`) and the field name on the Admin Interface Field Range Index Configuration page (Databases > *db_name* > Field Range Indexes).

  Note: If your system is set to reindex/refragment, newly created lexicons will not be available until reindexing is completed.

10.3 Word Lexicons

There are several types of word lexicons:

- Word Lexicon for the Entire Database
- Element/Element-Attribute Word Lexicons
- JSON Property Word Lexicons
- Field Word Lexicons

10.3.1 Word Lexicon for the Entire Database

A word lexicon covers the entire database, and holds all of the unique terms in the database, with uniqueness determined by the specified collation. You enable the word lexicon in the database page of the Admin Interface by enabling the `word lexicon` database setting. If the database already has content loaded, you must reindex the database before you can perform any lexicon queries. The following are the APIs for the word lexicon:

- `cts:words`
- `cts:word-match`

10.3.2 Element/Element-Attribute Word Lexicons

An XML element word lexicon or an XML element-attribute word lexicon contains all of the unique terms in the specified element or attribute, with uniqueness determined by the specified collation. The element word lexicons only contain words that exist in immediate text node children of the specified element as well as any text node children of elements defined in the Admin Interface as element-word-query-throughs or phrase-throughs; it does not include words from any other children of the specified element.

Create element and element-attribute word lexicons in the Admin Interface with the `Element Word Lexicons` and `Attribute Word Lexicons` links under the database in which you want to create the lexicons. You can also use the following Admin API functions:

- `admin:database-add-element-word-lexicon`
- `admin:database-add-element-attribute-word-lexicon`

Use the following functions to query element and element attribute word lexicons:

- `cts:element-words`
- `cts:element-word-match`
- `cts:element-attribute-words`
- `cts:element-attribute-word-match`

10.3.3 JSON Property Word Lexicons

A JSON property word lexicon contains all of the unique terms in the specified JSON property, with uniqueness determined by the specified collation. A JSON property word lexicon only contains words occurring in string values of the specified JSON property.

Create a JSON property word lexicon using the interfaces for XML element word lexicons. To create a lexicon with the Admin Interface, use the `Element Word Lexicons` section under the database in which you want to create the lexicon. To create a lexicon with the Admin API, use the function `admin:database-add-element-word-lexicon`.

Use the following functions to query JSON property word lexicons:

- `cts:json-property-words`
- `cts:json-property-word-match`

10.3.4 Field Word Lexicons

A field is a named object that you create at the database level, and it defines a set of elements which can be accessed together through the field. You can create word lexicons on fields, which list all of the unique words that are included in the field. You can create field word lexicons in the configuration page for each field. Like all other lexicons, field word lexicons are unique to a collation, and you can, if you need to, create multiple lexicons in different collations. For details on fields, see Fields Database Settings in the *Administrator's Guide*. The following are the APIs for the field word lexicons:

- `cts:field-words`
- `cts:field-word-match`

10.4 Element/Element-Attribute/Path Value Lexicons

An element value lexicon, element-attribute value lexicon, or a path value lexicon contains all of the unique values in the specified element or attribute. The values are the entire and exact contents of the specified element or attribute. You create element and element-attribute value lexicons in the Admin Interface by creating a range index of a particular type (for example, `xs:string`) for the element or attribute to which you want the value lexicon. The following are the APIs for the element, element-attribute, and path value lexicons:

- `cts:element-values`
- `cts:element-value-match`
- `cts:element-attribute-values`
- `cts:element-attribute-value-match`
- `cts:values`
- `cts:value-match`

The `cts:element-values` and `cts:element-value-match` functions are used to return values from element value lexicons implemented using element range indexes. The `cts:element-attribute-values` and `cts:element-attribute-value-match` functions are used to return values from attribute value lexicons implemented using attribute range indexes. The `cts:values` and `cts:value-match` functions are used to return values from path value lexicons implemented using path range indexes. A path value lexicon can be either an element or an attribute.

> **Note:** You can only create element value lexicons on simple elements (that is, the elements cannot have any element children).

When you have a value lexicon on an element or an attribute, you can also use the `cts:frequency` API to get fast and accurate counts of how many times the value occurs. You can either get counts of the number of fragments that have at least one instance of the value (using the default `fragment-frequency` option to the value lexicon APIs) or you can get total counts of values in each item (using the `item-frequency` option). For details and examples, see the documentation for `cts:frequency` and for the value lexicon APIs in the *MarkLogic XQuery and XSLT Function Reference*.

10.5 Field Value Lexicons

A field value lexicon contains all of the unique values for the specified field. You create field value lexicons in the Admin Interface by creating a range index of a particular type (for example, `xs:string`) for the field to which you want a field lexicon. The following are the APIs for field value lexicons:

- `cts:field-values`
- `cts:field-value-match`

When you have a value lexicon on a field, you can also use the `cts:frequency` API to get fast and accurate counts of how many times the value occurs. You can either get counts of the number of fragments that have at least one instance of the value (using the default `fragment-frequency` option to the value lexicon APIs) or you can get total counts of values in each item (using the `item-frequency` option). For details and examples, see the documentation for `cts:frequency` and for the value lexicon APIs in the *MarkLogic XQuery and XSLT Function Reference*.

Field value lexicons are useful in cases where something you want to treat as a discreet value does not occur in a single element or attribute. For example, consider the following XML structure:

```
<name>
  <first>Raymond</first>
  <middle>Clevie</middle>
  <last>Carver</last>
</name>
```

If you want to normalize names in the form `firstname lastname`, then you can create a field on this structure. The field might include the element `name` and exclude the element `middle`. The value of this instance of the field would then be `Raymond Carver`. If your document contained other name elements with the same structure, their values would be derived similarly. The range index for the field stores each unique instance of the field value.

For details on fields, see Fields Database Settings in the *Administrator's Guide*.

10.6 Value Co-Occurrences Lexicons

Value co-occurrence lexicons find pairs of element or attribute values that occur in the same fragment. If you have positions enabled in your range indexes, you can also specify a maximum word distance (`proximity=N` option) that the values must be from each other in order to match as a co-occurring pair. The following APIs support these lexicons:

- `cts:element-value-co-occurrences`
- `cts:element-attribute-value-co-occurrences`
- `cts:value-co-occurrences`
- `cts:field-value-co-occurrences`

These APIs return XML structures containing the pairs of co-occurring values. You can use `cts:frequency` on the output of these functions to find the frequency (the counts) of each co-occurrence.

Additionally, you can get co-occurrences from geospatial lexicons, as described in "Geospatial Lexicons" on page 439.

Note: Because the URI and collection lexicons are implemented as range indexes, you can specify a special QName for the document URI or collection URI lexicons to get the list of values with their URI or collections. The QNames are in the `http://marklogic.com/xdmp` namespace and the URI index has the local name `document` and the collection index has the local name `collection`, both using the `http://marklogic.com/collation/codepoint` collation. You can then use these QNames (for example, `xdmp:document` and `xdmp:collection`, as `xdmp` is bound to that namespace by default in the `1.0-ml` dialect) in `cts:element-value-co-occurrences` as one of the element QNames to find element value/document URI pairs or element value/collection URI pairs. Make sure to also specify the codepoint collation option for these QNames (for example, `"collation-2=http://marklogic.com/collation/codepoint"` if you are specifying one of these QNames as the second argument to `cts:element-value-co-occurences`).

Consider the following example with a document with the URI `/george.xml` that looks as follows:

```
<text>
  <e:person xmlns:e="http://marklogic.com/entity">George
  Washington</e:person> was the first President of the
  <e:gpe xmlns:e="http://marklogic.com/entity">United States</e:gpe>.
  <e:person xmlns:e="http://marklogic.com/entity">Martha
  Washington</e:person> was his wife.  They lived at
  <e:location xmlns:e="http://marklogic.com/entity">Mount
  Vernon</e:location>.
</text>
```

Before creating this document, create two string element range indexes: one for the `e:person` element and one for the `e:location` element, where `e` is bound to the namespace `http://marklogic.com/entity`.

Now you can run the following co-occurrence query to find all co-occurring people and locations:

```
xquery version "1.0-ml";

declare namespace e="http://marklogic.com/entity";
cts:element-value-co-occurrences(xs:QName("e:person"),
     xs:QName("e:location"))
```

This produces the following output:

```
<cts:co-occurrence xmlns:cts="http://marklogic.com/cts"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <cts:value xsi:type="xs:string">George Washington</cts:value>
  <cts:value xsi:type="xs:string">Mount Vernon</cts:value>
</cts:co-occurrence>
<cts:co-occurrence xmlns:cts="http://marklogic.com/cts"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <cts:value xsi:type="xs:string">Martha Washington</cts:value>
  <cts:value xsi:type="xs:string">Mount Vernon</cts:value>
</cts:co-occurrence>
```

If you wanted to get the frequency of how many of each co-occurring pair exist, either in each item or in each fragment (depending on whether you use the `item-frequency` or the default `fragment-frequency` option), use `cts:frequency` on the lexicon lookup as follows:

```
xquery version "1.0-ml";
declare namespace e="http://marklogic.com/entity";
for $x in cts:element-value-co-occurrences(xs:QName("e:person"),
               xs:QName("e:location"))
return cts:frequency($x)
(:
   returns a frequency of 1 for each pair if /george.xml
   is the only document in the database
:)
```

10.7 Geospatial Lexicons

The following APIs support the geospatial lexicons:

- `cts:element-attribute-pair-geospatial-boxes`
- `cts:element-attribute-pair-geospatial-value-match`
- `cts:element-attribute-pair-geospatial-values`
- `cts:element-attribute-value-geospatial-co-occurrences`
- `cts:element-child-geospatial-boxes`
- `cts:element-child-geospatial-value-match`
- `cts:element-child-geospatial-values`
- `cts:element-geospatial-boxes`
- `cts:element-geospatial-value-match`
- `cts:element-geospatial-values`
- `cts:element-pair-geospatial-boxes`
- `cts:element-pair-geospatial-value-match`
- `cts:element-pair-geospatial-values`
- `cts:element-value-geospatial-co-occurrences`

You must create the appropriate geospatial index to use its corresponding geospatial lexicon. For example, to use `cts:element-geospatial-values`, you must first create a geospatial element index. Use the Admin Interface (Databases > *database_name* > Geospatial Indexes) or the Admin API to create geospatial indexes for a database.

The `*-boxes` APIs return XML elements that show buckets of ranges, each bucket containing one or more `cts:box` values.

10.8 Range Lexicons

The range lexicons return values divided into buckets. The ranges are ranges of values of the type of the lexicon. A range index is required on the element(s) or attribute(s) specified in the range lexicon. The following APIs support these lexicons:

- `cts:element-attribute-value-ranges`
- `cts:element-value-ranges`
- `cts:value-ranges`
- `cts:field-value-ranges`

Additionally, there are the following geospatial box lexicons to find ranges of geospatial values divided into buckets:

- `cts:element-attribute-pair-geospatial-boxes`
- `cts:element-child-geospatial-boxes`
- `cts:element-geospatial-boxes`
- `cts:element-pair-geospatial-boxes`

The range lexicons return a sequence of XML nodes, one node for each bucket. You can use `cts:frequency` on the result set to determine the number of items (or fragments) in the buckets. The `"empties"` option specifies that an XML node is returned for buckets that have no values (that is, for buckets with a frequency of zero). By default, empty buckets are not included in the result set. For details about all of the options to the range lexicons, see the *MarkLogic XQuery and XSLT Function Reference*.

10.9 URI and Collection Lexicons

The URI and Collection lexicons respectively list all of the document URIs and all of the collection URIs in a database. To enable or disable these lexicons, use the Database Configuration page in the Admin Interface. Use these lexicons to quickly search through all of the URIs in a database. The following APIs support these lexicons:

- `cts:collection-match`
- `cts:collections`
- `cts:uri-match`
- `cts:uris`

10.10 Performing Lexicon-Based Queries

Lexicon queries return a sequence of words (or values in the case of value lexicons) from the appropriate lexicon. For string values, the words or values are returned in collation order, and the terms are case- and diacritic-sensitive. For other data types, the values are returned in order, where values that are "greater than" return before values that are "less than". This section lists the lexicon APIs and provides some examples and explanation of how to perform lexicon-based queries. It includes the following parts:

- Lexicon APIs
- Constraining Lexicon Searches to a cts:query Expression
- Using the Match Lexicon APIs
- Determining the Number of Fragments Containing a Lexicon Term

10.10.1 Lexicon APIs

Use the following Search Built-in XQuery APIs to perform lexicon-based queries:

- `cts:words`
- `cts:word-match`
- `cts:element-words`
- `cts:element-word-match`
- `cts:element-attribute-words`
- `cts:element-attribute-word-match`
- `cts:element-values`
- `cts:element-value-match`
- `cts:element-attribute-values`
- `cts:element-attribute-value-match`
- `cts:values`
- `cts:value-match`
- `cts:field-values`
- `cts:field-value-match`
- `cts:collection-match`
- `cts:collections`
- `cts:uri-match`
- `cts:uris`

In order to perform lexicon-based queries, the appropriate lexicon must be created. If the lexicon has not been created, the lexicon query will throw an exception.

The `cts:*-words` APIs return all of the words in the lexicon (or all of the words from a starting point if the optional `$start` parameter is used). The `cts:*-match` APIs return only words in the lexicon that match the wildcard pattern.

For details about the individual functions, see the Search APIs in the *MarkLogic XQuery and XSLT Function Reference*.

10.10.2 Constraining Lexicon Searches to a cts:query Expression

You can use the `$query` option of the lexicon APIs to constrain your lexicon lookups to fragments matching a particular `cts:query` expression. When you specify the `$query` option, the lexicon search returns all of the terms (or values for lexicon value queries) in the fragments that match the specified `cts:query` expression.

For example, the following is a query against a database of all of Shakespeare's plays fragmented at the SCENE level:

```
cts:words("et", (), "et tu")[1 to 10]

=> et ete even ever every eyes fais faith fall familiar
```

This query returns the first 10 words from the lexicon of words, starting with the word `et`, for all of the fragments that match the following query:

```
cts:word-query("et tu")
```

In the case of the Shakespeare database, there are 2 scenes that match this query, one from *The Tragedy of Julius Caesar* and one from *The Life of Henry the Fifth*. Note that this is a different set of words than if you omitted the `$query` parameter from the search. The following shows the query without the `$query` parameter. The results represent the 10 words in the entire word lexicon for all of the Shakespeare plays, starting with the word `et`:

```
cts:words("et")

=> et etc etceteras ete eternal eternally eterne eternity
   eternized etes
```

Note that when you constrain a lexicon lookup to a `cts:query` expression, it returns the lexicon items for any fragment in which the `cts:query` expression returns `true`. No filtering is done to the `cts:query` expression to validate that the match actually occurs in the fragment. In some cases, depending on the index options you have set, it can return `true` in cases where there is no actual match. For example, if you do not have `fast element word searches` enabled in the database configuration, it is possible for a `cts:element-word-query` to match a fragment because both the word and the element exist in the fragment, but not in the same element. The filtering stage of `cts:search` resolves these discrepancies, but they are not resolved in lexicon APIs that use the `$query` option. For details about how this works, see Understanding the Search Process and Understanding Unfiltered Searches sections in the *Query Performance and Tuning Guide*.

10.10.3 Using the Match Lexicon APIs

Each type of lexicon (word, element word, element-attribute word, element value, and element-attribute value) has a function (`cts:*-match`) which allows you to use a wildcard pattern to constrain the lexicon entries returned; the `cts:*-match` APIs return only words or values in the lexicon that match the wildcard pattern. The following query finds all of the words in the lexicon that start with `zou`:

```
cts:word-match("zou*")

=> Zounds zounds
```

It returns both the uppercase and lowercase words that match because search defaults to case-insensitive when all of the letters in the base of the wildcard pattern are lowercase. If you want to match the pattern case-sensitive, diacritic-sensitive, or with some other option, add the appropriate option to the query. For example:

```
cts:word-match("zou*", "case-sensitive")

=> zounds
```

For details on the query options, see the *MarkLogic XQuery and XSLT Function Reference*. For details on wildcard searches, see "Understanding and Using Wildcard Searches" on page 526.

10.10.4 Determining the Number of Fragments Containing a Lexicon Term

The lexicon contains the unique terms in a database. To minimize redundant disk I/Os when you are performing estimates following a query-constrained word lexicon lookup, and therefore for this type of query to be resolved as efficiently as possible, the `cts:word-query` should have the following characteristics:

- Specify the `unstemmed`, `case-sensitive`, and `diacritic-sensitive` options.
- Specify a `weight` of 0.

These characteristics ensure that the word being estimated is exactly the same as the word returned from the lexicon.

For example, if you want to figure out how many fragments contain a lexicon term, you can perform a query like the following:

```
<words>{
for $word in cts:words("aardvark", (),
     cts:directory-query("/", "infinity"))[1 to 1000]
  let $count := xdmp:estimate(cts:search(fn:doc(),
        cts:word-query($word,("unstemmed","case-sensitive",
                              "diacritic-sensitive"),0)))
return <word text="{$word}" count="{$count}"/> }
</words>
```

This query returns one `word` element per lexicon term, along with the matching term and counts of the number of fragments that have the term, under the specified directory (`/`), starting with the term `aardvark`. Sample output from this query follows:

```
<words>
  <word text="aardvark" count="10"/>
  <word text="aardvarks" count="10"/>
  <word text="aardwolf" count="5"/>
...
</words>
```

11.0 Using Range Queries in cts:query Expressions

MarkLogic Server allows you to access range indexes in a `cts:query` expression to constrain a search by a range of values in an element or attribute. This chapter describes some details about these range queries and includes the following sections:

- Overview of Range Queries
- Range Query cts:query Constructors
- Examples of Range Queries

11.1 Overview of Range Queries

This section provides an overview of what range queries are and why you might want to use them, and includes the following sections:

- Uses for Range Queries
- Requirements for Using Range Queries
- Performance and Coding Advantages of Range Queries

11.1.1 Uses for Range Queries

Range queries are designed to constrain searches on ranges of a value. For example, if you want to find all articles that were published in 2005, and if your content has an element (or an attribute or a property) named `PUBLISHDATE` with type `xs:date`, you can create a range index on the element `PUBLISHDATE`, then specify in a search that you want all articles with a `PUBLISHDATE` greater than December 31, 2004 and less than January 1, 2006. Because that element has a range index, MarkLogic Server can resolve the query extremely efficiently.

Because you can create range indexes on a wide variety of XML datatypes, there is a lot of flexibility in the types of content with which you can use range queries to constrain searches. In general, if you need to constrain on a value, it is possible to create a range index and use range queries to express the ranges in which you want to constrain the results.

11.1.2 Requirements for Using Range Queries

Keep in mind the following requirements for using range queries in your `cts:search` operations:

- Range queries require a range index to be defined on the element or attribute in which you want to constrain the results.
- The range index must be in the same collation as the one specified in the range query.
- If no collation is specified in the range query, then the query takes on the collation of the query (for example, if a collation is specified in the XQuery prolog, that is used). For details on collation defaults, see "How Collation Defaults are Determined" on page 622.

Because range queries require range indexes, keep in mind that range indexes take up space, add to memory usage on the machine(s) in which MarkLogic Server runs, and increase loading/reindexing time. As such, they are not exactly "free", although, particularly if you have a relatively small number of them, they will not use a huge amount of resources. The amount of resources used depends a lot on the content; how many documents have the elements and/or attributes specified, how often do those elements/attributes appear in the content, how large is the content set, and so on. As with many performance improvements, there are trade-offs to analyze, and the best way to analyze the impact is to experiment and see if the cost is worth the performance improvement. For details about range indexes and procedures for creating them, see the Range Indexes and Lexicons chapter in the *Administrator's Guide*.

11.1.3 Performance and Coding Advantages of Range Queries

Most of what you can express using range queries you can also express using predicates in XPath expressions. There are two big advantages of using range queries over XPath predicates:

- Performance
- Ease of coding

Using range queries in `cts:query` expressions can produce faster performance than using XPath predicates. Range indexes are in-memory structures, and because range indexes are required for range queries, they are usually very fast. There is no requirement for the range index when specifying an XPath predicate, and it is therefore possible to specify a predicate that might need to scan a large number of fragments, which could take considerable time. Additionally, because range queries are `cts:query` objects, you can use registered queries to pre-compile them, adding more performance advantages.

There are also coding advantages to range queries over XPath predicates. Because range queries are leaf-level `cts:query` constructors, they can be combined with other constructors (including other range query constructors) to form complex expressions. It is fairly easy to write XQuery code that takes user input from a form (from drop-down lists, text boxes, radio buttons, and so on) and use that user input to generate extremely complex `cts:query` expressions. It is very difficult to do that with XPath expressions. For details on `cts:query` expressions, see "Composing cts:query Expressions" on page 240.

11.2 Range Query cts:query Constructors

The following XQuery APIs are included in the range query constructors:

- `cts:element-attribute-range-query`
- `cts:element-range-query`
- `cts:path-range-query`
- corresponding accessor functions

Each API takes QNames, the type of operator (for example, >=, <=, and so on), values, and a collation as inputs. For details of these APIs and for their signatures, see the *MarkLogic XQuery and XSLT Function Reference*.

> **Note:** For release 3.2, range queries do not contribute to the score, regardless of the weight specified in the `cts:query` constructor.

11.3 Examples of Range Queries

The following are some examples that use range query constructors.

Consider a document with a URI `/dates.xml` with the following structure:

```
<root>
  <entry>
    <date>2007-01-01</date>
    <info>Some information.</info>
  </entry>
  <entry>
    <date>2006-06-23</date>
    <info>Some other information.</info>
  </entry>
  <entry>
    <date>1971-12-23</date>
    <info>Some different information.</info>
  </entry>
</root>
```

Assume you have defined an element range index of type `xs:date` on the QName `date` (note that you must either load the document after defining the range index or complete a reindex of the database after defining the range index).

You can now issue queries using the `cts:element-range-query` constructor. The following query searches the `entry` element of the document `/dates.xml` for entries that occurred on or before January 1, 2000.

```
cts:search(doc("/dates.xml")/root/entry,
  cts:element-range-query(xs:QName("date"), "<=",
      xs:date("2000-01-01") ) )
```

This query returns the following node, because it is the only one that satisfies the range query:

```
<entry>
    <date>1971-12-23</date>
    <info>Some different information.</info>
</entry>
```

The following query uses a `cts:and-query` to combine two date ranges, dates after January 1, 2006 and dates before January 1, 2008.

```
cts:search(doc("/dates.xml")/root/entry,
  cts:and-query((
   cts:element-range-query(xs:QName("date"), ">",
      xs:date("2006-01-01") ),
   cts:element-range-query(xs:QName("date"), "<",
      xs:date("2008-01-01") ) )) )
```

This query returns the following two nodes:

```
<entry>
    <date>2007-01-01</date>
    <info>Some information.</info>
</entry>

<entry>
    <date>2006-06-23</date>
    <info>Some other information.</info>
</entry>
```

12.0 Using Aggregate Functions

This chapter describes how to use builtin aggregate functions and aggregate user-defined functions (UDFs) to analyze values in lexicons and range indexes.

This chapter contains the following sections:

- Introduction to Aggregate Functions
- Using Builtin Aggregate Functions
- Using Aggregate User-Defined Functions

12.1 Introduction to Aggregate Functions

An aggregate function performs an operation over the values in one or more range indexes. For example, computing a sum or count over an element, attribute, or field range index. Aggregate functions are best used for analytics that produce a small number of results, such as computing a single numeric value across a set of range index values.

Aggregate functions use In-Database MapReduce, which greatly improves performance because:

- Analysis is parallelized across the hosts in a cluster, as well as across the database forests on each host.
- Analysis is performed close to the data.

MarkLogic Server provides builtin aggregate functions for common mathematical and statistical operations. You can also implement your own aggregate functions, using the Aggregate UDF interface. For details, see Implementing an Aggregate User-Defined Function in the *Application Developer's Guide*.

12.2 Using Builtin Aggregate Functions

MarkLogic Server provides the following builtin aggregate functions, accessible through the XQuery, REST, and Java APIs.

XQuery Function	REST and Java Aggregate Name
`cts:avg-aggregate`	`avg`
`cts:correlation`	`correlation`
`cts:count-aggregate`	`count`
`cts:covariance`	`covariance`

XQuery Function	REST and Java Aggregate Name
`cts:covariance-p`	`covariance-population`
`cts:max`	`max`
`cts:median`	`median`
`cts:min`	`min`
`cts:stddev`	`stddev`
`cts:stddev-p`	`stddev-population`
`cts:sum-aggregate`	`sum`
`cts:variance`	`variance`
`cts:variance-p`	`variance-population`

The table below summarizes how to call an aggregate function directly using the XQuery, REST and Java APIs:

Interface	Mechanism	Example

XQuery	Call the builtin function directly from your XQuery code.	`cts:sum-aggregate(`
		`  cts:element-reference(`
		`  xs:QName("Amount")`
		`  )`
		`)`

REST	Send a GET `/version/values/{name}` request, naming the function in the `aggregates` request parameter. For details, see Analyzing Lexicons and Range Indexes With Aggregate Functions in the *REST Application Developer's Guide*.	`GET` `/v1/values/amount?options=my-index-defns&aggregate=sum`

Java	Specify the aggregate name using `ValuesDefinition.setAggregate` and pass the `ValuesDefinition` to `QueryManager.values` or `QueryManager.tuples`. For details, see *Java Application Developer's Guide*.	`QueryManager qm = ...;`
		`ValuesDefinition vdef =`
		`  qm.newValuesDefinition(...);`
		`vdef.setAggregate("sum");`
		
		`TuplesHandle t =`
		`  qm.tuples(vdef,`
		`  new TuplesHandle());`

Interface	Mechanism	Example

Node.js	Specify the aggregate name using `valuesBuilder.aggregates` and use `DatabaseClient.values.read` to perform the computation. For details, see Analyzing Lexicons and Range Indexes with Aggregate Functions in the *Node.js Application Developer's Guide*.	`var vb = marklogic.valuesBuilder;`
		
		`db.values.read(`
		`  vb.fromIndexes('Amount')`
		`  .aggregates('sum')`
		`  .slice(0)`
		`)...`

You can also specify an aggregate function in a `<values/>` or `<tuples/>` element of query options. For example:

```
<options xmlns="http://marklogic.com/appservices/search">
  <values name="my-values">
    <aggregate apply="sum" />
    ...
  </values>
</options>
```

For more details, see "Search API: Understanding and Using" on page 28, the *Java Application Developer's Guide*, the *REST Application Developer's Guide*, or the *Node.js Application Developer's Guide*.

12.3 Using Aggregate User-Defined Functions

You can create an aggregate user-defined function (UDF) to analyze the values in one or more range indexes. An aggregate UDF must be installed before you can use it. For information on creating and installing aggregate UDFs, see User-Defined Functions in the *Application Developer's Guide*.

Aggregate UDFs are best for analyses that compute a small number of results over the values in one or more range indexes, rather than analyses that produce results in proportion to the number of range index values or the number of documents processed.

UDFs are identified by a relative path and a function name. The path is the path under which the plugin is installed. The path is *`scope/plugin-id`*, where *`scope`* is the scope passed to `plugin:install-from-zip` when the plugin is installed, and *`plugin-id`* is the ID specified in `<id/>` in the plugin manifest. For details, see Installing a Native Plugin in the *Application Developer's Guide*.

The following example uses an aggregate UDF called "myAvg" that is provided by the plugin installed with the path `native/sampleplugin`:

```
cts:aggregate("native/sampleplugin", "myAvg", ...)
```

The table below summarizes how to invoke aggregate UDFs in XQuery, Java, and RESTful applications.

Note: You can only pass extra parameters to an aggregate UDF from XQuery.

Interface	Mechanism	Example

XQuery	Call `cts:aggregate`, supplying the path to the native plugin that implements the aggregate and the aggregate name. Pass aggregate-specific parameters through the 4th argument.	`cts:aggregate(`
		`  **"native/samplePlugin",`**
		`  **"myAvg",`**
		`  cts:element-reference(`
		`  xs:QName("Amount")),`
		`  (plugin-arg1, plugin-arg2)`
		`)`

REST	Send a GET request to the `/values/{name}` service, supplying the path to the native plugin in `aggregatePath` and the function name in `aggregate`. For details, Analyzing Lexicons and Range Indexes With Aggregate Functions in the *REST Application Developer's Guide*.	`GET`
		`/v1/values/amount?options=myoptions&`
		`aggregatePath=native/samplePlugin&aggregate=myAvg`

Java	Set the aggregate name and path on a `ValuesDefinition`, then pass the `ValuesDefinition` to `QueryManager.values` or `QueryManager.tuples`. For details, see the *Java Application Developer's Guide*.	`QueryManager qm = ...;`
		`ValuesDefinition vdef =`
		`  qm.newValuesDefinition(...);`
		`vdef.setAggregate("myAvg");`
		`vdef.setAggregatePath(`
		`  "native/samplePlugin");`
		
		`TuplesHandle t =`
		`  qm.values(vdef,`
		`  new ValuesHandle());`

Node.js	Set the aggregate name and path using `valuesBuilder.udf` and `valuesBuilder.aggregates`, then use `DatabaseClient.values.read` to perform the computation. For details, see Analyzing Lexicons and Range Indexes with Aggregate Functions in the *Node.js Application Developer's Guide*.	`var vb =`
		`marklogic.valuesBuilder;`
		
		`db.values.read(`
		`  vb.fromIndexes('Amount')`
		`  .aggregates(`
		`  vb.udf(`
		`  '/native/samplePlugin,`
		`  'myAvg'))`
		`  .slice(0)`
		`)...`

You can also specify an aggregate UDF in a `<values/>` or `<tuples/>` element of query options. For example:

```
xquery version "1.0-ml";
import module namespace search =
"http://marklogic.com/appservices/search"
    at "/MarkLogic/appservices/search/search.xqy";

<options xmlns="http://marklogic.com/appservices/search">
  <values name="my-values">
    <aggregate apply="myAvg" udf="native/samplePlugin" />
    ...
  </values>
</options
```

For more details, see “Search API: Understanding and Using” on page 28, the *Java Application Developer’s Guide*, or the *REST Application Developer’s Guide*.

13.0 Highlighting Search Term Matches

This chapter describes ways you can use `cts:highlight` to wrap terms that match a search query with any markup. It includes the following sections:

- Overview of cts:highlight
- General Search and Replace Function
- Built-In Variables For cts:highlight
- Using cts:highlight to Create Snippets
- cts:walk Versus cts:highlight
- Common Usage Notes

For the syntax of `cts:highlight`, see the *MarkLogic XQuery and XSLT Function Reference*.

13.1 Overview of cts:highlight

When you execute a search in MarkLogic Server, it returns a set of nodes, where each node contains text that matches the search query. A common application requirement is to display the results with the matching terms highlighted, perhaps in bold or in a different color. You can satisfy these highlighting requirements with the `cts:highlight` function, which is designed with the following main goals:

- Make the task of highlighting search hits easy.
- Make queries that do text highlighting perform well.
- Make it possible to do more complex actions than simple text highlighting.

Even though it is designed to make it easy to highlight search term hits, the `cts:highlight` function is implemented as a general purpose function. The function substitutes search hits with an XQuery expression specified in the third argument. Because you can substitute the search term hits with any XQuery expression, you can perform all kinds of search and replace actions on terms that match a query. These search and replace operations will perform well, too, because `cts:highlight` is built-in to MarkLogic Server.

13.1.1 All Matching Terms, Including Stemmed, and Capitalized

When you use the standard XQuery string functions such as `fn:replace` and `fn:contains` to find matches, you must specify the exact string you want to match. If you are trying to highlight matches from a `cts:search` query, exact string matches will not find all of the hits that match the query. A `cts:highlight` query match, however, is anything that matches the `cts:query` specified as the second argument of `cts:highlight`.

If you have stemmed searches enabled, matches can be more than exact text matches. For example, `run`, `running`, and `ran` all match a query for `run`. For details on stemming, see "Understanding and Using Stemmed Searches" on page 507.

Similarly, query matches can have different capitalization than the exact word for which you actually searched. Additionally, wildcard matches (if wildcard indexes are enabled) will match a whole range of queries. Queries that use `cts:highlight` will find all of these matches and replace them with whatever the specified expression evaluates to.

13.2 General Search and Replace Function

Although it is designed to make highlighting easy, `cts:highlight` can be used for much more general search and replace operations. For example, if you wanted to replace every instance of the term `content database` with `contentbase`, you could issue a query similar to the following:

```
for $x in cts:search(//mynode, "content database")
return
cts:highlight($x, "content database", "contentbase")
```

This query happens to use the same search query in the `cts:search` as it does in the `cts:highlight`, but that is not required (although it is typical of text highlighting requirements). For example, the following query finds all of the nodes that contain the word `foo`, and then replaces the word `bar` in those nodes with the word `baz`:

```
for $x in cts:search(fn:doc(), "foo")
return
cts:highlight($x, "bar", "baz")
```

Because you can use any XQuery expression as the replace expression, you can perform some very complex search and replace operations with a relatively small amount of code.

13.3 Built-In Variables For cts:highlight

The `cts:highlight` function has three built-in variables which you can use in the replace expression. The expression is evaluated once for each query match, so each variable is bound to a sequence of query matches, and the value of the variables is the value of the query match for each iteration. This section describes the three variables and explains how to use them in the following subsections:

- Using the $cts:text Variable to Access the Matched Text
- Using the $cts:node Variable to Access the Context of the Match
- Using the $cts:queries Variable to Feed Logic Based on the Query
- Using $cts:start to Capture the String-Length Position
- Using $cts:action to Stop Highlighting

13.3.1 Using the $cts:text Variable to Access the Matched Text

The `$cts:text` variable holds the strings representing of the query match. For example, assume you have the following document with the URI `test.xml` in a database in which stemming is enabled:

```
<root>
  <p>I like to run to the market.</p>
  <p>She is running to catch the train.</p>
  <p>He runs all the time.</p>
</root>
```

You can highlight text from a query matching the word `run` as follows:

```
for $x in cts:search(doc("test.xml")/root/p, "run")
return
cts:highlight($x, "run", <b>{$cts:text}</b>)
```

The expression `<b>{$cts:text}</b>` is evaluated once for each query match, and it replaces the query match with whatever it evaluates to. Because `run`, `running`, and `ran` all match the `cts:query` for `run`, the results highlight each of those words and are as follows:

```
<p>I like to <b>run</b> to the market.</p>
<p>She is <b>running</b> to catch the train.</p>
<p>He <b>runs</b> all the time.</p>
```

13.3.2 Using the $cts:node Variable to Access the Context of the Match

The `$cts:node` variable provides access to the text node in which the match occurs. By having access to the node, you can create expressions that do things in the context of that node. For example, if you know your XML has a structure with a hierarchy of `book`, `chapter`, `section`, and `paragraph` elements, you can write code in the highlight expression to display the section in which each hit occurs. The following code snippet shows an XPath statement that returns the first element named `chapter` above the text node in which the highlighted term occurs:

```
$cts:node/ancestor::chapter[1]
```

You can then use this information to do things like add a link to display that chapter, search for some other terms within that chapter, or whatever you might need to do with the information. Once again, because `cts:highlight` evaluates an arbitrary XQuery expression for each search query hit, the variations of what you can do with it are virtually unlimited.

The following example shows how to use the `$cts:node` variable in a test to print the highlighted term in blue if its immediate parent is a `p` element, otherwise to print the highlightled term in red:

```
let $doc := <root>
                <p>This is blue.</p>
                <p><i>This is red italic.</i></p>
             </root>
return
cts:highlight($doc, cts:or-query(("blue", "red")),
 (if ( $cts:node/parent::p )
  then ( <font color="blue">{$cts:text}</font> )
  else ( <font color="red">{$cts:text}</font> ) )
            )
```

This query returns the following results:

```
<root>
 <p>This is <font color="blue">blue</font>.</p>
 <p><i>This is <font color="red">red</font>italic.</i></p>
</root>
```

13.3.3 Using the $cts:queries Variable to Feed Logic Based on the Query

The `$cts:queries` variable provides access to the `cts:query` that satisfies the query match. You can use that information to drive some logic about how you might highlight different queries in different ways.

For example, assume you have the following document with the URI `hellogoodbye.xml` in your database:

```
<root>
  <a>It starts with hello and ends with goodbye.</a>
</root>
```

You can then run the following query to use some simple logic which displays queries for `hello` in blue and queries for `goodbye` in red:

```
cts:highlight(doc("hellogoodbye.xml"),
              cts:and-query((cts:word-query("hello"),
                             cts:word-query("goodbye"))),
if ( cts:word-query-text($cts:queries) eq "hello" )
then ( <font color="blue">{$cts:text}</font> )
else ( <font color="red">{$cts:text}</font> ) )

returns:

<root>
  <a>It starts with <font color="blue">hello</font>
  and ends with <font color="red">goodbye</font>.</a>
</root>
```

13.3.4 Using $cts:start to Capture the String-Length Position

The `$cts:start` variable returns the starting position of the matching text (`$cts:text`), based on the string-length of the text node being processed (`$cts:node`).

13.3.5 Using $cts:action to Stop Highlighting

Use `xdmp:set` to change the value of `$cts:action` and specify what action should occur after processing a match. You can use this variable to control highlighting, typically based on some condition (such as how many matches have already occurred) that you have coded into your application). ou can specify for highlighting to `continue` (the default), to `skip` highlighting the remainder of the matches in the current text node, or to `break`, stopping highlighting for the rest of the input.

13.4 Using cts:highlight to Create Snippets

When you are performing searches, you often want to highlight the result of the search, showing only the part of the document in which the search match occurs. These portions of the document where the search matches are often called snippets. This section shows a simple example that describes the basic design pattern for using `cts:highlight` to create snippets. The example shown here is trivial in that it only prints out the parent element for the search hit, but it shows the pattern you can use to create useful snippets. A typical snippet might show the matched results in bold and show a few words before and after the results.

The basic design pattern to create snippets is to first run a `cts:search` to find your results, then, for search each match, run `cts:highlight` on the match to mark it up. Finally, you run the highlighted match through a recursive transformation or through some other processing to write out the portion of the document you are interested in. For details about recursive transformations, see Transforming XML Structures With a Recursive typeswitch Expression in the *Application Developer's Guide*.

The following example creates a very simple snippet for a search in the Shakespeare database. It simply returns the parent element for the text node in which the search matches. It uses `cts:highlight` to create a temporary element (named `HIGHLIGHTME`) around the element containing the search match, and then uses that temporary element name to find the matching element in the transformation.

```
xquery version "1.0-ml";
declare function local:truncate($x as item()) as item()*
{
  typeswitch ($x)
  case element(HIGHLIGHTME) return $x/node()
  case element(TITLE) return if ($x/../../PLAY) then $x else ()
  default return for $z in $x/node() return local:truncate($z)
};

let $query := "to be or not to be"
```

```
for $x in cts:search(doc(), $query)
return
local:truncate(cts:highlight($x, $query,
  <HIGHLIGHTME>{$cts:node/parent::element()}</HIGHLIGHTME>))
(:
   returns:
   <TITLE>The Tragedy of Hamlet, Prince of Denmark</TITLE>
   <LINE>To be, or not to be: that is the question:</LINE>
:)
```

This example simply returns the elements in which the match occurs (in this case, only one element matches the query) and the `TITLE` element that contains the title of the play. You can add any logic you want to create a snippet that is right for your application. For example, you might want to also print out the name of the act and the scene title for each search result, or you might want to calculate the line number for each result. Because you have the whole document available to you in the transformation, it is easy to do many interesting things with the content.

Note: The use of a recursive typeswitch makes sense assuming you are doing something interesting with various parts of the node returned from the search (for example, printing out the play title, act number, and scene name). If you only want to return the element in which the search match occurs, you can do something simpler. For example, you can use XPath on the highlighted expression to simplify this design pattern as follows:

```
let $query := "to be or not to be"
for $x in cts:search(doc(), $query)
return
cts:highlight($x, $query, <HIGHLIGHTME>{
    $cts:node/parent::element()}</HIGHLIGHTME>)//HIGHLIGHTME/node()
```

13.5 cts:walk Versus cts:highlight

The function `cts:walk` is similar to `cts:highlight`, but instead of returning a copy of the node passed in with the specified changes, it returns only the expression evaluations for the text node matches specified in the `cts:walk` call. Because `cts:walk` does not construct a copy of the node, it is faster than `cts:highlight`. In cases where you only need to return the expression evaluations, `cts:walk` will be more efficient than `cts:highlight`.

13.6 Common Usage Notes

This section shows some common usage patterns to be aware with when using `cts:highlight`. The following topics are included:

- Input Must Be a Single Node
- Using xdmp:set Side Effects With cts:highlight
- No Highlighting with cts:similar-query or cts:element-attribute-*-query

13.6.1 Input Must Be a Single Node

The input to `cts:highlight` must be a single node. That means that if you want to highlight query hits from a `cts:search` operation that returns multiple nodes, you must bind the results of the `cts:search` to a variable (in a `for` loop, for example), as in the following example:

```
for $x in cts:search(fn:doc(), "MarkLogic")
return
cts:highlight($x, "MarkLogic", <b>{$cts:text}</b>)
```

This query returns all of the documents in the database that contain `MarkLogic`, with `b` tags surrounding each query match.

Note: The input node to `cts:highlight` must be a document node or an element node; it cannot be a text node.

13.6.2 Using xdmp:set Side Effects With cts:highlight

If you want to keep the state of the highlighted terms so you can handle some instances differently than others, you can define a variable and then use the `xdmp:set` function to change the value of the variable as the highlighted terms are processed. Some common uses for this functionality are:

- Highlight only the first instance of a term.
- Highlight the first term in a different color then the rest of the terms.
- Keep a count on the number of terms matching the query.

The ability to change the state (also known as side effects) opens the door for infinite possibilities of what to do with matching terms.

The following example shows a query that highlights the first query match with a bold tag and returns only the matching text for the rest of the matches.

Assume you have following document with the URI `/docs/test.xml` in your database:

```
<html>
  <p>hello hello hello hello</p>
</html>
```

You can then run the following query to highlight just the first match:

```
let $count := 0
return
  cts:highlight(doc("/docs/test.xml"), "hello",
   (: Increment the count for each query match :)
    (xdmp:set($count, $count + 1 ),
     if ( $count = 1 )
     then ( <b>{$cts:text}</b> )
     else ( $cts:text ) )
```

```
        )

Returns:

<html>
  <p><b>hello</b> hello hello hello</p>
</html>
```

Because the expression is evaluated once for each query match, the `xdmp:set` call changes the state for each query match, having the side effect of the conditions being evaluated differently for each query match.

13.6.3 No Highlighting with cts:similar-query or cts:element-attribute-*-query

You cannot use `cts:highlight` to highlight results from queries containing `cts:similar-query` or any of the `cts:element-attribute-*-query` functions. Using `cts:highlight` with these queries will return the nodes without any highlighting.

14.0 Geospatial Search Applications

This chapter describes how to use the geospatial functions and describes the type of applications that might use these functions, and includes the following sections:

- Overview of Geospatial Data in MarkLogic Server
- Understanding Geospatial Coordinates and Regions
- Geospatial Indexes
- Performing a GeoSpatial Query
- Example: Simple XQuery Geospatial Search
- Summary of Other Geospatial Operations
- Converting To and From Common Geospatial Representations
- Constructing Geospatial Point and Region Values
- Geospatial Query Support in Other APIs

14.1 Overview of Geospatial Data in MarkLogic Server

In its most basic form, geospatial data is a set of latitude and longitude coordinates. Geospatial data in MarkLogic Server is marked up in XML elements and/or attributes and JSON properties. MarkLogic Server supports several common representations of geospatial data in XML and JSON. This section provides an overview of how geospatial data and queries work in MarkLogic Server, and includes the following topics:

- Terminology
- Coordinate System
- Types of Geospatial Queries
- XQuery Primitive Types And Constructors for Geospatial Queries
- Well-Known Text (WKT) and Well-Known Binary (WKB) Support

14.1.1 Terminology

The following terms are used to describe the geospatial features in MarkLogic Server:

- coordinate system

  A geospatial *coordinate system* is a set of mappings that map places on Earth to a set of numbers. The vertical axis is represented by a latitude coordinate, and the horizontal axis is represented by a longitude coordinate, and together they make up a coordinate system that is used to map places on the Earth. For more details, see “Latitude and Longitude Coordinates in MarkLogic Server” on page 466.

- point

  A geospatial *point* is the spot in the geospatial coordinate system representing the intersection of a given latitude and longitude. For more details, see "Points in MarkLogic Server" on page 466.

- proximity

  The *proximity* of search results is how close the results are to each other in a document. Proximity can apply to any type of search terms, included geospatial search terms. For example, you might want to find a search term *dog* that occurs within 10 words of a point in a given zip code.

- distance

  The *distance* between two geospatial objects refers to the geographical closeness of those geospatial objects.

14.1.2 Coordinate System

MarkLogic Server supports two types of coordinate systems for geospatial data:

- WGS84
- Raw

By default, MarkLogic Server uses the World Geodetic System (WGS84) as the basis for geocoding. WGS84 sets out a coordinate system that assumes a single map projection of the earth. WGS84 is widely used for mapping locations on the earth, and is used by a wide range of services, including many satellite services (notably: Global Positioning System—GPS) and Google Maps. There are other geocoding systems, some of which have advantages or disadvantages over WGS84 (for example, some are more accurate in a given region, some are less popular); MarkLogic Server uses WGS84, which is a widely accepted standard for global point representation. For details on WGS84, see http://en.wikipedia.org/wiki/World_Geodetic_System.

You can use the raw coordinate system when you want your points mapped onto a flat plane instead of onto the geometry of the earth.

14.1.3 Types of Geospatial Queries

You can use the search capabilities of MarkLogic to find documents containing points that match points or regions specified as input search criteria. The following types of geospatial queries are supported in MarkLogic Server:

- point query—matches a single point
- box query—any point within a rectangular box
- radius query—any point within a specified distance around a point
- polygon query—any point within a specified *n*-sided polygon

Geospatial query constructors are composable just like any other query constructors. For details, see "Composing cts:query Expressions" on page 240.

In addition to geospatial query constructors, MarkLogic provides built-in functions to perform geospatial operations such as calculating distance. For details, see "Summary of Other Geospatial Operations" on page 479.

> **Note:** Using the geospatial query constructors requires a valid geospatial license key; without a valid license key, searches that include geospatial queries will throw an exception.

14.1.4 XQuery Primitive Types And Constructors for Geospatial Queries

Geospatial queries and other operations are based on the following primitive geospatial types. Each of these geospatial primitive types is an instance of the `cts:region` base type.

XQuery	JavaScript
`cts:point`	`cts.point`
`cts:circle`	`cts.circle`
`cts:box`	`cts.box`
`cts:polygon`	`cts.polygon`
`cts:complex-polygon`	`cts.complexPolygon`
`cts:linestring`	`cts.linestring`

For each primitive type, a constructor of the same name exists for constructing values of that type. The constructors accept either the raw data, such as a pair of float values for constructing a point, or a string representing the serialization of the underlying primitive type.

For example, the following constructs a point from the raw data:

XQuery	JavaScript
`cts:point(38.7, -10.3)`	`cts.point(38.7, -10.3)`

For details, see "Constructing Geospatial Point and Region Values" on page 486.

You use these primitive types in geospatial `cts:query` constructors such as `cts:element-geospatial-query` and `cts:json-property-geospatial-query`, or their JavaScript equivalents. A geospatial query matches if the regions contain matching data in the context of a search. For details, see "Performing a GeoSpatial Query" on page 475.

These types are also used in geospatial operations such as the XQuery functions `geo:distance`, `geo:circle-intersects`, and `geo:polygon-contains`, or the JavaScript functions `geo.distance`, `geo.circleIntersects`, and `geo.polygonContains`. For details, see "Summary of Other Geospatial Operations" on page 479.

14.1.5 Well-Known Text (WKT) and Well-Known Binary (WKB) Support

MarkLogic supports the well-known text (WKT) and well-known binary (WKB) representations of geospatial data. You can use the following WKT and WKB objects in MarkLogic: `POINT`, `POLYGON`, `LINESTRING`, `TRIANGLE`, `MULTIPOINT`, `MULTILINESTRING`, `MULTIPOLYGON`, and `GEOMETRYCOLLECTION`.

For example, the following code uses ge.parseWkt to construct a polygon from its WKT representation:

Language	Example

XQuery	`geo:parse-wkt(`
	`  'POLYGON((0 0, 0 10, 10 10, 10 0, 0 0),(0 5, 0 7, 5 7, 5 5, 0 5))'`
	`)`

JavaScript	`geo.parseWkt(`
	`  'POLYGON((0 0, 0 10, 10 10, 10 0, 0 0),(0 5, 0 7, 5 7, 5 5, 0 5))'`
	`)`

For details, see "Converting To and From Common Geospatial Representations" on page 480.

14.2 Understanding Geospatial Coordinates and Regions

This section describes the rules for geospatial coordinates and the various regions (`cts:box`, `cts:circle`, `cts:complex-polygon`, `cts:linestring`, `cts:point`, and `cts:polygon`), and includes the following topics:

- Understanding the Basics of Coordinates and Points
- Understanding Geospatial Boxes
- Understanding Geospatial Polygons: Polygons, Complex Polygons, and Linestrings
- Understanding Geospatial Circles
- Linestrings

14.2.1 Understanding the Basics of Coordinates and Points

To understand how geospatial regions are defined in MarkLogic Server, you should first understand the basics of coordinates and of points. This section describes the following:

- Latitude and Longitude Coordinates in MarkLogic Server
- Points in MarkLogic Server

14.2.1.1 Latitude and Longitude Coordinates in MarkLogic Server

Latitudes have north/south coordinates. They start at 0 degrees for the equator and head north to 90 degrees for the north pole and south to -90 degrees for the south pole. If you specify a coordinate that is greater than 90 degrees or less than -90 degrees, the value is truncated to either 90 or -90, respectively.


Longitudes have east/west coordinates. They start at 0 degrees at the Prime Meridian and head east around the Earth to 180 degrees, and head west around the earth (from the Prime Meridian) to -180 degrees. If you travel 360 degrees, it brings you back to the Prime Meridian. If you go west from the Prime Meridian, the numbers go negative. For example, New York City is west of the Prime Meridian, and its longitude is -73.99 degrees. Adding or subtracting any multiple of 360 to a longitude coordinate gives an equivalent coordinate.

14.2.1.2 Points in MarkLogic Server

A point is simply a pair of latitude and longitude coordinates. Where the coordinates intersect is a place on the Earth. For example, the coordinates of San Francisco, California are a the pair that includes the latitude of 37.655983 and the longitude of -122.425525. The `cts:point` XQuery type or `cts.point` JavaScript type represent a point in MarkLogic Server. Use the `cts:point` or `cts.point` constructor to construct a point from a set of coordinates. Additionally, points are used to define the other regions in MarkLogic Server such `cts:box` in XQuery or `cts.polygon` in JavaScript.

14.2.2 Understanding Geospatial Boxes

Geospatial boxes allow you to make a region defined by four coordinates. The four coordinates define a *geospatial box* which, when projected onto a flat plane, forms a rectangular box. A point is said to be in that geospatial box if it is inside the boundaries of the box. The four coordinates that define a box represent the southern, western, northern, and eastern boundaries of the box. The box is two-dimensional, and is created by taking a projection from the three-dimensional Earth onto a flat surface. On the surface of the Earth, the edges of the box are arcs, but when those arcs are projected into a plane, they become two-dimensional latitude and longitude lines, and the space defined by those lines forms a rectangle (represented by a `cts:box` in XQuery or a `cts.box` in JavaScript), as shown in the following figure.



Projecting coordinates from the curved earth into a flat box

The following are the assumptions and restrictions associated with geospatial boxes:

- The four points on a box are south, west, north, and east, in that order.
- Assuming a projection from the Earth onto a two-dimensional plane, boxes are determined by going from the south western limit to south eastern limit (even if it passes the date line), then north to the north eastern limit (border on the poles), then west to the north western limit, then back south to the south western limit where you started.
- When determining the west/east boundary of the box, you always start at the western longitude and head east toward the eastern longitude. This means that if your western point is east of the date line, and your eastern point is west of the date line, then you will head east around the Earth until you get back to the eastern point.
- Similarly, when determining the south/north sides of the box, you always start at the southern latitude and head north to the northern latitude. You cannot cross the pole, however, as it does not make sense to have the northern point south of the southern point. If you do cross a pole, a search that uses that box will throw an `XDMP-BADBOX` runtime error (because you cannot go north from the north pole). Note that the error will happen at search time, not at box creation time.

- If the eastern coordinate is equal to the western coordinate, then only that longitude is considered. Similarly, if the northern coordinate is equal to the southern coordinate, only that latitude is considered. The consequence of these facts are the following:
    - If the western and eastern coordinates are the same, the box is a vertical line between the southern and northern coordinates passing through that longitude coordinate.
    - If the southern and northern coordinates are the same, the box is a horizontal line between the western and eastern coordinates passing through that latitude coordinate.
    - If the western and eastern coordinates are the same, and if the southern and northern coordinates are the same, then the box is a point specified by those coordinates.
- The boundaries on the box are either in or out of the box, depending on query options (there are various boundary options on the geospatial `cts:query` constructors to control this behavior).

14.2.3 Understanding Geospatial Polygons: Polygons, Complex Polygons, and Linestrings

Geospatial polygons allow you to make a region with n-sided boundaries for your geospatial queries. These boundaries can represent any area on Earth (with the exceptions described below). For example, you might create a polygon to represent a country or a geographical region. There are three ways to construct these types of geospatial regions in MarkLogic: polygons, complex polygons, and linestrings. This section describes some of the charateristics of polygons, and includes the following topics:

- Overview of Polygons
- Polygons
- Complex Polygons
- Linestrings

14.2.3.1 Overview of Polygons

Polygons offer a large degree of flexibility compared with circles or boxes. In exchange for the flexibility, geospatial polygons are not quite as fast and not quite as accurate as geospatial boxes. The efficiency of the polygons is proportional to the number of sides to the polygon. For example, a typical 10-sided polygon will likely perform faster than a typical 1000-sided polygon. The speed is dependent on many factors, including where the polygon is, the nature of your geospatial data, and so on.

The following are the assumptions and restrictions associated with geospatial polygons:

- Assumes the Earth is a sphere, divided by great circle arcs running through the center of the earth, one great circle divided the longitude (running through the Greenwich Meridian, sometimes called the Prime Meridian) and the other dividing the latitude (at the equator).
- Each side of the polygons are semi-spherical projections from the endpoints onto the spherical Earth surface. Therefore, the lines are not all in a single plane, but instead follow the curve of the Earth (approximated to be a sphere).
- A polygon cannot include both poles. Therefore, it cannot have both poles as a boundary (regardless of whether the boundaries are included), which means it cannot encompass the full 180 degrees of latitude.
- A polygon edge must be less than 180 degrees; that is, two adjacent points of a polygon must wrap around less than half of the earth's longitude or latitude. If you need a polygon to wrap around more than 180 degrees, you can still do it, but you must use more than two points. Therefore, adjacent vertices cannot be separated by more than 180 degrees of longitude. As a result, a polygon cannot include the pole, except along one of its edges. Also as a result, if two points that make up a polygon edge are greater than 180 degrees apart, MarkLogic Server will always choose the direction that is less than 180 degrees.
- Geospatial queries are constrained to XML elements, XML attributes, and JSON properties named in the query constructors. To cross multiple formats in a single query, use `cts:or-query` in XQuery or `cts.orQuery` in JavaScript.
- Some searches will throw a runtime exception if a polygon is not valid for the coordinate system. You specify the coordinate system at search time, not at polygon construction time.
- The boundaries on the polygon are either in or out of the polygon, depending on query options. You can set a variety of boundary options to control this behavior when constructing geospatial queries.
- Because of the spherical Earth assumption, and because points are represented by floats, results are not exact; polygons are not as accurate as the other methods because they use a sphere as a model of the Earth. While it may not be that intuitive, floats are used to represent points on the Earth because it turns out that there is no benefit in the accuracy if you use doubles (the Earth is just not that big).

14.2.3.2 Polygons

You can construct a polygon by specifying the points that make up the vertices of the polygon. All points that are bounded by the resulting region are defined to be contained within the region.

For details, see the `cts:polygon` XQuery function or the `cts.polygon` JavaScript function.

14.2.3.3 Complex Polygons

You can construct a complex polygon by constructing a polygon within zero or more other polygons. The resulting complex polygon is the part within the outer polygon but not within the inner polygon(s). Use the `cts:complex-polygon` XQuery function or the `cts.complexPolygon` JavaScript function to construct a complex polygon.

You can also cast a `cts:complex-polygon` or `cts.complexPolygon` with no holes (that is, with no inner polygons) to a `cts:polygon` or `cts.polygon`. If you specify multiple inner polygons, none of them should overlap each other.

14.2.3.4 Linestrings

A linestring is a sequence of connected joined arcs that do not necessarily form a closed loop the way a polygon forms a closed loop (although it is permissible for a linestring to form a closed loop). The "lines" are actually arcs because they are projected onto the earth's surface. A linestring supports equality and inequality: two linestrings are equal if all of their verticies are equal (or if they are both empty). You can cast a linestring to a polygion, resulting in a "flat" polygon that traces the same set of linestrings back to close the polygon.

To construct a linestring, use the `cts:linestring` XQuery function or the `cts.linestring` JavaScript function.

14.2.4 Understanding Geospatial Circles

Geospatial circles allow you to define a region with boundaries defined by a point with a radius specified in miles. The point and radius define a circle, and anything inside the circle is within the boundaries of the circle. The circle boundaries are either in or out, depending on query options. You can set a variety of boundary options to control this behavior when constructing geospatial queries.

To construct a circle, use the `cts:circle` XQuery function or the `cts.circle` JavaScript function.

14.3 Geospatial Indexes

Because you can store geospatial data as XML or JSON within a document, you can query the content constraining on the geospatial XML or JSON markup. You can create geospatial indexes to speed up geospatial queries and to enable geospatial lexicon queries, allowing you to take full advantage of having the geospatial data in your content. This section describes the different kinds of geospatial indexes and includes the following parts:

- Different Kinds of Geospatial Indexes
- Geospatial Index Positions
- Geospatial Lexicons

14.3.1 Different Kinds of Geospatial Indexes

This section describes the types of geospatial indexes and the structure of geospatial data assumed by each index type. You use the same index interfaces for both JSON and XML, but the structure of the data is different, as described in this section.

Use the Admin Interface to create any of these indexes, under Database > *database_name* > Geospatial Indexes. To learn more about creating indexes, see Range Indexes and Lexicons in the *Administrator's Guide*.

This section covers the following topics:

- Geospatial Element Indexes
- Geospatial XML Element Child Indexes
- Geospatial XML Element Pair Indexes
- Geospatial XML Attribute Pair Indexes
- Geospatial Path Range Indexes
- Geospatial JSON Property Indexes
- Geospatial JSON Property Child Indexes
- Geospatial JSON Property Pair Indexes

Note: You must have a valid geospatial license key to create or use any geospatial indexes.

14.3.1.1 Geospatial Element Indexes

With a geospatial element index, the geospatial data is represented by whitespace or punctuation (except `+`, `-`, or `.`) separated element content:

```
<element-name>37.52  -122.25</element-name>
```

For `point` format, the first entry represents the latitude coordinate, and the second entry represents the longitude coordinate. For `long-lat-point` format, the first entry represents the longitude coordinate and the second entry represents the latitude coordinate. You can also have other entries, but they are ignored (for example, KML has an additional altitude coordinate, which can be present but is ignored).

For JSON data requirements, see "Geospatial JSON Property Indexes" on page 473.

14.3.1.2 Geospatial XML Element Child Indexes

With a geospatial element child index, the geospatial data comes from whitespace or punctuation (except `+`, `-`, or `.`) separated element content, but only for elements that are a specific child of a specific element.

```
<element-name1>
  <element-name2>37.52  -122.25</element-name2>
</element-name1>
```

For `point` format, the first entry represents the latitude coordinate, and the second entry represents the longitude coordinate. For `long-lat-point` format, the first entry represents the longitude coordinate and the second entry represents the latitude coordinate.

For JSON data requirements, see "Geospatial JSON Property Child Indexes" on page 473.

14.3.1.3 Geospatial XML Element Pair Indexes

With a geospatial element pair index, the geospatial data comes from a specific pair of elements that are a child of another specific element.

```
<element-name>
  <latitude>37.52</latitude>
  <longitude>-122.25</longitude>
</element-name1>
```

For JSON data requirements, see "Geospatial JSON Property Pair Indexes" on page 474.

14.3.1.4 Geospatial XML Attribute Pair Indexes

With a geospatial attribute pair index, the geospatial data comes from a pair of specific attributes of a specific element.

```
<element-name latitude="37.52" longitude="-122.25"/>
```

14.3.1.5 Geospatial Path Range Indexes

With a geospatial path range index, the geospatial data is expressed in the same manner as a geospatial element index and the XML element, XML attribute, or JSON property to index is defined by a path expression.

The following table demonstrates the XPath expression to use when creating a path range index for several forms of example geospatial data.

Format	Example Data	Indexing Path Expression
XML	<a:data> <a:geo>37.52 -122.25</a:geo> </a:data>	/a:data/a:geo
XML	<a:data> <a:geo data="37.52 -122.25"/> </a:data>	/a:data/a:geo/@data

JSON	{ "geometry" : {
	  "type": "Point",
	  "coordinates": [37.52, -122.25]
	  }
	}
		/geometry[type="Point"]/array-node("coordinates")

Note: Once you have created a geospatial path range index using the Admin Interface, you cannot change the path expression. To change the path, you must remove the existing geospatial path range index and create a new one.

14.3.1.6 Geospatial JSON Property Indexes

Use a geospatial element index to index geospatial data in JSON documents when the point coordinates are contained in a single JSON property. The geospatial data must be represented in the property value as either whitespace/punctuation separated values in a string, or as an array of values. For example:

```
"prop-name": "37.52 -122.25"

"prop-name": [37.52, -122.25]
```

For `point` format, the first entry represents the latitude coordinate, and the second entry represents the longitude coordinate. For `long-lat-point` format, the first entry represents the longitude coordinate and the second entry represents the latitude coordinate. The value can include other entries, but they are ignored (for example, KML has an additional altitude coordinate, which can be present but is ignored).

14.3.1.7 Geospatial JSON Property Child Indexes

Use a geospatial element child index to index geospatial data in JSON when you want to limit the index to coordinate properties contained in a specific property. The geospatial data must be represented in the child property value as either whitespace/punctuation separated values in a string, or as an array of values.

For example, if your data looks like one of the following, you could create a geospatial element child index specifying "`theParent`" as the parent element (property) and "`theChild`" as the child element (property).

```
"theParent": {
  "theChild": "37.52 -122.25"
}

"theParent": {
  "theChild": [37.52, -122.25]
}
```

For `point` format, the first entry represents the latitude coordinate, and the second entry represents the longitude coordinate. For `long-lat-point` format, the first entry represents the longitude coordinate and the second entry represents the latitude coordinate.

14.3.1.8 Geospatial JSON Property Pair Indexes

Use a geospatial element pair index to index geospatial data in JSON when the point coordinates are contained in sibling JSON properties. For example, use this type of index when working with data similar to the following:

```
"theParent" : {
  "latitude": 37.52,
  "longitude": -122.25
}
```

14.3.2 Geospatial Index Positions

Each geospatial index has a range value positions option. Enabling range value positions speeds up queries that constrain a search by the distance between geospatial data and other search terms in the document, such as when using `cts:near-query` in XQuery or `cts.nearQuery` in Javascript.

Additionally, enabling element positions improves index resolution (more accurate estimates) for XML element and JSON property queries that involve geospatial queries (with a geospatial index with positions enabled for the geospatial data).

14.3.3 Geospatial Lexicons

Geospatial indexes enable geospatial lexicon lookups. The lexicon lookups enable very fast retrieval of geospatial values. For details on geospatial lexicons, see “Geospatial Lexicons” on page 439.

14.4 Performing a GeoSpatial Query

This section provides an overview of the Geospatial API, and includes the following parts:

- Basic Procedure for Performing a Geospatial Query
- Geospatial Query Constructors
- Geospatial Format Conversion Functions
- Example: Simple XQuery Geospatial Search

14.4.1 Basic Procedure for Performing a Geospatial Query

Using the geospatial API is just like using any `cts:query` constructors, where you use the `cts:query` as the second parameter (or a building block of the second parameter) of `cts:search`. The basic procedure involves the following steps:

1. Load geospatial data into a database.
2. Create geospatial indexes, if needed.
3. Construct primitive types to use in geospatial `cts:query` constructors.
4. Construct geospatial queries that use the geospatial primitive types.
5. Use the geospatial queries with the `cts:search` XQuery function or the `cts.search` JavaScript function.

Creating appropriate geospatial indexes in Step 2 can improve both speed and accuracy. Indexes are required for certain kinds of queries, such as range queries. Indexes are optional for queries such as value queries, but only if you use unfiltered search, which slows your search down. For details, see Fast Pagination and Unfiltered Searches in the *Query Performance and Tuning Guide*.

You can also use the non-search geospatial operations, such as the `cts:contains` XQuery function or the `cts.contains` JavaScript function. You can use such geospatial functions whether or not the input geospatial data is in the database.

14.4.2 Geospatial Query Constructors

The following geospatial query constructors are available. You can use these constructors with each other and with other `cts:query` constructors to build up complex queries.

XQuery	JavaScript
`cts:element-attribute-pair-geospatial-query`	`cts.elementAttributePairGeospatialQuery`
`cts:element-child-geospatial-query`	`cts.elementChildGeospatialQuery`
`cts:element-geospatial-query`	`cts.elementGeospatialQuery`
`cts:element-pair-geospatial-query`	`cts.elementPairGeospatialQuery`
`cts:json-property-child-geospatial-query`	`cts.jsonPropertyChildGeospatialQuery`
`cts:json-property-geospatial-query`	`cts.jsonPropertyGeospatialQuery`
`cts:json-property-pair-geospatial-query`	`cts.jsonPropertyPairGeospatialQuery`
`cts:path-geospatial-query`	`cts.pathGeospatialQuery`

For an example, see "Example: Simple XQuery Geospatial Search" on page 477.

You can also create geospatial queries from query text using the XQuery cts:parse function or the Server-Side JavaScript cts.parse function. For details, see "Creating a Query From Search Text With cts:parse" on page 245.

14.4.3 Geospatial Format Conversion Functions

MarkLogic provides XQuery and JavaScript library modules to translate Metacarta, GML, KML, GeoRSS, and GeoJSON formats to MarkLogic primitive geospatial types such as `cts:box`, `cts:circle`, `cts:point`, and `cts:polygon`.

The functions in these libraries are designed to take geospatial data in supported formats and construct `cts:region` primitive types to pass into the geospatial `cts:query` constructors and other geospatial operations.

For the signatures of these functions, see the Library Module section of the *MarkLogic XQuery and XSLT Function Reference* or the *MarkLogic Server-Side JavaScript Function Reference*.

14.4.4 Example: Simple XQuery Geospatial Search

This section provides an example showing a `cts:search` that uses a geospatial query.

Assume a document with the URI `/geo/zip_labels.xml` with the following form:

```
<labels>
  <label id="1">96044</label>
  ...
  <label id="589">95616</label>
  <label id="712">95616</label>
  <label id="715">95616</label>
  ...
</labels>
```

Assume you have polygon data in a document with the URI `/geo/zip.xml` with the following form:

```
<polygon id="712">
       0.383337584506173E+02,       -0.121659014798844E+03
       0.383133840000000E+02,       -0.121656011000000E+03
       0.383135090000000E+02,       -0.121666647000000E+03
       0.383135090000000E+02,       -0.121666647000000E+03
       0.383135120000000E+02,       -0.121666875000000E+03
       0.383349030000000E+02,       -0.121667035000000E+03
       0.383353510000000E+02,       -0.121657355000000E+03
       0.383496550000000E+02,       -0.121656811000000E+03
       0.383495590000000E+02,       -0.121646955000000E+03
       0.383494950000000E+02,       -0.121645323000000E+03
       0.383473190000000E+02,       -0.121645691000000E+03
       0.383370790000000E+02,       -0.121650187000000E+03
       0.383133840000000E+02,       -0.121656011000000E+03
</polygon>
```

You can then take the contents of the polygon element and cast it to a `cts:polygon` using the `cts:polygon` constructor. For example, the following returns a `cts:polygon` for the above data:

```
cts:polygon(fn:data(fn:doc("/geo/zip.xml")//polygon[@id eq "712"]))
```

Further assume you have content of the following form:

```
<feature id="1703188" class="School">
  <name>Ralph Waldo Emerson Junior High School</name>
  <state id="06">CA</state>
  <county id="113">Yolo</county>
  <lat dms="383306N">38.5515731</lat>
  <long dms="1214639W">-121.7774624</long>
  <elevation>17</elevation>
  <map>Merritt</map>
</feature>
```

Now consider the following XQuery:

```
let $searchterms := ("school", "junior")
let $zip := "95616"
let $ziplabel :=
fn:doc("/geo/zip_labels.xml")//label[contains(.,$zip)]
let $polygons :=
   for $p in fn:doc("/geo/zip.xml")//polygon[@id=$ziplabel/@id]
   return cts:polygon(fn:data($p))
let $query :=
   cts:and-query((
       for $term in $searchterms return cts:word-query($term),
       cts:element-pair-geospatial-query(xs:QName("feature"),
             xs:QName("lat"), xs:QName("long"), $polygons) ))
return  (
<h2>{fn:concat("Places with the term '",
               fn:string-join($searchterms, "' and the term '"),
               "' in the zipcode ", fn:data($zip), ":")}</h2>,
  <ol>{for $feature in cts:search(//feature, $query)
  order by $feature/name
  return (
  <li><h3>{fn:data($feature/name)," "}
  <code>({fn:data($feature/lat)},{fn:data($feature/long)})</code></h3>
  <p>{fn:data($feature/@class)} in {fn:data($feature/county)},
  {fn:data($feature/state)} from map {fn:data($feature/map)}</p></li> )
  }</ol> )
```

This returns results similar to the following (shown rendered in a browser):

Places with the term 'school' and the term 'junior' in the zipcode 95616:

1. **Emerson Junior High School** `(38.5476843,-121.7452392)`

   School in Yolo, CA from map Davis

2. **Oliver Wendell Holmes Junior High School** `(38.556573,-121.7363502)`

   School in Yolo, CA from map Davis

3. **Ralph Waldo Emerson Junior High School** `(38.5515731,-121.7774624)`

   School in Yolo, CA from map Merritt

14.5 Summary of Other Geospatial Operations

The following APIs are used to perform various operations and calculations on geospatial data:

XQuery	JavaScript
geo:polygon-contains	geo.polygonContains
geo:complex-polygon-contains	geo.complexPolygonContains
geo:region-contains	geo.regionContains
geo:arc-intersection	geo.arcIntersection
geo:box-intersects	geo.boxIntersects
geo:circle-intersects	geo.circleIntersects
geo:polygon-intersects	geo.polygonIntersects
geo:complex-polygon-intersects	geo.complexPolygonIntersects
geo:region-intersects	geo.regionIntersects
geo:region-approximate	geo.regionApproximate
geo:region-clean	geo.regionClean
geo:bounding-boxes	geo.boundingBoxes
geo:polygon-to-linestring	geo.polygonToLinestring
geo:linestring-reverse	geo.linestringReverse
geo:linestring-concat	geo.linestringConcat
geo:circle-polygon	geo.circlePolygon
geo:ellipse-polygon	geo.ellipsePolygon
geo:interior-point	geo.interiorPoint
geo:count-vertices	geo.countVertices
geo:count-distinct-vertices	geo.countDistinctVertices
geo:remove-duplicate-vertices	geo.removeDuplicateVertices
geo:distance	geo.distance

XQuery	JavaScript
`geo:shortest-distance`	`geo.shortestDistance`
`geo:destination`	`geo.destination`
`geo:bearing`	`geo.bearing`
`geo:approx-center`	`geo.approxCenter`
`geo:region-affine-transform`	`geo.regionAffineTransform`

For signatures and more details, see the Library Module section of the *MarkLogic XQuery and XSLT Function Reference* or the *MarkLogic Server-Side JavaScript Function Reference*.

14.6 Converting To and From Common Geospatial Representations

MarkLogic provides interfaces for converting between MarkLogic geospatial primitive types and several common geospatial text, XML, and JSON representations. This section covers the following topics:

- Conversion Overview
- WKT and WKB Conversions in XQuery
- WKT and WKB Conversions in JavaScript
- Mapping of WKT and WKB Types to MarkLogic Types

14.6.1 Conversion Overview

You can use MarkLogic APIs to convert to and from the following common geospatial representations:

- Well-Known Text (WKT)
- Well-Known Binary (WKB)
- GML
- KML
- GeoJSON
- GeoRSS

For example, the following XQuery code uses `geo:parse-gml` to convert a GML region into a `cts:region` (a polygon in this case). This function determines the output `cts:region` type from the kind of input GML region.

```
import module namespace geogml ="http://marklogic.com/geospatial/gml"
  at "/MarkLogic/geospatial/gml.xqy";

geogml:parse-gml(
  <gml:Polygon srsName="ML:wgs84"
      xmlns:gml="http://www.opengis.net/gml/3.2">
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="2">
          5.0 1.0 8.0 1.0 8.0 6.0 5.0 7.0 5.0 1.0
        </gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:Polygon>
)
```

If you know the input region type, you can also use one of the region-specific constructors to perform the equivalent conversion. For example, the above code could use `geogml:polygon` instead of `geogml:parse-gml`. For details, see "Constructing Geospatial Point and Region Values" on page 486.

The following Server-Side JavaScript code converts a GeoJSON polygon into a `cts.polygon`:

```
// Create a cts.polygon from a GeoJSON polygon
var geojson = require('/MarkLogic/geospatial/geojson.xqy');

geojson.polygon(
  { type: 'Polygon',
    coordinates: [
      [[100.0,0.0], [101.0, 0.0], [101.0, 1.0], [100.0, 1.0], [100.0, 0.0]]
  ] }
)
```

For each format, the XQuery API includes a `parse-`*`format`* function for converting from the common representation to a MarkLogic geospatial primitive type, and the JavaScript API includes a `parse`*`Format`* function for the same purpose. This operation is equivalent to calling the `geo:parse` XQuery function or the `geo.parse` JavaScript function with input of the same format. The API also includes a `to-`*`format`* XQuery function and `to`*`Format`* JavaScript function for converting from a MarkLogic primitive type to the target format.

For example, the GeoJSON library module includes the following functions that can be used to convert data between GeoJSON and `cts:region`.

XQuery	JavaScript
`geojson:parse-geojson`	`geojson.parseGeojson`
`geojson:to-geojson`	`geojson.toGeojson`
`geojson:box`	`geojson.box`
`geojson:circle`	`geojson.circle`
`geojson:complex-polygon`	`geojson.complexPolygon`
`geojson:linestring`	`geojson.linestring`
`geojson:multi-linestring`	`geojson.multiLinestring`
`geojson:point`	`geojson.point`
`geojson:polygon`	`geojson.polygon`

You can use the built-in `geo:parse` XQuery function or `geo.parse` JavaScript function to convert nodes in any of the supported formats into an equivalent MarkLogic geospatial primitive type, without regard to the input format or region type. For best performance, if you know the format, use the equivalent format-specific functions.

14.6.2 WKT and WKB Conversions in XQuery

MarkLogic represents geospatial data using the `cts:region` type and types derived from it, such as `cts:point`, `cts:polygon`, and `cts:circle`. You can convert from WKT or WKB into `cts:region` items and from `cts:region` into WKT or WKB.

Use the `geo:parse-wkt` function to convert WKT data into a sequence of `cts:region` items. Similarly, use `geo:parse-wkb` to convert WKB data into a sequence of `cts:region` items. You can use the resulting items in geospatial `cts:query` constructors or geospatial operations.

For example, the following call converts a WKT polygon with an inner and outer boundary into a `cts:complex-polygon`:

```
geo:parse-wkt("
 POLYGON(
  (0 0, 0 10, 10 10, 10 0, 0 0),
  (0 5, 0 7, 5 7, 5 5, 0 5) )" )
```

The input to `geo:parse-wkb` is a binary node that contains a WKB byte sequence. For example, the following code converts a WKB byte sequence representing the coordinates (-73.700380647, 40.739754168) into a `cts:point`:

```
geo:parse-wkb(
  binary { "01010000072675909D36C52C0E151BB43B05E4440" }
)
```

To convert from `cts:region` to WKT, use `geo:to-wkt`. For example, the following code returns a WKT `POINT`:

```
geo:to-wkt(cts:point(1, 2))
```

Similarly, the following code returns a WKB `POINT`:

```
geo:to-wkb(cts:point(1, 2))
```

You cannot convert a `cts:circle` or a `cts:box` to WKT. For more details on WKT, see http://en.wikipedia.org/wiki/Well-known_text.

14.6.3 WKT and WKB Conversions in JavaScript

MarkLogic represents geospatial data using the `cts.region` type and types derived from it, such as `cts.point`, `cts.polygon`, and `cts.circle`. MarkLogic provides the following conversions between WKT or WKB and `cts.region`: You can use the `cts.region` representation `cts:query` constructors or geospatial operations.

- Explict conversion from WKT or WKB to `cts.region` using the `geo.parseWkt` function. For example:

```
// Convert WKT polygon into a cts.complexPolygon
geo.parseWkt(
  'POLYGON((0 0, 0 10, 10 10, 10 0, 0 0),(0 5, 0 7, 5 7, 5 5, 0 5))'
)

// Convert WKB bye sequence representing the coordinates
// (-73.700380647, 40.739754168) into a cts.point
geo.parseWkb(
  new NodeBuilder()
    .addBinary('01010000072675909D36C52C0E151BB43B05E4440')
    .toNode()
)
```

- Explicit converstion from `cts.region` to WKT or WKB using the `geo.toWkt` or `geo.toWkb` functions. For example:

```
// cts.point to WKT
geo.toWkt(cts.point(1, 2))

// cts.point to WKB
geo.toWkb(cts.point(1, 2))
```

- Implicit conversion from WKT to `cts.region` where the expected type is a `cts.region`. For example:

```
// create a cts.polygon from WKT via implicit conversion
cts.polygon('POLYGON ((30 10, 40 40, 20 40, 10 20, 30 10))')
```

Note that `geo.parseWkt` and `geo.toWkt` return a `ValueIterator` rather than an array or a single value. The input to `geo.parseWkb` is a binary node that contains a WKB byte sequence.

The supported conversions from WKT to `cts.region` mean all the following calls pass the same `cts.polygon` value to `geo.polygonContains`, which returns true.:

```
// Use a cts.polygon created from a set of cts.point values
geo.polygonContains(
  cts.polygon([
    cts.point(30,10), cts.point(40,40), cts.point(20,40),
    cts.point(10,30), cts.point(30,10)]),
  cts.point(25,25))

// Use a cts.polygon created by explicitly converting from WKT
geo.polygonContains(
  geo.parseWkt('POLYGON ((30 10, 40 40, 20 40, 10 20, 30 10))'),
  cts.point(25,25))

// Use a cts.polygon created by implicitly converting from WKT
geo.polygonContains(
  cts.polygon('POLYGON ((30 10, 40 40, 20 40, 10 20, 30 10))'),
  cts.point(25,25))
```

You cannot convert a `cts.circle` or a `cts.box` to WKT. For more details on WKT, see http://en.wikipedia.org/wiki/Well-known_text.

14.6.4 Mapping of WKT and WKB Types to MarkLogic Types

The following table shows how the WKT and WKB types map to the MarkLogic geospatial types. That is, the equivalent value type resulting from calling the `geo:parse-wkt` XQuery function or `geo.parseWkt` JavaScript function, or the WKB equivalents.

WKT/WKB Geometry	MarkLogic XQuery Type	MarkLogic JavaScript Type
POINT	`cts:point`	`cts.point`
POINT EMPTY (WKT only)	`cts:point` (flagged as empty)	`cts.point` (flagged as empty)
POLYGON	`cts:complex-polygon` | `cts:polygon`	`cts.complexPolygon` | `cts.polygon`
POLYGON EMPTY	`cts:complex-polygon` (flagged as empty)	`cts.complexPolygon` (flagged as empty)
LINESTRING	`cts:linestring`	`cts.linestring`
LINESTRING EMPTY	`cts:linestring` (flagged as empty)	`cts.linestring` (flagged as empty)
TRIANGLE	`cts:polygon`	`cts.polygon`
TRIANGLE EMPTY	`cts:complex-polygon` (flagged as empty)	`cts.complexPolygon` (flagged as empty)
MULTIPOINT	`cts:point`*	zero or more `cts.point` nodes
MULTIPOINT EMPTY	`()`	an empty `ValueIterator`
MULTILINESTRING	`cts:linestring`*	zero or more `cts.linestring`
MULTILINESTRING EMPTY	`()`	null, empty array, or empty `ValueIterator`
MULTIPOLYGON	(`cts:polygon` | `cts:complex-polygon`)*	(`cts.polygon` | `cts.complexPolygon`)*

WKT/WKB Geometry	MarkLogic XQuery Type	MarkLogic JavaScript Type
MULTIPOLYGON EMPTY	`()`	null, empty array, or empty `ValueIterator`
GEOMETRYCOLLECTION	`cts:region*`	zero or more `cts.region` nodes
GEOMETRYCOLLECTION EMPTY	`()`	null, empty array, or empty `ValueIterator`
others	throws XDMP-BADWKT	throws XDMP-BADWKT

14.7 Constructing Geospatial Point and Region Values

Use the following APIs to construct geospatial regions. You can use the resulting region values in geospatial queries and other geospatial operations.

XQuery	JavaScript
`cts:box`	`cts.box`
`cts:circle`	`cts.circle`
`cts:complex-polygon`	`cts.complexPolygon`
`cts:linestring`	`cts.linestring`
`cts:point`	`cts.point`
`cts:polygon`	`cts.polygon`

These constructors accept either the raw data, such as a pair of float values for constructing a point, or a string representing the serialization of the underlying primitive type. The serialized representation can be either the MarkLogic internal representation, such as a serilaized cts:point, or a WKT serialization. If the primitive is not constructible from the string input, an exception is thrown.

For example, the following call constructs a `cts:polygon` from a string that is a serialized cts:point value (space-separated points):

XQuery	JavaScript
`cts:polygon("38,-10 40,-10 39, -15")`	`cts.polygon('38,-10 40,-10 39, -15')`

You can also construct the primitive types from XML or JSON nodes that contain geospatial data in the supported formats. For example, the following XQuery code uses the `geokml:box` function to construct a cts:box from an XML element containing a KML LatLongBox.

```
xquery version "1.0-ml";
import module namespace geokml = "http://marklogic.com/geospatial/kml"
  at "/MarkLogic/geospatial/kml.xqy";

geokml:box(
  <LatLongBox xmlns="http://www.opengis.net/kml/2.2">
    <north>30</north>
    <south>12.5</south>
    <east>-122.24</east>
    <west>-127.24</west>
  </LatLongBox>)
```

Similarly, the following example uses `geojson.box` JavaScript function to construct a cts.box from a JSON node that contains a suitable GeoJSON polygon. For example:

```
var geojson = require('/MarkLogic/geospatial/geojson.xqy');

geojson.box(
  { type: 'Feature',
    bbox: [-180.0, -90.0, 180.0, 90.0],
    geometry: {
      type: 'Polygon',
      coordinates: [[
        [-180.0, 10.0], [20.0, 90.0], [180.0, -5.0], [-30.0, -90.0]
      ]]
  }}
)
```

For details and examples on these functions, see the *MarkLogic XQuery and XSLT Function Reference* or the *MarkLogic Server-Side JavaScript Function Reference*. These functions are complementary to the type constructors with the same names, which are described in "XQuery Primitive Types And Constructors for Geospatial Queries" on page 464.

14.8 Geospatial Query Support in Other APIs

The Search API enables geospatial queries through the following features:

- Define geospatial constraints using query options such as `geo-elem-pair-constraint`, `geo-path-constraint`, and `geo-json-property-constraint`. For details, see `search:search` and "Search Customization Using Query Options" on page 368.
- Create geospatial structured queries using composers such as `geo-elem-query` and `geo-json-property-pair-query`. For details, see "Searching Using Structured Queries" on page 78.

- Add a `heatmap` to a geospatial constraint to generate geospatial facets. For an example, see "Geospatial Constraint Example" on page 380.

For information on specific geospatial query options, see "Appendix: Query Options Reference" on page 668.

The Client APIs for REST, Java and Node.js applications provide similar support:

- The REST and Java Client APIs support the same query options as the Search API for defining geospatial constraints and facets. For details, see the *REST Application Developer's Guide* or the *Java Application Developer's Guide*.
- The Node.js API `queryBuilder` interface includes geospatial query builders such as `queryBuilder.geoProperty`, as well as `queryBuilder.facet` for defining geospatial facets. For details, see *Node.js Application Developer's Guide*.

15.0 Marking Up Documents With Entity Enrichment

This chapter describes how to use entity enrichment in MarkLogic Server to add XML markup for entities such as people and places around text. It contains the following sections:

- Overview of Entity Enrichment
- Entity Enrichment Pipelines

15.1 Overview of Entity Enrichment

With XML, you can add element tags around text. If you add element tags around text that has a particular meaning, then you can then search for those tags to find occurrences of that meaningful thing. Common things to mark up with element tags are people and places, but there are many more things that are useful to mark up. Many industries have domain-specific things that are meaningful to mark up. For example, medical researchers might find it useful to mark up perscription drugs with a tag such as `RX`. The class of things to mark up are sometimes called *entities*, and the process of making XML more useful by finding these entities and then marking it up with meaningful tags (and searchable) is called *entity enrichment*.

MarkLogic Server is capable of integrating with third-party entity enrichment services. The Content Processing Framework makes it easy to call out to third-party tools, and there are some samples included to demonstrate this process, as described in “Sample Pipelines Using Third-Party Technologies” on page 490.

15.2 Entity Enrichment Pipelines

MarkLogic Server includes Content Processing Framework (CPF) applications to perform entity enrichment on your XML. You can use the CPF applications for third-party entity extraction technologies, or you can create custom applications with your own technology or some other third-party technology. This section includes the following parts:

- Sample Pipelines Using Third-Party Technologies
- Custom Entity Enrichment Pipelines

These CPF applications require you to install content processing on your database. For details on CPF, including information about domains and pipelines, see the *Content Processing Framework Guide* guide.

15.2.1 Sample Pipelines Using Third-Party Technologies

There are sample pipelines and CPF applications which connect to third-party entity enrichment tools. The sample pipelines are installed in the `<marklogic-dir>/Installer/samples` directory. There are sample pipelines for the following entity enrichment tools:

- TEMIS Luxid®
- Calais OpenCalais
- SRA NetOwl
- Janya
- Data Harmony

MarkLogic Server connects to these tools via a web service. Sample code is provided on an as-is basis; the sample code is not intended for production applications and is not supported. For details, including setup instructions, see the `README.txt` file and the `samples-license.txt` file in the `<marklogic-dir>/Installer/samples` directory.

15.2.2 Custom Entity Enrichment Pipelines

You can create custom CPF applications to enrich your documents using other third-party enrichment applications. To create a custom CPF application you will need the third party application, a way to connect to it (via a web service, for example), and you will need to write XQuery code and a pipeline file similar to the ones used for the sample applications described in the previous section.

16.0 Creating Alerting Applications

This chapter describes how to create alerting applications in MarkLogic Server as well as describes the components of alerting applications, and includes the following sections:

- Overview of Alerting Applications in MarkLogic Server
- cts:reverse-query Constructor
- XML Serialization of cts:query Constructors
- Security Considerations of Alerting Applications
- Indexes for Reverse Queries
- Alerting API
- Alerting Sample Application

Note: This chapter describes how to create alerting applications using XQuery and XML. You can also create alerting applications using JavaScript and JavaScript objects. It is a best practice to pass XML when the alert action is implemented by an XQuery module and a JavaScript object when the action is implemented by a JavaScript file.

16.1 Overview of Alerting Applications in MarkLogic Server

An *alerting application* is used to notify users when new content is available that matches a predefined (and usually stored) query. MarkLogic Server includes several infrastructure components that you can use to create alerting applications that have very flexible features and perform and scale to very large numbers of stored queries.

A sample alerting application, which uses the Alerting API, is available as an open source project on github (https://github.com/marklogic/alerting). The sample application has all of the low-level components needed in many enterprise-class alerting applications, but it is packaged in a sample application with a user interface designed to demonstrate the functionality of an alert application; your own applications would likely have a very different and more powerful user interface. Also, the sample application is for demonstration purposes only, and is not designed to be put into production; see the `samples-license.txt` file for more information. If you do not care about understanding the low-level components of an alerting application, you can skip to the sections of this chapter about the Alerting API and the sample application, “Alerting API” on page 495 and “Alerting Sample Application” on page 501.

The heart of the components for alerting applications is the ability to create *reverse queries*. A reverse query (`cts:reverse-query`) is a `cts:query` that returns true if the node supplied to the reverse query would match a query if that query were run in a search. For more details about `cts:reverse-query`, see “cts:reverse-query Constructor” on page 492.

Alerting applications use reverse queries and several other components, including serialized `cts:query` constructors, reverse query indexes, MarkLogic Server security components, the Alert API, Content Processing Framework domains and pipelines, and triggers.

> **Note:** Alerting applications require a valid alerting license key. The license key is required to use the reverse index and to use the Alerting API.

16.2 cts:reverse-query Constructor

The `cts:reverse-query` constructor is used in a `cts:query` expression. It returns true for `cts:query` nodes that match an input. For example, consider the following:

```
let $node := <a>hello there</a>
let $query := <xml-element>{cts:word-query("hello")}</xml-element>
return
cts:contains($query, cts:reverse-query($node))
(: returns true :)
```

This query returns `true` because the `cts:query` in `$query` would match `$node`. In concept, the `cts:reverse-query` constructor is the opposite of the other `cts:query` constructors; while the other `cts:query` constructors match documents to queries, the `cts:reverse-query` constructor matches queries to documents. This functionality is the heart of an alerting application, as it allows you to efficiently run searches that return all queries that, if they were run, would match a given node.

The `cts:reverse-query` constructor is fully composable; you can combine the `cts:reverse-query` constructor with other constructors, just like you can any other `cts:query` constructor. The Alerting API abstracts the `cts:reverse-query` constructor from the developer, as it generates any needed reverse queries. For details about how `cts:query` constructors work, see “Composing cts:query Expressions” on page 240.

16.3 XML Serialization of cts:query Constructors

A `cts:query` expression is used in a search to specify what to search for. A `cts:query` expression can be very simple or it can be arbitrarily complex. In order to store `cts:query` expressions, MarkLogic Server has an XML representation of a `cts:query`. Alerting applications store the serialized XML representation or `cts:query` expressions and index them with the reverse index. This provides fast and scalable answers to searches that ask “what queries match this document.” Storing the XML representation of a `cts:query` in a database is one of the components of an alerting application. The Alerting API abstracts the XML serialization from the developer. For more details about serializing a `cts:query` to XML, see the XML Serializations of cts:query Constructors section of the chapter “Composing cts:query Expressions” on page 240.

16.4 Security Considerations of Alerting Applications

Alerting applications typically allow individual users to create their own criteria for being alerted, and therefore there are some inherent security requirements in alerting applications. For example, you don't want everyone to be alerted when a particular user's alerting criteria is met, you only want that particular user alerted. This section describes some of the security considerations and includes the following parts:

- Alert Users, Alert Administrators, and Controlling Access
- Predefined Roles for Alerting Applications

16.4.1 Alert Users, Alert Administrators, and Controlling Access

Because there is both a need to manage an alerting application and a need for users of the alerting application to have some ability to perform actions on the database, alerting applications need to manage security. Users of an alerting application need to run some queries that they might not be privileged to run. For example, they need to look at configuration information in a controlled way. To manage this, alerting applications can use amps to allow users to perform operations for which they do not have privileges by providing the needed privileges *only* in the context of the alerting application. For details about amps and the MarkLogic Server security model, see the *Understanding and Using Security Guide* guide.

The Alerting API, along with the built-in roles `alert-admin` and `alert-user`, abstracts all of the complex security logic so you can create a applications that properly deal with security, but without having to manage the security yourself.

16.4.2 Predefined Roles for Alerting Applications

There are two pre-defined roles designed for use in alerting applications that are built using the Alerting API, as well as some internal roles that the Alerting API uses:

- Alert-Admin Role
- Alert-User Role
- Roles For Internal Use Only

16.4.2.1 Alert-Admin Role

The `alert-admin` role is designed to give administrators of an alerting applications all of the privileges that are needed to create configurations (alert configs) with the Alerting API. It has a significant amount of privileges, including the ability to run code as any user that has a rule, so only trusted users (users who are assumed to be non-hostile, appropriately trained, and follow proper administrative procedures) should be granted the `alert-admin` role. Assign the `alert-admin` role to administrators of your alerting application.

16.4.2.2 Alert-User Role

The `alert-user` role is a minimally privileged role. It is used in the Alerting API to allow regular alert users (as opposed to `alert-admin` users) to be able to execute code in the Alerting API. Some of that code needs to read and update documents used by the alerting application (configuration files, rules, and so on), and this role provides a mechanism for the Alerting API to give the access needed (and no more access) to users of an alerting application.


The `alert-user` role only has privileges that are used by the Alerting API; it does not provide execute privileges to any functions outside the scope of the Alerting API. The Alerting API uses the `alert-user` role as a mechanism to amp more privileged operations in a controlled way. It is therefore reasonably safe to assign this role to any user whom you trust to use your alerting application.

16.4.2.3 Roles For Internal Use Only

There are also two other roles used by the Alerting API which you should not explicitly grant to any user or role: `alert-internal` and `alert-execution`. These roles are used to amp special privileges within the context of certain functions of the Alerting API, and giving these roles to any users would give them privileges on the system that you might not want them to have; do not grant these roles to any users.

16.5 Indexes for Reverse Queries

You enable or disable the reverse query index in the database configuration by setting the `fast reverse searches` index setting to `true`:



The `fast reverse searches` index speeds up searches that use `cts:reverse-query`. For alerting applications to scale to large numbers of rules, you should enable fast reverse searches.

> **Note:** Alerting applications require a valid alerting license key. The license key is required to use the reverse index and to use the Alerting API.

16.6 Alerting API

The Alerting API is designed to help you build a robust alerting application. The API handles the details for security in the application, as well as provides mechanisms to set up all of the components of an alerting application. It is designed to make it easy to use triggers and CPF to keep the state of documents being alerted. This section describes the Alerting API and includes the following parts:

- Alerting API Concepts
- Using the Alerting API
- Using CPF With an Alerting Application

The Alerting API is implemented as an XQuery library module. For the individual function signatures and descriptions, see the *MarkLogic XQuery and XSLT Function Reference*.

16.6.1 Alerting API Concepts

There are three main concepts to understand when using the Alerting API:

- Alert Config
- Actions to Execute When an Alert Fires
- Rules For Firing Alerts

16.6.1.1 Alert Config

The alert *config* is the XML representation of an alerting configuration for an alerting application. Typically, an alerting application needs only one alert config, although you can have many if you need them. The Alerting API defines an XML representation of an alert config, and that XML representation is returned from the `alert:make-config` function. You then persist the config in the database using the `alert:config-insert` function. The Alerting API also has setter and getter functions to manipulate an alert config. The alert config is designed to be created and updated by an administrator of the alerting application, and therefore users who manipulate the alert config must have the `alert-admin` role.

16.6.1.2 Actions to Execute When an Alert Fires

An *action* is some XQuery or JavaScript code to execute when an alert occurs. An action could be to update a document in the database, to send an email, or whatever makes sense for your application. The action is an XQuery main module, and the Alerting API defines an XML representation of an action, and that XML representation is returned from the `alert:make-action` function. The action XML representation points to the XQuery main module that performs the action. You then persist this XML representation of an alert action in the database using the

`alert:action-insert` function. The Alerting API also has setter and getter functions to manipulate an alert action. Alert actions are designed to be created and updated by an administrator of the alerting application, and therefore users who manipulate alert actions must have the `alert-admin` role.

Alert actions are invoked or spawned with `alert:invoke-matching-actions` or `alert:spawn-matching-actions`, and the actions can accept the following external variables:

```
declare namespace alert = "http://marklogic.com/xdmp/alert";

declare variable $alert:config-uri as xs:string external;
declare variable $alert:doc as node() external;
declare variable $alert:rule as element(alert:rule) external;
declare variable $alert:action as element(alert:action) external;
```

These external variables are available to the action if it needs to use them. To use the variables, the above variable declarations must be in the prolog of the action module that is invoked or spawned.

16.6.1.3 Rules For Firing Alerts

A *rule* is the criteria for which a user is alerted combined with a reference to an action to perform if that criteria is met. For example, if you are interested in any new or changed content that matches a search for `jelly beans`, you can define a rule that fires an alert when a new or changed document comes in that has the term `jelly beans` in it. This might translate into the following `cts:query`:

```
cts:word-query("jelly beans")
```

The rule also has an action associated with it, which will be performed if the document matches the query. Alerting applications are designed to support very large numbers of rules with fast, scalable performance. The amount of work for each rule also depends on what the action is for each rule. For example, if you have an application that has an action to send an email for each matching rule, you must consider the impact of sending all of those emails if you have large numbers of matching rules.

The Alerting API defines an XML representation of a rule, and that XML representation is returned from the `alert:make-rule` function. You then persist the rule in the database using the `alert:rule-insert` function. Rules are designed to be created and updated by regular users of the alerting application. The Alerting API also has setter and getter functions to manipulate an alert rule. Because those regular users who create rules must have the needed privileges and permissions to perform certain tasks (such as reading and updating certain documents), a minimal set of privileges are required to insert a rule. Therefore users who create rules in an alerting application must have the `alert-user` role, which has a minimum set of privileges.

16.6.2 Using the Alerting API

Once you understand the concepts described in the previous section, using the Alerting API is straight-forward. This section describes the following details of using the Alerting API:

- Set Up the Configuration (User With alert-admin Role)
- Set Up Actions (User With alert-admin Role)
- Create Rules (Users With alert-user Role)
- Run the Rules Against Content

16.6.2.1 Set Up the Configuration (User With alert-admin Role)

The first step in using the Alerting API is to create an alert config. For details about an alert config, see "Alert Config" on page 495. You should create the alert config as an alerting application administrator (a user with the `alert-admin` role or the `admin` role). The following sample code demonstrates how to create an alert config:

```
(: run this a user with the alert-admin role :)
xquery version "1.0-ml";
import module namespace alert = "http://marklogic.com/xdmp/alert"
  at "/MarkLogic/alert.xqy";

let $config := alert:make-config(
      "my-alert-config-uri",
      "My Alerting App",
      "Alerting config for my app",
        <alert:options/> )
return
alert:config-insert($config)
```

16.6.2.2 Set Up Actions (User With alert-admin Role)

An alerting application administrator must also set up actions to be performed when an alert occurs. An action is an XQuery main module and can be arbitrarily simple or arbitrarily complex. For details about alert actions, see "Actions to Execute When an Alert Fires" on page 495.

In practice, setting up the actions will require a good understanding of what you are trying to accomplish in an alerting application. The following is an extremely simple action that sends a log message to the `ErrorLog.txt` file. To create this action, create an XQuery document under your App Server root with the following content:

```
xdmp:log(fn:concat(xdmp:get-current-user(), " was alerted"))
```

For example, if the App Server in which your alerting application is running has a root of `/space/alert`, put this XQuery document in `/space/alert/log.xqy`.

For another example of an alert action, see the `<marklogic-dir>/Modules/alert/log.xqy` XQuery file. Alert actions can perform any action you can write in XQuery.

You also need to set up the action with the Alerting API, as in the following example (run this as a user with the `alert-admin` role):

```
xquery version "1.0-ml";
import module namespace alert = "http://marklogic.com/xdmp/alert"
  at "/MarkLogic/alert.xqy";

let $action := alert:make-action(
    "xdmp:log",
    "log to ErrorLog.txt",
    xdmp:modules-database(),
    xdmp:modules-root(),
    "/alert-action.xqy",
    <alert:options>put anything here</alert:options> )
return
alert:action-insert("my-alert-config-uri", $action)
```

16.6.2.3 Create Rules (Users With alert-user Role)

You should set up the alerting application so that regular users of the application can create rules. You might have a form, for example, to assist users in creating the rules. The following is the basic code needed to set up a rule. Note that your code will probably be considerably more complex, as this code has no user interface. This code simply creates a rule with the action described above and associates a `cts:query` with the rule. Run this code as a user with the `alert-user` role.

```
xquery version "1.0-ml";
import module namespace alert = "http://marklogic.com/xdmp/alert"
  at "/MarkLogic/alert.xqy";

let $rule := alert:make-rule(
    "simple",
    "hello world rule",
    0, (: equivalent to xdmp:user(xdmp:get-current-user()) :)
    cts:word-query("hello world"),
    "xdmp:log",
    <alert:options/> )
return
alert:rule-insert("my-alert-config-uri", $rule)
```

Note: If your action performs any privileged activities, including reading or creating documents in the database, you will need to add the appropriate execute privileges and URI privileges to users running the application.

16.6.2.4 Run the Rules Against Content

To make the application fire alerts (that is, execute the actions for rules), you must run the rules against some content. You can do this in several ways, including setting up triggers with the Alerting API (`alert:create-triggers`), using CPF and the Alerting pipeline, or creating your own mechanism to run the rules against content.

To run the rules manually, you can use the `alert:spawn-matching-actions` or `alert:invoke-matching-actions` APIs. These are useful to run alerts in any context, either within an application or as an easy way to test your rules. The `alert:spawn-matching-actions` is good when you have many alerts that might fire at once, because it will spawn the actions to the task server to execute asynchronously. The `alert:invoke-matching-actions` API runs the action immediately, so be careful using this if there can be large numbers of matching actions, as they will all be run in the same context. You can run these APIs as any user, and whether or not they produce an action will depend upon what each rule's owner has permissions to see. The following is a very simple example that fires the previously created alert:

```
xquery version "1.0-ml";
import module namespace alert = "http://marklogic.com/xdmp/alert"
  at "/MarkLogic/alert.xqy";

alert:invoke-matching-actions("my-alert-config-uri",
      <doc>hello world</doc>, <options/>)
```

If you created the config, action, and rule as described in the previous sections, this logs the following to your `ErrorLog.txt` file when running the code as a user named `some-user` who has the `alert-user` role (assuming this user created the rule):

```
some-user was alerted
```

Note: If you have very large numbers of alerts, and if the actions for your rules are resource-intensive, invoking or spawning matching actions can produce a significant amount of query activity for your system. This is OK, as that is the purpose of an alerting application, but you should plan your resources accordingly.

16.6.3 Using CPF With an Alerting Application

It is a natural fit to use alerting applications built using the Alerting API with the Content Processing Framework (CPF). CPF is designed to keep state for documents, so it is easy to use CPF to keep track of when a document in a particular scope is created or updated, and then perform some action on that document. For alerting applications, that action involves running a reverse query on the changed documents and then firing alerts for any matching rules (the Alerting API abstracts the reverse query from the developer).

To simplify using CPF with alerting applications, there are pre-built pipelines for alerting. The pipelines are designed to be used with an alerting application built with the Alerting API. This Alerting CPF application will run alerts on all new and changed content within the scope of the CPF domain to which the Alerting pipeline is attached. The Alerting pipleine is suitable for most alerting applications. The Alerting (spawn) pipeline spawns the actions in separate tasks, and therefore will result in increased parallelism which is beneficial if you have many actions that result from a single document change. For example, if you have an application that allows users to specify a query to alert on, and if many people specify the same query (for example, the name of a popular singer), then with the Alerting pipeline, each of those actions is run serially, and the actions will recover even if there is a failure in the middle of them; with the Alerting (spawn) pipeline, each action is spawned as a separate request, allowing more parallelism, but if there is a failure during the actions, the actions will not restart. Furthermore, if your alerting action updates the document being alerted on, then you must use the Alerting (spawn) pipeline, as the Alerting pipeline would result in a deadlock.

If you use the Alerting pipelines with any of the other pipelines included with MarkLogic Server (for example, the conversion pipelines and/or the modular documents pipelines), the Alerting pipeline is defined to have a priority such that it runs after all of the other pipelines have completed their processing. This way, alerts happen on the final view of content that runs through a pipeline process. If you have any custom pipelines that you use with the Alerting pipeline, consider adding priorities to those pipelines so the alerting occurs in the order in which you are expecting.

To set up a CPF application that uses alerting, perform the following steps:

1. Enable the reverse index for your database, as described in “Indexes for Reverse Queries” on page 494.

2. Set up the alert config and alert actions as a user with the `alert-admin` role, as described in “Set Up the Configuration (User With alert-admin Role)” on page 497 and “Set Up Actions (User With alert-admin Role)” on page 497.

3. Set up an application to have users (with the `alert-user` role) define rules, as described in “Create Rules (Users With alert-user Role)” on page 498.

4. Install Content Processing in your database, if it is not already installed (Databases > *database_name* > Content Processing > Install tab).

5. Set up the `domain scope` for a domain.

6. Attach the Alerting pipeline and the Status Change Handling pipeline to the domain. You can also attach any other pipelines you need to the domain (for example, the various conversion pipelines).

7. Use either the `alert:config-set-cpf-domain-names` or `alert:config-set-cpf-domain-ids` function to notify the alerting configuration of the domain, so that the alerting action can determine what alerting configuration it is to use.

   For example, if your CPF domain's name is Default Documents, you could do the following.

```
alert:config-insert(
   alert:config-set-cpf-domain-names(
      alert:config-get($config-uri),
      ("Default Documents")))
```

   Note: An alerting configuration can be used with multiple CPF domains, in which case you set a sequence of multiple domain names or IDs.

Any new or updated content within the domain scope will cause all matching rules to fire their corresponding action. If you will have many alerts that are spawned to the task server, make sure the task server is configured appropriately for your machine. For example, if you are running on a machine that has 16 cores, you might want to raise the `threads` setting for the task server to a higher number then the default of 4. What you set the `threads` setting depends on what other work is going on your machine.

For details about CPF, see the *Content Processing Framework Guide* guide.

16.7 Alerting Sample Application

A sample alerting application is available on developer.marklogic.com/code. The sample application uses the Alerting API, and has all of the low-level components needed in many enterprise-class alerting applications, but it is packaged in a sample application with a user interface designed to demonstrate the functionality of an alert application; your own applications would likely have a very different and more powerful user interface. This sample code is provided on an as-is basis; the sample code is not intended for production applications and is not supported. For details, including setup instructions, see the code on developer.marklogic.com/code.

17.0 Using fn:count vs. xdmp:estimate

This chapter descibes some of the differences between the `fn:count` and `xdmp:estimate` functions, and includes the following sections:

- fn:count is Accurate, xdmp:estimate is Fast
- The xdmp:estimate Built-In Function
- Using cts:remainder to Estimate the Size of a Search
- When to Use xdmp:estimate

17.1 fn:count is Accurate, xdmp:estimate is Fast

The XQuery language provides general support for counting the number of items in a sequence through the use of the `fn:count` function. However, the general-purpose nature of `fn:count` makes it difficult to optimize. Sequences to be counted can include arbitrarily complex combinations of sequences stored in the database, constructed dynamically, filtered after retrieval or construction, etc. In most cases, MarkLogic Server must process the sequence in order to count it. This can have significant I/O requirements that would impact performance.

MarkLogic Server provides the `xdmp:estimate` XQuery built-in as an efficient way to approximate `fn:count`. Unlike `fn:count`, which frequently must process its answer by inspecting the data directly (hence the heavy I/O loads), `xdmp:estimate` computes its answer directly from indexes. In certain situations, the index-derived value will be identical to the value returned by `fn:count`. In others, the values differ to a varying degree depending on the specified sequence and the data. In instances where `xdmp:estimate` is not able to return a fast estimate, it will throw an error. Hence, you can depend on `xdmp:estimate` to be fast, just as you can depend on `fn:count` to be accurate.

Effectively, `xdmp:estimate` puts the decision to optimize counting through use of the indexes in the hands of the developer.

17.2 The xdmp:estimate Built-In Function

`xdmp:estimate` accepts searchable XPath expressions as its parameter and returns an approximation of the number of items in the sequence:

```
xdmp:estimate(/book)
xdmp:estimate(//titlepage[cts:contains(., "primer")])
xdmp:estimate(cts:search(//titlepage, cts:word-query("primer")))
xdmp:estimate(/object[.//id = "57483"])
```

`xdmp:estimate` does not always return the same value as `fn:count`. The `fn:count` function returns the exact number of items in the sequence that is provided as a parameter. In contrast, `xdmp:estimate` provides an answer based on the following rules:

1. If the parameter passed to `xdmp:estimate` is a searchable XPath expression, `xdmp:estimate` returns the number of fragments that it will select from the database for post-filtering. This number is computed directly from the indexes at extremely high performance. It may, however, differ from the actual `fn:count` of the sequence specified if either (a) there are multiple matching items within a single fragment or (b) there are fragments provisionally selected by the indexes that do not actually contain a matching item.

2. If the parameter passed to `xdmp:estimate` is not a searchable XPath expression (that is, it is not an XPath rooted at a `doc`, `collection()`, or `input()` function, or a / or // step), `xdmp:estimate` will throw an error.

`xdmp:estimate` is defined in this way to ensure a sharp contrast against the `fn:count` function. `xdmp:estimate` will always execute quickly. `fn:count` will always return the "correct" answer. Over time, as MarkLogic improves the server's underlying optimization capability, there will be an increasing number of scenarios in which `fn:count` is both correct and fast. But for the moment, we put the decision about which approach to take in the developer's hands.

17.3 Using cts:remainder to Estimate the Size of a Search

When you need to retrieve both search results and an estimate of the number of matching fragments as part of the same query statement, use the `cts:remainder` function. Running `cts:remainder` on a node or nodes returned by a search is more efficient that running `xdmp:estimate` on the sequence of nodes returned by `cts:search`. If you just need the estimate, but not the search results, then `xdmp:estimate` is more efficient.

`cts:remainder` returns the number of nodes remaining from a particular node of a search result set. When you run it on the first node, it returns the same result as `xdmp:estimate` on the search. `cts:remainder` also has the flexibility to return the estimated results of a search starting with any item in the search (for example, how many results remain after the 500th search item), and it does this in an efficient way.

Like `xdmp:estimate`, `cts:remainder` uses the indexes to find the *approximate* results based on unfiltered results. For an explanation of unfiltered results, see "Using Unfiltered Searches for Fast Pagination" in the *Query Performance and Tuning Guide*. For the syntax and examples of `cts:remainder`, see the *MarkLogic XQuery and XSLT Function Reference*.

17.4 When to Use xdmp:estimate

MarkLogic Server uses its indexes to *approximate* the identification of XML fragments that may contain constructs that match~~es~~ the specified XPath. This set of fragments is then filtered to determine the exact nodes to return for further processing.

For searchable XPath expressions, `xdmp:estimate` returns the number of fragments selected in the first approximation step described above. Because this operation is carried out directly from indexes, the operation is virtually instantaneous. However, there are two scenarios in which this approximation will not match the results that would be returned by `fn:count`:

1. If a fragment contains more than one matching item for the XPath specified, `xdmp:estimate` will *undercount* these items as a single item whereas `fn:count` would count them individually.
2. In addition, it is possible to *overcount*. Index optimization sometimes must over-select in order to ensure that no matching item is missed. During general query processing, these over-selected fragments are discarded in the second-stage filtering process. But `xdmp:estimate` will count these fragments as matching items whereas `fn:count` would exclude them.

Consider the sample query outlined below. The first step in the optimization algorithm outlined above is illustrated by the `xdmp:query-trace` output shown after the query:

Query:

```
/MedlineCitationSet/MedlineCitation//Author[LastName="Smith"])
```

Query trace output:

```
2004-04-06 17:49:39 Info: eval line 5: Analyzing path:
fn:doc()/child::MedlineCitationSet/child::MedlineCitation/
descendant::Author[child::LastName = "Smith"]
2004-04-06 17:49:39 Info: eval line 5: Step 1 is searchable: fn:doc()
2004-04-06 17:49:39 Info: eval line 4: Step 2 axis does not use
indexes:child
2004-04-06 17:49:39 Info: eval line 4: Step 2 test is searchable:
MedlineCitationSet
2004-04-06 17:49:39 Info: eval line 5: Step 2 is searchable:
child::MedlineCitationSet
2004-04-06 17:49:39 Info: eval line 4: Step 3 axis does not use
indexes:child
2004-04-06 17:49:39 Info: eval line 4: Step 3 test is searchable:
MedlineCitation
2004-04-06 17:49:39 Info: eval line 5: Step 3 is searchable:
child::MedlineCitation
2004-04-06 17:49:39 Info: eval line 5: Step 4 axis does not use
indexes:descendant
2004-04-06 17:49:39 Info: eval line 5: Step 4 test is searchable:
Author
2004-04-06 17:49:39 Info: eval line 5: Step 4 predicate 1 is
searchable:
child::LastName = "Smith"
2004-04-06 17:49:39 Info: eval line 5: Step 4 is searchable:
descendant::Author[child::LastName = "Smith"]
2004-04-06 17:49:39 Info: eval line 5: Path is searchable.
2004-04-06 17:49:39 Info: eval line 5: Gathering constraints.
```

```
2004-04-06 17:49:39 Info: eval line 4: Step 2 test contributed 1
constraint: MedlineCitationSet
2004-04-06 17:49:39 Info: eval line 4: Step 3 test contributed 2
constraints: MedlineCitation
2004-04-06 17:49:39 Info: eval line 5: Step 4 test contributed 1
constraint: Author
2004-04-06 17:49:39 Info: eval line 4: Comparison contributed hash
value constraint: LastName = "Smith"
2004-04-06 17:49:39 Info: eval line 5: Step 4 predicate 1 contributed 1
constraint: child::LastName = "Smith"
2004-04-06 17:49:39 Info: eval line 5: Executing search.
2004-04-06 17:49:39 Info: eval line 5: Selected 263 fragments to filter
```

In this scenario, applying `fn:count` to the XPath provided would tell us that there are 271 authors with a last name of "Smith" in the database. Using `xdmp:estimate` yields an answer of 263. In this example, `xdmp:estimate` undercounted because there are fragments with multiple authors named "Smith" in the database, and xdmp:estimate only counts the number of fragments.

Understanding when these situations will occur with a given database and dataset requires an in-depth understanding of the optimizer. Given that the optimizer evolves with every release of the server, this is a daunting task.

The following three sets of guidelines will help you know when and how to use `xdmp:estimate`:

- When Estimates Are Good Enough
- When XPaths Meet The Right Criteria
- When Empirical Tests Demonstrate Correctness

17.4.1 When Estimates Are Good Enough

In some situations, an estimate of the correct answer is good enough. Many search engines use this approach today, only estimating the total number of "hits" when displaying the first twenty results to the user. In scenarios in which the exact count is not important, it makes sense to use `xdmp:estimate`.

17.4.2 When XPaths Meet The Right Criteria

If you need to get the precise answer rather than just an approximation, there are some simple criteria to keep in mind if you want to use `xdmp:estimate` for its performance benefits:

1. Counting nodes that are either fragment or document roots will always return the correct result.

   Examples:

   ```
   xdmp:estimate(/node-name) is equivalent to count(/node-name)
   ```

```
xdmp:estimate(//MedlineCitation) is equivalent to count(//MedlineCitation)
```

if `MedlineCitation` is a fragment-root. For example, this constraint is how the sample Medline application is configured in the sample code on `http://support.marklogic.com`.

2. If a single fragment can contain more than one element that matches a predicate, you have the potential for undercounting. Assume that the sample data below resides in a single fragment:

```
<authors>
  <author>
    <last-name>Smith</last-name>
    <first-name>Alison</first-name>
  </author>
  <author>
    <last-name>Smith</last-name>
    <first-name>James</first-name>
  </author>
  <author>
    <last-name>Peterson</last-name>
    <first-name>David</first-name>
  </author>
</authors>
```

In this case, an XPath which specifies `fn:doc()//author[last-name = "Smith"]` will *undercount*, counting only one item for the two matches in the above sample data.

3. If the XPath contains multiple predicates, you have the potential of overcounting. Using the sample data above, an XPath which specifies `fn:doc()//author[last-name = "Smith"][first-name = "David"]` will not have any matches. However, since the above fragment contains author elements that satisfy the predicates `[last-name = "Smith"]` and `[first-name = "David"]` individually, it will be selected for post-filtering. In this case, `xdmp:estimate` will consider the above fragment a match and overcount.

17.4.3 When Empirical Tests Demonstrate Correctness

As a last step, you can use two techniques to understand the value that will be returned by `xdmp:estimate`:

1. At development time, use `xdmp:estimate` and `fn:count` to count the same sequence and see if the results are different for datasets which exhibit all the structural variation you expect in your production dataset.

2. Turn on `xdmp:query-trace`, evaluate the XPath sequence that you wish to use with `xdmp:estimate`, and inspect the query-trace output in the log file. This output will tell you how much of the XPath was searchable, how many fragments were selected (this is the answer that `xdmp:estimate` will provide), and how many ultimately matched (this is the answer that `fn:count` will provide).

18.0 Understanding and Using Stemmed Searches

This chapter describes how to use the stemmed search functionality in MarkLogic Server. The following sections are included:

- Stemming in MarkLogic Server
- Enabling Stemming
- Stemmed Searches Versus Word Searches
- Using cts:highlight or cts:contains to Find if a Word Matches a Query
- Interaction With Wildcard Searches

18.1 Stemming in MarkLogic Server

MarkLogic Server supports stemming in English and other languages. For a list of languages in which stemming is supported, see "Supported Languages" on page 603.

If stemmed searches are enabled in the database configuration, MarkLogic Server automatically searches for words that come from the same *stem* of the word specified in the query, not just the exact string specified in the query. A stemmed search for a word finds the exact same terms as well as terms that derive from the same meaning and part of speech as the search term. The stem of a word is not based on spelling. For example, `card` and `cardiac` have different stems even though the spelling of `cardiac` begins with `card`. On the other hand, `running` and `ran` have the same stem (`run`) even though their spellings are quite different. If you want to search for a word based on partial pattern matching (like the `card` and `cardiac` example above), use wildcard searches as described in "Understanding and Using Wildcard Searches" on page 526.

Stemming enables the search to return highly relevant matches that would otherwise be missed. For example, the terms `run`, `running`, and `ran` all have the same stem. Therefore, a stemmed search for the term `run` returns results that match elements containing the terms `running`, `ran`, and `runs`, as well as results for the specified term `run`.

The stemming supported in MarkLogic Server does not cross different parts of speech. For example, `conserve` (verb) and `conservation` (noun) are not considered to have the same stem because they have different parts of speech. Consequently, if you search for `conserve` with stemmed searches enabled, the results will include documents containing `conserve` and `conserves`, but not documents with `conservation` (unless `conserve` or `conserves` also appears).

Stemming is language-specific, that is, each word is treated to be in the specified language. The language can be specified with an `xml:lang` attribute or by several other methods, and a term in one language will not match a stemmed search for the same term in another language. For details on how languages affect queries, see "Querying Documents By Languages" on page 600.

Contains SAP BusinessObjects Text Analysis XI from SAP AG. Copyright © 1996-2011. All rights reserved.

18.2 Enabling Stemming

To use stemming in your searches, stemming must be enabled in your database configuration. All new databases created in MarkLogic Server have stemming enabled by default. Stemmed searches require indexes which are created at load, update, or reindex time. If you enable stemming in an existing database that did not previously have stemming enabled, you must either reload or reindex the database to ensure that you get stemmed results from searches. You should plan on allocating an additional amount of disk space about twice the size of the source content if you enable stemming.

There are three types of stemming available in MarkLogic Server: basic, advanced, and decompounding. The following table describes the stemming options available on the database configuration page of the Admin Interface.

Stemming Option	Description
OFF	No words are indexed for stemming.
Basic	This is the default. Each word is indexed to a single stem.
Advanced	Each word is indexed to one or more stems. Some words can have two or more meanings, and can therefore have multiple stems. For example, the word `further` stems to `further` (as in *he attended the party to further his career*) and it stems to `far` (as in *she was further along in her studies than he*).
Decompounding	All stems for each word are indexed, and smaller component words of large compound words are also indexed. Mostly used in languages such as German that use compound words.

If stemming is enabled for the database, you can further control the use of stemming at the query level. Stemming can be used with any of the MarkLogic `cts:query` constructor functions, such as `cts:word-query`, `cts:element-word-query`, and `cts:element-value-query`. Stemming options, `"stemmed"` or `"unstemmed"`, can be specified in the options parameter to the `cts:query` constructor. For more details on these functions, see the *MarkLogic XQuery and XSLT Function Reference* (http://docs.marklogic.com).

Query terms that contain a wildcard will not be stemmed. If you leave the stemming option unspecified, the system will perform a stemmed search for any word that does not contain a wildcard. Therefore, as long as stemming is enabled in the database, you do not have to enable stemming explicitly in a query.

If stemming is turned off in the database, and stemming is explicitly specified in the query, the query will throw an error.

18.3 Stemmed Searches Versus Word Searches

The stemmed search indexes and word search (unstemmed) indexes have overlapping functionality, and there is a good chance you can get the results you want with only the stemmed search indexes enabled (that is, leaving the word search indexes turned off).

Stemmed searches return relevance-ranked results for the words you search for *as well as for* words with the same stem as the words you search for. Therefore, you will get the same results as with a word search plus the results for items containing words with the same stem. In most search applications, this is the desirable behavior.

The only time you need to also have word search indexes enabled is when your application requires an exact word search to *only* return the exact match results (that is, to *not* return results based on stemming).

Additionally, the stemmed search indexes take up less disk space than the word search (unstemmed) indexes. You can therefore save some disk space and decrease load time when you use the default settings of stemmed search enabled and word search turned off in the database configuration. Every index has a cost in terms of disk space used and increased load times. You have to decide based on your application requirements if the cost of creating extra indexes is worthwhile for your application, and whether you can fulfill the same requirements without some of the indexes.

If you do need to perform word (unstemmed) searches when you only have stemmed search indexes enabled (that is, when word searches are turned off in the database configuration), you must do so by first doing a stemmed search and then filtering the results with an unstemmed `cts:query`, as described in “Unstemmed Searches” on page 601.

18.4 Using cts:highlight or cts:contains to Find if a Word Matches a Query

Because stemming enables query matches for terms that do not have the same spelling, it can sometimes be difficult to find the words that actually caused the query to match. You can use `cts:highlight` to test and/or highlight the words that actually matched the query. For details on `cts:highlight`, see the *MarkLogic XQuery and XSLT Function Reference* and "Highlighting Search Term Matches" on page 454.

You can also use `cts:contains` to test if a word matches the query. The `cts:contains` function returns `true` if there is a match, `false` if there is no match. For example, you can use the following function to test if a word has the same stem as another word.

```
xquery version "1.0-ml";
declare function local:same-stem(
  $word1 as xs:string, $word2 as xs:string)
  as xs:boolean
{
  cts:contains(text{$word1},$word2)
};

(: The following returns true because
   running has the same stem as run :)
local:same-stem("run", "running")
```

18.5 Interaction With Wildcard Searches

For information about how stemmed searches and Wildcard searches interact, see "Interaction with Other Search Features" on page 530.

19.0 Custom Dictionaries for Tokenizing and Stemming

Custom dictionaries are used to customize the way words are stemmed and tokenized for each language. This chapter describes custom dictionaries and contains the following sections:

- Custom Dictionaries in MarkLogic Server
- Dictionary and Entry Schemas
- Custom Dictionary Functions
- Usage Examples

19.1 Custom Dictionaries in MarkLogic Server

If you want to change the default stemming or tokenizing behavior for any MarkLogic supported and licensed language, you can create or modify a custom dictionary. The custom dictionary entries override the built-in stemming data or add new stemming data for MarkLogic to use. For example, assume “meeting” is mapped to stem “meet” in the built-in dictionary. But, due to calendar entries, you don't want “meeting” to match “meet”. You can prevent this by adding a custom dictionary entry for the word “meeting” with “meeting” as a stem.

Custom dictionaries have three uses:

- Japanese (`ja`), Simplified Chinese (`zh`), and Traditional Chinese (`zh_hant`) all use a linguistic tokenizer to divide text into tokens (words and punctuation) since these languages do not have spaces separating words. You can change the tokenizer’s behavior by adding entries to a language’s custom dictionary.
- For all languages which tokenize based on spaces and punctuation, as well as Japanese, their dictionaries map inflections of words to their dictionary form. For example, English’s dictionary maps “views”, ‘viewed”, and “viewing” all back to their common stem, “view”. You can change, delete, or add dictionary entries to modify what words are mapped to which stems. For more information on stemming and tokenizing, see “Understanding and Using Stemmed Searches” on page 507.
- Handling spelling variation and technical vocabulary, for words like “aluminum” and “aluminium”. Due to a dictionary entry, these two spellings are effectively the same for anything in the server based on stemming.

There is only one custom dictionary for each MarkLogic licensed and supported language. To get the custom dictionary for a language, first get a list of all of the licensed languages for your system. By iterating over this list, you can get any of your custom dictionaries. Custom dictionaries are stored in the data directory, so they survive MarkLogic server upgrades.

The custom dictionaries format and API make use of namespaces and are validated during dictionary writes to avoid runtime errors. However, MarkLogic does not check for duplicate entries which, while unnecessary, do not cause errors. Nor does it check for non-Latin characters in an English custom dictionary, although entries with such characters are invalid and not processed. Fixing errors in a custom dictionary does not require a restart.

Caution: Reindexing is required if documents are affected by custom dictionary changes. To determine what, if any, documents are affected before changing the dictionary, do a word search (not a stemmed search) for any words that your changes will add or delete. For example, if you are adding “viewer” to stem to “view” and deleting the “viewing” to “view” stem, you would want to search for both “viewer” and “viewing”, as these are the words which are affected by changing the dictionary. “view” itself is not affected. Documents containing those words will need reindexing after the dictionary change.

19.2 Dictionary and Entry Schemas

Custom dictionaries are stored as XML documents and use a dedicated namespace and a common entry format. Here is an example custom dictionary with a single entry:

```
<dictionary xmlns="http://marklogic.com/xdmp/custom-dictionary"
            xml:lang="en">
  <entry>
    <word>servlets</word>
    <stem>servlet</stem>
    <pos>Nn</pos>
  </entry>
</dictionary>
```

Note that the root `<dictionary>` element has an `xml:lang` attribute specifying the dictionary’s associated language, in this case English.

A dictionary can have any number of `<entry>` elements, which each contain three sub-elements:

- `<word>`: A string, it contains a word to be stemmed.
- `<stem>`: A string, the stem for the `<word>` string.

- `<pos>`: For languages without space-separated words, such as Chinese and Japanese, it specifies a *part of speech*. For other languages, it is ignored. If omitted, `Nn-Prop` (proper noun) is the default value. The common values are:

Value	Part of Speech
Adj	Adjective
Adv	Adverb
Interj	Interjection
Nn	Noun
NN-Prop	Proper Noun (default)
Verb	Verb

19.3 Custom Dictionary Functions

To use the `custom-dictionary.xqy` module in your own XQuery modules, include the following line in your XQuery prolog:

```
import module namespace cdict =
   "http://marklogic.com/xdmp/custom-dictionary" at
   "/MarkLogic/custom-dictionary.xqy";
```

This imports the module and binds the module namespace to the custom dictionary module prefix `cdict`.

There are four custom dictionary related functions, as shown below. Note that you cannot edit a custom dictionary in place. Instead, you have to first get the dictionary. Then add to, edit, or delete its entries. Finally, overwrite the old version by writing the new version out.

- Get All Licensed Languages (`cdict:get-languages`)
- Get A Custom Dictionary (`cdict:dictionary-read`)
- Add/Write A Custom Dictionary (`cdict:dictionary-write`)
- Delete A Custom Dictionary (`cdict:dictionary-delete`)

For more details on these functions, see *MarkLogic XQuery and XSLT Function Reference*.

19.3.1 Get All Licensed Languages

```
cdict:get-languages()
  as xs:string*
```

Requires the `http://marklogic.com/xdmp/privileges/custom-dictionary-user` privilege. Returns the 2-letter ISO language codes for all your server's licensed languages. A list of codes and their associated languages is at http://www.loc.gov/standards/iso639-2/php/code_list.php Note that MarkLogic only uses the 2-letter ISO 639-1 codes, including `zh`'s `zh_Hant` variant.

19.3.2 Get A Custom Dictionary

```
cdict:dictionary-read(
  $lang as xs:string
) as element(cdict:dictionary)
```

Requires the `http://marklogic.com/xdmp/privileges/custom-dictionary-user` privilege. `$lang` is an ISO language code. If `$lang` matches a licensed language with a custom dictionary, the local host returns that custom dictionary (which is the same across the cluster). The dictionary's `xml:lang` attribute is also returned, indicating its associated language. If `$lang` is not a licensed language, it raises an `XDMP-LANG` error.

19.3.3 Add/Write A Custom Dictionary

```
cdict:dictionary-write(
  $lang as xs:string,
  $dict as element(cdict:dictionary)
) as empty-sequence()
```

Requires the `http://marklogic.com/xdmp/privileges/custom-dictionary-admin` privilege. `$lang` is an ISO language code. `$dict` is the custom dictionary If `$lang` matches a licensed language and `$dict` validates, the cluster installs `$dict` and returns host IDs from where the dictionary is saved. If `$lang` is not a licensed language, it raises an `XDMP-LANG` error. If validation fails, it raises validation errors. `dictionary-write` ignores the `xml:lang` attribute.

19.3.4 Delete A Custom Dictionary

```
cdict:dictionary-delete(
  $lang as xs:string
) as empty-sequence()
```

Requires the `http://marklogic.com/xdmp/privileges/custom-dictionary-admin` privilege. `$lang` is an ISO language code. If `$lang` matches a licensed language with a custom dictionary, the dictionary is deleted and it returns the host IDs from which the dictionary was deleted. Raises an `XDMP-LANG` error if `$lang` is not a licensed language..

19.4 Usage Examples

The following code shows how to find a custom dictionary, get it, add and edit entries, write out the modified dictionary, and finally how to delete it. After each code sample is an example response.

First, get the sequence of supported and licensed languages:

```
xquery version "1.0-ml";
import module namespace cdict =
"http://marklogic.com/xdmp/custom-dictionary"
                 at "/MarkLogic/custom-dictionary.xqy";

cdict:get-languages()

==> ("en", "ja", "zh", "zh_Hant")
```

Next, get the dictionary contents for a particular language, in this case English (`en`):

```
xquery version "1.0-ml";
import module namespace cdict =
"http://marklogic.com/xdmp/custom-dictionary"
                at "/MarkLogic/custom-dictionary.xqy";

cdict:dictionary-read("en")

=> <cdict:dictionary
        xmlns:cdict="http://marklogic.com/xdmp/custom-dictionary"
        xml:lang="en">
     <cdict:entry>
        <cdict:word>Furbies</cdict:word>
        <cdict:stem>Furby</cdict:stem>
     </cdict:entry>
     <cdict:entry>
        <cdict:word>servlets</cdict:word>
        <cdict:stem>servlet</cdict:stem>
     </cdict:entry>
    </cdict:dictionary>
```

Put the contents in a file, for example `/var/tmp/cdict-en.xml`, then edit the file or modify it with XQuery to add new entries and/or delete or modify existing entries.

Next, install your modified dictionary in MarkLogic. The returned value is an empty sequence. Note that you do not have to specify where the dictionary goes, just what language to associate it with. The server knows where to put it. Since there can only be one custom dictionary for a language, this command overwrites any existing custom dictionary associated with the language argument.

```
xquery version "1.0-ml";
import module namespace dict =
"http://marklogic.com/xdmp/custom-dictionary"
                at "/MarkLogic/custom-dictionary.xqy";
let $dict := xdmp:document-get("/var/tmp/cdict-en.xml")/*
return
  cdict:dictionary-write("en",$dict)
=> empty sequence
```

Finally, if you want to delete your English custom dictionary, you would do something similar to the following, which returns the empty sequence.

```
xquery version "1.0-ml";
import module namespace cdict =
"http://marklogic.com/xdmp/custom-dictionary"
                at "/MarkLogic/custom-dictionary.xqy";
cdict:dictionary-delete("en")
=> empty sequence

xquery version "1.0-ml";
import module namespace cdict =
"http://marklogic.com/xdmp/custom-dictionary"
                at "/MarkLogic/custom-dictionary.xqy";
cdict:dictionary-read("en");
```

The previous examples use several queries, each query performing its own transaction, to read, save, and modify a custom dictionary. The following example accomplishes something similar in a single transaction, where the XQuery program reads and then modifies a custom dictionary.

```
(: Add an entry to the English custom dictionary :)
xquery version "1.0-ml";
import module namespace cdict =
         "http://marklogic.com/xdmp/custom-dictionary"
              at "/MarkLogic/custom-dictionary.xqy";
  let $language := "en"
(: Get the English custom dictionary :)
  let $dictionary := cdict:dictionary-read($language)
(: Specify the new entry element as XML (not as a string) :)
  let $entry := <cdict:entry>
                  <cdict:word>views</cdict:word>
                  <cdict:stem>view</cdict:stem>
                </cdict:entry>
(: First, check if there are already any dictionary entries :)
  return if (fn:empty($dictionary))
(: If no entries, then we have to create a cdict:dictionary
   element and insert our new entry before writing it out :)
      then cdict:dictionary-write($language,
                                  element cdict:dictionary {
                                      attribute xml:lang {
                                          $language },
                                      $entry})

(: If there are entries, just insert the new entry as a node and
   write out the dictionary :)
      else cdict:dictionary-write($language,
                                  xdmp:node-insert-child(
                                     $dictionary/dictionary,$entry))

(: Finally, test the new mapping; this should return "view":)
cts:stem("views", "en")
```

20.0 Extracting Metadata and Text From Binary Documents

This chapter describes how to extract metadata and/or text from binary documents. It contains the following sections:

- Metadata and Text Extraction Overview
- Usage Examples
- Supported Binary Formats

20.1 Metadata and Text Extraction Overview

Binary documents often have various associated metadata. For example, a JPEG image from a camera may have metadata of the camera's type and model number, a timestamp of when it was taken, and so on.

MarkLogic Server can access binary document metadata and then store it as XML in a properties document. You can then search and retrieve the metatdata using MarkLogic Server's rich XML search capabilities. In addition, for text-based binary documents, such as those in Microsoft Word format, MarkLogic can extract and index their text content.

MarkLogic Server server offers the XQuery built-in, `xdmp:document-filter`, and JavaScript method, `xdmp.documentFilter`, to extract and associate metadata from binary documents: These functions extract metadata and text from binary documents as XHTML. The results may be used as document properties. The extracted text contains little formatting or structure, so it is best used for search, classification, or other text processing.

20.2 Usage Examples

The following sections show how xdmp:document-filter works with various file types. The Microsoft Word section also provides code to extract only the metadata elements from combined metadata and text results.

- Microsoft Word
- File Archives
- PowerPoint

20.2.1 Microsoft Word

The following query and results are for a Microsoft Word document containing only the text "This is a test":

```
xquery version "1.0-ml";
  xdmp:document-filter(doc("/documents/test.docx"))
```

Returns:

```
<?xml version="1.0" encoding="UTF-8"?>
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <meta name="content-type" content="application/msword"/>
    <meta name="filter-capabilities"
          content="text subfiles HD-HTML"/>
    <meta name="AppName" content="Microsoft Office Word"/>
    <meta name="Author" content="Clark Kent"/>
    <meta name="Company" content="MarkLogic"/>
    <meta name="Creation_Date" content="2011-10-11T02:40:00Z"/>
    <meta name=”Description”
          content=”This is my comment.”/>
    <meta name="Last_Saved_Date" content="2011-10-11T02:41:00Z"/>
    <meta name="Line_Count" content="1"/>
    <meta name="Paragraphs_Count" content="1"/>
    <meta name="Revision" content="1"/>
    <meta name="Template" content="Normal"/>
    <meta name="Typist" content="Clark Kent"/>
    <meta name="Word_Count" content="4"/>
    <meta name="isys" content="SubType: Word 2007"/>
    <meta name="size" content="12691"/>
  </head>
  <body>
    <p>
    </p>
    <p>
       This is a test.</p>
    <p>
    </p>
  </body>
</html>
```

In the document, the word “test” is both italicized and bolded. `xdmp:document-filter` does not return such text formatting.

Expanding on the previous example, the following code uses `xdmp:document-filter` to extract only the metadata from that same Microsoft Word document:

```
xquery version "1.0-ml";
let $url := "/documents/test.docx"
return xdmp:document-set-properties(
  $url,
  for $meta in xdmp:document-filter(fn:doc($the-document))//*:meta
  return element {$meta/@name} {fn:string($meta/@content)}
)
```

The properties document now looks as follows:

```
xdmp:document-properties(“/documents/test.docx”)
```

returns:

```
<prop:properties xmlns:prop="http://marklogic.com/xdmp/property">
  <content-type>application/msword</content-type>
  <filter-capabilities>text subfiles HD-HTML</filter-capabilities>
  <AppName>Microsoft Office Word</AppName>
  <Author>Clark Kent</Author>
  <Company>MarkLogic</Company>
  <Creation_Date>2011-10-11T02:40:00Z</Creation_Date>
  <Description>This is my comment.</Description>
  <Last_Saved_Date>2011-10-11T02:41:00Z</Last_Saved_Date>
  <Line_Count>1</Line_Count>
  <Paragraphs_Count>1</Paragraphs_Count>
  <Revision>1</Revision>
  <Subject>Creating binary doc props</Subject>
  <Template>Normal/Template>
  <Typist>Clark Kent</Typist>
  <Word_Count>4</Word_Count>
  <isys>SubType: Word 2007</isys>
  <size>12691</size>
  <prop:last-modified>2011-10-12T09:47:10-07:00</prop:last-modified>
</prop:properties>
```

20.2.2 File Archives

If you need to extract files from `zip` archives for individual processing, use `xdmp:zip-manifest` and `xdmp:zip-get`. Use `xdmp:document-filter` if you just want all the text from the archive, since it does not preserve the embedded files' structure, but includes all of the documents' text. This is useful for finding the original location in search results; if you search for "Elvis" and use `xdmp:document-filter` on the various files, the results include every binary containing "Elvis", whether it is a zip archive, Word document, or photo.

In this example, `xdmp:document-filter` runs on the file archive `test.zip`, which consists of two Word files and a JPEG file,

```
xquery version "1.0-ml";
  xdmp:document-filter(doc("/documents/test.zip"))
```

returns

```
<?xml version="1.0" encoding="UTF-8"?>
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <meta name="content-type" content="application/zip"/>
    <meta name="filter-capabilities" content="subfiles"/>
    <meta name="AppName" content="Microsoft Office Word"/>
    <meta name="Author" content="Lois Lane"/>
    <meta name="Company" content="MarkLogic"/>
    <meta name="Creation_Date" content="2011-10-14T21:11:00Z"/>
    <meta name="Last_Saved_Date" content="2011-10-14T21:11:00Z"/>
    <meta name="Line_Count" content="1"/>
```

```
      <meta name="Paragraphs_Count" content="1"/>
      <meta name="Revision" content="2"/>
      <meta name="Template" content="Normal"/>
      <meta name="Typist" content="Lois Lane"/>
      <meta name="Word_Count" content="3"/>
      <meta name="isys" content="SubType: Word 2007"/>
      <meta name="Focal_Length" content="4"/>
      <meta name="Make" content="LG Electronics"/>
      <meta name="Model" content="VM670"/>
      <meta name="Original_Date_Time" content="2011:10:19 14:59:24"/>
      <meta name="Original_Date_Time.datetime"
            content="2011-10-19T14:59:24Z"/>
      <meta name="ResolutionUnit" content="2"/>
      <meta name="XResolution" content="72.000000"/>
      <meta name="YResolution" content="72.000000"/>
      <meta name="AppName" content="Microsoft Office Word"/>
      <meta name="Author" content="Clark Kent"/>
      <meta name="Company" content="MarkLogic"/>
      <meta name="Creation_Date" content="2011-10-11T02:40:00Z"/>
      <meta name="Last_Saved_Date" content="2011-10-11T02:41:00Z"/>
      <meta name="Line_Count" content="1"/>
      <meta name="Paragraphs_Count" content="1"/>
      <meta name="Revision" content="1"/>
      <meta name="Template" content="Normal"/>
      <meta name="Typist" content="Clark Kent"/>
      <meta name="Word_Count" content="2"/>
      <meta name="isys" content="SubType: Word 2007"/>
      <meta name="size" content="47730"/>
    </head>
  <body>
   <p>
   </p>
   <p>
    This is a another test.</p>
    <p>
    </p>
    <p>
      This is a test.</p>
    <p>
    </p>
  </body>
  </html>
```

While each sentence in this example's returned HTML body text is from a different file, there is no way to distinguish which text comes from which file. Similarly, the returned subfile metadata is not guaranteed to be returned in file order (for example, `name="a", name="b"` might be from different documents in the archive) and so also cannot be correctly associated with an individual subfile.

Also, individual subfiles in the archive are not necessarily distinguishable at all. In the above example, you cannot tell from the output how many files, or what file types, are in the archive. When using `xdmp:document-filter` on an archive, you should think of the archive as a single file, rather than a compilation of subfiles. You will get back all the metadata and text contained in the single archive file, but will have no way of associating that returned information with the individual subfiles it came from.

20.2.3 PowerPoint

The following query and results are for a two slide PowerPoint document, where each slide has a title and separate content:

```
xquery version "1.0-ml";
  xdmp:document-filter(doc("/documents/test.pptx"))
```

returns:

```
<?xml version="1.0" encoding="UTF-8"?>
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <meta name="content-type"
          content="application/vnd.ms-powerpoint"/>
    <meta name="filter-capabilities" content="text subfiles HD-HTML"/>
    <title>This is a test </title>
    <meta name="AppName" content="Microsoft Office PowerPoint"/>
    <meta name="Author" content="Clark Kent"/>
    <meta name="Company" content="MarkLogic"/>
    <meta name="Creation_Date" content="2011-10-17T19:58:34Z"/>
    <meta name="Last_Saved_Date" content="2011-10-17T20:00:13Z"/>
    <meta name="Paragraphs_Count" content="4"/>
    <meta name="Presentation_Format" content="On-screen Show (4:3)"/>
    <meta name="Revision" content="1"/>
    <meta name="Slide_Count" content="2"/>
    <meta name="Typist" content="Clark Kent"/>
    <meta name="Word_Count" content="12"/>
    <meta name="isys" content="SubType: PowerPoint 2007"/>
    <meta name="size" content="36909"/>
  </head>
  <body>
<p>
</p>
<p>
This is a test </p>
<p>
Of PowerPoint</p>
<p>


</p>
<p>
Test #3
```

```
</p>
<p>
Second Slide.</p>
<p>


</p>
</body>
</html>
```

Similarly, any text formatting is not returned, nor is any indicator of what role the text played on a slide (title, body, etc.), nor is there any way to tell what text belongs to which slide.

20.3 Supported Binary Formats

The following sections list the binary file formats and file extensions from which `xdmp:document-filter` can extract metadata and, depending on the format, text from. Due to the large number of formats, they are first broken down into general application areas, such as Databases or Multimedia, then each area lists its applicable formats and extensions.

Some formats can be identified by `xdmp:document-filter`, but have no text or metadata to extract, such as executables. For these, the returned `<meta name="content-type" content=.../>` identifies the file's format.

- Archives
- Databases
- Email and Messaging
- Multimedia
- Other
- Presentation
- Raster Image
- Spreadsheet
- Text and Markup
- Vector Image
- Word Processing and General Office

20.3.1 Archives

Formats: 7-Zip, ACE, ARJ, Bzip2, ISO Disk Image, Java Archive, LZH, Microsoft Cabinet, Microsoft Office Binder, RedHat Package Manager, Roshal Archive, Self-extracting .exe, StuffIt, StuffIt Self Extracting Archive, SuffIt X, GNU Zip, UNIX cpio, UNIX Tar, Zip, PKZip, WinZip

Extensions: .7Z, .ACE, .ARJ, .BZ2, .CAB, .CPIO, .EXE, .GZ, .ISO, JAR, LZH, .ORD, .RAR, .RPM, .SIT, .SEA, .SITX, .TAR, .TBZ2, .ZIP

20.3.2 Databases

Formats: dBase, dBase III, Microsoft Access, Paradox Database

Extensions: .DB, .DBF, .DB3, .MDB

20.3.3 Email and Messaging

Formats: Encoded mail messages of any of the forms MHT, Multipart Alternative, Multipart Digest, Multipart Mixed, Multipart Newsgroup, Multipart Signed, and TNEF. Also, the individual formats Eudora, Microsoft Outlook, Microsoft Outlook3, Microsoft Outlook Express3. Microsoft Outlook Forms Template, Sendmail "mbox", Thunderbird

Extensions: .EML, .MBOX, .MBX, .MHT, .MSG, .OFT, .PST

20.3.4 Multimedia

Formats: 3GP, Adobe Flash, Adobe Flash Video, Audio Video Interleave (AVI), DVD Information File, DVD Video Object, Microsoft Windows Movie Maker, Musical Instrument Digital Interface (MIDI), MPEG Video, MPEG-1 Audio Layer 3, MPEG-4 Video, MPEG-2 Audio Layer 3, OGG Flac Audio, OGG Vorbis Audio, QuickTime, Real Media, Waveform Audio File Format (WAVE), Window Media Audio, Windows Media Video.

Extensions: .3GP, .AIFF, .AVI, .BUP, .FLAC, .FLV, .IFO, .MID, .MIDI, .MOV, .MP3, .MP4, .MPG, .MSWMM, .OGG, .RM, .SMF, .SWF, .VOB, .WAV, .WMA, .WMV

20.3.5 Other

Formats: Apple Executable, BIN HEX Encoded, BitTorrent Metafile, Linux Executable and Linkable Format, Log File, Microsoft Project, Microsoft Windows DLL, Microsoft Windows Executable, Microsoft Windows Installer, Microsoft Windows, Shortcut, Open Access II (OAII), VCard, Uniplex

Extensions: .BIN, .COM, .DLL, .ELF, .EXE, .HBX, .HEX, .HQXX, .LNK, .LOG, .MPP, .MPX, .MSI, .SYS, .TORRENT, .VCF

20.3.6 Presentation

Formats: IBM Lotus Symphony Presentation, LibreOffice Presentation, Microsoft PowerPoint for Windows or Macintosh, OpenOffice Impress, StarOffice Impress

Extensions: .ODP, .ODS, .PPT, .PPTX, .SDI, .SDP, .SXI

20.3.7 Raster Image

Formats: Encapsulated PostScript, Grapics Interchange Format (GIF), Joint Photographic Experts Group (JPEG), Microsoft Document Imaging, Microsoft Windows Bitmap, PCX, Portable Network Graphic (PNG), Progressive JPEG, Tagged Image Format File (TIFF)

Extensions: .BMP, .EPS, .GFA, .GIF, .GIFF, .JIF, .JPEG, .JPG, .JPE, .MDI, .PCX, .PNG, .TIF, .TIFF

20.3.8 Spreadsheet

Formats: Comma Separated Values, Franeword Spreadsheet, IBM Lotus Symphony, LibreOffice Spreadsheet, Lotus 1-2-3, Microsoft Excel for Windows or Mac, Microsoft Works SS for DOS or Windows, OpenOffice Calc, StarOffice Calc

Extensions: .CSV, .FW3, .ODS, .SX, .SXC, .SXS, .XLS, XLSB, .XLSX, .WK., .WK3, .WK4, .WKS, .WPS

20.3.9 Text and Markup

Formats: ASCII Text (7 and 8 bit) , ANSI Text (7 and 8 bit), HTML (text only, codes revealed, metadata only), IBM DCA, Microsoft HTML Help, Microsoft OneNote, Rich Text Format, SGML Text, Source, Transcript, Unicode UTF8 and UTF16 and UCS2, XML, Windows Enhanced Meta File, Windows Meta File

Extensions: .CHM, .DCA, .EMF, .HTM, .HTML,.ONE, .RFT, .RTF, .SGML, .TXT, .XML, .WMF

20.3.10 Vector Image

Formats: Adobe Illustrator, Adobe InDesign, Adobe Photoshop, AutoCAD Drawing, AutoCAD drawing Exchange Format, Corel Draw Image, Intergraph-Microstation CAD, MathCAD, Microsoft XPS, Microsoft Visio

Extensions: .AI, .CDR, .DGN, .DWG, .DXF, .INDD, .MCD, .OXPS, .PSD, .VSD, .XMCD, .XPS

20.3.11 Word Processing and General Office

Formats: Adobe PDF, Adobe PostScript, Ami Pro for Windows, Apple iWork, Framework WP, Hangul, IBM DCA/FFT, IBM DisplayWrite, IBM Lotus Symphony Document, JustSystems Ichitaro, LibreOfffice Document, Lotus Manuscript, Lotus Notes, Mass 11, Microsoft Publisher, Microsoft Word for DOS/Windows/Macintosh, QuarkXpress, MultiMate, MultiMate Advantage, OpenOffice Writer, Professional Write for DOS, Professional Write Plus for Windows, Q&A Write, QuickBooks Backup, QuickBooks for Windows, StarOffice Writer, TrueType Font, VCalendar Electronic Calendar, Wang IWP, Wang WP Plus, Windows Write, WinWord, WordPerfect for DOS/Macintosh/Windows, Wordstar for DOS/Windows, Wordstar 2000 for DOS, XYwrite

Extensions: .AMI, .DCA, DOC, .DOCX, .DOX, .DW4, .FFT, .FW3, .ICS, .IWP, .JTD, .JBW, .JTT, ,KEY, .M11, .MAN, .MANU, .MNU, .NSF, .NUMBERS, .ODT, PAGES, .PDF, .PS, .PUT, .QCx, .QXx, .PW, .PW1, .PW2, .QA, .QA3, .QBB, .QBW, .RFT, .SAM, .SXW, .SDW, .TTF, .VCS, .WPD, WRI, .WS, .WS2, .WSD, .XY

21.0 Understanding and Using Wildcard Searches

This chapter describes wildcard searches in MarkLogic Server. The following sections are included:

- Wildcards in MarkLogic Server
- Enabling Wildcard Searches
- Interaction with Other Search Features

21.1 Wildcards in MarkLogic Server

Wildcard searches enable MarkLogic Server to return results that match combinations of characters and wildcards. Wildcard searches are not simply exact string matches, but are based on character pattern matching between the characters specified in a query and words in documents that contain those character patterns. This section describes wildcards and includes the following topics:

- Wildcard Characters
- Rules for Wildcard Searches

21.1.1 Wildcard Characters

MarkLogic Server supports two wildcard characters: `*` and `?`.

- `*` matches zero or more non-space characters.
- `?` matches exactly one non-space character.

For example, `he*` will match any word starting with `he`, such as `he`, `her`, `help`, `hello`, `helicopter`, and so on. On the other hand, `he?` will only match three-letter words starting with `he`, such as `hem`, `hen`, and so on.

21.1.2 Rules for Wildcard Searches

The following are the basic rules for wildcard searches in MarkLogic Server:

- There can be more than one wildcard in a single search term or phrase, and the two wildcard characters can be used in combination. For example, `m*??` will match words starting with `m` with three or more characters.
- Spaces are used as word breaks, and wildcard matching only works within a single word. For example, `m*th*` will match `method` but not `meet there`.
- If the `*` wildcard is specified by itself in a value query (for example, `cts:element-value-query`, `cts:element-value-match`), it matches everything (spanning word breaks). For example, `*` will match the value `meet me there`.

- If the `*` wildcard is specified with a non-wildcard character, it will match in value lexicon queries (for example, `cts:element-value-match`), but will not match in value queries (for example, `cts:element-value-query`). For example, `m*` will match the value `meet me there` for a value lexicon search (for example, `cts:element-value-match`) but will not match the value for a value query search (for example, `cts:element-value-query`), because the value query only matches the one word. A value search for `m* *` will match the value (because `m*` matches the first word and `*` matches everything after it).
- If `"wildcarded"` is explicitly specified in the `cts:query` expression, then the search is performed as a wildcard search.
- If neither `"wildcarded"` nor `"unwildcarded"` is specified in the `cts:query` expression, the database configuration and query text determine wildcarding. If the database has any wildcard indexes enabled (`three character searches`, `two character searches`, `one character searches`, or `trailing wildcard searches`) and if the query text contains either of the wildcard characters `?` or `*`, then the wildcard characters are treated as wildcards and the search is performed `"wildcarded"`. If none of the wildcard indexes are enabled, the wildcard characters are treated as punctuation and the search is performed `unwildcarded` (unless `"wildcarded"` is specified in the `cts:query` expression).
- If the query has the `punctuation-sensitive` option, then punctuation is treated as word characters for wildcard searches. For example, a `punctuation-sensitive` wildcard search for `d*benz` would match `daimler-benz`.
- If the query has the `whitespace-sensitive` option, then whitespace is treated as word characters. This can be useful for matching spaces in wildcarded value queries. You can use the `whitespace-sensitive` option in wildcarded word queries, too, although it might not make much sense, as it will match more than you might expect.
- You can only perform wildcard matches against JSON properties with text (string) values. Numbers, booleans, nulls are indexed separately in JSON. For details, see Creating Indexes and Lexicons Over JSON Documents in the *Application Developer's Guide*.

21.2 Enabling Wildcard Searches

Wildcard searches use character indexes, lexicons, and trailing wildcard indexes to speed performance. To ensure that wildcard searches are fast, you should enable at least one wildcard index (three character searches, trailing wildcard searches, two character searches, and/or one character searches) and fast element character searches (if you want fast searches within specific elements) in the Admin Interface database configuration screen. Wildcard are disabled by default. If you enable character indexes, you should plan on allocating an additional amount of disk space approximately three times the size of the source content.

This section describes the following topics:

- Specifying Wildcards in Queries
- Recommended Wildcard Index Settings

- Understanding the Wildcard Indexes

21.2.1 Specifying Wildcards in Queries

If any wildcard indexes are enabled for the database, you can further control the use of wildcards at the query level. You can use wildcards with any of the MarkLogic `cts:query` leaf-level functions, such as `cts:word-query`, `cts:element-word-query, and cts:element-value-query`. For details on the `cts:query` functions, see "Composing cts:query Expressions" on page 240. You can use the `"wildcarded"` and `"unwildcarded"` query option to turn wildcarding on or off explicitly in the `cts:query` constructor functions. See the *MarkLogic XQuery and XSLT Function Reference* for more details.

If you leave the wildcard option unspecified and there are any wildcard indexes enabled, MarkLogic Server will perform a wildcard query if `*` or `?` is present in the query. For example, the following search function:

```
cts:search(fn:doc(), cts:word-query("he*"))
```

will result in a wildcard search. Therefore, as long as any wildcard indexes are enabled in the database, you do not have to turn on wildcarding explicitly to perform wildcard searches.

When wildcard indexing is enabled in the database, the system will also deliver higher performance for `fn:contains`, `fn:matches`, `fn:starts-with` and `fn:ends-with` for most query expressions.

> **Note:** If character indexes, lexicons, and trailing wildcard indexes are all disabled in a database and wildcarding is explicitly enabled in the query (with the `"wildcarded"` option to the leaf-level `cts:query` constructor), the query will execute, but might require a lot of processing. Such queries will be fast if they are very selective and only need to do the wildcard searches over a relatively small amount of content, but can take a long time if they actually need to filter out results from a large amount of content.

21.2.2 Recommended Wildcard Index Settings

To enable any kind of wildcard query functionality with a good combination of performance and database size, MarkLogic recommends you enable the following index settings:

- `word searches`
- `three character word searches`
- `word positions`
- `word lexicon` in the codepoint collation
- `three character word positions`

For details, see"Understanding the Wildcard Indexes" on page 529 and Understanding the Text Index Settings in the *Administrator's Guide*.

This combination will provide accurate and fast wildcard queries for a wide variety of wildcard searches, including leading and trailing wildcarded searches. If you add the `trailing wildcard searches` index, you will get slightly more efficient trailing wildcard searches, but with increased database size.

If you only need wildcards against specific XML elements, XML attributes, JSON properties, or fields, you should consider using an element or field word lexicon instead of a general word lexicon. Doing so can improve the speed and accuracy of wildcard matching. Consider this option if you're primarily performing wildcard searches using the following query types or their equivalent:

- `cts:element-value-query`
- `cts:element-attribute-value-query`
- `cts:json-property-value-query`
- `cts:field-value-query`

21.2.3 Understanding the Wildcard Indexes

You configure the index settings at the database level, using the Admin Interface or Admin APIs (XQuery, Server-Side JavaScript, or REST). For details on configuring database settings and on other text indexes, see Database Settings and Text Indexing in the *Administrator's Guide*.

The following database settings can affect the performance and accuracy of wildcard searches. For details, see Understanding the Text Index Settings in the *Administrator's Guide*.

- word lexicons
- element, element attribute, and field word lexicons. (Use an element word lexicon for a JSON property).
- `three character searches`, `two character searches`, or `one character searches`. You do not need one or two character searches if three character searches is enabled.
- `three character word positions`
- `trailing wildcard searches`, `trailing wildcard word positions`, `fast element trailing wildcard searches`
- `fast element character searches`

The `three character searches` index combined with the word lexicon provides the best performance for most queries, and the `fast element character searches` index is useful when you submit element queries. One and two character searches indexes are only used if you submit wildcard searches that try and match only one or two characters and you do not have the combination of a word lexicon and the `three character searches` index. Because one and two character searches generally return a large number of matches, they might not justify the disk space and load time trade-offs.

Note: If you have the `three character searches` index enabled and two and one character indexes disabled, and if you have no word lexicon, it is still possible to issue a wildcard query that searches for a two or one character stem (for example, `ab*` or `a*`); these searches are allowed, but will not be fast. If you have a search user interface that allows users to enter such queries, you might want to check for these two or one character wildcard search patterns and issue an error, as these searches without the corresponding indexes can be slow and resource-intensive. Alternatively, add a codepoint collation word lexicon to your database.

As with all indexing, choosing which indexes to use is a trade-off. Enabling more indexes provides improved query performance, but uses more disk space and increases load and reindexing time. For most environments where wildcard searches are required, MarkLogic recommends enabling the `three character searches` and a codepoint collation word lexicon, but disabling one and two character searches.

If you only need to perform wildcard searches on specific elements, attributes, JSON properties, or fields, you can save some space and potentially improve accuracy by using an element, attribute, or field word lexicon instead of a general word lexicon.

Also, if you just want to apply wildcard searches to selected content, fields enable you to leave the wildcard indexes disabled at the database level, while still enabling them at the field level. For details, see Understanding Field Configurations in the *Administrator's Guide*.

21.3 Interaction with Other Search Features

This section describes the interactions between wildcard, stemming, and other search features in MarkLogic Server. The following topics are included:

- Wildcarding and Stemming
- Wildcarding and Punctuation Sensitivity

21.3.1 Wildcarding and Stemming

Wildcard searches can be used in combination with stemming (for details on stemming, see "Understanding and Using Stemmed Searches" on page 507); that is, queries can perform stemmed searches and wildcard searches at the same time. However, the system will not perform a stemmed search on words that are wildcarded. For example, assume a search phrase of `running car*`. The term `running` will be matched based on its stem. However, `car*` will be matched based on a wildcard search, and will match `car`, `cars`, `carriage`, `carpenter` and so on; stemmed word matches for the words matching the wildcard are *not* returned.

21.3.2 Wildcarding and Punctuation Sensitivity

Stemming and punctuation sensitivity perform independently of each other. However, there is an interaction between wildcarding and punctuation sensitivity. This section describes this interaction and includes the following parts:

- Implicitly and Explicitly Specifying Punctuation
- Rules for Punctuation and Wildcarding Interaction
- Examples of Wildcard and Punctuation Interactions

21.3.2.1 Implicitly and Explicitly Specifying Punctuation

MarkLogic Server allows you to explicitly specify whether a query is punctuation sensitive and whether it uses wildcards. You specify this in the options for the query, as in the following example:

```
cts:search(fn:doc(), cts:word-query("hello!", "punctuation-sensitive") )
```

If you include a wildcard character in a punctuation sensitive search, it will treat the wildcard as punctuation. For example, the following query matches `hello*`, but not `hellothere`:

```
cts:search(fn:doc(), cts:word-query("hello*", "punctuation-sensitive") )
```

If the punctuation sensitivity option is left unspecified, the system performs a punctuation sensitive search if there is any non-wildcard punctuation in the query terms. For example, if punctuation is not specified, the following query:

```
cts:search(fn:doc(), cts:word-query("hello!") )
```

will result in a punctuation sensitive search, and the following query:

```
cts:search(fn:doc(), cts:word-query("hello") )
```

will result in a punctuation insensitive search.

If a search is punctuation sensitive (whether implicitly or explicitly), MarkLogic Server will match the punctuation as well as the search term. Note that punctuation is not considered to be part of a word. For example, `mark!` is considered to be a word `mark` next to an exclamation point. If a search is punctuation insensitive, punctuation will match spaces.

21.3.2.2 Rules for Punctuation and Wildcarding Interaction

The characters `?` and `*` are considered punctuation in documents loaded into the database. However, `?` and `*` are also treated as wildcard characters in a query. This makes for interesting (and occasionally confusing) interaction between wildcarding and punctuation sensitivity.

The following are the rules for the interaction between punctuation and wildcarding. They will help you determine how the system behaves when there are interactions between the punctuation and wildcard characters.

1. When wildcard indexes are disabled in the database, all queries default to `"unwildcarded"`, and wildcard characters are treated as punctuation. If you specify `"wildcarded"` in the query, the query is a wildcard query and wildcard characters are treated as wildcards.

2. Wildcarding trumps (has precedence over) punctuation sensitivity. That is, if the `*` and/or `?` characters are present in a query, `*` and `?` are treated as wildcards and not punctuation unless wildcarding is turned off. If wildcarding is turned off in the query (`"unwildcarded"`), they are treated as punctuation.

3. If wildcarding and punctuation sensitivity are both explicitly off and punctuation characters (including `*` and `?`) are in the query, they are treated as spaces.

4. Wildcarding and punctuation sensitivity can be on at the same time. In this case, punctuation in a document is treated as characters, and wildcards in the query will match any character in the query, including punctuation characters. Therefore, the following query will match both `hello*` and `hellothere`:

```
cts:search(fn:doc(),
           cts:word-query("hello*",
                          ("punctuation-sensitive", "wildcarded") )
           )
```

21.3.2.3 Examples of Wildcard and Punctuation Interactions

This section contains examples of the output of queries in the following categories:

- Wildcarding and Punctuation Sensitivity Not Specified (Wildcard Indexes Enabled)
- Wildcarding Explicitly Off, Punctuation Sensitivity Not Specified
- Wildcarding Not Specified, Punctuation Sensitivity Explicitly On (Wildcard Indexes Enabled)

Wildcarding and Punctuation Sensitivity Not Specified (Wildcard Indexes Enabled)

The following examples show queries that are run when at least one wildcard index is enabled and no options are explicitly set on the `cts:word-query`.

- **Example query:** `cts:word-query("hello world")`

  Actual behavior: Wildcarding off, punctuation insensitive

  Will match: `hello world`, `hello ?! world`, `hello? world!` and so on

- **Example query:** `cts:word-query("hello?world")`

  Actual behavior: Wildcarding on, punctuation insensitive

  Will match: `helloaworld`

  Will not match: `hello world`, `hello!world`

- **Example query:** `cts:word-query("hello*world")`

  Actual behavior: Wildcarding on, punctuation insensitive

  Will match: `helloabcworld`

  Will not match: `hello to world`, `hello-to-world`

- **Example query:** `cts:word-query("hello * world")`

  Actual behavior: Wildcarding on, punctuation insensitive

  Will match: `hello to world`, `hello-to-world`

  Will not match: `helloaworld`, `hello world`, `hello ! world`

  Note: Adjacent spaces are collapsed for string comparisons in the server. In the query phrase `hello * world`, the two spaces on each side of the asterisk are not collapsed for comparison since they are not adjacent to each other. Therefore, `hello world` is not a match since there is only a single space between `hello` and `world` but `hello * world` requires two spaces because the spaces were not collapsed. The phrase `hello ! world` is also not a match because `!` is treated as a space (punctuation insensitive), and then all three consecutive spaces are collapsed to a single space before the string comparison.

- **Example query:** `cts:word-query("hello! world")`

  Actual behavior: Wildcarding off, punctuation sensitive

  Will match: `hello! world`

  Will not match: `hello world`, `hello; world`

- **Example query:** `cts:word-query("hey! world?")`

  Actual behavior: Wildcarding on, punctuation sensitive

  Will match: `hey! world?`, `hey! world!`, `hey! worlds`

  Will not match: `hey. world`

Wildcarding Explicitly Off, Punctuation Sensitivity Not Specified

The following examples show the matches for queries that specify `"unwildcarded"` and do not specify anything about punctuation-sensitivity.

- **Example query:** `cts:word-query("hello?world", "unwildcarded")`

  Actual behavior: Wildcarding off, punctuation sensitive

  Will match: `hello?world`

  Will not match: `hello world`, `hello;world`

- **Example query:** `cts:word-query("hello*world", "unwildcarded")`

  Actual behavior: Wildcarding off, punctuation sensitive

  Will match: `hello*world`

  Will not match: `helloabcworld`

Wildcarding Not Specified, Punctuation Sensitivity Explicitly On (Wildcard Indexes Enabled)

The following examples show queries that are run when at least one wildcard index is enabled and the `"punctuation-sensitive"` option is explicitly set on the `cts:word-query`.

- **Example query:** `cts:word-query("hello?world", "punctuation-sensitive")`

  Actual behavior: Wildcarding on, punctuation sensitive

  Will match: `hello?world`, `hello.world`, `hello*world`

  Will not match: `hello world`, `hello ! world`

- **Example query:** `cts:word-query("hello * world", "punctuation-sensitive")`

  Actual behavior: Wildcarding on, punctuation sensitive

  Will match: `hello abc world`, `hello ! world`

  Will not match: `hello-!- world`

- **Example query:** `cts:word-query("hello? world", "punctuation-sensitive")`

  Actual behavior: Wildcarding on, punctuation sensitive

  Will match: `hello! world`, `(hello) world`

Note: `(hello) world` is a match because `?` matches `)` and `(` is not considered part of the word `hello`.

Will not match: `ahello) world`, `hello to world`.

22.0 Collections

MarkLogic Server includes *collections*, which are groups of documents that enable queries to efficiently target subsets of content within a MarkLogic database.

Collections are described as part of the W3C XQuery specification, but their implementation is undefined. MarkLogic has chosen to emphasize collections as a powerful and high-performance mechanism for selecting sets of documents against which queries can be processed. This chapter introduces the `collection()` function, explains how collections are defined and accessed, and describes some of the basic performance characteristics with which developers should be familiar. This chapter includes the following sections:

- The collection() Function
- Collections Versus Directories
- Defining Collections
- Collection Membership
- Collections and Security
- Performance Characteristics

22.1 The collection() Function

The `collection()` function can be used anywhere in your XQuery that the `doc()` or `input()` functions are used. The `collection()` function has the following signature:

```
fn:collection($URI as xs:string*) as node*
```

Note: The MarkLogic Server implementation of the `collection()` function takes a sequence of URIs, so you can call the `collection()` function on one or more collections. The signature of the function in the W3C XQuery documentation only takes a single string. Also, the `fn` namespace is built-in to MarkLogic Server, so it is not necessary to prefix the function with its namespace.

To illustrate what the `collection()` function is used for, consider the following two XPath expressions:

```
fn:doc()//sonnet/line[cts:contains(., "flower")]

collection("english-lit/shakespeare")//sonnet/
                                      line[cts:contains(., "flower")]
```

The first expression returns a sequence of line nodes, each of which must be the child of a sonnet node, and each of which must contain the term *flower*, matched on a case-insensitive basis.

The second expression returns the same sequence, except that only line nodes contained within documents that are members of the `english-lit/shakespeare` collection. MarkLogic Server optimizes this expression. The operation that uses the `collection()` function, along with the rest of the XPath expression, is executed very efficiently through a series of index lookups.

As mentioned previously, the `collection()` function accepts either a single collection, as illustrated above, or a sequence of collections, as illustrated below:

```
collection(("english-lit/shakespeare",
            "american-lit/poetry"))//sonnet/
                                line[cts:contains(., "flower")]
```

The query above returns a sequence of line nodes that match the stated predicates that are members of either the `english-lit/shakespeare` collection or the `american-lit/poetry` collection or both. With this modification to the `collection()` function, its format now closely matches the format of the `doc()` function, which also takes a sequence of URIs. While there is currently no XPath-level support for more complex boolean membership conditions (for example, requiring membership in multiple collections (and), excluding documents that belong to certain collections (not) or requiring pure either-or membership (exclusive or)), you can achieve these conditions through the `where` clause in a surrounding FLWOR expression (see "Collection Membership" on page 540 for an example).

22.2 Collections Versus Directories

Collections are used to organize documents in a database. You can also use directories to organize documents in a database. The key differences in using collections to organize documents versus using directories are:

- Collections do not require member documents to conform to any URI patterns. They are not hierarchical; directories are. Any document can belong to any collection, and any document can also belong to multiple collections.
- You can delete all documents in a collection with the `xdmp:collection-delete` function. Similarly, you can delete all documents in a directory (as well as all recursive subdirectories and any documents in those directories) with the `xdmp:directory-delete` function.
- You cannot set properties on a collection; you can on a directory.

Except for the fact that you can use both collections and directories to organize documents, collections are unrelated to directories. For details on directories, see Properties Documents and Directories in the *Application Developer's Guide*.

22.3 Defining Collections

Collection membership for a document is defined implicitly. Rather than describing collections top-down (that is, specifying the list of documents that belong to a given collection), MarkLogic Server determines membership in a bottoms-up fashion, by aggregating the set of documents that describe themselves as being a member of the collection. You can use MarkLogic Server's security scheme to manage policies around collection membership.

Collections are named using URIs. Any URI is a legal name for a collection. The URI must be unique within the set of collections (both protected and unprotected) in your database.

The URIs that are used to name collections serve *only* as identifiers to the server. In particular, collections are *not* modeled on filesystem directories. Rather, collections are interpreted as sets, not as hierarchies. A document that belongs to collection `english-lit/poetry/sonnets` need not belong to collection `english-lit/poetry`. In fact, the existence of a collection with URI `english-lit/poetry/sonnets` does not imply the existence of collections with URI `english-lit/poetry` or URI `english-lit`.

There are two types of collections supported by MarkLogic Server: unprotected collections and protected collections. The two types are identical in terms of the syntactic application of the `collection()` function. However, differences emerge in the way they are defined, in who can access the collections, and in who can modify, add or remove documents from them. The following subsections descripe these two ways of defining collection:

- Implicitly Defining Unprotected Collections
- Explicitly Defining Protected Collections

22.3.1 Implicitly Defining Unprotected Collections

Unprotected collections are created *implicitly*.

When a document is first loaded into the system, the load directive (whether through XQuery or XDBC) optionally can specify the collections to which that document belongs. In that list of collections, the specification of a collection URI that has not previously been used is the only action that is needed to create that new unprotected collection.

If collections are left unspecified in the load directive, the document is added to the database with collection membership determined by the default collections that are defined for the current user through the security model and by inheritance from the current user's roles. The invocation of these default settings can also result in the creation of a new unprotected collection. If collections are left unspecified in the load directive and the current user has no default collections defined, the document will be added to the database without belonging to any collections.

In addition, once a document is loaded into the database, you can adjust its membership in collections with any of the following built-in XQuery functions (assuming you possess the appropriate permissions to modify the document in question):

- `xdmp:document-add-collections`
- `xdmp:document-remove-collections`
- `xdmp:document-set-collections`

If a collection URI that is not otherwise used in the database is passed as a parameter to `xdmp:document-add-collections` or `xdmp:document-set-collections`, a new unprotected collection is created.

Unprotected collections disappear when there are no documents in the database that are members. Consequently, using `xdmp:document-remove-collections`, `xdmp:document-set-collections` or `xdmp:document-delete` may result in unprotected collections disappearing.

The `xdmp:collection-delete` function, which deletes every document in a database that belongs to a particular collection (assuming that the current user has the required permissions on a per-document basis), always results in the specified unprotected collection disappearing.

> **Note:** The `xdmp:collection-delete` function will delete all documents in a collection, regardless of their membership in other collections.

22.3.2 Explicitly Defining Protected Collections

Protected collections are created *explicitly.*

Protected collections afford certain security protections not available with unprotected collections (see "Collections and Security" on page 540). Consequently, rather than the implicit model described above, protected collections must be explicitly defined using the Admin Interface *before* any documents are assigned to that collection.

Once a protected collection and its security policies have been defined, documents can be added to that collection through the same mechanisms as described above for unprotected collections. However, in addition to the appropriate permissions to modify the document, the user also needs to have the appropriate permissions to modify the protected collection.

Just as protected collections are created explicitly, the collection does not disappear if the state of the database changes and there are no documents currently belonging to that protected collection. To remove a protected collection from the database, the Admin Interface must be used to delete that collection's definition.

22.4 Collection Membership

As described above, the collections (unprotected and protected) to which a specific document belongs can be specified at load-time and can be modified once the document has been loaded into the database. Documents can belong to many collections simultaneously.

If specific collections are not defined at load-time, the server will automatically assign collection membership for the document based on both the user's and the user's aggregate roles' default collection membership settings. To load a document that does not belong to any collections, explicitly specify the empty sequence as the collections parameter.

Collection membership can be leveraged in any XPath expression that the `collection()`, `doc()`, or `input()` functions are used. In addition, collection membership for a particular document or node can be queried using the `xdmp:document-get-collections` built-in.

For example, the following expression returns a sequence of line nodes, each of which must be the child of a sonnet node, and each of which must contain the term *flower*, matched on a case-insensitive basis, that belong to either the `english-lit/shakespeare` collection or the `american-lit/poetry` collection or both:

```
collection(("english-lit/shakespeare",
            "american-lit/poetry"))//sonnet/
                                line[cts:contains(., "flower")]
```

By contrast, the following expression returns a similar sequence of line nodes, except that the resulting nodes must belong to either the `english-lit/poetry` collection or the `american-lit/poetry` collection or both, but not to the `english-lit/shakespeare` collection:

```
for $line in collection(("english-lit/poetry", "american-lit/
     poetry"))//sonnet/line[cts:contains(., "flower")]
where xdmp:document-get-collections($line) !=
     "english-lit/shakespeare"
return $line
```

22.5 Collections and Security

Collections interact with the MarkLogic Server security model in three basic ways:

- All users and roles can optionally specify default collections. These are the collections to which newly inserted documents are added if collections are not explicitly specified at load-time.
- Adding a document to a collection—both at load-time and after the document has been loaded into the database—is contingent on the user possessing permissions to insert or update the document in question.

- Removing a document from a collection and using `xdmp:collection-delete` are similarly contingent on the user's having appropriate permissions to update the document(s) in question.

Protected collections interact with the MarkLogic Server security model in three additional ways:

- Protected collections must be configured using the security module of the Admin Interface.
- Protected collections specify the roles that have read, insert and/or update permissions for the protected collection.
- Adding or removing documents from protected collections requires not only the appropriate permissions for the documents, but also the appropriate permissions for the collections involved.

22.5.1 Unprotected Collections

To add to the database a new document that belongs to one or more unprotected collections, the user must have (directly or indirectly) the permissions required to add the document. This means that the user must either possess the admin role or have both of the following:

- The privilege to execute the `xdmp:document-load` function, if that is the document insertion directive being used.
- Either the `unprotected-uri` privilege, the `any-uri` privilege, or an appropriate URI privilege on the specific path of the document to be inserted. For example, if the document being inserted has the URI `/docs/poetry/love.xml`, the appropriate URI privileges are `/`, `/docs`, `/docs/poetry`.

To modify the set of collections to which a document belongs, the user must either possess the admin role or have update permissions on the document.

To access an unprotected collection in an XPath expression, no special permissions are used. Access to each of the individual documents that belong to the specified collection is governed by that individual document's read permissions.

22.5.2 Protected Collections

To add to the database a new document that belongs to one or more protected collections, the user must have (directly or indirectly) the permissions required to add the document as well as the permissions required to add to the protected collection(s). This means that the user must either possess the admin role or have all of the following:

- The insert permission on the protected collection.
- The privilege to execute the `xdmp:document-load` function, if that is the document insertion directive being used.
- Either the `unprotected-uri` privilege, the `any-uri` privilege, or an appropriate URI privilege on the specific path of the document to be inserted. For example, if the document being inserted has the URI `/docs/poetry/love.xml`, the appropriate URI privileges are `/`, `/docs`, `/docs/poetry`.

To modify the set of protected collections to which a document belongs, the user must either possess the admin role or have:

- Update permissions on the collection
- Update permissions on the document

To access a protected collection in an XPath expression, the user must have read permissions on the collection. In addition, access to each of the individual documents that belong to the specified collection is governed by that individual document's read permissions. Note that access to the documents themselves (as opposed to membership in the collection) is governed by the current user's roles and the permissions associated with each document.

The user can convert an unprotected collection into a protected collection using the Security Function Library module `sec:protect-collection`. Access to this library module is dependent on the user's having the `protect-collection` privilege.

The user can convert a protected collection into an unprotected collection using the Security Function Library module `sec:unprotect-collection`. Access to this library module is dependent on the user's having the `unprotect-collection` privilege and update permissions on the protected collection.

22.6 Performance Characteristics

MarkLogic's implementation of collections is designed to optimize query performance against large volumes of documents. As with all designs, the implementation involves some trade-offs. This section provides a brief overview of the performance characteristics of collections and includes the following subsections:

- Number of Collections to Which a Document Belongs
- Adding/Removing Existing Documents To/From Collections

22.6.1 Number of Collections to Which a Document Belongs

At document load time, collection information is embedded into the document and stored in the database.

This design enables a MarkLogic database to handle millions of collections without difficulty. It also enables the `collection()` function itself to be extremely efficient, able to subset large datasets by collection with a single index operation. If the `collection()` function specifies more than one collection, an additional index operation is required for each collection specified. Assuming queries target similar collections, these index operations should be resolved within cache at extremely high performance.

One trade-off with this design is a practical constraint on the number of collections to which a single document should belong. While there is no architectural limit, the size of the database will grow as the average number of collections per document increases. This database growth is driven by an increase in the size of individual document fragments. The fragment size increases because each collection to which the document belongs embeds a small amount of information in the fragment. As fragments grow, the corresponding storage I/O time increases, resulting in performance degradation. It is important to note that the average number of collections per document does not impact *index resolution* time, merely the time to retrieve the content (fragments) from storage.

A practical guideline is that a document with fragments averaging 50K in size should not belong to more than 100 collections. This should keep the average fragment size increase to less than 10%.

22.6.2 Adding/Removing Existing Documents To/From Collections

A second trade-off with MarkLogic's implementation of collections is that adding or removing documents from collections once those documents are already in the database can be relatively resource-intensive. Changing the collections to which a document belongs requires rewriting every fragment of the document. For large documents, this can be demanding on both CPU and I/O resources. If collection membership is highly dynamic in your application, a better approach may be to use elements within the document itself to characterize membership.

23.0 Using the Thesaurus Functions

MarkLogic Server includes functions that enable applications to provide thesaurus capabilities. Thesaurus applications use thesaurus (synonym) documents to find words with similar meaning to the words entered by a user. A common example application expands a user search to include words with similar meaning to those entered in a search. For example, if the application uses a thesaurus document that lists car brands as synonyms for the word *car*, then a search for car might return results for *Alfa Romeo*, *Ford*, and *Hyundai*, as well as for the word *car*.

This chapter describes how to use the thesaurus functions and contains the following sections:

- The Thesaurus Module
- Function Reference
- Thesaurus Schema
- Capitalization
- Managing Thesaurus Documents
- Expanding Searches Using a Thesaurus in XQuery

23.1 The Thesaurus Module

There is an XQuery module to perform thesarus functions. You can use this module either in XQuery or in Server-Side JavaScript. The thesaurus functions are installed into the following XQuery module file:

- *install_dir*`/Modules/MarkLogic/thesaurus.xqy`

where *install_dir* is the directory in which MarkLogic Server is installed. The functions in the thesaurus module use the `thsr:` namespace prefix, which you must specify in your XQuery program (or specify your own namespace). To use any of the functions in XQuery, include the module and namespace declaration in the prolog of your XQuery program as follows:

```
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";
```

To use any of the functions in a JavaScript program, include a line similar to the following in your Server-Side JavaScript program:

```
var thsr = require("/MarkLogic/thesaurus");
```

23.2 Function Reference

The reference information for the thesaurus module functions is included in the *MarkLogic XQuery and XSLT Function Reference* and the *MarkLogic Server-Side JavaScript Function Reference* available through docs.marklogic.com.

23.3 Thesaurus Schema

Any thesaurus documents loaded into MarkLogic Server must conform to the thesaurus schema, installed into the following file:

- *install_dir*/Config/thesaurus.xsd

where *install_dir* is the directory in which MarkLogic Server is installed.

23.4 Capitalization

Thesaurus documents and the thesaurus functions are case-sensitive. Therefore, a thesaurus term for *Car* is different from a thesaurus term for *car* and any lookups for these terms are case-sensitive.

If you want your applications to be case-insensitive (that is, if you want the term *Car* to return thesaurus entries for both *Car* and *car*), your application must handle the case of the terms you want to lookup. There are several ways to handle case. For example, you can lowercase all the entries in your thesaurus documents and then lowercase the terms before performing the lookup from the thesaurus. For an example of lowercasing terms in a thesaurus document, see "Lowercasing Terms When Inserting a Thesaurus Document" on page 547.

23.5 Managing Thesaurus Documents

You can have any number of thesaurus documents in a database. You can also add to or modify any thesaurus documents that already exist. This section describes how to load and update thesaurus documents, and contains the following sections:

- Loading Thesaurus Documents in XQuery
- Loading Thesaurus Documents in JavaScript
- Lowercasing Terms When Inserting a Thesaurus Document
- Loading the XML Version of the WordNet Thesaurus
- Updating a Thesaurus Document
- Security Considerations With Thesaurus Documents
- Example Queries Using Thesaurus Management Functions

23.5.1 Loading Thesaurus Documents in XQuery

To use a thesaurus in a query, use the `thsr:load` function or the `thsr:insert` function to load a document as a thesaurus. For example, to load a thesaurus document with a URI `/myThsrDocs/wordnet.xml`, execute a query similar to the following:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";

thsr:load("c:\thesaurus\wordnet.xml", "/myThsrDocs/wordnet.xml")
```

This XQuery adds all of the `<entry>` elements from the `c:\thesaurus\wordnet.xml` file to a thesaurus with the URI `/myThsrDocs/wordnet.xml`. If the document already exists, then it is overwritten with the new content from the specified file.

Note: If you have a thesaurus document that is too large to fit into an in-memory list, you can split the thesaurus into multiple documents. If you do this, you must specify all of the thesaurus documents in the thesaurus APIs that take URIs as a parameter. Also, ensure that there are no duplicate entries between the different thesaurus documents.

23.5.2 Loading Thesaurus Documents in JavaScript

To use a thesaurus in a Server-Side JavaScript program, use the `thsr.load` function or the `thsr.insert` function to load a document as a thesaurus. For example, to load a thesaurus document with a URI `/myThsrDocs/wordnet.xml`, execute a query similar to the following:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.load("c:\thesaurus\wordnet.xml", "/myThsrDocs/wordnet.xml")
```

This JavaScript program adds all of the `<entry>` elements from the `c:\thesaurus\wordnet.xml` file to a thesaurus with the URI `/myThsrDocs/wordnet.xml`. If the document already exists, then it is overwritten with the new content from the specified file.

Note: If you have a thesaurus document that is too large to fit into an in-memory list, you can split the thesaurus into multiple documents. If you do this, you must specify all of the thesaurus documents in the thesaurus APIs that take URIs as a parameter. Also, ensure that there are no duplicate entries between the different thesaurus documents.

23.5.3 Lowercasing Terms When Inserting a Thesaurus Document

You can use the `thsr:insert` function to perform transformation on a document before inserting it as a thesaurus document. The following example shows how you can use the `xdmp:get` function to load a document into memory, then walk through the in-memory document and construct a new document which has lowercase terms.

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                              at "/MarkLogic/thesaurus.xqy";

thsr:insert("newThsr.xml",
     let $thsrMem := xdmp:get("C:\myFiles\thesaurus.xml")
     return
<thesaurus xmlns="http://marklogic.com/xdmp/thesaurus">
{
   for $entry in $thsrMem/thsr:entry
   return
       (: Write out and lowercase the term, then write out all of
          the children of this entry except for the term, which was
          already written out and lowercased :)
     <thsr:entry>
       <thsr:term>{lower-case($entry/thsr:term)}</thsr:term>
          {$entry/*[. ne $entry/thsr:term]}
      </thsr:entry>
}
</thesaurus>
            )
```

23.5.4 Loading the XML Version of the WordNet Thesaurus

You can download an XML version of the *WordNet* from the MarkLogic Developer site (developer.marklogic.com/code/dictionaries). Once you download the thesaurus file, you can load it as a thesaurus document using the `thsr:load` XQuery function or the `thsr.load` JavaScript function.

Perform the following steps to download and load the *WordNet Thesaurus*:

1. Go to the code section of developer.marklogic.com and find the following page:

   ```
   http://developer.marklogic.com/code/dictionaries
   ```

2. Click the GitHub link.

3. Navigate to the thesaurus document section and find the `thesaurus.xml` document.

4. Save `thesaurus.xml` to a file (for example, `c:\thesaurus\thesaurus.xml`). Alternately, clone the GitHub repository.

5. Load the thesaurus with an XQuery statement similar to the following:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                              at "/MarkLogic/thesaurus.xqy";

thsr:load("c:\thesaurus\thesaurus.xml", "/myThsrDocs/wordnet.xml")
```

Or you can load the thesaurus in JavaScript with a program similar to the following:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.load("c:\thesaurus\wordnet.xml", "/myThsrDocs/wordnet.xml");
```

This loads the thesaurus with a URI of `/myThsrDocs/wordnet.xml`. You can now use this URI with the thesaurus module functions.

23.5.5 Updating a Thesaurus Document

Use the following thesaurus functions to modify existing thesaurus documents:

XQuery Function	Server-Side JavaScript Function
`thsr:set-entry`	`thsr.setEntry`
`thsr:add-synonym`	`thsr.addSynonym`
`thsr:remove-entry`	`thsr.removeEntry`
`thsr:remove-term`	`thsr.removeTerm`
`thsr:remove-synonym`	`thsr.removeSynonym`

Additionally, the `thsr:insert` / `thsr.insert` function adds entries to an existing thesaurus document (as well as creates a new one if one does not exist at the specified URI).

Note: The transactional unit in MarkLogic Server is a query; therefore, if you are performing multiple updates to the same thesaurus document, be sure to perform those updates as part of separate queries. In XQuery, you can place a semi-colon between the update statements to start a new query (and therefore a new transaction). If you use a semicolon to start any new queries that uses thesaurus functions in XQuery, each query must include the `import` statement in the prolog to resolve the thesaurus namespace.

23.5.6 Security Considerations With Thesaurus Documents

Thesaurus documents are stored in XML format in the database. Therefore, they can be queried just like any other document. Note the following about security and thesaurus documents:

- By default, thesaurus documents are loaded into the following collections:
  - http://marklogic.com/xdmp/documents
  - http://marklogic.com/xdmp/thesaurus
- Thesaurus documents are loaded with the default permissions of the user who loads them. Make sure users who load thesaurus documents have approriate privileges, otherwise the documents might not have the needed permissions for reading and updating. For more information, see Setting Document Permissions in the *Loading Content Into MarkLogic Server Guide*.
- If you want to control access (read and/or write) to thesaurus documents beyond the default permissions with which the documents are loaded, perform an `xdmp:document-set-permissions` after a `thsr:load` operation.

23.5.7 Example Queries Using Thesaurus Management Functions

This section includes the following examples, in both XQuery and JavaScript:

- Example: Adding a New Thesaurus Entry in XQuery
- Example: Adding a New Thesaurus Entry in JavaScript
- Example: Removing a Thesaurus Entry
- Example: Removing Term(s) from a Thesaurus in XQuery
- Example: Removing Term(s) from a Thesaurus in JavaScript
- Example: Adding a Synonym to a Thesaurus Entry in XQuery
- Example: Adding a Synonym to a Thesaurus Entry in JavaScript
- Example: Removing a Synonym From a Thesaurus in XQuery
- Example: Removing a Synonym From a Thesaurus in JavaScript

23.5.7.1 Example: Adding a New Thesaurus Entry in XQuery

The following XQuery uses the `thsr:set-entry` function to add an entry for *Car* to the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                              at "/MarkLogic/thesaurus.xqy";

thsr:set-entry("/myThsrDocs/wordnet.xml",
<entry xmlns="http://marklogic.com/xdmp/thesaurus">
    <term>Car</term>
    <part-of-speech>noun</part-of-speech>
    <synonym>
      <term>Ford</term>
      <part-of-speech>noun</part-of-speech>
    </synonym>
    <synonym>
      <term>automobile</term>
      <part-of-speech>noun</part-of-speech>
    </synonym>
    <synonym>
      <term>Fiat</term>
      <part-of-speech>noun</part-of-speech>
    </synonym>
</entry>)
```

If the `/myThsrDocs/wordnet.xml` thesaurus has an identical entry, there will be no change to the thesaurus. If the thesaurus has no entry for *car* or has an entry for *car* that is not identical (that is, where the nodes are not equivalent), it will add the new entry. The new entry is added to the end of the thesaurus document.

23.5.7.2 Example: Adding a New Thesaurus Entry in JavaScript

The JavaScript `thsr.setEntry` function allows you to use a JavaScript object to update your thesaurs documents. The following JavaScript uses the `thsr.setEntry` function to add an entry for *Car* to the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.setEntry("/myThsrDocs/wordnet.xml",
{
      "term":"Car",
      "partOfSpeech":"noun",
      "synonyms":[
        {"term":"Ford",
         "partOfSpeech":"noun"
        },
        {"term":"automobile",
         "partOfSpeech":"noun"
        },
        {"term":"Fiat",
         "partOfSpeech":"noun"
        }
      ]
    });
```

If the `/myThsrDocs/wordnet.xml` thesaurus has an identical entry, there will be no change to the thesaurus. If the thesaurus has no entry for *car* or has an entry for *car* that is not identical (that is, where the nodes are not equivalent), it will add the new entry. The new entry is added to the end of the thesaurus document.

23.5.7.3 Example: Removing a Thesaurus Entry

The following XQuery uses the `thsr:remove-entry` function to remove the second entry for *Car* from the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";

thsr:remove-entry("/myThsrDocs/wordnet.xml",
                  thsr:lookup("/myThsrDocs/wordnet.xml","Car")[2])
```

Similarly, the following is a JavaScript example to do the same thing:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.removeEntry("/myThsrDocs/roget.xml",
    thsr.lookup("/myThsrDocs/roget.xml","Car").toObject()[1])
```

This removes the second *Car* entry from the `/myThsrDocs/wordnet.xml` thesaurus document.

23.5.7.4 Example: Removing Term(s) from a Thesaurus in XQuery

The following XQuery uses the `thsr:remove-term` function to remove all entries for the term *Car* from the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";

thsr:remove-term("/myThsrDocs/wordnet.xml", "Car")
```

This removes all of the *Car* terms from the `/myThsrDocs/wordnet.xml` thesaurus document. If you only have a single term for *Car* in the thesaurus, the `thsr:remove-term` function does the same as the `thsr:remove-entry` function.

23.5.7.5 Example: Removing Term(s) from a Thesaurus in JavaScript

The following JavaScript program uses the `thsr.removeTerm` function to remove all entries for the term *Car* from the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.removeTerm("/myThsrDocs/wordnet.xml", "Car")
```

This removes all of the *Car* terms from the `/myThsrDocs/wordnet.xml` thesaurus document. If you only have a single term for *Car* in the thesaurus, the `thsr.removeTerm` function does the same as the `thsr.removeEntry` function.

23.5.7.6 Example: Adding a Synonym to a Thesaurus Entry in XQuery

The following XQuery adds the synonym *Alfa Romeo* to the thesaurus entry for *car* in the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";

thsr:add-synonym(thsr:lookup("/myThsrDocs/wordnet.xml", "car"),
                 <thsr:synonym>
                    <thsr:term>Alfa Romeo</thsr:term>
                 </thsr:synonym>)
```

This query assumes that the lookup for the *car* thesaurus entry returns a single entry. If the *car* lookup returns multiple entries, you must specify a single entry. For example, if you wanted to add the synonym to the first *car* entry in the thesaurus, specify the first argument as follows:

```
thsr:lookup("/myThsrDocs/wordnet.xml", "car")[1]
```

23.5.7.7 Example: Adding a Synonym to a Thesaurus Entry in JavaScript

The following JavaScript program adds the synonym *Alfa Romeo* to the thesaurus entry for *car* in the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.addSynonym(
  thsr.lookup("/myThsrDocs/wordnet.xml", "car"
     // requires the "elements" option because addSynonym takes an
     // element, not a JSON object
     "elements"),
    {"synonym":{
       "term": "Alfa Romeo"}
    })
```

This assumes that the lookup for the *car* thesaurus entry returns a single entry. If the *car* lookup returns multiple entries, you must specify a single entry. Notice also that the lookup must specify `"elements"` because `thsr.addSynonym` requires an element entry. For example, if you wanted to add the synonym to the first *car* entry in the thesaurus, specify the first argument using the `first` variable from the following code:

```
fn.subsequence(
  thsr.lookup("/myThsrDocs/wordnet.xml", "car"), 2, 1))
```

23.5.7.8 Example: Removing a Synonym From a Thesaurus in XQuery

The following XQuery removes the synonym *Fiat* from the thesaurus entry for *car* in the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
                            at "/MarkLogic/thesaurus.xqy";

thsr:remove-synonym(thsr:lookup("/myThsrDocs/wordnet.xml", "car"),
                 <thsr:synonym>
                    <thsr:term>Fiat</thsr:term>
                 </thsr:synonym>)
```

This query assumes that the lookup for the *car* thesaurus entry returns a single entry. If the *car* lookup returns multiple entries, you must specify a single entry. For example, if you wanted to remove the synonym from the first *car* entry in the thesaurus, specify the first argument as follows:

```
thsr:lookup("/myThsrDocs/wordnet.xml", "car")[1]
```

23.5.7.9 Example: Removing a Synonym From a Thesaurus in JavaScript

The following JavaScript program removes the synonym *Fiat* from the thesaurus entry for *car* in the thesaurus with URI `/myThsrDocs/wordnet.xml`:

```
var thsr = require("/MarkLogic/thesaurus");
declareUpdate();

thsr.removeSynonym(thsr.lookup("/myThsrDocs/wordnet.xml", "car",
   "elements"),
   {"term": "Fiat"});
```

This query assumes that the lookup for the *car* thesaurus entry returns a single entry. If the *car* lookup returns multiple entries, you must specify a single entry. For example, if you wanted to remove the synonym from the first *car* entry in the thesaurus, specify the first argument as follows:

```
fn.subsequence(
  thsr.lookup("/myThsrDocs/wordnet.xml", "car"), 2, 1))
```

23.6 Expanding Searches Using a Thesaurus in XQuery

You can expand a search to include terms from a thesaurus as well as the terms entered in the search. Consider the following XQuery statement:

```
xquery version "1.0-ml";
import module namespace thsr="http://marklogic.com/xdmp/thesaurus"
   at "/MarkLogic/thesaurus.xqy";

cts:search(
doc("/Docs/hamlet.xml")//LINE,
thsr:expand(
  cts:word-query("weary"),
  thsr:lookup("/myThsrDocs/thesaurus.xml", "weary"),
  (),
  (),
  () )
)
```

This query finds all of the lines in Shakespeare's *Hamlet* that have the word *weary* or any of the synonyms of the word *weary.*

Thesaurus entries can have many synonyms, though. Therefore, when you expand a search, you might want to create a user interface in the application which provides a form allowing a user to specify the desired synonyms from the list returned by `thsr:expand`. Once the user chooses which synonyms to include in the search, the application can add those terms to the search and submit it to the database.

23.7 Expanding Searches Using a Thesaurus in JavaScript

You can expand a search to include terms from a thesaurus as well as the terms entered in the search. Consider the following JavaScript program:

```
var thsr = require("/MarkLogic/thesaurus");

var res = [];
for (var x of
cts.doc("/shakespeare/plays/hamlet.xml").xpath("//LINE")) {
if (cts.contains(x,
                 thsr.expand(
                   cts.wordQuery("weary"),
                   thsr.lookup("/myThsrDocs/thesaurus.xml", "weary"),
                   null, null, null ))) {
    res.push(x) } };
res;
```

This returns an array containing all of the lines in Shakespeare's *Hamlet* that have the word *weary* or any of the synonyms of the word *weary*.

Thesaurus entries can have many synonyms, though. Therefore, when you expand a search, you might want to create a user interface in the application which provides a form allowing a user to specify the desired synonyms from the list returned by `thsr.expand`. Once the user chooses which synonyms to include in the search, the application can add those terms to the search and submit it to the database.

24.0 Using the Spelling Correction Functions

MarkLogic Server includes functions that enable applications to provide spelling capabilities. Spelling applications use dictionary documents to find possible misspellings for words entered by a user. A common example application will prompt a user for words that might be misspelled. For example, if a user enters a search for the word *albetros*, an application that uses the spelling correction functions might prompt the user if she means *albatross*.

This chapter describes how to use the spelling correction functions and contains the following sections:

- Overview of Spelling Correction
- The Spelling Dictionary Management Module Functions
- Function Reference
- Dictionary Documents
- Capitalization
- Managing Dictionary Documents
- Testing if a Word is Spelled Correctly
- Getting Spelling Suggestions for Incorrectly Spelled Words

24.1 Overview of Spelling Correction

The spelling correction functions enable you to create applications that check if words are spelled correctly. It uses one or more dictionaries that you load into the database and checks words against a dictionary you specify. You can control everything about what words are in the dictionary. There are functions to manage the dictionaries, check spelling, and suggest words for misspellings.

24.2 Function Reference

The reference information for the spelling module functions is included in the *MarkLogic XQuery and XSLT Function Reference* and the *MarkLogic Server-Side JavaScript Function Reference* available through docs.marklogic.com. The spelling functions are divided into the following categories:

- The Spelling Built-In Functions
- The Spelling Dictionary Management Module Functions

24.2.1 The Spelling Built-In Functions

The spelling correction functions are built-in functions and do not require the `import module` statement in the XQuery prolog. The following are the spelling correction functions:

XQuery Function	Server-Side JavaScript Function
`spell:is-correct`	`spell.isCorrect`
`spell:suggest`	`spell.suggest`
`spell:suggest-detailed`	`spell.suggestDetailed`
`spell:double-metaphone`	`spell.doubleMetaphone`
`spell:levenshtein-distance`	`spell.levenshteinDistance`

The `spell:double-metaphone` / `spell.doubleMetaphone` and `spell:levenshtein-distance` / `spell.levenshteinDistance` functions return the raw values from which `spell:suggest` / `spell.suggest`, `spell:suggest-detailed` / `spell.levenshteinDistance`, and `spell:is-correct` / `spell.isCorrect` calculate their values.

The difference between `spell:suggest` (JavaScript `spell.suggest`) and `spell:suggest-detailed` (JavaScript `spell.suggestDetailed`) is that `spell:suggest-detailed` provides some of the information used in calculating the suggestions, and it returns a report (an XML representaiton in XQuery and an array of objects in JavaScript), whereas `spell:suggest` returns a sequence of suggested words. For most spelling applications, `spell:suggest` is sufficient, but if you want finer control of the suggestions you provide (for example, if you want to calculate your own order of returning the suggestions), you can use `spell:suggest-detailed` and then filter on some of the criteria returned in its XML or JSON output.

24.2.2 The Spelling Dictionary Management Module Functions

There is an XQuery module to perform management of dictionary documents. You can use this module in either XQuery or in Server-Side JavaScript. The spelling correction dictionary management functions are installed into the following XQuery module file:

- *install_dir*`/Modules/MarkLogic/spell.xqy`

where *install_dir* is the directory in which MarkLogic Server is installed. The functions in the spelling module use the `spell:` namespace prefix, which is predefined in the server.

To use the functions in this module in an XQuery program, include the module declaration in the prolog of your XQuery program as follows:

```
import module namespace spell = "http://marklogic.com/xdmp/spell"
   at "/MarkLogic/spell.xqy";
```

To use the functions in this module in a JavaScript program, include a line similar to the following in your Server-Side JavaScript program:

```
var spell = require("/MarkLogic/spell");
```

24.3 Dictionary Documents

There are two types of dictionary documents you can load into MarkLogic:

- XML Dictionary Document
- JSON Dictionary Document

There are sample XML and JSON dictionary documents available at the following GitHub repository:

https://github.com/marklogic/dictionaries

You can use these documents or create your own dictionaries. You can also use the `spell:make-dictionary` / `spell.makeDictionary` spelling management function to create a dictionary document, and then use `spell:load` / `spell.load` to load the dictionary into the database.

24.3.1 XML Dictionary Document

Any XML dictionary documents loaded into MarkLogic must have the following basic structure:

```
<dictionary xmlns="http://marklogic.com/xdmp/spell">
    <metadata>
    </metadata>
    <word></word>
    <word></word>
    ......
</dictionary>
```

The `<metadata>` element is optional. Use `spell:make-dictionary` / `spell.makeDictionary` and `spell:load` / `spell.load` to create your own dictionary documents.

24.3.2 JSON Dictionary Document

Any JSON dictionary documents loaded into MarkLogic must have the following basic structure:

```
{
 "metadata": { ... },
 "words": ["word1", "word2", ... ]
}
```

The `metadata` property is optional. Use `spell:make-dictionary` / `spell.makeDictionary` and `spell:load` / `spell.load` to create your own dictionary documents.

24.4 Capitalization

The spelling lookup functions (`spell:is-correct`, `spell:suggest`, and `spell:suggest-detailed` in XQuery, `spell.isCorrect`, `spell.suggest`, and `spell.suggestDetailed` in JavaScript) are case-sensitive, so case is important for words in a dictionary. Additionally, there are some special rules to handle the first character in a spelling lookup. The following are the capitalization rules for the spelling correction functions:

- A capital first letter in a spelling lookup query does not make the spelling incorrect for `spell:is-correct` / `spell.isCorrect`. For example, *Word* will match an entry for *word* in the dictionary.
- If a word has the first letter capitalized in the dictionary, then only exact matches will be correct for `spell:is-correct` / `spell.isCorrect`. For example, if *Word* is in the dictionary, then *word* is incorrect.
- If a word has other letters capitalized in the dictionary, then only exact matches (or exact matches except for the case of the first letter in the word) will match for `spell:is-correct` / `spell.isCorrect`. For example, *word* will not match an entry for *woRd*, nor will *WOrd*, but *WoRd* will match.
- The `spell:suggest` /`spell.suggest` functions and the `spell:suggest-detailed` / `spell.suggestDetailed` functions all observe the capitalization of the first letter only. For example, `spell:suggest("THe")` will return *The*, *Thee*, *They*, and so on as suggestions, while `spell:suggest("tHe")` will give *the*, *thee*, *they*, and so on. In other words, if you capitalize the first letter of the argument to the `spell:suggest` / `spell.suggest` function, the suggestions will all begin with a capital letter. Otherwise, you will get lowercase suggestions.

If you want your applications to ignore case, then you should create a dictionary with all lowercase words and lowercase (using the XQuery `fn:lower-case` function, for example) the word arguments of all `spell:is-correct` / `spell.isCorrect` and `spell:suggest` / `spell.suggest` functions before submitting your queries.

24.5 Managing Dictionary Documents

You can have any number of dictionary documents in a database. You can also add to or modify any dictionary documents that already exist. This section describes how to load and update dictionary documents, and contains the following topics:

- Loading Dictionary Documents in XQuery
- Loading Dictionary Documents in JavaScript
- Loading one of the Sample XML Dictionaries
- Updating a Dictionary Document
- Security Considerations With Dictionary Documents

24.5.1 Loading Dictionary Documents in XQuery

To use a dictionary in a query, it must be in the database. To load a dictionary document using XQuery, use the `spell:load` function or the `spell:insert` function. For example, to load a dictionary document with a URI `/mySpell/spell.xml`, execute a query similar to the following:

```
xquery version "1.0-ml";
import module "http://marklogic.com/xdmp/spell"
  at "/MarkLogic/spell.xqy";

spell:load("c:\dictionaries\spell.xml", "/mySpell/spell.xml")
```

This XQuery adds all of the `<word>` elements from the `c:\dictionaries\spell.xml` file to a dictionary with the URI `/mySpell/spell.xml`. If the document already exists, then it is overwritten with the new content from the specified file.

24.5.2 Loading Dictionary Documents in JavaScript

To use a dictionary in a query, it must be in the database. To load a dictionary document using JavaScript, use the `spell.load` function or the `spell.insert` function. For example, to load a dictionary document with a URI `/mySpell/spell.json`, execute a program similar to the following:

```
var spell = require("/MarkLogic/spell");
declareUpdate();
spell.load("c:/dictionaries/spell.json", "/mySpell/spell.json");
```

This loads the file at the specified path into the dictionary JSON document at the specified URI.

24.5.3 Loading one of the Sample XML Dictionaries

You can download a sample dictionary from the MarkLogic Community site (developer.marklogic.com/code#dictionaries). The community site links to github, which has small, medium, and large versions of the dictionary. Once you download a dictionary XML file, you can load it as a dictionary document using the `spell:load` function.

Perform the following steps to download and load a sample dictionary:

1. Go to the *Code* page of developer.marklogic.com:

   http://developer.marklogic.com/code/#dictionaries

2. Navigate to the dictionary document section, then click the github link:

   `https://github.com/marklogic/dictionaries`

3. In the dictionaries folder, choose the `small-dictionary.xml`, `medium-dictionary.xml`, or `large-dictionary.xml` file (or any other dictionary docments that might be available). The large dictionary has approximately 100,000 words and is about 3 MB to download. ALternately, you can choose `small-dictionary.json`, `medium-dictionary.json`, or `large-dictionary.json` file to load a JSON dictionary.

4. Save `<size>-dictionary.xml` (or the corresponding JSON document) to a file (for example, `c:\dictionaries\spell.xml`).

5. Load the dictionary with a command similar to the following:

```
xquery version "1.0-ml";
import module "http://marklogic.com/xdmp/spell" at
              "/MarkLogic/spell.xqy";

spell:load("c:\dictionaries\spell.xml", "/mySpell/spell.xml")
```

This loads the dictionary with a URI of `/mySpell/spell.xml`. You can now use this URI with the spelling correction module functions.

24.5.4 Updating a Dictionary Document

Use the following dictionary functions to modify existing dictionary documents:

- `spell:add-word` / `spell.addWord`
- `spell:remove-word` / `spell.removeWord`

The `spell:insert` XQuery function or the `spell.insert` JavaScript function will overwrite an existing dictionary if you specify an existing dictionary document (as well as creates a new one if one does not exist at the specified URI).

> **Note:** The transactional unit in MarkLogic Server is a query; therefore, if you are performing multiple updates to the same dictionary document, be sure to perform those updates as part of separate queries. In XQuery, you can place a semi-colon between the update statements to start a new query (and therefore a new transaction). If you use a semicolon to start any new queries that uses spelling correction functions in XQuery, each query must include the `import` statement in the prolog to resolve the spelling module.

The following topics are about updating dictionary documents:

- Example: Adding a New Word to a Dictionary in XQuery
- Example: Adding a New Word to a Dictionary in JavaScript
- Example: Removing a Word From a Dictionary in XQuery
- Example: Removing a Word From a Dictionary in JavaScript

24.5.4.1 Example: Adding a New Word to a Dictionary in XQuery

The following XQuery uses the `spell:add-word` function to add an entry for *albatross* to the dictionary with URI `/mySpell/Spell.xml`:

```
xquery version "1.0-ml";
import module "http://marklogic.com/xdmp/spell" at
              "/MarkLogic/spell.xqy";

spell:add-word("/mySpell/spell.xml", "albatross")
```

If the `/mySpell/spell.xml` dictionary has an identical entry, there will be no change to the dictionary. Otherwise, an entry for *albatross* is added to the dictionary.

24.5.4.2 Example: Adding a New Word to a Dictionary in JavaScript

The following JavaScript program uses the `spell.addWord` function to add an entry for *albatross* to the dictionary with URI `/mySpell/Spell.json`:

```
var spell = require("/MarkLogic/spell.xqy");
declareUpdate();

spell.addWord("/mySpell/spell.json", "albatross");
```

If the `/mySpell/spell.json` dictionary has an identical entry, there will be no change to the dictionary. Otherwise, an entry for *albatross* is added to the dictionary.

24.5.4.3 Example: Removing a Word From a Dictionary in XQuery

The following XQuery uses the `spell:remove-word` function to remove the entry for *albatross* dictionary with URI `/mySpell/Spell.xml`:

```
xquery version "1.0-ml";
import module "http://marklogic.com/xdmp/spell" at
              "/MarkLogic/spell.xqy";

spell:remove-word("/mySpell/spell.xml", "albatross")
```

This removes the word *albatross* from the `/mySpell/spell.xml` dictionary document.

24.5.4.4 Example: Removing a Word From a Dictionary in JavaScript

The following JavaScript program uses the `spell.removeWord` function to remove the entry for *albatross* dictionary with URI `/mySpell/Spell.json`:

```
var spell = require("/MarkLogic/spell.xqy");
declareUpdate();

spell.removeWord("/mySpell/spell.json", "albatross")
```

This removes the word *albatross* from the `/mySpell/spell.json` dictionary document.

24.5.5 Security Considerations With Dictionary Documents

Dictionary documents are stored in XML or JSON format in the database. Therefore, they can be queried just like any other document. Note the following about security and dictionary documents:

- By default, dictionary documents are loaded into the following collections:
  - `http://marklogic.com/xdmp/documents`
  - `http://marklogic.com/xdmp/spell`
- Dictionary documents are loaded with the default permissions of the user who loads them. Make sure users who load dictionary documents have appropriate privileges, otherwise the documents might not have the needed permissions for reading and updating. For more information, see Setting Document Permissions in the *Loading Content Into MarkLogic Server Guide*.
- If you want to control access (read and/or write) to dictionary documents beyond the default permissions with which the documents are loaded, perform an `xdmp:document-set-permissions` (JavaScript `xdmp.documentSetPermissions`) after a `spell:load` / `spell.load` operation.

24.6 Testing if a Word is Spelled Correctly

You can use the `spell:is-correct` XQuery function or the `spell.isCorrect` JavaScript function to see if a word is spelled correctly (according to the specified dictionary). Consider the following XQuery statement:

```
spell:is-correct("/mySpell/spell.xml", "alphabet")
```

This returns true because the word alphabet is spelled correctly. The following is the equivalent in JavaScript:

```
spell.isCorrect("/mySpell/spell.xml", "alphabet");
```

Now consider the following XQuery statement:

```
spell:is-correct("/mySpell/spell.xml", "alfabet")
```

This returns `false` because the word *alfabet* is not spelled correctly. The following is the equivalent in JavaScript:

```
spell.isCorrect("/mySpell/spell.xml", "alfabet");
```

24.7 Getting Spelling Suggestions for Incorrectly Spelled Words

You can write a query which returns spelling suggestions based on words in the specified dictionary. Consider the following XQuery statement:

```
spell:suggest("/mySpell/spell.xml", "alfabet")
```

Or the equivalent JavaScript program:

```
spell.suggest("/mySpell/spell.xml", "alfabet");
```

This returns the following results:

```
alphabet albeit alphabets aloft abet alphabeted affable alphabet's
alphabetic offbeat
```

The results are ranked in the order, where the first word is the one most likely to be the real spelling. Your application can then prompt the user if one of the suggested words was the actual word intended.

Now consider the following XQuery statement:

```
spell:suggest("/mySpell/spell.xml", "alphabet")
```

Or the equivalent JavaScript program:

```
spell.suggest("/mySpell/spell.xml", "alphabet");
```

This returns the empty sequence, indicating that the word is spelled correctly.

Note: The spelling correction functions only provide suggestions for words that are less than 64 characters in length, and the functions only return suggestions that are less than 64 characters.

25.0 Distinctive Terms and cts:similar-query

MarkLogic Server includes `cts:similar-query` and `cts:distinctive-terms`. With these search APIs, you can find what is distinctive about nodes, typically from search results, from a search perspective. This chapter describes `cts:similar-query` and `cts:distinctive-terms`, and includes the following sections:

- Understanding cts:similar-query
- Finding the Distinctive Terms of a Set of Nodes
- Understanding the cts:distinctive-terms Output
- Example Design Pattern: Making a Tag Cloud

25.1 Understanding cts:similar-query

You can use `cts:similar-query` to find nodes that are similar, from a search perspecitve, to the model nodes that you pass into the first parameter. The `cts:similar-query` constructor is a `cts:query` constructor, and you can combine it with other `cts:query` constructors as described in "Composing cts:query Expressions" on page 240.

Instead of looking in the indexes to find the terms that match the query, like other `cts:query` constructors, `cts:similar-query` takes the nodes passed in, runs them through an indexing process, and returns a `cts:query` that would match the model nodes with a high degree of relevance. You can pass various index and score options into `cts:similar-query` to influence the `cts:query` that it produces.

The query that it generates finds distinctive terms of the model nodes *based on the other documents in the database*.

25.2 Finding the Distinctive Terms of a Set of Nodes

If you want to find the terms that `cts:similar-query` uses to generate its `cts:query`, you can use `cts:distinctive-terms`. The output of `cts:distinctive-terms` is a `cts:class` element with several `cts:term` children. Each `cts:term` element contains a cts:query constructor, representing a term. Each `cts:term` element also contains scores and confidence for that term. MarkLogic Server uses these scores in calculating relevance.

You can pass many different options into `cts:distinctive-terms` to control which terms it generates. The database options control which terms will be most "relevant" to the model nodes, and therefore affect the `cts:distinctive-terms` output. If you take an iterative approach, you can try different indexing options to see which ones give the best results for your model nodes.

The distinctive terms generated or distinctive based on the other documents in the database, therfore, you will get much better results running this against a sizable database.

25.3 Understanding the cts:distinctive-terms Output

The following shows a simple `cts:distinctive-terms` query with its output:

```
let $node := doc("/shakespeare/plays/hamlet.xml")
return cts:distinctive-terms($node,
   <options xmlns="cts:distinctive-terms"
         xmlns:db="http://marklogic.com/xdmp/database">
    <use-db-config>false</use-db-config>
    <max-terms>3</max-terms>
    <db:word-searches>false</db:word-searches>
    <db:stemmed-searches>basic</db:stemmed-searches>
    <db:fast-phrase-searches>false</db:fast-phrase-searches>
    <db:fast-element-word-searches>false</db:fast-element-word-searches>
    <db:fast-element-phrase-searches>false</db:fast-element-phrase-searches>
   </options>)
=>
<cts:class name="dterms /shakespeare/plays/hamlet.xml" offset="0"
xmlns:cts="http://marklogic.com/cts">
  <cts:term id="7783238741996929314" val="981" score="981"
confidence="0.811494" fitness="1">
    <cts:word-query>
      <cts:text xml:lang="en">guildenstern</cts:text>
      <cts:option>case-insensitive</cts:option>
      <cts:option>diacritic-insensitive</cts:option>
      <cts:option>stemmed</cts:option>
      <cts:option>unwildcarded</cts:option>
    </cts:word-query>
  </cts:term>
  <cts:term id="4731147985682913359" val="956" score="956"
confidence="0.801087" fitness="1">
    <cts:word-query>
      <cts:text xml:lang="en">polonius</cts:text>
      <cts:option>case-insensitive</cts:option>
      <cts:option>diacritic-insensitive</cts:option>
      <cts:option>stemmed</cts:option>
      <cts:option>unwildcarded</cts:option>
    </cts:word-query>
  </cts:term>
  <cts:term id="1100490632300558572" val="949" score="949"
confidence="0.798149" fitness="1">
    <cts:word-query>
      <cts:text xml:lang="en">horatio</cts:text>
      <cts:option>case-insensitive</cts:option>
      <cts:option>diacritic-insensitive</cts:option>
      <cts:option>stemmed</cts:option>
      <cts:option>unwildcarded</cts:option>
    </cts:word-query>
  </cts:term>
</cts:class>
```

The output is a `cts:class` element, and each child is a `cts:term` element. The `cts:term` elements represent terms in a database, identified by a `cts:query`. Each term has numbers for `val`, `score`, `confidence`, and `fitness`.

The `val` and `score` attributes are values that approximate the score contribution of that term. The `confidence` attribute represents the `cts:confidence` value for the term. The `fitness` attribute represents the `cts:fitness` value for the term. For details on score, fitness, and confidence, see "Relevance Scores: Understanding and Customizing" on page 408.

The previous query only consider word-query terms. You can also have `cts:element-word-query` terms and `cts:near-query` terms for terms that are within an element or that are a word pair (a `cts:near-query` with a `distance` of 1). To see some of these kind of terms, try running a query like the following:

```
let $node := doc("/shakespeare/plays/hamlet.xml")
return cts:distinctive-terms($node,
   <options xmlns="cts:distinctive-terms"
         xmlns:db="http://marklogic.com/xdmp/database">
    <use-db-config>false</use-db-config>
    <max-terms>100</max-terms>
    <db:word-searches>false</db:word-searches>
    <db:stemmed-searches>basic</db:stemmed-searches>
    <db:fast-phrase-searches>true</db:fast-phrase-searches>
    <db:fast-element-word-searches>true</db:fast-element-word-searches>
    <db:fast-element-phrase-searches>true</db:fast-element-phrase-searches>
   </options>)
```

This query enables the `db:fast-element-word-searches` and `db:fast-element-phrase-searches` options, which will cause terms to appear in the output that are constrained to a particular element. Changing the database options to `cts:distictive-terms` and looking at the differences in the output will help you to understand both how the index options affect which terms are distinctive and, since `cts:similar-query` can use these same settings, how `cts:similar-query` decides if a document is "similar" to the model nodes.

25.4 Example Design Pattern: Making a Tag Cloud

Tag clouds are a popular visualization that show various terms, usually relevant to a search, and show the more relevant ones in a larger and/or more colorful font. You can use `cts:distinctive-terms` feed the data used to make a tag cloud. The basic design pattern is as follows:

- Experiment with options to create a `cts:distinctive-terms` query that produces results you are happy with.
- Set a `max-terms` size that is equal to the number of terms you want in your tag cloud.
- Come up with some algorithm to convert score (or fitness) into font size. For example, you might want to take the fitness and multiply it by 20 to get a font size.

- Use the above algorithm to iterate through your results and generate some html that creates a tag cloud.

The following sample code is a simplied example of this design pattern:

```
xquery version "1.0-ml";

let $hits :=
  let $terms :=
   let $node := doc("/shakespeare/plays/hamlet.xml")//LINE
   return cts:distinctive-terms($node,
   <options xmlns="cts:distinctive-terms"
         xmlns:db="http://marklogic.com/xdmp/database">
    <use-db-config>false</use-db-config>
    <max-terms>100</max-terms>
    <db:word-searches>false</db:word-searches>
    <db:stemmed-searches>basic</db:stemmed-searches>
    <db:fast-phrase-searches>false</db:fast-phrase-searches>
    <db:fast-element-word-searches>false</db:fast-element-word-searches>
    <db:fast-element-phrase-searches>false</db:fast-element-phrase-searches>
   </options>)//cts:term
  for $wq in $terms
  where $wq/cts:word-query
  return element word {
           attribute score {
             fn:round(($wq/@val div 20))},
           $wq/cts:word-query/cts:text/string() }
return <p>{
for $hit in $hits
order by $hit/string()
return (
<span style="{fn:concat("font-size: ",
          $hit/@score)}">{$hit/string()}
</span>, " " ) }</p>
```

The above query returns html which, when displayed in a browser, shows the 100 most distinctive with the most “relevant” terms in a larger font.

26.0 Training the Classifier

MarkLogic Server includes an XML support vector machine (SVM) classifier. This chapter describes the classifier and how to use it on your content, and includes the following sections:

- Understanding How Training and Classification Works
- Classifier API
- Leveraging XML With the Classifier
- Creating a Training Set
- Methodology For Determining Thresholds For Each Class
- Example: Training and Running the Classifier

26.1 Understanding How Training and Classification Works

The *classifier* is a set of APIs that allow you to define *classes*, or categories of nodes. By running samples of classes through the classifier to train it on what constitutes a given class, you can then run that trained classifier on unknown documents or nodes to determine to which classes each belongs. The process of classification uses the full-text indexing capabilities of MarkLogic Server, as well as its XML-awareness, to perform statistical analysis of terms in the training content to determine class membership. This section describes the concepts behind the classifier and includes the following parts:

- Training and Classification
- XML SVM Classifier
- Hyper-Planes and Thresholds for Classes
- Training Content for the Classifier

26.1.1 Training and Classification

There are two basic steps to using the classifier: training and classification. *Training* is the process of taking content that is known to belong to specified classes and creating a classifier on the basis of that known content. *Classification* is the process of taking a classifier built with such a training content set and running it on unknown content to determine class membership for the unknown content. Training is an iterative process whereby you build the best classifier possible, and classification is a one-time process designed to run on unknown content.

26.1.2 XML SVM Classifier

The MarkLogic Server classifier implements a support vector machine (SVM). An SVM classifier uses a well-known algorithm to determine membership in a given class, based on training data. For background on the mathematics behind support vector machine (SVM) classifiers, try doing a web search for `svm classifier`, or start by looking at the information on Wikipedia.

The basic idea is that the classifier takes a set of training content representing known examples of classes and, by performing statistical analysis of the training content, uses the knowledge gleaned from the training content to decide to which classes other unknown content belongs. You can use the classifier to gain knowledge about your content based on the statistical analysis performed during training.

Traditional SVM classifiers perform the statistical analysis using term frequency as input to the support vector machine calculations. The MarkLogic XML SVM classifier takes advantage of MarkLogic Server's XML-aware full-text indexing capabilities, so the terms that act as input to the classifier can include content (for example, words), structure information (for example, elements), or a combination of content and structure (for example, element-word relationships). All of the MarkLogic Server index options that affect terms are available as options in the classifier API, so you can use a wide variety of indexing techniques to tune the classifier to work the best for your sample content.

First you define your classes on a set of training content, and then the classifier uses those classes to analyze other content and determine its classification. When the classifier analyzes the content, there are two sometimes conflicting measurements it uses to help determine if the information in the new content belongs in or out of a class:

- *Precision*: The probability that what is classified as being in a class is actually in that class. High precision might come at the expense of missing some results whose terms resemble those of other results in other classes.
- *Recall*: The probability that an item actually in a class is classified as being in that class. High recall might come at the expense of including results from other classes whose terms resemble those of results in the target class.

When you are tuning your classifier, you need to find a balance between high precision and high recall. That balance depends on what your application goals and requirements are. For example, if you are trying to find trends in your content, then high precision is probably more important; you want to ensure that your analysis does not include irrelevant nodes. If you need to identify every instance of some classification, however, you probably need a high recall, as missing any members would go against your application goals. For most applications, you probably need somewhere in between. The process of training your classifier is where you determine the optimal values (based on your training content set) to make the trade-offs that make sense to your application.

26.1.3 Hyper-Planes and Thresholds for Classes


There are two main things that the computations behind the XML SVM classifier do:

- Determine the boundaries between each class. This is done during training.
- Determine the threshold for which the boundaries return the most distinctive results when determining class membership.


There can be any number of classes. A *term vector* is a representation of all of the terms (as defined by the index options) in a node. Therefore, classes consist of sets of term vectors which have been deemed similar enough to belong to the same class.

Imagine for a moment that each term forms a dimension. It is easy to visualize what a 2-dimensional picture of a class looks like (imagine an x-y graph) or even a 3-dimensional picture (imagine a room with height, width, and length). It becomes difficult, however, to visualize what the picture of these dimensions looks like when there are more than three dimensions. That is where *hyper-planes* become a useful concept.

Before going deeper into the concept of hyper-planes, consider a content set with two classes, one that are squares and one that are triangles. In the following figures, each square or triangle represents a term vector that is a member of either the square or triangle class, respectively.




Now try to draw a line to separate the triangles from the squares. In this case, you can draw such a line that nicely divides the two classes as follows:




If this were three dimensions, instead of a line between the classes it would be a *plane* between the classes. When the number of dimensions grows beyond three, the extension of the plane is called a *hyper-plane*; it is the generalized representation of a boundary of a class (sometimes called the edge of a class).

The previous examples are somewhat simplified; they are set up such that the hyper-planes can be drawn such that one class is completely on one side and the other is completely on the other. For most real-world content, there are members of each class on the other side of the boundaries as follows:




In these cases, you can draw other lines parallel to the boundaries (or in the *n*-dimensional cases, other hyper-planes). These other lines represent the *thresholds* for the classes. The distance between the boundary line and the threshold line represents the threshold value, which is a negative number indicating how far the outlier members of the class are from the class boundary. The following figure represents these thresholds.



The dotted lines represent some possible thresholds. The lines closer to the boundary represent thresholds with higher precision (but not complete precision), while the lines farther from the boundaries represent higher recall. For members of the triangle class that are on the other side of the square class boundaries, those members are not in the class, but if they are within the threshold you choose, then they are considered part of the class.

One of the classifier APIs (`cts:thresholds`) helps you find the right thresholds for your training content set so you can get the right balance between precision and recall when you run unknown content against the classifier to determin class membership.

The following figure shows the triangle class boundary, including the precision and recall calculations based on a threshold (the triangle class is below the threshold line):



Triangle Precision = 16/25 = .64
Triangle Recall = 16/17 = .94

26.1.4 Training Content for the Classifier

To find the best thresholds for your content, you need to *train* the classifier with sample content that represents members of all of the classes. It is very important to find good training samples, as the quality of the training will directly impact the quality of your classification.

The samples for each class should be statistically relevant, and should have samples that include both solid examples of the class (that is, samples that fall well into the positive side of the threshold from the class boundary) and samples that are close to the boundary for the class. The samples close to the boundary are very important, because they help determine the best thresholds for your content. For more details about training sets and setting the threshold, see "Creating a Training Set" on page 577 and "Methodology For Determining Thresholds For Each Class" on page 579.

26.2 Classifier API

The classifier has three XQuery built-in functions. This section gives an overview and explains some of the features of the API, and includes the following parts:

- XQuery Built-In Functions
- Data Can Reside Anywhere or Be Constructed
- API is Extremely Tunable
- Supports Versus Weights Classifiers
- Kernels (Mapping Functions)
- Find Thresholds That Balance Precision and Recall

For details about the syntax and usage of the classifier API, see the *MarkLogic XQuery and XSLT Function Reference*.

26.2.1 XQuery Built-In Functions

The classifier API includes three XQuery functions:

- `cts:classify`
- `cts:thresholds`
- `cts:train`

You use these functions to take training nodes use them to compute classifiers. Creating a classifier specification is an iterative process whereby you create training content, train the classifier (using `cts:train`) with the training content, test your classifier on some other training content (using `cts:classify`), compute the thresholds on the training content (using `cts:threshold`), and repeat this process until you are satisfied with the results. For details about the syntax and usage of the classifier API, see the *MarkLogic XQuery and XSLT Function Reference*.

26.2.2 Data Can Reside Anywhere or Be Constructed

The classifier APIs take nodes and elements, so you can either use XQuery to construct the data for the nodes you are classifying or training, or you can store them in the database (or somewhere else), whichever is more convenient. Because the APIs take nodes as parameters, there is a lot of flexibility in how you store your training and classification data.

> **Note:** There is an exception to this: if you are using the `supports` form of the classifier, then the training data must reside in the database, and you must pass in the training nodes when you perform classification (that is, when you run `cts:classify`) on unknown content.

26.2.3 API is Extremely Tunable

The classifier API has many options, and is therefore extremely tunable. You can choose the different index options and kernel types for `cts:train`, as well as specify limits and thresholds. When you change the kernel type for `cts:train`, it will effect the results you get from classification, as well as effect the performance. Because classification is an iterative process, experimentation with your own content set tends to help get better results from the classifier. You might change some parameters during different iterations and see which gives the better classification for your content.

The following section describes the differences between the supports and weights forms of the classifier. For details on what each option of the classifier does, see the *MarkLogic XQuery and XSLT Function Reference*.

26.2.4 Supports Versus Weights Classifiers

There are two forms of the classifier:

- `supports`: allows the use of some of the more sophisticated kernels. It encodes the classifier by reference to specific documents in the training set, and is therefore more accurate because the whole training document can be used for classification; however, that means that the whole training set must be available during classification, and it must be stored in the database. Furthermore, since constructing a term vector is exactly equivalent to indexing, each time the classifier is invoked it regenerates the index terms for the whole training set. On the other hand, the actual representation of the classifier (the XML returned from `cts:train`) may be a lot more compact. The other advantage of the `supports` form of the classifier is that it can give you error estimates for specific training documents, which may be a sign that those are misclassified or that other parameters are not set to optimal values.
- `weights`: encodes weights for each of the terms. For mathematical reasons, it cannot be used with the Gaussian or Geodesic kernels, although for many problems, those kernels give the best results. Since there will not be a weight for every term in training set (because of term compression), this form of the classifier is intrinsically less precise. If there are a lot of classes and a lot of terms, the classifier representation itself can get quite large. However, there is no need to have the training set on hand during classification, nor

to construct term vectors from it (in essence to regenerate the index terms), so `cts:classify` runs much faster with the `weights` form of the classifier.

Which one you choose depends on your answers to several questions and criteria, such as performance (does the `supports` form take too much time and resources for your data?), accuracy (are you happy with the results you get with the `weights` form with your data?), and other factors you might encounter while experimenting with the different forms. In general, the classifier is extremely tunable, and getting the best results for your data will be an iterative process, both on what you use for training data and what options you use in your classification.

26.2.5 Kernels (Mapping Functions)

You can choose different kernels during the training phase. The kernels are mapping functions, and they are used to determine the distance of a term vector from the edge of the class. For a description of each of the kernel mapping functions, see the documentation for `cts:train` in the *MarkLogic XQuery and XSLT Function Reference*.

26.2.6 Find Thresholds That Balance Precision and Recall

As part of the iterative nature of training to create a classifier specification, one of the overriding goals is to find the best threshold values for your classes and your content set. Ideally, you want to find thresholds that strike a balance between good precision and good recall (for details on precision and recall, see "XML SVM Classifier" on page 570). You use the `cts:thresholds` function to calculate the thresholds based on a training set. For an overview of the iterative process of finding the right thresholds, see "Methodology For Determining Thresholds For Each Class" on page 579.

26.3 Leveraging XML With the Classifier

Because the classifier operates from an XQuery context, and because it is built into MarkLogic Server, it is intrinsically XML-aware. This has many advantages. You can choose to classify based on a particular element or element hierarchy (or even a more complicated XML construct), and then use that classifier against either other like elements or element hierarchies, or even against a totally different set of element or element hierarchies. You can perform XML-based searches to find the best training data. If you have built XML structure into your content, you can leverage that structure with the classifier.

For example, if you have a set of articles that you want to classify, you can classify against only the `<executive-summary>` section of the articles, which can help to exclude references to other content sections, and which might have a more universal style and language than the more detailed sections of the articles. This approach might result in using terms that are highly relevant to the topic of each article for determining class membership.

26.4 Creating a Training Set

This section describes the training content set you use to create a classifier, and includes the following parts:

- Importance of the Training Set
- Defining Labels for the Training Set

26.4.1 Importance of the Training Set

The quality of your classification can only be as good as the training set you use to run the classifier. It is extremely important to choose sample training nodes that not only represent obvious examples of a class, but also samples which represent edge cases that belong in or out of a class.

Because the process of classification is about determining the edges of the classes, having good samples that are close to this edge is important. You cannot always determine what constitutes an edge sample, though, by examining the training sample. It is therefore good practice to get as many different kinds of samples in the training set as possible.

As part of the process of training the classifier, you might need to add more samples, verify that the samples are actually good samples, or even take some samples away (if they turn out to be poor samples) from some classes. Also, you can specify negative samples for a class. It is an iterative process of finding the right training data and setting the various training options until you end up with a classifier that works well for your data.

26.4.2 Defining Labels for the Training Set

The second parameter to `cts:train` is a label specification, which is a sequence of `cts:label` elements, each one having a one `cts:class` child. Each `cts:label` element represents a node in the training set. The `cts:label` elements must be in the order corresponding to the specified training nodes, and they each specify to which class the corresponding training node belongs. For example, the following `cts:label` nodes specifies that the first training node is in the class `comedy`, the second in the class `tragedy`, and the third in the class `history`:

```
<cts:label>
  <cts:class name="comedy"/>
</cts:label>
<cts:label>
  <cts:class name="tragedy"/>
</cts:label>
<cts:label>
  <cts:class name="history"/>
</cts:label>
```

Because the labels must be in the order corresponding to the training nodes, you might find it convenient to generate the labels from the training nodes. For example, the following code extracts the class name for the labels from a property names `playtype` stored in the property corresponding to the training nodes:

```
for $play in xdmp:directory("/plays/", "1")
return
  <cts:label>
```

```
    <cts:class name={
      xdmp:document-property(xdmp:node-uri($play))//playtype/text()}/>
  </cts:label>
```

If you have training samples that represent negative samples for a class (that is, they are examples of what does *not* belong in the class), you can label them such by specifying the `val="-1"` attribute on the `cts:class` element as follows:

```
<cts:class name="comedy" val="-1"/>
```

Additionally, you can include multiple classes in a label (because membership in one class is independent of membership in another). For example:

```
<cts:label>
  <cts:class name="comedy" val="-1"/>
  <cts:class name="tragedy"/>
  <cts:class name="history"/>
</cts:label>
```

26.5 Methodology For Determining Thresholds For Each Class

Use the following methodology to determine appropriate per-class thresholds for classification:

1. Partition the training set into two parts. Ideally, the partitions should be statistically equal. One way to achieve this is to randomize which nodes go into one partition and which go into the other.

2. Run `cts:train` on the first half of the training set.

3. Run `cts:classify` on the second half of the training set with the output of `cts:train` from the first half in the previous step. This is to validate that the training data you used produced good classification. Use the default value for the `thresholds` option for this run. The default value is a very large negative number, so this run will measure the distance from the actual class boundary for each node in the training set.


4. Run `cts:thresholds` to compute thresholds for the second half of the training set. This will further validate your training data and the parameters you set when running `cts:train` on your training data.

5. Iterate through the previous steps until you are satisfied with the results from your training content (that is, you until you are satisfied with the classifier you create). You might need to experiment with the various option settings for `cts:train` (for example, different kernels, different index settings, and so on) until you get the classification you desire.

6. After you are satisfied that you are getting good results, run `cts:classify` on the unknown documents, using the computed thresholds (the values from `cts:thresholds`) as the boundaries for deciding on class membership.

Note: Any time you pass thresholds to `cts:train`, the thresholds apply to `cts:classify`. You can pass them either with `cts:train` or `cts:classify`, though, and the effect is the same.

The following diagram illustrates this iterative process:



26.6 Example: Training and Running the Classifier

This section describes the steps needed to train the classifier against a content set of the plays of William Shakespeare. This is meant is a simple example for illustrating how to use the classifier, not necessarily as an example of the best results you can get out of the classifier. The steps are divided into the following parts:

- Shakespeare's Plays: The Training Set
- Comedy, Tragedy, History: The Classes
- Partition the Training Content Set
- Create Labels on the First Half of the Training Content
- Run cts:train on the First Half of the Training Content

- Run cts:classify on the Second Half of the Content Set
- Use cts:thresholds to Compute the Thresholds on the Second Half
- Evaluating Your Results, Make Changes, and Run Another Iteration
- Run the Classifier on Other Content

26.6.1 Shakespeare's Plays: The Training Set

When you are creating a classifier, the first step is to choose some training content. In this example, we will use the plays of William Shakespeare as the training set from which to create a classifier.

The Shakespeare plays are available in XML at the following URL (subject to the copyright restrictions stated in the plays):

http://www.oasis-open.org/cover/bosakShakespeare200.html

This example assumes the plays are loaded into a MarkLogic Server database under the directory `/shakespeare/plays/`. There are 37 plays.

26.6.2 Comedy, Tragedy, History: The Classes

After deciding on the training set, the next step is to choose classes in which you divide the set, as well as choosing labels for those classes. For Shakespeare, the classes are `COMEDY`, `TRAGEDY`, and `HISTORY`. You must decide which plays belong to each class. To determine which Shakespeare plays are comedies, tragedies, and histories, consult your favorite Shakespeare scholars (there is reasonable, but not complete agreement about which plays belong in which classes).

For convenience, we will store the classes in the properties document at each play URI. To create the properties for each document, perform something similar to the following for each play (inserting the appropriate class as the property value):

```
xdmp:document-set-properties("/shakespeare/plays/hamlet.xml",
      <playtype>TRAGEDY</playtype>)
```

For details on properties in MarkLogic Server, see Properties Documents and Directories in the *Application Developer's Guide*.

26.6.3 Partition the Training Content Set

Next, we will divide the training set into two parts, where we know the class of each node in both parts. We will use the first part to train and the second part to validate the classifier built from the first half of the training set. The two parts should be statistically random, and to do that we will simply take the first half in the order that the documents return from the `xdmp:directory` call. You can choose a more sophisticated randomization technique if you like.

26.6.4 Create Labels on the First Half of the Training Content

As we are taking the first half of the play for the training content, we will need labels for each node (in this example, we are using the document node for each play as the training nodes). To create the labels on the first half of the content, run a query statement similar to the following:

```
for $x in xdmp:directory("/shakespeare/plays/", "1")[1 to 19]
return
<cts:label>
  <cts:class name={xdmp:document-properties(xdmp:node-uri($x))
       //playtype/text()}/>
</cts:label>
```

Note: For simplicity, this example uses the first 19 items of the content set as the training nodes. The samples you use should use a statistically random sample of the content for the training set, so you might want to use a slightly more complicated method (that is, one that ensures randomness) for choosing the training set.

26.6.5 Run cts:train on the First Half of the Training Content

Next, you run `cts:train` with your training content and labels. The following code constructs the labels and runs `cts:train` to generate a classifier specification:

```
let $firsthalf := xdmp:directory("/shakespeare/plays/", "1")[1 to 19]
let $labels := for $x in $firsthalf
       return
       <cts:label>
         <cts:class name={xdmp:document-properties(xdmp:node-uri($x))
                //playtype/text()}/>
       </cts:label>
return
cts:train($firsthalf, $labels,
       <options xmlns="cts:train">
         <classifier-type>supports</classifier-type>
       </options>)
```

You can either save the generated classifier specification in a document in the database or run this code dynamically in the next step.

26.6.6 Run cts:classify on the Second Half of the Content Set

Next, you take the classifier specification created with the first half of the training set and run `cts:classify` on the second half of the content set, as follows:

```
let $firsthalf := xdmp:directory("/shakespeare/plays/", "1")[1 to 19]
let $secondhalf := xdmp:directory("/shakespeare/plays/", "1")[20 to 37]
let $classifier :=
  let $labels := for $x in $firsthalf
        return
        <cts:label>
          <cts:class name={xdmp:document-properties(xdmp:node-uri($x))
                           //playtype/text()}/>
        </cts:label>
  return
  cts:train($firsthalf, $labels,
      <options xmlns="cts:train">
        <classifier-type>supports</classifier-type>
      </options>)
return
cts:classify($secondhalf, $classifier,
      <options xmlns="cts:classify"/>,
      $firsthalf)
```

26.6.7 Use cts:thresholds to Compute the Thresholds on the Second Half

Next, calculate `cts:label` elements for the second half of the content and use it to compute the thresholds to use with the classifier. The following code runs `cts:train` and `cts:classify` again for clarity, although the output of each could be stored in a document.

```
let $firsthalf := xdmp:directory("/shakespeare/plays/", "1")[1 to 19]
let $secondhalf := xdmp:directory("/shakespeare/plays/", "1")[20 to 37]
let $firstlabels := for $x in $firsthalf
        return
        <cts:label>
          <cts:class name={xdmp:document-properties(xdmp:node-uri($x))
                                    //playtype/text()}/>
        </cts:label>
let $secondlabels := for $x in $secondhalf
        return
        <cts:label>
          <cts:class name={xdmp:document-properties(xdmp:node-uri($x))
                                    //playtype/text()}/>
        </cts:label>
let $classifier :=
    cts:train($firsthalf, $firstlabels,
      <options xmlns="cts:train">
        <classifier-type>supports</classifier-type>
      </options>)
let $classifysecond :=
  cts:classify($secondhalf, $classifier,
        <options xmlns="cts:classify"/>,
        $firsthalf)
return
cts:thresholds($classifysecond, $secondlabels)
```

This produces output similar to the following:

```
<thresholds xmlns="http://marklogic.com/cts">
  <class name="TRAGEDY" threshold="-0.00215207" precision="1"
         recall="0.666667" f="0.8" count="3"/>
  <class name="COMEDY" threshold="0.216902" precision="0.916667"
         recall="1" f="0.956522" count="11"/>
  <class name="HISTORY" threshold="0.567648" precision="1"
         recall="1" f="1" count="4"/>
</thresholds>
```

26.6.8 Evaluating Your Results, Make Changes, and Run Another Iteration

Finally, you can analyze the results from `cts:thresholds`. As an ideal, the thresholds should be zero. In practice, a negative number relatively close to zero makes a good threshold. The threshold for tragedy above is quite good, but the thresholds for the other classes are not quite as good. If you want the thresholds to be better, you can try running everything again with different parameters for the kernel, for the indexing options, and so on. Also, you can change your training data (to try and find better examples of comedy, for example).

26.6.9 Run the Classifier on Other Content

Once you are satisfied with your classifier, you can run it on other content. For example, you can try running it on SPEECH elements in the shakespeare plays, or try it on plays by other playwrights.

27.0 Results Clustering Using cts:cluster

MarkLogic Server includes `cts:cluster`, which uses statistical algorithms to find and label clusters of search results. This chapter describes `cts:cluster` and includes the following sections:

- Understanding cts:cluster
- Options to cts:cluster
- Understanding the cts:cluster Output
- Example that Creates an HTML Report of the Cluster

For details about the signature, the parameter syntax, and more examples, see `cts:cluster` in the *MarkLogic XQuery and XSLT Function Reference*.

27.1 Understanding cts:cluster

The `cts:cluster` function takes a set of nodes, typically from a search result set (although it can be any set of nodes), and provides a report that categorizes the result nodes in *clusters*. A *cluster* is a subset of the results that are statistically similar. For each cluster, it generates a label from the most distinctive terms in that cluster.

The output is an XML node, and you can use the output to generate a user interface that displays the results. For sample output, see “Understanding the cts:cluster Output” on page 588.

The clusterer creates clusters by taking the nodes you pass into `cts:cluster` and running it through the MarkLogic Server indexer. This is very similar to the process when you load a document into the database, but the indexing for results clustering is all done in memory, whereas in the database the indexes are stored to disk. The product of indexing is terms, with each term having a frequency (the number of times it occurs in the document and in the result set). Depending on which index settings you use, you will get a different set of terms. The clusterer takes into account each of the terms, as well as information about the terms (for example, weights and term frequency), to calculate the clusters.

You pass options into `cts:cluster` that determine the behavior of the cluster as well as specify the index settings to use when creating the clusters. For more information about the options, see “Options to cts:cluster” on page 587, as well as the API documentation for `cts:cluster` in the *MarkLogic XQuery and XSLT Function Reference*.

When deciding how to use the clusterer, think about what your requirements are. Many settings you choose in the clusterer are trade-offs between performance and the quality of the results clusters. You might need to experiment to find what works well for your application.

Note the following about the clusterer:

- Every time you cluster, the indexer is run on the supplied nodes to generate the data.
- The more nodes you send to `cts:cluster`, the longer it will take. For real time analysis, more than a few thousand might get too slow for a user to wait. Ideally, between 100 and 1000 nodes is a good balance between performance and good results.
- You can set `<hierarchical-levels>` to a value of greater than 1 to generate clusters of clusters. The parent `attribute` tells you which cluster is its parent. You can then iterate through the result set to create a user interface that shows the tree-like hierarchy.
- The labels might change from run-to-run. Specifying a higher value of `<num-tries>` tends to make the labels more consistent from run-to-run, but will increase the time it takes to produce the clusters.
- The labels come from the most distinctive terms. Some terms (such element terms) are turned into strings. If you want to see the terms used to create the labels, set the `<details>true</details>` option.

27.2 Options to cts:cluster

You can set options to `cts:cluster` in an options node. You can set the following types of options:

- Clustering (cts:cluster) Options
- Indexing (db:) Options

Each of these types of options is in its own namespace.

27.2.1 Clustering (cts:cluster) Options

The clustering options are in the `cts:cluster` namespace. These options determine the output and the behavior of the clusterer. Note the following about the clusterer options:

- When tuning the options, try to balance performance, accuracy, and quality of the results.
- The `<details>` option returns the distinctive terms (these are `cts` terms) used for each cluster. You can use these to try and construct your own labels by generating `cts:query` constructors from each term. You can then use those queries against some of your data to generate some labels, if that makes sense for your application.
- The `<algorithm>` option sets the algorithm MarkLogic Server uses to calculate the clusters: `k-means` or `lsi`. Both are statistical algorithms and have well-known and published papers describing them (to learn more, you can start here: http://en.wikipedia.org/wiki/K-means_clustering and http://en.wikipedia.org/wiki/Latent_semantic_indexing). The default is `k-means`, which tends to be slightly faster, but gives slightly less stable results than `lsi`.

- You can control the number of clusters using `<min-clusters>` and `<max-clusters>` settings. It is possible for `cts:cluster` to return less than the number of clusters in `<min-clusters>` if the most it can calculate based on your data is less than that value.
- The `<num-tries>` option specifies the number of times to run the clusterer against the specified data. The default is 1. Because of the way the algorithms work, running the cluster multiple times will increase the number of terms, and tends to improve the accuracy of the clusters. It does so at the cost of performance, as each time it runs, it has to do more work.

27.2.2 Indexing (db:) Options

The indexing options control which terms are created. MarkLogic Server uses these terms to calculate the clusters, based on term frequency, distinctive terms, and other factors relating to relevancy. Note the following about the `db` options:

- They are set in the options node, and are in the `http://marklogic.com/xdmp/database` namespace.
- The `cts:cluster` database options are the same as the database options for `cts:distinctive-terms`.
- You can construct the options by hand or use the Admin API to construct the options.
- Fields are a good way of indexing only the words you are interested in, and allows you to set weights for certain elements. For details on how fields work, see Fields Database Settings in the *Administrator's Guide*.
- The `<use-db-options>` `cts:cluster` option (in the `cts:cluster` namespace) takes the combination of the database options set in the context database, the specified database options, and any default values for options. This can be a convenient way for setting complicated options.
- Iterate with different options to get the right mix of performance and term choices.

27.3 Understanding the cts:cluster Output

The following shows sample `cts:cluster` output:

```
<clustering xmlns="http://marklogic.com/cts">
  <cluster id="15899142696064772767" label="law, his, hath" count="8" nodes="2
11 22 24 27 30 40 78"/>
  <cluster id="161987570467386344" label="earth, lose, hast" count="1"
nodes="28"/>
  <cluster id="14947979602052601851" label="mark, most, talbot" count="91"
nodes="1 3 4 5 6 7 8 9 10 12 13 14 15 16 17 18 19 20 21 23 25 26 29 31 32 33 34
35 36 37 38 39 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61
62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 79 80 81 82 83 84 85 86 87 88
89 90 91 92 93 94 95 96 97 98 99 100"/>
  <cluster id="143845517505877166" parent-id="15899142696064772767"
```

```
label="note, captain, antony" count="4" nodes="2 22 30 40"/>
  <cluster id="12625796822979427066" parent-id="15899142696064772767"
label="king, from, so" count="4" nodes="11 24 27 78"/>
  <cluster id="9134217245415181471" parent-id="14947979602052601851"
label="talbot, somerset, who" count="4" nodes="62 72 73 74"/>
  <cluster id="1248501351668626361" parent-id="14947979602052601851"
label="pompey, wall, cleopatra" count="44" nodes="1 4 5 6 12 13 14 19 33 34 37
39 41 42 45 46 47 48 49 50 51 53 54 55 56 58 60 61 64 65 68 71 75 77 84 87 88
89 92 95 96 97 98 99"/>
  <cluster id="6447791006134911106" parent-id="14947979602052601851"
label="our, voice, these" count="10" nodes="17 29 59 69 79 80 91 93 94 100"/>
  <cluster id="7874080124275500326" parent-id="14947979602052601851"
label="which, peace, blood" count="33" nodes="3 7 8 9 10 15 16 18 20 21 23 25
26 31 32 35 36 38 43 44 52 57 63 66 67 70 76 81 82 83 85 86 90"/>
  <options xmlns="cts:cluster" xmlns:db="http://marklogic.com/xdmp/database">
    <algorithm>k-means</algorithm>
    <db:word-searches>true</db:word-searches>
    <db:fast-phrase-searches>false</db:fast-phrase-searches>
    <db:fast-element-word-searches>true</db:fast-element-word-searches>
    <db:language>en</db:language>
    <max-clusters>10</max-clusters>
    <min-clusters>3</min-clusters>
    <hierarchical-levels>2</hierarchical-levels>
    <initialization>smart</initialization>
    <max-terms>200</max-terms>
    <label-max-terms>3</label-max-terms>
    <label-ignore-words>a as of s the when</label-ignore-words>
    <num-tries>1</num-tries>
    <score>logtfidf</score>
    <use-db-config>false</use-db-config>
    <details>false</details>
    <overlapping>false</overlapping>
  </options>
</clustering>
```

The output is a `cts:clustering` element. The output includes each cluster, as well as the options node used to create it. You can use XQuery or XSLT to iterate through the output, creating a report (for example, in HTML) of the results.

The attributes on the <cluster> element describe the cluster. The following table describes the attributes on the <cluster> element:

cluster Attribute	Description
id	A random number used to identify the cluster.
parent-id	The ID of the parent cluster, when <hierarchical-levels> is set to a value greater than 1.
label	The terms that comprise the label, comma separated. To make your own label, return the <details> and use the terms to generate a label.
count	The number of nodes in the cluster.
nodes	A set of NMTOKEN values, where each value lists the position of the node. The position is ordered by relevance, the first being the most relevant to the cluster and the last being the least relevant. The number refers to the position in the nodes input to cts:cluster. For example, a value of 10 indicates that it is the tenth node in the sequence passed into the first parameter of cts:cluster.

27.4 Example that Creates an HTML Report of the Cluster

The following example creates an HTML report of the cluster. It uses the Shakespeare plays database. To see the results, cut and paste the example and run it against a database that contains the Shakespeare plays (modify the URI of the directory used in the cts:search to the URI of the database directory in which you have loaded the Shakespeare plays).

```
xquery version "1.0-ml" ;

(: cluster the Shakespeare speeches, disregarding the speaker,
   and show the results in an html table :)

declare namespace db="http://marklogic.com/xdmp/database" ;
declare namespace cl="cts:cluster" ;
declare namespace dt="cts:distinctive-terms" ;

(: generally we want to cluster the top N results, where N is
   around 100 to 1,000 (smaller numbers for best performance).
   all speeches = 31,029;
   speeches that contain "love" = 1,864;
   "war" = 359; "joy" = 201;
   "beast" = 94;
   "aunt"=24
:)
let $search-term := xdmp:get-request-field("search-term", "aunt")
```

```
let $max-terms := xdmp:get-request-field("max-terms", "100")
let $use-db-config :=
  xdmp:get-request-field("use-db-config", "false")
let $algorithm := xdmp:get-request-field("algorithm", "k-means")
let $options-node :=
   <options xmlns="cts:cluster" >
      <hierarchical-levels>5</hierarchical-levels>
      <overlapping>false</overlapping>
      <label-max-terms>1</label-max-terms>
      <label-ignore-words>a of the when s as</label-ignore-words>
      <max-clusters>10</max-clusters>
      <algorithm>{ $algorithm }</algorithm>
     <!-- turn all database-level indexing options OFF - only use field
terms -->
      <db:word-searches>false</db:word-searches>
      <db:stemmed-searches>false</db:stemmed-searches>

<db:fast-case-sensitive-searches>false</db:fast-case-sensitive-searche
s>

<db:fast-diacritic-sensitive-searches>false</db:fast-diacritic-sensiti
ve-searches>
      <db:fast-phrase-searches>false</db:fast-phrase-searches>
      <db:phrase-throughs/>
      <db:phrase-arounds/>

<db:fast-element-word-searches>false</db:fast-element-word-searches>

<db:fast-element-phrase-searches>false</db:fast-element-phrase-searche
s>
      <db:element-word-query-throughs/>

<db:fast-element-character-searches>false</db:fast-element-character-s
earches>
      <db:range-element-indexes/>
      <db:range-element-attribute-indexes/>
      <db:one-character-searches>false</db:one-character-searches>
      <db:two-character-searches>false</db:two-character-searches>
      <db:three-character-searches>false</db:three-character-searches>

<db:trailing-wildcard-searches>false</db:trailing-wildcard-searches>

<db:fast-element-trailing-wildcard-searches>false</db:fast-element-tra
iling-wildcard-searches>
      <db:fields>
        <field xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://marklogic.com/xdmp/database">
          <field-name>speeches</field-name>
          <include-root>false</include-root>
          <word-lexicons/>
          <!-- create stem and phrase terms for this field -->
          <!-- if the XML were richer, we would have used
               fast-element-word-searches and
               fast-element-phrase-searches too -->
```

```
            <stemmed-searches>advanced</stemmed-searches>
            <db:fast-phrase-searches>true</db:fast-phrase-searches>
            <included-elements>
             <included-element>
               <namespace-uri/>
               <localname>LINE</localname>
               <weight>1.0</weight>
               <attribute-namespace-uri/>
               <attribute-localname/>
               <attribute-value/>
             </included-element>
             <included-element>
               <namespace-uri/>
               <localname>SPEECH</localname>
               <weight>1.0</weight>
               <attribute-namespace-uri/>
               <attribute-localname/>
               <attribute-value/>
             </included-element>
           </included-elements>
         <excluded-elements>
           <excluded-element>
             <namespace-uri/>
             <localname>SPEAKER</localname>
           </excluded-element>
          </excluded-elements>
         </field>
     </db:fields>
  </options>

(: build the page :)
let $page :=
<html>
<head><title>Example - clustering - speeches</title></head>
<body>
<table border="1" cellpadding="1" cellspacing="1">
<tr>
<th>Label</th>
<th>Count</th>
<th>Speakers</th>
</tr>
{
let $things-to-cluster :=
  cts:search(
     (: specify the directory in which you have loaded the plays :)
     xdmp:directory( "/shakespeare/plays/" )//SPEECH,
        $search-term
        )
(: iterate through the cts:cluster results node :)
for $cluster in
    cts:cluster( $things-to-cluster, $options-node )/cts:cluster
return
    <tr>
     <td>{ fn:data( $cluster/@label ) }</td>
```

```
      <td>{ fn:data( $cluster/@count ) }</td>
      <td>
        <table>{
 for $clustered-node-ref in fn:data( $cluster/@nodes )
 return
      <tr><td>{ fn:string(
        $things-to-cluster[$clustered-node-ref]//SPEAKER )
      }</td></tr>
        }</table>
       </td>
      </tr>}
</table>
</body>
</html>

return ( xdmp:set-response-content-type("text/html"),
 $page, xdmp:elapsed-time() )
```

28.0 Language Support in MarkLogic Server

MarkLogic Server supports loading and querying content in multiple languages. This chapter describes how languages are handled in MarkLogic Server, and includes the following sections:

- Overview of Language Support in MarkLogic Server
- Tokenization and Stemming
- Language Aspects of Loading and Updating Documents
- Querying Documents By Languages
- Supported Languages
- Generic Language Support

28.1 Overview of Language Support in MarkLogic Server

In MarkLogic Server, the language of the content is specified when you load the content and the language of the query is specified when you query the content. At load-time, the content is tokenized, indexed, and stemmed (if enabled) based on the language specified during the load. Also, MarkLogic Server uses any languages specified at the element level in the XML markup for the content (see "xml:lang Attribute" on page 598), making it possible to load documents with multiple languages. Similarly, at query time, search terms are tokenized (and stemmed) based on the language specified in the `cts:query` expression. The result is that a query performed in one language might not yield the same results as the same query performed in another language, as both the indexes that store the information about the content and the queries against the content are language-aware.

Even if your content is entirely in a single language, MarkLogic Server is still multiple-language aware. If your content is all in a single language, and if that language is the default language for that database, and if the content does not have any language (`xml:lang`) attributes, and if your queries all specify (or default to) the language in which the content is loaded, then everything will behave as if there is a single language.

Because MarkLogic Server is multiple-language aware, it is important to understand the fundamental aspects of languages when loading and querying content in MarkLogic Server. The remainder of this chapter, particularly "Language Aspects of Loading and Updating Documents" on page 598 and "Querying Documents By Languages" on page 600, describe these details.

28.2 Tokenization and Stemming

To understand the language implications of querying and loading documents, you must first understand tokenization and stemming, which are both language-specific. This section describes these topics, and has the following parts:

- Language-Specific Tokenization
- Stemmed Searches in Different Languages

28.2.1 Language-Specific Tokenization

When you search for a string (typically a word or a phrase) in MarkLogic Server, or when you load content (which is made up of text strings) into MarkLogic Server, the string is broken down to a set of parts, each of which is called a *token*. Each token is classified as a word, as punctuation, or as whitespace. The process of breaking down strings into tokens is called *tokenization*. Tokenization occurs during document loading as well as during query evaluation, and they are independent of each other.

Tokenization is language-specific; that is, a given string is tokenized differently depending on the language in which it is tokenized. The language is determined based on the language specified at load or query time (or the database default language if no language is specified) and on any `xml:lang` attributes in the content (for details, see "xml:lang Attribute" on page 598).

Note the following about the way strings are tokenized in MarkLogic Server:

- The `cts:tokenize` API will return how text is tokenized in the specified language.
- Using `xdmp:describe` of a `cts:tokenize` expression returns the tokens and the type of tokens produced from the specified string. For example:

```
xdmp:describe(cts:tokenize("this is, obviously, a phrase", "en"), 100)
=> (cts:word("this"), cts:space(" "), cts:word("is"),
   cts:punctuation(","), cts:space(" "), cts:word("obviously"),
   cts:punctuation(","), cts:space(" "), cts:word("a"),
   cts:space(" "), cts:word("phrase"))
```

- Every query has a language associated with it; if the language is not explicitly specified in the `cts:query` expression, then it takes on the default language of the database.

- MarkLogic Server comes configured such that when an element is in an Asian or Middle Eastern language, the Latin characters tokenize as English. This allows searches to find English words inside Asian or Middle Eastern language elements. For example, a search in English can find Latin characters in a Simplified Chinese element as in the following:

```
let $x := <el xml:lang="zh">Chinese-text-here hello</el>
return
$x//el[cts:contains(.,
         cts:word-query("hello", ("stemmed", "lang=en")))]

=> <el xml:lang="zh">Chinese-text-here hello</el>
```

  A stemmed search for the Latin characters in a non-English language, however, will not find the non-English word stems (it will only find the non-English word itself, which stems to itself). Similarly, Asian or Middle Eastern characters will tokenize in a language appropriate to the character set, even when they occur in elements that are not in their language. The result is that searches in English sometimes match content that is labeled in an Asian or Middle Eastern character set, and vice-versa. For example, consider the following (`zh` is the language code for Simplified Chinese):

```
let $x :=
<root>
 <el xml:lang="en">hello</el>
 <el xml:lang="fr">hello</el>
 <el xml:lang="zh">hello</el>
</root>
return
$x//el[cts:contains(.,
         cts:word-query("hello", ("stemmed", "lang=en")))]

=> <el xml:lang="en">hello</el>
   <el xml:lang="zh">hello</el>
```

  This search, even though in English, returns both the element in English and the one in Chinese. It returns the Chinese element because the word “hello” is in Latin characters and therefore tokenizes as English, and it matches the Chinese query (which also tokenizes “hello” in English).

- If your application has specialized tokenization requirements, you can use custom tokenizer overrides to modify how characters are grouped into tokens. For details, see “Custom Tokenization” on page 605.

28.2.2 Stemmed Searches in Different Languages

A *stemmed* search for a term matches all the terms that have the same stem as the search term (which includes the exact same terms in the language specified in the query). Words that are derived from the same meaning and part of speech have the same stem (for example, “mouse” and “mice”). Some words can have multiple stems (if the same word can be used as a different part of speech, or if there are two words with the same spelling), and if you use advanced stemming (which can find multiple stems for a word), then stemmed searches find all of the words having the same stem as any of the stems. The purpose of stemming is to increase the recall for a search. For details about how stemming works in MarkLogic Server, including the different stemming types of stemming available, see “Understanding and Using Stemmed Searches” on page 507. This sections describes how the language settings affect stemmed searches.

To get the stem of a search term, you must take the language into consideration. For example, the word “chat” is a different word in French than it is in English (in French, it is a noun meaning “cat”, in English, it is a verb meaning to converse informally). In French, “chatting” is not a word, and therefore it does not stem to “chat”. But in English, “chatting” does stem to “chat”. Therefore, stemming is language-specific, and stemmed searches in one language might find different results than stemmed searches in another.

At query time, you can specify a language (or if you do not specify a language, the default language of the database is used). This language is used when performing a stemmed search. The language specification is in the options to the `cts:query` expression. For example, the following `cts:query` expression specifies a stemmed search in French for the word “chat”, and it only matches tokens that are stemmed in French.

```
cts:word-query("chat", ("stemmed", "lang=fr"))
```

For more details about how languages affect queries, see “Querying Documents By Languages” on page 600.

At load time, the specified language is used to determine in which language to stem the words in the document. For more details about the language aspects of loading documents, see “Language Aspects of Loading and Updating Documents” on page 598.

For details about the syntax of the various `cts:query` constructors, see the *MarkLogic XQuery and XSLT Function Reference*.

28.3 Language Aspects of Loading and Updating Documents

This section describes the impact of languages on loading and updating documents, and includes the following sections:

- Tokenization and Stemming
- xml:lang Attribute
- Language-Related Notes About Loading and Updating Documents

28.3.1 Tokenization and Stemming

Tokenization and stemming occur when loading documents, just as they do when querying documents (for details, see "Language-Specific Tokenization" on page 595 and "Stemmed Searches in Different Languages" on page 597). When loading documents, the `stemmed search` indexes are created based on the language. The tokenization and stemming at load time is completely independent from the tokenization and stemming at query time.

28.3.2 xml:lang Attribute

You can specify languages in XML documents at the element level by using the `xml:lang` attribute. MarkLogic Server uses the `xml:lang` attribute to determine the language with which to tokenize and stem the contents of that element. Note the following about the `xml:lang` attribute:

- The `xml:lang` attribute (see http://www.w3.org/TR/2006/REC-xml-20060816/#sec-lang-tag) has some special properties such as not needing to declare the namespace bound to the `xml` prefix, and that it is inherited by all children of the element (unless they explicitly have a different `xml:lang` value).
- You can explicitly add an `xml:lang` attribute to the root node of a document during loading by specifying the `default-language` option to `xdmp:document-load`; without the `default-language` option, the root node will remain as-is.
- If no `xml:lang` attribute is present, then the document is processed in the default language of the database into which it is loaded.
- For the purpose of indexing terms, the language specified by the `xml:lang` attribute only applies to stemmed search terms; the `word searches` (unstemmed) database configuration setting indexes terms irrespective of language. Tokenization of terms honors the `xml:lang` value for both `stemmed searches` and `word searches` index settings in the database configuration.
- All of the text node children and text node descendants of an element with an `xml:lang` attribute are treated as the language specified in the `xml:lang` attribute, unless a child element has an `xml:lang` attribute with a different value. If so, any text node children and text node descendants are treated as the new language, and so on until no other `xml:lang` attributes are encountered.

- The value of the `xml:lang` attribute must conform to the following lexical standard: http://www.ietf.org/rfc/rfc3066.txt. The following are some typical `xml:lang` attributes (specifying French, Simplified Chinese, and English, respectively):

```
xml:lang="fr"
xml:lang="zh"
xml:lang="en"
```

- If an element has an `xml:lang` attribute with a value of the empty string (`xml:lang=""`), then any `xml:lang` value in effect (from some ancestor `xml:lang` value) is overridden for that element; its value takes on the database language default. Additionally, if a `default-language` option is specified during loading, any empty string `xml:lang` values are replaced with the language specified in the `default-language` option. For example, consider the following XML:

```
<rhone xml:lang="fr">
   <wine>vin rouge</wine>
   <wine xml:lang="">red wine</wine>
</rhone>
```

  In this sample, the phrase “vin rouge” is treated as French, and the phrase “red wine” is treated in the default language for the database (English by default).

  If this sample was loaded with a default-language option specifying Italian (specifying `<default-language>it</default-language>` for the `xdmp:document-load` option, for example), then the resulting document would be as follows:

```
<rhone xml:lang="fr">
   <wine>vin rouge</wine>
   <wine xml:lang="it">red wine</wine>
</rhone>
```

28.3.3 Language-Related Notes About Loading and Updating Documents

When you load content into MarkLogic Server, it determines how to index the content based on several factors, including the language specified during the load operation, the default language of the database, and any languages encoded into the content with `xml:lang` attributes. Note the following about languages with respect to loading content, updating content, and changing language settings on a database:

- Changing the default language starts a reindex operation if `reindex enable` is set to `true`.
- Documents with no `xml:lang` attribute are indexed upon load or update in the database default language.
- Any content within an element having an `xml:lang` attribute is indexed in that language. Additionally, the `xml:lang` value is inherited by all of the descendants of that element, until another `xml:lang` value is encountered.

- MarkLogic Server comes configured such that when an element is in an Asian or Middle Eastern language, the Latin characters tokenize as English. Therefore, a document with Latin characters in a non-English language will create stemmed index terms in English for those Latin characters. Similarly, Asian or Middle Eastern characters will tokenize in their respective languages, even in elements that are not in their language.

28.4 Querying Documents By Languages

Full-text search queries (queries that use `cts:search` or `cts:contains`) are language-aware; that is, they search for text, tokenize the search terms, and stem (if enabled) in a particular language. This section describes how queries are language-aware and describes their behavior. It includes the following topics:

- Tokenization, Stemming, and the xml:lang Attribute
- Language-Aware Searches
- Unstemmed Searches
- Unknown Languages

28.4.1 Tokenization, Stemming, and the xml:lang Attribute

Tokenization and stemming are both language-specific; that is, a string can be tokenized and stemmed differently in different languages. For searches, the language is specified by the cts:query constructors (or by the default language of the database if a language is not specified). For more details, see “Tokenization and Stemming” on page 595. For nodes constructed in XQuery, any `xml:lang` attributes are treated the same way as if the document were loaded into a database. For details, see “xml:lang Attribute” on page 598.

28.4.2 Language-Aware Searches

All searches in MarkLogic Server are language-aware. You can construct searches using `cts:search or cts:contains`, each of which takes a `cts:query` expression. Each leaf-level `cts:query` constructor in the `cts:query` expression specifies a language (or defaults to a language). For details on the `cts:query` constructors, see “Composing cts:query Expressions” on page 240.

All searches use the language setting in the `cts:query` constructor to determine how to tokenize the search terms. Stemmed searches also use the language setting to derive stems. Unstemmed searches use the specified language for tokenization but use the unstemmed (`word searches`) indexes, which are language-independent.

28.4.3 Unstemmed Searches

An *unstemmed* search matches terms that are exactly like the search term; it does not take into consideration the stem of the word. Unstemmed searches match terms in a language independent way, but tokenize the search according to the specified language. Therefore, when you specify a language in an unstemmed query, the language applies only to tokenization; the unstemmed query will match any text in any language that matches the query.

Note the following characteristics of unstemmed searches:

- Unstemmed searches require `word search` indexes, otherwise they throw an exception (this is a change of behavior from MarkLogic Server 3.1, see the *Release Notes* for details). You can perform unstemmed searches without `word search` indexes using `cts:contains`, however. To perform unstemmed searches without the `word search` indexes enabled, use a `let` to bind the results of a stemmed search to a variable, and then filter the results using `cts:contains` with an unstemmed query.

  The following example demonstrates this. The following example binds the stemmed search results to a variable, then iterates over the results, filtering out all but the unstemmed results in the `where` clause (using `cts:contains` with a `cts:query` that specifies the `unstemmed` option).

  ```
  let $search := cts:search(doc(), cts:word-query("my words",
                                      ("stemmed", "lang=en")))
  for $x in $search
  where cts:contains($x, cts:word-query("my words", "unstemmed"))
  return $x
  ```

  Note: While it is likely that everything returned by this search will have an English match to the `cts:query`, it does not necessarily *guarantee* that everything returned is in English. Because this search returns documents, it is possible for a document to contain words in another language that do not match the language-specific query, but do match the unstemmed query (if the document contains text in multiple languages, and if it has “my words” in some other language than the one specified in the stemmed `cts:query`).

- The `word search` indexes have no language information.
- Unstemmed searches use the `lang=<language>` option to determine the language for tokenization.

- Unstemmed searches search all content, regardless of language (and regardless of `lang=<language>` option). The language only affects how the search terms are tokenized. For example, the following unstemmed search returns true:

```
(: returns true :)
let $x := <el xml:lang="fr">chat</el>
return
cts:contains($x, cts:word-query("chat", ("unstemmed", "lang=en")))
```

  whereas the following stemmed search returns false:

```
(: returns false :)
let $x := <el xml:lang="fr">chat</el>
return
cts:contains($x, cts:word-query("chat", ("stemmed", "lang=en")))
```

28.4.4 Unknown Languages

If the language specified in a search is not one of the languages in which language-specific stemming and tokenization are supported, or if it is a language for which you do not have a license key, then it is treated as a generic language. Typically, generic languages with Latin script are tokenized the same way as English, with token breaks at whitespace and punctuation, and with each word stemming to itself, but this is not always the case (especially for languages supported by MarkLogic Server—see “Supported Languages” on page 603—but for which you are not licensed). For details, see “Generic Language Support” on page 604.

28.5 Supported Languages

This section lists languages with advanced stemming and tokenization support in MarkLogic Server. All of the languages except English require a license key with support for the language. If your license key does not include support for a given language, the language is treated as a generic language (see "Generic Language Support" on page 604). The following are the supported languages:

- English
- French
- Italian
- German
- Russian
- Spanish
- Arabic
- Chinese (Simplified and Traditional)
- Korean
- Persian (Farsi)
- Dutch
- Japanese
- Portuguese
- Norwegian (Nynorsk and Bokmål)
- Swedish

For a list of base collations and character sets used with each language, see "Collations and Character Sets By Language" on page 624.

28.6 Generic Language Support

You can load and query documents in any language into MarkLogic Server, as long as you can convert the character encoding to UTF-8. If the language is not one of the languages with advanced support, or if the language is one for which you are not licensed, then the tokenization is performed in a generic way (on whitespace and punctuation characters for non-Asian characters, and on each character for Asian characters), and each term stems to itself.

For example, if you load the following document:

```
<doc xml:lang="nn">
  <a>Some text in any language here.</a>
</doc>
```

then that document is loaded as the language `nn`, and a stemmed search in any other language would not match. Therefore, the following does not match the document:

```
(: does not match because it was stemmed as "nn" :)
cts:search(doc(), cts:word-query("language", ("stemmed", "lang=en"))
```

and the following search does match the document:

```
(: does match because the query specifies "nn" as the language :)
cts:search(doc(), cts:word-query("language", ("stemmed", "lang=nn"))
```

For generic language searches in languages for which MarkLogic does not provide advanced language support (the languages described in “Supported Languages” on page 603), those languages are all treated as the same language for stemmed searches. Therefore, a stemmed search that matches a document in one language without advanced language support will also match a document in another language without advanced language support.

Generic language support allows you to query documents in any language, regardless of which languages you are licensed for or which languages have advanced support. Because the generic language support only stems words to themselves, queries in these languages will not include variations of words based on their meanings in the results. If you desire further support than the generic language support for some particular language, contact MarkLogic Technical Support.

29.0 Custom Tokenization

Use custom tokenizer overrides on fields to change the classification of characters in content and query text. Character re-classification affects searches because it changes the tokenization of text blocks. The following topics are covered:

- Introduction to Custom Tokenizer Overrides
- How Character Classification Affects Tokenization
- Using xdmp:describe to Explore Tokenization
- Performance Impact of Using Tokenizer Overrides
- Defining a Custom Tokenizer Override
- Examples of Custom Tokenizer Overrides

29.1 Introduction to Custom Tokenizer Overrides

A custom tokenizer override enables you to change the tokenizer classification of a character when it occurs within a field. You can use this flexibility to improve search efficiency, enable searches for special character patterns, and normalize data.

> **Note:** You can only define a custom tokenizer override on a field. For details, see Overview of Fields in the *Administrator's Guide*.

As discussed in "Tokenization and Stemming" on page 595, tokenization breaks text content and query text into word, punctuation, and whitespace tokens. Built-in language specific rules define how to break text into tokens. During tokenization, each character is classified as a word, symbol, punctuation, or space character. Each symbol, punctuation, or space character is one token. Adjacent word characters are grouped together into a single word token. Word and symbol tokens are indexed; space and punctuation tokens are not.

For example, with default tokenization, a text run of the form "456-1111" breaks down into 2 word tokens and 1 punctuation token. You can use a query similar to the following one to examine the break down:

```
xquery version "1.0-ml";
xdmp:describe(cts:tokenize("456-1111"));

==> ( cts:word("456"), cts:punctuation("-"), cts:word("1111") )
```

If you define a custom tokenizer override that classifies hyphen as a character to remove, the tokenizer produces the single word token "4561111". In combination with other database configuration changes, this can enable more accurate wildcard searches or allow searches to match against variable input such as 456-1111 and 4561111. For a full example, see "Example: Improving Accuracy of Wildcard-Enabled Searches" on page 610.

Tokenization rules apply to both content and query text. Since tokenizer overrides can only be applied to fields, you must use field queries such as `cts:field-word-query` or `cts:field-value-query` to take advantage of your overrides.

You cannot override a character to its default class. For example, the space character (" ") has class `space` by default, so you cannot define an override that classifies it as `space`.

You cannot override a composite character that decomposes into multiple characters when NFD Unicode normalization is applied.

29.2 How Character Classification Affects Tokenization

You can define a custom tokenizer override to classify a character as one of the following categories:

- `space`: Treat as whitespace. Whitespace is not indexed.
- `word`: Adjacent word characters are grouped into a single token that is indexed.
- `symbol`: Each symbol character forms a single token that is indexed.
- `remove`: Eliminate the character from consideration when creating tokens.

Note that re-classifying a character such that it is treated as punctuation in query text can trigger punctuation-sensitive field word and field value queries. For details, see "Wildcarding and Punctuation Sensitivity" on page 531.

The table below illustrates how each kind of override impacts tokenization:

Char Class	Example Input	Default Tokenization	Override	Result
space	`10x40`	`10x40` (word)	`admin:database-tokenizer-override ("x","space")`	`10` (word) `x` (space) `40` (word)
word	`456-1111`	`456` (word) `-` (punc.) `1111` (word)	`admin:database-tokenizer-override ("-","word")`	`456-1111` (word)
symbol	`@1.2`	`@` (punc.) `1.2` (word)	`admin:database-tokenizer-override ("@","symbol")`	`@` (symbol) `1.2` (word)
remove	`456-1111`	`456` (word) `-` (punc.) `1111` (word)	`admin:database-tokenizer-override ("-","remove")`	`4561111` (word)

29.3 Using xdmp:describe to Explore Tokenization

You can use `xdmp:describe` with `cts:tokenize` to explore how the use of fields and tokenizer overrides affects tokenization. Passing the name of a field to `cts:tokenize` applies the overrides defined on the field to tokenization.

The following example shows the difference between the default tokenization rules (no field), and tokenization using a field named "dim" that defines tokenizer overrides. For configuration details on the field used in this example, see "Example: Searching Within a Word" on page 612.

```
xquery version "1.0-ml";
xdmp:describe(cts:tokenize("20x40"));
xdmp:describe(cts:tokenize("20x40",(),"dim"))

==>
cts:word("20x40")
(cts:word("20"), cts:space("x"), cts:word("40"))
```

You can use this method to test the effect of new overrides.

You can also include a language as the second argument to `cts:tokenize`, to explore language specific effects on tokenization. For example:

```
xdmp:describe(cts:tokenize("20x40","en","dim"))
```

For more details on the interaction between language and tokenization, see "Language Support in MarkLogic Server" on page 594.

29.4 Performance Impact of Using Tokenizer Overrides

Using tokenizer overrides can make indexing and searching take longer, so you should only use overrides when truly necessary. For example, if a custom override is in scope for a search, then filtered field queries require retokenization of every text node checked during filtering.

If you have a small number of tokenizer overrides, the impact should be modest.

If you define a custom tokenizer on a field with a very broad scope, expect a larger performance hit. Choosing to re-classify commonly occurring characters like " " (space) as a symbol or word character can cause index space requirements to greatly increase.

29.5 Defining a Custom Tokenizer Override

You can only define a custom tokenizer override on a field. You can configure a custom tokenizer override in the following ways:

- Programmatically, using the function `admin:database-add-field-tokenizer-override` in the Admin API.
- Interactively, using the Admin Interface. For details, see Configuring Fields in the *Administrator's Guide*.

Note: Even if reindexing is disabled, when you add tokenizer overrides to a field, those tokenization changes take effect immediately, so all new queries against the field will use the new tokenization (even if it is indexed with the previous tokenization).

For example, assuming the database configuration already includes a field named `phone`, the following XQuery adds a custom tokenizer override to the field that classifies "-" as a `remove` character and `"@"` as a symbol:

```
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
  at "/MarkLogic/admin.xqy";

let $dbid := xdmp:database("myDatabase")
let $config :=
  admin:database-add-field-tokenizer-override(
    admin:get-configuration(), $dbid, "phone",
    (admin:database-tokenizer-override("-","remove"),
     admin:database-tokenizer-override("@", "symbol"))
  )
return admin:save-configuration($config)
```

29.6 Examples of Custom Tokenizer Overrides

This section contains the following examples related to using custom tokenizer overrides:

- Example: Configuring a Field with Tokenizer Overrides
- Example: Improving Accuracy of Wildcard-Enabled Searches
- Example: Data Normalization
- Example: Searching Within a Word
- Example: Using the Symbol Classification

29.6.1 Example: Configuring a Field with Tokenizer Overrides

The following query demonstrates creating a field, field range index, and custom tokenizer overrides using the Admin API. You can also perform these operations using the Admin Interface.

Use this example as a template if you prefer to use XQuery to configure the fields used in the remaining examples in this section. Replace the database name, field name, included element name, and tokenizer overrides with settings appropriate for your use case.

```
(: Create the field :)
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $config := admin:get-configuration()
let $dbid := xdmp:database("YourDatabase")
return admin:save-configuration(
  admin:database-add-field(
    $config, $dbid,
    admin:database-field("example", fn:false())
  )
);

(: Configure the included elements and field range index :)
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $dbid := xdmp:database("YourDatabase")
let $config := admin:get-configuration()
let $config :=
  admin:database-add-field-included-element(
    $config, $dbid, "example",
    admin:database-included-element(
      "", "your-element", 1.0, "", "", "")
  )
let $config :=
  admin:database-add-range-field-index(
    $config, $dbid,
    admin:database-range-field-index(
      "string", "example",
      "http://marklogic.com/collation/", fn:false())
  )
return admin:save-configuration($config);

(: Define custom tokenizer overrides :)
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $config := admin:get-configuration()
let $dbid := xdmp:database("YourDatabase")
return admin:save-configuration(
  admin:database-add-field-tokenizer-override(
    $config, $dbid, "example",
    (admin:database-tokenizer-override("(", "remove"),
     admin:database-tokenizer-override(")", "remove"),
     admin:database-tokenizer-override("-", "remove"))
```

```
    )
);
```

29.6.2 Example: Improving Accuracy of Wildcard-Enabled Searches

This example demonstrates using custom tokenizers to improve the accuracy and efficiency of unfiltered search on phone numbers when three character searches are enabled on the database to support wildcard searches.

Run the following query in Query Console to load the sample data into the database.

```
xdmp:document-insert("/contacts/Abe.xml",
  <person>
    <phone>(202)456-1111</phone>
  </person>);
xdmp:document-insert("/contacts/Mary.xml",
  <person>
    <phone>(202)456-1112</phone>
  </person>);
xdmp:document-insert("/contacts/Bob.xml",
  <person>
    <phone>(202)111-4560</phone>
  </person>);
xdmp:document-insert("/contacts/Bubba.xml",
  <person>
    <phone>(456)202-1111</phone>
  </person>)
```

Use the Admin Interface or a query similar to the following to enable three character searches on the database to support wildcard searches.

```
xquery version "1.0-ml";
import module namespace admin = "http://marklogic.com/xdmp/admin"
    at "/MarkLogic/admin.xqy";

let $config := admin:get-configuration()
return admin:save-configuration(
  admin:database-set-three-character-searches($config,
    xdmp:database("YourDatabase"), fn:true())
)
```

With three character searches enabled, the following unfiltered search returns false positives because the query text tokenizes into two word tokens, “202” and “456”, with the wildcard applying only to the “456” token.

```
xquery version "1.0-ml";
cts:search(
  fn:doc(),
  cts:word-query("(202)456*"),
  "unfiltered")//phone/text()
```

```
==>
(456)202-1111
(202)456-1111
(202)111-4560
(202)456-1112
```

To improve the accuracy of the search, define a field on the `phone` element and define tokenizer overrides to eliminate all the punctuation characters from the field values. Use the Admin Interface to define a field with the following characteristics, or modify the query in "Example: Configuring a Field with Tokenizer Overrides" on page 608 and run it in Query Console.

Field Property	Setting
Name	`phone`
Field type	`root`
Include root	`false`
Included elements	`phone` (no namespace)
Range field index	scalar type: `string` field name: `phone` collation: `http://marklogic.com/collation/` (default) range value positions: `false` (default) invalid values: `reject` (default)
Tokenizer overrides	`remove (` (left parenthesis) `remove )` (right parenthesis) `remove -` (hyphen)

This field definition causes the phone numbers to be indexed as single word tokens such as "4562021111" and "2021114560". If you perform the following search, the false positives are eliminated:

```
xquery version "1.0-ml";
cts:search(fn:doc(),
  cts:field-word-query("phone", "(202)456*"),
  "unfiltered")//phone/text()

==>
(202)456-1111
(202)456-1112
```

If the field definition did not include the tokenizer overrides, the field word query would include the same false positives as the initial word query.

29.6.3 Example: Data Normalization

In “Example: Improving Accuracy of Wildcard-Enabled Searches” on page 610, custom tokenizer overrides are used to remove punctuation from phone numbers of the form (202)456-1111. The overrides provide the additional benefit of normalizing query text because the tokenizer overrides apply to query text as well as content.

If you define “(“, “)”, “-”, and “ “ (space) as `remove` characters, then a phone number such as (202)456-1111 is indexed as the single word 2024561111, and all the following query text examples will match exactly in an unfiltered search:

- (202)456-1111
- 202-456-1111
- 202 456-1111
- 2024561111

The same overrides also normalize indexing during ingestion: If the input data contains all of the above patterns in the `phone` element, the data is normalized to a single word token for indexing in all cases.

For sample input and details on configuring an applicable field, see “Example: Improving Accuracy of Wildcard-Enabled Searches” on page 610.

29.6.4 Example: Searching Within a Word

This example demonstrates using custom tokenizer overrides to create multiple tokens out of what would otherwise be considered a single word. This makes it possible to search successfully for a portion of the word.

Suppose you have input documents that include a `dimensions` element of the form MxN, where M and N are the number of feet. For example, “10x4” is the measurement of an area that is 10 feet by 4 feet. You cannot search for “all documents which includes at least one dimension of 10 feet” because `10x4` tokenizes as a single word.

To demonstrate, run the following query in Query Console to load the sample documents:

```
xquery version "1.0-ml";
xdmp:document-insert("/plots/plot1.xml",
  <plot>
    <dimensions>10x4</dimensions>
  </plot>);
xdmp:document-insert("/plots/plot2.xml",
  <plot>
    <dimensions>25x10</dimensions>
  </plot>);
xdmp:document-insert("/plots/plot3.xml",
  <plot>
```

```
    <dimensions>5x4</dimensions>
  </plot>)
```

Next, run the following word query against the database and observe that there are no matches:

```
xquery version "1.0-ml";
cts:search(fn:doc(), cts:word-query("10"),"unfiltered")
```

Use the Admin Interface to define a field with the following characteristics, or modify the query in “Example: Configuring a Field with Tokenizer Overrides” on page 608 and run it in Query Console.

Field Property	Setting
Name	`dim`
Field type	`root`
Include root	`false`
Included elements	`dimensions` (no namespace)
Range field index	scalar type: `string` field name: `dim` collation: `http://marklogic.com/collation/` (default) range value positions: `false` (default) invalid values: `reject` (default)
Tokenizer overrides	`space x`

The field divides each `dimension` text node into two tokens, split at “x”. Therefore, the following field word query now finds matches in the example documents:

```
xquery version "1.0-ml";
cts:search(fn:doc(), cts:field-word-query("dim", "10"),"unfiltered")

==>
<plot>
  <dimensions>25x10</dimensions>
</plot>
<plot>
  <dimensions>10x4</dimensions>
</plot>
```

29.6.5 Example: Using the Symbol Classification

This example demonstrates the value of classifying some characters as `symbol`. Suppose you are working with Twitter data, where the appearance of `@word` in Tweet text represents a user and `#word` represents a topic identifier ("hash tag"). For this example, we want the following search semantics to apply:

- If you search for a naked term, such as `NASA`, the search should match ocurrences of the naked term ("`NASA`") or topics ("`#NASA`"), but not users ("`@NASA`").
- If you search for a user (`@NASA`), the search should only match users, not naked terms or topics.
- If you search for a topic (`#NASA`), the search should only match topics, not naked terms or users.

The following table summarizes the desired search results:

Query Text	Should Match	Should Not Match
`NASA`	`NASA` `#NASA`	`@NASA`
`@NASA`	`@NASA`	`NASA` `#NASA`
`#NASA`	`#NASA`	`NASA` `@NASA`

If you do not define any token overrides, then the terms `NASA`, `@NASA`, and `#NASA` tokenize as follows:

- `NASA`: `cts:word("NASA")`
- `@NASA`: `cts:punctuation("@"), cts:word("NASA")`
- `#NASA`: `cts:punctuation("#"), cts:word("NASA")`

Assuming a punctuation-insensitive search, this means all three query strings devolve to searching for just `NASA`.

If you define a tokenizer override for `@` that classifies it as a word character, then `@NASA` tokenizes as a single word and will not match naked terms or topics. That is, `@NASA` tokenizes as:

```
cts:word("@NASA")
```

However, classifying `#` as a word character does not have the desired effect. It causes the query text `#NASA` to match topics, as intended, but it also excludes matches for naked terms. The solution is to classify `#` as a symbol. Doing so causes the following tokenization to occur:

```
cts:word("#"),cts:word("NASA")
```

Now, searching for `#NASA` matches adjacent occurrences of `#` and `NASA`, as in a topic, and searching for just `NASA` matches both topics and naked terms. Users (`@NASA`) continue to be excluded because of the tokenizer override for `@`.

30.0 Encodings and Collations

In addition to the language support described in "Language Support in MarkLogic Server" on page 594, MarkLogic Server also supports many character encodings and has the ability to sort the content in a variety of collations. This chapter describes the MarkLogic Server support of encodings and collations, and includes the following sections:

- Character Encoding
- Collations
- Collations and Character Sets By Language

30.1 Character Encoding

MarkLogic Server stores all content in the UTF-8 encoding. If you try to load non-UTF-8 content into MarkLogic Server without translating it to UTF-8, the server throws an exception. If you have non-UTF-8 content, then you can specify the encoding for the content during ingestion, and MarkLogic Server will translate it to UTF-8. If the content cannot be translated, MarkLogic Server throws an exception indicating that there is non-UTF-8 content.

You can specify an explicit encoding in the following ways:

- If your content is ingested on behalf of an HTTP request, you can specify an encoding in the HTTP headers, such as setting the `charset` parameter of the Content-type header.
- Set the `encoding` option of the functions listed in the following table.

XQuery	JavaScript
`xdmp:document-load`	`xdmp.documentLoad`
`xdmp:document-get`	`xdmp.documentGet`
`xdmp:zip-get`	`xdmp.zipGet`
`xdmp:gunzip`	`xdmp.gunzip`
`xdmp:xslt-invoke`	`xdmp.xsltInvoke`

Encoding is determined using the following precedence, from highest to lowest:

- The encoding option of the ingestion function, if set.
- The encoding specified by the HTTP headers, if present.
- Otherwise, assume UTF-8.

If you set the `encoding` option to "auto", then MarkLogic tries to determine the encoding from the document content.

If the encoding is UTF-8 and any non-UTF-8 characters are found, an exception is thrown indicating the content contains non-UTF-8 characters.

MarkLogic Server assumes the character set you specify is actually the character set of the content. If you specify an encoding that is different from the actual content encoding, the result can be unpredictable: You might get an exception in some situations, but you might end up with the wrong characters in other situations.

For details on the syntax of the `encoding` option, see the *MarkLogic XQuery and XSLT Function Reference*.

30.2 Collations

This section describes collations in MarkLogic Server. Collations specify the order in which strings are sorted and how they are compared. The section includes the following parts:

- Overview of Collations
- Two Common Collation URIs
- Collation URI Syntax
- Backward Compatibility with 3.1 Range Indexes and Lexicons
- UCA Root Collation
- How Collation Defaults are Determined
- Specifying Collations

30.2.1 Overview of Collations

A *collation* specifies the order for sorting strings. The collation settings determine the order for operations where the order is specified (either implicitly or explicitly) and for operations that use Range Indexes. Examples of operations that specify the order are XQuery statements with an `order by` clause, XQuery standard functions that compare order (for example, `fn:compare`, `fn:substring-after`, `fn:substring-before`, and so on), and lexicon functions (for example, `cts:words`, `cts:element-word-match`, `cts:element-values`, and so on). Additionally, collations determine uniqueness in string comparisons, so two strings that are equal according to one collation might be not be equal according to another.

The codepoint-order collation sorts according to the Unicode codepoint order, which does not take into account any language-specific information. There are other collations that are often used to specify language-specific sorting differences. For example, a code point sort puts all uppercase letters before lower-case letters, so the word `Zounds` sorts before the word `abracadabra`. If you use a collation that sorts upper and lower-case letters together (for example, the order `A a B b C c`, and so on), then `abracadabra` sorts before `Zounds`.

Collations are specified with a URI (for example, `http://marklogic.com/collation/`). The collation URIs are specific to MarkLogic Server, but they specify collations according to the Unicode collation standards. There are many variations to collations, and many sort orders that are based on preferences and traditions in various languages. The following section describes the syntax of collation URIs. Although there are a huge number of collation URIs possible, most applications will use only a small number of collations. For more information about collations, see http://icu.sourceforge.net/userguide/Collate_Concepts.html.

30.2.2 Two Common Collation URIs

The following are two very common collation URIs used in MarkLogic Server:

- `http://marklogic.com/collation/`
- `http://marklogic.com/collation/codepoint`

The first one is the UCA Root Collation (see "UCA Root Collation" on page 622), and is the system default. The second is the codepoint order collation, and was the default in pre-3.2 releases of MarkLogic Server.

30.2.3 Collation URI Syntax

Collations in MarkLogic Server are specified by a URI. All collations begin with the string `http://marklogic.com/collation/`. The syntax for collations is as follows:

```
http://marklogic.com/collation/<locale>[/<attribute>]*
```

This section describes the following parts of the syntax:

- Locale Portion of the Collation URI
- Attribute Portion of the Collation URI

30.2.3.1 Locale Portion of the Collation URI

The `<locale>` portion of the collation URI must be a valid locale, and is defined as follows:

```
<locale> ::= <language>[-<script>][_<region>][@(collation=<value>;)+]
```

For a list of valid language codes, see the following:

```
http://www.loc.gov/standards/iso639-2/php/code_list.php
```

For a list of valid script codes, see the following:

```
http://www.unicode.org/iso15924/iso15924-codes.html
```

For a list of valid region codes, see the following:

```
http://www.iso.org/iso/en/prods-services/iso3166ma/02iso-3166-code-lists/list-en1.html
```

Some languages (for example, German and Chinese) have multiple collations you can specify in the locale. To specify one of these language-specific collation variants, use the `@collation=<value>` portion of the syntax.

If you do not specify a locale in the collation URI, the UCA Root Collation is used by default (for details, see "UCA Root Collation" on page 622).

Note: While you can specify many valid language, script, or region codes, MarkLogic Server only fully supports those that are relevant to and most commonly used with the supported languages. For a list of supported languages along with their common collations, see "Collations and Character Sets By Language" on page 624.

The following table lists some typical locales, along with a brief description:

Locale	Description	Collation URI
`en`	English language	`http://marklogic.com/collation/en`
`en_US`	English language with United States region	`http://marklogic.com/collation/en_US`
`zh`	Chinese language	`http://marklogic.com/collation/zh`
`de@collation=phonebook`	German language with the `phonebook` collation	`http://marklogic.com/collation/de@collation=phonebook`

30.2.3.2 Attribute Portion of the Collation URI

There can be zero or more `<attribute>` portions of the collation URI. Attributes further specify characteristics such as which collation to use, whether to be case sensitive or case insensitive, and so on. You only need to specify attributes if they differ from the defaults for the specified locale. Attributes have the following syntax:

```
<attribute> ::= <strength> | <case-level> | <case-first> |
                <alternate> | <numeric-collation> |
                <variable-top> | <normalization-checking> |
                <french> | <hiragana>
```

The following table describes the various attributes. For simplicity, terms like case-sensitive, diacritic-sensitive, and others are used. In actuality, the definitions of these terms for use in collations are somewhat more complicated. For the exact technical meaning of each attribute, see http://icu.sourceforge.net/userguide/Collate_Concepts.html.

Attribute	Legal Values	Descriptions
`<strength>` The level of comparison to use.	`S1`	Specifies case and diacritic insensitive.
	`S2`	Specifies diacritic sensitive and case insensitive.
	`S3`	Specifies case and diacritic sensitive.
	`S4`	Specifies punctuation sensitive.
	`SI`	Specifies identity (codepoint differentiated).
`<case-level>` Enable or disable the case sensitive level, skipping the diacritic sensitive level. So diacritic insensitive, case sensitive is `/S1/EO` Default: `EX`	`EO`	Specifies enable case-level.
	`EX`	Specifies disable case-level.
`<case-first>` Specifies whether uppercase sorts before or after lowercase. Default: `CX`	`CU`	Specifies that uppercase sorts first.
	`CL`	Specifies that lowercase sorts first.
	`CX`	Off.

Attribute	Legal Values	Descriptions
`<alternate>` Specifies how to handle variable characters. (As completely ignorable or as normal characters.) Default: `AN`	`AN`	Specifies that all characters are non-ignorable; that is, include all spaces and punctuation characters when sorting characters.
	`AS`	Specifies that variable characters are shifted (ignored) according to the `variable-top` setting.
`<numeric-collation>` Order numbers as numbers rather than collation order (for example, 20 < 100). Default: `MX`	`MO`	Specifies numeric ordering.
	`MX`	Specifies non-numeric ordering (order according to the collation).
`<variable-top>` Used with `alternate` to specify which variable characters are ignorable. Any character that is primary-less-than (for details on this concept, see the Unicode link in "UCA Root Collation" on page 622) the cutoff character will be treated as ignorable. Only meaningful in combination with `AS`. Default: `T0000`	`T0000`	Specifies that all variable characters (typically whitespace and punctuation) are ignored for sorting variable characters.
	`T0020`	Specifies that whitespace is ignorable when sorting characters. For example, `/T0020/AS` means that period (a variable character) would be treated as a regular character but space would be ignorable. Therefore: `A B = AB and AB < A.B.`
	`T00BB`	Specifies that most punctuation and space characters are ignorable when sorting characters. Specifically, characters whose sort key is less than or equal to `00BB` are ignorable.
`<normalization-checking>` Specifies whether to perform Unicode normalization on the input string. Default: `NX`	`NO`	Specifies normalize Unicode.
	`NX`	Specifies do not normalize Unicode.

Attribute	Legal Values	Descriptions
`<french>` Specifies whether to apply the French accent ordering rule (that is, to reverse the ordering at the `S3` level). Default: `FX`	`FO`	Specifies French accent ordering.
	`FX`	Specifies normal ordering (according to the collation).
`<hiragana>` Specifies whether to add an additional level to distinguish Hiragana from Katakana. Default: `HX`	`HO`	Hiragana mode on.
	`HX`	Hiragana mode off.

30.2.4 Backward Compatibility with 3.1 Range Indexes and Lexicons

Range Indexes and lexicons that were created in MarkLogic Server 3.1 use the Unicode codepoint collation order. If you want them to use a different collation in any of these indexes and/or lexicons, you must change the collation and re-create the index, and then reindex the database (if `reindex enable` is set to true, it will automatically begin reindexing).

30.2.5 UCA Root Collation

The Unicode collation algorithm (UCA) root collation in MarkLogic Server is used when no default exists. It uses the Unicode codepoint collation with S3 (case and diacritic sensitive) strength, and it has the following URI:

```
http://marklogic.com/collation/
```

The UCA root collation adds more useful case and diacritic sensitivity to the Unicode codepoint order, so it will make more sensible sort orders when you take case sensitivity and diacritic sensitivity into consideration. For more details about the UCA, see http://www.unicode.org/unicode/reports/tr10/.

30.2.6 How Collation Defaults are Determined

The collation used for requests in MarkLogic Server is based on the settings of various parameters in the Admin Interface and on what is specified in your XQuery code. Each App Server has a default collation specified, and that is used in the absence of anything else that overrides it. Note the following about collations and their defaults.

- Collations are specified at the App Server level, on Range Indexes, and on lexicons.
- App Servers, Range Indexes, and lexicons upgraded from 3.1 remain in codepoint order (`http://marklogic.com/collation/codepoint`).
- New App Servers default to the UCA Root Collation (`http://marklogic.com/collation/`).
- New Range Indexes and lexicons default to UCA Root Collation (`http://marklogic.com/collation/`).
- You can specify a default collation in an XQuery prolog, which overrides the App Server default. For example, the following query will use the French collation:

```
xquery version "1.0-ml";
declare default collation "http://marklogic.com/collation/fr";

for $x in ("côte", "cote", "coté", "côté", "cpte" )
order by $x
return $x
```

- The codepoint collation URI is as follows:

```
http://marklogic.com/collation/codepoint
```

  The following is an alias to the codepoint collation URI (used with the `1.0` strict XQuery dialect):

```
http://www.w3.org/2005/xpath-functions/collation/codepoint
```

- Collation URIs displayed in the Admin Interface are stored and displayed as the canonical representation of the URI entered. The canonical representation is equivalent to the URI entered, but changes the order and simplifies portions of the collation URI string to a predetermined order. The `xdmp:collation-canonical-uri` built-in XQuery function returns the canonical URI of any valid collation URI.
- The empty string URI becomes codepoint collation. Therefore, the following returns as shown:

```
xdmp:collation-canonical-uri("")
=> http://marklogic.com/collation/codepoint
```

- The collation used in an XQuery module is determined on a per-module basis. Therefore, a module might call another module that uses a different collation, as each module determines its collation independent of the module that called it (based on the App Server defaults, collation prolog declaration, and so on).
- When a module is invoked or spawned from another module, or when a request is submitted via an `xdmp:eval` call from another module, the new request inherits the collation context of the calling module. That context can be overridden in the query (for

example, with a `declare default collation` expression in the prolog), but it will default to the context from the calling module.

- If no other collations are in effect (for example, for scheduled tasks), the codepoint collation is used.

30.2.7 Specifying Collations

You can specify collations in many places. Some common places to specify collations are:

- In the `order by` clause of a FLWOR expression.
- In an App Server configuration in the Admin Interface.
- In a lexicon or Range Index specification in the Admin Interface.
- In many W3C standard XQuery functions (for example, `fn:compare`, `fn:contains`, `fn:starts-with`, `fn:ends-with`, `fn:substring-after`, `fn:substring-before`, `fn:deep-equals`, `fn:distinct-values`, `fn:index-of`, `fn:max`, `fn:min`).
- In the lexicon APIs (`cts:words`, `cts:word-match`, `cts:element-words`, `cts:element-values`, and so on).
- In the range query constructors (`cts:element-range-query`, `cts:element-attribute-range-query`).

30.3 Collations and Character Sets By Language

The following table lists the languages in which MarkLogic Server supports language-specific tokenization and stemming. It also lists some common collations and character sets for each language.

Language	Base Collations		Character Sets
English	`http://marklogic.com/collation/en`	case/diacritic sensitive	`ISO-8859-1` `cp1252`
	`http://marklogic.com/collation/en/S1`	case/diacritic insensitive	
	`http://marklogic.com/collation/en/S2`	diacritic sensitive	
	`http://marklogic.com/collation/en/S1/EO`	case sensitive	

Language	Base Collations		Character Sets
French	http://marklogic.com/collation/fr	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/fr/S1	case/diacritic insensitive	
	http://marklogic.com/collation/fr/S2	diacritic sensitive	
	http://marklogic.com/collation/fr/S1/EO	case sensitive	
Italian	http://marklogic.com/collation/it	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/it/S1	case/diacritic insensitive	
	http://marklogic.com/collation/it/S2	diacritic sensitive	
	http://marklogic.com/collation/it/S1/EO	case sensitive	
German	http://marklogic.com/collation/de	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/de/S1	case/diacritic insensitive	
	http://marklogic.com/collation/de/S2	diacritic sensitive	
	http://marklogic.com/collation/de/S1/EO	case sensitive	
	http://marklogic.com/collation/de@collation=phonebook	alternate German collation	
Spanish	http://marklogic.com/collation/es	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/es/S1	case/diacritic insensitive	
	http://marklogic.com/collation/es/S2	diacritic sensitive	
	http://marklogic.com/collation/es/S1/EO	case sensitive	
	http://marklogic.com/collation/es@collation=traditional	Treats ll and ch as distinct characters	

Language	Base Collations		Character Sets
Russian	http://marklogic.com/collation/ru	case/diacritic sensitive	cp1251 KOI8-R ISO-8859-5
	http://marklogic.com/collation/ru/S1	case/diacritic insensitive	
	http://marklogic.com/collation/ru/S2	diacritic sensitive	
	http://marklogic.com/collation/ru/S1/EO	case sensitive	
Arabic	http://marklogic.com/collation/ar	form-variant sensitive	cp1256 ISO-8859-6
	http://marklogic.com/collation/ar/S1	form-variant insensitive	
Chinese (Simplified and Traditional)	http://marklogic.com/collation/zh (simplified)	case/diacritic sensitive	Simplified: GB18030 GB2312 EUC-CN hz-gb-2312 cp936 Traditional: Big5 Big5-HKSCS cp950 GB18030
	http://marklogic.com/collation/zh-Hant (traditional)	case/diacritic sensitive	
	http://marklogic.com/collation/zh-Hant@collation=stroke (traditional with simplified order)	locale-specific variant	
	http://marklogic.com/collation/zh@collation=pinyan (simplified with traditional order)	locale-specific variant	
Korean	http://marklogic.com/collation/ko	case/diacritic sensitive	ISO 2022-KR EUC-KR KS X 1001 cp949 GB12052 KSC 5636
	http://marklogic.com/collation/ko/S1	case/diacritic insensitive	

Language	Base Collations		Character Sets
Persian (Farsi)	http://marklogic.com/collation/fa	case/diacritic sensitive	cp1256 ISO-8859-6
	http://marklogic.com/collation/fa/S1	case/diacritic insensitive	
	http://marklogic.com/collation/fa/S2	diacritic sensitive	
	http://marklogic.com/collation/fa/NX	disable normalization	
Dutch	http://marklogic.com/collation/nl	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/nl/S1	case/diacritic insensitive	
	http://marklogic.com/collation/nl/S2	diacritic sensitive	
	http://marklogic.com/collation/nl/S1/EO	case sensitive	
Japanese	http://marklogic.com/collation/ja http://marklogic.com/collation/ja/S1	case/diacritic insensitive	Shift JIS: cp932 ibm-942 ibm-943 EUC-JP: EUC-JISX0213 ibm-954 ISO-2022-JP: ISO-2022-JP-1 ISO-2022-JP-2 ISO-2022-JP-3 ISO-2022-JP-2004
	http://marklogic.com/collation/ja/S2	diacritic sensitive	
	http://marklogic.com/collation/ja/S1/EO	case sensitive	
	http://marklogic.com/collation/ja/S4/HX	Hiragana mode off	
Portuguese	http://marklogic.com/collation/pt	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/pt/S1	case/diacritic insensitive	
	http://marklogic.com/collation/pt/S2	diacritic sensitive	
	http://marklogic.com/collation/pt/S1/EO	case sensitive	


Language	Base Collations		Character Sets
Norwegian (Nynorsk and Bokmål)	http://marklogic.com/collation/nn (Nynorsk)	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/nn/S1	case/diacritic insensitive	
	http://marklogic.com/collation/nn/S2	diacritic sensitive	
	http://marklogic.com/collation/nn/S1/EO	case sensitive	
	http://marklogic.com/collation/nb (Bokmål)	case/diacritic sensitive	
	http://marklogic.com/collation/nb/S1	case/diacritic insensitive	
	http://marklogic.com/collation/nb/S2	diacritic sensitive	
	http://marklogic.com/collation/nb/S1/EO	case sensitive	
Swedish	http://marklogic.com/collation/sv	case/diacritic sensitive	ISO-8859-1 cp1252
	http://marklogic.com/collation/sv/S1	case/diacritic insensitive	
	http://marklogic.com/collation/sv/S2	diacritic sensitive	
	http://marklogic.com/collation/sv/S1/EO	case sensitive	

All of the languages except English require a license key to enable. If you do not have the license key for one of the supported languages, it is treated as a generic language, and each word is stemmed to itself and it is tokenized in a generic way (on whitespace and punctuation characters for non-Asian characters, and on each character for Asian characters). For more information, see "Generic Language Support" on page 604. The language-specific collations are available to all languages, regardless of what languages are enabled in the license key.

31.0 Data Visualization Widgets

This chapter introduces the use of visualization widgets to display MarkLogic Server search results. These widgets provide a means to display data in picture or graph form. You can incorporate visualization widgets directly in the display output of applications you write, or incorporate them in applications created with Application Builder.

The following is the search page from the Oscars application created by Application Builder. Every object on the page is a visualization widget.




This chapter contains the following sections:

- Overview of Visualization Widgets
- Working with the Visualization Widgets
- Overview of the Widget Architecture
- Adding Visualization Widgets to an HTML Page
- Example: Adding Widgets to Applications
- Visualization Widget Limitations
- Set Up A Proxy
- Widget API Reference


31.1 Overview of Visualization Widgets

MarkLogic Server provides six visualization widget types:


- Line Chart; a two-dimensional graph that shows a left to right series of data points, with each two consecutive data points connected by a straight line. Though line graphs can be associated with any facet type, they are typically used to show a time series, with the line representing chronological movement.




- Pie Chart: a two-dimensional circle, divided into different colored sections, one for each data value. A section's percentage of the circle's area is equivalent to the percentage of the data value's contents relative to the whole of the data (for example, if there are 16 total datums, and 8 of them have the value "red", the pie chart section corresponding to the "red" value will be half of the circle). Data values can be either non-continuous (colors, restaurant dishes) or continuous (height, weight, test scores).




- Column Chart: a chart with horizontal rectangular bars representing the amount of a particular discrete value. Values can be either non-continuous (colors, restaurant dishes) or continuous (height, weight, test scores).




- Bar Chart: a chart with vertical rectangular bars representing the amount of a particular discrete value. Values can be either non-continuous (colors, restaurant dishes) or continuous (height, weight, test scores).



- Point Map: A Google map with data points representing search results, each associated with a geospatial value. For example, assuming the data is in the database and the map widget was configured for this, a pin would appear over the town of Nevada, Missouri, to indicate the birthplace of actor/director John Huston. You can zoom in and out on the map, as well as pan in all directions.



- Heat Map: A Google map with results' geographic frequency represented as colored blobs located at distinct points on the map. For example, if there was a large number of results located in San Carlos, CA, there would be a large blob centered on that location on the map. If there was a small number of results located in Los Angeles, there would be a small blob centered on that map location.



31.2 Working with the Visualization Widgets

This section contains the following subsections:


- Building The Oscars Example Application
- General Operation of Widgets
- Working with the Line Chart Widget
- Working with the Bar and Column Chart Widgets
- Working with the Pie Chart Widget
- Working with the Map Widget

31.2.1 Building The Oscars Example Application


The quickest and easiest way to learn how to use visualization widgets is to use Application Builder to build an example Oscars application, as described in Building the Oscars Sample Application in the *Application Builder Developer's Guide*.

To add all of the widget types to the Oscars application, navigate to the Assemble page in Application Builder and do the following:


1. Click on the circled pointer at the right of the "Layout your application" section in the top left of the page.




2. A "Select a Template" popup window appears, giving you layout choices for your applications results page. Select the four-widget layout at the bottom on the right.




3. Click on the each widget box in your application layout:



4. Select the widget on the right that you want to add to the layout:



5. Each widget must be associated with a facet, which is set at the bottom of the Assemble page. For example, to have the column chart represent the number of awards on the data set, set the facet to 'award' and the measure to 'Count':



Note: Currently, Count is the only available measure for widgets.

6. Deploy your application, as described in Deploy Page in the *Application Builder Developer's Guide*.


31.2.2 General Operation of Widgets

In general, clicking on a widget item (for example, a bar on a bar chart) changes the search query for the page and, as a result, the sidebar, results, and any other widgets on the page are updated to reflect the new search term. The only exceptions to this is the line chart widget and clicking on a marker in a map widget.


Searches initiated through the widgets are stemmed searches, which means the results returned for a term like "name" also include 'names,' 'named', and so on.

31.2.3 Working with the Line Chart Widget

The following Line Chart shows the search results on the "decade" facet, with each dot indicating the number of nominations during that "decade." The chart's y-axis is the number of nominations, and its x-axis is the year, going from the first Oscars in 1920 to the present.




If you mouse over the Line Chart, a tool tip window appears, giving the date and number of nominations associated with the nearest data point, for example "Decade: 1970s" and "Nominations: 44"




Note: Line charts are currently read-only and do not update the sidebar, results, or other widgets on the page.

31.2.4 Working with the Bar and Column Chart Widgets


The following Bar and Column Charts show the search results on the "decade" facet.






If you mouse over a Bar or Column Chart, a tool tip window appears, giving the number of nominations (either by decade or film, depending on which chart) and film name or decade (again, depending on which chart) associated with the nearest bar. Clicking and dragging the mouse over the chart does not do anything. Clicking a single bar changes the Results area of the page to only show the search results associated with the film or decade, depending on the chart. Clicks on charts also change other widgets on the page, applying the value of the clicked bar as an additional search term to those widgets.

Note in the chart shown below, which has had the 1920s bar clicked, the number of Results is 10, the same as the number of results which occurred in the 1920s.




31.2.5 Working with the Pie Chart Widget

The following Pie Chart shows the search results on the "name" facet.




If you mouse over a Pie Chart, a tool tip window appears, giving the name value and number of search matching nominations associated with the nearest section, for example "Clint Eastwood: 3". Clicking on a single Pie Chart section updates the Sidebar and Results sections, so that they only show the results for the Name value associated with that Pie Chart section. For example, if you click on the section for Clint Eastwood, only search results associated with Clint Eastwood appear in the page's Sidebar and Results sections.




31.2.6 Working with the Map Widget

Before you can select a map widget, you must create a geospatial element pair index. Navigate to the Search tab in Application Builder, click Add New at the bottom of the page, select Geospatial, and name it 'map'. Click Create Geospatial Constraint.




Navigate to the Assemble page, select the map widget, and assign it the map facet. Deploy the application.



Note: If you are writing an application in which you expect over 25,000 map loads per day, you will be required to purchase an a Map API Key from Google. Enter the key in the Map API Key field in the Map Setup section.


The map widget in the deployed application shows the search results on the entire Oscars data set. Each circle represents a cluster of markers. The color of and the number inside the marker cluster represents the number of results. If you select facets to narrow the data set, the map will change to represent that subset of results.



Clicking and dragging the mouse over the map widget causes the map display to pan or move in the drag direction. If you click on marker cluster, you can drill down to more marker clusters and finally to individual markers, which represent each nominee's birthplace.



Unlike the other widgets, clicking on a marker does *not* update the Sidebar or Results. Rather, it open an info window containing the actor's name, birth date, and birth place, such as "Joan Crawford / Born 1905-03-23 / San Antonio, Texas".



The Sidebar and Results will be updated if you use the Draw Shape tool to select one or more markers on the map. Click on the polygon icon to set the map to Draw Shape mode:



For example, to update the search results based on two markers, left-click points and drag lines around the markers to draw a polygon as shown below:



31.3 Overview of the Widget Architecture

The front end architecture of the widgets is based on modules that can both send messages and receive them, but no module has any knowledge of other modules or the page at large. Each module has a listener that listens for messages that meet specific parameters. Similarly, a module sends out messages into the common medium without specific knowledge of the recipient of that message, but other modules with the proper listeners will receive those messages. In this fashion, module can be added and removed in realtime without disrupting the flow of the application, and there is no need for a controller to keep tabs on all of the application's modules. This maintains a strong separation of interests and allows for easier unit testing.

Modules are not aware of other modules. They can only trigger events and listen for events. The only information exchange between modules is through listening to messages in the common medium. There is no tracking of the particular source of information or particular destination. Messages are released into the common medium and read by those modules that have the proper listeners for picking up those particular messages.

The widget architectural model makes heavy use of event bubbling in the Document Object Model (DOM). There are two basic types of modules: Widget modules and controller modules. In most instances, there is a single controller module and one or more widget modules.

This section contains the following topics:

- Widgets
- Controller
- Identification
- Interaction within a Widget
- Shadow Queries

31.3.1 Widgets

Using event handlers, widgets listen for newData events in order to listen for new pieces of data to render. Similarly, widgets can generate newQuery events in order to communicate a change in the query based on internal changes to the widget.

Two simple degenerate cases are a search bar widget and a results widget:

- The search bar is a widget which does not react to any newData messages, but it does generate newQuery messages in response to a user typing a text query and clicking Search.
- The results widget does not typically send out newQuery messages, but rather, merely renders the results of a query. The exception to this is, if results have been implemented with pagination, then the results widget will send newQuery messages in order to paginate.

Widgets usually use a hybrid of the two types, both displaying information and updating the query in order to update the view into that query. An individual widget doesn't necessarily know the whole query, but tends to have control over a portion of it. Most visualizations take ownership of a particular facet and apply or remove a filter on the search based on that facet.

31.3.2 Controller

The controller is a module just like a widget. It's main job is listening to newQuery events and posting newData events. The controller makes use of a private comm (communicator) object that is responsible for making Ajax calls to the server for new data. For example, when panning a map widget, the map needs to update the marker clusters, which requires a query. The map widget sends out an event that the controller hears and passes on to the comm object, which requests the data and sends it back to the map widget.

The controller and comm object offer a lot of extensibility room for features like caching and data manipulations. The controller accepts an option configuration object that specifies things like the endpoint to access on the server, the application wrapper, the widget class, etc. By specifying a limited application wrapper, multiple controllers, for example, can be created on the page each running a separate application. They only respond to messages within their application container. Similarly, two applications can share a container on the page and use different widget classes to control their individual widgets.

The controller receives newQuery events and translates the query object into a structured query, which is appended to the Ajax call generated in the comm object.

31.3.3 Identification

Widgets are identified and linked to a controller using an HTML class. Applications generated by Application Builder name this class “widget.”

For example, to add the results widget to the page, specify the following:

```
<div id="results" class="widget"></div>
```

31.3.4 Interaction within a Widget

Interactions within widgets consist of selecting data or pagination. Each widget has an internal `updateQuery` method that can be called with a query object to send out a newQuery event. In the case of visual widgets, it makes "selections" on facets to update the query. A column chart or pie chart takes a single selection and a map takes an area (a polygon). For example, clicking on a bar in a column chart generates a selection event which bubbles up from the DOM and is read by the widget, which translates the selection into a newQuery event. The translation logic lives in the widget.

31.3.5 Shadow Queries

The basic idea of a shadow query is that, with many widgets on a page, multiple selections can be made at once and, if widgets are updating with each search, clicking on a widget essentially nullifies its further usefulness in searching because it will only display the one result that is the current selection.

The idea of shadow queries is to provide a “context” or “shadow” for these selected widgets. When a widget is selected, the selection is highlighted, but the other categories remain visible while the other widgets on the page update. When the next widget is selected, two queries are fired, one is the general search that's updating unselected widgets and the results pane; the other is the “shadow query” for the selected widget. This shadow query is a copy of the main search query, except without the selected widget's contribution to that search. This renders a view "around" the selection in the widget and greatly expands the power of widgets on the page by offering a very deep view into the data.

Shadow Queries work by taking advantage of the datastream. The datastream is set in two places, once in each widget upon instantiation (`datastream` is a parameter in the `createWidget` method described in “ML.createWidget (Null Widget) Method” on page 659) and also upon creation of shadow queries in the controller. The datastream is used to match a shadow query to the widget that it is shadowing.

Here is how datastreams work:

- If a query has no datastream, it will update all unselected widgets (or widgets with no datastream of their own set).
- If a query has a datastream and it matches the widget's datastream, then the widget will update; whether the widget is selected or not.
- If a query has a datastream and it does not match the widget's datastream, then the widget will do nothing.

  Note: When a widget sets off a shadow query by making a selection, it will not render the next update it receives, as that update is informing the widget of its already current state.

31.4 Adding Visualization Widgets to an HTML Page

Some code is common to both chart widgets (Bar, Column, Line, and Pie Charts) and map widgets (Point and Heat).

31.4.1 Common JavaScript And CSS In The <head> Element

In your `<head>` element, first, add your external library dependencies for line, bar, column, and pie charts:

```
<!-- external library dependencies -->
<script src="lib/external/jquery-1.7.1.min.js"
        type="text/javascript"></script>
<script src="lib/external/highscharts.src.js"
        type="text/javascript"></script>
```

If you are using map widgets, you must also include the following external libraries:

```
<!-- external web map files... -->
<script
src="http://maps.googleapis.com/maps/api/js?key=&amp;sensor=false&amp;
region=US&amp;libraries=drawing"
type="text/javascript">
</script>
<script src="lib/external/mxn-2.0.18/mxn.js?(googlev3)"
type="text/javascript"></script>
<script src="lib/external/heatmap.js" type="text/javascript"></script>
<script src="lib/external/heatmap-gmaps.js"
type="text/javascript"></script>
<script src="lib/external/markerclusterer_min.js"
type="text/javascript"></script>
```

Then add calls to the internal widget framework library. Of course, if you are not using histograph widgets, you do not need to include the `chart.js` library, and if you are not using map widgets you do not need to include the `map.js` library:

```
<!-- internal widget framework library -->
<script src="lib/controller.js" type="text/javascript"></script>
<script src="lib/widget.js" type="text/javascript"></script>
<script src="/lib/viz/chart/chart.js" type-"text/javascript"></script>
<script src="/lib/viz/map/map.js" type-"text/javascript"></script>
```

Finally, you may want to define a CSS style for your widget elements: This is optional, as there is a set of default CSS styles for the various widget types in the library (see `/lib/viz/chart.css` and `/lib/viz/map.css`). If you do define a custom style, do something similar to the following, defining your widgets' display parameters to meet your application's requirements. Of course, you do not have to call your element `widget`, especially if you want to have different display parameters for different visualization widgets and thus need to define several different elements.

```
<style type="text/css">
       .widget {
                width: 500px;
                display: block;
                float: left;
               }
</style>
```

31.4.2 Common Code In The <body> Element

You must define each widget as a separate `<div>` element with either the default class `"widget"` or the class name you specified when initializing widgets with `ML.controller.init` and its `widgetClass` option (see "ML.controller Methods" on page 657). In the example later on, which has three visualization widgets (two charts and one map), you have:

```
<div id="decadeContainer" class="widget"></div>
<div id="actorContainer" class="widget"></div>
<div id="locationContainer" class="widget"></div>
```

Next, define a `<script>` that:

1. Define the PHP search proxy that authenticates with the server and forwards queries to the REST endpoint on MarkLogic Server: :

   ```
   ML.controller.init({proxy: "proxy.php"});
   ```

   For details on how to define the PHP proxy, see "Set Up A Proxy" on page 656

2. Still in the `<script>`, define configuration variables for each of your visualization widgets. The configuration parameters differ for chart and map widgets (and also for Point Map and Heat Map map widgets), so see below for detailed examples and later for a complete list of possible configuration parameters for all visualization widget types. But placeholders for the three widgets in our full example would look like:

```
var yearConfig = {
...chart configuration parameters...
}

var actorConfig = {
...chart configuration parameters...
}

var mapConfig = {
...point and heat map configuration parameters...
}
```

3. Finally, activate the widget controller and the widgets themselves and close the `<script>`. `ML.controller.init` takes as its argument the variable you defined back in 1) that contains the information about the proxy server and this application's search endpoint, in this case `config`.

   `ML.chartWidget` and `ML.mapWidget` both have the same signature of widget element name, widget type, and configuration parameters variable name, and only differ in whether a chart or map widget is created.

```
ML.controller.init(config); //connect to the var with our proxy value

//chartWidget can take 'line' or 'bar' or 'column' or 'pie'
//mapWidget just takes 'map'
ML.chartWidget('decadeContainer', 'line', yearConfig);
ML.chartWidget('actorContainer', 'bar', actorConfig);
ML.mapWidget('locationContainer', 'map', mapConfig);
```

31.4.3 Initialize the Display

To initialize the widgets' display, use the use the `ML.controller.loadDat`a method of the controller:

```
ML.controller.loadData();
```

End the script with the usual `</script>`.

31.5 Example: Adding Widgets to Applications

This section describes how to add visualization widgets to an existing search application. In order to add visualization widgets, you must do the following:

- Obtain a set of files for creating the visualization widgets.
- Create an App Server that implements an instance of the MarkLogic REST API.
- Set up a proxy to connect to the REST server. For this document, we make use of a PHP server to host the proxy.
- Define a search options node to expose facet data to the widgets.
- Create an HTML page that configures and displays the widgets in your application.

It is assumed that you have a MarkLogic database set up when you begin the following process.

1. Create a database, named `restaurants`, in MarkLogic Server.

2. Create a REST server for the database, as described in Creating a REST API Instance in the *Information Studio Developer's Guide*. This will automatically create a modules database that starts with the name of the REST server, followed by `-modules`. For example, if you name the REST server `restaurants`, a database, named `restaurants-modules`, is automatically created. In this example, the REST server is located at: `myhost:5437`.

3. Using the Admin interface, create the following element range indexes in the `restaurants` database. These correspond to the facets to visualize using the widget:

scalar type	localname
`string`	`Type`
`int`	`SqFtEst`

4. Use Query Console execute the following query to load some documents into your `restaurants` database:

```
xquery version "1.0-ml";

xdmp:document-insert(
  "/1.xml",
  <restaurant>
    <id>1</id>
    <DBA> 123 Deli - Lee's </DBA>
    <Type> Restaurant, &lt; 500 sq' </Type>
    <SqFtEst> 500 </SqFtEst>
    <StreetAddress> 123 1st St </StreetAddress>
    <City> San Francisco </City>
    <State> CA </State>
    <FullAddress> 123 1st St, San Francisco CA </FullAddress>
    <Latitude>37.78946</Latitude>
    <Longitude>-122.39717</Longitude>
  </restaurant>),

xdmp:document-insert(
  "/2.xml",
  <restaurant>
    <id>2</id>
    <DBA> Dave's Dive </DBA>
    <Type> Restaurant, &lt; 700 sq' </Type>
    <SqFtEst> 700 </SqFtEst>
    <StreetAddress>2 1 Mission St </StreetAddress>
    <City> Bismarck </City>
    <State> ND </State>
    <FullAddress> 21 Mission St, Bismarck ND </FullAddress>
    <Latitude>46.48</Latitude>
    <Longitude>-100.47</Longitude>
  </restaurant>),

xdmp:document-insert(
  "/3.xml",
  <restaurant>
    <id>3</id>
    <DBA> Wayne's Steakhouse </DBA>
    <Type> Restaurant, &lt; 1000 sq' </Type>
    <SqFtEst> 1000 </SqFtEst>
    <StreetAddress> 444 Feick St </StreetAddress>
    <City> Albany </City>
    <State> NY </State>
    <FullAddress>444 Feick St, Albany NY</FullAddress>
    <Latitude>42.40</Latitude>
    <Longitude>-73.45</Longitude>
  </restaurant>),
```

```
xdmp:document-insert(
  "/4.xml",
  <restaurant>
    <id>4</id>
    <DBA> Megha </DBA>
    <Type> Restaurant, &lt; 1000 sq' </Type>
    <SqFtEst> 1000 </SqFtEst>
    <StreetAddress> 4531 Front St </StreetAddress>
    <City> Carlsbad </City>
    <State> NM </State>
    <FullAddress> 4531 Front St, Carlsbad NM </FullAddress>
    <Latitude>32.26</Latitude>
    <Longitude>-104.15</Longitude>
  </restaurant>),

xdmp:document-insert(
  "/5.xml",
  <restaurant>
    <id>5</id>
    <DBA> Gordon's Grubhaus </DBA>
    <Type> Restaurant, &lt; 300 sq' </Type>
    <SqFtEst> 300 </SqFtEst>
    <StreetAddress> 3421 Capital Wy </StreetAddress>
    <City> El Paso </City>
    <State> TX </State>
    <FullAddress> 421 Capital Wy, El Paso TX </FullAddress>
    <Latitude>31.46</Latitude>
    <Longitude>-106.28</Longitude>
  </restaurant>)
```

5. Use Query Console to load the following search options node into the `restaurants-modules` database. This exposes the facets required for the visualizations.

   Note: You must be logged into MarkLogic Server as a user with the `rest-admin` privilege to run this query.

```
xdmp:http-put("http://myhost:5437/v1/config/query/all",
<options xmlns="xdmp:http">
  <authentication method="digest">
    <username>admin</username>
    <password>admin</password>
  </authentication>
  <headers>
    <content-type>application/xml</content-type>
    <accept>application/xml</accept>
  </headers>
</options>,
text { xdmp:quote(
<options xmlns="http://marklogic.com/appservices/search">
  <constraint name="Type">
    <range type="xs:string" facet="true">
      <element ns="" name="Type"/>
      <facet-option>limit=10</facet-option>
      <facet-option>frequency-order</facet-option>
      <facet-option>descending</facet-option>
    </range>
    </constraint>
    <constraint name="SqFtEst">
      <range type="xs:int" facet="true">
        <element ns="" name="SqFtEst"/>
        <facet-option>limit=5</facet-option>
        <facet-option>frequency-order</facet-option>
        <facet-option>descending</facet-option>
      </range>
    </constraint>
</options>
) }
)
```

6. Enter the following URL, where `<server>:<rest-port>` identify your REST server. You should see an options node file with all your constraints set up.

```
http://<server>:<rest-port>/v1/config/query/all
```

7. Navigate to the public directory for your PHP-enabled Apache server. In this example, this is `/var/www/html`.

8. Download the files for the visualization widgets from:

```
http://localhost:8000/appbuilder/customappfiles.xqy
```

9. Unzip the `customappfiles.xqy` file and copy the five subfolders (constraint, css, images, lib, and skins) to the public directory for your PHP-enabled Apache server.

   Note: In this example, there is no 'application' directory, as there is in applications created by Application Builder.

10. Create a PHP proxy file, named `proxy.php`, in the public directory for your PHP-enabled Apache server with the following contents. Make sure the `CURLOPT_URL` option points to your `restaurants` server (`myhost:5437`, in this example) and that the `CURLOPT_USERPWD` option contains your login credentials for MarkLogic Server.

```
<?PHP

$queryString = $_SERVER['QUERY_STRING'];
parse_str($queryString, $vars);
unset($vars['proxyPath']);
$queryString = http_build_query($vars);

$options = array(
CURLOPT_URL => 'http://myhost:5437' . $_GET["proxyPath"] . '?' .
$queryString, // location of the rest server. Be sure to preserve the
query string unaltered

CURLOPT_HTTPAUTH => CURLAUTH_DIGEST, // it is very important to set the
authentication type to digest

CURLOPT_USERPWD => 'admin:admin', // this is your username and password
for the server. be sure your role has read permissions on the database

CURLOPT_HTTPHEADER => array('Content-type: application/json'), // the
server won't respond properly unless the content-type is
application/json
);

// Only set POST options for POSTs, not GETs
if ($_SERVER['REQUEST_METHOD'] === 'POST') {
$options[CURLOPT_POST] =  1; // queries are sent in the post body, with
options like pagination in the query string

$options[CURLOPT_POSTFIELDS] = file_get_contents('php://input'); // we
are not sending a traditional form map through the post, so avoid using
the standard $_POST
}

$ch = curl_init(); // create curl
curl_setopt_array($ch, $options); // set curl options
curl_exec($ch); // execute curl

?>
```

11. Create an HTML file with the following contents in the public directory for your PHP-enabled Apache server.

```
<html>
<head>
  <title>Custom App</title>

  <!-- external library dependencies -->
  <script src="lib/external/jquery-1.7.1.min.js"
    type="text/javascript"></script>
  <script src="lib/external/highcharts.src.js"
    type="text/javascript"></script>

  <!-- internal widget framework library -->
  <script src="lib/controller.js" type="text/javascript"></script>
  <script src="lib/widget.js" type="text/javascript"></script>

  <!-- visualization framework libraries -->
  <script src="lib/viz/chart/chart.js" type="text/javascript">
  </script>
  <link media="screen, print" href="lib/viz/chart/chart.css"
    rel="stylesheet" type="text/css">

  <style type="text/css">
    .widget {
       width: 500px; display: block; float: left;
    }
  </style>
</head>

<body>
  <h2>MarkLogic Custom Application</h2>
  <div id="typeContainer" class="widget"></div>
  <div id="sqftContainer" class="widget"></div>
  <script type="text/javascript">

<!-- If you have a proxy, identify it here. -->
  var config = { proxy: "proxy.php" };

  var typeConfig = { constraint: 'Type',
                     constraintType: 'range-unbucketed',
                     dataType: 'xs:string',
                     title: 'Type',
                     dataLabel: 'Type' };
```

```
    var sqftConfig = { constraint: 'SqFtEst',
                       constraintType: 'range-unbucketed',
                       dataType: 'xs:int',
                       title: 'Square Feet',
                       dataLabel: 'Square Feet' };

    ML.controller.init(config);
    ML.chartWidget('typeContainer', 'column', typeConfig);
    ML.chartWidget('sqftContainer', 'bar', sqftConfig);


  <!-- This will trigger the intial empty search -->
    ML.controller.loadData();
  </script>
  </body>
  </html>
```

12. Make sure all of the files in the public directory for your PHP-enabled Apache server are publicly accessible.

13. In a browser, enter the URL for your PHP-enabled Apache server host. For example:

```
http://myhost/index.html
```

14. You should see a page like the following:



31.6 Visualization Widget Limitations

There are several limitations common to most or all widget types. These are:

- Non-map widgets size to their given container and do not scroll. Map widgets can be scrolled within the map itself, just as in most common map programs. You can zoom in or out, pan left, right, up, and down, etc. This does not affect the map's container, only the view of the map itself. The map can be set so as to disable zooming or panning. Panning is restricted North to South, so you are not allowed to pan past the North or South poles.
- Non-map widgets do not support multiple-dimension visualizations (i.e. one facet per widget).
- Map results are taken from the geo facet, rather than the search results themselves. … it maybe useful to highlight that and give a screen shot of /v1/search?options=all&view=facets
- In maps, panning and zoom generate a new query that is consumed by the map to 'paint' markers and marker clusters. The reason for this approach is to have an efficient mechanism to display maps that potentially have large data sets so that data queries are incremental, rather than returning all data points.
- Tooltip behavior is defined by the chart widget and cannot be customized through Application Builder

31.7 Set Up A Proxy

In order to run a custom app, you generally need to run your queries through a proxy in order to authenticate on your MarkLogic REST server instance.

There is a proxy variable in the controller configuration that should be set to the base path of your proxy. The controller will append a 'proxyPath' URL parameter that your proxy should read. The proxyPath will point to the absolute path on the MarkLogic REST sever instance that the query needs to be proxied to. If the proxy is called with a POST, it should pass along the POST data to the MarkLogic REST server instance unchanged. It should also pass all url parameters aside from the proxyPath parameter. In the case of a GET request, just the url parameters are needed. The responses should be passed straight through unaltered.

An example PHP implementation is described in "Example: Adding Widgets to Applications" on page 649. Note that several options, such as the location of the REST server and the username and password values, may not be the same as your values. Edit the code so that it uses your values. Put this code in a publicly accessible file on your PHP server, for example, `proxy.php`, which will serve as your application's search endpoint.

After confirming you have the proxy working correctly, add a `proxy` option to the `ML.controller.init` method in your `index.html` page to identify the PHP proxy. For example:

```
ML.controller.init({proxy: "proxy.php"});
```

31.8 Widget API Reference

This section serves as a reference to the configuration options for each visualization widget and related methods. Bar, Column, Line, and Pie Charts all have the same configuration options. While it may seem odd to include Pie Charts with the others, if you consider a "slice" of a Pie Chart as serving the same basic purpose as a bar/column/datapoint on the other charts, it should make sense.

The topics in this section are:

- ML.controller Methods
- ML.createWidget (Null Widget) Method
- General Widget Methods
- ML.chartWidget Method
- ML.mapWidget Method
- Widget Events
- Widget Query Structure
- Widget Query Update Structure
- Search Results Format
- Facet Structure
- Internal Widget Events

31.8.1 ML.controller Methods

Method	Description
`init`	Takes an optional config object made up of name/value pair configuration options in the above table. All values are optional and default to those used in the application built by Application Builder.
`getData(query)`	This is the direct method to call with a query for such actions as doing an initial load of data, or wanting to reset a search for some reason. The query object is required, but can be empty. For example: `ML.controller.getData({});`
`loadData`	Performs the initial data loading on the page. Will read the url for a bookmarked query if bookmarking is enabled. Call loadData() after initializing all the widgets.

The `ML.controller.init` method has the signature:

```
ML.controller.init ({option1: value1, option2: value2...});
```

Valid options are:

Option	Description
`appWrapper`	Lets you wrap your application in a section of the page so it doesn't interfere with the rest of it. This is the uppermost element of the widget application. It defaults to the body tag, encompassing the whole page, but can be passed any jQuery selector to allow for multiple separate widget applications to be on a single page (for example, if you want to display data from different databases) or as a safety measure for preventing interference with an exiting application. Events and interactions are completely contained within the appWrapper. Default: `body`
`version`	Version of the MarkLogic Server REST API. Default: `v1`
`optionsNode`	The options node that contains the constraints being queried against. Default: `all`
`startPage`	Sets the default starting page for results pagination. This does not affect visualization widgets, just the end search results. Default: `1`
`useShadows`	Turns shadows queries on or off globally in the application. Default: `true`
`widgetClass`	This is the jQuery selector that identifies widgets within the app. Any element with the class `widget` will receive newData events automatically in the default setup. Default: `.widget`

Option	Description
`proxy`	If using a proxy, provide the path to the proxy here. See proxies section for instructions on setting up a proxy. Default: `false`
`enableBookmarking`	Turns on bookmarking support. Default: `true`
`bookmarkingDelimiters`	Delimiters to be used encoding the current query in the URL. Default: `['*_*', '*__*']`
`pageSize`	Number of results returned for a query (does not affect constraints displayed in widgets). Default: `10`

31.8.2 ML.createWidget (Null Widget) Method

The 'null widget' is the core class of a widget in the application. The role of the null widget is to handle general communication behavior and incoming data. Visualizations, such as charts and maps, as well as controls, such as the search bar or displays like the results pane, are all extensions of the basic null widget.

```
ML.createWidget(container, renderCB, datastream, constraintType)
```

Parameter	Description
`container`	Required id of the container element for the widget. Recommended to be a div.
`renderCB`	Optional A callback function to execute when the widget receives a 'newData' event. The function is passed the server's response for the purpose of rendering those results.
`datastream`	Optional* An identifier that allows a widget to respond to shadow queries. Generally should be set to the constraint name for the widget

Parameter	Description
`constraintType`	Optional* the constraintType must be set if the widget is using faceted data. It must match the type of constraint on the server's index for that constraint. Must be "range", "constraint", or "geo". Determines how the structured query is generated. Map data is always of type geo. Other data can be range or constraint, depending on whether they are range indexes or collections on the server.

*required for shadow queries to work

31.8.3 General Widget Methods

Method	Description
`updateQuery(queryUpdate)`	Takes a queryUpdate object as an argument (see controller objects above) and causes the widget to trigger an updateQuery method. Abstract method for widgets without selection that need to update the query, like a searchbox.
`getSelection()`	Returns the currently selected value of the widget if it exists, null otherwise.

31.8.4 ML.chartWidget Method

The method used to create line, bar, column, and pie widgets is:

```
ML.chartWidget(containerID, type, config);
```

Parameter	Description
`containerID`	Id of the container element for the widget. Recommended to be a `div`. (required)
`type`	Type of chart. This can be: • `line` - line chart • `bar` - bar graph • `column` - column chart • `pie` - pie chart
`config`	The configuration object consisting of the options listed in the table below.

The `ML.chartWidget` configuration options are:

Option	Description
`constraint`	Name of the constraint facet whose data the chart renders. If invalid, the chart will not render. Defaults to `""`.
`constraintType`	Type of the constraint facet whose data the chart renders. Used to construct the query. Allowed values: `range`, `constraint`, `geo`. Value must specify the type of constraint the query is being run on in order to run the search. If invalid, either the query will not execute or cause an error on the server. Defaults to `""` (no actual default value).
`title`	String of the widget's displayed title. Defaults to `""`.
`subtitle`	String of the widget's displayed subtitle. Defaults to `""`.
`dataLabel`	String of the displayed label of type of values in the graph. Defaults to `""`.
`dataType`	String of the type of data displayed in the graph. Use the datatype of the constraint in the database. To disable the setting of the range, set `dataType` to `"string"`. Takes `"string"`, `"datetime"`, `"int"`, etc. Defaults to `"string"`.

Option	Description
`includeOthers`	When `true`, an "other" category is in the chart for when results are limited. For example, when showing the top 10 actors in terms of number of Oscar nominations as well as an others category for the total number of other actors with an Oscar nomination. Takes `true` or `false` Defaults to `false`.
`othersLabel`	String of the displayed label for "other" results as described in `includeOthers`. Defaults to `"Other"`.
`hideXAxisValues`	When `true`, hides the x-axis labels otherwise seen below the graph. Useful when dense columns result in unreadable labels. *Note*: Pie Charts have no x-axis, and Column Charts' x-axis is the vertical, not horizontal, axis. Takes `true` or `false`. Defaults to `false`

31.8.5 ML.mapWidget Method

The method used to create map widgets is:

```
ML.mapWidget('locationContainer', 'map', mapConfig);
```

The following are configuration options for map widgets. They are used to define a configuration variable similar to:

```
var mapConfig = {
       constraintType: 'geo',
       dataStream: 'results',
       statusContainerId: 'debug',
       width: 698,
       height: 512,
       ...
};
```

The point map configuration options are:

Option	Description
`geoConstraint`	Define a geographic constraint on the search results. Has the value of the geo constraint from the database associated with the map. Defaults to `""`.
`mapWidth`	Width of map (and its container) in pixels. Defaults to `485`.
`mapHeight`	Height of map (and its container) in pixels. Defaults to `300`.
`mapProvider`	Source of maps. At present, only the default value for Google Maps is supported. Defaults to `"googlev3"`.

Option	Description
`zoomControlType`	Show zoom control. Takes either `"small"` or `"large"` Defaults to `"small"`.
`showMapTypes`	Show the available types of maps (satellite, road, etc.). Takes either `"true"` or `"false"`. Defaults to `"false"`.
`showSelectControls`	Show the Map widget search selection controls for selecting an area as an overlay. Takes either `"true"` or `"false"`. "Defaults to `"false"`.
`showMapControls`	Show the Map widget controls (switch from Point to Heat Map and vice versa) overlay. Takes either `"true"` or `"false"`. Defaults to `"false"`.
`minZoomLevel`	Defines lower limit of map's zoom values. Defaults to `2`.
`maxZoomLevel`	Defines upper limit of map's zoom values. Defaults to `14`.
`constrainPan`	Determines if map's pan function is constrained (i.e. if true, the visual area of the map is fixed). Takes `"true"` or `"false"`. Defaults to `"true"`.
`constrainZoom`	Determines if map's zoom function is constrained (i.e. if true, you cannot zoom in or out). Takes `"true"` or `"false"`. Defaults to `"true"`.
`autoCenterZoom`	When true, auto centers on any object on the screen (markers, polygons) Takes `"true"` or `"false"`. Defaults to `"true"`.
`showMarkersOnLoad`	When true, shows the map pointers indicating search matches when the map is loaded. Takes `"true"` or `"false"`. Defaults to `"true"`.
`showHeatmap`	Determines if the map is a Heat Map (`"true"`) or a Point Map (`"false"`). Takes `"true"` or `"false"`. Defaults to `"false"`.
`defaultMarkerIcon`	Image used to display a search result hit on a map. Takes an image file. Defaults to `"/images/map_red_shadow.png"`.

In addition to the point map options above, heat maps also have the following options:

Option	Description
`heatMapRadius`	Larger values mean each point contributes to a larger "hot" area on the map. Takes an integer. Defaults to `15`.
`heatMapOpacity`	Takes an integer between `0` and `100` (least and most opaque) that determines entity opacity. Defaults to `90`.
`searchColor`	Defines a color for lines (polygon, circle, square, etc.) in search results. Takes an HTML hexadecimal color value. Defaults to `"#FF0000"` (red).

Option	Description
`searchFillColor`	Defines a color for fill in the search results, i.e. the search polygon area. Takes an HTML hexadecimal color value. Defaults to "".
`searchOpacity`	Defines the level of opacity in the color of search result circles. Takes a value between 0 and 1 inclusive, where 0 is least opaque and 1 is most opaque. Defaults to `1`.
`searchFillOpacity`	Defines the level of search fill opacity (i.e. in the search polygon area). Takes a value between 0 and 1 inclusive, where 0 is least opaque and 1 is most opaque. Defaults to `0`.

31.8.6 Widget Events

Event	Description
`updateQuery`	This event is posted by widgets making selections. The controller listens for this event bubbling up the DOM tree on the appWrapper element. See below for the data structure of the attached JSON object.

`newData`	This event is posted to all of the application's widgets with an attached Data object of the following form:
	
	`{`
	`  data: <server results>,`
	`  query: <query object for search>`
	`}`

`newQuery`	Resets the current query to the provided query instead of updating the current search query
`getBounds`	Gets the upper and lower bounds for the provided constraint from the values endpoint on the REST server. The constraint is attached to the event

`newBounds`	Publishes a bounds object to the widgets which will set the xAxis scale of the visualization widgets using constraint in the bounds object. It has the following form:
	
	`{`
	`  min: <min_value>`
	`  max: <max_value>`
	`  constraint: <constraint>`
	`}`

31.8.7 Widget Query Structure

Query Structure (can be empty)

Field	Description
`text`	Text query that is passed directly to server unaltered. Supports all the query syntax of previous build app versions. (optional)
`facets`	An array of facet objects representing selections from widgets on the page. See Facet Structure Below (optional)
`page`	Page number for use in paginating the search results (optional)
`datastream`	Used to determine which widgets will render the query (optional)

31.8.8 Widget Query Update Structure

Field	Description
`facet`	Name of the facet/constraint to update
`value`	Name of the selected value within the facet to search on
`text`	Text query that is passed directly to server unaltered. Supports all the query syntax of previous build app versions.
`constraintType`	Must be "range", "constraint", or "geo". Determines how the structured query is generated. Map data is always of type geo. Other data can be range or constraint, depending on whether they are range indexes or collections on the server.

31.8.9 Search Results Format

The search results format (REST API)

Field	Description
`total`	Total results returned by the search
`start`	Result number of the first returned result
`page-length`	Number of results returned in this query
`results`	Array of result objects

Field	Description

`facets`	List of all facets and facet-results for the search.
	
	`<facet-name>: {`
	`type: "xs:<data-type>",`
	`facetValues: [`
	`{name: <record name>, count: <int>},`
	`…`
	`]`
	`}`

`report`	String report with information about the query.
`metrics`	Metrics on the search from the server

31.8.10 Facet Structure

\

Field	Description
value	'name' of facet value that is selected and will be used to update the search. For example, in the actors facet of the Oscars app, this might be "Humphrey Bogart"
constraintType	Must be "range", "constraint", or "geo". Determines how the structured query is generated. Map data is always of type geo. Other data can be range or constraint, depending on whether they are range indexes or collections on the server.
geo	The geo property contains one of the following: • `geo.poly` - an array of lat/lng points • `geo.box` - 4 properties: north, south, east, west; whose values are lat/lng points • `geo.circle` - radius and a point object with latitude and longitude.

31.8.11 Internal Widget Events

Event	Description

`selection`	Selection events are caught by the widget container and used to generate queryUpdate events (see controller events). A selection event has an attached selection object of the following form:
	
	`{ facet:`
	`  <facet name>,`
	`  value: <selected value>`
	`}`
	
	To unselect, simply pass a facet with no value property like so:
	
	`{facet: "decade"}`

`page`	Page events are used for adjusting the pagination of the search results. The data passed along with the event has a page property that specifies the page number to display.

32.0 Appendix: Query Options Reference

This appendix is a reference guide to the query options used for search and lexicon analysis by the XQuery Search API and the MarkLogic Client APIs (REST, Java, Node.js). This appendix contains the following topics:

- How to Use This Reference
- Options Summary
- additional-query
- concurrency-level
- constraint
- debug
- default-suggestion-source
- extract-document-data
- forest
- fragment-scope
- grammar
- operator
- page-length
- quality-weight
- result-decorator
- return-aggregates
- return-constraints
- return-facets
- return-frequencies
- return-metrics
- return-plan
- return-qtext
- return-query
- return-results
- return-similar
- return-values
- search-option

- searchable-expression
- sort-order
- suggestion-source
- term
- transform-results
- tuples
- values
- Term Options
- Facet Options
- Range Options
- Geospatial Options
- Suggestion Options
- Values Options

32.1 How to Use This Reference

This reference describes the layout of the query options structure usable with search and lexicon query interfaces of the XQuery Search API (`search:search`, `search:values`, etc.) and the Client APIs (REST, Java, Node.js). Both XML and JSON representations are shown, but not all APIs support both representations; consult the reference for the API you're using.

Some of the APIs provide builders for constructing query options, so you do not need to know the syntax. However, this appendix can still be useful with a builder because it provides details on the meaning, defaults, and limits for specific option components.

The Syntax Summary for each option shows all possible components, but not all are required and some cannot be used together. Refer to the Component Description section for details on a given option.

Option components that can be specified as repeating XML elements are usually represented by array values in JSON. In many cases, you can omit the array wrapper if there is only one element.

32.2 Options Summary

A single options node or object can contain can contain options useful for document searches, lexicon and index queries, and/or search term completion suggestions. However, not all options are used by all operations. For example, the `values` and `tuples` options only apply to lexicon query operations (`search:values`), `default-suggestion-source` only applies to search term completion suggestion operations (`search:suggest`), and `extract-document-data` only applies to document searches (`search:search`).

A set of query options has the following structure. You can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<options>`
`  anyOption...`
`</additional-query>`
	`{"options": {`
	`  anyOption, ...`
	`}`

Where *anyOption* is zero or more of the child components summarized in the following table. For more details about a given option, see the option-specific topic.

Key	Description
additional-query	Additional serialized cts:query's, as XML literals. This option has array value in JSON and can appear multiple times in XML.
concurrency-level	The maximum number of threads used to resolve facets.
constraint	Zero or more constraints that limit the scope of a search and/or define facets which can be returned as part of the search results. This option has array value in JSON and can appear multiple times in XML.
debug	Whether or not to enable debugging mode. The default is `false`.
default-suggestion-source	Defines the content to be used as the default source of suggestions (see `search:suggest`).
extract-document-data	Specify element, attribute, or JSON property content from the search matches to return.
forest	One or more forest IDs. This option has array value in JSON and can appear multiple times in XML.
fragment-scope	Controls the global fragment scope over which to search.
grammar	A custom search grammar definition.
operator	A list of state elements, each representing a unique run-time configuration option. This option has array value in JSON and can appear multiple times in XML.

Key	Description
page-length	The number of results to return per page. The default value is 10.
quality-weight	Specifies a a weighting factor to use in the query. The default value is 1.0.
return-aggregates	Include the result of running a builtin or user-defined aggregate function. Applies only to queries against values or tuples.
return-constraints	Include the input constraint definitions in the results. The default is false.
return-facets	Include resolved facets in the results. The default is true.
return-frequencies	Include frequencies in the results. The default is true.
return-metrics	Include performance statistics in the results. The default is true.
return-plan	Include `xdmp:plan` output in the results. The default is false.
return-qtext	Include the original query text in the results. The default is true.
return-query	Include the XML query representation in the results. The default is false.
return-results	Include search results in the output. The default is true.
return-similar	Include with each search result a list of URLs of similar documents in the database. The default is false.
return-values	When querying a range index or values lexicon, whether or not to include the index/lexicon values in the results. Default: true.
search-option	For advanced users, one or more options to pass to the underlying query operation. This option has array value in JSON and can appear multiple times in XML.
searchable-expression	An XPath expression to be searched. Whatever expression is specified is returned from the search.
sort-order	Set the default sort order. The first such value is the primary sort order, the second is secondary sort order, and so on. This option has array value in JSON and can appear multiple times in XML.

Key	Description
suggestion-source	Specify a search term completion suggestion source.
transform-results	Specify a function to use to process a search result for the snippet output.
tuples	Define one or more value lexicons query against, matching value co-occurrences. That is, tuples of values, each of which appear in the same fragment.
values	Define one or more value lexicons to query against.

32.3 additional-query

Use this option to specify one or more additional cts queries to apply when searching documents and generating suggestions. The queries are AND'd with the input query. The query results are constrained by the `additional-query`(s).

Specify each additional query value as the serialized XML representation of a `cts:query`.

- Syntax Summary
- Component Description
- Examples
- See Also

32.3.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<additional-query>`
`  serialized-cts-query`
`</additional-query>`
	`"additional-query": [`
	`  "serialized-cts-query"`
	`]`

32.3.2 Component Description

The text value that represents each additional query is a serialized `cts:query`. In XML options, it is represented as XML. In JSON options, it is a string containing the serialized XML.

If your query options include multiple additional queries, they are AND'd together, as if with `cts:and-query`.

32.3.3 Examples

The following example constrains the results to the directory named `/my/directory/`. Whitespace and linebreaks are added for readability.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <additional-query>`
	`  <cts:directory-query xmlns:cts="http://marklogic.com/cts">`
	`  <cts:uri>/my/directory/</cts:uri>`
	`  </cts:directory-query>`
	`  </additional-query>`
	`</options>`

JSON	`{"options": {`
	`  "additional-query":[`
	`  "<directory-query xmlns='http://marklogic.com/cts'>`
	`  <uri>/my/directory/</uri>`
	`  </directory-query>"`
	`  ]`
	`}}`

32.3.4 See Also

For more details, see the following topics:

- "XML Serializations of cts:query Constructors" on page 274
- "Understanding cts:query" on page 240
- The built-in functions in the `cts` namespace in the *XQuery and XSLT Reference Guide*

32.4 concurrency-level

The maximum number of threads to use when resolving facets. The default is 8, which specifies that at most 8 threads will be used concurrently to resolve facets. The value of this option should be an integer value greater than 0. The default value is 8.

The following example specifies a concurrency level of 16.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <concurrency-level>16</concurrency-level>`
	`</options>`

JSON	`{"options": {`
	`  "concurrency-level": 16`
	`}}`

32.5 constraint

This option forms the outer container for a constraint definition. Use constraints to limit the scope of a search and/or define facets that can be returned as part of the search results. Constraints can also be applicable when generating search suggestions. No constraints are defined by default.

Each constraint must include a name that is unique among the options in scope for a search. The constraint name can be used as a term qualifier in a string query; for details, see "Searching Using String Queries" on page 65. The name can also be used to identify the constraint in some kinds of structured queries and QBE's.

This section includes the following high level topics about the constraint option:

- Syntax Summary
- Component Description
- Examples
- See Also

This section also includes detailed descriptions of each of the following constraint types and the more complex components of range and geospatial constraints, such as bucket, computed-bucket, and heatmap.

- range
- value
- word
- collection
- container
- element-query
- properties

- geo-attr-pair
- geo-elem
- geo-elem-pair
- geo-json-property
- geo-json-property-pair
- geo-path
- custom
- heatmap
- bucket
- computed-bucket
- path-index

32.5.1 Syntax Summary

This option has the following structure. Each constraint must include a name and exactly one constraint specification. An options node can define multiple constraints. In JSON, the `constraint` array can be empty. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<constraint name="`*uniqueName*`">` `  <annotation/>` `  `*anyConstraintType* `</constraint>`	`"constraint": [` `  {"name": "`*uniqueName*`",` `  "annotation": `*string*`,` `  *anyConstraintType* ` }` `]`

Where *anyConstraintType* is one of the following constraint specifications:

- range
- value
- word
- collection
- container
- element-query
- properties

- geo-attr-pair
- geo-elem
- geo-elem-pair
- geo-json-property
- geo-json-property-pair
- geo-path
- custom

32.5.2 Component Description

The components of this option have the following semantics. A constraint can contain the following child elements or properties.

Element, Attribute or Property Name	Description
`name`	Required. An identifier for the constraint. The name must be unique within the in-scope query options and may not contain whitespace.
`annotation`	Your comments. Annotations have no effect on a query.
`anyConstraintType`	A constraint specification. For a list of constraint types, see “Syntax Summary” on page 675.

32.5.3 Examples

The following example defines two constraints: a container constraint that limits matches to those that occur within an XML element named “TITLE”, and a value constraint that limits matches to the values in an XML element named “COST”. For more examples, refer to the individual constraint types.

Format	Example
XML	<options xmlns="http://marklogic.com/appservices/search"> <constraint name="title"> <container> <element ns="" name="TITLE" /> </container> </constraint> <constraint name="cost"> <value> <element ns="" name="COST" /> </value> </constraint> </options>

JSON	{"options": {
	  "constraint": [
	  { "name": "title",
	  "container": {
	  "element": {
	  "ns": "",
	  "name": "TITLE"
	  }}},
	  { "name": "cost",
	  "value": {
	  "element": {
	  "ns": "",
	  "name": "COST"
	  }}}
	  ]
	}}

32.5.4 See Also

For more details, see the following topics and the See Also topics for individual constraint types.

- “Constraint Options” on page 369

32.5.5 range

A component of a constraint option that specifies an XML element, XML element attribute, field, JSON property, or XPath expression on which to constrain by range, as in a range query.

There must be a range index of the specified type (and collation for string range indexes) defined for the specified element, attribute, JSON property, field, or path.

For best performance of range constraints that include `bucket` or `computed-bucket` specifications, define the buckets in a consistent, sorted order (ascending or descending). If the order is not consistent, then the bucketed results are returned in the order specified, regardless of any sorting `facet-option` in the specification.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.5.1 Syntax Summary

This option has the following structure. The definition must include exactly one of `element`, `field`, `json-property`, or `path-index` descriptor. If there is an `element`, an `attribute` descriptor may also be included. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<range type="indexedType"`
`collation="collURI"`
`facet="boolean"`
`nullable="boolean">`
`<element ns="namespace" name="name"/>`
`<attribute ns="namespace" name="name"/>`
`<field name="name"/>`
`<json-property>name</json-property>`
`<path-index/>`
`<fragment-scope>scope</fragment-scope>`
`<bucket/>`
`<computed-bucket/>`
`<facet-option>option</facet-option>`
`<range-option>option</range-option>`
`</range>`
	`"range": {`
	`"type": string,`
	`"collation" : string,`
	`"facet": boolean,`
	
	`"element": {`
	`"ns": "namespace",`
	`"name": "name"`
	`},`
	`"attribute": {`
	`"ns": "namespace",`
	`"name": "name"`
	`},`
	`"field": {"name": "name"},`
	`"json-property": "name",`
	`"path-index": [path index desc],`
	`"fragment-scope": "scope",`
	`"bucket": [bucket descriptor],`
	`"computed-bucket": [bucket desc],`
	`"facet-option" : [ "option" ],`
	`"range-option": [ "option" ],`
	`"nullable" : boolean`
	`}`

32.5.5.2 Component Description

The components of this option have the following semantics. The definition must include exactly one of `element`, `json-property`, `field`, or `path-index`. All other components are optional.

Element, Attribute or Property Name	Description
`type`	The type of the values in the associated index. The database configuration must include a range index with this type. Use collation to further disambiguate range indexes of type `xs:string`.
`collation`	A collation URI. If this value is present, the database configuration should include a range index of type `xs:string` that uses this collation. If not specified, the default Root Collation is assumed. For details, see "Collations" on page 617.
`facet`	Whether or not to include facets based on this constraint in the query results.
`nullable`	Whether or not to allow null values in tuples when making a values query.
`element`	Defines an XML element to constrain by. If there is an `element`, there can also be an `attribute`. Specify the element local name in `name`. If the element is in a namespace, specify the namespace URI in `ns`. The database configuration must include a corresponding element or element attribute range index.
`attribute`	Defines an XML element attribute to constrain by. There must be an accompanying `element` descriptor. Specify the attribute local name in `name`. If the attribute is in a namespace, specify the namespace URI in `ns`. The database configuration must include a corresponding element attribute range index.
`json-property`	Defines a JSON property to constrain by. The database configuration must include a corresponding element range index. (JSON properties are indexed using element range indexes.)
`field`	Defines a field to constrain by. The database configuration must include a corresponding field range index.

Element, Attribute or Property Name	Description
`path-index`	Defines a reference to a path range index (by XPath expression). For details, see "path-index" on page 735. The database configuration must include a corresponding path range index.
`fragment-scope`	Set a local fragment scope for this constraint. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).
`bucket`	Zero or more named ranges of static values. For details, see "bucket" on page 727.
`computed-bucket`	Zero or more named ranges of dynamic values. For details, see "computed-bucket" on page 731.
`facet-option`	Specify faceting options to apply when generating facets. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see "Facet Options" on page 796.
`range-option`	Specify range options that influence the interpretation of the constraint. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<range-option>min-occurs=2</range-option>` in XML, or `"range-option": ["min-occurs=2"]` in JSON. For details, see "Range Options" on page 797.

32.5.5.3 Examples

This section contains an example contains one of each type of range constraint and an example that demonstrates the use of faceting options. For more examples, see "bucket" on page 727 and "computed-bucket" on page 731.

The following example includes one of each basic type of range constraint: element, element attribute, JSON property, field, and path index. The database configuration must include a range index that corresponds to each constraint.

Format	Example

XML	<options xmlns="http://marklogic.com/appservices/search">
	  <constraint name="elem">
	  <range type="xs:string">
	  <element ns="myNsURI" name="anElemName"/>
	  </range>
	  </constraint>
	  <constraint name="attr">
	  <range type="xs:string">
	  <element ns="myNsURI" name="anElemName"/>
	  <attribute ns="myNsURI" name="anAttrName" />
	  </range>
	  </constraint>
	  <constraint name="json-prop">
	  <range type="xs:string">
	  <json-property>aPropName</json-property>
	  </range>
	  </constraint>
	  <constraint name="field">
	  <range type="xs:string"
	  collation="http://marklogic.com/collation/codepoint">
	  <field name="aFieldName"/>
	  </range>
	  </constraint>
	  <constraint name="path">
	  <range type="xs:gYear" facet="true">
	  <path-index xmlns:my="http://example.com">
	  /publication/my:meta/my:year
	  </path-index>
	  </range>
	  </constraint>
	</options>

Format	Example

JSON	{"options": {
	  "constraint": [
	  { "name": "elem",
	  "range": {
	  "type": "xs:string",
	  "element": { "ns": "myNsURI", "name": "anElemName" }
	  }},
	  { "name": "attr",
	  "range": {
	  "type": "xs:string",
	  "element": { "ns": "myNsURI", "name": "anElemName" },
	  "attribute": { "ns": "myNsURI", "name": "anAttrName" }
	  }},
	  { "name": "json-prop",
	  "range": {
	  "type": "xs:string",
	  "json-property": { "name": "aPropName" }
	  }},
	  { "name": "field",
	  "range": {
	  "type": "xs:string",
	  "collation": "http://marklogic.com/collation/codepoint",
	  "field": { "name": "aFieldName" }
	  }},
	  { "name": "path",
	  "range": {
	  "type": "xs:gYear",
	  "facet": true,
	  "path-index": {
	  "namespaces": {"my": "http://example.com"},
	  "text": "/publication/my:meta/my:year"
	  }
	  }}
	  ]
	}}

The following example defines a constraint that is used to generate facets. The `facet-option` values are passed to the underlying lexicon calls.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="color">`
	`  <range type="xs:string" facet="true">`
	`  <element ns="myNsURI" name="bodycolor"/>`
	`  <facet-option>frequency-order</facet-option>`
	`  <facet-option>descending</facet-option>`
	`  </range>`
	`  </constraint>`
	`  <constraint name="owner">`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [`
	`  { "name": "color",`
	`  "range": {`
	`  "type": "xs:string",`
	`  "facet": true,`
	`  "element": { "ns": "myNsURI", "name": "bodycolor" },`
	`  "facet-option": [ "frequence-order", "descending" ]`
	`  }}]`
	`}}`

32.5.5.4 See Also

For more details on using this option, see the following topics:

- “Constrained Searches and Faceted Navigation” on page 32
- “Constraint Options” on page 369
- “Using Relational Operators on Constraints” on page 70
- “Support for Multiple Query Types” on page 24

32.5.6 value

A component of a constraint option that specifies a XML element, XML attribute, JSON property, or field on which to constrain, as in a value query. For JSON property constraints, you can optionally specify a node using `value/@type`. If present, type must be one of `string` (default), `number`, `boolean`, or `null`. You cannot create facets from a value constraint.

- Syntax Summary
- Component Description
- Examples

- See Also

32.5.6.1 Syntax Summary

A value constraint definition has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<value type="jsonNodeType">`
`  <element ns="namespace" name="name"/>`
`  <attribute ns="namespace" name="name"/>`
`  <field name="fieldName"/>`
`  <json-property>name</json-property>`
`  <fragment-scope>scope</fragment-scope>`
`  <weight>double</weight>`
`  <term-option>option</term-option>`
`</value>`
	`"value": {`
	`  "type": "jsonNodeType"`
	`  "element": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "attribute": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "json-property": "name",`
	`  "field": {"name": "fieldName"},`
	`  "fragment-scope": "scope",`
	`  "weight": double,`
	`  "fragment-scope": "scope",`
	`  "term-option": [ "option" ]`
	`}`

32.5.6.2 Component Description

The components of this option have the following semantics. The definition must include exactly one of `element`, `json-property`, or `field`. If there is an `element`, there can also be an `attribute`.

Element, Attribute or Property Name	Description
`type`	A JSON node type, one of `string` (default), `boolean`, `null`, `number`. Only meaningful for JSON content. Use `type` to constrain the matches to values in this node type. Non-JSON documents never contain nodes of these types. Optional.
`element`	Defines an XML element on which to constrain queries If there is an `element`, there can also be an `attribute`. Specify the element local name in `name`. If the element is in a namespace, specify the namespace URI in `ns`.
`attribute`	Defines an XML element attribute on which to constrain queries. There must be an accompanying `element` descriptor. Specify the attribute local name in `name`. If the attribute is in a namespace, specify the namespace URI in `ns`.
`json-property`	Defines a JSON property on which to constrain queries.
`field`	Defines a field on which to constrain queries.
`weight`	Higher weights move search results up in the relevance order. The default is 1.0. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64); weights greater than 64 will have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.
`fragment-scope`	Set a local fragment scope for this constraint. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).
`term-option`	Specify options to apply when generating facets. In XML, specify multiple options by including the element multiple times. If the option has a value, the element or array item value is of the form *`option=value`*. For example: `<term-option>lang=en</term-option>` in XML, or `"term-option": ["lang=en"]` in JSON. “Term Options” on page 796.

32.5.6.3 Examples

The following example includes a value constraint of each type: element, element attribute, JSON property, and field.

Format	Example
XML	<options xmlns="http://marklogic.com/appservices/search"> <constraint name="my-elem-value"> <value> <element ns="my-namespace" name="my-localname"/> </value> </constraint> <constraint name="my-attr-value"> <value> <attribute ns="" name="my-attribute"/> <element ns="my-namespace" name="my-localname"/> </value> </constraint> <constraint name="my-json-value"> <value type="number"> <json-property>myNumericPropName</json-property> </value> </constraint> <constraint name="my-field-value"> <value> <field name="fieldvalue"/> <weight>2.0</weight> </value> </constraint> </options>

Format	Example

JSON	<pre>{"options": {
	  "constraint": [
	  { "name": "my-elem-value",
	  "value": {
	  "element": {"ns": "my-namespace","name": "my-localname"}
	  }},
	  { "name": "my-attr-value",
	  "value": {
	  "element": {"ns": "my-namespace","name": "my-localname"},
	  "attribute": {"ns": "","name": "my-attribute"}
	  }},
	  { "name": "my-json-value",
	  "value": {
	  "type": "number",
	  "json-property": "myNumericPropName"
	  }},
	  { "name": "my-field-value",
	  "value": {
	  "field": {"name": "fieldName"},
	  "weight": 2.0
	  }}
	  ]
	}}</pre>

32.5.6.4 See Also

For more details on using this option, see the following topics:

- “Constraint Options” on page 369
- “Value Constraint Example” on page 376
- “Support for Multiple Query Types” on page 24

32.5.7 word

A component of a constraint option that specifies the XML element, XML element attribute, JSON property, or field on which to constrain by word. You cannot create facets from a word constraint.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.7.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<word>`
`  <element ns="namespace" name="name"/>`
`  <attribute ns="namespace" name="name"/>`
`  <field name="name"/>`
`  <json-property>name</json-property>`
`  <fragment-scope>scope</fragment-scope>`
`  <weight>double</weight>`
`  <term-option>option</term-option>`
`</word>`
	`"word": {`
	`  "element": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "attribute": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "json-property": "name",`
	`  "field": {"name": "name"},`
	`  "fragment-scope": "scope",`
	`  "weight": double,`
	`  "fragment-scope": "scope",`
	`  "term-option": [ "option" ]`
	`}`

32.5.7.2 Component Description

The child components of this option have the following semantics:

Element, Attribute or Property Name	Description
`element`	Defines an XML element on which to constrain queries If there is an `element`, there can also be an `attribute`. Specify the element local name in `name`. If the element is in a namespace, specify the namespace URI in `ns`.
`attribute`	Defines an XML element attribute on which to constrain queries. There must be an accompanying `element` descriptor. Specify the attribute local name in `name`. If the attribute is in a namespace, specify the namespace URI in `ns`.
`json-property`	Defines a JSON property on which to constrain queries.

Element, Attribute or Property Name	Description
`field`	Defines a field on which to constrain queries.
`weight`	Higher weights move search results up in the relevance order. The default is 1.0. The weight should be less than or equal to 64 and greater than or equal to -16 (between -16 and 64); weights greater than 64 will have the same effect as a weight of 64. Weights less than the absolute value of 0.0625 (between -0.0625 and 0.0625) are rounded to 0, which means that they do not contribute to the score.
`fragment-scope`	Set a local fragment scope for this constraint. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).
`term-option`	Specify options to apply when generating facets. In XML, specify multiple options by including the element multiple times. If the option has a value, the element or array item value is of the form *`option=value`*. For example: `<term-option>lang=en</term-option>` in XML, or `"term-option": ["lang=en"]` in JSON. For details, see “Term Options” on page 796.

32.5.7.3 Examples

The following example includes a word constraint of each possible type (element, element attribute, JSON property, and field). The JSON property constraint demonstrates the use of term options. The field constraint demonstrates the use of a custom weight.

Format	Example
XML	<options xmlns="http://marklogic.com/appservices/search"> <constraint name="my-elem-value"> <word> <element ns="my-namespace" name="my-localname"/> </word> </constraint> <constraint name="my-attr-value"> <word> <attribute ns="" name="my-attribute"/> <element ns="my-namespace" name="my-localname"/> </word> </constraint> <constraint name="my-json-value"> <word> <json-property>myPropName</json-property> <term-option>case-sensitive</term-option> <term-option>unstemmed</term-option> </word> </constraint> <constraint name="my-field-value"> <word> <field name="fieldvalue"/> <weight>2.0</weight> </word> </constraint> </options>

Format	Example

JSON	<pre>{"options": {
	  "constraint": [
	  { "name": "my-elem-value",
	  "word": {
	  "element": {"ns": "my-namespace","name": "my-localname"}
	  }},
	  { "name": "my-attr-value",
	  "word": {
	  "element": {"ns": "my-namespace","name": "my-localname"},
	  "attribute": {"ns": "","name": "my-attribute"}
	  }},
	  { "name": "my-json-value",
	  "word": {
	  "json-property": "myPropName",
	  "term-option": ["case-sensitive", "unstemmed"]
	  }},
	  { "name": "my-field-value",
	  "value": {
	  "field": {"name": "fieldName"},
	  "weight": 2.0
	  }}
	  ]
	}}</pre>

32.5.7.4 See Also

For more details on using this option, see the following topics:

- “Constraint Options” on page 369
- “Word Constraint Examples” on page 376
- “Support for Multiple Query Types” on page 24

32.5.8 collection

A component of a constraint option that constrains results by collection, matching either documents in the specified collections or in collections with the specified collection URI prefix.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.8.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<collection prefix="URIpfx" facet="boolean">`
`  <facet-option>`*`option`*`</facet-option>`
`</collection>`
	`"collection": {`
	`  "prefix": "`*`URIprefix`*`",`
	`  "facet-option": [ "`*`option`*`" ],`
	`  "facet": `*`boolean`*
	`}`

32.5.8.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`prefix`	Constrain matches to collections with collection URIs matching this prefix. Use this component to as shorthand when constraining by collections with a shared URI prefix. For details, see “Examples” on page 693.
`facet`	Whether or not to generate facets from this constraint. Default: true.
`facet-option`	Specify options to apply when generating facets. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. “Facet Options” on page 796.

32.5.8.3 Examples

The following example defines a constraint that limits results to matches in documents in collections with the URI prefix "/my/collection/". The constraint also indicates facets should be generated using the collection (`facet` is true). The facet option `limit` specifies that at most 5 results are returned.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="mycoll" facet="true">`
	`  <collection prefix="/my/collection/"/>`
	`  <facet-option>limit=5</facet-option>`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [`
	`  { "name": "mycoll",`
	`  "collection": {`
	`  "prefix": "/my/collection/",`
	`  "facet": true,`
	`  "facet-option": [ "limit=5" ]`
	`  }}`
	`  ]`
	`}}`

For example, if your database includes documents in the collections "/my/collection/animals" and "/my/collections/edibles", then the following string query text matches documents containing the term "aardvark" that are also in the collection "/my/collection/animals".

```
mycoll:animals AND aardvark
```

Omit the prefix to constrain on complete collection URIs. For example, if you omit `prefix` from the above constraint definition, then you would find the same documents with the following query text:

```
mycoll:/my/collection/animals AND aardvark
```

32.5.8.4 See Also

For more details on using this option, see the following topics:

- "Collection Constraint Example" on page 377
- "Collections" on page 536
- "Constraint Options" on page 369
- `cts:collection-query`

32.5.9 container

A component of a constraint option that specifies a constraint that restricts a search to a specified XML element or JSON property container. You cannot create facets from a container constraint.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.9.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<container>`
`  <element ns="`*`namespace`*`" name="`*`name`*`"/>`
`  <json-property>`*`name`*`</json-property>`
`  <fragment-scope>`*`scope`*`</fragment-scope>`
`</container>`
	`"container": {`
	`  "element": {`
	`  "ns": "`*`namespace`*`",`
	`  "name": "`*`name`*`"`
	`  },`
	`  "json-property": "`*`name`*`",`
	`  "fragment-scope": "`*`scope`*`"`
	`}`

32.5.9.2 Component Description

The components of this option have the following semantics. The constraint must include exactly one of `element` or `json-property`.

Element, Attribute or Property Name	Description
`element`	Defines an XML element on which to constrain queries. Specify the element local name in `name`. If the element is in a namespace, specify the namespace URI in `ns`.
`json-property`	Defines a JSON property on which to constrain queries.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.9.3 Examples

The following example includes two container constraints, one on an XML element and one on a JSON property.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="ele-container-constraint">`
	`  <container>`
	`  <element name="title" ns="http://my/namespace" />`
	`  </container>`
	`  </constraint>`
	`  <constraint name="json-container-constraint">`
	`  <container>`
	`  <json-property>author</json-property>`
	`  </container>`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [`
	`  { "name": "ele-container-constraint",`
	`  "container": {`
	`  "element": {"ns": "http://my/namespace","name": "title"}`
	`  }},`
	`  { "name": "json-container-constraint",`
	`  "container": {`
	`  "json-property": "author",`
	`  }}`
	`  ]`
	`}}`

32.5.9.4 See Also

For more details on using this option, see the following topics:

- “Constraint Options” on page 369
- “Support for Multiple Query Types” on page 24

32.5.10 element-query

A component of a constraint option that specifies a constraint that restricts the search to the specified element. You cannot create facets from an `element-query` constraint.

> **Note:** This option is deprecated. Use container instead.

- Syntax Summary
- Component Description

- Examples

32.5.10.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<element-query ns="namespace" name="name"/>`
`  <fragment-scope>scope</fragment-scope>`
`</element-query>`
	`"element-query": {`
	`  "ns": "namespace",`
	`  "name": "name",`
	`  "fragment-scope": "scope"`
	`}`

32.5.10.2Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`ns`	The namespace of the element, if it is in a namespace.
`name`	Required. The local name of the element.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.10.3Examples

The following example demonstrates an element-query constraint on the element “title” in the namespace `http://my/namespace`. This option is deprecated; use container instead.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="elem-constraint">`
	`  <element-query name="title" ns="http://my/namespace" />`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [`
	`  { "name": "elem-constraint",`
	`  "element-query": {`
	`  "ns": "http://my/namespace",`
	`  "name": "title"`
	`  }}`
	`  ]`
	`}}`

32.5.11 properties

A component of a constraint option that limits matches to those found in document properties. To constrain by JSON property, see “container” on page 694.

- Syntax Summary
- Examples
- See Also

32.5.11.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON
All elements are in the namespace `http://marklogic.com/appservices/search`. `<properties/>`	`{ "properties": null }`

32.5.11.2Examples

The following example limits matches to those found in document properties.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="prop-constraint">`
	`  <properties />`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [{`
	`  "name": "prop-constraint",`
	`  "properties": null" }`
	`  }]`
	`}}`

32.5.11.3See Also

For more details on using this option, see the following topics:

- “Constraint Options” on page 369
- “Support for Multiple Query Types” on page 24
- `cts:properties-fragment-query`

32.5.12 geo-attr-pair

A component of a constraint option that models a geospatial index with coordinates stored as XML element attributes. That is, geospatial data of the following form:

```
<parent lat="value" lon="value">
```

For similar JSON data, use geo-json-property-pair.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.12.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-attr-pair>`
`  <parent ns="namespace" name="elemName" />`
`  <lat ns="namespace" name="attrName" />`
`  <lon ns="namespace" name="attrName" />`
`  <facet-option>option</facet-option>`
`  <heatmap>heatmap descriptor</heatmap>`
`  <fragment-scope>scope</fragment-scope>`
`  <geo-option>option</geo-option>`
`</geo-attr-pair>`
	`"geo-attr-pair": {`
	`  "parent": [{`
	`  "ns": "namespace",`
	`  "name": "elemName",`
	`  }],`
	`  "lat": [{`
	`  "ns": "namespace",`
	`  "name": "attrName",`
	`  }],`
	`  "lon": [{`
	`  "ns": "namespace",`
	`  "name": "attrName",`
	`  }],`
	`  "facet-option": [ option ],`
	`  "heatmap": {heatmap desc},`
	`  "geo-option": [ option ],`
	`  "fragment-scope": "scope",`
	`}`

32.5.12.2Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-point`" to the query options configuration. For more details, see `cts:element-attribute-pair-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`parent`	Required. Identifies an element that can contain the latitude and longitude attributes. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple parents are defined, the query matches if any one of them matches. This component can have array value in JSON.
`lat`	Required. Identifies the attribute of `parent` that contains the latitude value. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple elements are defined, the query matches if any one of them matches. However, only the first matching latitude attribute in any point instance is checked. This component can have array value in JSON.
`lon`	Required. Identifies the attribute of `parent` that contains the longitude value. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple elements are defined, the query matches if any one of them matches. However, only the first matching longitude attribute in any point instance is checked. This component can have array value in JSON.

Element, Attribute or Property Name	Description
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see "heatmap" on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see "Facet Options" on page 796.
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see "Geospatial Options" on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.12.3Examples

The following example defines a geospatial element attribute pair constraint named "my-geo-attr-pair". Facets will be generated for the constraint, using the region defined in the `heatmap`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-attr-pair">`
	`  <geo-attr-pair>`
	`  <parent ns="ns1" name="my-elem"/>`
	`  <lat ns="ns2" name="attr1"/>`
	`  <lon ns="ns2" name="attr2"/>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-attr-pair>`
	`  </constraint>`
	`</options>`

JSON	`{"options":{`
	`  "constraint": [{`
	`  "name": "my-geo-attr-pair",`
	`  "geo-attr-pair": {`
	`  "parent": { "ns": "ns1", "name": "my-elem" },`
	`  "lat": { "ns": "ns2", "name": "attr1" },`
	`  "lon": { "ns": "ns3", "name": "attr2" },`
	`  "facet-option": [ "empties" ],`
	`  "heatmap": {`
	`  "s": 23.2, "w": -118.3, "n": 23.3, "e": -118.2,`
	`  "latdivs": 4, "londivs": 4`
	`  }`
	`  }`
	`  }]`
	`}}`

32.5.12.4See Also

For more details on using this option, see the following topics:

- `cts:element-attribute-pair-geospatial-query`
- "Constraint Options" on page 369
- "Geospatial Search Applications" on page 462

32.5.13 geo-elem

A component of a constraint option that models a geospatial index with coordinates stored in a single XML element. That is, geospatial data with the following structure. The specification of a parent element is optional.

```
<parent>
  <elem>lat-lon-values</elem>
</parent>
```

For similar JSON data, use geo-json-property.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.13.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-elem>`
`  <parent ns="namespace" name="elemName" />`
`  <element ns="namespace" name="elemName" />`
`  <facet-option>option</facet-option>`
`  <heatmap>heatmap descriptor</heatmap>`
`  <fragment-scope>scope</fragment-scope>`
`  <geo-option>option</geo-option>`
`</geo-elem>`
	`"geo-attr-pair": {`
	`  "parent": [{`
	`  "ns": "namespace",`
	`  "name": "elemName",`
	`  }],`
	`  "element": [{`
	`  "ns": "namespace",`
	`  "name": "elemName",`
	`  }],`
	`  "facet-option": [ option ],`
	`  "heatmap": {heatmap desc},`
	`  "geo-option": [ option ],`
	`  "fragment-scope": "scope"`
	`}`

32.5.13.2Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-point`" to the query options configuration. For more details, see `cts:element-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`parent`	Optional. Identifies an element that can contain the latitude and longitude elements. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple parents are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`element`	Required. Identifies the element containing the latitude and longitude values. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple elements are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see “heatmap” on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see “Facet Options” on page 796.
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see “Geospatial Options” on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.13.3Examples

The following example defines two `geo-elem` constraints, one without a parent element specification and one with a parent element specification.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-elem">`
	`  <geo-elem>`
	`  <element ns="ns1" name="my-elem"/>`
	`  <geo-option>type=long-lat-point</geo-option>`
	`  </geo-elem>`
	`  </constraint>`
	`  <constraint name="my-geo-elem-child">`
	`  <geo-elem>`
	`  <parent ns="ns1" name="the-parent"/>`
	`  <element ns="ns1" name="the-child"/>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-elem>`
	`  </constraint>`
	`</options>`

JSON	`{"options":{`
	`  "constraint": [`
	`  { "name": "my-geo-elem",`
	`  "geo-elem": {`
	`  "element": { "ns": "ns1", "name": "my-elem" },`
	`  "geo-option": [ "type=long-lat-point" ]`
	`  }},`
	`  { "name": "my-geo-elem-child",`
	`  "geo-elem": {`
	`  "parent": { "ns": "ns1", "name": "the-parent" },`
	`  "element": { "ns": "ns1", "name": "the-child" },`
	`  "facet-option": [ "empties" ],`
	`  "heatmap": {`
	`  "s": 23.2, "w": -118.3, "n": 23.3, "e": -118.2,`
	`  "latdivs": 4, "londivs": 4`
	`  }`
	`  }}`
	`  ]`
	`}}`

32.5.13.4See Also

For more details on using this option, see the following topics:

- `cts:element-child-geospatial-query`

- `cts:element-geospatial-query`
- "Geospatial Search Applications" on page 462

32.5.14 geo-elem-pair

A component of a constraint option that models a geospatial index with coordinates stored in 2 XML elements that are children of the same parent element. That is, geospatial data of the following form:

```
<parent>
  <lat>latitudeValue</lat>
  <lon>longitudeValue</lon>
</parent>
```

For similar JSON data, use geo-json-property-pair.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.14.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-elem-pair>`
`  <parent ns="namespace" name="elemName" />`
`  <lat ns="namespace" name="attrName" />`
`  <lon ns="namespace" name="attrName" />`
`  <facet-option>option</facet-option>`
`  <heatmap>heatmap descriptor</heatmap>`
`  <fragment-scope>scope</fragment-scope>`
`  <geo-option>option</geo-option>`
`</geo-elem-pair>`
	`"geo-elem-pair": {`
	`  "parent": [{`
	`  "ns": "namespace",`
	`  "name": "elemName",`
	`  }],`
	`  "lat": [{`
	`  "ns": "namespace",`
	`  "name": "attrName",`
	`  }],`
	`  "lon": [{`
	`  "ns": "namespace",`
	`  "name": "attrName",`
	`  }],`
	`  "facet-option": [ option ],`
	`  "heatmap": {heatmap desc},`
	`  "geo-option": [ option ],`
	`  "fragment-scope": "scope",`
	`}`

32.5.14.2Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-points`" to the query options configuration. For more details, see `cts:element-pair-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`parent`	Required. Identifies an element that can contain the latitude and longitude elements. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple parents are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`lat`	Required. Identifies the element containing the latitude value. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple elements are defined, the query matches if any one of them matches. However, only the first matching child in any point instance is checked. This component can have an array value in JSON, but need not if there is only one item.
`lon`	Required. Identifies the element containing the longitude value. Use `ns` and `name` to define the namespace (if any) and local name of the element, respectively. If multiple elements are defined, the query matches if any one of them matches. However, only the first matching child in any point instance is checked. This component can have an array value in JSON, but need not if there is only one item.
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see “heatmap” on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see “Facet Options” on page 796.

Element, Attribute or Property Name	Description
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see "Geospatial Options" on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.14.3Examples

The following example defines a geospatial element pair constraint named "my-geo-elem-pair".

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-elem-pair">`
	`  <geo-elem-pair>`
	`  <parent ns="ns1" name="the-parent"/>`
	`  <lat ns="ns2" name="child1"/>`
	`  <lon ns="ns3" name="child2"/>`
	`  <geo-option>boundaries-excluded</geo-option>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-elem-pair>`
	`  </constraint>`
	`</options>`

Format	Example

JSON	{"options":{
	"constraint": [{
	"name": "my-geo-elem-pair",
	"geo-elem": {
	"parent": { "ns": "ns1", "name": "the-parent" },
	"lat": { "ns": "ns2", "name": "child1" },
	"lon": { "ns": "ns3", "name": "child2" },
	"geo-option": ["boundaries-excluded"],
	"facet-option": ["empties"],
	"heatmap": {
	"s": 23.2, "w": -118.3, "n": 23.3, "e": -118.2,
	"latdivs": 4, "londivs": 4
	}
	}
	}]
	}}

32.5.14.4See Also

For more details on using this option, see the following topics:

- “Geospatial Search Applications” on page 462
- `cts:element-pair-geospatial-query`

32.5.15 geo-json-property

A component of a constraint option that models a geospatial index with coordinates stored in a single JSON property. That is, geospatial data with the either of the following structures:

```
"parentProperty": { "property": lat-lon-values }

"property": lat-lon-values
```

This topic has the following sections:

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.15.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-json-property>`
`  <parent-property>`*`name`*`</parent-property>`
`  <json-property>`*`name`*`</json-property>`
`  <facet-option>`*`option`*`</facet-option>`
`  <heatmap>`*`heatmap descriptor`*`</heatmap>`
`  <fragment-scope>`*`scope`*`</fragment-scope>`
`  <geo-option>`*`option`*`</geo-option>`
`</geo-json-property>`
	`"geo-json-property": {`
	`  "parent-property": ["`*`name`*`"],`
	`  "json-property": ["`*`name`*`"],`
	`  "facet-option": [ `*`option`*` ],`
	`  "heatmap": {`*`heatmap desc`*`},`
	`  "geo-option": [ `*`option`*` ],`
	`  "fragment-scope": "`*`scope`*`",`
	`}`

32.5.15.2Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-points`" to the query options configuration. For more details, see `cts:json-property-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`parent-property`	Optional. Identifies the parent JSON property that can contain the latitude and longitude property. If multiple parents are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`json-property`	Required. Identifies the JSON property containing the latitude and longitude values. If multiple properties are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.

Element, Attribute or Property Name	Description
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see "heatmap" on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see "Facet Options" on page 796.
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see "Geospatial Options" on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.15.3Examples

The following example defines two geospatial JSON property constraints, one with a parent property and one without. The second constraint also illustrates the use of the `geo-option`, `facet-option`, and `heatmap` components.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-json-child">`
	`  <geo-json-property>`
	`  <parent-property>parent<parent-property>`
	`  <json-property>child</json-property>`
	`  </geo-json-property>`
	`  </constraint>`
	`  <constraint name="my-geo-json-property">`
	`  <geo-json-property>`
	`  <json-property>location</json-property>`
	`  <geo-option>boundaries-excluded</geo-option>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-json-property>`
	`  </constraint>`
	`</options>`

JSON	`{"options":{`
	`  "constraint": [`
	`  { "name": "my-geo-json-child",`
	`  "geo-json-property": {`
	`  "parent-property": "parent",`
	`  "json-property": "child",`
	`  }},`
	`  { "name": "my-geo-json",`
	`  "geo-json-property": {`
	`  "json-property": "location",`
	`  "geo-option": [ "boundaries-excluded" ],`
	`  "facet-option": [ "empties" ],`
	`  "heatmap": {`
	`  "s": 23.2, "w": -118.3, "n": 23.3, "e": -118.2,`
	`  "latdivs": 4, "londivs": 4`
	`  }`
	`  }},`
	`  ]`
	`}}`

32.5.15.4See Also

For more details on using this option, see the following topics:

- “Geospatial Search Applications” on page 462

- `cts:json-property-geospatial-query`
- `cts:json-property-child-geospatial-query`

32.5.16 geo-json-property-pair

A component of a constraint option that models a geospatial index with coordinates stored in a pair of JSON properties that are children of a specific parent property. That is, geospatial data of the following form:

```
"parentProperty": {
  "latProperty": lat-value,
  "lonProperty": lon-value
}
```

This topic has the following sections:

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.16.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-json-property-pair>`
`  <parent-property>`*name*`</parent-property>`
`  <lat-property>`*name*`</lat-property>`
`  <lon-property>`*name*`</lon-property>`
`  <facet-option>`*option*`</facet-option>`
`  <heatmap>`*heatmap descriptor*`</heatmap>`
`  <fragment-scope>`*scope*`</fragment-scope>`
`  <geo-option>`*option*`</geo-option>`
`</geo-json-property-pair>`
	`"geo-json-property-pair": {`
	`  "parent-property": ["`*name*`"],`
	`  "lat-property": ["`*name*`"],`
	`  "lon-property": ["`*name*`"],`
	`  "facet-option": [ `*option*` ],`
	`  "heatmap": {`*heatmap desc*`},`
	`  "geo-option": [ `*option*` ],`
	`  "fragment-scope": "`*scope*`",`
	`}`

32.5.16.2 Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-points`" to the query options configuration. For more details, see `cts:json-property-pair-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`parent-property`	Required. Identifies the parent JSON property that can contain the latitude and longitude property. If multiple parents are defined, the query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`lat-property`	Required. Identifies the JSON property containing the latitude. If multiple properties are defined, the query matches if any one of them matches. However, only the first matching child in any point instance is checked. This component can have an array value in JSON, but need not if there is only one item.
`lon-property`	Required. Identifies the JSON property containing the longitude. If multiple properties are defined, the query matches if any one of them matches. However, only the first matching child in any point instance is checked. This component can have an array value in JSON, but need not if there is only one item.
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see “heatmap” on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see “Facet Options” on page 796.

Element, Attribute or Property Name	Description
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see "Geospatial Options" on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.16.3Examples

The following example defines a geospatial JSON property pair constraint, including the use of the `geo-option`, `facet-option`, and `heatmap` components.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-json-pair">`
	`  <geo-json-property-pair>`
	`  <parent-property>parent</parent-property>`
	`  <lat-property>child1</lat-property>`
	`  <lon-property>child2</lon-property>`
	`  <geo-option>boundaries-excluded</geo-option>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-json-property-pair>`
	`  </constraint>`
	`</options>`

Format	Example

JSON	{"options":{
	"constraint": [
	{ "name": "my-geo-json-pair",
	"geo-json-property": {
	"parent-property": "parent",
	"lat-property": "child1",
	"lon-property": "child2",
	"geo-option": ["boundaries-excluded"],
	"facet-option": ["empties"],
	"heatmap": {
	"s": 23.2, "w": -118.3, "n": 23.3, "e": -118.2,
	"latdivs": 4, "londivs": 4
	}
	}},
	]
	}}

32.5.16.4See Also

For more details on using this option, see the following topics:

- “Geospatial Search Applications” on page 462
- `cts:json-property-pair-geospatial-query`

32.5.17 geo-path

A component of a constraint option that models a geospatial index with coordinates stored in an XML element, XML attribute, or JSON property described by an XPath expression.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.17.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<geo-path>`
`  <path-index/>`
`  <facet-option>`*`option`*`</facet-option>`
`  <heatmap/>`
`  <fragment-scope>`*`scope`*`</fragment-scope>`
`  <geo-option>`*`option`*`</geo-option>`
`</geo-path>`
	`"geo-path": {`
	`  "path-index": [`*`path index desc`*`],`
	`  "facet-option": [ `*`option`*` ],`
	`  "heatmap": {`*`heatmap desc`*`},`
	`  "geo-option": [ `*`option`*` ],`
	`  "fragment-scope": "`*`scope`*`",`
	`}`

32.5.17.2Component Description

By default coordinates are stored as (latitude,longitude) points. To reverse the coordinate order, add the geo-option "`long-lat-points`" to the query options configuration. For more details, see `cts:json-property-pair-geospatial-query`.

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`path-index`	Required. A geospatial path range index reference. For details, see “path-index” on page 735 You can specify more than one `path-index`. The query matches if any one of them matches. This component can have an array value in JSON, but need not if there is only one item.
`heatmap`	A model of a two-dimensional grid, used to categorize data along two dimensions for faceting. For details, see “heatmap” on page 724.
`facet-option`	Specify options to apply when generating facets. You can only include facet options when there is a `heatmap`. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see “Facet Options” on page 796.

Element, Attribute or Property Name	Description
`geo-option`	Specify options that customize the constraint, such as whether or not to include boundaries. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<geo-option>score-function=linear</geo-option>` in XML, or `"geo-option": ["score-function=linear"]` in JSON. For details, see "Geospatial Options" on page 798.
`fragment-scope`	Set a local fragment scope for this constraint to further constrain where matches occur. The local fragment scope overrides the global fragment scope. For example, a `fragment-scope` of `properties` on a range constraint enables you to facet on a value stored in a property, even if you are searching over documents. Allowed values: `properties`, `documents` (default).

32.5.17.3Examples

The following example illustrates a geospatial path constraint for an XML element or JSON property addressable with the XPath Expression "/a/b".

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-geo-path">`
	`  <geo-path>`
	`  <path-index>/a/b</path-index>`
	`  <geo-option>boundaries-excluded</geo-option>`
	`  <facet-option>empties</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-path>`
	`  </constraint>`
	`</options>`

JSON	`{"options":{`
	`  "constraint": [`
	`  { "name": "my-geo-path",`
	`  "geo-path": {`
	`  "path-index": { "text": "/a/b" },`
	`  "geo-option": [ "boundaries-excluded" ],`
	`  "facet-option": [ "empties" ],`
	`  "heatmap": {`
	`  "s": 23.2,`
	`  "w": -118.3,`
	`  "n": 23.3,`
	`  "e": -118.2,`
	`  "latdivs": 4,`
	`  "londivs": 4`
	`  }`
	`  }},`
	`  ]`
	`}}`

32.5.17.4See Also

For more details on using this option, see the following topics:

- "Geospatial Search Applications" on page 462
- `cts:path-geospatial-query`

32.5.18 custom

A component of a constraint that defines a custom constraint along with the functions that implement it.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.18.1Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<custom facet="boolean">`
`  <parse apply="funcName"`
`  ns="namespace"`
`  at="/path/to/module.xqy"/>`
`  <start-facet apply="funcName"`
`  ns="namespace"`
`  at="/path/to/module.xqy"/>`
`  <finish-facet apply="funcName"`
`  ns="namespace"`
`  at="/path/to/module.xqy"/>`
`  <facet-option>option</facet-option>`
`  <term-option>option</term-option>`
`</custom>`
	`"custom": {`
	`  "facet": boolean`
	`  "parse": {`
	`  "apply": "funcName",`
	`  "ns": "namespace",`
	`  "at": "/path/to/module.xqy"`
	`  },`
	`  "start-facet": {`
	`  "apply": "funcName",`
	`  "ns": "namespace",`
	`  "at": "/path/to/module.xqy"`
	`  },`
	`  "finish-facet": {`
	`  "apply": "funcName",`
	`  "ns": "namespace",`
	`  "at": "/path/to/module.xqy"`
	`  },`
	`  "facet-option": [ option ],`
	`  "term-option": [ option ]`
	`}`

32.5.18.2Component Description

The components of this option have the following semantics. The functions that implement the constraint behavior are identified by a name (`apply`) and optional namespace (`ns`), and the full path to the module that contains the function implementation (`at`).

Element, Attribute or Property Name	Description
`facet`	Required. Whether or not to use this constraint for faceting. If `facet` is false, you do not need to specify `start-facet` or `finish-facet` functions. If facet is true, you must specify a finish-facet function and can specify a `start-facet` function.
`parse`	Required. Identifies the function used to parse the input query text or structured query.
`start-facet`	Identifies a function that makes lexicon API calls to return the values and counts used to construct facets from this constraint. Required if `facet` is true and you use the `concurrent` facet option; optional otherwise.
`finish-facet`	Identifies a function that accepts input from the `start-facet` function (if used) and constructs a facet element.
`facet-option`	Specify options to apply when generating facets. In XML, specify multiple options by including the element multiple times. The element or array item value is of the form *`option=value`*. For example: `<facet-option>limit=5</facet-option>` in XML, or `"facet-option": ["limit=5"]` in JSON. For details, see “Facet Options” on page 796.
`term-option`	Specify options to apply when generating facets. In XML, specify multiple options by including the element multiple times. If the option has a value, the element or array item value is of the form *`option=value`*. For example: `<term-option>lang=en</term-option>` in XML, or `"term-option": ["lang=en"]` in JSON. For details, see “Term Options” on page 796.

32.5.18.3Examples

The following example illustrates a custom constraint that supplies `parse`, `start-facet`, and `finish-facet` functions. All three functions are in the namespace "my-namespace", implemented in an XQuery module installed as /my/module.xqy. For a complete example that includes function implementations, see "Creating a Custom Constraint" on page 40.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-custom">`
	`  <custom facet="true">`
	`  <parse apply="my-parse-function"`
	`  ns="my-namespace" at="/my/module.xqy"/>`
	`  <start-facet apply="my-start-function"`
	`  ns="my-namespace" at="/my/module.xqy"/>`
	`  <finish-facet apply="my-finish-function"`
	`  ns="my-namespace" at="/my/module.xqy"/>`
	`  <facet-option>concurrent</facet-option>`
	`  </custom>`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [`
	`  { "name": "my-custom",`
	`  "custom": {`
	`  "facet": true,`
	`  "parse": {`
	`  "apply": "my-parse-function",`
	`  "ns": "my-namespace",`
	`  "at": "/my/module.xqy"`
	`  },`
	`  "start-facet": {`
	`  "apply": "my-start-function",`
	`  "ns": "my-namespace",`
	`  "at": "/my/module.xqy"`
	`  },`
	`  "finish-facet": {`
	`  "apply": "my-finish-function",`
	`  "ns": "my-namespace",`
	`  "at": "/my/module.xqy"`
	`  },`
	`  "facet-option": [ "concurrent" ],`
	`  }},`
	`  ]`
	`}}`

32.5.18.4See Also

For more details on using this option, see the following topics:

- "Creating a Custom Constraint" on page 40

32.5.19 heatmap

A component of a geospatial constraint that models a two-dimensional grid used to categorize data along two dimensions. Use with geospatial indexes and queries to generate geospatial facets in the form of boxes, similar to the boxes created by `cts:geospatial boxes`.

A `heatmap` can only occur as a sub-component a geospatial constraint, such as geo-elem or geo-json-property. It is required when generating facets from a geospatial constraint.

A heatmap is a bounding box defined by 4 cooridnates (n, w, e, w) and the number of latitudinal and longitudinal divisions in which to subdivide the region for faceting purposes. The bounding box is divided equally into the requested number of buckets. The bounding coordinates of the buckets have single point float precision.

By default, each box facet returned in the search response is the minimum bounding box of all points in the enclosing bucket. Use the "gridded" facet option to return the bucket coordinates defined by the lat and lon divisions instead. Empty buckets return no facets by default; use the "empties" facet option to return empty bucket boxes.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.19.1Syntax Summary

This component has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<heatmap s="double" w="double" n="double" e="double" latdivs="unsignedInt", londivs="unsignedInt" />`
	`"heatmap": {`
	`  "n": double,`
	`  "s": double,`
	`  "e": double,`
	`  "w": double,`
	`  "latdivs": unsignedInt,`
	`  "londivs": unsignedInt`
	`}`

32.5.19.2Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`n`	Required. Heatmap bounding box north coordinate.
`s`	Required. Heatmap bounding box south coordinate.
`e`	Required. Heatmap bounding box east coordinate.
`w`	Required. Heatmap bounding box west coordinate.
`latdivs`	Required. The number of latitude divisions to apply to the bounding box.
`londivs`	Required. The number of longitude divisions to apply to the bounding box.

32.5.19.3Examples

The following example defines a geospatial JSON property pair constraint, with latitude values in `event/latitude` and longitude values in `event/longitude`. Since the constraint defines a `heatmap`, geospatial facets are generated by default. Since the constraint includes the "gridded" facet option, the boxes generated as facets use the dimensions defined by the lat and lon divs defined by the heatmap, rather than the the smallest box within each that encompasses all matching points.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="geo-pair">`
	`  <geo-json-property-pair>`
	`  <parent-property>event</parent-property>`
	`  <lat-property>latitude</lat-property>`
	`  <lon-property>longitude</lon-property>`
	`  <facet-option>gridded</facet-option>`
	`  <heatmap s="23.2" w="-118.3" n="23.3" e="-118.2"`
	`  latdivs="4" londivs="4"/>`
	`  </geo-json-property-pair>`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [{`
	`  "name": "geo-pair",`
	`  "geo-json-property-pair": {`
	`  "parent-property": "event",`
	`  "lat-property": "latitude",`
	`  "lon-property": "longitude",`
	`  "facet-option": [ "gridded" ],`
	`  "heatmap": {`
	`  "s": 24.0, "n": 49.0,`
	`  "e": -67.0,"w": -125.0,`
	`  "latdivs": 5, "londivs": 4`
	`  }}`
	`  }]`
	`}}`

Applied to a search, the heatmap causes the search response to include a `boxes` component, similar to the following:

Format	Search Response Excerpt

XML	`...`
	`<boxes name="geo-pair">`
	`  <box count="2" s="34" w="-125" n="39" e="-110.5"/>`
	`  <box count="12" s="34" w="-110.5" n="39" e="-96"/>`
	`</boxes>`
	`...`

JSON	`...`
	`"facets": {`
	`  "geo-pair": {`
	`  "boxes": [`
	`  { "count": 2,`
	`  "s": 34, "w": -125,`
	`  "n": 39, "e": -110.5`
	`  },`
	`  { "count": 12,`
	`  "s": 34, "w": -110.5,`
	`  "n": 39, "e": -96`
	`  }`
	`  ]`
	`...`

32.5.19.4See Also

For more details on using this option, see the following topics:

- “Geospatial Constraint Example” on page 380
- “Geospatial Search Applications” on page 462

32.5.20 bucket

A component of a range constraint that defines a range of static values within the constraint that can be used in range query expressions and for generating facets. For dynamic value ranges, refer to “computed-bucket” on page 731.

Values assigned to a bucket meet the following criteria:

```
ge <= value < lt
```

Where `ge` and `lt` represent the "ge" and "lt" values specified in the bucket descriptor.

- Syntax Summary

- Component Description
- Examples
- See Also

32.5.20.1Syntax Summary

This component has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API. The bucket definition must contain either a `lt` or `ge` value and may contain both.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<bucket name="name"`
`ge="value" lt="value">`
`displayLabel`
`</bucket>`
	`"bucket": [{`
	`"name": "name",`
	`"label": "displayLabel",`
	`"lt": value,`
	`"ge": value`
	`}]`

32.5.20.2Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`name`	Required. The bucket identifier. The name should be unique within the context of the enclosing constraint. The bucket name can be used in string query terms to represent values that fall into the bucket. For details, see “Examples” on page 733.
`label (JSON)` `fn:data() (XML)`	Text that can be used to label the bucket when displaying facets. In XML, this is the text data contained in the `<bucket/>` element. Optional. The display label has no functional use in searches. If present, it is returned in facets so that applications can use it for display purposes.
`lt`	The upper bound for values assigned to this bucket. Optional, but a bucket must include at least one boundary value. Values assigned to this bucket must be less than this value. Must be an atomic value.
`ge`	The lower bound for values assigned to this bucket. Optional, but a bucket must include at least one boundary value. Value assigned to this bucket must be greater than or equal to this value. Must be an atomic value.

32.5.20.3Examples

The following example defines a path range constraint that includes 3 buckets for faceting, corresponding to matches in the ranges ($x < 5$), ($5 <= x < 10$), and ($10 <= x < 15$). For display purposes, these buckets are labeled “less than 5”, “5 to 9”, and “10 to 15”.

You can use the bucket names in string query range expressions. For example, a string search for “pindex:low” finds values less than 5 in nodes with the path `/Employee/fn`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="pindex">`
	`  <range type="xs:string" facet="true">`
	`  <path-index>/Employee/fn</path-index>`
	`  <bucket name="low" lt="5">less than 5</bucket>`
	`  <bucket name="medium" lt="10" ge="5">5 to 9</bucket>`
	`  <bucket name="high" lt="15" ge="10">10 to 15</bucket>`
	`  </range>`
	`  </constraint>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [{`
	`  "name": "pindex",`
	`  "range": {`
	`  "type": "xs:string",`
	`  "facet": true,`
	`  "path-index": {"text": "/Employee/fn"},`
	`  "bucket": [`
	`  { "name": "low",`
	`  "lt": "5",`
	`  "label": "less than 5"`
	`  },`
	`  { "name": "medium",`
	`  "ge": "5",`
	`  "lt": "10",`
	`  "label": "5 to 9"`
	`  },`
	`  { "name": "high",`
	`  "ge": "10",`
	`  "lt": "15",`
	`  "label": "10 to 15"`
	`  }`
	`  ]`
	`  }`
	`  }]`
	`}}`

32.5.20.4See Also

For more details on using this option, see the following topics:

- “range” on page 677
- “Buckets Example” on page 60
- “Example: Path Range Index Constraint Query Options” on page 402

32.5.21 computed-bucket

A component of a range constraint that defines a range of dynamic values within the constraint that can be used in range query expressions and for generating facets. For static value ranges, refer to “bucket” on page 727.

Values assigned to a given computed bucket meet the following criteria:

```
(anchor + ge) <= value < (anchor + lt)
```

Where `anchor`, `ge`, and `lt` are values specified in the bucket descriptor.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.21.1Syntax Summary

This component has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

The bucket definition must include at least one of (`ge`, `lt`) and may include both. You must include at least one anchor value. The anchor value can be shared by both boundaries or be boundary-specific. For example, if the bucket definition includes a `lt` value, then it must include either an `anchor` or `lt-anchor` value.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<computed-bucket name="name"`
`ge="value" lt="value">`
`anchor="anchorValue"`
`lt-anchor="anchorValue"`
`ge-anchor="anchorValue"`
`displayLabel`
`</computed-bucket>`
	`"computed-bucket": [{`
	`"name": "name",`
	`"label": "displayLabel",`
	`"lt": value,`
	`"ge": value,`
	`"anchor": "anchorValue",`
	`"lt-anchor": "anchorValue",`
	`"gt-anchor": "anchorValue"`
	`}]`

32.5.21.2Component Description

The components of this option have the following semantics.

Element, Attribute or Property Name	Description
`name`	Required. The bucket identifier. The name should be unique within the context of the enclosing constraint. The bucket name can be used in string query terms to represent values that fall into the bucket. For details, see “Examples” on page 733.
`label (JSON)` `data() (XML)`	Text that can be used to label the bucket when displaying facets. In XML, this is the text data contained in the `<bucket/>` element. Optional. The display label has no functional use in searches. If present, it is returned in facets so that applications can use it for display purposes.
`lt`	The upper bound for values assigned to this bucket. Optional, but a bucket must include at least one boundary definition. Values assigned to this bucket must be less than this value. Must be an atomic value.

Element, Attribute or Property Name	Description
ge	The lower bound for values assigned to this bucket. Optional, but a bucket must include at least one boundary definition. Value assigned to this bucket must be greater than or equal to this value. Must be an atomic value.
anchor	A dynamic anchor literal value for the bucket. The bucket bounds are relative to this dynamic value. Optional if you include a boundary-specific anchor (lt-anchor, ge-anchor) for the included boundary values. Allowed values: now, start-of-day, start-of-month, start-of-year.
lt-anchor	Overrides anchor for computing the bucket upper bound. Optional. Allowed values: now, start-of-day, start-of-month, start-of-year.
ge-anchor	Overrides anchor for computing the bucket lower bound. Optional. Allowed values: now, start-of-day, start-of-month, start-of-year.

32.5.21.3Examples

The following example defines an element range constraint on xs:dateTime values that includes 4 buckets, corresponding to matches for the values in dynamic ranges relative to “now”.

Format	Example

XML	<options xmlns="http://marklogic.com/appservices/search">
	  <constraint name="made">
	  <range type="xs:dateTime">
	  <element ns="http://example.com" name="manufactured"/>
	  <computed-bucket name="today" ge="P0D" lt="P1D"
	  anchor="now">Today</computed-bucket>
	  <computed-bucket name="30-days" ge="-P30D" lt="P1D"
	  anchor="now">Last 30 days</computed-bucket>
	  <computed-bucket name="60-days" ge="-P60D" lt="P1D"
	  anchor="now">Last 60 Days</computed-bucket>
	  <computed-bucket name="year" ge="-P1Y" lt="P1D"
	  anchor="now">Last Year</computed-bucket>
	  </range>
	  </constraint>
	</options>

Format	Example

JSON	<pre>{ "options": {
	  "constraint": [{
	  "name": "made",
	  "range": {
	  "type": "xs:dateTime",
	  "element": {
	  "ns": "http://example.com",
	  "name": "manufactured"
	  },
	  "computed-bucket": [
	  { "name": "today",
	  "ge": "P0D",
	  "lt": "P1D",
	  "anchor": "now",
	  "label": "Today"
	  },
	  { "name": "30-days",
	  "ge": "-P30D",
	  "lt": "P1D",
	  "anchor": "now",
	  "label": "Last 30 days"
	  },
	  { "name": "60-days",
	  "ge": "-P60D",
	  "lt": "P1D",
	  "anchor": "now",
	  "label": "Last 60 Days"
	  },
	  { "name": "year",
	  "ge": "-P1Y",
	  "lt": "P1D",
	  "anchor": "now",
	  "label": "Last Year"
	  }
	  ]
	  }
	  }]
	}}</pre>

32.5.21.4See Also

For more details on using this option, see the following topics:

- “range” on page 677
- “Computed Buckets Example” on page 62
- “Example: Element Attribute Range Constraint Query Options” on page 404

32.5.22 path-index

This component identifies a path range index for use in a constraint definition.

- Syntax Summary
- Component Description
- Examples
- See Also

32.5.22.1Syntax Summary

This component has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<path-index xmlns:nsPrefix="nsURI">`
`  pathExpression`
`</path-index>`
	`"path-index": {`
	`  "text": "pathExpression"`
	`  "namespaces": {`
	`  "nsPrefix": "nsURI"`
	`  }`
	`}`

32.5.22.2Component Description

In XML, specify the XPath expression as the element value. In JSON, specify the XPath expression as the value of the "text" property. The database configuration must include a corresponding path range index.

The path expression is limited to the subset of XPath that can be used to define a path range index. For details, see Understanding Path Range Indexes in *Administrator's Guide*.

In XML, define any namespace prefix bindings used in the path expression as `xmlns` attributes of the `path-index` element.

In JSON, define any namespace prefix bindings used in the path expression in the "namespaces" property. The value of a `path-index` can be an array in contexts where you can specify multiple path index references.

32.5.22.3Examples

The following option defines a path index based range constraint and a path index based values specification. The range constraint path index uses namespace prefixes. Path range indexes corresponding to the paths `/data/a` and `/ns1:data/ns2:b` must exist.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="myPathConstraint">`
	`  <range type="xs:int">`
	`  <path-index xmlns:ns1="/my/ns1"`
	`  xmlns:n2="/my/ns2">/data/b</path-index>`
	`  </range>`
	`  </constraint>`
	`  <values name="myValuesSpec">`
	`  <range type="xs:int">`
	`  <path-index>/ns1:data/ns2:a</path-index>`
	`  </range>`
	`  </values>`
	`</options>`

JSON	`{ "options": {`
	`  "constraint": [ {`
	`  "name": "myPathConstraint",`
	`  "range": {`
	`  "type": "xs:int",`
	`  "path-index": {`
	`  "text": "/ns1:data/ns2:b",`
	`  "namespaces": {`
	`  "ns1": "/my/ns1",`
	`  "n2": "/my/ns2"`
	`  }`
	`  }`
	`  }`
	`  } ],`
	`  "values": [`
	`  { "name": "myValuesSpec",`
	`  "range": {`
	`  "type": "xs:int",`
	`  "path-index": { "text": "/data/a" }`
	`  }`
	`  }`
	`  ]`
	`} }`

32.5.22.4See Also

For more details on using this option, see the following topics:

- “constraint” on page 674

- Defining Path Range Indexes in the *Administrator's Guide*

32.6 debug

Whether or not to enable debug mode during a search or lexicon query. Allowed values: `true`, `false` (default). When debug mode is enabled, additional report elements are included in the search results summary.

The following example enables debug mode.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <debug>true</debug>`
	`</options>`

JSON	`{"options": {`
	`  "debug": true`
	`}}`

32.7 default-suggestion-source

This option defines a constraint source for generating suggestions for naked terms with `search:suggest`. Suggestions are often used for type-ahead suggestions in a search user interface. For terms qualified by a constraint prefix, such as "tag:value", use the "suggestion-source" on page 774 option. For more details, see default-suggestion-source Option in the *Search Developer's Guide*.

- Syntax Summary
- Component Description
- Examples
- See Also

32.7.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

Either use `ref` to specify the name of a constraint defined elsewhere in the in-scope options, or omit `ref` and define a single range, word, or collection constraint or word lexicon.

Your options can only include one default suggestion source.

Note: The use of `word-lexicon` (the database-wide word lexicon) is not recommended as best practice; collection and range lexicons yield the best performance.

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<default-suggestion-source ref="constraint">`
`  <range/>`
`  <word/>`
`  <collection/>`
`  <word-lexicon collation="collURI">`
`  <fragment-scope>scope</fragment-scope>`
`  </word-lexicon>`
`  <suggestion-option>option</suggestion-option>`
`</default-suggestion-source>`
	`"default-suggestion-source" : {`
	`  "ref": "constraintName",`
	`  "range": { constraint defn },`
	`  "word": { constraint defn },`
	`  "collection": {constr. defn},`
	`  "word-lexicon": {`
	`  "collation": "collURI",`
	`  "fragment-scope": "scope"`
	`  },`
	`  "suggestion-option": [option]`
	`}`

32.7.2 Component Description

The components of this option have the following semantics. Note that the `range`, `word`, `collection`, and `word-lexicon` components are mutually exclusive of each other.

Element, Attribute or Property Name	Description
`ref`	The name of a constraint defined in the same set of query options. Optional. If a `ref` value is present and a matching constraint exists, that constraint takes precedence over any `range`, `word`, `collection` or `word-lexicon` defined within this option.
`range`	Defines a range constraint that limits suggestions to values that match this constraint.
`word`	Defines a word constraint that limits suggestions to words that match this constraint.
`collection`	Defines a collection constraint that limits suggestions to collection names. If a prefix is present on the constraint definition, constrain suggestions to collection names with the given prefix.
`word-lexicon`	Limit suggestions to words found in the word lexicon.
`suggestion-option`	Query options to use in generating suggestions. For details, see "Suggestion Options" on page 799.

32.7.3 Examples

The following example constrains suggestions for naked terms to those values in the XML element (or JSON property, in the JSON example) with the name “beast”. The constraint is defined external to the `default-suggestion-source`. A range index must be configured on “beast”. If you request suggestions for the partial search term “an”, the “animal:” constraint prefix is also included in the suggestions because constraint names are always included.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="animal">`
	`  <range type="xs:string">`
	`  <element name="beast"/>`
	`  </range>`
	`  </constraint>`
	`  <default-suggestion-source ref="animal"/>`
	`</options>`

JSON	`{"options": {`
	`  "constraint": [{`
	`  "name": "animal",`
	`  "range": {`
	`  "type": "xs:string",`
	`  "json-property": "beast"`
	`  }}],`
	`  "default-suggestion-source" : {`
	`  "ref": "animal"`
	`  }`
	`}}`

The following example has the same effect as the previous one, but the constraint is defined inside the `default-suggestion-source`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`<default-suggestion-source>`
	`<range type="xs:string">`
	`<element name="beast"/>`
	`</range>`
	`</default-suggestion-source>`
	`</options>`

JSON	`{"options": {`
	`"default-suggestion-source" : {`
	`"range": {`
	`"type": "xs:string",`
	`"json-property": "beast"`
	`}}`
	`}}`

The following example generates suggestions from collection names with the prefix “/subject/”. For example if you have documents in the collections "/subject/math" and "/subject/science" and you request suggestions for the partial query text “sc”, then “science” is returned as a suggestion.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`<default-suggestion-source>`
	`<collection prefix="/subject/" />`
	`</default-suggestion-source>`
	`</options>`

JSON	`{"options": {`
	`"default-suggestion-source" : {`
	`"collection": { "prefix": "/subject/" }`
	`}`
	`}}`

32.7.4 See Also

For more details on using this option, see the following topics:

- Search Term Completion Using search:suggest in the *Search Developer’s Guide*
- Java: Generating Search Term Completion Suggestions in the *Java Application Developer’s Guide*

- REST: Generating Search Term Completion Suggestions in the *REST Application Developer's Guide*
- Node.js: Generating Search Term Completion Suggestions in the *Node.js Application Developer's Guide*

32.8 extract-document-data

Use `extract-document-data` to select one or more XML elements, XML attributes, or JSON properties from each matching document to return in the results of a document search. Selection is via an absolute XPath expression. The XPath expression in extract-path is limited to the subset suitable for defining path range indexes; for details, see Limitations on Index Path Expressions in the *Administrator's Guide*.

- Syntax Summary
- Component Description
- Examples
- See Also

Specify the elements, attributes, or properties as absolute XPath expressions in `extract-path`. Use the `selected` property to indicate what data to return in the selected document components. If `extract-path` is absent or contains no path expressions, the entire content of each matching document is included in the result set.

The manner in which the extracted content is returned depends on the calling context. Using the option in the following calling context returns the extracted content inside the search result summary:

- XQuery: `search:search` or `search:resolve` functions
- REST Client API: `GET:/v1/search` or `POST:/v1/search` with an Accept header of `application/json` or `application/xml`
- Node.js: `DatabaseClient.documents.query` that returns a search result summary instead of documents (`queryBuilder.withOptions({categories: 'none'})`) and includes a result slice with an `extract` clause.
- Java: `QueryManager.search` returns the extracted content in the search results. Access the content using `MatchDocumentSummary.getExtracted`.

Using the option in the following calling contexts returns the extracted content as a sequence of documents:

- XQuery: `search:resolve-nodes`
- REST Client API: `GET:/v1/search` or `POST:/v1/search` with an Accept header of `multipart/mixed` (a multi-document read)

- Node.js: `DatabaseClient.documents.query` that returns documents and includes a result slice with an `extract` clause.
- Java: The `DocumentPage` returned by `DocumentManager.search` contains an extracted document instead of a full document for each match.

32.8.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<extract-document-data selected=value>`
`  <extract-path xmlns:pfx="nsURI">`
`  abs-xpath-expr`
`  </extract-path>`
`</extract-document-data>`
	`"extract-document-data": {`
	`  "selected": value,`
	`  "extract-path": [ abs-xpath-expr ]`
	`}`

32.8.2 Component Description

The components of this option have the following semantics. Setting `selected` to "all" or failing to specify at least one `extract-path` XPath expression means to "extract" the entire document.

Element, Attribute or Property Name	Description
`selected`	How to handle the content selected by `extract-path`. Allowed values: • `include` (default): Include the targeted item(s) in the results. • `include-with-ancestors`: Include the targeted item(s) and all containing ancestors. • `exclude`: Include everything except the targeted item(s). • `all`: Include the entire document For examples of using each setting, see Extracting a Portion of Matching Documents in the *Search Developer's Guide*.
`extract-path`	Optional. The absolute XPath expression of an XML element, XML element attribute, or JSON property that is a target for extraction. You can specify multiple paths. The path expressions are limited to the subset of XPath that can be used to define a path range index. For details, see Understanding Path Range Indexes in *Administrator's Guide*. If a path requires namespace prefixes, define the binding on the `extract-path` XML element, or predefine the binding using a capability such as the REST Client API method `PUT:/v1/config/namespaces` or Java Client API `NamespaceManager` interface.

32.8.3 Examples

The following example targets two items for extraction with the XPath expressions "/my:location" and "/who/userName". Since `selected` is "include", just these elements (or JSON properties) will be include in the extraction results.

A namespace binding is required for "/my:location". In XML options, the binding can be specified on the enclosing `extract-path`, as shown below. When defining options using JSON or when using an API that does not provide this level of control, you must predefine the namespace binding.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <extract-document-data selected="include">`
	`  <extract-path xmlns:my="/my/namespace">/my:location</extract-path>`
	`  <extract-path>/who/userName</extract-path>`
	`  </extract-document-data>`
	`</options>`

JSON	`{"options": {`
	`  "extract-document-data": {`
	`  selected: "include",`
	`  extract-path: [ "/my:location", "/who/userName" ]`
	`  }`
	`} }`

32.8.4 See Also

For more details on using this option, see the following topics:

- Extracting a Portion of Matching Documents in the *Search Developer's Guide*
- REST: Using Namespace Bindings in the *REST Application Developer's Guide*
- Java:
  - Extracting a Portion of Matching Documents in the *Java Application Developer's Guide*
  - Namespaces in the *Java Application Developer's Guide*
- Node.js: Extracting a Portion of Each Matching Document in the *Node.js Application Developer's Guide*

32.9 forest

This option specifies forests to which a search or lexicon query will be constrained. Identify each forest by an unsigned long forest id. If no forest ids are specified, all forests in the database are searched, which is the default behavior.

Note: In the JSON representation, represent the forest ids as a strings because forest ids can exceed the maximum number value supported by JSON.

The following example limits the search to two forests.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <forest>13081837393370312889</forest>`
	`  <forest>13081837393370234811</forest>`
	`</options>`

JSON	`{"options": {`
	`  "forest": ["13081837393370312889","13081837393370234811"]`
	`}}`

For additional examples, see `cts:search`.

32.10 fragment-scope

This option controls the global fragment scope over which to search. The global scope applies to what the search returns (that is, if it returns results from document fragments or from property fragments) and is inherited by any constraints that do not explicitly override the `fragment-scope`.

Allowed values: `properties`, `documents` (default)

You can override the global fragment scope by setting a local fragment scope inside a constraint or term definition. For example, a `fragment-scope` of `properties` on a range constraint enables faceting on a value stored in a property, even if you are searching over documents.

For details, see “Fragment Scope Option” on page 386.

The following example sets the global fragment scope to “properties”.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <fragment-scope>properties</fragment-scope>`
	`</options>`

JSON	`{"options": {`
	`  "fragment-scope": "properties"`
	`}}`

32.11 grammar

The wrapper element for a custom search grammar definition. The default grammar defines "Google-style" parsing; for details, see “The Default String Query Grammar” on page 66.

- Syntax Summary
- Component Description
- Examples
- See Also

See the following topics for a detailed description of the starter and joiner components of a grammar.

- starter
- joiner

32.11.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<grammar>`
`  <quotation>quoteChar</quotation>`
`  <implicit options=">`*`ctsQuery`*`</implicit>`
`  <starter/>`
`  <joiner/>`
`</grammar>`
	`"grammar": {`
	`  "quotation": "`*`quoteChar`*`",`
	`  "implict": "`*`ctsQuery`*`",`
	`  "starter": [...],`
	`  "joiner": [...]`
	`}`

32.11.2 Component Description

The components of this option have the following semantics. The grammar should contain at least one `implicit`, `starter`, or `joiner`. If the grammar is empty, then query text is parsed according to the term options.

Element, Attribute or Property Name	Description
`quotation`	The string to use to delimit the start and end of a phrase. You cannot specify a search that includes quotation character. For example, in the default grammar, you cannot search for a double quote (") because this is the `quotation` character.
`implicit`	A serialized `cts:query` used to join two search terms when they are not separated by an explicit operator. By default, the Search API uses a `cts:and-query`,. For example, in the default grammar, “cat dog” is equivalent to “cat AND dog”. Your grammar should include at most one `implicit` component.
`starter`	Define a unary operator or a pair of group delimiters. For example, the default grammar includes a starter for the unary operator “-” that is bound to `cts:not-query` and a starter for “(“ and “)” for grouping. For details, see “starter” on page 750. Your grammar can include zero or more starters.
`joiner`	Define a binary operator that joins two query expressions. For example, the default grammar defines joiners such as “AND”, “OR”, and “LT”. For details, see “joiner” on page 752. Your grammar can include zero or more joiners.

32.11.3 Examples

The following example is a subset of the default grammar. You can obtain the complete grammar by calling `search:get-default-options`.

Format	Example

XML	<options xmlns="http://marklogic.com/appservices/search">
	  <grammar>
	<quotation>"</quotation>
	  <implicit>
	  <cts:and-query strength="20" xmlns:cts="http://marklogic.com/cts"/>
	  </implicit>
	  <starter strength="30" apply="grouping" delimiter=")">(</starter>
	  <starter strength="40" apply="prefix" element="cts:not-query">-</starter>
	  <joiner strength="10" apply="infix" element="cts:or-query"
	  tokenize="word">OR</joiner>
	  <joiner strength="20" apply="infix" element="cts:and-query"
	  tokenize="word">AND</joiner>
	  </grammar>
	</options>

JSON	{"options": {
	  "grammar": {
	  "starter": [
	  {
	  "strength": 30,
	  "apply": "grouping",
	  "delimiter": ")",
	  "label": "("
	  },
	  {
	  "strength": 40,
	  "apply": "prefix",
	  "element": "cts:not-query",
	  "label": "-"
	  },
	  ],
	  "joiner": [{
	  "strength": 10,
	  "apply": "infix",
	  "element": "cts:or-query",
	  "tokenize": "word",
	  "label": "OR"
	  }],
	  "quotation": "\"",
	  "implicit": "<cts:and-query strength=\"20\"
	xmlns=\"http://marklogic.com/appservices/search\"
	xmlns:cts=\"http://marklogic.com/cts\"/>"
	  }
	  }
	}

32.11.4 See Also

For more details on using this option, see the following topics:

- "Modifying and Extending the String Query Grammar" on page 71

32.11.5 starter

A `starter` is a child of a grammar option that defines a unary operator or a group operator. For more details, see "grammar" on page 747.

Use the apply-at-ns pattern described in Search Customization Via Options and Extensions in *Search Developer's Guide* to define the XQuery library function that implements the starter. The function must produce a cts:query element of the type named by `element`.

- Syntax Summary
- Component Description
- Examples

32.11.5.1 Syntax Summary

The `starter` component of a grammar option has the following structure. The operator token is the text data of the `starter` element in XML and the value of the `label` property in JSON. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<starter strength="int"`
`apply="funcName"`
`ns="namespaceURI"`
`at="modulePath"`
`element="qName"`
`options="optList"`
`delimiter="delimChar"`
`tokenize="value">`
`opToken`
`</starter>`
	`"starter": [{`
	`"label": "opToken",`
	`"strength": number,`
	`"apply": "funcName",`
	`"ns": "namespaceURI",`
	`"at": "modulePath",`
	`"element": "qName",`
	`"options": "optList",`
	`"tokenize": "value",`
	`"delimiter": "delimChar",`
	`}]

32.11.5.2Component Description

The `starter` component of a grammar option has the following semantics:

Element, Attribute or Property Name	Description
`fn:data() (XML)` `label (JSON)`	Required. The starter operator token. For example, the default grammar includes a starter with the minus sign (-) as the operator, which enables query text such as "-cat". If defining a pair of grouping delimiters such as "(" and ")", place set this component to the group start delimiter ("(") and set `delimiter` to the group end deliminter (")").
`strength`	Required. The order of precedence of this starter relative to other operators in this grammar. Higher strength tokens or groups are processed before lower ones.
`apply`	The local-name of a function that parses expressions using this starter. This can be one of the functions pre-defined by the default grammar or a custom function; for a custom function, you must also include `ns` and `at` values.
`ns`	The XQuery module that contains the `apply` function, if using a user-defined function.
`at`	The module from which the `apply` function is imported, if using a user-defined function.
`element`	A `cts:query` element name that identifies the type of cts:query element produced by the parsing function. For example, the default grammar defines a negation starter using the minus sign, which produces a `cts:not-query`.
`options`	A space-separated list of options that are passed through to the underlying `apply` function.
`tokenize`	Allowed values: "word" or "default".
`delimiter`	When defining a pair of grouping deliminters, the string to use as a the delimiter of the end of the grouping. For example, if defining "(" and ")" as group delimiters, set `delimiter` to ")".

32.11.5.3Examples

The following example shows the definition of the "-" (not) unary operator and "( )" grouping operator defined by the default grammar.

Format	Example

XML	`<starter strength="30" apply="grouping" delimiter=")">(</starter>`
	`<starter strength="40" apply="prefix"`
	`  element="cts:not-query">-</starter>`

JSON	`"starter": [`
	`  { "strength": 30,`
	`  "apply": "grouping",`
	`  "delimiter": ")",`
	`  "label": "("`
	`  },`
	`  { "strength": 40,`
	`  "apply": "prefix",`
	`  "element": "cts:not-query",`
	`  "label": "-"`
	`  }`
	`]`

32.11.6 joiner

A `joiner` is a child of a grammar option that defines a binary operator. For more details, see "grammar" on page 747.

Use the apply-at-ns pattern described in Search Customization Via Options and Extensions in *Search Developer's Guide* to define the XQuery library function that implements the joiner. The function must produce a cts:query element of the type named by `element`.

- Syntax Summary
- Component Description
- Examples

32.11.6.1Syntax Summary

The `joiner` component of a grammar option has the following structure. The operator token is the text data of the `starter` element in XML and the value of the `label` property in JSON. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<joiner strength="int"`
`apply="funcName"`
`ns="namespaceURI"`
`at="modulePath"`
`element="qName"`
`options="optList"`
`compare="operator"`
`consume="nTokens"`
`tokenize="value">`
`opToken`
`</joiner>`
	`"joiner": [{`
	`"label": "opToken",`
	`"strength": number,`
	`"apply": "funcName",`
	`"ns": "namespaceURI",`
	`"at": "modulePath",`
	`"element": "qName",`
	`"options": "optList",`
	`"compare": "operator",`
	`"consume": nTokens`
	`"tokenize": "value"`
	`}]`

32.11.6.2Component Description

The `joiner` component of a grammar option have the following semantics:

Element, Attribute or Property Name	Description
`fn:data() (XML)` `label (JSON)`	Required. The joiner operator token. For example, the default grammar includes a joiner with "AND" as the operator, which enables query text such as "cat AND dog".
`strength`	Required. The order of precedence of this operator relative to other operators in this grammar. Higher strength tokens or groups are processed before lower ones.
`apply`	The local-name of a function that parses expressions using this operator. This can be one of the functions pre-defined by the default grammar or a custom function; for a custom function, you must also include `ns` and `at` values.
`ns`	The XQuery module that contains the `apply` function, if using a user-defined function.

Element, Attribute or Property Name	Description
`at`	The module from which the `apply` function is imported, if using a user-defined function.
`element`	A `cts:query` element name that identifies the type of cts:query element produced by the parsing function. For example, the default grammar defines AND as a joiner that produces a `cts:and-query`.
`options`	A space-separated list of options that are passed through to the underlying `apply` function.
`compare`	The range query comparison operator to apply when defining a relational operator. Allowed values: `LT`, `LE`, `GT`, `GE`, `NE`, `EQ`.
`consume`	The number of tokens to consume when parsing the right operand of the joiner. For example, the `near/` operator defined by the default grammar consumes one token when parsing "A NEAR B", but it consumes two tokens when parsing the expression "A NEAR/3 B" (th count, 3, and B).
`tokenize`	Allowed values: "word" or "default".

32.11.6.3Examples

The following examples from the default grammar define the AND and LT operators. For more examples, see the default grammar.

Format	Example

XML	`joiner strength="20" apply="infix" element="cts:and-query"`
	`tokenize="word">AND</joiner>`
	`<joiner strength="50" apply="constraint" compare="LT"`
	`tokenize="word">LT</joiner>`

JSON	`"joiner": [`
	`{ "strength": 20,`
	`"apply": "infix",`
	`"element": "cts:and-query",`
	`"tokenize": "word",`
	`"label": "label"`
	`},`
	`{ "strength": 50,`
	`"apply": "constraint",`
	`"compare": "LT",`
	`"tokenize": "word",`
	`"label": "LT"`
	`},`
	`]`

32.12 operator

A named wrapper for one or more state elements, each representing a unique run-time configuration option. An operator defines a set of options that can be applied at query time when "*opName*:*state*" is encountered in the query text.

For example, if an operator with the name "sort" is defined, then the query text "sort:foo" will select the "foo" of the "sort" operator at query runtime, using the options specified on that state element. Options affecting query parsing (such as `constraint`, `grammar`, `term`, `empty`) may not be configured via operators.

- Syntax Summary
- Component Description
- Examples
- Examples

32.12.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<operator name="opName">`
`  <state name="stateName">`
`  <additional-query>`
`  ctsQuery`
`  </additional-query>`
`  <debug>boolean</debug>`
`  <forest>forestId</forest>`
`  <page-length>int</page-length>`
`  <quality-weight>double</quality-weight>`
`  <search-option>option</search-option>`
`  <searchable-expression>`
`  pathExpr`
`  </searchable-expression>`
`  <sort-order/>`
`  <transform-results/>`
`  </state>`
`</operator>`
	`"operator: {`
	`  "name": "opName",`
	`  "state": [ {`
	`  "name": "stateName",`
	`  "additional-query": "ctsQuery",`
	`  "debug": boolean,`
	`  "forest": forestId,`
	`  "page-length": integer,`
	`  "quality-weight": double,`
	`  "search-option": [ "option" ],`
	`  "searchable-expression":`
	`  "pathExpr",`
	`  "sort-order": [ ... ],`
	`  "transform-results": ...`
	`  } ]`
	`}`

32.12.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`name`	Required. The name of this operator. The name must be unique across all operators and constraints in scope.
`state`	One or more state definitions for the operator.
`state/name`	Required. The name of this state.
`state/additional-query`	A cts:query to evaluate when the operator is in this state.
`state/debug`	Whether or not to enable debug logging. Default: false.
`state/forest`	A forest id. This must be an unsigned long value.
`state/page-length`	The page length into which results should be chunked.

Element, Attribute or Property Name	Description
`state/quality-weight`	Specifies a a weighting factor to use in the query. The default value is 1.0.
`state/search-option`	Search options passed to the `additional-query`. You can include zero or more options.
`state/searchable-expression`	Specifies an XPath expression to search. For details, see “searchable-expression” on page 768.
`state/sort-order`	Specifies a sort order to apply. For details, see “sort-order” on page 770.
`state/transform-results`	Define a transformation to use when applying this state. For details, see “transform-results” on page 782.

32.12.3 Examples

The following example defines 2 operators, named “sort” and “page-length”. The “sort” operator has 2 states, “down” and “up”. The “nresults” operator has 2 states, “few” and “many”. This allows you, for example, to include a search term of the form `sort:up` to request results in ascending order. Similarly, a search term of the form `nresults:many` cause 50 matches to be returned.

Format	Example
XML	<options xmlns="http://marklogic.com/appservices/search"> <operator name="sort"> <state name="up"> <sort-order> <direction>ascending</direction> <score/> </sort-order> </state> <state name="down"> <sort-order> <direction>ascending</direction> <score/> </sort-order> </state> </operator> <operator name="nresults"> <state name="few"> <page-length>10</page-length> </state> <state name="many"> <page-length>50</page-length> </state> </operator> </options>

Format	Example

JSON	<pre>{"options": {
	  "operator": [
	  { "name": "sort",
	  "state": [
	  { "name": "down",
	  "sort-order": [{
	  "direction": "descending",
	  "score": null
	  }]
	  },
	  { "name": "up",
	  "sort-order": [{
	  "direction": "ascending",
	  "score": null
	  }]
	  }
	  ]
	  },
	  { "name": "nresults",
	  "state": [
	  { "name": "few",
	  "page-length": 10
	  },
	  { "name": "many",
	  "page-length": 50
	  }
	  ]
	  }]
	} }</pre>

32.12.4 See Also

For more details on using this option, see the following topics:

- “Operator Options” on page 382

32.13 page-length

This option specifies the number of search results to include in each page of returned results. The default value is 10.

The following example sets the page length to 20.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <page-length>20</page-length>`
	`</options>`

JSON	`{"options": {`
	`  "page-length": 20`
	`}}`

32.14 quality-weight

This option specifies a document quality weight to use when computing scores. The value should be a double. The default value is 1.0.

The following example sets the quality weight to 2.0.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <quality-weight>2.0</quality-weight>`
	`</options>`

JSON	`{"options": {`
	`  "quality-weight": 2.0`
	`}}`

32.15 result-decorator

Defines a custom search result decorator XQuery function that is used to decorate each search `result` with additional information. Before performing a search that uses this option, the XQuery library module containing the function must be installed in the App Server modules database at the XPath given by `at`.

- Syntax Summary
- Component Description
- Examples
- See Also

32.15.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<result-decorator apply="`*`funcName`*`"`
`ns="`*`namespaceURI`*`"`
`at="`*`modulePath`*`" />`
	`"result-decorator": {`
	`"apply": "funcName",`
	`"ns": "`*`namespaceURI`*`",`
	`"at": "`*`modulePath`*`"`
	`}`

32.15.2 Component Description

The components of this option have the following semantics. The module identified by the option must be installed under the App Server root or int he modules database at the location identified by the `at` XPath expression.

Element, Attribute or Property Name	Description
`apply`	The localname of a custom result decorator function. You must also specify `ns` and `at`.
`ns`	The namespace of the function in apply. This must match the namespace declaration of the XQuery library module containing the `apply` function.
`at`	The XPath to the XQuery library module containing the `apply` function.

32.15.3 Examples

The following example specifies the function `decorator` in the XQuery library module located at `/ext/my.domain/decorator.xqy`. assuming the module namespace is `http://marklogic.com/example/my-lib`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <result-decorator apply="decorator"`
	`  ns="http://marklogic.com/example/my-lib"`
	`  at="/ext/my.domain/decorator.xqy"/>`
	`</options>`

JSON	`{"options": {`
	`  "result-decorator": {`
	`  "apply": "decorator",`
	`  "ns": "http://marklogic.com/example/my-lib",`
	`  "at": "/ext/my.domain/decorator.xqy"`
	`  }`
	`} }`

32.16 return-aggregates

This option specifies whether or not to include the result of running a builtin or user-defined aggregate function in the result of a lexicon query, such as `search:values`. Aggregates are not applicable to document searches (`search:search`).

Default: `false` (do not include). This option applies only to queries against values or tuples.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-aggregates>true</return-aggregates>`
	`</options>`

JSON	`{"options": {`
	`  "return-aggregates": true`
	`}}`

For details, see the following topics:

- “Return Options” on page 385
- “Using Aggregate Functions” on page 449

- XQuery: `search:values`
- REST: Analyzing Lexicons and Range Indexes With Aggregate Functions in the *REST Application Developer's Guide*

32.17 return-constraints

This option specifies whether or not to include original constraint definitions in the result summary (`search:response`) of a document search. Default: `false` (do not include). For details, see "Return Options" on page 385.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-constraints>true</return-constraints>`
	`</options>`

JSON	`{"options": {`
	`  "return-constraints": true`
	`}}`

32.18 return-facets

This option specifies whether or not to include facets in the result summary (`search:response`) from a document search. Default: `true` (include).

The following example sets the option to false.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-facets>false</return-facets>`
	`</options>`

JSON	`{"options": {`
	`  "return-facets": false`
	`}}`

For details, see the following topics:

- "Return Options" on page 385
- "Constrained Searches and Faceted Navigation" on page 32

32.19 return-frequencies

This option specifies whether or not to include term frequencies in the search result summary for a values or tuples lexicon query. Default: `true` (include).

For details, see "Return Options" on page 385.

The following example sets the option to false.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-frequencies>false</return-frequencies>`
	`</options>`

JSON	`{"options": {`
	`  "return-frequencies": false`
	`}}`

32.20 return-metrics

This option specifies whether or not to include performance metrics in the search result summary (`search:response`). Default: `true` (include).

For details, see "Return Options" on page 385.

The following example sets the option to false.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-metrics>false</return-metrics>`
	`</options>`

JSON	`{"options": {`
	`  "return-metrics": false`
	`}}`

32.21 return-plan

This option specifies whether or not to include a query plan in the result summary (`search:response`) of a document search. Default: `false` (do not include). The query plan enables you to examine the evaluation plan for a query, which can aid query tuning. For example, you can determine whether or not your range indexes are being used as you expect them to be.

For details, see "Return Options" on page 385 and `xdmp:plan`.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-plan>true</return-plan>`
	`</options>`

JSON	`{"options": {`
	`  "return-plan": true`
	`}}`

32.22 return-qtext

This option specifies whether or not to include the original query text in the search result summary (`search:response`). Default: `true` (include).

For details, see “Return Options” on page 385.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-qtext>true</return-qtext>`
	`</options>`

JSON	`{"options": {`
	`  "return-qtext": true`
	`}}`

32.23 return-query

This option specifies whether or not to include the final representation of your query as XML in the result summary (`search:response`) of a document search. Default: `false` (do not include).

For details, see “Return Options” on page 385.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-query>true</return-query>`
	`</options>`

JSON	`{"options": {`
	`  "return-query": true`
	`}}`

32.24 return-results

This option specifies whether or not to include search result details (`search:result`) in the result summary (`search:response`) of a document search. Default: `true` (include). You can use the transform-results option to control the formatting of the results.

For details, see “Return Options” on page 385.

The following example sets the option to false.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-results>false</return-results>`
	`</options>`

JSON	`{"options": {`
	`  "return-results": false`
	`}}`

32.25 return-similar

This option specifies whether or not to include a list of similar documents in each search result in the result summary (`search:response`) of a document search. Default: `false` (do not include).

For details, see “Return Options” on page 385.

The following example sets the option to true.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-similar>true</return-similar>`
	`</options>`

JSON	`{"options": {`
	`  "return-similar": true`
	`}}`

32.26 return-values

This option specifies whether or not to include the index/lexicon values in the search results summary when performing a lexicon or index query, such as with `search:values`. Default: `true` (include).

For details, see “Return Options” on page 385.

The following example sets the option to false.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <return-values>false</return-values>`
	`</options>`

JSON	`{"options": {`
	`  "return-values": false`
	`}}`

32.27 search-option

Advanced users can use this option to pass options to the underlying cts query option. For example, use this option to pass through options such as “filtered”, “unfiltered”, and “score-logtfidf”. See the XQuery function `cts:search` for a list of possible values.

This option can appear multiple times in XML and has array value in JSON.

The following example specifies two advanced search options.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <search-option>filtered</search-option>`
	`  <search-option>format-text</search-option>`
	`</options>`

JSON	`{"options": {`
	`  "search-option": ["filtered", "format-text"]`
	`}}`

32.28 searchable-expression

This option specifies an XPath expression to be searched when performing a document search. For example, if you specify `//p`, then `p` elements that match the search criteria are returned.

The expression must be an inline fully searchable XPath expression, and all necessary namespaces must be declared. The default value is `fn:collection()`, which searches all documents in the database.

> **Note:** Using this option in the `options` section of a combined query evaluated using the REST, Java, or Node.js Client API requires the `rest-admin` role or equivalent privileges if the expression is not a valid indexable path. For details, see Using Dynamically Defined Query Options in the *REST Application Developer's Guide*.

This option does not affect facet results. To constrain facets, use the `additional-query` option.

- Syntax Summary
- Component Description
- Examples
- See Also

32.28.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<searchable-expression xmlns:`*prefix*`="`*nsURI*`">`
`  `*xpathExpr*
`</searchable-expression>`
	`"searchable-expression": {`
	`  "text": "`*xpathExpr*`",`
	`  "namespaces" : {`
	`  "`*prefix*`": "`*nsURI*`"`
	`  }`
	`}`

32.28.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`fn:data() (XML)` `text (JSON)`	A fully searchable XPath expression. In XML, the expression is simply the text data of the `searchable-expression` element. If the expression uses namespace prefixes, you must define the prefixes in the option.
`@xmlns:`*prefix* `(XML)` `namespaces (JSON)`	Define a binding between a prefix used in the searchable XPath expression and a namespace URI. In JSON, each child property of the namespaces component is of the form "*prefix*": "*namespaceURI*". In XML, define the binding using the standard xmlns attribute syntax.

32.28.3 Examples

The following example searches over elements addressed by the XPath expression "/ex:orders/com:company".

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <searchable-expression xmlns:ex="http:example.com"`
	`  xmlns:com="http://company.com">`
	`  /ex:orders/com:company`
	`  </searchable-expression>`
	`</options>`

JSON	`{"options": {`
	`  "searchable-expression": {`
	`  "text": "/ex:orders/com:company",`
	`  "namespaces": {`
	`  "ex": "http:example.com",`
	`  "com": "http://company.com"`
	`  }`
	`  }`
	`}}`

32.28.4 See Also

For more details on using this option, see the following topics:

- "Searchable Expression Option" on page 385

32.29 sort-order

Defines the sort order of an element, element attribute, field, or JSON property during a document search.

A set of options can contain multiple `sort-order` specifiers. The first such specification is the primary sort order, the second is the secondary sort order, and so on. The default sort order is to sort by score, descending.

- Syntax Summary
- Component Description
- Examples

32.29.1 Syntax Summary

A `sort-order` option must contain exactly one `element`, `score`, `field`, or `json-property` child. If there is an `element` child it can optionally have an `attribute` sibling (to specify an attribute of the preceding element). Both the `element` and `attribute` must have `ns` and `name` attributes to specify the namespace and local-name of the specified element and attribute.

The database configuration must include a range index on any XML element, XML element attribute, JSON property, or field used to control sort order.

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<sort-order type="xsType" collation="collURI"`
`  direction="value">`
`  <element ns="namespace" name="name"/>`
`  <attribute ns="namespace" name="name"/>`
`  <field name="name"/>`
`  <json-property>name</json-property>`
`  <score/>`
`</sort-order>`
	`"sort-order": {`
	`  "type": "xsType",`
	`  "collation" : "collURI",`
	`  "direction" : "value",`
	`  "element": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "attribute": {`
	`  "ns": "namespace",`
	`  "name": "name"`
	`  },`
	`  "field": {"name": "name"},`
	`  "json-property": "name",`
	`  "score": null`
	`}`

32.29.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`element`	Identifies an XML element to which this sort order applies, or the element containing the attribute to which this sort order applies. If specifying only an element, you must set `type` to match the range index type of this element. If an `element` is present, you cannot include a `field` or `json-property` child.
`attribute`	Identifies the element attribute to which this sort order applies. You must set `type` to match the range index type of this attribute. If an `attribute` property is present, you cannot also specify `field` or `json-property`, and you must specify `element`.
`field`	Identifies the field to which this sort order applies. Cannot be used with `element`, `attribute` or `json-property`. You should not apply `sort-order` to a field that has more than one included element.
`json-property`	Identifies the JSON property to which this sort order applies. Cannot be used with `element`, `attribute` or `field`.
`score`	Sort by the score of the search result. For details, see Relevance Scores: Understanding and Customizing in the *Search Developer's Guide*.
`type`	If you are sorting by an element, an attribute, or a JSON property, you must specify a type property with a value corresponding to the range index type of that element, attribute, or property. For example, `xs:string`, `xs:dateTime`, and so on.
`collation`	A collation URI. Optionally specify a collation when `type` is xs:string; otherwise, use the collation of the query.
`direction`	Specify the sorting direction. Default: `descending`. Allowed values: `ascending`, `descending`.

32.29.3 Examples

The following example specifies a primary sort order using the element value for `my-element` and a secondary sort order of score ascending. The database configuration must include a range index on `my-element` with the specified collation.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <sort-order type="xs:string"`
	`  collation="http://marklogic.com/collation/"`
	`  direction="ascending">`
	`  <element ns="my-namespace" name="my-element"/>`
	`  </sort-order>`
	`  <sort-order direction="ascending">`
	`  <score/>`
	`  </sort-order>`
	`</options>`

JSON	`{"options": {`
	`  "sort-order": [`
	`  { "direction": "descending",`
	`  "type": "xs:string",`
	`  "collation": "http://marklogic.com/collation/",`
	`  "element": {`
	`  "name": "my-element",`
	`  "ns": "my-namespace",`
	`  }`
	`  },`
	`  { "direction": "ascending",`
	`  "score": null`
	`  }`
	`  ]`
	`} }`

32.30 suggestion-source

This option defines a search term completion suggestion source for a constraint-qualified search term using `search:suggest` (or an equivalent operation). That is, terms of the form "animal:cat". Suggestions are often used for type-ahead suggestions in a search user interface.

By default, suggestions for constraint-qualified terms are generated based on the qualifying constraint. Use this option to specify an alternative source. This option is useful when you use a named constraint for searching and facets, but you want to use a different source for type-ahead suggestions without re-parsing your search terms.

For naked terms that are unqualified by a constraint prefix, such as "cat", use the default-suggestion-source option. For more details, see default-suggestion-source Option in the *Search Developer's Guide*.

- Syntax Summary
- Component Description
- Examples
- See Also

32.30.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

You must include ref, and it should refer to a named constraint defined elsewhere in your options.

> **Note:** The use of `word-lexicon` (the database-wide word lexicon) is not recommended as best practice; collection and range lexicons yield the best performance.

XML	JSON

All elements are in the namespace
`http://marklogic.com/appservices/search`.
 	
`<suggestion-source ref="constraint">`
`  <range/>`
`  <word/>`
`  <collection/>`
`  <word-lexicon collation="collURI">`
`  <fragment-scope>scope</fragment-scope>`
`  </word-lexicon>`
`  <suggestion-option>option</suggestion-option>`
`</suggestion-source>`
	`"suggestion-source" : [{`
	`  "ref": "constraintName",`
	`  "range": { constraint defn },`
	`  "word": { constraint defn },`
	`  "collection": {constr. defn},`
	`  "word-lexicon": {`
	`  "collation": "collURI",`
	`  "fragment-scope": "scope"`
	`  },`
	`  "suggestion-option": [option]`
	`}]`

32.30.2 Component Description

The components of this option have the following semantics. Use `ref` to identify the constraint to override. Use `range`, `word`, `collection`, or `word-lexicon` to define the overriding suggestion source. Note that the `range`, `word`, `collection`, and `word-lexicon` components are mutually exclusive of each other.

A constraint defined within a `suggestion-source` can include a `collation` value, which specifies the collation of the value lexicon used during query evaluation. If no collation is specified, then the query uses the default collation for the context in which the query is evaluated.

Element, Attribute or Property Name	Description
`ref`	Required. The name of the constraint overridden by this option. The named constraint must be defined elsewhere in the options. If the option specifies only ref with no `range`, `word`, `collection`, or `word-lexicon`, then no suggestions are generated when the named constraint is applied.
`range`	Defines a range constraint that limits suggestions to values that match this constraint.
`word`	Defines a word constraint that limits suggestions to words that match this constraint.
`collection`	Defines a collection constraint that limits suggestions to collection names. If a prefix is present on the constraint definition, constrain suggestions to collection names with the given prefix.
`word-lexicon`	Limit suggestions to words found in the database-wide word lexicon. The use of `word-lexicon` is not recommended as best practice; collection and range lexicons yield the best performance.
`suggestion-option`	Query options to use in generating suggestions. For details, see “Suggestion Options” on page 799.

32.30.3 Examples

The following options define 3 constraints (“color”, “price”, and “pets”), along with a `suggestion-source` option applicable to each. The suggestion source for “color” specifies suggestions matches should be case-sensitive. The suggestion source for “price” specifies that no suggestions should be generated from “price”. The suggestion source for “pets” specifies that suggestions should be drawn from an alternative source, rather than the collection defined by the original constraint

Format	Example
XML	<options xmlns="http://marklogic.com/appservices/search"> <constraint name="color"> <word> <json-property>color</json-property> </word> </constraint> <suggestion-source ref="color"> <suggestion-option>case-sensitive</suggestion-option> </suggestion-source> <constraint name="price"> <range type="xs:unsignedInt"> <element ns="" name="price"/> </range> </constraint> <suggestion-source ref="price"/> <constraint name="pets"> <collection prefix="/my/collection/" facet="true" /> </constraint> <suggestion-source ref="pets"> <collection prefix="/some/collection/subset/" </suggestion-source> </options>

Format	Example

JSON	{"options": {
	  "constraint": [
	  { "name": "color",
	  "word": { "json-key": "color" }
	  },
	  { "name": "price",
	  "range": {
	  "type": "xs:unsignedInt",
	  "element": { "ns": "", "name": "price" }
	  }
	  },
	  { "name": "pets",
	  "collection": { "prefix": "/my/collection", "facet": true}
	  }
	  ],
	  "suggestion-source": [
	  { "ref": "color", "suggestion-option": ["case-sensitive"] },
	  { "ref": "price" },
	  { "ref": "pets",
	  "collection": { "prefix": "/my/collcetion/subset" }
	  }
	  ]
	} }

32.30.4 See Also

For more details on using this option, see the following topics:

- Search Term Completion Using search:suggest in the *Search Developer's Guide*
- Java: Generating Search Term Completion Suggestions in the *Java Application Developer's Guide*
- REST: Generating Search Term Completion Suggestions in the *REST Application Developer's Guide*
- Node.js: Generating Search Term Completion Suggestions in the *Node.js Application Developer's Guide*

32.31 term

This option defines the handling of empty searches and controls options for how individual terms (that is, terms not associated with a constraint) will be represented when parsing the search terms. This option only applies to document searches and search term suggestions.

An "empty" search when you pass an empty query text string to `search:search` or an equivalent operation. To control how empty searches (that is, the empty string passed into `search:search`) are resolved, specify an `empty` child element with an `apply` attribute. The value of the `apply` attribute specifies the behavior for empty searches: a value of `all-results` specifies that empty searches return everything in the database, a value of `no-results` (the default) specifies that an empty search returns nothing.

You can also specify a `default` child element which determines special handling to all terms, so you can have all terms apply a set of rules such as query weighting, specifying a element or attribute value or word query to be used as a default, or specifying a constraint to be applied by default.

Include a `fragment-scope` element to limit the scope of term queries to document or fragment scope. The local definition overrides a global fragment scope on the enclosing `options` element as long as the term definition does not include a constraint definition or reference, or a custom function specification.

- Syntax Summary
- Component Description
- Examples

32.31.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<term apply="funcName" ns="namespaceURI" at="modulePath">`
`  <default ref="constraintName">`
`  <word/>`
`  <value/>`
`  <range/>`
`  </default>`
`  <empty apply="value" />`
`  <weight>double</weight>`
`  <term-option>option</term-option>`
`  <fragment-scope>scope</fragment-scope>`
`</term>`
	`"term": {`
	`"default": {`
	`  "ref": "constraintName",`
	`  "word": ...,`
	`  "value": ...,`
	`  "range": ...`
	`  },`
	`  "empty": {`
	`  "apply": "value",`
	`  },`
	`  "weight": double,`
	`  "fragment-scope": "scope"`
	`  "apply": "funcName",`
	`  "ns": "namespaceURI",`
	`  "at": "modulePath"`
	`  "term-option": [ "option" ],`
	`}`

32.31.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`apply`	The local-name of a function that parses expressions using this starter. This can be one of the functions pre-defined by the default grammar or a custom function; for a custom function, you must also include `ns` and `at` values.
`ns`	The XQuery module that contains the `apply` function, if using a user-defined function.
`at`	The module from which the `apply` function is imported, if using a user-defined function.
`default`	Specify default handling of naked terms. Either use `ref` to provide the name of a constraint defined elsewhere in the options, or define a `range`, `value`, or `word` constraint child to apply.
`empty`	Specify how to resolve an empty, such as when an empty string query is passed to `search:search`. Set apply to either `"all-results"` or `"no-results"`. Default: `all-results`.
`weight`	A weighting factor to apply to individual terms. Default: 1.0.
`term-option`	Zero or more options to apply to term matching. For details, see “Term Options” on page 796.
`fragment-scope`	Specifies a local fragment scope for evaluating term. The local `fragment-scope` overrides any global `fragment-scope`. However, this local scope is ignored if the containing `term` definition includes a constraint definition, constraint reference, or a custom function (via `apply`). Allowed values: `properties`, `documents` (default).

32.31.3 Examples

The following example specifies that an empty search should return no results, and that terms are matched diacritic-insensitive and unwildcarded.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <term>`
	`  <empty apply="no-results" />`
	`  <term-option>diacritic-insensitive</term-option>`
	`  <term-option>unwildcarded</term-option>`
	`  </term>`
	`<options>`

JSON	`{"options": {`
	`  "term": {`
	`  "empty": {"apply": "no-results"},`
	`  "term-options": ["diacritic-insensitive", "unwildcarded"]`
	`  }`
	`}}`

The following example specifies a custom term handling function.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <term apply="my-handler" ns="/my/namespace" at="/my/custom.xqy">`
	`  <empty apply="all-results" />`
	`  </term>`
	`<options>`

JSON	`{"options": {`
	`  "term": {`
	`  "apply": "my-handler",`
	`  "ns": "/my/namespace",`
	`  "at": "/my/custom.xqy",`
	`  "empty": {"apply": "no-results"},`
	`  }`
	`}}`

The following example specifies that terms with no constraint qualifier should be parsed as a weighted word query on the element with QName `foo:bar`:

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <term>`
	`  <default>`
	`  <word>`
	`  <element ns="foo" name="bar" />`
	`  <weight>2.0</weight>`
	`  </word>`
	`  </default>`
	`  </term>`
	`<options>`

JSON	`{"options": {`
	`  "term": {`
	`  "default": {`
	`  "word": {`
	`  "element": { "ns": "foo", "name": "bar" },`
	`  "weight" 2.0`
	`  }`
	`  }`
	`  }`
	`}}`

The following example specifies that a constraint defined elsewhere in the options should be applied to terms:

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <constraint name="my-constraint">...</constraint>`
	`  <term>`
	`  <default ref="my-constraint" />`
	`  </term>`
	`<options>`

JSON	`{"options": {`
	`  "constraint": { "name": "my-constraint", ... },`
	`  "term": {`
	`  "default": {`
	`  "ref": { "my-constraint" }`
	`  }`
	`  }`
	`}}`

32.32 transform-results

Specifies a function to use to process a search result for the snippet output. The default is that each result is formatted using the built-in default snippetting function. For details, see “Modifying Your Snippet Results” on page 387.

You can also use one of the other pre-defined snippeting functions or define your own custom snippet generation function. See the description of `apply` in “Component Description” on page 784. When you define a custom function, you can pass in parameters using the param child elements or properties.

- Syntax Summary
- Component Description
- Examples
- See Also

32.32.1 Syntax Summary

Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

When using a built-in snippeting function, this option can take one of the following forms:

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<transform-results apply="snippet">`
`  <preferred-matches>`
`  <element ns="namespace" name="elemName" />`
`  <json-property>name</json-property>`
`  </preferred-matches>`
`  <per-match-tokens>value</per-match-tokens>`
`  <max-matches>value</max-matches>`
`  <max-snippet-chars>value</max-snippet-chars>`
`</transform-results>`
 	
`<transform-results apply="metadata-snippet">`
`  <preferred-matches>`
`  <element ns="namespace" name="elemName" />`
`  <json-property>name</json-property>`
`  </preferred-matches>`
`</transform-results>`
 	
`<transform-results apply="raw" />`
 	
`<transform-results apply="empty-snippet" />`
	`"transform-results": {`
	`  "apply": "snippet",`
	`  "per-match-tokens": number,`
	`  "max-matches": number,`
	`  "max-snippet-chars": number,`
	`  "preferred-matches": {`
	`  "element": [{`
	`  "ns": "namespaceURI",`
	`  "name": "elemName"`
	`  }],`
	`  "json-property": ["name"]`
	`  }`
	`}`
	
	`"transform-results": {`
	`  "apply": "metadata-snippet",`
	`  "preferred-matches": {`
	`  "element": [{`
	`  "ns": "namespaceURI",`
	`  "name": "elemName"`
	`  }],`
	`  "json-property": ["name"]`
	`  }`
	`}`
	
	`"transform-results": {`
	`  "apply": "raw",`
	`}`
	
	`"transform-results": {`
	`  "apply": "empty-snippet",`
	`}`

To use a custom snippeting function, use the following form of the option:

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<transform-results apply="customFunc"`
`ns="namespaceURI" at="modulePath">`
`userDefinedParams`
`</transform-results>`
	Using the built-in snippeters:
	
	`"transform-results": {`
	`"apply": "funcName",`
	`"ns": "namespaceURI",`
	`"at": "modulePath",`
	`"userDefinedParam": value`
	`}`

32.32.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`apply`	The local-name of a built-in or custom function with which to produce snippet output for a search result. The following are the builtin function names; any other value is taken to be the name of a custom snippeting function. • `snippet` (default) • `raw`: return the whole node • `empty-snippet`: return an empty snippet • `metadata-snippet`: return the snippet from the specified element in the properties document
`preferred-matches`	When using the `snippet` or `metadata-snippet` built-in function, the snippet alogorithm looks for matches first in the specified XML element or JSON property nodes in each snippet. If no matches are found in the preferred elements and/or properties, the algorithm falls back to default content.
`per-match-tokens`	When using the `snippet` built-in function, the maximum number of tokens (typically words) per matching node that surround the highlighted term(s) in the snippet. Default: 30.
`max-matches`	When using the `snippet` built-in function, the maximum number of nodes containing a highlighted term that will display in the snippet. Default: 4.

Element, Attribute or Property Name	Description
`max-snippet-chars`	When using the `snippet` built-in function, limit total snippet size to this many characters. Default: 200.
`ns`	When using a custom snippeting function, the namespace URI of the containing module.
`at`	When using a custom snippeting function, the path to the module containing the function.
`userDefinedParams`	When using a custom snippeting function, specify parameters to pass to the custom function as additional XML elements or JSON properties on the option.

32.32.3 Examples

The following example modifies the characteristics of the default snippeting function (`apply=snippet` is implicit because no function is named).

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <transform-results>`
	`  <max-matches>5</max-matches>`
	`  <max-snippet-chars>100</max-snippet-chars>`
	`  <preferred-matches>`
	`  <element ns="/my/namespace" name="some-element" />`
	`  <json-property>myProperty</json-property>`
	`  </preferred-matches>`
	`  </transform-results>`
	`</options>`

JSON	`{"options": {`
	`  "transform-results": {`
	`  "max-matches": 5,`
	`  "max-snippet-chars": 100,`
	`  "preferred-matches": {`
	`  "element": [{"ns": "/my/namespace", "name": "some-element"}],`
	`  "json-property": ["myProperty"]`
	`  }`
	`  }`
	`}}`

The following example illustrates how to use the “raw” built-in snippeter. Use the same form for “empty-snippet”, but change the value of `apply`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <transform-results apply="raw" />`
	`  <max-matches>5</max-matches>`
	`  </transform-results>`
	`</options>`

JSON	`{"options": {`
	`  "transform-results": {"apply": "raw"}`
	`}}`

The following example demonstrates how to specify a custom snippet function and pass in some parameter values:

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <transform-results apply="my-snippeter"`
	`  ns="/my/namespace" at="/my-library.xqy">`
	`  <my-param1>42</my-param1>`
	`  <my-param2>abc</my-param2>`
	`  </transform-results>`
	`</options>`

JSON	`{"options": {`
	`  "transform-results": {`
	`  "apply": "my-snippeter",`
	`  "ns": "/my/namespace",`
	`  "at": "/my-library.xqy",`
	`  "my-param1": 42,`
	`  "my-param2": "abc"`
	`  }`
	`}}`

32.32.4 See Also

For more details on using this option, see the following topics:

- “Modifying Your Snippet Results” on page 387
- Customizing Search Snippets in the *REST Application Developer’s Guide*

32.33 tuples

The tuples option identifies values range indexes or lexicons in which to find value co-occurrences. Co-occurrences take the form of a `values-response` in the query response. Use this option with `search:values` and equivalent lexicon query interfaces.

You can specify range and geospatial indexes or the collection or URI lexicons. Include an `aggregate` child to specify an aggregate builtin or user-defined function to apply to the values. You can further tailor your results using top level options such as return-frequencies, return-values, and return-aggregates.

- Syntax Summary
- Component Description
- Examples
- See Also

32.33.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<tuples name="name" style="value">`
`  <range/>`
`  <geo-elem/>`
`  <geo-elem-pair/>`
`  <geo-attr-pair/>`
`  <geo-json-property/>`
`  <geo-json-property-pair/>`
`  <geo-path>`
`  <collection/>`
`  <uri/>`
`  <aggregate apply="funcName"`
`  udf="udfName" />`
`  <values-option>option</values-option>`
`</tuples>`
	`"tuples": {`
	`  "style": "value",`
	`  "name": "name",`
	`  "collection": ...,`
	`  "range": ...,`
	`  "geo-elem": ...,`
	`  "geo-elem-pair": ...,`
	`  "geo-attr-pair": ...,`
	`  "geo-json-property": ...,`
	`  "geo-json-property-pair": ...,`
	`  "geo-path": ...,`
	`  "collection": null,`
	`  "uri": null,`
	`  "aggregate": [{`
	`  "apply": "funcName",`
	`  "udf": string`
	`  }],`
	`"values-option": [ "option" ]`
	`}`

32.33.2 Component Description

The components of this option have the following semantics:

Element, Attribute or Property Name	Description
`name`	Required. The name identifying this tuples definition.
`style`	How to format the results. Allowed values: `default`, `consistent`. When set to `consistent`, the output is structured the same whether returning single values or tuples. When set to `default`, the layout differs between values and tuples results.
`range`	A range constraint with which to extract values from a range index or value lexicon.
`geo-elem`	A geospatial element constraint with which to extract values from a geospatial index.
`geo-elem-pair`	A geospatial element pair constraint with which to extract values from a geospatial index.
`geo-attr-pair`	A geospatial element attribute constraint with which to extract values from a geospatial index.
`geo-json-property`	A geospatial JSON property constraint with which to extract values from a geospatial index.
`geo-json-property-pair`	A geospatial JSON property pair constraint with which to extract values from a geospatial index.
`geo-path`	A geospatial path constraint with which to extract values from a geospatial index.

Element, Attribute or Property Name	Description
`collection`	Extract values from the collection lexicon.
`uri`	Extract values from the URI lexicon.
`aggregate`	Specify builtin or user-defined aggregate functions to apply to lexicon values or value co-occurrences. The `apply` child is required and names the built-in or user-defined aggregate function to apply. When using a UDF, use `udf` to specify the path to the native plugin library containing the implementation of the function. In XML, specify this element multiple times to compute multiple aggregates.
`values-option`	Specify zero or more options that affect the values under consideration. For details, see "Values Options" on page 799.

32.33.3 Examples

The following example specifies co-occurrences between editor and author element values.

Format	Example

XML	<options xmlns="http://marklogic.com/appservices/search">
	  <tuples name="editor-author">
	  <range type="xs:string"
	  collation="http://marklogic.com/collation">
	  <element name="editor" ns="" />
	  </range>
	  <range type="xs:string"
	  collation="http://marklogic.com/collation">
	  <element name="author" ns="" />
	  </range>
	  <values-option>limit=5</values-option>
	  </tuples>
	</options>

JSON	{"options": {
	  "tuples": [{
	  "name": "editor-author",
	  "indexes": [
	  {"range": {
	  "type": "xs:string",
	  "collation": "http://marklogic.com/collation",
	  "element": {
	  "name": "editor",
	  "ns": ""
	  }
	  } },
	  {"range": {
	  "type": "xs:string",
	  "collation": "http://marklogic.com/collation",
	  "element": {
	  "name": "author",
	  "ns": ""
	  }
	  } }
	  ],
	  "values-option": ["limit=5"]
	  }]
	} }

32.33.4 See Also

For details on using this option, see the following topics:

- “Browsing With Lexicons” on page 431

- "Returning Lexicon Values With search:values" on page 52
- "Using Aggregate Functions" on page 449
- Java: Apply Dynamic Query Options to Document Searches in the *Java Application Developer's Guide*
- Node.js: Querying Lexicons and Range Indexes in the *Node.js Application Developer's Guide*
- REST: Querying Lexicons and Range Indexes in the *REST Application Developer's Guide*

32.34 values

The `values` option constrains a values search to one or more range indexes or lexicons. Matched values take the form of a `values-response` in the query response. Use this option with `search:values` and equivalent interfaces.

You can specify range and geospatial indexes or the collection or URI lexicons. Include an `aggregate` child to specify an aggregate builtin or user-defined function to apply to the values. You can further tailor your results using top level options such as return-frequencies, return-values, and return-aggregates.

- Syntax Summary
- Component Description
- Examples
- See Also

32.34.1 Syntax Summary

This option has the following structure. Note that you can only use the JSON form with selected Client APIs, such as the REST Client API.

XML	JSON

All elements are in the namespace `http://marklogic.com/appservices/search`.
 	
`<values name="name" style="value">`
`  <range/>`
`  <geo-elem/>`
`  <geo-elem-pair/>`
`  <geo-attr-pair/>`
`  <geo-json-property/>`
`  <geo-json-property-pair/>`
`  <geo-path>`
`  <collection/>`
`  <uri/>`
`  <aggregate apply="funcName"`
`  udf="udfName" />`
`  <values-option>option</values-option>`
`</values>`
	`"values": {`
	`  "style": "value",`
	`  "name": "name",`
	`  "range": ...,`
	`  "geo-elem": ...,`
	`  "geo-elem-pair": ...,`
	`  "geo-attr-pair": ...,`
	`  "geo-json-property": ...,`
	`  "geo-json-property-pair": ...,`
	`  "geo-path": ...,`
	`  "collection": null,`
	`  "uri": null,`
	`  "aggregate": [{`
	`  "apply": "funcName",`
	`  "udf": string`
	`  }],`
	`"values-option": [ "option" ]`
	`}`

32.34.2 Component Description

The components of this option have the following semantics. You can only include one index/lexicon specification.

Element, Attribute or Property Name	Description
`name`	Required. The name identifying this tuples definition.
`style`	How to format the results. Allowed values: `default`, `consistent`. When set to `consistent`, the output is structured the same whether returning single values or tuples. When set to `default`, the layout differs between values and tuples results.
`range`	A range constraint with which to extract values from a range index or value lexicon.
`geo-elem`	A geospatial element constraint with which to extract values from a geospatial index.

Element, Attribute or Property Name	Description
`geo-elem-pair`	A geospatial element pair constraint with which to extract values from a geospatial index.
`geo-attr-pair`	A geospatial element attribute constraint with which to extract values from a geospatial index.
`geo-json-property`	A geospatial JSON property constraint with which to extract values from a geospatial index.
`geo-json-property-pair`	A geospatial JSON property pair constraint with which to extract values from a geospatial index.
`geo-path`	A geospatial path constraint with which to extract values from a geospatial index.
`collection`	Extract values from the collection lexicon.
`uri`	Extract values from the URI lexicon.
`aggregate`	Specify builtin or user-defined aggregate functions to apply to the lexicon values. The `apply` child is required and names the built-in or user-defined aggregate function to apply. When using a UDF, use `udf` to specify the path to the native plugin library containing the implementation of the function. In XML, specify this element multiple times to compute multiple aggregates.
`values-option`	Specify zero or more options that affect the values under consideration. For details, see "Values Options" on page 799.

32.34.3 Examples

The following example illustrates several kinds of values query specification: An element range index spec that uses `values-option`, a URI lexicon spec, a collection lexicon spec, and a JSON property range index spec that applies a custom aggregate function to index values. For more examples, see `search:values`.

Format	Example

XML	`<options xmlns="http://marklogic.com/appservices/search">`
	`  <values name="editor-author">`
	`  <range type="xs:string"`
	`  collation="http://marklogic.com/collation">`
	`  <element name="editor" ns="" />`
	`  </range>`
	`  <values-option>limit=5</values-option>`
	`  </values>`
	`  <values name="uris">`
	`  <uri/>`
	`  </values>`
	`  <values name="coll">`
	`  <collection/>`
	`  </values>`
	`  <values name="aggregate">`
	`  <range type="xs:double">`
	`  <json-property>test</json-property>`
	`  </range>`
	`  <aggregate apply="mycalc" udf="sampleplugin" />`
	`  </values>`
	`</options>`

Format	Example

JSON	<pre>{"options": {
	  "values": [
	  { "name": "editor-author",
	  "range": {
	  "type": "xs:string",
	  "collation": "http://marklogic.com/collation",
	  "element": { "name": "editor", "ns": "" }
	  },
	  "values-option": "limit=5"
	  },
	  { "name": "uris",
	  "uri": null
	  },
	  { "name": "coll",
	  "collection": null
	  },
	  { "name": "aggregate",
	  "range": {
	  "type": "xs:double",
	  "json-property": "test"
	  },
	  "aggregate": [{
	  "apply": "mycalc",
	  "udf": "sampleplugin"
	  }]
	  }
	  ]
	} }</pre>

32.34.4 See Also

For details on using this option, see the following topics:

- The XQuery function `search:values`
- “Browsing With Lexicons” on page 431
- “Returning Lexicon Values With search:values” on page 52
- “Using Aggregate Functions” on page 449
- Java: Apply Dynamic Query Options to Document Searches in the *Java Application Developer’s Guide*
- Node.js: Querying Lexicons and Range Indexes in the *Node.js Application Developer’s Guide*
- REST: Querying Lexicons and Range Indexes in the *REST Application Developer’s Guide*

32.35 Term Options

The following options can be specified as the value of a `term-option` child in options that support them, such as a value or word constraint. By default, a query uses the same default options as the underlying cts:query constructors, and the defaults change based on your index configuration.

The following term options are supported:

- case-sensitive
- case-insensitive
- diacritic-sensitive
- diacritic-insensitive
- punctuation-sensitive
- punctuation-insensitive
- whitespace-sensitive
- whitespace-insensitive
- stemmed
- unstemmed
- wildcarded
- unwilcarded
- exact
- lang=*iso639code*

32.36 Facet Options

The following options can be specified as the value of a `facet-option` child in constraint types that can be used as a facet (any constraints except word, value, element-query, or property).

Legal values for a `facet-option` are generally any option that can be passed into the underlying query or lexicon API. The following list enumerates the `facet-option` values, but be aware that some options are only available with some range types. For more detail on these options, see the documentation for the underlying range or lexicon APIs.

The following facet options are supported:

- ascending
- descending
- empties
- any

- document
- properties
- locks
- frequency-order
- item-order
- fragment-frequency
- item-frequency
- type=type
- timezone=TZ
- limit=N
- sample=N
- truncate=N
- skip=N
- score-logtfidf
- score-logtf
- score-simple
- score-random
- checked
- unchecked
- concurrent
- map

32.37 Range Options

The following options can be specified as the value of a `range-option` child in options that support them, such as a range constraint.

- `score-function=zero` (default)
- `score-function=reciprocal`
- `score-function=linear`
- `slope-factor=`*number*
- `max-occurs=`*number*
- `min-occurs=`*number*

- `cached`
- `uncached`
- `synonym`

For details, see Including a Range or Geospatial Query in Scoring and `cts:element-range-query` (XQuery) or `cts.elementRangeQuery` (JavaScript), or equivalent functions for other constraint types.

32.38 Geospatial Options

The following options can be specified as the value of a `geospatial-option` child in options that support them, such as a geo-elem or geo-json-property.

- `coordinate-system=`*wgs84*
- `units=`*miles*
- `boundaries-included`
- `boundaries-excluded`
- `boundaries-latitude-excluded`
- `boundaries-longitude-excluded`
- `boundaries-south-excluded`
- `boundaries-north-excluded`
- `boundaries-east-excluded`
- `boundaries-west-excluded`
- `boundaries-circle-excluded`
- `type=`*point*
- `type=`*long-lat-point*
- `score-function=zero` (default)
- `score-function=reciprocal`
- `score-function=linear`
- `slope-factor=`*number*
- `cached`
- `uncached`
- `synonym`

32.39 Suggestion Options

The following options can be specified as the value of a `suggestion-option` child in a default-suggestion-source or suggestion-source option.

- `case-sensitive`
- `case-insensitive`
- `diacritic-sensitive`
- `diacritic-insensitive`
- `ascending`
- `descending`
- `frequency-order`
- `item-order`
- `fragment-frequency`
- `item-frequency`
- `type=`*type*
- `timezone=`*TZ*
- `sample=`*N*
- `truncate=`*N*
- `score-logtfidf`
- `score-logtf`
- `score-simple`
- `score-random`
- `checked`
- `unchecked`

32.40 Values Options

The following options can be specified as the value of a `values-option` child in a tuples or values option. For a description of these options, see `cts:values` and `cts:values-tuples` in the *XQuery and XSLT Reference Guide*. Some options can only be used when defining a values configurations; others can only be used when defining tuples.

- ascending
- descending
- any

- document
- properties
- locks
- frequency-order
- item-order
- fragment-frequency
- item-frequency
- timezone=*TZ*
- limit=*N*
- skip=*N*
- sample=*N*
- truncate=*N*
- score-logtfidf
- score-logtf
- score-simple
- score-random
- score-zero
- checked
- unchecked
- concurrent
- map (for values only)
- ordered (for tuples only)
- proximity=*N* (for tuples only)

33.0 Technical Support

MarkLogic provides technical support according to the terms detailed in your Software License Agreement or End User License Agreement.

We invite you to visit our support website at http://help.marklogic.com to access information on known and fixed issues, knowledge base articles, and more. For licensed customers with an active maintenance contract, see the Support Handbook for instructions on registering support contacts and on working with the MarkLogic Technical Support team.

Complete product documentation, the latest product release downloads, and other useful information is available for all developers at http://developer.marklogic.com. For general questions, join the general discussion mailing list, open to all MarkLogic developers.

34.0 Copyright

MarkLogic Server 8.0 and supporting products.

NOTICE

Copyright © 2018 MarkLogic Corporation.

This technology is protected by one or more U.S. Patents 7,127,469, 7,171,404, 7,756,858, 7,962,474, 8,935,267, 8,892,599 and 9,092,507.

All MarkLogic software products are protected by United States and international copyright, patent and other intellectual property laws, and incorporate certain third party libraries and components which are subject to the attributions, terms, conditions and disclaimers found at http://docs.marklogic.com/guide/copyright/legal.

MarkLogic and the MarkLogic logo are trademarks or registered trademarks of MarkLogic Corporation in the United States and other countries. All other trademarks are property of their respective owners.

For all copyright notices, including third-party copyright notices, see the Combined Product Notices for your version of MarkLogic.